

RF Exposure Evaluation Report

Product : Wireless Multimedia Keyboard
Trade mark : MINISO
Model/Type reference : K616,K617,K618, K619
Serial Number : N/A
Report Number : EED32N80982802
FCC ID : 2ART4-K616
Date of Issue : Oct. 22, 2021
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF
Exposure Guidance v06
Test result : PASS

Prepared for:

MINISO CORPORATION
2501 ROOM 2501, NO.486 HEYE SQUARE,
KANGWANG MIDDLE ROAD, LIWAN DISTRICT,
GUANGZHOU, GUANGDONG, CHINA

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385



Compiled by:

Approved by:

weishifeng

weishifeng

David Wang

David Wang

Reviewed by:

Aaron Ma

Aaron Ma

Date:

Oct. 22, 2021

Check No.: 1449081021

2 Version

Version No.	Date	Description
00	Oct. 22, 2021	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 EUT RF Exposure.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	MINISO CORPORATION
Address of Applicant:	2501 ROOM 2501, NO.486 HEYE SQUARE, KANGWANG MIDDLE ROAD, LIWAN DISTRICT, GUANGZHOU, GUANGDONG, CHINA
Manufacturer:	Dongguan Eranode electronics limited
Address of Manufacturer:	building 2, No.17 DAHUAN Road, Dalingshan Town, Dongguan City, Guangdong Province
Factory:	Dongguan Eranode electronics limited
Address of Factory:	building 2, No.17 DAHUAN Road, Dalingshan Town, Dongguan City, Guangdong Province

4.2 General Description of EUT

Product Name:	Wireless Multimedia Keyboard
Mode No.(EUT):	K616, K617, K618, K619
Test Mode	K616
Trade Mark:	MINISO
EUT Supports Radios application:	BT 5.1 Single module 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	BT 5.1 Single module 2402MHz to 2480MHz;
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	662x_FCC_Rev1.4d
Antenna Type:	PCB antenna
Antenna Gain:	-1.52dBi
Power Supply:	1.5V Batteries; AA
Max Conducted Peak Output Power:	-10.16 dBm The Max Conducted Peak Output Power data refer to the report EED32N80982801
Sample Received Date:	Oct. 08, 2021
Sample tested Date:	Oct. 09, 2021 to Oct. 17, 2021
Remark: Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. Only the model K616 was tested, their circuit design, layout, components used and internal wiring are the same, but the model, color appearance is different.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.2 EUT RF Exposure

The tune-up power is -10.5 dBm +/- 0.5dB, therefore the highest tune-up power is

-10 dBm (0.10mW) @2480 Mhz

When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

So,

$(0.10\text{mW} / 5\text{mm}) * (2.480\text{GHz}^{0.5}) = 0.03$

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * \sqrt{f(\text{GHz})} = 0.03 < 3.0$

Therefore, standalone SAR measurements are not required for both head and body.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32N80982801 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***