

FCC REPORT

(GSM & WCDMA)

Applicant: 3Wolves Technology CO., LTD.

Address of Applicant: 4th floor, B building, Hai Da decoration park, Majialong industry zone, Nanshan district, Shenzhen city, Guang Dong province.P.R.C

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: M2

Trade mark: 3Wolves

FCC ID: 2ARTMM2

Applicable standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22 Subpart H
FCC CFR Title 47 Part 24 Subpart E

Date of sample receipt: 05 Nov., 2018

Date of Test: 05 Nov., to 13 Dec., 2018

Date of report issued: 14 Dec., 2018

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2. Version

Version No.	Date	Description
00	14 Dec., 2018	Original

Tested by:

Carey Chen

Test Engineer

Date:

14 Dec., 2018

Reviewed by:

Wimer Zhang

Project Engineer

Date:

14 Dec., 2018

3. Contents

Page

1.	COVER PAGE	1
2.	VERSION	2
3.	CONTENTS	3
4.	TEST SUMMARY	4
5.	GENERAL INFORMATION	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T	5
5.3	TEST MODES	7
5.4	DESCRIPTION OF SUPPORT UNITS	7
5.5	MEASUREMENT UNCERTAINTY	7
5.6	LABORATORY FACILITY	7
5.7	LABORATORY LOCATION	8
5.8	TEST INSTRUMENTS LIST	8
6.	TEST RESULTS	9
6.1	CONDUCTED OUTPUT POWER, ERP AND EIRP	9
6.2	PEAK-TO-AVERAGE POWER RATIO	11
6.3	OCCUPY BANDWIDTH	13
6.4	MODULATION CHARACTERISTIC	18
6.5	OUT OF BAND EMISSION AT ANTENNA TERMINALS	18
6.6	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	24
6.7	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	28
6.8	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	30
7	TEST SETUP PHOTO	32
8	EUT CONSTRUCTIONAL DETAILS	33

4. Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Peak-to-Average Power Ratio	Part 24.232 (d)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917(b) Part 24.238(b)	Pass
Out of band emission at antenna terminals	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Field strength of spurious radiation	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 22.355 Part 24.235 Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 22.355 Part 24.235 Part 2.1055(d)(2)	Pass
Pass: The EUT complies with the essential requirements in the standard.		

5. General Information

5.1 Client Information

Applicant:	3Wolves Technology CO., LTD.
Address:	4th floor, B building, Hai Da decoration park, Majialong industry zone, Nanshan district, Shenzhen city, Guang Dong province. P.R.C
Manufacturer	3Wolves Technology CO., LTD.
Address:	4th floor, B building, Hai Da decoration park, Majialong industry zone, Nanshan district, Shenzhen city, Guang Dong province. P.R.C

5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	M2
Operation Frequency range:	GSM 850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz WCDMA Band V: 826.4MHz-846.6MHz
Modulation type:	GSM/GPRS: GMSK, UMTS: QPSK
Antenna type:	Internal Antenna
Antenna gain:	GSM850: -1.2dBi PCS1900: 1.62dBi WCDMA Band V: -0.98dBi
Power supply:	Rechargeable Li-ion Battery DC3.7 V-2600mAh
AC adapter:	Model: SCJ-05100 Input: AC100-240V, 50/60Hz, 0.2A Output: DC 5V, 800mA
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency List:

GSM 850		PCS1900	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
....			
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
...	...	...	...
250	848.60	809	1909.60
251	848.80	810	1909.80
WCDMA Band V			
Channel	Frequency (MHz)		
4132	826.40		
4133	826.60		
....			
4182	836.40		
4183	836.60		
4184	836.80		
...	...		
4232	846.40		
4233	846.60		

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

GSM850			PCS1900		
Channel		Frequency(MHz)	Channel		Frequency(MHz)
Lowest channel	128	824.20	Lowest channel	512	1850.20
Middle channel	190	836.60	Middle channel	661	1880.00
Highest channel	251	848.80	Highest channel	810	1909.80
WCDMA Band V					
Channel		Frequency(MHz)			
Lowest channel	4132	826.40			
Middle channel	4183	836.60			
Highest channel	4233	846.60			

5.3 Test modes

Operating Environment:	
Temperature:	Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.7Vdc, Extreme: Low 3.5 Vdc, High 4.20 Vdc
Test mode:	
GSM mode	Keep the EUT communication with simulated station in GSM mode
GPRS mode	Keep the EUT communication with simulated station in GPRS mode
RMC mode	Keep the EUT communication with simulated station in RMC mode
HSDPA	Keep the EUT communication with simulated station in HSDPA mode
HSUPA	Keep the EUT communication with simulated station in HSUPA mode
Remark: The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes with power adaptor, earphone and Data cable. Just the worst case position (H mode) shown in report.	

5.4 Description of Support Units

Test Equipment	Manufacturer	Model No.	Serial No.
Simulated Station	Anritsu	MT8820C	6201026545

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.7 Laboratory Location


Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.8 Test Instruments list

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Biconical Antenna	SCHWARZBECK	VUBA9117	359	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2017	11-20-2018
				11-21-2018	11-20-2019
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2017	11-20-2018
				11-21-2018	11-20-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Spectrum Analyzer	Agilent	N9020A	MY50510123	11-10-2017	11-09- 2018
				11-10-2018	11-09- 2019
Signal Generator	Rohde & Schwarz	SMX	835454/016	03-07-2018	03-06-2019
Signal Generator	R&S	SMR20	1008100050	03-07-2018	03-06-2019
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019
DC Power Supply	XinNuoEr	WYK-10020K	1409050110020	10-31-2017	10-30-2018
Temperature Humidity Chamber	HengPu	HPGDS-500	20140828008	09-24-2018	09-23-2019
Simulated Station	Rohde & Schwarz	CMW500	140493	07-16-2018	07-15-2019

6. Test results


6.1 Conducted Output Power, ERP and EIRP

Test Requirement:	FCC part 22.913(a)(2), FCC part 24.232(c)
Test Method:	ANSI/TIA-603-D 2010
Limit:	GSM 850: 7W, PCS 1900: 2W WCDMA Band V: 7W
Test setup:	 The diagram illustrates the test setup. On the left is a blue rectangular box labeled 'System simulator'. A line connects it to a small black square labeled 'ATT' (attenuator). Another line connects the 'ATT' to a black rectangular box labeled 'EUT' (Equipment Under Test).
Test Procedure:	The transmitter output was connected to a calibrated attenuator, the other end of which was connected to the simulated station. Transmitter output power was read off in dBm.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

EUT Mode		Burst Average power (dBm)		
		128	190	251
		824.20 (MHz)	836.60 (MHz)	848.80 (MHz)
GSM 850		31.62	31.63	31.94
GPRS 850 (1 Uplink slot)		31.86	31.93	31.84
GPRS 850 (2 Uplink slot)		30.44	30.52	30.67
GPRS 850 (3 Uplink slot)		28.28	28.45	28.48
GPRS 850 (4 Uplink slot)		27.20	27.30	27.45
Antenna Gain (dBi)		-1.20		
Max. ERP (dBm)		28.59		
ERP Limit (dBm)		38.45		
EUT Mode		Burst Average power (dBm)		
		512	661	810
		1850.20 (MHz)	1880.00 (MHz)	1909.80 (MHz)
PCS 1900		28.51	28.35	28.19
GPRS 1900 (1 Uplink slot)		28.87	28.74	28.52
GPRS 1900 (2 Uplink slot)		27.82	27.26	27.24
GPRS 1900 (3 Uplink slot)		25.93	25.55	25.24
GPRS 1900 (4 Uplink slot)		25.09	24.58	23.86
Antenna Gain (dBi)		1.62		
Max. EIRP (dBm)		30.49		
EIRP Limit (dBm)		33.00		
EUT Mode		Burst Average power (dBm)		
		4132	4183	4233
		826.40 (MHz)	836.60 (MHz)	846.60 (MHz)
UMTS 850 HSDPA	Subtest 1	23.04	23.07	23.30
	Subtest 2	22.63	22.58	22.97
	Subtest 3	21.10	21.11	21.32
	Subtest 4	21.15	20.99	21.24
UMTS 850 HSUPA	Subtest 1	22.89	22.98	23.21
	Subtest 2	22.90	23.02	23.25
	Subtest 3	21.07	20.91	21.55
	Subtest 4	23.00	23.07	23.30
	Subtest 5	22.05	22.20	22.38
UMTS 850 RMC	12.2kbps	24.02	24.03	24.30
UMTS 850 AMR	12.2kbps	23.90	23.92	24.20
Antenna Gain (dBi)		-0.98		
Max. ERP (dBm)		21.17		
ERP Limit (dBm)		38.45		
Note: EIRP (dBm) = Burst Average power (dBm) + Antenna Gain (dBi).				
ERP (dBm) = EIRP (dBm) - 2.15 (dB).				


6.2 Peak-to-Average Power Ratio

Test Requirement:	FCC part 24.232(d)
Test Method	ANSI/TIA-603-D 2010
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test setup:	 The diagram shows a test setup where a System simulator and a Spectrum Analyzer are connected to a Splitter. The Splitter is connected to an ATT (Attenuator) and then to the EUT (Equipment Under Test).
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 Set the CCDF option in spectrum analyzer, $RBW \geq OBW$, 3 Set the EUT working in highest power level, measured and recorded the 0.1% as PAPR level. 4 Repeat step 1~3 at other frequency and modulations.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:

Modulation	Test channel	PAPR
GSM 850	190	-0.07
PCS 1900	661	-0.06
UMTS 850 RMC	4183	3.16

Test plots as below:



6.3 Occupy Bandwidth

Test Requirement:	FCC part 22.917(b), FCC part 24.238(b)
Test Method:	ANSI/TIA-603-D 2010
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular units: the top one is labeled 'System simulator' and the bottom one is labeled 'Spectrum Analyzer'. Both have a single output port. These two ports are connected to a single input port of a white rectangular unit labeled 'Splitter'. The 'Splitter' has two output ports. One output port is connected to a black rectangular unit labeled 'ATT' (Attenuator). The other output port is connected to a black rectangular unit labeled 'EUT' (Equipment Under Test).
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (kHz)	-26dB bandwidth (kHz)
GSM 850	128	824.2	244	318
	190	836.6	246	316
	251	848.8	246	322
PCS 1900	512	1850.2	244	320
	661	1880.0	250	318
	810	1909.8	248	318
UMTS 850 12.2k RMC	4132	826.4	4160	4700
	4183	836.6	4180	4720
	4233	846.6	4160	4680

Note: GSM & GPRS use the same modulation technical (GMSK), and with the same channels, so the 99% OBW and the -26dB of GPRS not performed.

Test plot as follows:


GSM 850

99% Occupy bandwidth




Date: 12.DEC.2018 15:00:16

Lowest channel



Date: 12.DEC.2018 15:00:57


Middle channel



Date: 12.DEC.2018 15:01:13


Highest channel

26dB Emission Bandwidth




Date: 12.DEC.2018 15:00:31

Lowest channel



Date: 12.DEC.2018 15:00:45

Middle channel




Date: 12.DEC.2018 15:01:27

Highest channel


PCS 1900

99% Occupy bandwidth




Date: 12.DEC.2018 08:49:23

26dB Emission Bandwidth




Date: 12.DEC.2018 08:49:35

Lowest channel




Date: 12.DEC.2018 08:50:02

Lowest channel




Date: 12.DEC.2018 08:49:50

Middle channel



Date: 12.DEC.2018 08:50:20

Middle channel




Date: 12.DEC.2018 08:50:35

Highest channel

Highest channel


UMTS 850 12.2k RMC

99% Occupy bandwidth




Date: 12,DEC,2018 09:01:02

26dB Emission Bandwidth




Date: 12,DEC,2018 09:01:12

Lowest channel




Date: 12,DEC,2018 09:01:47

Lowest channel




Date: 12,DEC,2018 09:01:36

Middle channel



Date: 12,DEC,2018 09:02:17

Middle channel



Date: 12,DEC,2018 09:02:28


Highest channel

Highest channel

6.4 Modulation Characteristic


According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

6.5 Out of band emission at antenna terminals

Test Requirement:	FCC part 22.917(a), FCC part 24.238(a)
Test Method:	ANSI/TIA-603-D 2010
Limit:	-13dBm
Test setup:	 The diagram illustrates the test setup for out-of-band emission testing. It shows a System simulator connected to a Spectrum Analyzer. The output of the System simulator is connected to a Splitter. The output of the Splitter is connected to an ATT (Attenuator). The output of the ATT is connected to the EUT (Equipment Under Test).
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 100 kHz when below 1GHz, 1MHz when above 1 GHz; sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW=100 kHz, VBW=300 kHz when below 1 GHz, RBW =1 MHz, VBW=3 MHz when above 1 GHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Test plots as follows (Spurious emission):

GSM 850 Lowest Channel



Date: 12.DEC.2018 15:05:01


30MHz~1GHz



Date: 12.DEC.2018 08:46:25


1GHz~9GHz

Middle channel



Date: 12.DEC.2018 15:05:22


30MHz~1GHz



Date: 12.DEC.2018 08:46:44


1GHz~9GHz

Highest Channel



Date: 12.DEC.2018 15:05:58


30MHz~1GHz



Date: 12.DEC.2018 08:47:11


1GHz~9GHz

PCS 1900 Lowest Channel



Date: 12.DEC.2018 08:53:54


30MHz~1GHz



Date: 13.DEC.2018 11:35:25


1GHz~20GHz

Middle Channel



Date: 12.DEC.2018 08:53:33


30MHz~1GHz



Date: 12.DEC.2018 08:55:28


1GHz~20GHz

Highest Channel



Date: 12.DEC.2018 08:54:13


30MHz~1GHz



Date: 12.DEC.2018 08:56:14


1GHz~20GHz

UMTS 850 12.2k RMC Lowest Channel



Date: 12.DEC.2018 09:06:57


30MHz~1GHz



Date: 13.DEC.2018 11:40:40


1GHz~9GHz

Middle Channel



Date: 12.DEC.2018 09:06:07


30MHz~1GHz



Date: 13.DEC.2018 11:41:12


1GHz~9GHz

Highest Channel



Date: 12.DEC.2018 09:06:31

30MHz~1GHz




Date: 13.DEC.2018 11:41:33

1GHz~9GHz


Band edge emission:

GSM850



Date: 12.DEC.2018 15:04:01


Lowest channel



Date: 12.DEC.2018 15:02:06


Highest channel

PCS1900




Date: 12.DEC.2018 15:10:14

Lowest channel





Date: 12.DEC.2018 15:11:01

Highest channel



6.6 Field strength of spurious radiation measurement

Test Requirement:	FCC part 22.917(a), FCC part 24.238(a)
Test Method:	ANSI/TIA-603-D 2010
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz 
Test Procedure:	1. The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $ERP / EIRP = S.G. \text{ output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details.
Test results:	Passed


Measurement Data (worst case):

GSM850				
Lowest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-51.47	-13.00	Pass
2472.60	V	-54.39		
3296.80	V	-50.33		
1648.40	Horizontal	-49.57	-13.00	Pass
2472.60	H	-55.28		
3296.80	H	-51.36		
Middle channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-55.27	-13.00	Pass
2509.80	V	-53.19		
3346.40	V	-50.74		
1673.20	Horizontal	-52.29	-13.00	Pass
2509.80	H	-55.28		
3346.40	H	-51.36		
Highest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-51.29	-13.00	Pass
2546.40	V	-54.38		
3395.20	V	-53.17		
1697.60	Horizontal	-48.27	-13.00	Pass
2546.40	H	-52.43		
3395.20	H	-40.29		
Remark:				
1. The emission levels of below 1 GHz are very lower than the limit and not show in test report.				

PCS1900				
Lowest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-51.16	-13.00	Pass
5550.60	V	-50.29		
3700.40	Horizontal	-51.37	-13.00	Pass
5550.60	H	-50.73		
Middle channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-50.67	-13.00	Pass
5640.00	V	-49.52		
3760.00	Horizontal	-51.08	-13.00	Pass
5640.00	H	-49.27		
Highest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-50.64	-13.00	Pass
5729.40	V	-49.73		
3819.60	Horizontal	-50.65	-13.00	Pass
5729.40	H	-48.97		
Remark:				
1. The emission levels of below 1 GHz are very lower than the limit and not show in test report.				

WCDMA BAND V 12.2k RMC				
Lowest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1652.80	Vertical	-52.48	-13.00	Pass
2479.20	V	-56.61		
3305.60	V	-52.12		
1652.80	Horizontal	-50.08	-13.00	Pass
2479.20	H	-56.09		
3305.60	H	-52.42		
Middle channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-56.35	-13.00	Pass
2509.80	V	-55.39		
3346.40	V	-52.05		
1673.20	Horizontal	-53.82	-13.00	Pass
2509.80	H	-56.51		
3346.40	H	-52.53		
Highest channel				
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1693.20	Vertical	-49.87	-13.00	Pass
2539.80	V	-55.07		
3386.40	V	-51.45		
1693.20	Horizontal	-44.91	-13.00	Pass
2539.80	H	-55.3		
3386.40	H	-52.34		
Remark:				
1. The emission levels of below 1 GHz are very lower than the limit and not show in test report.				


6.7 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part 22.355, FCC Part 24.235, FCC Part 2.1055(a)(1)(b)
Test Method:	ANSI/TIA-6-3-D 2010
Limit:	±2.5 ppm
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue boxes labeled 'SS' (Signal Source) and 'SA' (Spectrum Analyzer). They are connected to a central grey box labeled 'Divider'. The 'Divider' is connected to a black box labeled 'EUT' (Equipment Under Test) which is located inside a larger blue box labeled 'Temperature & Humidity Chamber'. Below the 'Divider' is a grey box labeled 'Power Source' with two green circles. Red lines connect the 'Power Source' to the 'EUT'.
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (the worst channel):

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	182	0.217547	±2.5	Pass
	-20	163	0.194836		
	-10	155	0.185274		
	0	152	0.181688		
	10	141	0.168539		
	20	124	0.148219		
	30	133	0.158977		
	40	126	0.150610		
	50	171	0.204399		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	180	0.095745	±2.5	Pass
	-20	165	0.087766		
	-10	124	0.065957		
	0	139	0.073936		
	10	162	0.086170		
	20	177	0.094149		
	30	150	0.079787		
	40	164	0.087234		
	50	174	0.092553		
Reference Frequency: WCDMA BAND V 12.2k RMC Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.80	-30	186	0.222328	±2.5	Pass
	-20	142	0.169735		
	-10	153	0.182883		
	0	176	0.210375		
	10	180	0.215157		
	20	166	0.198422		
	30	129	0.154196		
	40	138	0.164953		
	50	154	0.184078		
Note: Only the worst case shown in the report.					

6.8 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part 22.355, FCC Part 24.235, FCC Part 2.1055(d)(2)
Test Method:	ANSI/TIA-603-D 2010
Limit:	±2.5ppm
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue boxes labeled 'SS' (Signal Source) and 'SA' (Spectrum Analyzer). They are connected to a central grey box labeled 'Divider'. The 'Divider' is connected to a black box labeled 'EUT' (Equipment Under Test) which is located inside a larger blue box labeled 'Temperature & Humidity Chamber'. Below the 'Divider' is a grey box labeled 'Power Source' with two green terminals. Red and black wires connect the 'Power Source' to the 'EUT'.
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specify extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (the worst channel):

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	88	0.105188	±2.5	Pass
	3.80	78	0.093235		
	3.50	55	0.065742		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	90	0.047872	±2.5	Pass
	3.80	77	0.040957		
	3.50	86	0.045745		
Reference Frequency: UMTS 850 12.2k RMC Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.35	95	0.113555	±2.5	Pass
	3.80	73	0.087258		
	3.55	69	0.082477		