TEST REPORT

Part 15 Subpart C 15.247

Equipment under test	Smart automatic measuring device for electricity
Model name	VMS-V7
FCC ID	2ARVOVMS-V7
Applicant	Y TECH CO.,LTD.
Manufacturer	Y TECH CO.,LTD.
Date of test(s)	2018.11.29 ~ 2018.12.03
Date of issue	2018.12.04

Issued to
Y TECH CO.,LTD.
13509 startup-dong-209-ho, KET, 25, Saenari-ro, Bundang-gu,
Seongnam-si, Gyeonggi-do, Republic of Korea
Tel: +82-31-789-8103 / Fax: +82-31-789-8102

Issued by
KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Young-Jin Lee Test engineer	Hyeon-Su, Jang Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Revision history

Revision	Date of issue	Test report No.	Description
-	2018.12.04	KES-RF-18T0114	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Device modifications 5
1.4. Accessory information 5
1.5. Software and Firmware description 5
1.6. Measurement results explanation example 5
1.7. Measurement Uncertainty 5
1.8. Frequency/channel operations 5
2. Summary of tests 6
3. Test results 7
3.1. 6 dB bandwidth 7
3.2. Output power 9
3.3. Power spectral density 11
3.4. Radiated restricted band and emissions 13
3.5. Conducted spurious emissions & band edge 28
Appendix A. Measurement equipment 30
Appendix B. Test setup photos 31

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1. General information

Applicant:	Y TECH CO.,LTD.
Applicant address:	13509 startup-dong-209-ho, KET, 25, Saenari-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
Test site:	KES Co., Ltd.
Test site address:	3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s):	15.247
FCC ID:	2ARVOVMS-V7
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Smart automatic measuring device for electricity
Frequency range	2 402 ㎒ ~ 2 480 ㎒ (BLE)
Model:	VMS-V7
Modulation technique	GFSK
Number of channels	2 402 ㎒ ~ 2 480 ㎒ (BLE) : 40ch
Antenna specification	2.4 ㎓ Antenna type : PCB antenna, Peak gain : -2.36 ㏈i
Power source	DC 3.7 V (Internal Rechargeable Li-Po Battery)

1.2. Test configuration

The **Y TECH CO.,LTD. VMS-V7 FCC ID: 2ARVOVMS-V7** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05
ANSI C63.10-2013

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.3. Device modifications
N/A

1.4. Accessory information
N/A

1.5. Software and Firmware description
The software and firmware installed in the EUT is version 1.0

1.6. Measurement results explanation example
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 0.93 + 10 = 10.93 (dB)

1.7. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.62 dB
Uncertainty for Radiation emission test (include Fundamental emission)	9kHz - 30MHz	4.54 dB
	30MHz - 1GHz	4.36 dB
	Above 1GHz	5.00 dB
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

1.8. Frequency/channel operations

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	1
. .	. .	. .
20	2 442	1
. .	. .	. .
39	2 480	1

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass
15.247(e)	Power spectral density	Pass
15.205 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8

Test setup



ANSI C63.10-2013 - Section 11.8.1

1. RBW = 100 ㎑.
2. VBW ≥ [3 × RBW].
3. Detector = peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 ㏈ relative to the maximum level measured in the fundamental emission.

ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 ㏈, if the functionality described above (i.e., RBW = 100 ㎑, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 ㏈.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 ㎒, 2 400 ~ 2 483.5 ㎒, and 5 725 ~ 5 850 ㎒ bands. The minimum 6 ㏈ bandwidth shall be at least 500 ㎑.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Frequency(㎒)	6 dB bandwidth(㎒)	Limit(㎒)
2 402	0.699	0.5
2 442	0.699	
2 480	0.699	

LE







N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

1. Set the RBW ≥ DTS bandwidth.
2. Set VBW ≥ [3 × RBW].
3. Set span ≥ [3 × RBW].
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold
7. Allow trace to fully stabilize
8. Use peak marker function to determine the peak amplitude level

ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS ba ndwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 ㎒, 2 400~2 483.5 ㎒, and 5 725~5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)
LE	-10.08	-10.59	-9.71	-10.32	-8.80	-9.36

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.3. Power spectral density

Test procedure

ANSI C63.10-2013 - Section 11.10.2

Test setup



Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to 3 ㎑ ≤ RBW ≤ 100 ㎑
d. Set the VBW ≥ [3 × RBW].
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.
j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 ㏈m in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Results

Frequency(㎒)	PSD (dBm)	Limit(dBm)
2 402	-26.00	8
2 442	-25.19	
2 480	-24.49	

LE







Blank

3.4. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Test procedure below 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 ㎒

1. Spectrum analyzer settings for f < 1 ㎓:
   ① Span = wide enough to fully capture the emission being measured
   ② RBW = 100 ㎑
   ③ VBW ≥ RBW
   ④ Detector = quasi peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
2. Spectrum analyzer settings for f ≥1 ㎓: Peak
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 ㎒
   ④ Detector = peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
   ⑦ Trace was allowed to stabilize

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3. Spectrum analyzer settings for $f \geq 1$ GHz: Average
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 MHz
   ③ VBW ≥ 3 × RBW
   ④ Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
   ⑤ Averaging type = power(i.e., RMS)
      1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
      2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
   ⑥ Sweep = auto
   ⑦ Trace = max hold
   ⑧ Perform a trace average of at least 100 traces.
   ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
      1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is 10 log(1/x), where x is the duty cycle.
      2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
      3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Note.

1. f <30 MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40\log(D_m/Ds)$
   $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20\log(D_m/Ds)$
   Where:
   F_d = Distance factor in dB
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
3. CF(Correction factors(dB)) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d(dB)
4. Field strength(dBμV/m) = Level(dBμV) + CF (dB) + or DCF(dB)
5. Margin(dB) = Limit(dBμV/m) - Field strength(dBμV/m)
6. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation.**
8. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
9. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400/F(㎑)
0.490 ~ 1.705	30	24000/F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Duty cycle

Regarding to KDB 558074 D01_v05, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Minimum VBW (㎑)	Duty cycle correction factor (㏈)
0.400	0.626	0.639	63.9	2.5	2.7

Duty cycle (Linear) = T_{on} time/Period

Minimum VBW(㎑) = 1/T_{on}, where T is on time in second

DCF(Duty cycle correction factor (㏈)) = 10log(1/duty cycle)

Middle channel



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 30 ㎒)

Mode:	LE
Distance of measurement:	3 meter
Channel:	39 (Worst case)

Horizontal	Vertical
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 1 000 ㎒) – Worst case

Mode:	LE
Distance of measurement:	3 meter
Channel:	39 (Worst case)

Horizontal // Vertical



No.	Frequency [MHz]	(P)	Reading [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]
1	39.821	H	52.0	-29.8	22.2	40.0	17.8
2	79.470	H	58.3	-34.8	23.5	40.0	16.5
3	119.361	H	69.0	-31.6	37.4	43.5	6.1
4	159.253	H	71.8	-32.0	39.8	43.5	3.7
5	256.010	H	68.6	-26.9	41.7	46.0	4.3
6	342.098	H	61.6	-24.5	37.1	46.0	8.9
7	39.579	V	56.0	-29.9	26.1	40.0	13.9
8	44.550	V	54.2	-28.6	25.6	40.0	14.4
9	118.755	V	60.5	-31.5	29.0	43.5	14.5
10	195.506	V	61.6	-28.8	32.8	43.5	10.7
11	260.375	V	64.2	-26.8	37.4	46.0	8.6
12	586.538	V	58.8	-17.6	41.2	46.0	4.8

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Above 1 000 ㎒)

Mode: LE

Distance of measurement: 3 meter

Channel: 00

- **Spurious**

Frequency (㎒)	Level (dB㎶)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
1 846.60	50.73	Peak	H	-2.59	-	48.14	74.00	25.86
2 338.60	51.02	Peak	H	-0.32	-	50.70	74.00	23.30
4 813.00	57.07	Peak	H	7.66	-	64.73	74.00	9.27
4 813.00	37.92	Average	H	7.66	-	45.58	54.00	8.42
7 200.00	48.21	Peak	H	11.26	-	59.47	74.00	14.53
7 200.00	32.81	Average	H	11.26	-	44.07	54.00	9.93
1 849.50	47.99	Peak	V	-2.56	-	45.43	74.00	28.57
2 338.60	50.85	Peak	V	-0.32	-	50.53	74.00	23.47
4 813.00	53.37	Peak	V	7.66	-	61.03	74.00	12.97
4 813.00	36.20	Average	V	7.66	-	43.86	54.00	10.14
7 200.00	46.71	Peak	V	11.26	-	57.97	74.00	16.03
7 200.00	32.91	Average	V	11.26	-	44.17	54.00	9.83

- **Band edge**

Frequency (㎒)	Level (dB㎶)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB㎶/m)	Limit (dB㎶/m)	Margin (dB)
2 337.76	52.78	Peak	H	-0.32	-	52.46	74.00	21.54
2 337.91	50.75	Peak	V	-0.32	-	50.43	74.00	23.57

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Horizontal // Average for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode: LE

Distance of measurement: 3 meter

Channel: 20

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 849.50	48.64	Peak	H	-2.56	-	46.08	74.00	27.92
2 379.20	51.86	Peak	H	-0.24	-	51.62	74.00	22.38
2 506.50	52.62	Peak	H	0.01	-	52.63	74.00	21.37
4 878.00	55.74	Peak	H	8.17	-	63.91	74.00	10.09
4 878.00	37.37	Average	H	8.17	-	45.54	54.00	8.46
7 331.00	47.54	Peak	H	11.82	-	59.36	74.00	14.64
7 331.00	32.49	Average	H	11.82	-	44.31	54.00	9.69
1 849.50	47.66	Peak	V	-2.56	-	45.10	74.00	28.90
2 379.50	53.55	Peak	V	-0.24	-	53.31	74.00	20.69
2 506.50	52.51	Peak	V	0.01	-	52.52	74.00	21.48
4 878.00	51.14	Peak	V	8.17	-	59.31	74.00	14.69
4 878.00	34.98	Average	V	8.17	-	43.15	54.00	10.85
7 331.00	44.27	Peak	V	11.82	-	56.09	74.00	17.91
7 331.00	31.94	Average	V	11.82	-	43.76	54.00	10.24

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Horizontal // Average for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.
1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode: LE

Distance of measurement: 3 meter

Channel: 39

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 846.60	50.73	Peak	H	-2.59	-	48.14	74.00	25.86
2 338.60	51.02	Peak	H	-0.32	-	50.70	74.00	23.30
2 466.00	53.66	Peak	H	-0.08	-	53.58	74.00	20.42
4 813.00	57.07	Peak	H	7.66	-	64.73	74.00	9.27
4 813.00	37.92	Average	H	7.66	-	45.58	54.00	8.42
7 200.00	48.21	Peak	H	11.26	-	59.47	74.00	14.53
7 200.00	32.81	Average	H	11.26	-	44.07	54.00	9.93
1 849.50	47.99	Peak	V	-2.56	-	45.43	74.00	28.57
2 338.60	50.85	Peak	V	-0.32	-	50.53	74.00	23.47
2 466.00	53.51	Peak	V	-0.08	-	53.43	74.00	20.57
4 813.00	53.37	Peak	V	7.66	-	61.03	74.00	12.97
4 813.00	36.20	Average	V	7.66	-	43.86	54.00	10.14
7 200.00	46.71	Peak	V	11.26	-	57.97	74.00	16.03
7 200.00	32.91	Average	V	11.26	-	44.17	54.00	9.83

- **Band edge**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.72	52.92	Peak	H	-0.05	-	52.87	74.00	21.13
2 483.77	51.05	Peak	V	-0.05	-	51.00	74.00	23.00

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Horizontal // Average for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (18 ㎓ to 30 ㎓) – Worst case

Mode:	LE
Distance of measurement:	3 meter
Channel:	39 (Worst case)

Horizontal	Vertical
	

Note.
1. No spurious emission were detected above 18 ㎓.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.5. Conducted spurious emissions & band edge

Test setup



Test procedure

Band edge

ANSI C63.10-2013 - Section 11.11

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Set the RBW = 100 ㎑
4. Set the VBW = [3 × RBW].
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow trace to fully stabilize.

Out of band emissions

ANSI C63.10-2013 - Section 11.11

1. Start frequency was set to 30 ㎒ and stop frequency was set to 25 ㎓ for 2.4 ㎓ frequencies and 40 ㎓ for 5 ㎓ frequencies
2. Set the RBW = 100 ㎑
3. Set the VBW = [3 × RBW].
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow trace to fully stabilize.

Limit

According to 15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

LE













This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV30	101389	1 year	2019.01.19
Spectrum Analyzer	R&S	FSV40	101002	1 year	2019.06.29
8360B Series Swept Signal Generator	HP	83630B	3844A00786	1 year	2019.01.22
Power Meter	Anritsu	ML2495A	1438001	1 year	2019.01.25
Pulse Power Sensor	Anritsu	MA2411B	1339205	1 year	2019.01.25
Attenuator	Agilent	8493C	82507	1 year	2019.01.22
Loop Antenna	Schwarzbeck	FMZB1513	225	2 years	2019.05.10
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	9168-714	2 years	2018.11.28
Horn Antenna	A.H	SAS-571	414	2 years	2019.02.15
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	2 years	2019.02.15
High Pass Filter	Wainwright Instrument Gmbh	WHJS3000-10TT	1	1 year	2019.06.29
Low Pass Filter	Wainwright Instrument Gmbh	WLK1.0/18G-10TT	1	1 year	2019.06.29
Broadband Amplifier	Schwarzbeck	BBV9721	PS9721-003	1 year	2019.01.23
Preamplifier	AGILENT	8449B	3008A01729	1 year	2019.01.11
EMI Test Receiver	R&S	ESU26	100551	1 year	2019.04.11
DC Power supply	Agilent	6632B	MY43004090	1 year	2019.06.28

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook computer	LG Electronics Inc.,	LG15N53	NEZ65167208

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr