

## TEST REPORT

**Application No.:** SZEM1903011376CR  
**Applicant:** SHENZHEN DBK ELECTRONICS CO., LTD  
**Address of Applicant:** No.8 Qinghua Road, Zhu Village, Fucheng New Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province, China  
**Manufacturer:** SHENZHEN DBK ELECTRONICS CO., LTD.  
**Address of Manufacturer:** Room No.208-1, 308, 404-408 in Building Five, 2-4 Floor in Building Three, No.8 Qinghua Road, Zhu Village, Fucheng New Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province, P.R.China  
**Factory:** SHENZHEN DBK ELECTRONICS CO., LTD.  
**Address of Factory:** Room No.208-1, 308, 404-408 in Building Five, 2-4 Floor in Building Three, No.8 Qinghua Road, Zhu Village, Fucheng New Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province, P.R.China

### Equipment Under Test (EUT):

**EUT Name:** Wireless charger  
**Model No.:** CP6732-RZ  
**Trade mark:** DBK  
**FCC ID:** 2ARVRCP6732  
**Standard(s) :** 47 CFR Part 18  
**Date of Receipt:** 2019-03-06  
**Date of Test:** 2019-03-12 to 2019-03-26  
**Date of Issue:** 2019-05-08

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

*Keny Xu*

Keny Xu  
EMC Laboratory Manager





| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2019-05-08 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                                                                                     |  |
|--------------------------|--|-------------------------------------------------------------------------------------|--|
| Authorized for issue by: |  |                                                                                     |  |
|                          |  |    |  |
|                          |  | Leo Li /Project Engineer                                                            |  |
|                          |  |  |  |
|                          |  | Eric Fu /Reviewer                                                                   |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)



## 2 Test Summary

| Radio Spectrum Matter Part |                |          |             |        |
|----------------------------|----------------|----------|-------------|--------|
| Item                       | Standard       | Method   | Requirement | Result |
| Conducted disturbance      | 47 CFR Part 18 | FCC MP-5 | Part 18.307 | Pass   |
| Radiated emission          | 47 CFR Part 18 | FCC MP-5 | Part 18.305 | Pass   |



### 3 Contents

|                                                  | Page |
|--------------------------------------------------|------|
| 1 COVER PAGE .....                               | 1    |
| 2 TEST SUMMARY .....                             | 3    |
| 3 CONTENTS .....                                 | 4    |
| 4 GENERAL INFORMATION .....                      | 5    |
| 4.1 DETAILS OF E.U.T. ....                       | 5    |
| 4.2 DESCRIPTION OF SUPPORT UNITS .....           | 5    |
| 4.3 MEASUREMENT UNCERTAINTY .....                | 5    |
| 4.4 TEST LOCATION.....                           | 6    |
| 4.5 TEST FACILITY.....                           | 6    |
| 4.6 DEVIATION FROM STANDARDS.....                | 6    |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS ..... | 6    |
| 5 EQUIPMENT LIST.....                            | 7    |
| 6 RADIO SPECTRUM MATTER TEST RESULTS.....        | 8    |
| 6.1 CONDUCTED DISTURBANCE.....                   | 8    |
| 6.1.1 E.U.T. Operation .....                     | 8    |
| 6.1.2 Test Setup Diagram.....                    | 8    |
| 6.1.3 Measurement Procedure and Data.....        | 9    |
| 6.2 RADIATED EMISSION .....                      | 12   |
| 6.2.1 E.U.T. Operation .....                     | 13   |
| 6.2.2 Test Setup Diagram.....                    | 13   |
| 6.2.3 Measurement Procedure and Data.....        | 13   |
| 7 PHOTOGRAPHS.....                               | 17   |
| 7.1 TEST SETUP.....                              | 17   |
| 7.2 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)..... | 17   |

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                                                                                   |
|----------------------|---------------------------------------------------------------------------------------------------|
| Power supply:        | Input: DC 5V/2A, DC 9V/1.67A<br>Output:<br>WPC: 5W(DC 5V/1A), 7.5W(DC 5V/1.5A), 10W(DC 9V/1.1A)   |
| Cable:               | USB cable: 100cm shielded                                                                         |
| Antenna Type:        | Loop Antenna                                                                                      |
| Modulation Type:     | Load Modulation                                                                                   |
| Operation Frequency: | 109.21kHz to 178.68kHz                                                                            |
| Remark:              | Tests were conducted in all three load modes and the worst case 10W(DC 9V/1.1A) is reported only. |

### 4.2 Description of Support Units

| Description  | Manufacturer    | Model No.  | Serial No.   |
|--------------|-----------------|------------|--------------|
| iPhone 8     | Apple           | A1863      | F4GVQ656JC6D |
| Mobile Phone | SAMSUNG         | SM-G9500   | R28J9140LPB  |
| USB Adapter  | Client supplied | KA1803A-EU | N/A          |
| iPhone 8     | Apple           | A1863      | F4GVQ656JC6D |

### 4.3 Measurement Uncertainty

| No. | Item                            | Measurement Uncertainty              |
|-----|---------------------------------|--------------------------------------|
| 1   | Conduction Emission             | $\pm 3.0\text{dB}$ (150kHz to 30MHz) |
| 2   | Radiated Spurious emission test | $\pm 4.5\text{dB}$ (Below 1GHz)      |
|     |                                 | $\pm 4.8\text{dB}$ (Above 1GHz)      |
| 3   | Temperature test                | $\pm 1^\circ\text{C}$                |
| 4   | Humidity test                   | $\pm 3\%$                            |
| 5   | Supply voltages                 | $\pm 1.5\%$                          |
| 6   | Time                            | $\pm 3\%$                            |

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Conducted disturbance |                   |               |              |            |              |
|-----------------------|-------------------|---------------|--------------|------------|--------------|
| Equipment             | Manufacturer      | Model No      | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room        | ChangZhou ZhongYu | GB-88         | SEM001-06    | 2017-05-10 | 2020-05-09   |
| Measurement Software  | AUDIX             | e3 V5.4.1221d | N/A          | N/A        | N/A          |
| Coaxial Cable         | SGS               | N/A           | SEM024-01    | 2018-07-12 | 2019-07-11   |
| LISN                  | Rohde & Schwarz   | ENV216        | SEM007-01    | 2018-09-25 | 2019-09-24   |
| LISN                  | ETS-LINDGREN      | 3816/2        | SEM007-02    | 2019-04-01 | 2020-03-31   |
| EMI Test Receiver     | Rohde & Schwarz   | ESCI          | SEM004-02    | 2019-04-01 | 2020-03-31   |

| Radiated emission                     |                      |                 |              |            |              |
|---------------------------------------|----------------------|-----------------|--------------|------------|--------------|
| Equipment                             | Manufacturer         | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 10m Semi-Anechoic Chamber             | SAEMC                | FSAC1018        | SEM001-03    | 2018-03-31 | 2021-03-30   |
| Measurement Software                  | AUDIX                | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                         | SGS                  | N/A             | SEM029-01    | 2018-07-12 | 2019-07-11   |
| EMI Test Receiver (9kHz-7GHz)         | Rohde & Schwarz      | ESR             | SEM004-03    | 2019-04-01 | 2020-03-31   |
| Trilog-Broadband Antenna (30MHz-1GHz) | Schwarzbeck          | VULB9168        | SEM003-18    | 2016-06-29 | 2019-06-28   |
| Pre-amplifier                         | Sonoma Instrument Co | 310N            | SEM005-04    | 2019-04-12 | 2020-04-11   |
| Active Loop Antenna                   | ETS-Lindgren         | 6502            | SEM003-08    | 2017-08-22 | 2020-08-21   |

| General used equipment          |                                           |          |              |            |              |
|---------------------------------|-------------------------------------------|----------|--------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No | Inventory No | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-03    | 2018-09-27 | 2019-09-26   |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-04    | 2018-09-27 | 2019-09-26   |
| Humidity/ Temperature Indicator | Mingle                                    | N/A      | SEM002-08    | 2018-09-27 | 2019-09-26   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3     | SEM002-01    | 2019-04-04 | 2020-04-03   |

## 6 Radio Spectrum Matter Test Results

### 6.1 Conducted disturbance

Test Requirement Part 18.307  
Test Method: FCC MP-5  
Limit:

| Frequency of emission (MHz) | Conducted limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15-0.5                    | 66 to 56*              | 56 to 46* |
| 0.5-5                       | 56                     | 46        |
| 5-30                        | 60                     | 50        |


\*Decreases with the logarithm of the frequency.

#### 6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 21.3 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar  
Test mode a:Charge mode\_Keep the EUT charging

#### 6.1.2 Test Setup Diagram




### 6.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor


Mode:a; Line:Live Line



Site : Shielding Room  
Condition: Line  
Job No. : 11376CR  
Test mode: a

|    | Freq  | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz   | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.17  | 0.02       | 9.66        | 27.55      | 37.23 | 54.90      | -17.67     | Average |
| 2  | 0.17  | 0.02       | 9.66        | 45.95      | 55.63 | 64.90      | -9.27      | QP      |
| 3  | 0.20  | 0.02       | 9.66        | 17.81      | 27.49 | 53.58      | -26.09     | Average |
| 4  | 0.20  | 0.02       | 9.66        | 39.10      | 48.78 | 63.58      | -14.80     | QP      |
| 5  | 0.51  | 0.06       | 9.67        | 16.84      | 26.57 | 46.00      | -19.43     | Average |
| 6  | 0.51  | 0.06       | 9.67        | 29.97      | 39.70 | 56.00      | -16.30     | QP      |
| 7  | 1.04  | 0.09       | 9.74        | 11.45      | 21.28 | 46.00      | -24.72     | Average |
| 8  | 1.04  | 0.09       | 9.74        | 22.31      | 32.14 | 56.00      | -23.86     | QP      |
| 9  | 2.68  | 0.16       | 9.71        | 13.62      | 23.49 | 46.00      | -22.51     | Average |
| 10 | 2.68  | 0.16       | 9.71        | 22.35      | 32.22 | 56.00      | -23.78     | QP      |
| 11 | 21.37 | 0.25       | 10.12       | 0.36       | 10.73 | 50.00      | -39.27     | Average |
| 12 | 21.37 | 0.25       | 10.12       | 21.43      | 31.80 | 60.00      | -28.20     | QP      |

Mode:a; Line:Neutral Line



Site : Shielding Room  
Condition: Neutral  
Job No. : 11376CR  
Test mode: a

|    | Freq  | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|-------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz   | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.17  | 0.02       | 9.64        | 27.14      | 36.80 | 54.72      | -17.92     | Average |
| 2  | 0.17  | 0.02       | 9.64        | 44.18      | 53.84 | 64.72      | -10.88     | QP      |
| 3  | 0.20  | 0.02       | 9.64        | 17.80      | 27.46 | 53.54      | -26.08     | Average |
| 4  | 0.20  | 0.02       | 9.64        | 37.89      | 47.55 | 63.54      | -15.99     | QP      |
| 5  | 0.88  | 0.08       | 9.71        | 23.00      | 32.79 | 46.00      | -13.21     | Average |
| 6  | 0.88  | 0.08       | 9.71        | 32.93      | 42.72 | 56.00      | -13.28     | QP      |
| 7  | 1.19  | 0.11       | 9.70        | 16.19      | 26.00 | 46.00      | -20.00     | Average |
| 8  | 1.19  | 0.11       | 9.70        | 24.88      | 34.69 | 56.00      | -21.31     | QP      |
| 9  | 2.78  | 0.16       | 9.68        | 12.11      | 21.95 | 46.00      | -24.05     | Average |
| 10 | 2.78  | 0.16       | 9.68        | 21.68      | 31.52 | 56.00      | -24.48     | QP      |
| 11 | 21.26 | 0.25       | 10.15       | 10.28      | 20.68 | 50.00      | -29.32     | Average |
| 12 | 21.26 | 0.25       | 10.15       | 15.54      | 25.94 | 60.00      | -34.06     | QP      |

## 6.2 Radiated emission

Test Requirement: Part 18.305  
Test Method: FCC MP-5  
Measurement Distance: 3m  
Frequency range: 9KHz-30MHz  
Limit:

(b) The field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following:

| Equipment                                           | Operating frequency                        | RF Power generated by equipment (watts) | Field strength limit (uV/m)                                                | Distance (meters)                  |
|-----------------------------------------------------|--------------------------------------------|-----------------------------------------|----------------------------------------------------------------------------|------------------------------------|
| Any type unless otherwise specified (miscellaneous) | Any ISM frequency                          | Below 500<br>500 or more                | 25<br>$25 \times \text{SQRT}(\text{power}/500)$                            | 300<br><sup>1</sup> 300            |
|                                                     | Any non-ISM frequency                      | Below 500<br>500 or more                | 15<br>$15 \times \text{SQRT}(\text{power}/500)$                            | 300<br><sup>1</sup> 300            |
| Industrial heaters and RF stabilized arc welders    | On or below 5,725 MHz<br>Above 5,725 MHz   | Any<br>Any                              | 10<br>( <sup>2</sup> )                                                     | 1,600<br>( <sup>2</sup> )          |
| Medical diathermy                                   | Any ISM frequency<br>Any non-ISM frequency | Any<br>Any                              | 25<br>15                                                                   | 300<br>300                         |
| Ultrasonic                                          | Below 490 kHz                              | Below 500<br>500 or more                | 2,400/F(kHz)<br>$2,400/F(\text{kHz}) \times \text{SQRT}(\text{power}/500)$ | 300<br><sup>3</sup> 300            |
|                                                     | 490 to 1,600 kHz<br>Above 1,600 kHz        | Any<br>Any                              | 24,000/F(kHz)<br>15                                                        | 30<br>30                           |
| Induction cooking ranges                            | Below 90 kHz<br>On or above 90 kHz         | Any<br>Any                              | 1,500<br>300                                                               | <sup>4</sup> 30<br><sup>4</sup> 30 |

<sup>1</sup>Field strength may not exceed 10 µV/m at 1600 meters. Consumer equipment operating below 1000 MHz is not permitted the increase in field strength otherwise permitted here for power over 500 watts.

<sup>2</sup>Reduced to the greatest extent possible.

<sup>3</sup>Field strength may not exceed 10 µV/m at 1600 meters. Consumer equipment is not permitted the increase in field strength otherwise permitted here for over 500 watts.

<sup>4</sup>Induction cooking ranges manufactured prior to February 1, 1980, shall be subject to the field strength limits for miscellaneous ISM equipment.

### Remark:

1 This product belongs to non-ISM equipment, the field strength limit is 15uV/m at 300 meter distance.

2 Limit:  $20\log(15\text{uV/m}) + 20\log(300/3) = 23.52 + 40 = 63.52\text{dBuV/m}$  at 3 meters distance



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Laboratory


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

### 6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 51 % RH Atmospheric Pressure: 1015 mbar  
Test mode a: Charge mode\_Keep the EUT charging

### 6.2.2 Test Setup Diagram



### 6.2.3 Measurement Procedure and Data


- Test Procedure:
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber(30MHz-1000MHz) and 3 meter semi-anechoic chamber(9kHz-30MHz). The table was rotated 360 degrees to determine the position of the highest radiation.
  - The EUT was set 10 meters(30MHz-1000MHz) and 10 meter (9kHz-30MHz) away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
  - Above 30MHz: The Analyzer/Receiver scanned from 30MHz to 1000MHz. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  - Below 30MHz: The Analyzer/Receiver scanned from 9kHz to 30MHz. The antenna height is 2 meters above the ground to determine the maximum

value of the field strength.

- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 2 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Repeat above procedures until all frequencies measured was complete.
- i. Measurement Requirement:
  - 1) This product belongs to non-ISM equipment, the field strength limit is 15uV/m at 300 meter distance.
  - 2) Limit:  $20\log(15\text{uV/m}) + 20\log(300/3) = 23.52 + 40 = 63.52\text{dBuV/m}$  at 3 meters distance.



Mode a:  
9kHz-150kHz



Condition: 3m  
Job No. : 11376CR  
Test Mode: a

|      | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  |
|------|------|------------|------------|---------------|------------|--------|------------|------------|---------|
|      | MHz  | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         |
| 1 pp | 0.01 | 0.25       | 16.81      | 31.61         | 64.42      | 49.87  | 63.52      | -13.65     | Average |
| 2    | 0.04 | 0.14       | 12.96      | 32.18         | 64.55      | 45.47  | 63.52      | -18.05     | Average |
| 3    | 0.13 | 0.06       | 11.80      | 32.67         | 54.72      | 33.91  | 63.52      | -29.61     | Average |




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode a:  
150kHz-30MHz



Condition: 3m  
Job No. : 11376CR  
Test Mode: a

|      | Freq | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  |
|------|------|------------|------------|---------------|------------|--------|------------|------------|---------|
|      | MHz  | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         |
| 1 pp | 0.17 | 0.07       | 11.76      | 32.67         | 81.90      | 61.06  | 63.52      | -2.46      | Average |
| 2    | 0.59 | 0.14       | 11.82      | 32.66         | 63.90      | 43.20  | 63.52      | -20.32     | Average |
| 3    | 2.17 | 0.35       | 12.12      | 32.65         | 51.22      | 31.04  | 63.52      | -32.48     | Average |



## 7 Photographs

### 7.1 Test Setup

Refer to Setup Photos

### 7.2 EUT Constructional Details (EUT Photos)

Refer to EUT external and internal photos

- End of the Report -



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (China) (SGS) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com