


Prüfbericht-Nr.: <i>Test report No.:</i>	60362410 001	Auftrags-Nr.: <i>Order No.:</i>	168156015	Seite 1 von 24 <i>Page 1 of 24</i>
Kunden-Referenz-Nr.: <i>Client reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	13.03.2020	
Auftraggeber: <i>Client:</i>	SHENZHEN DBK ELECTRONICS CO.,LTD. Room No .208-1,308, 404-408 in Building Five, 2-4 Floor in Building Three, No.8 Qinghua Road, Zhu Village ,Fucheng New Community, Guanlan Street, Longhua District, Shenzhen City, Guangdong Province, P.R.China			
Prüfgegenstand: <i>Test item:</i>	Qi Wireless Charging Pad			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	NS-MWPC10K, NS-MWPC10K-C, NS-MWPC10KTP, NS-xxxxxxxxxx, MD-xxxxxxxxxx, PT- xxxxxxxxxxxx, DX- xxxxxxxxxxxx, RF- xxxxxxxxxxxx ("x" can be 0-9, A-Z, a-z, "-" or blank, for market purpose only, all models are identical except the model name or color) (Trademark: INSIGNIA, MODAL, Platinum, DYNEX, Rocketfish)			
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.207	RSS-216 issue 2 January 2016		
	CFR47 FCC Part 15: Subpart C Section 15.209	RSS-GEN issue 5 March 2019		
		RSS-102 issue 5 March 2015		
Wareneingangsdatum: <i>Date of receipt:</i>	17.03.2020	Refer to photos document		
Prüfmuster-Nr.: <i>Test sample No.:</i>	A001072446-018 to 019			
Prüfzeitraum: <i>Testing period:</i>	18.03.2020 - 10.04.2020			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
				
20.05.2020 Jonathan Li / Project Manager		20.05.2020 Sam Lin / Technical Certifier		
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>
Sonstiges / Other:				
FCC ID: 2ARVRWC074				
IC: 25947-WC074 HVIN: NS-MWPC10K-C				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
* Legende: 1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend: 1 = very good	2 = good	3 = satisfactory	4 = sufficient	5 = poor
P(ass) = passed a.m. test specifications(s)		F(ail) = failed a.m. test specifications(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.				
<i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 99% BANDWIDTH

RESULT: Pass

5.1.3 RADIATED EMISSIONS

RESULT: Pass

5.1.4 CONDUCTED EMISSIONS

RESULT: Pass

Contents

1	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	8
3.5	SUBMITTED DOCUMENTS.....	8
4	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	9
4.5	TEST SETUP DIAGRAM	10
5	TEST RESULTS	11
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
5.1.1	<i>Antenna Requirement</i>	<i>11</i>
5.1.2	<i>99% Bandwidth</i>	<i>12</i>
5.1.3	<i>Radiated Emissions.....</i>	<i>13</i>
5.1.4	<i>Conducted emissions.....</i>	<i>21</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	24
7	LIST OF TABLES.....	24

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

FCC Registration No.: 694916

IC Registration No.: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

TÜV Rheinland (Shenzhen) Co., Ltd.

Radio Spectrum Testing				
Description	Manufacturer	Model	Serial No.	Cal. until
Wireless Connectivity Tester	R&S	CMW270	101375	20.08.2020
Signal Analyzer	R&S	FSV 40	101441	20.08.2020
Vector Signal Generator	R&S	SMBV100A	263301	21.08.2020
Signal Generator	R&S	SMB100A	115186	21.08.2020
OSP	R&S	OSP 150	101017	17.12.2020
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
Test Software	R&S	WMS32 (V10.50.10)	N/A	N/A
Power Meter	R&S	NRP2	107105	17.12.2020
Wideband Power Sensor	R&S	NRP-Z81	105350	17.12.2020
Humid & Temp Programmable Tester	BOST	NTH090-60	19040801	16.04.2020
Shielding Room 8#	Albatross	SR8	APC17151-SR8	23.07.2020
Unwanted Emission Testing				
Description	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	19.08.2020
Signal Analyzer	R&S	FSV 40	101439	21.08.2020
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	21.08.2020
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	20.08.2020
Amplifier	R&S	SCU-18F	180070	20.08.2020
Amplifier	R&S	SCU40A	100475	20.08.2020
Trilog Broadband Antenna (30 MHz - 1 GHz)	Schwarzbeck	VULB9162	193	02.09.2020

Double-Ridged Antenna (1-18 GHz)	ETS-LINDGREN	3117	00218717	02.09.2020
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	02.09.2020
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	01.09.2020
Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18313	02.09.2020
Test software	R&S	V10.40.10-EMC32	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	07.06.2020

Conducted Emissions

Description	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR3	102428	03.09.2020
Artificial Mains Network	R&S	ENV216	102333	19.08.2020
Attenuator	R&S	ESH2Z31	100300	19.08.2020
EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A

Radiated Emission (3m chamber)

Description	Manufacturer	Model	Serial No.	Cal. until
3m SAC	ETS	SAC3	CT001632-Q1362	23.08.2020
EMI Test Receiver	R&S	ESR7	102111	04.01.2021
Horn Antenna	R&S	HF907	102706	01.09.2020
Preamplifier	FIT	SCU-18F	180077	19.08.2020
Active magnetic loop antenna	SCHWARZBECK	FMZB1519B	00080	19.08.2020
Trilog-Broadband antenna	SCHWARZBECK	VULB9168	0945	12.09.2020
Switching Controller Interface	R&S	OSP 120	102039	N/A
EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Test	Parameters	Expanded uncertainty (U_{lab})	Expanded uncertainty (U_{cisp})
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 3.70 dB ± 3.30 dB	± 3.8 dB ± 3.4 dB
Radiated Emission (3m SAC)	Level accuracy (30MHz to 1000MHz)	± 4.52 dB	± 6.3 dB
	Level accuracy (above 1000MHz)	± 4.37 dB	N/A

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The device is a Qi Wireless Charging Pad.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Qi Wireless Charging Pad
Type Designation	NS-MWPC10K, NS-MWPC10K-C, NS-MWPC10KTP, NS-xxxxxxxxxx, MD-xxxxxxxxxx, PT- xxxxxxxxxxxx, DX- xxxxxxxxxxxx, RF-xxxxxxxxxx ("x" can be 0-9, A-Z, a-z, "-" or blank, for market purpose only, all models are identical except the model name or color)
Trademark	INSIGNIA, MODAL, Platinum, DYNEX, Rocketfish
FCC ID	2ARVRWC074
IC	25947-WC074
Input Voltage	DC 5V@2A/9V@2A/12V@1.5A via AC/DC Adapter
Test voltage	AC 120V, 60Hz
Technical Specification of WPT	
Operating Frequency	111-205KHz
Extreme Temperature Range	0°C - +35°C
Modulation	FSK
Antenna Type	Coil Antenna
Wireless output	10W maximum

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wireless charging
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- FCC/IC Label and Location Info

- Block Diagram

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5&6. All testing were performed according to the procedures in ANSI C63.10: 2013 & ANSI C63.4: 2014

4.3 Special Accessories and Auxiliary Equipment

Table 3: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Electrical Load	SHENZHEN DBK ELECTRONICS CO.,LTD.	N/A	N/A	N/A
Mobile Phone	SANGSUM	Galaxy S9	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Conducted Transmitter Measurement





Diagram of Measurement Equipment Configuration for Mains Conduction Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard	:	Part 15.203
	:	RSS-Gen Clause 6.8
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has an internal antenna, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 99% Bandwidth

RESULT:
Pass
Test Specification


Test standard : RSS-Gen Clause 6.7
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 23.03.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : A
 Ambient temperature : 25 °C
 Relative humidity : 56 %
 Atmospheric pressure : 101 kPa

For details refer to following test result.

Operating frequency (kHz)	99% Bandwidth (kHz)
127.625	1.068



5.1.3 Radiated Emissions

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.209 RSS-216 Clause 6.2.2.2
Basic standard	: ANSI C63.10: 2013 & ANSI C63.4:2014
Limits	: Refer to 15.209(a) RSS-Gen Issue 5 Table 4
Kind of test site	: 3m Semi-anechoic Chamber


Test Setup

Date of testing	: 19.03.2020, 09.04.2020
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Ambient temperature	: 23 °C
Relative humidity	: 48 %
Atmospheric pressure	: 101 kPa

Refer to following test plots for details of test result.


9KHz – 90KHz

X axis




Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.014670	51.48	---	144.26	92.78	100.0	286.0	20.0	0.0
0.014670	---	48.28	124.28	75.99	100.0	286.0	20.0	0.0
0.051467	---	52.02	113.37	61.35	100.0	286.0	20.0	0.0
0.051583	62.37	---	133.34	70.97	100.0	286.0	20.0	0.0

Y axis



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.014670	---	44.55	124.28	79.73	100.0	240.0	20.0	0.0
0.014670	50.66	---	144.26	93.59	100.0	240.0	20.0	0.0
0.052104	---	47.73	113.27	65.54	100.0	240.0	20.0	0.0
0.052451	57.98	---	133.20	75.22	100.0	240.0	20.0	0.0


Z axis



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.051351	---	41.57	113.39	71.83	100.0	286.0	20.0	0.0
0.051641	49.87	---	133.33	83.46	100.0	286.0	20.0	0.0


110KHz – 490KHz

X axis




Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.146000	79.61	---	124.31	44.70	100.0	262.0	20.0	0.0
0.146000	---	79.47	104.32	24.84	100.0	262.0	20.0	0.0
0.291950	---	48.65	98.30	49.65	100.0	185.0	20.0	0.0
0.292250	49.63	---	118.29	68.65	100.0	185.0	20.0	0.0
0.438000	---	57.52	94.77	37.26	100.0	252.0	20.0	0.0
0.438200	58.11	---	114.77	56.66	100.0	263.0	20.0	0.0

Y axis



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.146000	72.39	---	124.31	51.92	100.0	140.0	20.0	0.0
0.146000	---	72.27	104.32	32.05	100.0	140.0	20.0	0.0
0.292150	47.10	---	118.29	71.19	100.0	113.0	20.0	0.0
0.292200	---	44.79	98.29	53.50	100.0	113.0	20.0	0.0
0.438000	51.14	---	114.77	63.63	100.0	163.0	20.0	0.0
0.438000	---	50.32	94.77	44.45	100.0	163.0	20.0	0.0


Z axis



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)
0.137943	84.72	---	124.80	40.08	100.0	240.0	20.0	0.0
0.137943	---	84.64	104.81	20.17	100.0	240.0	20.0	0.0
0.413900	62.78	---	115.27	52.48	100.0	236.0	20.0	0.0
0.413900	---	62.61	95.27	32.65	100.0	236.0	20.0	0.0


9KHz – 30MHz

X axis




Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)	Trd Corr. (dB/m)
0.146072	78.50	104.31	25.82	100.0	258.0	20.0	0.0	20.0
0.435331	57.51	94.83	37.32	100.0	253.0	20.0	0.0	20.0
0.729441	47.30	70.34	23.04	100.0	217.0	20.0	0.0	20.0

Y axis




Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)	Trd Corr. (dB/m)
0.145770	71.90	104.33	32.43	100.0	142.0	20.0	0.0	20.0
0.435331	50.69	94.83	44.13	100.0	163.0	20.0	0.0	20.0
0.725052	40.31	70.40	30.09	100.0	356.0	20.0	0.0	20.0


Z axis



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Azimuth (deg)	Corr. (dB/m)	Preamp (dB)	Trd Corr. (dB/m)
0.051703	42.97	113.33	70.37	100.0	265.0	20.0	0.0	20.0
0.140432	83.20	104.66	21.46	100.0	218.0	20.0	0.0	20.0
0.417772	62.00	95.19	33.18	100.0	238.0	20.0	0.0	20.0
0.698713	52.95	70.72	17.77	100.0	251.0	20.0	0.0	20.0
0.979655	47.11	67.78	20.68	100.0	220.0	20.0	0.0	20.0
1.260596	42.30	65.59	23.29	100.0	229.0	20.0	0.0	20.0

30MHz - 1GHz
Horizontal


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
48.721000	24.26	40.00	15.74	100.0	H	222.0
204.406000	27.29	43.50	16.21	100.0	H	268.0
98.676000	31.49	43.50	12.01	200.0	H	0.0
556.613000	26.67	46.00	19.33	200.0	H	0.0
96.057000	33.03	43.50	10.47	200.0	H	7.0
935.786000	32.74	46.00	13.26	200.0	H	143.0

Vertical


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
43.386000	30.34	40.00	9.66	100.0	V	84.0
49.045000	39.00	40.00	2.07	101.0	V	277.0
53.170000	37.13	40.00	4.68	107.0	V	330.0
71.613000	28.02	40.00	11.99	100.0	V	204.0
96.348000	33.21	43.50	10.29	100.0	V	296.0
204.988000	28.21	43.50	15.29	100.0	V	131.0

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
49.045000	34.86	40.00	5.14	1000.0	120.000	101.0	V	277.0
53.170000	32.02	40.00	7.98	1000.0	120.000	107.0	V	330.0

5.1.4 Conducted emissions

RESULT:**Pass****Test Specification**


Test standard	:	FCC Part 15.207 RSS-216 Clause 6.2.2.1
Basic standard	:	ANSI C63.4:2014
Frequency range	:	150KHz - 30MHz
Classification	:	Class B
Limit	:	FCC Part 15.207 (a)
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	07.04.2020
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Earthing	:	Not connected
Ambient temperature	:	23 °C
Relative humidity	:	48 %
Atmospheric pressure	:	101 kPa

Refer to following test plots for details of test result.


L Line



Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.174000	---	25.94	54.77	28.83	L1	9.6
0.178000	46.68	---	64.58	17.90	L1	9.6
0.234000	44.12	---	62.31	18.18	L1	9.6
0.306000	---	31.86	50.08	18.22	L1	9.6
0.433500	---	39.72	47.18	7.46	L1	9.7
0.433500	51.71	---	57.18	5.47	L1	9.7
0.503500	52.65	---	56.00	3.35	L1	9.7
0.504000	---	41.49	46.00	4.51	L1	9.7
1.384000	---	29.41	46.00	16.59	L1	9.7
1.384000	43.61	---	56.00	12.39	L1	9.7
22.548000	37.10	---	60.00	22.90	L1	10.4
22.624000	---	26.21	50.00	23.79	L1	10.4

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.433500	---	40.88	47.19	6.31	200.0	9.000	L1	9.7
0.433500	49.86	---	57.19	7.32	200.0	9.000	L1	9.7
0.503500	50.27	---	56.00	5.73	200.0	9.000	L1	9.7
0.504000	---	41.50	46.00	4.50	200.0	9.000	L1	9.7

N Line



Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.202000	54.19	---	63.53	9.34	N	9.6
0.202000	---	28.25	53.53	25.28	N	9.6
0.358000	49.80	---	58.78	8.98	N	9.7
0.426000	---	29.83	47.33	17.50	N	9.7
0.516000	---	33.59	46.00	12.41	N	9.7
0.520000	48.69	---	56.00	7.31	N	9.7
1.608000	---	23.30	46.00	22.70	N	9.7
1.608000	38.56	---	56.00	17.44	N	9.7
3.360000	---	27.42	46.00	18.58	N	9.8
3.360000	37.13	---	56.00	18.87	N	9.8
22.720000	41.94	---	60.00	18.06	N	10.5
23.112000	---	30.86	50.00	19.14	N	10.5

6 Photographs of the Test Set-Up

Refer to test photo document.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Technical Specification of EUT	8
Table 3: List of Accessories and Auxiliary Equipment.....	9

Appendix A: Photographs of the Test Set-Up

APPENDIX A: PHOTOGRAPHS OF THE TEST SET-UP	1
PHOTOGRAPH 1: SET-UP PHOTO FOR RADIATED EMISSION, 9KHz - 30MHz	2
PHOTOGRAPH 2: SET-UP PHOTO FOR RADIATED EMISSION, 30MHz - 1GHz	2
PHOTOGRAPH 3: SET-UP PHOTO FOR CONDUCTED EMISSION ON AC MAINS	3

Photograph 1: Set-up photo for Radiated Emission, 9KHz - 30MHz



Photograph 2: Set-up photo for Radiated Emission, 30MHz - 1GHz



Photograph 3: Set-up photo for Conducted Emission on AC Mains

