



 CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN

WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK,
DO NOT EXPOSE THE APPLIANCE TO RAIN OR MOISTURE.

CE FCC

FCC ID:2ARWY-WS70

WARNING:
Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does

cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

RF EXPOSURE STATEMENT:
The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

1. Please use the attached charging line for charging. If you are unsure of the type of power available, please consult your dealer.
2. The device has a built-in lithium battery. Please do not put it into the fire or near the heat source.

3. This equipment is not waterproof. Do not put into water or other liquids.
4. Please do not attempt to repair the equipment, because opening the lid after may make you touch the danger point voltage or other risks, if this equipment is the need for maintenance, please to qualified maintenance personnel for repair.
5. If you are not using this product for a long time, you should unplug the charging cable.
6. Avoid the power cord being trampled or the position of the socket and the connecting device being too tight at the plug.

The Device Has A Built-in Lithium Battery. Please Do Not Put It Into The Fire Or Near The Heat Source.

It is a mini wireless system, apply with 6.35mm audio devices, with strong anti-interference ability, through the obstacles of strong, stable transmission no pause etc in order to avoid signal attenuation, wireless system should be close to acting area as far as possible, and with a large metal, wall, scaffolding and other

objects at least keep a distance of 1.5 meters, and as far as possible to ensure that between transmitter and receiver are empty signal direct way. To avoid being unable to use due to low battery, please kindly check the batteries are good before use.

Channel	Choose 10 in 100 Channels (Randomly select 10 after next code pairing)
Distortion	<0.05%
Signal-To-Noise Ratio	>100dB
Latency	< 3ms
System Frequency Response	20~20kHz
Reception Sensitivity	< -110dbm @20dbsinad
Transmission Distance	150ft
Full Working Hours	≥5Hours(Circumstantial)


1/4" Audio Output/Input

ON/OFF/Check Battery Frequency hopping

Code Button


Micro USB charging port

When the device is shut down or started up, double-click the front button, and the four green lights on the side will display the current power information, which will be off after 3 seconds.



DEVICE CHARGING

1. With Dual-ended USB cable that can charge both the receiver and transmitter, please choose 5V 2A adapter for charging.
2. When charging, the battery capacity is displayed as the picture




- 1 The first light is flickering, the battery was charged 1%-25%.
- 2 The second light is flickering, the battery was charged 26%-50%.
- 3 The third light is flickering, the battery was charged 51%-75%.
- 4 The fourth light is flickering, the battery was charged 75%-100%.

Our product uses polymer lithium battery. Please charge the product before using it. If not used for a long time, charge the product once or more than three months.

Power on: Long press the button for 2 seconds when the transmitter and receiver are in power off state. The LED indicator light is always green, the device power on successfully. Enter normal working condition.

Power off: Long press the button for 2 seconds while the transmitter and receiver are in power on state. The LED indicator light is off and the device shut down successfully.



* After power on, the green light of the transmitter is always on, while the green light of the receiver is flashing, indicating that the device is not connected normally.

Connect the transmitter to the guitar and the receiver to the Amplifier, long press the start button of transmitter and receiver, the green lights of the transmitter and receiver always keeps on, enter normal working condition. If the following situations occur:

please solve as follows.

Not pairing successfully: If the transmitter green light keeps on and the receiver red light flashing, proves that the pairing is not successful. Should restart the transmitter and receiver.

No sound after pairing: If there is no green light on both the transmitter and receiver, no sound when playing, you can try to re-pairing the products.

Device frequency hopping When using the device, there are signal interference around the device that cause the device not work properly. Frequency hopping can be performed on the device.




This product has been set by default before delivery and can be used directly after starting up. If the product can't be used directly, try to reset the code.



Pair code: When a transmitter connected with multiple receiver or transmitter and receiver are not the original equipment, can be long press on the code button to red light flashing, when transmitter and receiver normally on a green light, namely to code success!

This system can support 30 sets to use at the same time without interference (above 500ft²). When using multiple equipment, please turn on and test the wireless transmitter and receiver one to one to avoid signal crossing.

After the test of each pair of wireless system is completed, then start and test the next pair of wireless system. If there is any signal interference during test period, can choose frequency hopping key to frequency hopping.



A transmitter can be used with multiple receivers. For example : There are four effects on a stage, you can use one transmitter and four receivers. Connect and performances at the same time!

Device debugging: After turn off all the similar wireless system, use thin iron wire to long press the code button and release

the button until the red light flashing on four receivers. Use thin iron wire to long press the code button of one transmitter; release the button when the red light flashing on the transmitter and all the receivers. It will take 20 seconds. When the green light of transmitter and receivers is always on, four receivers can receive signal from one transmitter at the same time. One-to-many functions can be realized. All code debugging time should be completed within 20 seconds.

