



LTE Cat NB1 Band 13. Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=0.

Low Channel:




High Channel:




LTE Cat NB1 Band 13. Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=3.

Low Channel:




High Channel:




LTE Cat NB1 Band 13. QPSK. BW=15 kHz. Tone Number=12. Tone Offset=0. MSC/TBS=5.

Low Channel:



High Channel:



LTE Cat NB1 Band 66:

LTE Cat NB1 Band 66. Pi/2-BPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=0.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	60.51000	59.67000	59.04000
-26 dBc Bandwidth (kHz)	41.32760	41.34220	41.03800
Measurement uncertainty (kHz)	<±0.35		

LTE Cat NB1 Band 66. Pi/4-QPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=3.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	65.49000	64.53000	63.39000
-26 dBc Bandwidth (kHz)	41.91200	41.85220	41.73120
Measurement uncertainty (kHz)	<±0.35		

LTE Cat NB1 Band 66. Pi/2-BPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=0.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 66. Pi/4-QPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=3.


Low Channel:



Middle Channel:



High Channel:



LTE Cat NB1 Band 66. Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=0.

	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	126.09000	125.37000	124.95000
-26 dBc Bandwidth (kHz)	128.30300	127.71850	126.83340
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 66. Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=3.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	125.28000	125.82000	123.39000
-26 dBc Bandwidth (kHz)	131.87300	143.04400	129.83300
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 66. QPSK. BW=15 kHz. Tone Number=12. Tone Offset=0. MSC/TBS=5.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	188.80000	187.90000	187.70000
-26 dBc Bandwidth (kHz)	308.18270	306.42800	307.99500
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 66. Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=0.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 66. Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=3.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 66. QPSK. BW=15 kHz. Tone Number=12. Tone Offset=0. MSC/TBS=5.


Low Channel:



Middle Channel:



High Channel:



LTE Cat NB1 Band 85:

LTE Cat NB1 Band 85. Pi/2-BPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=0.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	57.87000	58.02000	59.07000
-26 dBc Bandwidth (kHz)	41.28780	41.21040	41.32410
Measurement uncertainty (kHz)	<±0.35		

LTE Cat NB1 Band 85. Pi/4-QPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=3.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	62.67000	62.52000	62.79000
-26 dBc Bandwidth (kHz)	41.73780	41.87040	41.77400
Measurement uncertainty (kHz)	<±0.35		

LTE Cat NB1 Band 85. Pi/2-BPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=0.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 85. Pi/4-QPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=23. MSC/TBS=3.


Low Channel:



Middle Channel:



High Channel:



LTE Cat NB1 Band 85. Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=0.

	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	125.73000	125.10000	124.83000
-26 dBc Bandwidth (kHz)	130.85760	128.48200	123.33510
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 85. Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=3.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	123.81000	123.75000	125.31000
-26 dBc Bandwidth (kHz)	141.36250	143.02560	143.51100
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 85. QPSK. BW=15 kHz. Tone Number=12. Tone Offset=0. MSC/TBS=5.


	Low Channel	Middle Channel	High Channel
99% Occupied Bandwidth (kHz)	188.40000	188.00000	189.70000
-26 dBc Bandwidth (kHz)	309.26110	304.04950	277.51620
Measurement uncertainty (kHz)	<±0.58		

LTE Cat NB1 Band 85. Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=0.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 85. Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=5. MSC/TBS=3.


Low Channel:



Middle Channel:




High Channel:




LTE Cat NB1 Band 85. QPSK. BW=15 kHz. Tone Number=12. Tone Offset=0. MSC/TBS=5.


Low Channel:



Middle Channel:



High Channel:



CF 715.8 MHz10000 ptsSpan 500.0 kHz

Ready

Spurious emissions at antenna terminals

Limits

1. LTE Cat NB1 Band 8. FCC §27.1509 (a).

FCC §27.1509 (a):

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) in watts by at least the following amounts:

- (a) For 900 MHz broadband operations in 897.5–900.5 MHz band by at least $43 + 10 \log (P)$ dB.

2. LTE Cat NB1 Band 13.

FCC §27.53 (c):

On any frequency outside the 776-788 MHz band. the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. Compliance is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

On all frequencies between 763-775 MHz and 793-805 MHz. by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment. for mobile and portable stations. Compliance is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

RSS-130 4.7.1 and 4.7.2:

4.7.1 General unwanted emissions limits:

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

4.7.2 Additional unwanted emissions limits:

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

- a. the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
 - i. $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and
 - ii. $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment
- b. the e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

3. LTE Cat NB1 Band 66.

FCC §27.53 (h). RSS-139 5.6:

Unwanted emissions shall be measured in terms of average values.

For all equipment, the TRP or total conducted power (sum of conducted power across all antenna connectors) of the unwanted emissions outside the frequency block or frequency block group shall not exceed the limits shown in table 6.

Table 6: Unwanted emission limits	
Offset from the edge of the frequency block or frequency block group	Unwanted emission limits
1 MHz	-13 dBm/(1% of OB*)
>1 MHz	-13 dBm/MHz

*OB is the occupied bandwidth.

In addition to complying with the above limits, equipment operating in the band 2180-2200 MHz may require additional filtering (see SRSP-519).

4. LTE Cat NB1 Band 85.

FCC §27.53 (g):

For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

RSS-130. Clause 4.7.1:

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB.

At P_o transmitting power, the specified minimum attenuation becomes $43+10 \log (P_o)$, and the level in dBm relative to P_o becomes:

$$P_o \text{ (dBm)} - [43 + 10 \log (P_o \text{ in mW}) - 30] = -13 \text{ dBm}$$

At P_o transmitting power, the specified minimum attenuation becomes $65+10 \log (P_o)$, and the level in dBm relative to P_o becomes:


$$P_o \text{ (dBm)} - [65 + 10 \log (P_o \text{ in mW}) - 30] = -35 \text{ dBm}$$

Method

The EUT RF output connector was connected to a spectrum analyser and to the Universal Radio Communication tester R&S CMW500 (selecting maximum transmission power of the EUT and different modes of modulation) using a 50-Ohm attenuator and a power divider.

The reading of the spectrum analyser is corrected with the attenuation loss of connection between output terminal of EUT and input of the spectrum analyser.

Test Setup



Results

The next results are for the worst-case configuration for each LTE Cat NB1 Band.

LTE Cat NB1 Band 8:

A preliminary scan determined the worst-case:

Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=11. MSC/TBS=3.

Frequency range 9 KHz - 10 GHz:

- Low Channel: No spurious frequencies at less than 20 dB below the limit.
- High Channel: No spurious frequencies at less than 20 dB below the limit.

LTE Cat NB1 Band 13:

A preliminary scan determined the worst-case:

Pi/4-QPSK. BW=3.75 kHz. Tone Number=1. Tone Offset=0. MSC/TBS=3.

Frequency range 9 KHz - 8 GHz:

- Low Channel: Spurious frequencies at less than 20 dB below the limit:

Frequency (MHz)	Emission limitations conducted (dBm)
774.5362	-43.8
773.0398	-51.4
769.3846	-54.53

- High Channel: Spurious frequencies at less than 20 dB below the limit:

Frequency (MHz)	Emission limitations conducted (dBm)
794.4346	-54.5

LTE Cat NB1 Band 66:

A preliminary scan determined the worst-case:

Pi/2-BPSK. BW=15 kHz. Tone Number=1. Tone Offset=0. MSC/TBS=0.

Frequency range 9 KHz - 18 GHz:

- Low Channel: No spurious signals found.
- Middle Channel: No spurious signals found.
- High Channel: No spurious signals found.

LTE Cat NB1 Band 85:

A preliminary scan determined the worst-case:

Pi/4-QPSK. BW=15 kHz. Tone Number=1. Tone Offset=0. MSC/TBS=3.

Frequency range 9 KHz - 8 GHz:

- Low Channel: No spurious frequencies at less than 20 dB below the limit.
- Middle Channel: No spurious frequencies at less than 20 dB below the limit.
- High Channel: No spurious frequencies at less than 20 dB below the limit.

Measurement uncertainty (dB): $\leq \pm 2.76$

Verdict: PASS