

RF Exposure Evaluation Report

APPLICANT : Barking Labs Corp.
EQUIPMENT : Fi Ultra
BRAND NAME : Fi
MODEL NAME : U1
FCC ID : 2ARXN-U1
STANDARD : 47 CFR Part 2.1093

The product evaluation date was started from May. 06, 2026 and completed on May. 06, 2026. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part2.1093, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE EVALUATION	7
5. SIMULTANEOUS TRANSMISSION ANALYSIS	7



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA630915	Rev. 01	Initial issue of report.	May 07, 2026



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Barking Labs Corp.
Address	419 Lafayette St., Floor 2, New York, NY 10003

Manufacturer	
Company Name	Barking Labs Corp.
Address	419 Lafayette St., Floor 2, New York, NY 10003

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Fi Ultra
Brand Name	Fi
Model Name	U1
FCC ID	2ARXN-U1
Wireless Technology and Frequency Range	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 66: 1710 MHz ~ 1780 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	LTE: QPSK / 16QAM WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth LE
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

**3. Maximum RF average output tune up power among production units****<LTE >**

Mode		Maximum Average Power (dBm)
LTE	Band 2	25.00
	Band 4	25.00
	Band 12	25.00
	Band 25	25.00
	Band 66	25.00

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	14.50
	802.11g	16.00
	802.11n-HT20	16.00

<Bluetooth>

Mode		Maximum Average Power (dBm)
Bluetooth LE		11.00



4. RF Exposure Evaluation

General Note:

- Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Wireless Interface	LTE					WiFi	BLE
	B2	B4	B12	B25	B66		
TX Frequency(MHz)	1910.00	1755.00	716.00	1915.00	1780.00	2462.00	2480.00
Maximum Conducted Power (dBm)	25.00	25.00	25.00	25.00	25.00	16.00	11.00
Maximum Power(mW)	316.23	316.23	316.23	316.23	316.23	39.81	12.59
Most Conservative Tx Duty Cycle (%)	1.00	1.00	1.00	1.00	1.00	1.10	0.21
Duty Factor Adjusted Maximum Output Power (mW)	3.16	3.16	3.16	3.16	3.16	0.44	0.03
Separation Distance (mm)	<5.00	<5.00	<5.00	<5.00	<5.00	<5.00	<5.00
Exclusion Threshold	0.87	0.84	0.53	0.87	0.84	0.14	0.01
SAR Testing Required?	NO	NO	NO	NO	NO	NO	NO
Estimated SAR	0.116	0.112	0.071	0.117	0.112	0.018	0.001

5. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Fi Ultra
1.	WWAN + Bluetooth	Yes

Note:

- According to the EUT characteristic, WLAN 2.4GHz and WWAN/Bluetooth can not transmit simultaneously.
- According to the EUT characteristic, WWAN and Bluetooth can transmit simultaneously.

1	2	1+2
WWAN	Bluetooth	Summed 1g SAR (W/kg)
Estimated 1g SAR (W/kg)	Estimated 1g SAR (W/kg)	
0.117	0.001	0.118

Conclusion:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion and and complied with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for 1g SAR and 4.0 W/kg for extremity SAR) specified in FCC 47 CFR part 2 (2.1093).

-----THE END-----