FCC TEST REPORT

Client Name	:	iConnectZone Inc d/b/a SAYA
Address	:	525 S Hewitt Stree Los Angeles CA 90013
Product Name	:	Saya Ultrasonic Water Meter
Date	:	Jun. 14, 2019

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information....5
1.1. Client Information....5
1.2. Description of Device (EUT)....5
1.3. Auxiliary Equipment Used During Test....6
1.4. Description of Test Modes....6
1.5. List of channels....7
1.6. Description Of Test Setup....8
1.7. Test Equipment List....9
1.8. Measurement Uncertainty....10
1.9. Description of Test Facility....10
2. Summary of Test Results....11
3. Conducted Emission Test....12
3.1. Test Standard and Limit....12
3.2. Test Setup....12
3.3. Test Procedure....12
3.4. Test Data....12
4. Radiation Spurious Emission and Band Edge....18
4.1. Test Standard and Limit....18
4.2. Test Setup....18
4.3. Test Procedure....19
4.4. Test Data....20
5. Maximum Peak Output Power Test....27
5.1. Test Standard and Limit....27
5.2. Test Setup....27
5.3. Test Procedure....27
5.4. Test Data....27
6. 6DB Occupy Bandwidth Test....30
6.1. Test Standard and Limit....30
6.2. Test Setup....30
6.3. Test Procedure....30
6.4. Test Data....30
7. Power Spectral Density Test....33
7.1. Test Standard and Limit....33
7.2. Test Setup....33
7.3. Test Procedure....33
7.4. Test Data....33
8. 100kHz Bandwidth of Frequency Band Edge Requirement....36
8.1. Test Standard and Limit....36
8.2. Test Setup....36

8.3. Test Procedure....36
8.4. Test Data....36
9. Antenna Requirement....40
9.1. Test Standard and Requirement....40
9.2. Antenna Connected Construction....40
APPENDIX I -- TEST SETUP PHOTOGRAPH....41
APPENDIX II -- EXTERNAL PHOTOGRAPH....43
APPENDIX III -- INTERNAL PHOTOGRAPH....47

TEST REPORT

Applicant	:	iConnectZone Inc d/b/a SAYA
Manufacturer	:	HANGZHOU ZHONGPEI ELECTRONICS CO.,LTD
Product Name	:	Saya Ultrasonic Water Meter
Model No.	:	SAYA-WMILSA0100, 20180000031
Trade Mark	:	Saya
Rating(s)	:	Input: DC 5V, 2A(Via adapter Input: AC 100~240V, 50/60Hz, 250mA; with DC 3.6V, 8500 mAh Battery inside)

Test Standard(s)	:	**FCC Part15 Subpart C 2018, Section 15.247**
Test Method(s)	:	**ANSI C63.10: 2013, KDB558074 D01 DTS Meas Guidance v05**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt	Feb. 26, 2019
Date of Test	Feb. 26~Apr. 30, 2019
Prepared By	(Engineer / Oliay Yang)
Reviewer	(Supervisor / Snowy Meng)
Approved & Authorized Signer	(Manager / Sally Zhang)

Anbotek (SZ) Compliance Laboratory Limited Anbotek Product Safety * Approved *

Address: 1/F, Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86)755-26066440 Fax:(86)755-26014772 Email:service@anbotek.com
Hotline 400-003-0500 www.anbotek.com

1. General Information

1.1. Client Information

Applicant	:	iConnectZone Inc d/b/a SAYA
Address	:	525 S Hewitt Stree Los Angeles CA 90013
Manufacturer	:	HANGZHOU ZHONGPEI ELECTRONICS CO.,LTD
Address	:	Floor 4, Building 4, No.2630, Yuhangtang Road, Cangqian, Yuhang, Hangzhou, Zhejiang,311121 China
Factory	:	HANGZHOU ZHONGPEI ELECTRONICS CO.,LTD
Address	:	Floor 4, Building 4, No.2630, Yuhangtang Road, Cangqian, Yuhang, Hangzhou, Zhejiang,311121 China

1.2. Description of Device (EUT)

Product Name	:	Saya Ultrasonic Water Meter	
Model No.	:	SAYA-WMILSA0100, 20180000031 (Note: All samples are the same except the model name, so we prepare "SAYA-WMILSA0100" for test only.)	
Trade Mark	:	Saya	
Test Power Supply	:	AC 240V, 60Hz for adapter/ AC 120V, 60Hz for adapter/ DC 3.6V Battery inside	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	910MHz~920MHz
		Number of Channel:	11 Channels
		Modulation Type:	LoRa
		Antenna Type:	PIFA Antenna
		Antenna Gain(Peak):	1.5 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	MODEL: S008CU0500200 Input: 100-240V~ 50/60Hz, 250mA Output: DC 5V, 2000mA

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	
Mode 1	CH01	TX Only
Mode 2	CH06	
Mode 3	CH11	

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	910	04	913	07	916	10	919
02	911	05	914	08	917	11	920
03	912	06	915	09	918		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 26, 2018	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 05, 2018	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 05, 2018	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 05, 2018	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 05, 2018	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 19, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 20, 2018	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Nov. 20, 2018	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Nov. 05, 2018	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 05, 2018	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 05, 2018	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 05, 2018	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 05, 2018	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 05, 2018	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 05, 2018	1 Year
19.	DC Power Supply	LW	TPR-6420D	374470	Oct. 31, 2018	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Nov. 01, 2018	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages.

During the test, pre-scan all the modes, and found Low channel(TX+Charging Mode) which is the worst case, only the worst case is recorded in the report.

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 23.3℃ Hum.: 67%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.4100	22.44	19.94	42.38	57.65	-15.27	QP	
2	0.4260	3.48	19.95	23.43	47.33	-23.90	AVG	
3	0.7860	19.09	20.06	39.15	56.00	-16.85	QP	
4	0.7860	1.36	20.06	21.42	46.00	-24.58	AVG	
5	1.4900	17.81	20.13	37.94	56.00	-18.06	QP	
6	1.4900	0.01	20.13	20.14	46.00	-25.86	AVG	
7	1.8140	14.71	20.14	34.85	56.00	-21.15	QP	
8	1.8260	-0.98	20.14	19.16	46.00	-26.84	AVG	
9	2.1140	15.07	20.14	35.21	56.00	-20.79	QP	
10	2.3660	-1.26	20.15	18.89	46.00	-27.11	AVG	
11	3.3940	-1.77	20.17	18.40	46.00	-27.60	AVG	
12	3.5020	14.49	20.17	34.66	56.00	-21.34	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 23.3℃ Hum.: 67%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2700	3.04	19.89	22.93	51.12	-28.19	AVG	
2	0.3980	19.14	19.93	39.07	57.89	-18.82	QP	
3	0.6380	-1.36	20.02	18.66	46.00	-27.34	AVG	
4	0.8900	18.54	20.09	38.63	56.00	-17.37	QP	
5	0.9580	-2.31	20.11	17.80	46.00	-28.20	AVG	
6	1.2059	16.12	20.12	36.24	56.00	-19.76	QP	
7	1.4580	-1.74	20.13	18.39	46.00	-27.61	AVG	
8	1.4780	16.70	20.13	36.83	56.00	-19.17	QP	
9	1.8460	14.31	20.14	34.45	56.00	-21.55	QP	
10	1.8860	-1.85	20.14	18.29	46.00	-27.71	AVG	
11	2.4060	-2.81	20.15	17.34	46.00	-28.66	AVG	
12	2.5059	14.36	20.15	34.51	56.00	-21.49	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 23.3℃ Hum.: 67%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.3940	18.55	19.93	38.48	57.98	-19.50	QP	
2	0.3940	3.37	19.93	23.30	47.98	-24.68	AVG	
3	0.5820	3.12	20.00	23.12	46.00	-22.88	AVG	
4	0.5899	17.99	20.01	38.00	56.00	-18.00	QP	
5	1.1460	13.40	20.12	33.52	56.00	-22.48	QP	
6	1.4900	13.19	20.13	33.32	56.00	-22.68	QP	
7	1.5740	-0.50	20.13	19.63	46.00	-26.37	AVG	
8	1.8740	-0.53	20.14	19.61	46.00	-26.39	AVG	
9	1.8900	12.42	20.14	32.56	56.00	-23.44	QP	
10	2.2820	-1.64	20.15	18.51	46.00	-27.49	AVG	
11	3.1780	12.45	20.16	32.61	56.00	-23.39	QP	
12	3.7380	-2.18	20.17	17.99	46.00	-28.01	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 23.3℃ Hum.: 67%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.2700	2.57	19.89	22.46	51.12	-28.66	AVG	
2	0.3899	17.23	19.93	37.16	58.06	-20.90	QP	
3	0.4980	17.38	19.98	37.36	56.03	-18.67	QP	
4	0.5899	0.35	20.01	20.36	46.00	-25.64	AVG	
5	0.6140	18.44	20.01	38.45	56.00	-17.55	QP	
6	1.0740	11.04	20.12	31.16	56.00	-24.84	QP	
7	1.0740	-2.27	20.12	17.85	46.00	-28.15	AVG	
8	1.5380	12.85	20.13	32.98	56.00	-23.02	QP	
9	1.5780	-2.50	20.13	17.63	46.00	-28.37	AVG	
10	1.9500	-2.49	20.14	17.65	46.00	-28.35	AVG	
11	1.9940	11.59	20.14	31.73	56.00	-24.27	QP	
12	2.3179	-3.27	20.15	16.88	46.00	-29.12	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, pre-scan all the modes, and found the Middle channel(TX Only) which is the worst case, only the worst case is recorded in the report.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Results (30~1000MHz)

Job No.:	SZAWW190226001-01	Temp.(℃)/Hum.(%RH):	21.5℃/54%RH
Standard:	FCC PART 15C	Power Source:	AC 120V, 60Hz for adapter
Test Mode:	Mode 2	Polarization:	Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	71.8320	56.02	-22.11	33.91	40.00	-6.09	QP	300	0	
2	143.8295	55.55	-22.43	33.12	43.50	-10.38	QP	300	77	
3	389.3549	43.29	-13.19	30.10	46.00	-15.90	QP	300	141	
4	517.2480	46.15	-11.00	35.15	46.00	-10.85	QP	300	212	
5	878.3214	35.36	-5.13	30.23	46.00	-15.77	QP	300	360	
6	916.0687	86.28	-4.52	81.76	94.00	-12.24	QP	300	184	

Test Results (30~1000MHz)

Job No.:	SZAWW190226001-01	Temp.(℃)/Hum.(%RH):	21.5℃/54%RH
Standard:	FCC PART 15C	Power Source:	AC 120V, 60Hz for adapter
Test Mode:	Mode 2	Polarization:	Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	47.9940	47.33	-15.87	31.46	40.00	-8.54	QP	300	0	
2	582.7425	48.45	-9.53	38.92	46.00	-7.08	QP	300	64	
3	750.1083	49.96	-6.99	42.97	46.00	-3.03	QP	300	212	
4	890.7278	40.91	-3.93	36.98	46.00	-9.02	QP	300	299	
5	916.0687	84.93	-3.52	81.41	94.00	-12.59	QP	300	266	
6	938.8326	40.31	-3.15	37.16	46.00	-8.84	QP	300	360	

Test Results (30~1000MHz)

Job No.:	SZAWW190226001-01	Temp.(℃)/Hum.(%RH):	21.5℃/54%RH
Standard:	FCC PART 15C	Power Source:	AC 240V, 60Hz for adapter
Test Mode:	Mode 2	Polarization:	Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	71.8319	55.25	-22.11	33.14	40.00	-6.86	QP	300	0	
2	95.7622	54.12	-22.15	31.97	43.50	-11.53	QP	300	54	
3	143.8295	59.37	-22.43	36.94	43.50	-6.56	QP	300	121	
4	155.9101	55.43	-22.06	33.37	43.50	-10.13	QP	300	227	
5	289.0021	54.45	-18.87	35.58	46.00	-10.42	QP	300	360	
6	916.0687	87.64	-4.52	83.12	94.00	-10.86	QP	300	283	

Test Results (30~1000MHz)

Job No.:	SZAWW190226001-01	Temp.(℃)/Hum.(%RH):	21.5℃/54%RH
Standard:	FCC PART 15C	Power Source:	AC 240V, 60Hz for adapter
Test Mode:	Mode 2	Polarization:	Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	31.2893	50.83	-17.18	33.65	40.00	-6.35	QP	300	0	
2	47.9940	48.52	-15.87	32.65	40.00	-7.35	QP	300	47	
3	144.3348	56.25	-18.43	37.82	43.50	-5.68	QP	300	121	
4	154.8204	53.54	-18.11	35.43	43.50	-8.07	QP	300	220	
5	750.1083	45.08	-6.99	38.09	46.00	-7.91	QP	300	360	
6	916.0687	85.27	-3.52	81.75	94.00	-12.25	QP	300	135	

Test Results (1GHz-25GHz)

Test Mode: CH01					Test channel: Lowest				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1820.00	H	53.41	7.39	28.73	26.31	63.22	74	-10.78	PK
1820.00	H	39.32	7.39	28.73	26.31	49.13	54	-4.87	AV
2730.00	H	51.38	8.10	29.71	27.01	62.18	74	-11.82	PK
2730.00	H	37.15	8.10	29.71	27.01	47.95	54	-6.05	AV
3640.00	H	--	--	--	--	--	--	--	PK
3640.00	H	--	--	--	--	--	--	--	AV
1810.00	V	49.53	7.39	28.73	26.31	59.34	74	-14.66	PK
1810.00	V	33.77	7.39	28.73	26.31	43.58	54	-10.42	AV
2715.00	V	50.64	8.10	29.71	27.01	61.44	74	-12.56	PK
2715.00	V	37.49	8.10	29.71	27.01	48.29	54	-5.71	AV
3620.00	V	--	--	--	--	--	--	--	PK
3620.00	V	--	--	--	--	--	--	--	AV

Test Mode: CH06					Test channel: Middle				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1830.00	H	49.11	7.41	28.72	26.31	58.93	74	-15.07	PK
1830.00	H	36.46	7.41	28.72	26.31	46.28	54	-7.72	AV
2745.00	H	51.52	8.11	29.71	27.01	62.33	74	-11.67	PK
2745.00	H	34.14	8.11	29.71	27.01	44.95	54	-9.05	AV
3660.00	H	--	--	--	--	--	--	--	PK
3660.00	H	--	--	--	--	--	--	--	AV
1830.00	V	52.51	7.41	28.72	26.31	62.33	74	-11.67	PK
1830.00	V	37.8	7.41	28.72	26.31	47.62	54	-6.38	AV
2745.00	V	47.41	8.11	29.71	27.01	58.22	74	-15.78	PK
2745.00	V	36.1	8.11	29.71	27.01	46.91	54	-7.09	AV
3660.00	V	--	--	--	--	--	--	--	PK
3660.00	V	--	--	--	--	--	--	--	AV

Test Mode: CH11					Test channel: Highest				
Frequency (MHz)	Antenna Pol.	Reading (dBuV/m)	Cable Loss (dB)	Ant Factor (dB)	Amplifier (dB)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Det. Mode
1840.00	H	51.58	7.43	28.69	26.31	61.39	74	-12.61	PK
1840.00	H	35.55	7.43	28.69	26.31	45.36	54	-8.64	AV
2760.00	H	47.65	8.15	29.84	27.01	58.63	74	-15.37	PK
2760.00	H	33.64	8.15	29.84	27.01	44.62	54	-9.38	AV
3680.00	H	--	--	--	--	--	--	--	PK
3680.00	H	--	--	--	--	--	--	--	AV
1850.00	V	48.41	7.43	28.69	26.31	58.22	74	-15.78	PK
1850.00	V	36.54	7.43	28.69	26.31	46.35	54	-7.65	AV
2775.00	V	46.34	8.15	29.84	27.01	57.32	74	-16.68	PK
2775.00	V	34.95	8.15	29.84	27.01	45.93	54	-8.07	AV
3700.00	V	--	--	--	--	--	--	--	PK
3700.00	V	--	--	--	--	--	--	--	AV

Remark:

1. Level = Reading + Cable Loss+Ant Factor-Amplifier
2. " -- " Mark indicated Background Noise Level

Radiated Band Edge:

Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Det.
902.00	40.69	22.45	4.48	31.33	36.29	46.00	-9.71	H	QP
928.00	38.38	22.59	4.54	31.35	34.16	46.00	-11.84	H	QP
902.00	43.97	22.45	4.48	31.33	39.57	46.00	-6.43	V	QP
928.00	40.14	22.59	4.54	31.35	35.92	46.00	-10.08	V	QP

Remark:

Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	30dBm

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW ≥DTS bandwidth.
2. Set the VBW≥3*RBW.
3. Set the span≥ 3*RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Test Item	:	Max. peak output power	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V, 60Hz for adapter	Temperature	:	22.9℃
Test Result	:	PASS	Humidity	:	56%RH

Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
910	13.256	30	PASS
915	13.297	30	PASS
920	**13.670**	30	PASS



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Swept SA
Marker 1 920.208000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
11:56:17 PM Mar 28, 2019
Mkr1 920.208 MHz
13.670 dBm
10 dB/div
Log
Ref 20.00 dBm
Center 920.000 MHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Span 8.000 MHz
Sweep 1.000 ms (1001 pts)

CH: High

6. 6DB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 100kHz, VBW≥3*RBW =300kHz,
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and –6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Test Item	:	6dB Bandwidth	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V, 60Hz for adapter	Temperature	:	22.9℃
Test Result	:	PASS	Humidity	:	56%RH

Channel	Frequency(MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	910	765.0	>500	PASS
Middle	915	723.4		PASS
High	920	715.2		PASS



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Occupied BW
Center Freq 920.000000 MHz
Center Freq: 920.000000 MHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 30 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
11:51:33 PM Mar 28, 2019
10 dB/div
Ref 20.00 dBm
Log
Center 920 MHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3 MHz
Sweep 1 ms
Occupied Bandwidth
755.71 kHz
Total Power 21.6 dBm
Transmit Freq Error -35.404 kHz
OBW Power 99.00 %
x dB Bandwidth 715.2 kHz
x dB -6.00 dB
MSG
STATUS

CH: High

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Test Item	:	Power Spectral Density	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V, 60Hz for adapter	Temperature	:	22.9℃
Test Result	:	PASS	Humidity	:	56%RH

Channel	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	910	7.404	8.00	PASS
Middle	915	7.081	8.00	PASS
High	920	7.745	8.00	PASS



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Swept SA
Marker 1 920.242228000 MHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
11:57:24 PM Mar 28, 2019
Mkr1 920.242 2 MHz
7.745 dBm
10 dB/div
Log
Ref 20.00 dBm
Center 920.0000 MHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 1.148 MHz
Sweep 121.1 ms (1001 pts)

CH: High

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Test Item	:	Band edge	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V, 60Hz for adapter	Temperature	:	22.9℃
Test Result	:	PASS	Humidity	:	56%RH

Frequency Band (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Results
902	75.527	>20	PASS
928	75.504	>20	PASS



CH: Low



CH: High

Conducted Emission Method



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 12/100
11:55:45 PM Mar 28, 2019
Mkr1 920 MHz
13.649 dBm
10 dB/div
Ref 20.00 dBm
Log
-6.36 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)
1 N 1 f 920 MHz 13.649 dBm
2 N 1 f 1.828 GHz -42.008 dBm

CH: High

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna

9.2. Antenna Connected Construction

The antenna is a PIFA Antenna which permanently attached, and the best case gain of the antenna is 1.5 dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement



Photo of Radiation Emission Test





APPENDIX II -- EXTERNAL PHOTOGRAPH





ECTACO®
SWITCHING POWER SUPPLY
MODEL:S008CU0500200
INPUT:100-240V~
50/60Hz 250mA
OUTPUT: 5.0V ⎓ 2000mA
ROHS
c UL us
LISTED 20HK E178074
EFFICIENCY LEVEL: IV
OFFICE EQUIPMENT USE ONLY AND
INFORMATION TECHNOLOGY ONLY
MADE IN CHINA
GS-JL

APPENDIX III -- INTERNAL PHOTOGRAPH









Address: 1/F, Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86)755-26066440 Fax:(86)755-26014772 Email:service@anbotek.com
Hotline 400-003-0500
www.anbotek.com




ANT



---------- End of Report ----------