

TEST REPORT

On behalf of

Shanghai Teraoka Electronic Co., Ltd.

Product Name: SMART CARD TERMINAL

Model No.: WB-20

FCC ID: 2ARYWWB-20

Prepared For: Shanghai Teraoka Electronic Co., Ltd.
Tinglin Industry Development Zone, Jinshan District,
Shanghai, China

Prepared By: Audix Technology (Shanghai) Co., Ltd.
3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500



File No. : C1D2011005
Report No. : ACI-F21123
Date of Test : 2021.01.17
Date of Report : 2021.05.25

The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS	4
1.1 Description of Standards and Results.....	4
2 GENERAL INFORMATION.....	5
2.1 Description of Equipment Under Test.....	5
2.2 Test Information	6
2.3 Sample Description	6
2.4 Supported equipment.....	6
2.5 Description of Test Facility	6
3 DFS MEASUREMENT.....	7
3.1 Test Equipment.....	7
3.2 Block Diagram of Test Setup	7
3.3 Specification Limits	7
3.4 Operating Condition of EUT	9
3.5 Test Procedure	9
3.6 Threshold Level.....	9
3.7 Test Results	10
4 DEVIATION TO TEST SPECIFICATIONS.....	14
5 MEASUREMENT UNCERTAINTY LIST	15

TEST REPORT

Applicant : Shanghai Teraoka Electronic Co., Ltd.
EUT Description : SMART CARD TERMINAL
(A) Model No. : Refer to Sec.2.1
(B) Power Supply : DC5V
(C) Test Voltage : DC5V (Via Adaptor)

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART E
AND ANSI C63.10-2013*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart E limits.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested is technically compliance with the FCC limits.

This report applies to above tested Sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.


The test results for EUT's BLE/ WIFI (2.4G)/BT / WIFI (5G) function are contained in No.ACI-F21108, ACI-F21109, ACI-F21121, ACI-F21122 report.

Date of Test : 2021.01.17 Date of Report : 2021.06.04

Producer :


JAREY LU / Supervisor

Reviewer :


BYRON WU / Deputy Assistant Manager

 For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : 
Authorized Signature(s) BYRON KWO/Assistant General Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item		Test Standard	Results	Meets Limit
EMISSION				
Transmit Power Control (TPC)		FCC RULES AND REGULATIONS PART 15 SUBPART E AND ANSI C63.10:2013	N/A	15.247(h)(1)
DFS	Non-Occupancy Period	FCC RULES AND REGULATIONS PART 15 SUBPART E AND ANSI C63.10:2013	N/A	15.247(h)(2)
	DFS Detection Threshold		N/A	
	Channel Availability Check Time		N/A	
	U-NII Detection Bandwidth		N/A	
	DFS Detection Threshold		N/A	
	Channel Closing Transmission Time		Pass	
	Channel Move Time		Pass	
	U-NII Detection Bandwidth		N/A	
N/A is an abbreviation for Not Applicable.				

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : SMART CARD TERMINAL

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model Number : WB-20

Radio Tech : Bluetooth 4.2;
IEEE 802.11 a/b/g/n/ac.

Channel Freq. : BLE: 2402MHz-2480MHz;
BT: 2402MHz-2480MHz
IEEE 802.11a:
5180MHz—5240MHz; 5260MHz—5320MHz
5500MHz—5700MHz; 5745MHz—5825MHz
IEEE 802.11ac VHT20:
5180MHz—5240MHz; 5260MHz—5320MHz
5500MHz—5700MHz; 5745MHz—5825MHz
IEEE 802.11ac VHT40:
5190MHz—5230MHz; 5270MHz—5310MHz
5510MHz—5670MHz; 5755MHz—5795MHz
IEEE 802.11ac VHT80:
5210MHz, 5290MHz; 5530MHz—5610MHz; 5775MHz
IEEE 802.11b: 2412MHz—2462MHz
IEEE 802.11g: 2412MHz—2462MHz
IEEE802.11nHT20:
2412MHz—2462MHz;
5180MHz—5240MHz; 5260MHz—5320MHz
5500MHz—5700MHz; 5745MHz—5825MHz
IEEE802.11nHT40:
5190MHz—5230MHz; 5270MHz—5310MHz
5510MHz—5670MHz; 5755MHz—5795MHz

Modulation : BLE: GFSK;
BT: FHSS, GFSK, DPSK, DQPSK;
802.11b: DSSS (CCK, DQPSK, DBPSK);
802.11a/g/n: OFDM (64QAM, 16QAM, QPSK, BPSK);
802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK).

DFS Info. : Operational Mode:
☐ Master
☒ Client without Radar Detection
☐ Client with Radar Detection

TPC Info. : TPC Function:
☐ With TPC
☒ Without TPC

Antenna Info. : Antenna Type: SMA Antenna
Antenna Gain: 5 dBi
The Antenna was an antenna that uses a unique coupling to the intentional radiator that is comply with 15.203 requirement.

Applicant : Shanghai Teraoka Electronic Co., Ltd.
Tinglin Industry Development Zone, Jinshan District, Shanghai, China

Manufacturer : same as Applicant

Factory : same as Applicant

2.2 Test Information

The EUT was operation at client mode, the modulation and channel was selected by a Wi-Fi Router.

Modulation	Test Channel	Frequency (MHz)
802.11ac-VHT80	58	5290
	106	5530

2.3 Sample Description

Test Item	Model Number	Sample Number	Date of receipted
DFS	WB-20	E20111479-04/04	2020.11.02

2.4 Supported equipment

Brand : HUAWEI
Product Name: : Adaptor
Model Name : HW-050200C01

2.5 Description of Test Facility

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F and 4F, 34Bldg, 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China.

Accredited by NVLAP, Lab Code : 200371-0

FCC Designation Number : CN5027

Test Firm Registration Number : 954668


3 DFS MEASUREMENT

3.1 Test Equipment

The following test equipment was used during the Emission Bandwidth measurement:

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A	MY52221182	2020.09.16	1 Year
2.	MXG Vector Signal Generator	KEYSIGHT	N5182B	MY53051937	2020.03.08	1 Year
3.	DFS Radar Profiles	KEYSIGHT	N7607B Signal Studio	V3.2.0.0	--	--
4.	AX6000 Dual-band Wi-Fi Router	ASUS	RT-AX88U		--	--

3.2 Block Diagram of Test Setup



3.3 Specification Limits

§15.407(h)(2)(iii):

Channel Move Time. After a radar's presence is detected, all transmissions shall cease on the operating channel within 10 seconds. Transmissions during this period shall consist of normal traffic for a maximum of 200 ms after detection of the radar signal. In addition, intermittent management and control signals can be sent during the remaining time to facilitate vacating the operating channel.

KDB 905462 D02:

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
$EIRP \geq 200$ milliwatt	-64 dBm
$EIRP < 200$ milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
$EIRP < 200$ milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.
Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.
Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

3.4 Operating Condition of EUT

The EUT operate as client, connect to the Wi-Fi Router.

3.5 Test Procedure

The conducted setup shown on Section 3.2 was used to measure the Channel Closing Transmission Time and Channel Move Time.

For a Client Device without DFS, the Channel Move Time and Channel Closing Transmission Time requirements will be verified with one Short Pulse Radar Type defined in Table 5 of KDB 905462 D02.

The Client Device (EUT) is associated with the Master Device (Wi-Fi Router). The Data Traffic is streamed from the Master Device to the Client Device. Radar waveforms generated with the Vector Signal Generator are injected into the Master Device on the operating channel.

Observe the transmissions of the EUT at the end of the radar burst on the operating channel for duration greater than 10 seconds. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.

3.6 Threshold Level

Threshold Level = -62dBm + Antenna Gain = -62dBm + 5.0dBi = -57dBm.

3.7 Test Results



PASSED.

All the test results are attached in next pages.

(Test Date: 2021.01.17 Temperature: 23°C Humidity: 51 %)


Modulation	Channel	Frequency (MHz)	Channel Move Time (s)	Limit (s)
802.11ac-VH T80	58	5290	0.0056254	10
	106	5530	0.9028806	10

Modulation	Channel	Frequency (MHz)	Channel Closing Transmission Time (ms)	Limit (ms)
802.11ac-VH T80	58	5290	0.0018751	200
	106	5530	0.0164075	200


Threshold Level:**802.11ac-VHT80 CH5290MHz****802.11ac-VHT80 CH5530MHz**

Data Traffic Plot:

802.11ac-VHT80 CH5290MHz




802.11ac-VHT80 CH5530MHz




Channel Move Time & Channel Closing Transmission Time:

802.11ac-VHT80 CH5290MHz



802.11ac-VHT80 CH5530MHz



4 DEVIATION TO TEST SPECIFICATIONS

None.

5 MEASUREMENT UNCERTAINTY LIST

The measurement uncertainty was estimated for test on the EUT according to CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage of K=2.

The uncertainties value is not used in determining the PASS/FAIL results.

Test Items/Facilities	Frequency/Equipment/Unit	Uncertainty
Conducted Emission No.1 Shielded Room	9kHz~150kHz	±3.2 dB
	150kHz~30MHz	±3.1 dB
Conducted Emission No.3 Shielded Room	150kHz~30MHz	±3.1 dB
Radiated Emission	30MHz~200MHz, Horizontal	±3.4 dB
	30MHz~200MHz, Vertical	±4.0 dB
	200MHz~1000MHz, Horizontal	±3.7 dB
	200MHz~1000MHz, Vertical	±5.1 dB
	1GHz~6GHz	±5.7 dB
	6GHz~18GHz	±4.7 dB
Output Power Test	50MHz~18GHz	0.77 dB
Power Density Test	9kHz~6GHz	1.08 dB
RF Frequency Test	9kHz~40GHz	6×10^{-4}
Bandwidth Test	9kHz~6GHz	1.5×10^{-3}
RF Radiated Power Test	30MHz~1000MHz	3.06 dB
Conducted Output Power Test	50MHz~18GHz	0.83 dB
AC Voltage(<10kHz) Test	120V~230V	0.04 %
DC Power Test	0V~30V	0.4 %
Temperature	-40°C~+100°C	0.52 °C
Humidity	30%~95%	2.6 %