FCC Radio Test Report

FCC ID: *2ARZ3-BT-X50*

Original Grant

Report No.	:	TB-FCC171987
Applicant	:	Technaxx Deutschland GmbH & Co. KG
Equipment Under Test (EUT)		
EUT Name	:	SPEAKER
Model No.	:	BT-X50
Series Model No.	:	FY-43,FY-25,FY-35,FY-34,FY-40,FY-42,FY-38,FY-39AB,FY-41,FY-45,FY-46,FY-47,FY-49,FY-50
Brand Name	:	N/A
Receipt Date	:	2020-03-19
Test Date	:	2020-03-19 to 2020-03-26
Issue Date	:	2020-03-28
Standards	:	FCC Part 15, Subpart C 15.247
Test Method	:	ANSI C63.10: 2013
Conclusions	:	**PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer	:	Garen	Garen
Engineer Supervisor	:	IVAN SU	Ivan Su
Engineer Manager	:	Ray Lai	Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS 2
1. GENERAL INFORMATION ABOUT EUT 5
1.1 Client Information 5
1.2 General Description of EUT (Equipment Under Test) 5
1.3 Block Diagram Showing the Configuration of System Tested 6
1.4 Description of Support Units 7
1.5 Description of Test Mode 7
1.6 Description of Test Software Setting 8
1.7 Measurement Uncertainty 9
1.8 Test Facility 10
2. TEST SUMMARY 11
3. TEST SOFTWARE 11
4. TEST EQUIPMENT 12
5. CONDUCTED EMISSION TEST 13
5.1 Test Standard and Limit 13
5.2 Test Setup 13
5.3 Test Procedure 13
5.4 Deviation From Test Standard 14
5.5 EUT Operating Mode 14
5.6 Test Data 14
6. RADIATED EMISSION TEST 15
6.1 Test Standard and Limit 15
6.2 Test Setup 16
6.3 Test Procedure 17
6.4 Deviation From Test Standard 17
6.5 EUT Operating Condition 17
6.6 Test Data 17
7. RESTRICTED BANDS REQUIREMENT 18
7.1 Test Standard and Limit 18
7.2 Test Setup 18
7.3 Test Procedure 18
7.4 Deviation From Test Standard 19
7.5 EUT Operating Condition 19
7.6 Test Data 19
8. NUMBER OF HOPPING CHANNEL 20
8.1 Test Standard and Limit 20
8.2 Test Setup 20
8.3 Test Procedure 20
8.4 Deviation From Test Standard 20
8.5 EUT Operating Condition 20

8.6 Test Data 20
9. AVERAGE TIME OF OCCUPANCY 21
9.1 Test Standard and Limit 21
9.2 Test Setup 21
9.3 Test Procedure 21
9.4 EUT Operating Condition 21
9.4 Deviation From Test Standard 22
9.5 EUT Operating Condition 22
9.6 Test Data 22
10. CHANNEL SEPARATION AND BANDWIDTH TEST 23
10.1 Test Standard and Limit 23
10.2 Test Setup 23
10.3 Test Procedure 23
10.4 Deviation From Test Standard 24
10.5 EUT Operating Condition 24
10.6 Test Data 24
11. PEAK OUTPUT POWER TEST 25
11.1 Test Standard and Limit 25
11.2 Test Setup 25
11.3 Test Procedure 25
11.4 Deviation From Test Standard 25
11.5 EUT Operating Condition 25
11.6 Test Data 25
12. ANTENNA REQUIREMENT 26
12.1 Standard Requirement 26
12.2 Deviation From Test Standard 26
12.3 Antenna Connected Construction 26
12.4 Result 26
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA 27
ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT AND BAND EDGE TEST DATA 38
ATTACHMENT D-- NUMBER OF HOPPING CHANNEL TEST DATA 50
ATTACHMENT E-- AVERAGE TIME OF OCCUPANCY TEST DATA 52
ATTACHMENT G-- PEAK OUTPUT POWER TEST DATA 64

Revision History

Report No.	Version	Description	Issued Date
TB-FCC171987	Rev.01	Initial issue of report	2020-03-28

1. General Information about EUT

1.1 Client Information

Applicant	:	Technaxx Deutschland GmbH & Co. KG
Address	:	Kruppstrasse 105 60388 Frankfurt am Main Germany
Manufacturer	:	Technaxx Deutschland GmbH & Co. KG
Address	:	Kruppstrasse 105 60388 Frankfurt am Main Germany

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	SPEAKER	
Models No.	:	BT-X50,FY-43,FY-25,FY-35,FY-34,FY-40,FY-42,FY-38,FY-39AB,FY-41, FY-45,FY-46,FY-47,FY-49,FY-50	
Model Difference	:	All these models are in the same PCB, layout and electrical circuit, the only difference is model name.	
Product Description	:	Operation Frequency:	Bluetooth V5.0(BT): 2402~2480 MHz
		Number of Channel:	Bluetooth: 79 Channels See Note 2
		Max Peak Output Power:	Bluetooth: -5.932dBm(π/4-DQPSK)
		Antenna Gain:	0dBi PCB Antenna
		Modulation Type:	GFSK: -6.596dBm π/4-DQPSK: -5.932dBm
Power Rating	:	Input: DC 5V DC 3.7V 500mAh by Li-ion battery	
Software Version	:	AC6925C_2.6.1	
Hardware Version	:	V1.1	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark	:	The antenna gain and adapter provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.	

Note:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) Channel List:

Bluetooth Channel List					
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
00	**2402**	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	**39**	**2441**	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	**78**	**2480**
25	2427	52	2454		
26	2428	53	2455		

(3) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

Charging + TX Mode



TX Mode



1.4 Description of Support Units

Equipment Information				
Name	**Model**	**FCC ID/VOC**	**Manufacturer**	**Used "√"**
Adapter	CS-1201000	----	----	√
Cable Information				
Number	**Shielded Type**	**Ferrite Core**	**Length**	**Note**
Cable 1	Yes	NO	1.0M	Accessory

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	**Description**
Mode 1	Charging + TX Mode Channel 00
For Radiated Test	
Final Test Mode	**Description**
Mode 1	TX GFSK Mode Channel 00
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode(π/4-DQPSK) Channel 00/39/78
Mode 4	Hopping Mode(GFSK)
Mode 5	Hopping Mode(π/4-DQPSK)

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:
TX Mode: GFSK (1 Mbps)
TX Mode: π/4-DQPSK (2 Mbps)

(2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	**LaunchEngmode**		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
π/4-DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	±3.50 dB ±3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	±4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	±4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	±4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025：2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01. FCC Accredited Test Site Number: 854351.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	N/A
Note: N/A is an abbreviation for Not Applicable.				

3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE

4. Test Equipment

1. Conducted Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 13, 2019	Jul. 12, 2020
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 13, 2019	Jul. 12, 2020
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 13, 2019	Jul. 12, 2020
LISN	Rohde & Schwarz	ENV216	101131	Jul. 13, 2019	Jul. 12, 2020
Radiation Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	FSVR	1311.006K40-100945-DH	Feb. 09, 2020	Feb. 08, 2021
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Jan. 27, 2019	Jan. 26, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Jan. 27, 2019	Jan. 26, 2020
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.02, 2020	Mar. 01, 2021
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.02, 2020	Mar. 01, 2021
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Mar.02, 2020	Mar. 01, 2021
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 13, 2019	Jul. 12, 2020
Pre-amplifier	Sonoma	310N	185903	Mar.02, 2020	Mar. 01, 2021
Pre-amplifier	HP	8449B	3008A00849	Mar.02, 2020	Mar. 01, 2021
Pre-amplifier	SKET	LNPA_1840G-50	SK201904032	Jul. 27, 2019	Jul. 26, 2020
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.02, 2020	Mar. 01, 2021
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 13, 2019	Jul. 12, 2020
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 16, 2019	Sep. 15, 2020
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 16, 2019	Sep. 15, 2020
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 16, 2019	Sep. 15, 2020
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 16, 2019	Sep. 15, 2020

5. Conducted Emission Test

5.1 Test Standard and Limit

5.1.1Test Standard

FCC Part 15.207

5.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:
(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequencies.
(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.2 Test Setup



5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

5.4 Deviation From Test Standard

No deviation

5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Please refer to the Attachment A.

6. Radiated Emission Test

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209

6.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

6.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

6.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

(2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

(4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

(5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

(6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.

(7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

(8) For the actual test configuration, please see the test setup photo.

6.4 Deviation From Test Standard

No deviation

6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

6.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

7. Restricted Bands Requirement

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.209

FCC Part 15.205

7.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54
Note: All restriction bands have been tested, only the worst case is reported.		

7.2 Test Setup



7.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

(2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
(4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
(5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
(6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
(7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
(8) For the actual test configuration, please see the test setup photo.

7.4 Deviation From Test Standard

No deviation

7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

7.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

Please refer to the Attachment C.

8. Number of Hopping Channel

8.1 Test Standard and Limit

8.1.1 Test Standard

FCC Part 15.247 (a)(1)

8.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

8.2 Test Setup



8.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

8.4 Deviation From Test Standard

No deviation

8.5 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

8.6 Test Data

Please refer to the Attachment D.

9. Average Time of Occupancy

9.1 Test Standard and Limit

9.1.1 Test Standard

FCC Part 15.247 (a)(1)

9.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)	Average Time of Occupancy	0.4 sec

9.2 Test Setup



9.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
(2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
(3) Use video trigger with the trigger level set to enable triggering only on full pulses.
(4) Sweep Time is more than once pulse time.
(5) Set the centre frequency on any frequency would be measure and set the frequency span to zero.
(6) Measure the maximum time duration of one single pulse.
(7) Set the EUT for packet transmitting.
(8) Measure the maximum time duration of one single pulse.

9.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:
{Total of Dwell} = {Pulse Time} * (1600 / X) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4s * {Number of Hopping Frequency}

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2, 3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

9.4 Deviation From Test Standard

No deviation

9.5 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

9.6 Test Data

Please refer to the Attachment E.

10. Channel Separation and Bandwidth Test

10.1 Test Standard and Limit

10.1.1 Test Standard

FCC Part 15.247

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	<=1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

10.2 Test Setup



10.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:
Channel Separation: RBW=100 kHz, VBW=100 kHz.
Bandwidth: RBW=30 kHz, VBW=100 kHz.

(3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.

(4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

10.4 Deviation From Test Standard

No deviation

10.5 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

10.6 Test Data

Please refer to the Attachment F.

11. Peak Output Power Test

11.1 Test Standard and Limit

11.1.1 Test Standard

FCC Part 15.247 (b) (1)

11.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

11.2 Test Setup



11.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.

RBW=3 MHz, VBW≥ RBW for bandwidth more than 1MHz.

11.4 Deviation From Test Standard

No deviation

11.5 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

11.6 Test Data

Please refer to the Attachment G.

12. Antenna Requirement

12.1 Standard Requirement

12.1.1 Standard

FCC Part 15.203

12.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

12.2 Deviation From Test Standard

No deviation

12.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 0dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

12.4 Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
☒Permanent attached antenna
☐Unique connector antenna
☐Professional installation antenna

Attachment A-- Conducted Emission Test Data

Temperature:	24℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	Mode 1		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.3740	29.42	9.83	39.25	58.41	-19.16	QP
2		0.3740	22.03	9.83	31.86	48.41	-16.55	AVG
3		0.5460	32.98	9.95	42.93	56.00	-13.07	QP
4	*	0.5460	29.93	9.95	39.88	46.00	-6.12	AVG
5		1.1180	22.40	9.66	32.06	56.00	-23.94	QP
6		1.1180	15.85	9.66	25.51	46.00	-20.49	AVG
7		2.9739	18.74	9.86	28.60	56.00	-27.40	QP
8		2.9739	11.66	9.86	21.52	46.00	-24.48	AVG
9		6.3100	19.56	9.83	29.39	60.00	-30.61	QP
10		6.3100	11.87	9.83	21.70	50.00	-28.30	AVG
11		11.1380	20.89	9.82	30.71	60.00	-29.29	QP
12		11.1380	12.68	9.82	22.50	50.00	-27.50	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	24℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Neutral		
Test Mode:	Mode 1		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.3740	29.04	9.83	38.87	58.41	-19.54	QP
2		0.3740	21.61	9.83	31.44	48.41	-16.97	AVG
3		0.5460	33.03	9.95	42.98	56.00	-13.02	QP
4	*	0.5460	30.04	9.95	39.99	46.00	-6.01	AVG
5		1.1140	17.40	9.66	27.06	56.00	-28.94	QP
6		1.1140	12.76	9.66	22.42	46.00	-23.58	AVG
7		2.9660	23.29	9.86	33.15	56.00	-22.85	QP
8		2.9660	16.33	9.86	26.19	46.00	-19.81	AVG
9		4.4460	25.77	9.85	35.62	56.00	-20.38	QP
10		4.4460	19.14	9.85	28.99	46.00	-17.01	AVG
11		11.4819	32.49	9.82	42.31	60.00	-17.69	QP
12		11.4819	18.16	9.82	27.98	50.00	-22.02	AVG

Emission Level= Read Level+ Correct Factor

Attachment B-- Radiated Emission Test Data

9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V60HZ		
Ant. Pol.	Horizontal		
Test Mode:	Mode 1 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		80.0806	43.40	-22.56	20.84	40.00	-19.16	QP
2		133.6188	44.37	-22.47	21.90	43.50	-21.60	QP
3		164.9075	53.39	-20.67	32.72	43.50	-10.78	QP
4		261.9753	53.83	-16.80	37.03	46.00	-8.97	QP
5	*	325.5958	55.45	-15.17	40.28	46.00	-5.72	QP
6		369.4047	48.40	-13.51	34.89	46.00	-11.11	QP

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V60HZ		
Ant. Pol.	Vertical		
Test Mode:	Mode 1 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		31.7313	41.38	-14.32	27.06	40.00	-12.94	QP
2		45.6948	47.38	-21.90	25.48	40.00	-14.52	QP
3		74.6569	52.31	-23.10	29.21	40.00	-10.79	QP
4		164.9075	53.72	-20.67	33.05	43.50	-10.45	QP
5		314.3765	46.56	-15.53	31.03	46.00	-14.97	QP
6	*	434.0651	47.80	-11.87	35.93	46.00	-10.07	QP

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz(Only worse case is reported)

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4803.394	38.86	13.47	52.33	74.00	-21.67	peak
2	*	4804.714	28.68	13.47	42.15	54.00	-11.85	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.604	28.60	13.47	42.07	54.00	-11.93	AVG
2		4803.832	38.86	13.47	52.33	74.00	-21.67	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4880.530	39.36	13.53	52.89	74.00	-21.11	peak
2	*	4882.708	28.69	13.54	42.23	54.00	-11.77	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4882.066	40.46	13.54	54.00	74.00	-20.00	peak
2	*	4882.702	28.76	13.54	42.30	54.00	-11.70	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4960.234	28.31	13.61	41.92	54.00	-12.08	AVG
2		4960.240	39.89	13.61	53.50	74.00	-20.50	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4958.956	38.35	13.62	51.97	74.00	-22.03	peak
2	*	4959.130	28.30	13.62	41.92	54.00	-12.08	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2402MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4802.902	38.18	13.47	51.65	74.00	-22.35	peak
2	*	4804.714	28.59	13.47	42.06	54.00	-11.94	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX π /4-DQPSK Mode 2402MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.922	28.57	13.47	42.04	54.00	-11.96	AVG
2		4805.392	41.48	13.47	54.95	74.00	-19.05	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2441MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.610	28.79	13.54	42.33	54.00	-11.67	AVG
2		4883.428	39.33	13.54	52.87	74.00	-21.13	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX π /4-DQPSK Mode 2441MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4881.436	39.57	13.54	53.11	74.00	-20.89	peak
2	*	4882.708	28.75	13.54	42.29	54.00	-11.71	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.130	28.35	13.62	41.97	54.00	-12.03	AVG
2		4961.500	38.45	13.62	52.07	74.00	-21.93	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX π /4-DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4959.610	28.29	13.61	41.90	54.00	-12.10	AVG
2		4961.020	39.34	13.61	52.95	74.00	-21.05	peak

Emission Level= Read Level+ Correct Factor

Conducted Emission Test Data

π /4-DQPSK Mode (Only worse case is reported)

2402 MHz



π /4-DQPSK Mode

2441 MHz



π /4-DQPSK Mode

2480 MHz



Attachment C-- Restricted Bands Requirement and Band Edge Test Data

(1) Radiation Test

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	40.19	2.91	43.10	74.00	-30.90	peak
2		2390.000	29.63	2.91	32.54	54.00	-21.46	AVG
3	X	2402.000	88.50	2.95	91.45	Fundamental Frequency		peak
4	*	2402.200	82.76	2.95	85.71	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	40.41	2.91	43.32	74.00	-30.68	peak
2		2390.000	29.31	2.91	32.22	54.00	-21.78	AVG
3	X	2402.000	82.64	2.95	85.59	Fundamental Frequency		peak
4	*	2402.200	77.47	2.95	80.42	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	88.71	3.38	92.09	Fundamental Frequency		peak
2	*	2480.000	83.15	3.38	86.53	Fundamental Frequency		AVG
3		2483.500	52.42	3.40	55.82	74.00	-18.18	peak
4		2483.500	44.84	3.40	48.24	54.00	-5.76	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	80.70	3.38	84.08	Fundamental Frequency		peak
2	*	2479.800	75.73	3.38	79.11	Fundamental Frequency		AVG
3		2483.500	46.14	3.40	49.54	74.00	-24.46	peak
4		2483.500	37.15	3.40	40.55	54.00	-13.45	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	39.37	2.91	42.28	74.00	-31.72	peak
2		2390.000	29.07	2.91	31.98	54.00	-22.02	AVG
3	X	2402.000	88.43	2.95	91.38	Fundamental Frequency		peak
4	*	2402.200	81.00	2.95	83.95	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX π/4-DQPSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	40.41	2.91	43.32	74.00	-30.68	peak
2		2390.000	29.25	2.91	32.16	54.00	-21.84	AVG
3	X	2402.000	82.63	2.95	85.58	Fundamental Frequency		peak
4	*	2402.200	75.64	2.95	78.59	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2480MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	89.25	3.38	92.63	Fundamental Frequency		peak
2	*	2480.000	81.65	3.38	85.03	Fundamental Frequency		AVG
3		2483.500	52.61	3.40	56.01	74.00	-17.99	peak
4		2483.500	43.88	3.40	47.28	54.00	-6.72	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX π/4-DQPSK Mode 2480MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2479.800	81.77	3.38	85.15	Fundamental Frequency		peak
2	*	2480.000	74.65	3.38	78.03	Fundamental Frequency		AVG
3		2483.500	44.93	3.40	48.33	74.00	-25.67	peak
4		2483.500	37.64	3.40	41.04	54.00	-12.96	AVG

Emission Level= Read Level+ Correct Factor

(2) Conducted Test

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX GFSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		





Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	GFSK Hopping Mode		
Remark:	Only worse case is reported		





Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX π /4-DQPSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		





Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	π /4-DQPSK Hopping Mode		
Remark:	Only worse case is reported		





Attachment D-- Number of Hopping Channel Test Data

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode		

Frequency Range	Test Mode	Quantity of Hopping Channel	Limit
2402MHz~2480MHz	GFSK	79	**>15**
	π /4-DQPSK	79	

GFSK Mode



π /4-DQPSK Mode


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.441750000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
05:47:09 PM Mar 22, 2020
Ref Offset 3.94 dB
10 dB/div
Ref 23.94 dBm
Mkr1 2.401 586 5 GHz
-12.182 dBm
Start 2.40000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 8.000 ms (1001 pts)
1 N 1 f 2.401 586 5 GHz -12.182 dBm
2 N 1 f 2.480 327 0 GHz -13.276 dBm

Attachment E-- Average Time of Occupancy Test Data

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode (GFSK)		

Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1DH1	2441	0.378	120.96	31.60	**400**	**PASS**
1DH3	2441	1.634	261.44	31.60	**400**	**PASS**
1DH5	2441	2.882	307.41	31.60	**400**	**PASS**

1DH1 Total of Dwell= Pulse Time(1600/2)*31.6/79*

1DH3 Total of Dwell= Pulse Time(1600/4)*31.6/79*

1DH5 Total of Dwell= Pulse Time(1600/6)*31.6/79*

GFSK Hopping Mode 1DH1

2441 MHz



GFSK Hopping Mode 1DH3

2441 MHz



GFSK Hopping Mode 1DH5

2441 MHz



Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode (π /4-DQPSK)		

Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2DH1	2441	0.387	123.84	31.60	**400**	**PASS**
2DH3	2441	1.640	262.40	31.60	**400**	**PASS**
2DH5	2441	2.887	307.95	31.60	**400**	**PASS**

2DH1 Total of Dwell= Pulse Time(1600/2)*31.6/79*

2DH3 Total of Dwell= Pulse Time(1600/4)*31.6/79*

2DH5 Total of Dwell= Pulse Time(1600/6)*31.6/79*

π /4-DQPSK **Hopping Mode 2DH1**

2441 MHz



π /4-DQPSK Hopping Mode 2DH3

2441 MHz



π /4-DQPSK Hopping Mode 2DH5

2441 MHz



Attachment F-- Channel Separation and Bandwidth Test Data

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX Mode (GFSK)		

Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	820.69	866.4	
2441	819.55	870.9	
2480	821.98	867.5	

GFSK TX Mode

2402 MHz



GFSK TX Mode

2441 MHz



GFSK TX Mode

2480 MHz



Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX Mode (π/4-DQPSK)		

Channel frequency (MHz)	99% OBW (kHz)	20dB Bandwidth (kHz)	20dB Bandwidth *2/3 (kHz)
2402	1166.9	1250	833.33
2441	1165.8	1250	833.33
2480	1163.2	1222	814.67

π/4-DQPSK TX Mode

2402 MHz



π /4-DQPSK TX Mode

2441 MHz



π /4-DQPSK TX Mode

2480 MHz



Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode (GFSK)		

Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)
2402	980	577.60
2441	1000	580.60
2480	1000	578.33

GFSK Hopping Mode

2402 MHz



GFSK Hopping Mode

2441 MHz

GFSK Hopping Mode

2480 MHz

Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode (π/4-DQPSK)		

Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)
2402	1000	833.33
2441	1000	833.33
2480	990	814.67

π/4-DQPSK Hopping Mode

2402 MHz



π /4-DQPSK Hopping Mode

2441 MHz



π /4-DQPSK Hopping Mode

2480 MHz

Attachment G-- Peak Output Power Test Data

Temperature:	25℃	**Relative Humidity:**	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX Mode (GFSK)		

Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
2402	-6.596	**30**
2441	-7.277	
2480	-8.195	

GFSK TX Mode

2402 MHz



GFSK TX Mode

2441 MHz



GFSK TX Mode

2480 MHz



Temperature:	25℃	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX Mode (π/4-DQPSK)		

Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
2402	-5.932	30
2441	-6.725	
2480	-7.614	

π/4-DQPSK TX Mode

2402 MHz



π /4-DQPSK TX Mode

2441 MHz



π /4-DQPSK TX Mode

2480 MHz



-----END OF REPORT-----