

# TEST REPORT


**Application No.:** SZCR2503001079ME  
**Applicant:** SHENZHEN XFT MEDICAL LIMITED  
**Address of Applicant:** Room 203, Building 1, Biomedicine Innovations Industrial Park, #14 Jinhui Road, Pingshan District Shenzhen 518118 China  
**Manufacturer:** SHENZHEN XFT MEDICAL LIMITED  
**Address of Manufacturer:** Room 203, Building 1, Biomedicine Innovations Industrial Park, #14 Jinhui Road, Pingshan District Shenzhen 518118 China  
**Factory:** SHENZHEN XFT MEDICAL LIMITED  
**Address of Factory:** Room 203, Building 1, Biomedicine Innovations Industrial Park, #14 Jinhui Road, Pingshan District Shenzhen 518118 China

**Equipment Under Test (EUT):**

**EUT Name:** Nerve and Muscle Stimulator  
**Model No.:** XFT-2001F, XFT-2001FB ♣  
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**Trade Mark:** XFT  
**FCC ID:** 2AS2I2001F  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2025-03-20  
**Date of Test:** 2025-03-20 to 2025-03-27  
**Date of Issue:** 2025-04-27

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager

## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 2 of 66

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2025-04-27 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                            |  |  |
|--------------------------|--|----------------------------|--|--|
| Authorized for issue by: |  |                            |  |  |
|                          |  | Edison Li                  |  |  |
|                          |  | Edison Li/Project Engineer |  |  |
|                          |  | Eric Fu                    |  |  |
|                          |  | Eric Fu/Reviewer           |  |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                                 |        |
|--------------------------------------|----------------------------------|--------|-------------------------------------------------|--------|
| Item                                 | Standard                         | Method | Requirement                                     | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass   |

| Radio Spectrum Matter Part                            |                                  |                                           |                                           |        |
|-------------------------------------------------------|----------------------------------|-------------------------------------------|-------------------------------------------|--------|
| Item                                                  | Standard                         | Method                                    | Requirement                               | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2020) Section 6.2            | 47 CFR Part 15, Subpart C 15.207          | Pass   |
| Radiated Emissions which fall in the restricted bands |                                  | ANSI C63.10 (2020) Section 6.10.5 & 11.12 | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Below 1GHz                |                                  | ANSI C63.10 (2020) Section 6.4,6.5        | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Radiated Spurious Emissions Above 1GHz                |                                  | ANSI C63.10 (2020) Section 6.6 & 11.12    | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |
| Conducted Peak Output Power                           |                                  | ANSI C63.10 (2020) Section 11.9.1         | 47 CFR Part 15, Subpart C 15.247(b)(3)    | Pass   |
| Minimum 6dB Bandwidth                                 |                                  | ANSI C63.10 (2020) Section 11.8.1         | 47 CFR Part 15, Subpart C 15.247a(2)      | Pass   |
| Power Spectrum Density                                |                                  | ANSI C63.10 (2020) Section 11.10.3        | 47 CFR Part 15, Subpart C 15.247(e)       | Pass   |
| Conducted Band Edges Measurement                      |                                  | ANSI C63.10 (2020) Section 6.10.4         | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions                          |                                  | ANSI C63.10 (2020) Section 11.11          | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |

### Declaration of EUT Family Grouping:

Model No.: XFT-2001F, XFT-2001FB

Only the model XFT-2001F was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference on model No..



## 3 Contents

|                                                                 | Page      |
|-----------------------------------------------------------------|-----------|
| <b>1 Cover Page .....</b>                                       | <b>1</b>  |
| <b>2 Test Summary.....</b>                                      | <b>3</b>  |
| <b>3 Contents .....</b>                                         | <b>4</b>  |
| <b>4 General Information.....</b>                               | <b>6</b>  |
| 4.1 Details of E.U.T. ....                                      | 6         |
| 4.2 Description of Support Units.....                           | 6         |
| 4.3 Measurement Uncertainty .....                               | 7         |
| 4.4 Test Location .....                                         | 8         |
| 4.5 Test Facility.....                                          | 8         |
| 4.6 Deviation from Standards.....                               | 8         |
| 4.7 Abnormalities from Standard Conditions.....                 | 8         |
| <b>5 Equipment List .....</b>                                   | <b>9</b>  |
| <b>6 Radio Spectrum Technical Requirement.....</b>              | <b>11</b> |
| 6.1 Antenna Requirement .....                                   | 11        |
| 6.1.1 Test Requirement: .....                                   | 11        |
| 6.1.2 Conclusion .....                                          | 11        |
| <b>7 Radio Spectrum Matter Test Results.....</b>                | <b>12</b> |
| 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz) .....   | 12        |
| 7.1.1 E.U.T. Operation .....                                    | 12        |
| 7.1.2 Test Mode Description .....                               | 12        |
| 7.1.3 Test Setup Diagram .....                                  | 12        |
| 7.1.4 Measurement Procedure and Data.....                       | 13        |
| 7.2 Radiated Emissions which fall in the restricted bands ..... | 16        |
| 7.2.1 E.U.T. Operation .....                                    | 16        |
| 7.2.2 Test Mode Description .....                               | 16        |
| 7.2.3 Test Setup Diagram .....                                  | 17        |
| 7.2.4 Measurement Procedure and Data.....                       | 18        |
| 7.3 Radiated Spurious Emissions Below 1GHz.....                 | 23        |
| 7.3.1 E.U.T. Operation .....                                    | 23        |
| 7.3.2 Test Mode Description .....                               | 23        |
| 7.3.3 Test Setup Diagram .....                                  | 24        |
| 7.3.4 Measurement Procedure and Data.....                       | 24        |
| 7.4 Radiated Spurious Emissions Above 1GHz .....                | 27        |
| 7.4.1 E.U.T. Operation .....                                    | 27        |
| 7.4.2 Test Mode Description .....                               | 27        |
| 7.4.3 Test Setup Diagram .....                                  | 27        |
| 7.4.4 Measurement Procedure and Data.....                       | 28        |
| 7.5 Conducted Peak Output Power .....                           | 33        |
| 7.5.1 E.U.T. Operation .....                                    | 33        |



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 5 of 66

|       |                                               |    |
|-------|-----------------------------------------------|----|
| 7.5.1 | Test Mode Description .....                   | 33 |
| 7.5.2 | Test Setup Diagram .....                      | 34 |
| 7.5.3 | Measurement Procedure and Data .....          | 34 |
| 7.6   | Minimum 6dB Bandwidth .....                   | 35 |
| 7.6.1 | E.U.T. Operation .....                        | 35 |
| 7.6.2 | Test Mode Description .....                   | 35 |
| 7.6.3 | Test Setup Diagram .....                      | 35 |
| 7.6.4 | Measurement Procedure and Data .....          | 35 |
| 7.7   | Power Spectrum Density .....                  | 36 |
| 7.7.1 | E.U.T. Operation .....                        | 36 |
| 7.7.2 | Test Mode Description .....                   | 36 |
| 7.7.3 | Test Setup Diagram .....                      | 36 |
| 7.7.4 | Measurement Procedure and Data .....          | 36 |
| 7.8   | Conducted Band Edges Measurement .....        | 37 |
| 7.8.1 | E.U.T. Operation .....                        | 37 |
| 7.8.2 | Test Mode Description .....                   | 37 |
| 7.8.3 | Test Setup Diagram .....                      | 38 |
| 7.8.4 | Measurement Procedure and Data .....          | 38 |
| 7.9   | Conducted Spurious Emissions .....            | 39 |
| 7.9.1 | E.U.T. Operation .....                        | 39 |
| 7.9.2 | Test Mode Description .....                   | 39 |
| 7.9.3 | Test Setup Diagram .....                      | 40 |
| 7.9.4 | Measurement Procedure and Data .....          | 40 |
| 8     | Test Setup Photo .....                        | 41 |
| 9     | EUT Constructional Details (EUT Photos) ..... | 41 |
| 10    | Appendix .....                                | 42 |



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                                                                                                                                                                                                                                                        |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:        | AC/DC Adapter<br>Model: GTM41078-0605-USB<br>Input: AC 100-240V, 50/60Hz, 0.3A<br>Output: DC 5.0V, 1.2A, 6.0W<br><br>Rechargeable Li-ion Polymer Battery<br>Model: SH652432<br>Rated Capacity: 520mAh, 1.924Wh<br>Rated Voltage: 3.7V<br>Limited Charger Voltage: 4.2V |
| Operation Frequency: | 2402MHz to 2480MHz                                                                                                                                                                                                                                                     |
| Bluetooth Version:   | V5.0                                                                                                                                                                                                                                                                   |
| Modulation Type:     | GFSK                                                                                                                                                                                                                                                                   |
| Number of Channels:  | 40                                                                                                                                                                                                                                                                     |
| Channel Spacing:     | 2MHz                                                                                                                                                                                                                                                                   |
| Data rate:           | 1Mbps, 2Mbps                                                                                                                                                                                                                                                           |
| Antenna Type:        | PCB Antenna                                                                                                                                                                                                                                                            |
| Antenna Gain:        | 0.338dBi                                                                                                                                                                                                                                                               |

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

| Description  | Manufacturer | Model No.              | Serial No.        |
|--------------|--------------|------------------------|-------------------|
| Type-C Cable | SGS          | N/A                    | REF. No. SEA07B00 |
| RF Cable     | SGS          | N/A(cable loss: 0.8dB) | N/A               |



## 4.3 Measurement Uncertainty

| Test Item                                             | Measurement Uncertainty                                          |
|-------------------------------------------------------|------------------------------------------------------------------|
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | $\pm 3.1\text{dB}$                                               |
| Radiated Emissions which fall in the restricted bands | $\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz) |
| Radiated Spurious Emissions Below 1GHz                | $\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m            |
| Radiated Spurious Emissions Above 1GHz                | $\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)      |
| Conducted Peak Output Power                           | $\pm 0.75\text{dB}$                                              |
| Minimum 6dB Bandwidth                                 | $\pm 3\%$                                                        |
| Power Spectrum Density                                | $\pm 2.84\text{dB}$                                              |
| Conducted Band Edges Measurement                      | $\pm 0.75\text{dB}$                                              |
| Conducted Spurious Emissions                          | $\pm 0.75\text{dB}$                                              |

### Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR/ETSI}}$  (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 8 of 66

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 4.6 Deviation from Standards

None

### 4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Testing Services Co., Ltd. Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Conducted Emissions at AC Power Line (150kHz-30MHz) |                  |                  |               |            |              |
|-----------------------------------------------------|------------------|------------------|---------------|------------|--------------|
| Equipment                                           | Manufacturer     | Model No.        | Inventory No. | Cal Date   | Cal Due Date |
| Shielding Room                                      | ZhongYu Electron | GB-88            | SEM001-06     | 2022-05-14 | 2025-05-13   |
| EMI Test Receiver                                   | Rohde&Schwarz    | ESR              | SZ-WRG-M-047  | 2025-01-08 | 2026-01-07   |
| Measurement Software                                | AUDIX            | e3 V8.2014-6-27a | N/A           | N/A        | N/A          |
| Coaxial Cable                                       | SGS              | N/A              | SEM024-01     | 2024-07-06 | 2025-07-05   |
| LISN                                                | Rohde&Schwarz    | ENV216           | SEM007-01     | 2024-08-15 | 2025-08-14   |
| LISN                                                | ETS-LINDGREN     | 3816/2           | SEM007-02     | 2025-03-03 | 2026-03-02   |

| Radiated Emissions which fall in the restricted bands |                 |                 |               |            |              |
|-------------------------------------------------------|-----------------|-----------------|---------------|------------|--------------|
| Equipment                                             | Manufacturer    | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| Signal & Spectrum Analyzer                            | Rohde & Schwarz | FSV             | SZ-WRG-M-048  | 2025-01-07 | 2026-01-06   |
| Low Noise Amplifier 30M-8GHz                          | Tonscend        | TAP30M8G30      | SZ-WRG-M-050  | 2025-01-07 | 2026-01-06   |
| Double Ridge Horn Antenna 1GHz-18GHz                  | SCHWARZBECK     | BBHA 9120 D     | SZ-WRG-M-055  | 2023-12-21 | 2025-12-20   |
| RSE Test Software                                     | AUDIX           | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Chamber                                               | CRTSGSSAC966    | N/A             | SZ-WRG-C-063  | 2025-01-06 | 2028-01-05   |
| Humidity and Temperature Indicator                    | deli            | 8838            | SEM002-46     | 2024-07-24 | 2025-07-23   |

| Radiated Spurious Emissions Below 1GHz |                      |                 |               |            |              |
|----------------------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                              | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| Loop Antenna                           | ETS-Lindgren         | 6502            | SEM003-08     | 2023-11-20 | 2025-11-19   |
| 3m Semi-Anechoic Chamber               | ETS-LINDGREN         | N/A             | SEM001-01     | 2023-06-19 | 2026-06-18   |
| MXE EMI Receiver                       | Agilent Technologies | N9038A          | SEM004-15     | 2024-08-14 | 2025-08-13   |
| BiConiLog Antenna                      | ETS-LINDGREN         | 3142C           | SEM003-01     | 2023-09-16 | 2025-09-15   |
| Pre-Amplifier                          | Agilent Technologies | 8447D           | SEM005-01     | 2025-03-04 | 2026-03-03   |
| Measurement Software                   | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable                          | SGS                  | N/A             | SEM025-01     | 2024-07-06 | 2025-07-05   |

# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 10 of 66

| Radiated Spurious Emissions Above 1GHz |                 |                 |               |            |              |
|----------------------------------------|-----------------|-----------------|---------------|------------|--------------|
| Equipment                              | Manufacturer    | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| Signal & Spectrum Analyzer             | Rohde & Schwarz | FSV             | SZ-WRG-M-048  | 2025-01-07 | 2026-01-06   |
| Low Noise Amplifier 1G-18GHz           | Tonscend        | TAP01018050     | SZ-WRG-M-051  | 2025-01-07 | 2026-01-06   |
| Low Noise Amplifier 18G-40GHz          | Tonscend        | TAP18040048     | SZ-WRG-M-052  | 2025-01-08 | 2026-01-07   |
| Double Ridge Horn Antenna 1GHz-18GHz   | SCHWARZBECK     | BBHA 9120 D     | SZ-WRG-M-055  | 2023-12-21 | 2025-12-20   |
| SHF-EHF Horn 15GHz-40GHz               | SCHWARZBECK     | BBHA 9170       | SZ-WRG-M-056  | 2023-12-25 | 2025-12-24   |
| RSE Test Software                      | AUDIX           | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Chamber                                | CRTSGSSAC966    | N/A             | SZ-WRG-C-063  | 2025-01-06 | 2028-01-05   |
| Humidity and Temperature Indicator     | deli            | 8838            | SEM002-46     | 2024-07-24 | 2025-07-23   |

| RF Conducted Test    |              |               |               |            |              |
|----------------------|--------------|---------------|---------------|------------|--------------|
| Equipment            | Manufacturer | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| DC Power Supply      | Chroma       | 62012P-80-60  | SEM011-11     | 2024-08-14 | 2025-08-13   |
| MXA Signal Analyzer  | KEYSIGHT     | N9020A        | SEM004-19     | 2025-03-04 | 2026-03-03   |
| Measurement Software | TST PASS     | TST PASS V2.0 | N/A           | N/A        | N/A          |
| Coaxial Cable        | SGS          | N/A           | SEM031-01     | 2024-07-06 | 2025-07-05   |
| Attenuator           | Huber+Suhner | 6620_SMA-50-1 | SEM021-09     | 2025-03-03 | 2026-03-02   |

| General used equipment          |                                           |           |               |            |              |
|---------------------------------|-------------------------------------------|-----------|---------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-32     | 2024-07-24 | 2025-07-23   |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-33     | 2024-07-24 | 2025-07-23   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3      | SEM002-01     | 2025-03-03 | 2026-03-02   |

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.338dBi.

Antenna location: Refer to internal photo.



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

| Frequency of emission(MHz) | Conducted limit(dBμV) |           |
|----------------------------|-----------------------|-----------|
|                            | Quasi-peak            | Average   |
| 0.15-0.5                   | 66 to 56*             | 56 to 46* |
| 0.5-5                      | 56                    | 46        |
| 5-30                       | 60                    | 50        |

\*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C


Humidity: 44.5 % RH

Atmospheric Pressure: 1020 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Pre-scan              | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 7.1.3 Test Setup Diagram



## 7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor




## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 14 of 66

Test Mode: 02; Line: Live line



Site : Shielding Room

Condition: Line

Job No. : 01079ME

Test mode: 02

|     | Freq    | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|-----|---------|------------|-------------|------------|-------|------------|------------|---------|
|     | MHz     | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1   | 0.1650  | 0.06       | 10.17       | 40.65      | 50.88 | 65.21      | -14.33     | QP      |
| 2   | 0.1650  | 0.06       | 10.17       | 24.39      | 34.62 | 55.21      | -20.59     | Average |
| 3 * | 0.4083  | 0.07       | 9.66        | 34.83      | 44.56 | 57.68      | -13.12     | QP      |
| 4 * | 0.4083  | 0.07       | 9.66        | 22.08      | 31.81 | 47.68      | -15.87     | Average |
| 5   | 1.3521  | 0.10       | 9.58        | 22.73      | 32.41 | 56.00      | -23.59     | QP      |
| 6   | 1.3521  | 0.10       | 9.58        | 11.76      | 21.44 | 46.00      | -24.56     | Average |
| 7   | 1.9801  | 0.10       | 9.58        | 22.67      | 32.35 | 56.00      | -23.65     | QP      |
| 8   | 1.9801  | 0.10       | 9.58        | 10.91      | 20.59 | 46.00      | -25.41     | Average |
| 9   | 2.5400  | 0.11       | 9.62        | 21.42      | 31.15 | 56.00      | -24.85     | QP      |
| 10  | 2.5400  | 0.11       | 9.62        | 10.80      | 20.53 | 46.00      | -25.47     | Average |
| 11  | 11.6208 | 0.22       | 9.78        | 24.67      | 34.67 | 60.00      | -25.33     | QP      |
| 12  | 11.6208 | 0.22       | 9.78        | 13.29      | 23.29 | 50.00      | -26.71     | Average |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (SZEMC) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 15 of 66

Test Mode: 02; Line: Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 01079ME

Test mode: 02

|     |         | Cable | LISN   | Read  | Limit | Over  |                |
|-----|---------|-------|--------|-------|-------|-------|----------------|
|     | Freq    | Loss  | Factor | Level | Level | Line  | Limit Remark   |
|     | MHz     | dB    | dB     | dBuV  | dBuV  | dBuV  | dB             |
| 1 * | 0.1668  | 0.06  | 10.12  | 40.35 | 50.53 | 65.12 | -14.59 QP      |
| 2 * | 0.1668  | 0.06  | 10.12  | 24.48 | 34.66 | 55.12 | -20.46 Average |
| 3   | 0.4083  | 0.07  | 9.73   | 31.08 | 40.88 | 57.68 | -16.80 QP      |
| 4   | 0.4083  | 0.07  | 9.73   | 16.43 | 26.23 | 47.68 | -21.45 Average |
| 5   | 0.9481  | 0.09  | 9.56   | 17.80 | 27.45 | 56.00 | -28.55 QP      |
| 6   | 0.9481  | 0.09  | 9.56   | 6.98  | 16.63 | 46.00 | -29.37 Average |
| 7   | 1.9182  | 0.10  | 9.55   | 18.98 | 28.63 | 56.00 | -27.37 QP      |
| 8   | 1.9182  | 0.10  | 9.55   | 8.68  | 18.33 | 46.00 | -27.67 Average |
| 9   | 4.7969  | 0.12  | 9.56   | 17.95 | 27.63 | 56.00 | -28.37 QP      |
| 10  | 4.7969  | 0.12  | 9.56   | 7.33  | 17.01 | 46.00 | -28.99 Average |
| 11  | 10.9050 | 0.21  | 9.64   | 25.67 | 35.52 | 60.00 | -24.48 QP      |
| 12  | 10.9050 | 0.21  | 9.64   | 9.53  | 19.38 | 50.00 | -30.62 Average |



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12

Measurement Distance: 3m

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C

Humidity: 50.8 % RH


Atmospheric Pressure: 1020 mbar

### 7.2.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



## 7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.




BLE\_1M\_TX\_CH\_00\_Horizontal-Peak



Condition: 3m HORIZONTAL  
Job No : 01879HE  
Mode : 2402 Band edge  
BLE 1M

|      | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark | Aux Factor |
|------|----------|------------|------------|---------------|------------|--------|------------|------------|--------|------------|
|      | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        | dB         |
| 1    | 2309.761 | 6.82       | 27.46      | 31.54         | 46.29      | 49.83  | 74.00      | -24.97     | peak   | 0.00       |
| 2    | 2390.000 | 6.82       | 27.46      | 31.54         | 42.85      | 45.62  | 74.00      | -28.38     | peak   | 0.00       |
| 3 pp | 2402.000 | 6.84       | 27.50      | 31.54         | 94.90      | 97.70  | 74.00      | 23.70      | peak   | 0.00       |


BLE\_1M\_TX\_CH\_00\_Horizontal-AVG



Condition: 3m HORIZONTAL  
Job No : 01879HE  
Mode : 2402 Band edge  
BLE 1M

|      | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  | Aux Factor |
|------|----------|------------|------------|---------------|------------|--------|------------|------------|---------|------------|
|      | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         | dB         |
| 1    | 2309.993 | 6.81       | 27.38      | 31.54         | 38.80      | 41.45  | 54.00      | -12.55     | Average | 0.00       |
| 2    | 2390.000 | 6.82       | 27.46      | 31.54         | 34.06      | 36.88  | 54.00      | -17.12     | Average | 0.00       |
| 3 pp | 2402.000 | 6.84       | 27.50      | 31.54         | 94.23      | 97.03  | 54.00      | 43.03      | Average | 0.00       |


BLE\_1M\_TX\_CH\_00\_Vertical-Peak



Condition: 3m VERTICAL  
Job No : 01879HE  
Mode : 2402 Band edge  
BLE 1M

|      | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark | Aux Factor |
|------|----------|------------|------------|---------------|------------|--------|------------|------------|--------|------------|
|      | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |        | dB         |
| 1    | 2370.294 | 6.82       | 27.38      | 31.54         | 47.59      | 50.25  | 74.00      | -23.75     | peak   | 0.00       |
| 2    | 2390.000 | 6.82       | 27.46      | 31.54         | 47.32      | 50.06  | 74.00      | -23.94     | peak   | 0.00       |
| 3 pp | 2402.000 | 6.84       | 27.50      | 31.54         | 92.53      | 95.33  | 74.00      | 21.33      | peak   | 0.00       |

BLE\_1M\_TX\_CH\_00\_Vertical-AVG




Condition: 3m VERTICAL  
Job No : 01879HE  
Mode : 2402 Band edge  
BLE 1M

|      | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  | Aux Factor |
|------|----------|------------|------------|---------------|------------|--------|------------|------------|---------|------------|
|      | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         | dB         |
| 1    | 2370.093 | 6.82       | 27.38      | 31.54         | 37.27      | 39.93  | 54.00      | -14.07     | Average | 0.00       |
| 2    | 2390.000 | 6.82       | 27.46      | 31.54         | 34.21      | 36.95  | 54.00      | -17.05     | Average | 0.00       |
| 3 pp | 2402.000 | 6.84       | 27.50      | 31.54         | 91.87      | 94.67  | 54.00      | 40.67      | Average | 0.00       |




BLE\_1M\_TX\_CH\_39\_Horizontal-Peak



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 1M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB   |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 93.28         | 96.88      | 74.00  | 22.88  | peak | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 58.38         | 62.03      | 74.00  | -11.97 | peak | 0.00   |            |
| 3 | 2483.821    | 7.40       | 27.80  | 31.55      | 58.40         | 62.05      | 74.00  | -11.95 | peak | 0.00   |            |


BLE\_1M\_TX\_CH\_39\_Horizontal-AVG



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 1M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB      |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 92.54         | 96.14      | 54.00  | 42.14  | Average | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 35.24         | 38.89      | 54.00  | -15.11 | Average | 0.00   |            |
| 3 | 2483.846    | 7.40       | 27.80  | 31.55      | 35.86         | 38.71      | 54.00  | -15.29 | Average | 0.00   |            |


BLE\_1M\_TX\_CH\_39\_Vertical-Peak



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 1M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB   |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 91.67         | 95.27      | 74.00  | 21.27  | peak | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 57.97         | 61.62      | 74.00  | -12.38 | peak | 0.00   |            |
| 3 | 2483.846    | 7.40       | 27.80  | 31.55      | 56.96         | 60.61      | 74.00  | -13.39 | peak | 0.00   |            |

BLE\_1M\_TX\_CH\_39\_Vertical-AVG




Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 1M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB      |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 90.93         | 94.53      | 54.00  | 40.53  | Average | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 34.74         | 38.39      | 54.00  | -15.61 | Average | 0.00   |            |
| 3 | 2483.896    | 7.40       | 27.80  | 31.55      | 34.68         | 38.25      | 54.00  | -15.75 | Average | 0.00   |            |




BLE\_2M\_TX\_CH\_00\_Horizontal-Peak



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2402 Band edge  
BLE 2M

| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB     | dB   |        | dB         |
| 1 2369.993    | 6.81       | 27.38  | 31.54      | 45.69         | 48.34      | 74.00  | -25.66 | peak | 0.00   |            |
| 2 2390.000    | 6.82       | 27.46  | 31.54      | 44.16         | 46.90      | 74.00  | -27.10 | peak | 0.00   |            |
| 3 pp 2402.000 | 6.04       | 27.50  | 31.54      | 94.88         | 97.68      | 74.00  | 23.68  | peak | 0.00   |            |


BLE\_2M\_TX\_CH\_00\_Horizontal-AVG



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2402 Band edge  
BLE 2M

| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB     | dB      |        | dB         |
| 1 2370.194    | 6.82       | 27.38  | 31.54      | 37.66         | 40.32      | 54.00  | -13.68 | Average | 0.00   |            |
| 2 2390.000    | 6.82       | 27.46  | 31.54      | 34.37         | 37.11      | 54.00  | -16.89 | Average | 0.00   |            |
| 3 pp 2402.000 | 6.04       | 27.50  | 31.54      | 93.14         | 95.94      | 54.00  | 41.94  | Average | 0.00   |            |


BLE\_2M\_TX\_CH\_00\_Vertical-Peak



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2402 Band edge  
BLE 2M

| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB     | dB   |        | dB         |
| 1 2338.169    | 6.80       | 27.28  | 31.53      | 47.19         | 49.74      | 74.00  | -24.26 | peak | 0.00   |            |
| 2 2390.000    | 6.82       | 27.46  | 31.54      | 46.13         | 48.87      | 74.00  | -25.13 | peak | 0.00   |            |
| 3 pp 2402.000 | 6.04       | 27.50  | 31.54      | 92.63         | 95.43      | 74.00  | 21.43  | peak | 0.00   |            |

BLE\_2M\_TX\_CH\_00\_Vertical-AVG



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2402 Band edge  
BLE 2M


| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB     | dB      |        | dB         |
| 1 2369.792    | 6.81       | 27.38  | 31.54      | 36.45         | 39.10      | 54.00  | -14.90 | Average | 0.00   |            |
| 2 2390.000    | 6.82       | 27.46  | 31.54      | 34.77         | 37.51      | 54.00  | -16.49 | Average | 0.00   |            |
| 3 pp 2402.000 | 6.04       | 27.50  | 31.54      | 90.86         | 93.66      | 54.00  | 39.66  | Average | 0.00   |            |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


BLE\_2M\_TX\_CH\_39\_Horizontal-Peak



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 2M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB   |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 93.20         | 96.00      | 74.00  | 22.00  | peak | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 57.92         | 61.57      | 74.00  | -12.43 | peak | 0.00   |            |
| 3 | 2483.846    | 7.40       | 27.80  | 31.55      | 57.00         | 60.73      | 74.00  | -13.27 | peak | 0.00   |            |


BLE\_2M\_TX\_CH\_39\_Horizontal-AVG



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 2M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB      |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 91.37         | 94.97      | 54.00  | 40.97  | Average | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 39.67         | 43.52      | 54.00  | -10.48 | Average | 0.00   |            |
| 3 | 2483.846    | 7.40       | 27.80  | 31.55      | 38.15         | 41.00      | 54.00  | -12.20 | Average | 0.00   |            |


BLE\_2M\_TX\_CH\_39\_Vertical-Peak



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 2M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB   |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 91.77         | 95.37      | 74.00  | 21.37  | peak | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 56.24         | 59.89      | 74.00  | -14.11 | peak | 0.00   |            |
| 3 | 2483.921    | 7.40       | 27.80  | 31.55      | 56.00         | 59.65      | 74.00  | -14.35 | peak | 0.00   |            |

BLE\_2M\_TX\_CH\_39\_Vertical-AVG



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 Band edge  
BLE 2M

|   | Freq        | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over    | Remark | Aux Factor |
|---|-------------|------------|--------|------------|---------------|------------|--------|--------|---------|--------|------------|
|   | MHz         | dB         | dB/m   | dB         | dB            | dBuV       | dBuV/m | dBuV/m | dB      |        | dB         |
| 1 | pp 2480.000 | 7.37       | 27.78  | 31.55      | 89.95         | 93.55      | 54.00  | 39.55  | Average | 0.00   |            |
| 2 | 2483.500    | 7.40       | 27.80  | 31.55      | 36.45         | 42.10      | 54.00  | -11.90 | Average | 0.00   |            |
| 3 | 2483.871    | 7.40       | 27.80  | 31.55      | 37.17         | 40.82      | 54.00  | -13.18 | Average | 0.00   |            |



## 7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| 960-1000       | 500                              | 3                            |

### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 46.8 % RH


Atmospheric Pressure: 1020 mbar

### 7.3.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Pre-scan              | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.3.3 Test Setup Diagram



### 7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 02; Polarity: Horizontal




Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : 01079ME  
Test Mode: 02

|      | Ant     | Cable | Preamp | Read  |        | Limit  | Over  |           |
|------|---------|-------|--------|-------|--------|--------|-------|-----------|
| Freq | Factor  | Loss  | Factor | Level | Level  | Line   | Limit | Remark    |
| MHz  | dB/m    | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB    |           |
| 1    | 30.962  | 20.76 | 0.68   | 27.79 | 23.75  | 17.40  | 40.00 | -22.60 QP |
| 2    | 50.057  | 12.75 | 0.86   | 27.73 | 23.68  | 9.56   | 40.00 | -30.44 QP |
| 3    | 229.293 | 16.35 | 1.91   | 27.05 | 22.86  | 14.07  | 46.00 | -31.93 QP |
| 4    | 377.259 | 20.80 | 2.50   | 27.06 | 24.32  | 20.56  | 46.00 | -25.44 QP |
| 5    | 451.135 | 21.19 | 2.76   | 27.36 | 30.97  | 27.56  | 46.00 | -18.44 QP |
| 6 q  | 948.761 | 28.23 | 4.25   | 26.42 | 22.64  | 28.70  | 46.00 | -17.30 QP |



Test Mode: 02; Polarity: Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : 01079ME  
Test Mode: 02

|      | Ant     | Cable | Preamp | Read  |        | Limit  | Over  |           |
|------|---------|-------|--------|-------|--------|--------|-------|-----------|
| Freq | Factor  | Loss  | Factor | Level | Level  | Line   | Limit | Remark    |
| MHz  | dB/m    | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB    |           |
| 1    | 31.289  | 20.60 | 0.69   | 27.79 | 24.37  | 17.87  | 40.00 | -22.13 QP |
| 2    | 86.807  | 11.28 | 1.14   | 27.63 | 25.74  | 10.53  | 40.00 | -29.47 QP |
| 3    | 90.537  | 11.77 | 1.16   | 27.62 | 29.65  | 14.96  | 43.50 | -28.54 QP |
| 4    | 400.432 | 20.60 | 2.58   | 27.16 | 23.70  | 19.72  | 46.00 | -26.28 QP |
| 5    | 684.745 | 25.75 | 3.50   | 27.76 | 25.26  | 26.75  | 46.00 | -19.25 QP |
| 6 q  | 929.008 | 28.16 | 4.20   | 26.56 | 23.71  | 29.51  | 46.00 | -16.49 QP |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12

Measurement Distance: 3m

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| Above 1000     | 500                              | 3                            |

#### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C


Humidity: 50.8 % RH

Atmospheric Pressure: 1020 mbar

#### 7.4.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 7.4.3 Test Setup Diagram



Above 1GHz



## 7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

### Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.




BLE\_1M\_TX\_CH\_00\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01879HE  
Mode : 2402 TX RSE  
BLE 1M

| Freq          | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark | Aux Factor |
|---------------|------------|------------|---------------|------------|--------|--------|--------|--------|------------|
| MHz           | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        | dB         |
| 1 4804.110    | 8.90       | 31.92      | 56.16         | 64.83      | 49.49  | 74.00  | -24.51 | Peak   | 0.00       |
| 2 7200.309    | 11.10      | 36.60      | 56.54         | 55.35      | 46.54  | 74.00  | -27.46 | Peak   | 0.00       |
| 3 11237.330   | 14.30      | 39.64      | 53.57         | 48.57      | 48.94  | 74.00  | -25.06 | Peak   | 0.00       |
| 4 14242.000   | 16.83      | 39.80      | 54.38         | 48.10      | 50.35  | 74.00  | -23.65 | Peak   | 0.00       |
| 5 16908.970   | 18.45      | 39.69      | 54.30         | 46.09      | 49.93  | 74.00  | -24.07 | Peak   | 0.00       |
| 6 pp18000.000 | 18.64      | 43.80      | 54.50         | 44.99      | 52.93  | 74.00  | -21.07 | Peak   | 0.00       |


BLE\_1M\_TX\_CH\_00\_Vertical



Condition: 3m VERTICAL  
Job No : 01879HE  
Mode : 2402 TX RSE  
BLE 1M

| Freq          | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark | Aux Factor |
|---------------|------------|------------|---------------|------------|--------|--------|--------|--------|------------|
| MHz           | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        | dB         |
| 1 4804.110    | 8.90       | 31.92      | 56.16         | 63.48      | 48.14  | 74.00  | -25.86 | Peak   | 0.00       |
| 2 7920.911    | 11.40      | 37.64      | 55.96         | 52.98      | 46.06  | 74.00  | -27.94 | Peak   | 0.00       |
| 3 11172.560   | 14.21      | 39.57      | 53.55         | 48.50      | 48.73  | 74.00  | -25.27 | Peak   | 0.00       |
| 4 13249.930   | 15.91      | 40.25      | 54.48         | 48.76      | 50.44  | 74.00  | -23.56 | Peak   | 0.00       |
| 5 16891.040   | 19.64      | 39.60      | 54.27         | 45.73      | 50.70  | 74.00  | -23.30 | Peak   | 0.00       |
| 6 pp17948.050 | 18.75      | 43.44      | 54.49         | 45.44      | 53.14  | 74.00  | -20.86 | Peak   | 0.00       |


BLE\_1M\_TX\_CH\_19\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01879HE  
Mode : 2440 TX RSE  
BLE 1M

| Freq          | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark | Aux Factor |
|---------------|------------|------------|---------------|------------|--------|--------|--------|--------|------------|
| MHz           | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        | dB         |
| 1 4874.043    | 8.97       | 32.15      | 56.21         | 62.60      | 47.51  | 74.00  | -26.49 | Peak   | 0.00       |
| 2 7943.838    | 11.48      | 37.69      | 55.94         | 53.19      | 46.42  | 74.00  | -27.58 | Peak   | 0.00       |
| 3 10393.710   | 13.50      | 39.00      | 53.86         | 50.56      | 49.20  | 74.00  | -24.80 | Peak   | 0.00       |
| 4 14038.450   | 16.47      | 39.90      | 54.40         | 48.51      | 50.48  | 74.00  | -23.52 | Peak   | 0.00       |
| 5 16891.040   | 19.64      | 39.60      | 54.27         | 45.45      | 50.42  | 74.00  | -23.58 | Peak   | 0.00       |
| 6 pp18000.000 | 18.64      | 43.80      | 54.50         | 45.13      | 53.07  | 74.00  | -20.93 | Peak   | 0.00       |

BLE\_1M\_TX\_CH\_19\_Vertical




Condition: 3m VERTICAL  
Job No : 01879HE  
Mode : 2440 TX RSE  
BLE 1M

| Freq          | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark | Aux Factor |
|---------------|------------|------------|---------------|------------|--------|--------|--------|--------|------------|
| MHz           | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        | dB         |
| 1 4874.043    | 8.97       | 32.15      | 56.21         | 59.88      | 44.79  | 74.00  | -29.21 | Peak   | 0.00       |
| 2 7943.838    | 11.48      | 37.69      | 55.94         | 53.80      | 47.03  | 74.00  | -26.97 | Peak   | 0.00       |
| 3 11076.100   | 14.14      | 39.48      | 53.52         | 49.09      | 49.19  | 74.00  | -24.81 | Peak   | 0.00       |
| 4 14242.000   | 16.83      | 39.80      | 54.38         | 47.53      | 49.78  | 74.00  | -24.22 | Peak   | 0.00       |
| 5 16891.040   | 19.64      | 39.60      | 54.27         | 45.11      | 50.00  | 74.00  | -23.92 | Peak   | 0.00       |
| 6 pp17948.050 | 18.75      | 43.44      | 54.49         | 45.57      | 53.27  | 74.00  | -20.73 | Peak   | 0.00       |




BLE\_1M\_TX\_CH\_39\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 TX RSE  
BLE 1M

| Freq | Cable       | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit  | Over | Aux  |
|------|-------------|-------|--------|-------|--------|-------|--------|--------|------|------|
| MHz  | dB          | dB/m  | dB     | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB   | dB   |
| 1    | 4959.307    | 9.07  | 32.20  | 56.27 | 61.26  | 46.26 | 74.00  | -27.74 | Peak | 0.00 |
| 2    | 7852.524    | 11.36 | 37.41  | 56.02 | 53.93  | 46.68 | 74.00  | -27.32 | Peak | 0.00 |
| 3    | 11975.108   | 14.42 | 39.78  | 53.79 | 48.64  | 49.05 | 74.00  | -24.95 | Peak | 0.00 |
| 4    | 14119.838   | 16.40 | 39.88  | 54.39 | 48.14  | 50.83 | 74.00  | -23.97 | Peak | 0.00 |
| 5    | 16891.040   | 19.64 | 39.60  | 54.27 | 45.78  | 50.75 | 74.00  | -23.25 | Peak | 0.00 |
| 6    | pp18000.000 | 18.64 | 43.80  | 54.50 | 44.84  | 52.78 | 74.00  | -21.22 | Peak | 0.00 |


BLE\_1M\_TX\_CH\_39\_Vertical



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 TX RSE  
BLE 1M

| Freq | Cable       | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit  | Over | Aux  |
|------|-------------|-------|--------|-------|--------|-------|--------|--------|------|------|
| MHz  | dB          | dB/m  | dB     | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB   | dB   |
| 1    | 5904.305    | 10.04 | 33.74  | 56.89 | 54.96  | 41.85 | 74.00  | -32.15 | Peak | 0.00 |
| 2    | 7898.049    | 11.48 | 37.59  | 55.98 | 53.09  | 46.18 | 74.00  | -27.82 | Peak | 0.00 |
| 3    | 10768.540   | 13.51 | 39.34  | 53.64 | 49.58  | 48.71 | 74.00  | -25.29 | Peak | 0.00 |
| 4    | 13288.280   | 15.99 | 40.29  | 54.47 | 47.92  | 49.73 | 74.00  | -24.27 | Peak | 0.00 |
| 5    | 16842.290   | 18.46 | 39.60  | 54.25 | 47.27  | 51.08 | 74.00  | -22.92 | Peak | 0.00 |
| 6    | pp17896.250 | 18.87 | 43.08  | 54.48 | 45.34  | 52.81 | 74.00  | -21.19 | Peak | 0.00 |


BLE\_2M\_TX\_CH\_00\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2402 TX RSE  
BLE 2M

| Freq | Cable       | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit  | Over | Aux  |
|------|-------------|-------|--------|-------|--------|-------|--------|--------|------|------|
| MHz  | dB          | dB/m  | dB     | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB   | dB   |
| 1    | 4804.110    | 8.90  | 31.92  | 56.16 | 65.34  | 50.00 | 74.00  | -24.00 | Peak | 0.00 |
| 2    | 7200.309    | 11.10 | 36.60  | 56.54 | 54.76  | 45.92 | 74.00  | -28.08 | Peak | 0.00 |
| 3    | 11837.450   | 14.61 | 39.64  | 53.75 | 48.36  | 48.06 | 74.00  | -25.94 | Peak | 0.00 |
| 4    | 14242.800   | 16.83 | 39.80  | 54.38 | 47.57  | 49.82 | 74.00  | -24.18 | Peak | 0.00 |
| 5    | 16891.040   | 19.64 | 39.60  | 54.27 | 45.72  | 50.69 | 74.00  | -23.31 | Peak | 0.00 |
| 6    | pp17948.050 | 18.75 | 43.44  | 54.49 | 45.49  | 53.19 | 74.00  | -20.81 | Peak | 0.00 |

BLE\_2M\_TX\_CH\_00\_Vertical




Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2402 TX RSE  
BLE 2M

| Freq | Cable       | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit  | Over | Aux  |
|------|-------------|-------|--------|-------|--------|-------|--------|--------|------|------|
| MHz  | dB          | dB/m  | dB     | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB   | dB   |
| 1    | 4804.110    | 8.90  | 31.92  | 56.16 | 60.62  | 45.28 | 74.00  | -28.72 | Peak | 0.00 |
| 2    | 7943.838    | 11.40 | 37.69  | 55.94 | 52.96  | 46.19 | 74.00  | -27.81 | Peak | 0.00 |
| 3    | 11302.400   | 14.39 | 39.70  | 53.59 | 48.05  | 48.55 | 74.00  | -25.45 | Peak | 0.00 |
| 4    | 14242.800   | 16.83 | 39.80  | 54.38 | 47.03  | 49.28 | 74.00  | -24.72 | Peak | 0.00 |
| 5    | 16891.040   | 19.64 | 39.60  | 54.27 | 45.31  | 50.28 | 74.00  | -23.72 | Peak | 0.00 |
| 6    | pp18000.000 | 18.64 | 43.80  | 54.50 | 45.35  | 53.29 | 74.00  | -20.71 | Peak | 0.00 |




BLE\_2M\_TX\_CH\_19\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2440 TX RSE  
BLE 2M

| Freq          | Cable | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit | Over | Aux |
|---------------|-------|-------|--------|-------|--------|-------|--------|-------|------|-----|
| MHz           | dB    | dB/m  | dB     | dB    | dB     | dB    | dB     | dB    | dB   | dB  |
| 1 4874.043    | 8.97  | 32.15 | 56.21  | 62.47 | 47.38  | 74.00 | -26.62 | Peak  | 0.00 |     |
| 2 7852.524    | 11.36 | 37.41 | 56.02  | 53.70 | 46.45  | 74.00 | -27.55 | Peak  | 0.00 |     |
| 3 11871.718   | 14.63 | 39.67 | 53.76  | 48.38 | 48.92  | 74.00 | -25.08 | Peak  | 0.00 |     |
| 4 13326.758   | 15.92 | 40.30 | 54.47  | 47.89 | 49.64  | 74.00 | -24.36 | Peak  | 0.00 |     |
| 5 16842.290   | 18.64 | 39.60 | 54.25  | 46.27 | 50.08  | 74.00 | -23.92 | Peak  | 0.00 |     |
| 6 pp18000.000 | 18.64 | 43.80 | 54.58  | 45.28 | 53.22  | 74.00 | -20.78 | Peak  | 0.00 |     |


BLE\_2M\_TX\_CH\_19\_Vertical



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2440 TX RSE  
BLE 2M

| Freq          | Cable | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit | Over | Aux |
|---------------|-------|-------|--------|-------|--------|-------|--------|-------|------|-----|
| MHz           | dB    | dB/m  | dB     | dB    | dB     | dB    | dB     | dB    | dB   | dB  |
| 1 4874.043    | 8.97  | 32.15 | 56.21  | 57.87 | 42.78  | 74.00 | -31.22 | Peak  | 0.00 |     |
| 2 7989.893    | 11.46 | 37.78 | 55.91  | 52.98 | 46.31  | 74.00 | -27.69 | Peak  | 0.00 |     |
| 3 10908.470   | 14.10 | 39.30 | 53.51  | 49.40 | 49.37  | 74.00 | -24.63 | Peak  | 0.00 |     |
| 4 14242.000   | 16.83 | 39.00 | 54.38  | 47.21 | 49.46  | 74.00 | -24.54 | Peak  | 0.00 |     |
| 5 16891.040   | 19.64 | 39.60 | 54.27  | 45.19 | 50.16  | 74.00 | -23.84 | Peak  | 0.00 |     |
| 6 pp17896.250 | 18.87 | 43.08 | 54.48  | 45.20 | 52.67  | 74.00 | -21.33 | Peak  | 0.00 |     |


BLE\_2M\_TX\_CH\_39\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2440 TX RSE  
BLE 2M

| Freq          | Cable | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit | Over | Aux |
|---------------|-------|-------|--------|-------|--------|-------|--------|-------|------|-----|
| MHz           | dB    | dB/m  | dB     | dB    | dB     | dB    | dB     | dB    | dB   | dB  |
| 1 4959.307    | 9.07  | 32.20 | 56.27  | 60.47 | 45.47  | 74.00 | -28.53 | Peak  | 0.00 |     |
| 2 7432.914    | 11.10 | 36.77 | 56.35  | 54.66 | 46.18  | 74.00 | -27.82 | Peak  | 0.00 |     |
| 3 11906.070   | 14.62 | 39.71 | 53.77  | 48.20 | 48.76  | 74.00 | -25.24 | Peak  | 0.00 |     |
| 4 13211.698   | 15.84 | 40.21 | 54.48  | 48.66 | 50.23  | 74.00 | -23.77 | Peak  | 0.00 |     |
| 5 16891.040   | 19.64 | 39.60 | 54.27  | 46.37 | 51.34  | 74.00 | -22.66 | Peak  | 0.00 |     |
| 6 pp18000.000 | 18.64 | 43.80 | 54.58  | 44.78 | 52.72  | 74.00 | -21.28 | Peak  | 0.00 |     |

BLE\_2M\_TX\_CH\_39\_Vertical




Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2440 TX RSE  
BLE 2M

| Freq          | Cable | Loss  | Factor | Ant   | Preamp | Read  | Level  | Limit | Over | Aux |
|---------------|-------|-------|--------|-------|--------|-------|--------|-------|------|-----|
| MHz           | dB    | dB/m  | dB     | dB    | dB     | dB    | dB     | dB    | dB   | dB  |
| 1 5904.305    | 10.04 | 33.74 | 56.89  | 55.23 | 42.12  | 74.00 | -31.88 | Peak  | 0.00 |     |
| 2 7920.911    | 11.40 | 37.64 | 55.96  | 53.40 | 46.64  | 74.00 | -27.36 | Peak  | 0.00 |     |
| 3 11467.000   | 14.19 | 39.63 | 53.64  | 49.34 | 49.52  | 74.00 | -24.48 | Peak  | 0.00 |     |
| 4 14242.000   | 16.83 | 39.00 | 54.38  | 47.02 | 49.27  | 74.00 | -24.73 | Peak  | 0.00 |     |
| 5 16891.040   | 19.64 | 39.60 | 54.27  | 44.09 | 49.86  | 74.00 | -24.14 | Peak  | 0.00 |     |
| 6 pp17948.050 | 18.75 | 43.44 | 54.49  | 45.40 | 53.10  | 74.00 | -20.90 | Peak  | 0.00 |     |




BLE\_1M\_TX\_CH\_00\_Horizontal



Condition: 3m HORIZONTAL  
Job No : 01079ME  
Mode : 2400 TX RSE  
BLE 1M

| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|------------|------------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB         |            |        | dB         |
| 1 pp23572.330 | 6.76       | 38.45  | 50.31      | 52.97         | 38.33      | 74.00  | -35.67     | Peak       |        | -9.54      |

BLE\_1M\_TX\_CH\_00\_Vertical



Condition: 3m VERTICAL  
Job No : 01079ME  
Mode : 2400 TX RSE  
BLE 1M

| Freq          | Cable Loss | Factor | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark | Aux Factor |
|---------------|------------|--------|------------|---------------|------------|--------|------------|------------|--------|------------|
| MHz           | dB         | dB/m   | dB         | dBuV          | dBuV/m     | dBuV/m | dB         |            |        | dB         |
| 1 pp23611.000 | 6.76       | 38.52  | 50.32      | 52.40         | 37.82      | 74.00  | -36.18     | Peak       |        | -9.54      |

## 7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.1

Limit:

| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--------------------------------------------------------|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C

Humidity: 47.0 % RH


Atmospheric Pressure: 1020 mbar

### 7.5.1 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

Please Refer to Appendix for Details



### 7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
 Test Method: ANSI C63.10 (2020) Section 11.8.1  
 Limit:  $\geq 500$  kHz


#### 7.6.1 E.U.T. Operation

Operating Environment:  
 Temperature: 23.3 °C Humidity: 47.0 % RH Atmospheric Pressure: 1020 mbar

#### 7.6.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 7.6.3 Test Setup Diagram



#### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

### 7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.3

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

#### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C


Humidity: 47.0 % RH

Atmospheric Pressure: 1020 mbar

#### 7.7.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 7.7.3 Test Setup Diagram



#### 7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



## 7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C

Humidity: 47.0 % RH


Atmospheric Pressure: 1020 mbar

### 7.8.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.8.3 Test Setup Diagram



### 7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C

Humidity: 47.0 % RH


Atmospheric Pressure: 1020 mbar

### 7.9.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                               |
|-----------------------|-----------|-----------------------------------------------------------------------------------------------------------|
| Pre-scan              | 00        | TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Pre-scan              | 01        | TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 02        | Charge + TX mode(1Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 03        | Charge + TX mode(2Mbps)_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.9.3 Test Setup Diagram



### 7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

## 8 Test Setup Photo

Refer to Setup Photo for SZCR2503001079ME

## 9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2503001079ME



## 10 Appendix

### 1. Duty Cycle

#### 1.1 Test Result



##### 1.1.1 Ant1

| Ant1 |         |                 |           |             |                |                                   |                       |
|------|---------|-----------------|-----------|-------------|----------------|-----------------------------------|-----------------------|
| Mode | TX Type | Frequency (MHz) | T_on (ms) | Period (ms) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | Max. DC Variation (%) |
| 1M   | SISO    | 2402            | 0.396     | 0.625       | 63.36          | 1.98                              | 0.00                  |
|      |         | 2440            | 0.396     | 0.625       | 63.36          | 1.98                              | 0.00                  |
|      |         | 2480            | 0.395     | 0.625       | 63.20          | 1.99                              | 0.03                  |
| 2M   | SISO    | 2402            | 0.209     | 0.625       | 33.44          | 4.76                              | 0.00                  |
|      |         | 2440            | 0.210     | 0.625       | 33.60          | 4.74                              | 0.00                  |
|      |         | 2480            | 0.210     | 0.625       | 33.60          | 4.74                              | 0.00                  |




### 1.2 Test Graph


#### 1.2.1 Ant1




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV



2M\_MCH\_2440MHz\_Ant1\_NTNV



2M\_HCH\_2480MHz\_Ant1\_NTNV



## 2. Bandwidth

### 2.1 Test Result

#### 2.1.1 OBW(Report only)



| Mode | TX Type | Frequency (MHz) | ANT | 99% Occupied Bandwidth (MHz) |       | Verdict |
|------|---------|-----------------|-----|------------------------------|-------|---------|
|      |         |                 |     | Result                       | Limit |         |
| 1M   | SISO    | 2402            | 1   | 1.053                        | /     | Pass    |
|      |         | 2440            | 1   | 1.057                        | /     | Pass    |
|      |         | 2480            | 1   | 1.058                        | /     | Pass    |
| 2M   | SISO    | 2402            | 1   | 2.082                        | /     | Pass    |
|      |         | 2440            | 1   | 2.086                        | /     | Pass    |
|      |         | 2480            | 1   | 2.089                        | /     | Pass    |

#### 2.1.2 6dB BW


| Mode | TX Type | Frequency (MHz) | ANT | 6dB Bandwidth (MHz) |            | Verdict |
|------|---------|-----------------|-----|---------------------|------------|---------|
|      |         |                 |     | Result              | Limit      |         |
| 1M   | SISO    | 2402            | 1   | 0.693               | $\geq 0.5$ | Pass    |
|      |         | 2440            | 1   | 0.696               | $\geq 0.5$ | Pass    |
|      |         | 2480            | 1   | 0.697               | $\geq 0.5$ | Pass    |
| 2M   | SISO    | 2402            | 1   | 1.147               | $\geq 0.5$ | Pass    |
|      |         | 2440            | 1   | 1.162               | $\geq 0.5$ | Pass    |
|      |         | 2480            | 1   | 1.158               | $\geq 0.5$ | Pass    |

### 2.2 Test Graph


#### 2.2.1 OBW




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV





2M\_MCH\_2440MHz\_Ant1\_NTNV




2M\_HCH\_2480MHz\_Ant1\_NTNV




### 2.2.2 6dB BW




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV



2M\_MCH\_2440MHz\_Ant1\_NTNV



2M\_HCH\_2480MHz\_Ant1\_NTNV



## 3. Maximum Conducted Output Power

### 3.1 Test Result

#### 3.1.1 Power

| Mode | TX Type | Frequency (MHz) | Maximum Peak Conducted Output Power (dBm) |       | Verdict |
|------|---------|-----------------|-------------------------------------------|-------|---------|
|      |         |                 | ANT1                                      | Limit |         |
| 1M   | SISO    | 2402            | 3.53                                      | <=30  | Pass    |
|      |         | 2440            | 3.49                                      | <=30  | Pass    |
|      |         | 2480            | 3.46                                      | <=30  | Pass    |
| 2M   | SISO    | 2402            | 3.54                                      | <=30  | Pass    |
|      |         | 2440            | 3.51                                      | <=30  | Pass    |
|      |         | 2480            | 3.49                                      | <=30  | Pass    |

## 4. Maximum Power Spectral Density



### 4.1 Test Result

#### 4.1.1 PSD


| Mode | TX Type | Frequency (MHz) | Maximum PSD (dBm/3kHz) |       | Verdict |
|------|---------|-----------------|------------------------|-------|---------|
|      |         |                 | ANT1                   | Limit |         |
| 1M   | SISO    | 2402            | -11.99                 | <=8   | Pass    |
|      |         | 2440            | -11.97                 | <=8   | Pass    |
|      |         | 2480            | -12.07                 | <=8   | Pass    |
| 2M   | SISO    | 2402            | -14.48                 | <=8   | Pass    |
|      |         | 2440            | -14.53                 | <=8   | Pass    |
|      |         | 2480            | -14.45                 | <=8   | Pass    |

### 4.2 Test Graph


#### 4.2.1 PSD




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV



2M\_MCH\_2440MHz\_Ant1\_NTNV



2M\_HCH\_2480MHz\_Ant1\_NTNV



## 5. Unwanted Emissions In Non-restricted Frequency Bands

### 5.1 Test Result

#### 5.1.1 Ref

| Mode | TX Type | Frequency (MHz) | ANT | Level of Reference (dBm) |
|------|---------|-----------------|-----|--------------------------|
| 1M   | SISO    | 2402            | 1   | 3.44                     |
|      |         | 2440            | 1   | 3.40                     |
|      |         | 2480            | 1   | 3.38                     |
| 2M   | SISO    | 2402            | 1   | 3.43                     |
|      |         | 2440            | 1   | 3.39                     |
|      |         | 2480            | 1   | 3.40                     |

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

#### 5.1.2 CSE



| Mode | TX Type | Frequency (MHz) | ANT | Level of Reference (dBm) | Limit (dBm) | Verdict |
|------|---------|-----------------|-----|--------------------------|-------------|---------|
| 1M   | SISO    | 2402            | 1   | 3.44                     | -16.56      | Pass    |
|      |         | 2440            | 1   | 3.44                     | -16.56      | Pass    |
|      |         | 2480            | 1   | 3.44                     | -16.56      | Pass    |
| 2M   | SISO    | 2402            | 1   | 3.43                     | -16.57      | Pass    |
|      |         | 2440            | 1   | 3.43                     | -16.57      | Pass    |
|      |         | 2480            | 1   | 3.43                     | -16.57      | Pass    |

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.




### 5.2 Test Graph


#### 5.2.1 Ref




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV





2M\_MCH\_2440MHz\_Ant1\_NTNV




2M\_HCH\_2480MHz\_Ant1\_NTNV




### 5.2.2 CSE




### 1M\_MCH\_2440MHz\_Ant1\_NTNV




### 1M\_HCH\_2480MHz\_Ant1\_NTNV




1M\_HCH\_2480MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV




2M\_LCH\_2402MHz\_Ant1\_NTNV




2M\_MCH\_2440MHz\_Ant1\_NTNV



2M\_HCH\_2480MHz\_Ant1\_NTNV



2M\_HCH\_2480MHz\_Ant1\_NTNV





## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250300107902

Page: 66 of 66

- End of the Report -



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (CSTC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 [www.sgsgroup.com.cn](http://www.sgsgroup.com.cn)  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

Member of the SGS Group (SGS SA)