



**FCC ID: 2AS3LX2**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT-EDR

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculatio n | SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|---------------------|-------------------------|--------------------|
| GFSK       | 2.402               | -1.09                  | 0.78                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49127             | 3.00                    | YES                |
|            | 2.441               | -0.14                  | 0.97                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49524             | 3.00                    | YES                |
|            | 2.480               | 1.93                   | 1.56                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49918             | 3.00                    | YES                |
| Pi/4 DQPSK | 2.402               | -3.14                  | 0.49                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49127             | 3.00                    | YES                |
|            | 2.441               | 0.01                   | 1.00                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49524             | 3.00                    | YES                |
|            | 2.480               | -0.26                  | 0.94                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49918             | 3.00                    | YES                |
| 8DPSK      | 2.402               | -2.77                  | 0.53                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49127             | 3.00                    | YES                |
|            | 2.441               | 0.70                   | 1.17                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49524             | 3.00                    | YES                |
|            | 2.480               | 0.43                   | 1.10                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49918             | 3.00                    | YES                |

**Conclusion:**

For the max result :  $0.49918 \leq \text{FCC Limit } 3.0$  for 1g SAR.