

## TEST REPORT

**Product** : Lightweight TWS Earphones  
**Trade mark** : MINISO  
**Model/Type reference** : X16  
**Serial Number** : N/A  
**Report Number** : EED32N80941101  
**FCC ID** : 2AS5O-X16  
**Date of Issue** : Oct. 28 2021  
**Test Standards** : 47 CFR Part 15 Subpart C  
**Test result** : PASS

Prepared for:

**China Etech Groups Ltd**  
**16/F, Block C, 2nd Phase of Central Avenue,**  
**Haihong Industrial Area, Xixiang Road,**  
**Baoan District, Shenzhen, China**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**



Compiled by:

*Martin Lee*

Martin Lee

Approved by:

*David Wang*

David Wang

Reviewed by:

*Aaron Ma*

Aaron Ma

Date:

Oct. 28, 2021

Check No.: 8310260921

# 1 Contents

|                                                               | Page      |
|---------------------------------------------------------------|-----------|
| <b>1 CONTENTS.....</b>                                        | <b>2</b>  |
| <b>2 VERSION.....</b>                                         | <b>3</b>  |
| <b>3 TEST SUMMARY.....</b>                                    | <b>4</b>  |
| <b>4 GENERAL INFORMATION.....</b>                             | <b>5</b>  |
| 4.1 CLIENT INFORMATION.....                                   | 5         |
| 4.2 GENERAL DESCRIPTION OF EUT.....                           | 5         |
| 4.3 TEST CONFIGURATION.....                                   | 7         |
| 4.4 TEST ENVIRONMENT.....                                     | 7         |
| 4.5 DESCRIPTION OF SUPPORT UNITS.....                         | 7         |
| 4.6 TEST LOCATION.....                                        | 8         |
| 4.7 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)..... | 8         |
| 4.8 EQUIPMENT LIST.....                                       | 9         |
| <b>5 TEST RESULTS AND MEASUREMENT DATA.....</b>               | <b>11</b> |
| 5.1 ANTENNA REQUIREMENT.....                                  | 11        |
| 5.2 MAXIMUM CONDUCTED OUTPUT POWER.....                       | 12        |
| 5.3 20DB EMISSION BANDWIDTH.....                              | 13        |
| 5.4 CARRIER FREQUENCY SEPARATION.....                         | 14        |
| 5.5 NUMBER OF HOPPING CHANNEL.....                            | 15        |
| 5.6 TIME OF OCCUPANCY.....                                    | 16        |
| 5.7 BAND EDGE MEASUREMENTS.....                               | 17        |
| 5.8 CONDUCTED SPURIOUS EMISSIONS.....                         | 18        |
| 5.9 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....              | 19        |
| 5.10 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS.....       | 21        |
| <b>6 APPENDIX A.....</b>                                      | <b>43</b> |
| <b>PHOTOGRAPHS OF TEST SETUP.....</b>                         | <b>44</b> |
| <b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....</b>         | <b>45</b> |

## 2 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | Oct. 28, 2021 | Original    |
|             |               |             |
|             |               |             |

### 3 Test Summary

| Test Item                                     | Test Requirement                                    | Result |
|-----------------------------------------------|-----------------------------------------------------|--------|
| Antenna Requirement                           | 47 CFR Part 15, Subpart C Section 15.203/15.247 (c) | PASS   |
| AC Power Line Conducted Emission              | 47 CFR Part 15, Subpart C Section 15.207            | N/A    |
| Maximum Conducted Output Power                | 47 CFR Part 15, Subpart C Section 15.247 (b)(1)     | PASS   |
| 20dB Emission Bandwidth                       | 47 CFR Part 15, Subpart C Section 15.247 (a)(1)     | PASS   |
| Carrier Frequency Separation                  | 47 CFR Part 15, Subpart C Section 15.247 (a)(1)     | PASS   |
| Number of Hopping Channels                    | 47 CFR Part 15, Subpart C Section 15.247 (a)(1)     | PASS   |
| Time of Occupancy                             | 47 CFR Part 15, Subpart C Section 15.247 (a)(1)     | PASS   |
| Pseudorandom Frequency Hopping Sequence       | 47 CFR Part 15, Subpart C Section 15.247(b)(4)      | PASS   |
| Band Edge Measurements                        | 47 CFR Part 15, Subpart C Section 15.247(d)         | PASS   |
| Conducted Spurious Emissions                  | 47 CFR Part 15, Subpart C Section 15.247(d)         | PASS   |
| Radiated Spurious emissions                   | 47 CFR Part 15, Subpart C Section 15.205/15.209     | PASS   |
| Restricted bands around fundamental frequency | 47 CFR Part 15, Subpart C Section 15.205/15.209     | PASS   |

N/A: When the EUT charging, BT will not work , So Not Applicable.

Remark:

Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

## 4 General Information

### 4.1 Client Information

|                          |                                                                                                                    |
|--------------------------|--------------------------------------------------------------------------------------------------------------------|
| Applicant:               | China Etech Groups Ltd                                                                                             |
| Address of Applicant:    | 16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang Road, Baoan District, Shenzhen, China |
| Manufacturer:            | China Etech Groups Ltd                                                                                             |
| Address of Manufacturer: | 16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang Road, Baoan District, Shenzhen, China |
| Factory:                 | Dongguan China ETECH GROUPS CO.,LTD.                                                                               |
| Address of Factory:      | Room 501,Building 6, No.2 Hong Jin Road, Li Zhou Jiao Village, Hongmei Town, Dongguan City                         |

### 4.2 General Description of EUT

|                                                                                                                         |                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Product Name:                                                                                                           | Lightweight TWS Earphones                                                                                          |
| Mode No.:                                                                                                               | X16                                                                                                                |
| Trade mark:                                                                                                             | MINISO                                                                                                             |
| Bluetooth Version:                                                                                                      | V5.0                                                                                                               |
| Operation Frequency:                                                                                                    | 2402MHz~2480MHz                                                                                                    |
| Modulation Technique:                                                                                                   | Frequency Hopping Spread Spectrum(FHSS)                                                                            |
| Modulation Type:                                                                                                        | GFSK, $\pi/4$ DQPSK, 8DPSK                                                                                         |
| Number of Channel:                                                                                                      | 79                                                                                                                 |
| Hopping Channel Type:                                                                                                   | Adaptive Frequency Hopping systems                                                                                 |
| Product Type:                                                                                                           | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location |
| Antenna Type:                                                                                                           | PCB antenna                                                                                                        |
| Antenna Gain:                                                                                                           | 0dBi                                                                                                               |
| Power Supply:                                                                                                           | lithium battery: DC 3.7V, Charge by DC 5.0V                                                                        |
| Test Voltage:                                                                                                           | DC 3.7V                                                                                                            |
| Sample Received Date:                                                                                                   | Sep. 27, 2021                                                                                                      |
| Sample tested Date:                                                                                                     | Sep. 27, 2021 to Oct. 12, 2021                                                                                     |
| Note: Since the RF parameters of the left and right earplugs are the same, only the left ear was tested in this report. |                                                                                                                    |

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 0                                   | 2402MHz   | 20      | 2422MHz   | 40      | 2442MHz   | 60      | 2462MHz   |
| 1                                   | 2403MHz   | 21      | 2423MHz   | 41      | 2443MHz   | 61      | 2463MHz   |
| 2                                   | 2404MHz   | 22      | 2424MHz   | 42      | 2444MHz   | 62      | 2464MHz   |
| 3                                   | 2405MHz   | 23      | 2425MHz   | 43      | 2445MHz   | 63      | 2465MHz   |
| 4                                   | 2406MHz   | 24      | 2426MHz   | 44      | 2446MHz   | 64      | 2466MHz   |
| 5                                   | 2407MHz   | 25      | 2427MHz   | 45      | 2447MHz   | 65      | 2467MHz   |
| 6                                   | 2408MHz   | 26      | 2428MHz   | 46      | 2448MHz   | 66      | 2468MHz   |
| 7                                   | 2409MHz   | 27      | 2429MHz   | 47      | 2449MHz   | 67      | 2469MHz   |
| 8                                   | 2410MHz   | 28      | 2430MHz   | 48      | 2450MHz   | 68      | 2470MHz   |
| 9                                   | 2411MHz   | 29      | 2431MHz   | 49      | 2451MHz   | 69      | 2471MHz   |
| 10                                  | 2412MHz   | 30      | 2432MHz   | 50      | 2452MHz   | 70      | 2472MHz   |
| 11                                  | 2413MHz   | 31      | 2433MHz   | 51      | 2453MHz   | 71      | 2473MHz   |
| 12                                  | 2414MHz   | 32      | 2434MHz   | 52      | 2454MHz   | 72      | 2474MHz   |
| 13                                  | 2415MHz   | 33      | 2435MHz   | 53      | 2455MHz   | 73      | 2475MHz   |
| 14                                  | 2416MHz   | 34      | 2436MHz   | 54      | 2456MHz   | 74      | 2476MHz   |
| 15                                  | 2417MHz   | 35      | 2437MHz   | 55      | 2457MHz   | 75      | 2477MHz   |
| 16                                  | 2418MHz   | 36      | 2438MHz   | 56      | 2458MHz   | 76      | 2478MHz   |
| 17                                  | 2419MHz   | 37      | 2439MHz   | 57      | 2459MHz   | 77      | 2479MHz   |
| 18                                  | 2420MHz   | 38      | 2440MHz   | 58      | 2460MHz   | 78      | 2480MHz   |
| 19                                  | 2421MHz   | 39      | 2441MHz   | 59      | 2461MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel             | Frequency |
|---------------------|-----------|
| The Lowest channel  | 2402MHz   |
| The Middle channel  | 2441MHz   |
| The Highest channel | 2480MHz   |

### 4.3 Test Configuration

| EUT Test Software Settings:                                                                                                 |                                                                                    |                |
|-----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|----------------|
| Software:                                                                                                                   | BT_Tool (manufacturer declare)                                                     |                |
| EUT Power Grade:                                                                                                            | Class2 (Power level is built-in set parameters and cannot be changed and selected) |                |
| Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. |                                                                                    |                |
| Mode                                                                                                                        | Channel                                                                            | Frequency(MHz) |
| DH1/DH3/DH5                                                                                                                 | CH0                                                                                | 2402           |
|                                                                                                                             | CH39                                                                               | 2441           |
|                                                                                                                             | CH78                                                                               | 2480           |
| 2DH1/2DH3/2DH5                                                                                                              | CH0                                                                                | 2402           |
|                                                                                                                             | CH39                                                                               | 2441           |
|                                                                                                                             | CH78                                                                               | 2480           |
| 3DH1/3DH3/3DH5                                                                                                              | CH0                                                                                | 2402           |
|                                                                                                                             | CH39                                                                               | 2441           |
|                                                                                                                             | CH78                                                                               | 2480           |

### 4.4 Test Environment

| Operating Environment:       |            |
|------------------------------|------------|
| Radiated Spurious Emissions: |            |
| Temperature:                 | 22~25.0 °C |
| Humidity:                    | 50~55 % RH |
| Atmospheric Pressure:        | 1010mbar   |
| RF Conducted:                |            |
| Temperature:                 | 22~25.0 °C |
| Humidity:                    | 50~55 % RH |
| Atmospheric Pressure:        | 1010mbar   |

### 4.5 Description of Support Units

The EUT has been tested with associated equipment below.  
support equipment

| Description | Manufacturer | Model No. | Certification  | Supplied by |
|-------------|--------------|-----------|----------------|-------------|
| Notebook    | DELL         | DELL 3490 | FCC ID and DOC | CTI         |

#### 4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

#### 4.7 Measurement Uncertainty (95% confidence levels, k=2)

| No. | Item                            | Measurement Uncertainty |
|-----|---------------------------------|-------------------------|
| 1   | Radio Frequency                 | $7.9 \times 10^{-8}$    |
| 2   | RF power, conducted             | 0.46dB (30MHz-1GHz)     |
|     |                                 | 0.55dB (1GHz-18GHz)     |
| 3   | Radiated Spurious emission test | 3.3dB (9kHz-30MHz)      |
|     |                                 | 4.3dB (30MHz-1GHz)      |
|     |                                 | 4.5dB (1GHz-18GHz)      |
|     |                                 | 3.4dB (18GHz-40GHz)     |
| 4   | Conduction emission             | 3.5dB (9kHz to 150kHz)  |
|     |                                 | 3.1dB (150kHz to 30MHz) |
| 5   | Temperature test                | 0.64°C                  |
| 6   | Humidity test                   | 3.8%                    |
| 7   | DC power voltages               | 0.026%                  |

## 4.8 Equipment List

| RF test system                   |               |                              |               |                        |                            |
|----------------------------------|---------------|------------------------------|---------------|------------------------|----------------------------|
| Equipment                        | Manufacturer  | Mode No.                     | Serial Number | Cal. Date (mm-dd-yyyy) | Cal. Due date (mm-dd-yyyy) |
| Spectrum Analyzer                | Keysight      | N9010A                       | MY54510339    | 12-28-2020             | 12-27-2021                 |
| Signal Generator                 | Keysight      | N5182B                       | MY53051549    | 12-28-2020             | 12-27-2021                 |
| Temperature/ Humidity Indicator  | biaozhi       | HM10                         | 1804186       | 06-23-2021             | 06-22-2022                 |
| High-pass filter                 | Sinoscite     | FL3CX03WG18<br>NM12-0398-002 | ---           | ---                    | ---                        |
| High-pass filter                 | MICRO-TRONICS | SPA-F-63029-4                | ---           | ---                    | ---                        |
| DC Power                         | Keysight      | E3642A                       | MY56376072    | 12-28-2020             | 12-27-2021                 |
| PC-1                             | Lenovo        | R4960d                       | ---           | ---                    | ---                        |
| Power unit                       | R&S           | OSP120                       | 101374        | 12-28-2020             | 12-27-2021                 |
| RF control unit                  | JS Tonscend   | JS0806-2                     | 158060006     | 12-28-2020             | 12-27-2021                 |
| BT&WI-FI Automatic test software | JS Tonscend   | JS1120-3                     | ---           | ---                    | ---                        |

| 3M Semi/full-anechoic Chamber    |                  |                      |               |                        |                            |
|----------------------------------|------------------|----------------------|---------------|------------------------|----------------------------|
| Equipment                        | Manufacturer     | Model No.            | Serial Number | Cal. date (mm-dd-yyyy) | Cal. Due date (mm-dd-yyyy) |
| 3M Chamber & Accessory Equipment | TDK              | SAC-3                | ---           | 05-24-2019             | 05-23-2022                 |
| TRILOG Broadband Antenna         | Schwarzbeck      | VULB9163             | 9163-618      | 05-16-2021             | 05-15-2022                 |
| Loop Antenna                     | Schwarzbeck      | FMZB 1519B           | 1519B-076     | 04-15-2021             | 04-14-2024                 |
| Receiver                         | R&S              | ESC17                | 100938-003    | 10-16-2020             | 10-15-2021                 |
| Multi device Controller          | maturo           | NCD/070/10711<br>112 | ---           | ---                    | ---                        |
| Temperature/ Humidity Indicator  | Shanghai qixiang | HM10                 | 1804298       | 06-24-2021             | 06-23-2022                 |
| Cable line                       | Fulai(7M)        | SF106                | 5219/6A       | ---                    | ---                        |
| Cable line                       | Fulai(6M)        | SF106                | 5220/6A       | ---                    | ---                        |
| Cable line                       | Fulai(3M)        | SF106                | 5216/6A       | ---                    | ---                        |
| Cable line                       | Fulai(3M)        | SF106                | 5217/6A       | ---                    | ---                        |


| 3M full-anechoic Chamber        |              |                   |               |                        |                            |
|---------------------------------|--------------|-------------------|---------------|------------------------|----------------------------|
| Equipment                       | Manufacturer | Model No.         | Serial Number | Cal. date (mm-dd-yyyy) | Cal. Due date (mm-dd-yyyy) |
| RSE Automatic test software     | JS Tonscend  | JS36-RSE          | 10166         | ---                    | ---                        |
| Receiver                        | Keysight     | N9038A            | MY57290136    | 03-04-2021             | 03-03-2022                 |
| Spectrum Analyzer               | Keysight     | N9020B            | MY57111112    | 03-04-2021             | 03-03-2022                 |
| Spectrum Analyzer               | Keysight     | N9030B            | MY57140871    | 03-04-2021             | 03-03-2022                 |
| TRILOG Broadband Antenna        | Schwarzbeck  | VULB 9163         | 9163-1148     | 04-28-2021             | 04-27-2024                 |
| Horn Antenna                    | Schwarzbeck  | BBHA 9170         | 9170-832      | 04-15-2021             | 04-14-2024                 |
| Horn Antenna                    | ETS-LINDGREN | 3117              | 00057407      | 07-04-2021             | 07-03-2024                 |
| Preamplifier                    | EMCI         | EMC184055SE       | 980597        | 05-20-2021             | 05-19-2022                 |
| Preamplifier                    | EMCI         | EMC001330         | 980563        | 04-15-2021             | 04-14-2022                 |
| Preamplifier                    | JS Tonscend  | 980380            | EMC051845 SE  | 12-31-2020             | 12-30-2021                 |
| Temperature/ Humidity Indicator | biaozhi      | GM1360            | EE1186631     | 04-16-2021             | 04-15-2022                 |
| Fully Anechoic Chamber          | TDK          | FAC-3             | ---           | 01-09-2021             | 01-08-2024                 |
| Cable line                      | Times        | SFT205-NMSM-2.50M | 394812-0001   | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMSM-2.50M | 394812-0002   | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMSM-2.50M | 394812-0003   | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMSM-2.50M | 393495-0001   | ---                    | ---                        |
| Cable line                      | Times        | EMC104-NMNM-1000  | SN160710      | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMSM-3.00M | 394813-0001   | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMNM-1.50M | 381964-0001   | ---                    | ---                        |
| Cable line                      | Times        | SFT205-NMSM-7.00M | 394815-0001   | ---                    | ---                        |
| Cable line                      | Times        | HF160-KMKM-3.00M  | 393493-0001   | ---                    | ---                        |

## 5 Test results and Measurement Data


### 5.1 Antenna Requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 47 CFR Part 15C Section 15.203 /247(c) |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:<br/>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> |                                        |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Please see Internal photos             |
| The antenna is PCB antenna. The best case gain of the antenna is 0dBi.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                        |


## 5.2 Maximum Conducted Output Power

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (b)(1)                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Method:           | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Test Setup:            |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                               |
| Test Procedure:        | <p>Use the following spectrum analyzer settings:</p> <p>Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</p> <p>RBW &gt; the 20 dB bandwidth of the emission being measured</p> <p>VBW ≥ RBW</p> <p>Sweep = auto</p> <p>Detector function = peak</p> <p>Trace = max hold</p> <p>Allow the trace to stabilize.</p> <p>Use the marker-to-peak function to set the marker to the peak of the emission.</p> |
| Limit:                 | 21dBm                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                                                                         |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                                                                           |
| Test Results:          | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                    |


### 5.3 20dB Emission Bandwidth

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test Method:           | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Setup:            |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Procedure:        | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.<br/>Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel; <math>1\% \leq RBW \leq 5\%</math> of the 20 dB bandwidth; <math>VBW \geq 3RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold.</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| Limit:                 | NA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Results:          | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |


## 5.4 Carrier Frequency Separation

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Test Method:           | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test Setup:            |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Procedure:        | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings:<br/>Span = wide enough to capture the peaks of two adjacent channels; RBW is set to approximately 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel;<br/>VBW<math>\geq</math>RBW; Sweep = auto;<br/>Detector function = peak; Trace = max hold.</li> <li>5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.<br/>Record the value in report.</li> </ol> |
| Limit:                 | Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Exploratory Test Mode: | Hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Results:          | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |


## 5.5 Number of Hopping Channel

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings: Span = the frequency band of operation; set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller; VBW≥RBW; Sweep= auto; Detector function = peak; Trace = max hold.</li> <li>5. The number of hopping frequency used is defined as the number of total channel.</li> <li>6. Record the measurement data in report.</li> </ol> |
| Limit:            | Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Test Mode:        | Hopping transmitting with all kind of modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Results:     | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |


## 5.6 Time of Occupancy

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Enable the EUT hopping function.</li> <li>4. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW shall be <math>\leq</math> channel spacing and where possible RBW should be set <math>\gg 1/T</math>, where T is the expected dwell time per channel; VBW <math>\geq</math> RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.</li> <li>5. Measure and record the results in the test report.</li> </ol> |
| Limit:            | The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Mode:        | Hopping transmitting with all kind of modulation and all kind of data type.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test Results:     | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## 5.7 Band edge Measurements

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Test Method:           | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Setup:            |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Test Procedure:        | <ol style="list-style-type: none"> <li>1. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>2. Set RBW = 100 kHz, VBW = 300 kHz (<math>\geq</math>RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.</li> <li>3. Enable hopping function of the EUT and then repeat step 2 and 3.</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.                                                                                                                                                                                                       |
| Exploratory Test Mode: | Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                                                                                                                                                                                                                                  |
| Test Results:          | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## 5.8 Conducted Spurious Emissions

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Test Method:           | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Setup:            |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Procedure:        | <ol style="list-style-type: none"> <li>1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW.</li> <li>4. Measure and record the results in the test report.</li> <li>5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol> |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.                                                                                                                                                                                                                                                                                                                           |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Test Results:          | Refer to Appendix A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## 5.9 Pseudorandom Frequency Hopping Sequence

### Test Requirement:

### 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### Compliance for section 15.247(a)(1)


According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



### Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

### Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

**Compliance for section 15.247(h)**

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

## 5.10 Radiated Spurious Emission & Restricted bands

|                   |                                                                                                                                                                                                                                                                             |                                     |                   |            |                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------|------------|-----------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205                                                                                                                                                                                                                                   |                                     |                   |            |                             |
| Test Method:      | ANSI C63.10: 2013                                                                                                                                                                                                                                                           |                                     |                   |            |                             |
| Test Site:        | Measurement Distance: 3m (Semi-Anechoic Chamber)                                                                                                                                                                                                                            |                                     |                   |            |                             |
| Receiver Setup:   | Frequency                                                                                                                                                                                                                                                                   | Detector                            | RBW               | VBW        | Remark                      |
|                   | 0.009MHz-0.090MHz                                                                                                                                                                                                                                                           | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                   | 0.009MHz-0.090MHz                                                                                                                                                                                                                                                           | Average                             | 10kHz             | 30kHz      | Average                     |
|                   | 0.090MHz-0.110MHz                                                                                                                                                                                                                                                           | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                   | 0.110MHz-0.490MHz                                                                                                                                                                                                                                                           | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                   | 0.110MHz-0.490MHz                                                                                                                                                                                                                                                           | Average                             | 10kHz             | 30kHz      | Average                     |
|                   | 0.490MHz -30MHz                                                                                                                                                                                                                                                             | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                   | 30MHz-1GHz                                                                                                                                                                                                                                                                  | Peak                                | 100 kHz           | 300kHz     | Peak                        |
|                   | Above 1GHz                                                                                                                                                                                                                                                                  | Peak                                | 1MHz              | 3MHz       | Peak                        |
|                   |                                                                                                                                                                                                                                                                             | Peak                                | 1MHz              | 10kHz      | Average                     |
| Limit:            | Frequency                                                                                                                                                                                                                                                                   | Field strength<br>(microvolt/meter) | Limit<br>(dBuV/m) | Remark     | Measurement<br>distance (m) |
|                   | 0.009MHz-0.490MHz                                                                                                                                                                                                                                                           | 2400/F(kHz)                         | -                 | -          | 300                         |
|                   | 0.490MHz-1.705MHz                                                                                                                                                                                                                                                           | 24000/F(kHz)                        | -                 | -          | 30                          |
|                   | 1.705MHz-30MHz                                                                                                                                                                                                                                                              | 30                                  | -                 | -          | 30                          |
|                   | 30MHz-88MHz                                                                                                                                                                                                                                                                 | 100                                 | 40.0              | Quasi-peak | 3                           |
|                   | 88MHz-216MHz                                                                                                                                                                                                                                                                | 150                                 | 43.5              | Quasi-peak | 3                           |
|                   | 216MHz-960MHz                                                                                                                                                                                                                                                               | 200                                 | 46.0              | Quasi-peak | 3                           |
|                   | 960MHz-1GHz                                                                                                                                                                                                                                                                 | 500                                 | 54.0              | Quasi-peak | 3                           |
|                   | Above 1GHz                                                                                                                                                                                                                                                                  | 500                                 | 54.0              | Average    | 3                           |
|                   | Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. |                                     |                   |            |                             |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Procedure:        | <p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz:<br/>Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | Non-hopping transmitting mode with all kind of modulation and all kind of data type.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Final Test Mode:       | Through Pre-scan, find the 3DH5 of data type and 8DPSK modulation is the worst case.<br>Pretest the EUT at Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the middle channel.<br>Only the worst case is recorded in the report.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## Radiated Spurious Emission below 1GHz:


During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case middle channel of 3DH5 for 8DPSK was recorded in the report.

### Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 59.6850     | -18.45      | 45.79          | 27.34          | 40.00          | 12.66       | PASS   | Horizontal | Peak   |
| 2  | 143.9864    | -21.87      | 48.11          | 26.24          | 43.50          | 17.26       | PASS   | Horizontal | Peak   |
| 3  | 263.9874    | -16.27      | 46.95          | 30.68          | 46.00          | 15.32       | PASS   | Horizontal | Peak   |
| 4  | 360.5121    | -13.79      | 50.79          | 37.00          | 46.00          | 9.00        | PASS   | Horizontal | Peak   |
| 5  | 556.5687    | -9.65       | 43.58          | 33.93          | 46.00          | 12.07       | PASS   | Horizontal | Peak   |
| 6  | 884.0734    | -5.14       | 37.01          | 31.87          | 46.00          | 14.13       | PASS   | Horizontal | Peak   |

## Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 43.9694     | -17.34      | 38.58          | 21.24          | 40.00          | 18.76       | PASS   | Vertical | Peak   |
| 2  | 68.5129     | -20.46      | 40.92          | 20.46          | 40.00          | 19.54       | PASS   | Vertical | Peak   |
| 3  | 120.0250    | -20.08      | 46.17          | 26.09          | 43.50          | 17.41       | PASS   | Vertical | Peak   |
| 4  | 199.8640    | -17.85      | 39.76          | 21.91          | 43.50          | 21.59       | PASS   | Vertical | Peak   |
| 5  | 348.4828    | -14.12      | 41.88          | 27.76          | 46.00          | 18.24       | PASS   | Vertical | Peak   |
| 6  | 556.6657    | -9.64       | 37.69          | 28.05          | 46.00          | 17.95       | PASS   | Vertical | Peak   |

### Radiated Spurious Emission above 1GHz:

| Mode: |             |             | GFSK Transmitting |                |                | Channel:    |        | 2402 MHz |        |
|-------|-------------|-------------|-------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]    | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1294.8295   | 1.05        | 43.03             | 44.08          | 74.00          | 29.92       | Pass   | H        | PK     |
| 2     | 1810.4810   | 3.36        | 41.64             | 45.00          | 74.00          | 29.00       | Pass   | H        | PK     |
| 3     | 4804.1203   | -16.23      | 62.17             | 45.94          | 74.00          | 28.06       | Pass   | H        | PK     |
| 4     | 7206.2804   | -11.83      | 61.53             | 49.70          | 74.00          | 24.30       | Pass   | H        | PK     |
| 5     | 9607.4405   | -7.37       | 59.20             | 51.83          | 74.00          | 22.17       | Pass   | H        | PK     |
| 6     | 13758.7172  | -1.69       | 50.87             | 49.18          | 74.00          | 24.82       | Pass   | H        | PK     |
| 7     | 1400.0400   | 1.39        | 44.23             | 45.62          | 74.00          | 28.38       | Pass   | V        | PK     |
| 8     | 1999.5000   | 4.55        | 43.57             | 48.12          | 74.00          | 25.88       | Pass   | V        | PK     |
| 9     | 4804.1203   | -16.23      | 61.43             | 45.20          | 74.00          | 28.80       | Pass   | V        | PK     |
| 10    | 7206.2804   | -11.83      | 55.44             | 43.61          | 74.00          | 30.39       | Pass   | V        | PK     |
| 11    | 9608.4406   | -7.37       | 61.78             | 54.41          | 74.00          | 19.59       | Pass   | V        | PK     |
| 12    | 9609.4406   | -7.37       | 52.62             | 45.25          | 54.00          | 8.75        | Pass   | V        | AV     |
| 13    | 14490.7661  | -0.08       | 49.83             | 49.75          | 74.00          | 24.25       | Pass   | V        | PK     |

| Mode: |             |             | GFSK Transmitting |                |                | Channel:    |        | 2441 MHz |        |
|-------|-------------|-------------|-------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]    | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1263.8264   | 0.97        | 42.82             | 43.79          | 74.00          | 30.21       | Pass   | H        | PK     |
| 2     | 1981.6982   | 4.45        | 41.83             | 46.28          | 74.00          | 27.72       | Pass   | H        | PK     |
| 3     | 4882.1255   | -16.21      | 60.82             | 44.61          | 74.00          | 29.39       | Pass   | H        | PK     |
| 4     | 7323.2882   | -11.65      | 61.32             | 49.67          | 74.00          | 24.33       | Pass   | H        | PK     |
| 5     | 9764.4510   | -7.50       | 61.34             | 53.84          | 74.00          | 20.16       | Pass   | H        | PK     |
| 6     | 15513.8343  | 0.38        | 51.10             | 51.48          | 74.00          | 22.52       | Pass   | H        | PK     |
| 7     | 1394.2394   | 1.37        | 44.49             | 45.86          | 74.00          | 28.14       | Pass   | V        | PK     |
| 8     | 1990.6991   | 4.50        | 43.11             | 47.61          | 74.00          | 26.39       | Pass   | V        | PK     |
| 9     | 4882.1255   | -16.21      | 60.95             | 44.74          | 74.00          | 29.26       | Pass   | V        | PK     |
| 10    | 7323.2882   | -11.65      | 56.93             | 45.28          | 74.00          | 28.72       | Pass   | V        | PK     |
| 11    | 9763.4509   | -7.50       | 63.81             | 56.31          | 74.00          | 17.69       | Pass   | V        | PK     |
| 12    | 9765.4510   | -7.49       | 53.90             | 46.41          | 54.00          | 7.59        | Pass   | V        | AV     |
| 13    | 14340.7561  | 0.24        | 49.05             | 49.29          | 74.00          | 24.71       | Pass   | V        | PK     |

| Mode: |             |             | GFSK Transmitting |                |                | Channel:    |        | 2480 MHz |        |
|-------|-------------|-------------|-------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]    | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1447.6448   | 1.43        | 42.82             | 44.25          | 74.00          | 29.75       | Pass   | H        | PK     |
| 2     | 1727.6728   | 3.03        | 42.19             | 45.22          | 74.00          | 28.78       | Pass   | H        | PK     |
| 3     | 4960.1307   | -15.97      | 66.16             | 50.19          | 74.00          | 23.81       | Pass   | H        | PK     |
| 4     | 7440.2960   | -11.34      | 65.81             | 54.47          | 74.00          | 19.53       | Pass   | H        | PK     |
| 5     | 7441.2961   | -11.34      | 56.81             | 45.47          | 54.00          | 8.53        | Pass   | H        | AV     |
| 6     | 9920.4614   | -7.10       | 62.61             | 55.51          | 74.00          | 18.49       | Pass   | H        | PK     |
| 7     | 9921.4614   | -7.10       | 54.68             | 47.58          | 54.00          | 6.42        | Pass   | H        | AV     |
| 8     | 14387.7592  | 1.02        | 48.55             | 49.57          | 74.00          | 24.43       | Pass   | H        | PK     |
| 9     | 1397.6398   | 1.38        | 44.13             | 45.51          | 74.00          | 28.49       | Pass   | V        | PK     |
| 10    | 1972.4973   | 4.41        | 41.62             | 46.03          | 74.00          | 27.97       | Pass   | V        | PK     |
| 11    | 4960.1307   | -15.97      | 65.21             | 49.24          | 74.00          | 24.76       | Pass   | V        | PK     |
| 12    | 7440.2960   | -11.34      | 61.30             | 49.96          | 74.00          | 24.04       | Pass   | V        | PK     |
| 13    | 9920.4614   | -7.10       | 61.96             | 54.86          | 74.00          | 19.14       | Pass   | V        | PK     |
| 14    | 9921.4614   | -7.10       | 52.43             | 45.33          | 54.00          | 8.67        | Pass   | V        | AV     |
| 15    | 14391.7595  | 1.08        | 49.07             | 50.15          | 74.00          | 23.85       | Pass   | V        | PK     |

| Mode: |             |             | $\pi/4$ DQPSK Transmitting |                |                | Channel:    |        | 2402 MHz |        |
|-------|-------------|-------------|----------------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]             | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1150.4150   | 0.82        | 44.41                      | 45.23          | 74.00          | 28.77       | Pass   | H        | PK     |
| 2     | 1797.6798   | 3.27        | 42.71                      | 45.98          | 74.00          | 28.02       | Pass   | H        | PK     |
| 3     | 4803.1202   | -16.23      | 62.48                      | 46.25          | 74.00          | 27.75       | Pass   | H        | PK     |
| 4     | 7206.2804   | -11.83      | 59.10                      | 47.27          | 74.00          | 26.73       | Pass   | H        | PK     |
| 5     | 9608.4406   | -7.37       | 58.25                      | 50.88          | 74.00          | 23.12       | Pass   | H        | PK     |
| 6     | 14531.7688  | 0.03        | 49.53                      | 49.56          | 74.00          | 24.44       | Pass   | H        | PK     |
| 7     | 1207.4207   | 0.82        | 43.59                      | 44.41          | 74.00          | 29.59       | Pass   | V        | PK     |
| 8     | 1992.0992   | 4.51        | 44.05                      | 48.56          | 74.00          | 25.44       | Pass   | V        | PK     |
| 9     | 4804.1203   | -16.23      | 59.78                      | 43.55          | 74.00          | 30.45       | Pass   | V        | PK     |
| 10    | 7035.2690   | -11.74      | 54.82                      | 43.08          | 74.00          | 30.92       | Pass   | V        | PK     |
| 11    | 9608.4406   | -7.37       | 61.73                      | 54.36          | 74.00          | 19.64       | Pass   | V        | PK     |
| 12    | 9609.4406   | -7.37       | 52.95                      | 45.58          | 54.00          | 8.42        | Pass   | V        | AV     |
| 13    | 13834.7223  | -1.75       | 50.60                      | 48.85          | 74.00          | 25.15       | Pass   | V        | PK     |

| Mode: |             |             | $\pi/4$ DQPSK Transmitting |                      |                      | Channel:    |        | 2441 MHz |        |
|-------|-------------|-------------|----------------------------|----------------------|----------------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dB $\mu$ V]       | Level [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1358.0358   | 1.25        | 43.31                      | 44.56                | 74.00                | 29.44       | Pass   | H        | PK     |
| 2     | 1937.2937   | 4.22        | 41.57                      | 45.79                | 74.00                | 28.21       | Pass   | H        | PK     |
| 3     | 4882.1255   | -16.21      | 62.18                      | 45.97                | 74.00                | 28.03       | Pass   | H        | PK     |
| 4     | 7323.2882   | -11.65      | 59.66                      | 48.01                | 74.00                | 25.99       | Pass   | H        | PK     |
| 5     | 9764.4510   | -7.50       | 59.92                      | 52.42                | 74.00                | 21.58       | Pass   | H        | PK     |
| 6     | 13682.7122  | -1.75       | 50.81                      | 49.06                | 74.00                | 24.94       | Pass   | H        | PK     |
| 7     | 1454.6455   | 1.43        | 43.65                      | 45.08                | 74.00                | 28.92       | Pass   | V        | PK     |
| 8     | 1795.0795   | 3.26        | 41.97                      | 45.23                | 74.00                | 28.77       | Pass   | V        | PK     |
| 9     | 4882.1255   | -16.21      | 60.83                      | 44.62                | 74.00                | 29.38       | Pass   | V        | PK     |
| 10    | 7403.2936   | -11.50      | 55.64                      | 44.14                | 74.00                | 29.86       | Pass   | V        | PK     |
| 11    | 9764.4510   | -7.50       | 61.88                      | 54.38                | 74.00                | 19.62       | Pass   | V        | PK     |
| 12    | 9765.4510   | -7.49       | 53.00                      | 45.51                | 54.00                | 8.49        | Pass   | V        | AV     |
| 13    | 13683.7122  | -1.75       | 50.79                      | 49.04                | 74.00                | 24.96       | Pass   | V        | PK     |

| Mode: |             |             | $\pi/4$ DQPSK Transmitting |                      |                      | Channel:    |        | 2480 MHz |        |
|-------|-------------|-------------|----------------------------|----------------------|----------------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dB $\mu$ V]       | Level [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1232.4232   | 0.88        | 43.40                      | 44.28                | 74.00                | 29.72       | Pass   | H        | PK     |
| 2     | 1807.8808   | 3.34        | 41.59                      | 44.93                | 74.00                | 29.07       | Pass   | H        | PK     |
| 3     | 4960.1307   | -15.97      | 66.09                      | 50.12                | 74.00                | 23.88       | Pass   | H        | PK     |
| 4     | 7439.2960   | -11.34      | 64.67                      | 53.33                | 74.00                | 20.67       | Pass   | H        | PK     |
| 5     | 9920.4614   | -7.10       | 60.59                      | 53.49                | 74.00                | 20.51       | Pass   | H        | PK     |
| 6     | 12399.6266  | -4.69       | 52.93                      | 48.24                | 74.00                | 25.76       | Pass   | H        | PK     |
| 7     | 1268.0268   | 0.98        | 43.25                      | 44.23                | 74.00                | 29.77       | Pass   | V        | PK     |
| 8     | 1794.6795   | 3.26        | 43.38                      | 46.64                | 74.00                | 27.36       | Pass   | V        | PK     |
| 9     | 4960.1307   | -15.97      | 63.40                      | 47.43                | 74.00                | 26.57       | Pass   | V        | PK     |
| 10    | 7440.2960   | -11.34      | 60.34                      | 49.00                | 74.00                | 25.00       | Pass   | V        | PK     |
| 11    | 9920.4614   | -7.10       | 60.72                      | 53.62                | 74.00                | 20.38       | Pass   | V        | PK     |
| 12    | 13744.7163  | -1.71       | 51.18                      | 49.47                | 74.00                | 24.53       | Pass   | V        | PK     |

| Mode: |             |             | 8DPSK Transmitting |                |                | Channel:    |        | 2402 MHz |        |
|-------|-------------|-------------|--------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]     | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1265.2265   | 0.97        | 42.99              | 43.96          | 74.00          | 30.04       | Pass   | H        | PK     |
| 2     | 1867.4867   | 3.79        | 42.20              | 45.99          | 74.00          | 28.01       | Pass   | H        | PK     |
| 3     | 4804.1203   | -16.23      | 61.77              | 45.54          | 74.00          | 28.46       | Pass   | H        | PK     |
| 4     | 7206.2804   | -11.83      | 59.36              | 47.53          | 74.00          | 26.47       | Pass   | H        | PK     |
| 5     | 9608.4406   | -7.37       | 58.69              | 51.32          | 74.00          | 22.68       | Pass   | H        | PK     |
| 6     | 15174.8117  | 1.70        | 48.32              | 50.02          | 74.00          | 23.98       | Pass   | H        | PK     |
| 7     | 1383.0383   | 1.33        | 42.75              | 44.08          | 74.00          | 29.92       | Pass   | V        | PK     |
| 8     | 1997.6998   | 4.54        | 45.17              | 49.71          | 74.00          | 24.29       | Pass   | V        | PK     |
| 9     | 4804.1203   | -16.23      | 61.01              | 44.78          | 74.00          | 29.22       | Pass   | V        | PK     |
| 10    | 7206.2804   | -11.83      | 55.81              | 43.98          | 74.00          | 30.02       | Pass   | V        | PK     |
| 11    | 9607.4405   | -7.37       | 64.59              | 57.22          | 74.00          | 16.78       | Pass   | V        | PK     |
| 12    | 9609.4406   | -7.37       | 53.00              | 45.63          | 54.00          | 8.37        | Pass   | V        | AV     |
| 13    | 14353.7569  | 0.45        | 48.88              | 49.33          | 74.00          | 24.67       | Pass   | V        | PK     |

| Mode: |             |             | 8DPSK Transmitting |                |                | Channel:    |        | 2441 MHz |        |
|-------|-------------|-------------|--------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]     | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1250.0250   | 0.93        | 42.89              | 43.82          | 74.00          | 30.18       | Pass   | H        | PK     |
| 2     | 1779.2779   | 3.21        | 42.06              | 45.27          | 74.00          | 28.73       | Pass   | H        | PK     |
| 3     | 4882.1255   | -16.21      | 62.04              | 45.83          | 74.00          | 28.17       | Pass   | H        | PK     |
| 4     | 7323.2882   | -11.65      | 58.35              | 46.70          | 74.00          | 27.30       | Pass   | H        | PK     |
| 5     | 9763.4509   | -7.50       | 61.99              | 54.49          | 74.00          | 19.51       | Pass   | H        | PK     |
| 6     | 9765.4510   | -7.49       | 51.84              | 44.35          | 54.00          | 9.65        | Pass   | H        | AV     |
| 7     | 13757.7172  | -1.69       | 50.94              | 49.25          | 74.00          | 24.75       | Pass   | H        | PK     |
| 8     | 1396.8397   | 1.38        | 43.11              | 44.49          | 74.00          | 29.51       | Pass   | V        | PK     |
| 9     | 1794.4794   | 3.26        | 43.46              | 46.72          | 74.00          | 27.28       | Pass   | V        | PK     |
| 10    | 4882.1255   | -16.21      | 58.19              | 41.98          | 74.00          | 32.02       | Pass   | V        | PK     |
| 11    | 7323.2882   | -11.65      | 55.48              | 43.83          | 74.00          | 30.17       | Pass   | V        | PK     |
| 12    | 9764.4510   | -7.50       | 63.38              | 55.88          | 74.00          | 18.12       | Pass   | V        | PK     |
| 13    | 9765.4510   | -7.49       | 54.23              | 46.74          | 54.00          | 7.26        | Pass   | V        | AV     |
| 14    | 14411.7608  | 1.05        | 48.79              | 49.84          | 74.00          | 24.16       | Pass   | V        | PK     |

| Mode: |             |             | 8DPSK Transmitting |                |                | Channel:    |        | 2480 MHz |        |
|-------|-------------|-------------|--------------------|----------------|----------------|-------------|--------|----------|--------|
| NO    | Freq. [MHz] | Factor [dB] | Reading [dBμV]     | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
| 1     | 1383.4383   | 1.34        | 42.71              | 44.05          | 74.00          | 29.95       | Pass   | H        | PK     |
| 2     | 1794.8795   | 3.26        | 42.81              | 46.07          | 74.00          | 27.93       | Pass   | H        | PK     |
| 3     | 4960.1307   | -15.97      | 62.33              | 46.36          | 74.00          | 27.64       | Pass   | H        | PK     |
| 4     | 7440.2960   | -11.34      | 61.60              | 50.26          | 74.00          | 23.74       | Pass   | H        | PK     |
| 5     | 9920.4614   | -7.10       | 61.94              | 54.84          | 74.00          | 19.16       | Pass   | H        | PK     |
| 6     | 9921.4614   | -7.10       | 52.46              | 45.36          | 54.00          | 8.64        | Pass   | H        | AV     |
| 7     | 13748.7166  | -1.70       | 51.14              | 49.44          | 74.00          | 24.56       | Pass   | H        | PK     |
| 8     | 1396.6397   | 1.38        | 43.99              | 45.37          | 74.00          | 28.63       | Pass   | V        | PK     |
| 9     | 1996.8997   | 4.53        | 44.14              | 48.67          | 74.00          | 25.33       | Pass   | V        | PK     |
| 10    | 4960.1307   | -15.97      | 59.04              | 43.07          | 74.00          | 30.93       | Pass   | V        | PK     |
| 11    | 7440.2960   | -11.34      | 57.07              | 45.73          | 74.00          | 28.27       | Pass   | V        | PK     |
| 12    | 9920.4614   | -7.10       | 59.27              | 52.17          | 74.00          | 21.83       | Pass   | V        | PK     |
| 13    | 14335.7557  | 0.15        | 50.12              | 50.27          | 74.00          | 23.73       | Pass   | V        | PK     |

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Restricted bands:

Test plot as follows:

|         |                   |          |          |
|---------|-------------------|----------|----------|
| Mode:   | GFSK Transmitting | Channel: | 2402 MHz |
| Remark: |                   |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2390.0000   | 5.77        | 41.36          | 47.13          | 74.00          | 26.87       | PASS   | Horizontal | PK     |
| 2  | 2390.0000   | 5.77        | 30.62          | 36.39          | 54.00          | 17.61       | PASS   | Horizontal | AV     |

|         |                   |          |          |
|---------|-------------------|----------|----------|
| Mode:   | GFSK Transmitting | Channel: | 2402 MHz |
| Remark: |                   |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2390.0000   | 5.77        | 44.38          | 50.15          | 74.00          | 23.85       | PASS   | Vertical | PK     |
| 2  | 2390.0000   | 5.77        | 29.52          | 35.29          | 54.00          | 18.71       | PASS   | Vertical | AV     |

|         |                   |          |          |
|---------|-------------------|----------|----------|
| Mode:   | GFSK Transmitting | Channel: | 2480 MHz |
| Remark: |                   |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2483.5000   | 6.57        | 40.82          | 47.39          | 74.00          | 26.61       | PASS   | Horizontal | PK     |
| 2  | 2483.5000   | 6.57        | 30.07          | 36.64          | 54.00          | 17.36       | PASS   | Horizontal | AV     |

|         |                   |          |          |
|---------|-------------------|----------|----------|
| Mode:   | GFSK Transmitting | Channel: | 2480 MHz |
| Remark: |                   |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2483.5000   | 6.57        | 40.59          | 47.16          | 74.00          | 26.84       | PASS   | Vertical | PK     |
| 2  | 2483.5000   | 6.57        | 29.96          | 36.53          | 54.00          | 17.47       | PASS   | Vertical | AV     |

|         |                            |          |          |
|---------|----------------------------|----------|----------|
| Mode:   | $\pi$ /4DQPSK Transmitting | Channel: | 2402 MHz |
| Remark: |                            |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2390.0000   | 5.77        | 41.44          | 47.21          | 74.00          | 26.79       | PASS   | Horizontal | PK     |
| 2  | 2390.0000   | 5.77        | 29.50          | 35.27          | 54.00          | 18.73       | PASS   | Horizontal | AV     |

|         |                            |          |          |
|---------|----------------------------|----------|----------|
| Mode:   | $\pi$ /4DQPSK Transmitting | Channel: | 2402 MHz |
| Remark: |                            |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2390.0000   | 5.77        | 42.13          | 47.90          | 74.00          | 26.10       | PASS   | Vertical | PK     |
| 2  | 2390.0000   | 5.77        | 29.69          | 35.46          | 54.00          | 18.54       | PASS   | Vertical | AV     |

|         |                            |          |          |
|---------|----------------------------|----------|----------|
| Mode:   | $\pi$ /4DQPSK Transmitting | Channel: | 2480 MHz |
| Remark: |                            |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2483.5000   | 6.57        | 48.17          | 54.74          | 74.00          | 19.26       | PASS   | Horizontal | PK     |
| 2  | 2483.5000   | 6.57        | 29.84          | 36.41          | 54.00          | 17.59       | PASS   | Horizontal | AV     |

|         |                            |          |          |
|---------|----------------------------|----------|----------|
| Mode:   | $\pi$ /4DQPSK Transmitting | Channel: | 2480 MHz |
| Remark: |                            |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2483.5000   | 6.57        | 40.16          | 46.73          | 74.00          | 27.27       | PASS   | Vertical | PK     |
| 2  | 2483.5000   | 6.57        | 29.41          | 35.98          | 54.00          | 18.02       | PASS   | Vertical | AV     |

|         |                    |          |          |
|---------|--------------------|----------|----------|
| Mode:   | 8DPSK Transmitting | Channel: | 2402 MHz |
| Remark: |                    |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2390.0000   | 5.77        | 40.28          | 46.05          | 74.00          | 27.95       | PASS   | Horizontal | PK     |
| 2  | 2390.0000   | 5.77        | 29.89          | 35.66          | 54.00          | 18.34       | PASS   | Horizontal | AV     |

|         |                    |          |          |
|---------|--------------------|----------|----------|
| Mode:   | 8DPSK Transmitting | Channel: | 2402 MHz |
| Remark: |                    |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2390.0000   | 5.77        | 40.72          | 46.49          | 74.00          | 27.51       | PASS   | Vertical | PK     |
| 2  | 2390.0000   | 5.77        | 29.42          | 35.19          | 54.00          | 18.81       | PASS   | Vertical | AV     |

|         |                    |          |          |
|---------|--------------------|----------|----------|
| Mode:   | 8DPSK Transmitting | Channel: | 2480 MHz |
| Remark: |                    |          |          |


Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity   | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|------------|--------|
| 1  | 2483.5000   | 6.57        | 41.06          | 47.63          | 74.00          | 26.37       | PASS   | Horizontal | PK     |
| 2  | 2483.5000   | 6.57        | 29.34          | 35.91          | 54.00          | 18.09       | PASS   | Horizontal | AV     |

|         |                    |          |          |
|---------|--------------------|----------|----------|
| Mode:   | 8DPSK Transmitting | Channel: | 2480 MHz |
| Remark: |                    |          |          |

### Test Graph



| NO | Freq. [MHz] | Factor [dB] | Reading [dBμV] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Result | Polarity | Remark |
|----|-------------|-------------|----------------|----------------|----------------|-------------|--------|----------|--------|
| 1  | 2483.5000   | 6.57        | 40.51          | 47.08          | 74.00          | 26.92       | PASS   | Vertical | PK     |
| 2  | 2483.5000   | 6.57        | 29.56          | 36.13          | 54.00          | 17.87       | PASS   | Vertical | AV     |

### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

## 6 Appendix A

Refer to Appendix: Bluetooth Classic of EEED32N80941101.