

RF Exposure evaluation

FCC ID: **2AS6M-TT-1203**

According to 447498 D01 General RF Exposure Guidance v06

4.3. General SAR test exclusion guidance

4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following: [(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

³⁰ This is equivalent to the formula written as: [(max. power of channel, including tune-up tolerance, mW)/(60/ $\sqrt{f(\text{GHz})}$ mW)] $\cdot [20 \text{ mm}/(\text{min. test separation distance, mm})] \leq 1.0$ for 1-g SAR; also see Appendix A for approximate exclusion threshold numerical values at selected frequencies and distances.

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((\text{dBuV/m})/20)/10^6$

d = measurement distance in meters (m)---3m

So $\text{pt} = (\text{EXd})^2/30 \times \text{gt}$

RF Exposure evaluation

Copied from the FCC test report: clause 9.4 Maximum Peak Output Power

Test Result:

For BLE:

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	-4.24	0.3767	1000
	2442	-2.13	0.6124	1000
	2480	-1.59	0.6934	1000

Note: the antenna gain of 0dB less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

EIRP/ dBm= Conducted Max Output Power/ dBm+ Antenna gain /dBi.

General RF Exposure:

$(0.3767\text{mW})/5.0\text{mm} \times \sqrt{2.402\text{ GHz}} = 0.11$

$(0.6124\text{mW})/5.0\text{mm} \times \sqrt{2.442\text{ GHz}} = 0.19$

$(0.6934\text{mW})/5.0\text{mm} \times \sqrt{2.480\text{ GHz}} = 0.22$

SAR requirement: S=3.0

General RF Exposure<3

Then SAR evaluation is not required