



FCC TEST REPORT

FCC ID:2AS6X-HD76

Applicant: Shenzhen Future Charger Technology co., LTD

Address: Yongfengtian Industrial Park , fenghuang third industrial zone, Fuyong town, Baoan District, Shenzhen, China

Manufacturer: F&C TECHNOLOGY COMPANY LIMITED (VIETNAM)

Address: Factory No. 09 (Production Area Type 2), Lot TR-C-15, Tien Phong 5 Street, BW Supply Chain City Industrial Park, Binh Duong Ward, Ho Chi Minh City, Vietnam.

EUT: Wireless Charger Mouse Pad

Trade Mark: N/A

Model Number: HD76
HD89, HD92, HD93, HD99, HD114, HD115, HD117, HD123, BSJHD76B-US, BSJHD93B-US, BSJHD99B-US, USFOHD76B, USFOHDHD92B, USFOHD93B, USFOHD99B, USFOHD114B, USFOHD114BL, USFOHD114PK, USFOHD114GY, USFOHD89B, AHD76B, AHD76E1PD, AHD76E2PD, AHD76MPD, AHD76SPD, AHD76S, AHD76PK, AHD115B, AHD89B, AHD123B, MHD109B-US, MHD123B-US, MHD89B-US, MHD89E-US, MHD89O-US, MHD89M-US, AHD117BPD, AHD117B, AHD76-PD, AHD76SPD, AHD76PKPD, AHD115BPD, AHD89BPD, AHD123BPD, USFOHD76BPD, USFOHD76B-NEW, USFOHD76BPD-NEW, USFOHDHD92BPD, USFOHD93BPD, USFOHD99BPD, USFOHD114BPD, USFOHD114BLPD, USFOHD114PKPD, USFOHD114GYPD, USFOHD89BPD, MHD89BPD-US, MHD109BPD-US, MHD123BPD-US

Date of Receipt: Nov. 07, 2025

Test Date: Nov. 07, 2025 to Nov. 14, 2025

Date of Report: Nov. 19, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C

Test Result: Pass

Report Number: DLE-251119007R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

**TABLE OF CONTENTS**

1. VERSION	3
2. TEST SUMMARY	4
2.1 TEST FACILITY	5
2.2 MEASUREMENT UNCERTAINTY	5
3. GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 TEST MODE	7
3.3 BLOCK DIAGRAM OF EUT CONFIGURATION	9
3.4 TEST CONDITIONS	10
3.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	10
3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. CONDUCTED EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULT	14
5. RADIATED EMISSION MEASUREMENT	16
5.1 RADIATED EMISSION LIMITS	16
5.2 ANECHOIC CHAMBER TEST SETUP DIAGRAM	17
5.3 TEST PROCEDURE	18
5.4 DEVIATION FROM TEST STANDARD	18
5.5 TEST RESULT	18
6. 20DB BANDWIDTH TEST	24
6.1 TEST PROCEDURE	24
6.2 LIMIT	24
6.3 TEST SETUP	24
6.4 DEVIATION FROM STANDARD	24
6.5 TEST RESULT	25
7. ANTENNA REQUIREMENT	26
8. TEST SETUP PHOTO	27
9. EUT CONSTRUCTIONAL DETAILS	27

**1. VERSION**

Report No.	Version	Description	Approved
DLE-251119007R	Rev.01	Initial issue of report	Nov. 19, 2025



2. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolon Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB identifier: CN0118

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF conducted Spurious Emission	U=2.2dB
7	RF Occupied Bandwidth	U=1.8MHz
8	humidity uncertainty	U=5.3%
9	Temperature uncertainty	U=0.59℃



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Wireless Charger Mouse Pad
Model No.:	HD76
Serial No.:	HD89,HD92,HD93,HD99,HD114,HD115,HD117,HD123,BSJHD76B-US,BSJHD93B-US,BSJHD99B-US,USFOHD76B,USFOHDHD92B,USFOHD93B,USFOHD99B,USFOHD114B,USFOHD114BL,USFOHD114PK,USFOHD114GY,USFOHD89B,AHD76B,AHD76E1PD,AHD76E2PD,AHD76MPD,AHD76SFPD,AHD76S,AHD76PK,AHD115B,AHD89B,AHD123B,MHD109B-US,MHD123B-US,MHD89B-US,MHD89E-US,MHD89O-US,MHD89M-US,AHD117BPD,AHD117B,AHD76-PD,AHD76SPD,AHD76PKPD,AHD115BPD,AHD89BPD,AHD123BPD,USFOHD76BPD,USFOHD76B-NEW,USFOHD76BPD-NEW,USFOHDHD92BPD,USFOHD93BPD,USFOHD99BPD,USFOHD114BPD,USFOHD114BLPD,USFOHD114PKPD,USFOHD114GYPD,USFOHD89BPD,MHD89BPD-US,MHD109BPD-US,MHD123BPD-US
Model Difference:	All the model are the same circuit , only the model name are different.
Hardware Version:	V 1.0
Software Version:	V 1.1
Operation Frequency:	ANT 1: 115kHz ~ 205kHz, ANT 2:115KHz~148KHz
Modulation Type:	ASK
Antenna Type:	Loop Coil Antenna
Antenna Gain:	0dBi
Ratings:	Input: 5V/3A, 9V/3A Mobile phone output:15W max Earphone output:5W max
Transmitting Mode:	Keep the EUT in continuously Wireless Charger Mouse Pad mode



3.2 TEST MODE

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.




EUT mode of operation before folding:

Test Modes:	Description:
Phone Coil+Earphone Coil	Mode 1: AC/DC Adapter+EUT + Phone +Earphone (Battery Status:<1%)
	Mode 2: AC/DC Adapter+EUT + Phone +Earphone (Battery Status:<50%)
	Mode 3: AC/DC Adapter+EUT + Phone +Earphone (Battery Status:<100%)
Phone Coil	Mode 4 :AC/DC Adapter+EUT + Phone (Battery Status:<1%)
	Mode 5: AC/DC Adapter+EUT + Phone (Battery Status:<50%)
	Mode 6: AC/DC Adapter+EUT + Phone (Battery Status:<100%)
Earphone Coil	Mode 7:AC/DC Adapter+EUT +Earphone (Battery Status:<1%)
	Mode 8:AC/DC Adapter+EUT+Earphone (Battery Status:<50%)
	Mode 9:AC/DC Adapter+EUT +Earphone (Battery Status:<100%)
No Loads	AC/DC Adapter+EUT




3.3 BLOCK DIAGRAM OF EUT CONFIGURATION

Conducted Emission



Radiated Emission





3.4 TEST CONDITIONS

Temperature: 23~26℃

Relative Humidity: 54~63 %

3.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Wireless Charger Mouse Pad	N/A	HD76	N/A	EUT
E-2	AC/DC Adapter	N/A	X569	N/A	Auxiliary
E-3	Phone	Apple	iPhone XR	N/A	Auxiliary
E-4	Earphone	Baseus	E3	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	DC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Oct.25,2025	Oct.24,2026
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Oct.25,2025	Oct.24,2026
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Oct.27,2025	Oct.26,2026
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Oct.27,2025	Oct.26,2026
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Oct.25,2025	Oct.24,2026
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Oct.25,2025	Oct.24,2026
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Oct.25,2025	Oct.24,2026
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Oct.25,2025	Oct.24,2026
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Oct.25,2025	Oct.24,2026
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Oct.25,2025	Oct.24,2026
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Oct.25,2025	Oct.24,2026
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Oct.25,2025	Oct.24,2026
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Oct.25,2025	Oct.24,2026
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Oct.25,2025	Oct.24,2026
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Oct.25,2025	Oct.24,2026
16	D.C. Power Supply	LongWei	PS-305D	010964729	Oct.25,2025	Oct.24,2026

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov.05,2023	Nov.04,2026
2	EMI Receiver	R&S	ESR	101421	Oct.25,2025	Oct.24,2026
3	LISN	R&S	ENV216	102417	Oct.25,2025	Oct.24,2026
4	843 Cable 1#	ChengYu	CE Cable	001	Oct.25,2025	Oct.24,2026

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ EMC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ EMC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



4. CONDUCTED EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	DC 9V from adapter input AC 120V/60Hz.	Test Mode :	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2310	17.79	19.66	37.45	62.41	-24.96	QP	P	
2	0.2355	11.47	19.66	31.13	52.25	-21.12	AVG	P	
3	0.5774	18.27	19.63	37.90	56.00	-18.10	QP	P	
4	0.5954	10.67	19.63	30.30	46.00	-15.70	AVG	P	
5	1.3919	4.18	19.66	23.84	46.00	-22.16	AVG	P	
6	1.3964	14.95	19.66	34.61	56.00	-21.39	QP	P	
7	4.0109	16.26	19.71	35.97	56.00	-20.03	QP	P	
8	4.2404	8.72	19.71	28.43	46.00	-17.57	AVG	P	
9	9.7440	20.51	19.76	40.27	60.00	-19.73	QP	P	
10	9.7440	14.18	19.76	33.94	50.00	-16.06	AVG	P	
11	23.5049	20.82	19.78	40.60	50.00	-9.40	AVG	P	
12	23.7345	26.24	19.78	46.02	60.00	-13.98	QP	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lisen factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. All test modes were tested, with only the worst Mode 1 recorded.



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	DC 9V from adapter input AC 120V/60Hz.	Test Mode :	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3435	16.88	19.64	36.52	59.12	-22.60	QP	P	
2	0.3435	12.58	19.64	32.22	49.12	-16.90	AVG	P	
3	0.5954	10.20	19.62	29.82	46.00	-16.18	AVG	P	
4	0.6000	17.68	19.62	37.30	56.00	-18.70	QP	P	
5	3.7860	6.56	19.69	26.25	46.00	-19.75	AVG	P	
6	3.9255	17.81	19.69	37.50	56.00	-18.50	QP	P	
7	6.5355	18.95	19.72	38.67	60.00	-21.33	QP	P	
8	6.5355	12.96	19.72	32.68	50.00	-17.32	AVG	P	
9	12.4980	20.29	19.75	40.04	60.00	-19.96	QP	P	
10	12.9570	16.22	19.76	35.98	50.00	-14.02	AVG	P	
11	23.2800	25.75	19.75	45.50	60.00	-14.50	QP	P	
12	23.2800	19.08	19.75	38.83	50.00	-11.17	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lism factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. All test modes were tested, with only the worst Mode 1 recorded.

**5. RADIATED EMISSION MEASUREMENT**

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

5.1 RADIATED EMISSION LIMITS**Limits for frequency below 30MHz**


Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz


Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value

5.2 ANECHOIC CHAMBER TEST SETUP DIAGRAM

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



5.3 TEST PROCEDURE

Below 30MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving loop antenna and in the center of a loop antenna, which was mounted on the top of a variable-height antenna tower.
- For each suspected emission, the EUT was arranged to its worst case, the height of interference-receiving loop antenna centre is 1 meter above the ground, and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- Both coaxial (loop plane perpendicular to the ground plane and to the measurement axis) and coplanar (loop plane perpendicular to the ground plane and coplanar with the measurement axis) polarizations of the antenna are set to make the measurement.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

30MHz-1GHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5 TEST RESULT

Measurement data:


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40



ANT-1 - 9 kHz~30 MHz

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	coaxial
Test Voltage :	DC 9V from adapter input AC 120V/60Hz.	Test Mode :	Mode 4



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0091	64.66	0.05	64.71	128.42	-63.71	peak
2	0.0160	39.57	20.49	60.06	123.52	-63.46	peak
3	0.0357	31.61	20.08	51.69	116.55	-64.86	peak
4	0.1250	72.43	19.91	92.34	105.67	-13.33	peak
5	0.2452	21.20	20.10	41.30	99.81	-58.51	peak
6	0.7043	18.75	20.38	39.13	70.65	-31.52	peak


Remarks:

- 1.An initial pre-scan was performed on the peak detector.
- 2.Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
- 3.Final Level = Reading level + Correct Factor.
- 4.Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
- 5.Margin= Measurement Level-Limit.
- 6.Tests were conducted in both the coaxial and coplanar directions, and only the worst coaxial data is presented.



ANT-2 - 9 kHz~30 MHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	coaxial
Test Voltage:	DC 9V from adapter input AC 120V/60Hz.	Test Mode:	Mode 7



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0091	64.66	0.05	64.71	128.42	-63.71	peak
2	0.0189	39.06	20.46	59.52	122.08	-62.56	peak
3	0.0280	34.21	20.26	54.47	118.66	-64.19	peak
4	0.1259	72.42	19.92	92.34	105.60	-13.26	peak
5	0.2452	21.20	20.10	41.30	99.81	-58.51	peak
6	0.7043	18.75	20.38	39.13	70.65	-31.52	peak


Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
5. Margin= Measurement Level-Limit.
6. Tests were conducted in both the coaxial and coplanar directions, and only the worst coaxial data is presented.



ANT1+2 - 9 kHz~30 MHz

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	coaxial
Test Voltage :	DC 9V from adapter input AC 120V/60Hz.	Test Mode :	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0091	64.66	0.05	64.71	128.42	-63.71	peak
2	0.0198	37.93	20.45	58.38	121.67	-63.29	peak
3	0.1250	73.03	19.91	92.94	105.67	-12.73	peak
4	0.1259	73.02	19.92	92.94	105.60	-12.66	peak
5	0.2827	20.53	20.12	40.65	98.58	-57.93	peak
6	0.7043	18.75	20.38	39.13	70.65	-31.52	peak


Remarks:

- 1.An initial pre-scan was performed on the peak detector.
- 2.Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
- 3.Final Level = Reading level + Correct Factor.
- 4.Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
- 5.Margin= Measurement Level-Limit.
- 6.Tests were conducted in both the coaxial and coplanar directions, and only the worst coaxial data is presented.



ANT1+2 - 30MHz-1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 9V from adapter input AC 120V/60Hz.	Test Mode:	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	58.4074	42.90	-15.56	27.34	40.00	-12.66	QP
2	151.0665	50.51	-18.92	31.59	43.50	-11.91	QP
3	176.8878	51.41	-20.39	31.02	43.50	-12.48	QP
4	245.0900	60.64	-19.88	40.76	46.00	-5.24	QP
5	321.0608	51.66	-21.52	30.14	46.00	-15.86	QP
6	411.8240	49.37	-20.84	28.53	46.00	-17.47	QP

Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
5. Margin= Measurement Level-Limit.
6. All test modes were tested, with only the worst Mode 1 recorded.



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 9V from adapter input AC 120V/60Hz.	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	52.7600	54.27	-18.89	35.38	40.00	-4.62	QP
2	71.0803	57.33	-21.04	36.29	40.00	-3.71	QP
3	151.0665	57.58	-22.92	34.66	43.50	-8.84	QP
4	245.0900	54.20	-23.90	30.30	46.00	-15.70	QP
5	326.7395	49.32	-22.08	27.24	46.00	-18.76	QP
6	836.2443	34.95	-8.76	26.19	46.00	-19.81	QP

Remarks:

- 1.An initial pre-scan was performed on the peak detector.
- 2.Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
- 3.Final Level = Reading level + Correct Factor.
- 4.Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
- 5.Margin= Measurement Level-Limit.
- 6.All test modes were tested, with only the worst Mode 1 recorded.



6. 20DB BANDWIDTH TEST


6.1 TEST PROCEDURE

1. Se span = 1.5 ~ 5 times OBW.
2. Set RBW = 1%~5% OBW.
3. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
4. Detector = peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.2 LIMIT

N/A

6.3 TEST SETUP



6.4 DEVIATION FROM STANDARD

No deviation.




6.5 TEST RESULT


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 9V

Test Coil	Frequency (kHz)	20dB Bandwidth (kHz)	Result
ANT 1	120.00	2.541	Pass
ANT 2	126.00	2.520	Pass

ANT1:



ANT2:





7. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is Loop Coil antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details	



8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****