



TEST REPORT



Report No. : KES-EM261605-R1

Page 1 / 20

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

- Name : AMOSENSE
- Address : 19-1BL, 90, 4sandan 5-gil, Jiksan-eup, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea

2. Sample Description

- Product item : RKE Transceiver
- Model name : ASRKET01
- Variant model : -
- Manufacturer etc. : AMOSENSE
- Manufacturer address : 19-1BL, 90, 4sandan 5-gil, Jiksan-eup, Seobuk-gu, Cheonan-si, Chungcheongnam-do, Republic of Korea

3. FCC ID : 2AS9T-ASRKET01

4. Date of test : 2026. 05. 11. ~ 2026. 05. 11.

5. Location of Test : Permanent Testing Lab
○ Address : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea

6. Test method used : FCC 47 CFR Part 15, Subpart B (ANSI C63.4a-2017),
IC ICES-003 Issue 7 (ANSI C63.4a-2017)

7. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.

This laboratory is not accredited for the test results marked *.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : DaeHyun Kim	Name : DongHun Jang

2026. 06. 23.

KES Co., Ltd.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
2026. 06. 16.	KES-EM261605	Issued
2026. 06. 23.	KES-EM261605-R1	Reissuance of modifications due to IC Number removal

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

- ☒ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").
- ☐ Other (to be specified, for example when required by the standard or client)



TABLE OF CONTENTS

1	Laboratory Information	4
1.1	Test Location.....	4
1.2	Laboratory Accreditations and Listings	4
2	Test Summary	5
2.1	Class and Voltage.....	5
2.2	Summary of Test Results	5
2.3	Remarks when standards applied	5
2.4	Variant Model Differences	5
2.5	Device Modifications	5
3	General Product Description	6
4	EUT Setup and Operation Mode	7
4.1	EUT Configuration	7
4.2	System Configuration	7
4.3	External I/O Cabling	8
4.4	EUT Operating Mode(s).....	8
4.5	Test operating S/W	8
4.6	Configuration	9
5	Measurement Procedure.....	10
6	Test Item.....	11
6.1	Radiated Emissions(Below 1 GHz)	11
6.2	Radiated Emissions(Above 1 GHz)	16
7	Test Setup Photos and EUT Photographs	19
7.1	Test Setup Photos	19



1 Laboratory Information

1.1 Test Location

Category	Details
Address	473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
Class A	DC 12 V

2.2 Summary of Test Results

Regulation			
47 CFR Part 15, Subpart B / ICES-003 Issue 7			
Test Item	Test Standard	Test Result	Remark
Conducted Emissions at Mains Power Ports	ANSI C63.4a-2017	N/A	NOTE 1
Radiated Emissions(Below 1 GHz)		PASS	-
Radiated Emissions(Above 1 GHz)		PASS	-
* N/A: Not Applicable (NOTE 1) Not applicable for products that operate on DC power.			

2.3 Remarks when standards applied

N/A

2.4 Variant Model Differences

N/A

2.5 Device Modifications

N/A



3 General Product Description

Division	Specificity
Power	DC 12 V
Port	6 Pin
Operating Frequency	433.92 MHz
Components	EUT 1 EA



4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
RKE Transceiver	ASRKET01	-	AMONSENSE.CO., LTD.	EUT
Notebook	NT500R5W	0Q2C91AJ800076W	Samsung Electronics Co., Ltd	-
Notebook Adapter	A13-040N2A	-	CHICONYPower TECHNOLOGY (SUZHOU)CO., LTD.	-
Jig Board 1	-	-	-	-
Jig Board 2	-	-	-	-
PCAN-USB	-	-	Peak Systems	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-



4.3 External I/O Cabling

Mode 1 , Mode 2

Start		End		Cable Spec.	
Product Name	I/O Port	Product Name	I/O Port	Length(m)	Shield
EUT	6 Pin	Jig Board 1	6 Pin	1.0	U
	Wireless	Jig Board 2	Wireless	-	-
Jig Board 1	RS-232	PCAN-USB	RS-232	-	-
PCAN-USB	USB	Notebook	USB	0.3	U
Jig Board 2	Micro 5 Pin	Notebook	USB	0.8	U

* Unshielded=U, Shielded=S

4.4 EUT Operating Mode(s)


Category	Mode	Operating
Mode 1	TX	Connect the test equipment and Jig Board 1 via a wire and turn on the power. Connect Jig Board 1 and PCAN-USB via a wire to the laptop. Connect Jig Board 2 to the laptop via a wire. Transmit a wireless signal from the test equipment using the program provided by the applicant. The test was conducted by receiving the wireless signal on Jig Board 2 and verifying through the log whether it was received successfully.
Mode 2	RX	Connect the test equipment and Jig Board 1 via a wire and turn on the power. Connect Jig Board 1 and PCAN-USB via a wire to the laptop. Connect Jig Board 2 to the laptop via a wire. Transmit a wireless signal from Jig Board 2 using the program provided by the applicant. The test was conducted by receiving the wireless signal on the test equipment and verifying through the log whether it was received successfully.

4.5 Test operating S/W

Name	Version	Manufacture Company
-	-	-



4.6 Configuration



EUT – Jig Board 2 : 433 MHz TX / 433 MHz RX

Mode 1 , Mode 2



5 Measurement Procedure

- Conducted Emissions

The conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. If the conducted emission exceed the average limit with the instrument set to the quasi-peak mode, the measurements are made in the average mode. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. Quasi-peak readings are distinguished with a "QP".

- Radiated Electric Field Emissions

The test was done at a SEMI ANECHOIC CHAMBER with quasi-peak detector. The final test data was measured using a Quasi-Peak detector below 1 GHz at 10 m or 3 m distance and a Peak and Average detector above 1 GHz at 3 m distance. Test was proceeded worst case test mode and cable configuration. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

Measurement procedures was In accordance with ANSI C63.4 or CISPR 32.

◆ Calculation

- Conducted Emissions

$\text{QuasiPeak[dBuV]} / \text{CAverage[dBuV]} = \text{Reading Value[dBuV]} + \text{Corr. [dB]}$

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 GHz)

$\text{Result(QP)} [\text{dB}(\mu\text{V/m})] = (\text{Reading(QP)}[\text{dB}(\mu\text{V})] + \text{c.f}[\text{dB}(1/\text{m})])$

$\text{Margin(QP)}[\text{dB}] = \text{Limit}[\text{dB}(\mu\text{V/m})] - \text{Result(QP)} [\text{dB}(\mu\text{V/m})]$

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 GHz)

$\text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})] = (\text{Reading(PK/CAV)}[\text{dB}(\mu\text{V})] + \text{c.f}[\text{dB}(1/\text{m})])$

$\text{Margin(PK/CAV)}[\text{dB}] = \text{Limit}[\text{dB}(\mu\text{V/m})] - \text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})]$

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



6 Test Item

6.1 Radiated Emissions(Below 1 GHz)

6.1.1 Test Equipment


Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2026-02-12	2027-02-12	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100574	2026-04-24	2027-04-24	■
TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	2024-11-08	2026-11-08	■

6.1.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m

6.1.3 Test Conditions :

Temperature	Relative Humidity
(23.1 ~ 23.1) °C	(36.8 ~ 36.8) % R.H.


6.1.4 Diagram of test setup





6.1.5 Test Result

- Test Date : 2026-05-11
- Test Mode : Mode 1(FCC)




※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM261605-R1

Page 13 / 20

- Test Date : 2026-05-11
- Test Mode : Mode 1(IC)




※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM261605-R1

Page 14 / 20

- Test Date : 2026-05-11
- Test Mode : Mode 2(FCC)




※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM261605-R1

Page 15 / 20

- Test Date : 2026-05-11
- Test Mode : Mode 2(IC)



※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.1.6 Remark

Complies with the test requirements.
Mode 1 , Mode 2 : 433 MHz (Exclusion band)



6.2 Radiated Emissions(Above 1 GHz)

6.2.1 Test Equipment


Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #5	-	SY Corporation	-	-	-	■
ES10/RE Software	ES10/RE	TOYO	2022.01.000	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2026-02-12	2027-02-12	■
PREAMPLIFIER	8449B	HP	3008A00538	2026-04-29	2027-04-29	■
HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	2025-11-05	2026-11-05	■
ATTENUATOR	8491B	HP	23094	2026-02-12	2027-02-12	■

6.2.2 Test Location : SEMI ANECHOIC CHAMBER #5

6.2.3 Test Conditions :

Temperature	Relative Humidity
(21.9 ~ 21.9) °C	(36.8 ~ 36.8) % R.H.


6.2.4 Diagram of test setup





6.2.5 Test Result

- Test Date : 2026-05-11
- Test Mode : Mode 1



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB (μV)]	Reading PK [dB (μV)]	c.f. [dB (1/m)]	Result AV [dB (μV/m)]	Result PK [dB (μV/m)]	Limit AV [dB (μV/m)]	Limit PK [dB (μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1046.669	V	31.4	44.9	-1.1	30.3	43.8	60.0	80.0	29.7	36.2	100.0	318.3	
2	1108.330	H	31.3	44.0	-0.8	30.5	43.2	60.0	80.0	29.5	36.8	280.0	184.0	
3	1190.177	H	30.5	43.8	-0.3	30.2	43.5	60.0	80.0	29.8	36.5	265.0	319.1	
4	1292.789	V	30.5	43.8	0.2	30.7	44.0	60.0	80.0	29.3	36.0	100.0	104.5	
5	1361.936	H	30.9	43.9	0.6	31.5	44.5	60.0	80.0	28.5	35.5	277.0	43.5	
6	1439.505	H	30.3	43.6	1.0	31.3	44.6	60.0	80.0	28.7	35.4	251.0	309.8	
7	1512.102	V	31.7	43.6	1.4	33.1	45.0	60.0	80.0	26.9	35.0	100.0	354.7	
8	1562.299	H	30.0	43.9	1.6	31.6	45.5	60.0	80.0	28.4	34.5	293.0	330.9	
9	1723.203	V	30.0	43.5	2.3	32.3	45.8	60.0	80.0	27.7	34.2	100.0	34.1	
10	1804.706	H	29.8	44.6	2.7	32.5	47.3	60.0	80.0	27.5	32.7	271.0	321.6	
11	1864.447	V	29.4	43.3	2.9	32.3	46.2	60.0	80.0	27.7	33.8	114.0	315.8	
12	1946.029	V	28.9	42.5	3.1	32.0	45.6	60.0	80.0	28.0	34.4	108.0	99.3	


※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

※ The Average of the test data is the cispr average result.



○ Test Date : 2026-05-11

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB (μV)]	Reading PK [dB (μV)]	c.f. [dB (1/m)]	Result AV [dB (μV/m)]	Result PK [dB (μV/m)]	Limit AV [dB (μV/m)]	Limit PK [dB (μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1212.770	H	30.6	45.0	-0.2	30.4	44.8	60.0	80.0	29.6	35.2	255.0	283.3	
2	1286.894	H	30.8	43.8	0.2	31.0	44.0	60.0	80.0	29.0	36.0	260.0	27.3	
3	1311.466	H	31.1	43.7	0.3	31.4	44.0	60.0	80.0	28.6	36.0	221.0	8.7	
4	1335.517	V	30.7	44.5	0.4	31.1	44.9	60.0	80.0	28.9	35.1	105.0	139.1	
5	1406.994	V	30.0	43.4	0.8	30.8	44.2	60.0	80.0	29.2	35.8	100.0	359.4	
6	1432.830	V	29.9	43.8	0.9	30.8	44.7	60.0	80.0	29.2	35.3	100.0	347.5	
7	1488.258	H	30.9	43.2	1.2	32.1	44.4	60.0	80.0	27.9	35.6	278.0	187.0	
8	1590.269	V	30.1	43.8	1.7	31.8	45.5	60.0	80.0	28.2	34.5	100.0	98.9	
9	1674.400	H	30.2	44.0	2.1	32.3	46.1	60.0	80.0	27.7	33.9	270.0	5.7	
10	1772.771	V	29.7	43.2	2.5	32.2	45.7	60.0	80.0	27.8	34.3	110.0	221.0	
11	1817.206	V	29.4	43.9	2.7	32.1	46.6	60.0	80.0	27.9	33.4	100.0	23.2	
12	1886.993	H	29.8	43.5	2.9	32.7	46.4	60.0	80.0	27.3	33.6	290.0	256.5	

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

※ The Average of the test data is the cispr average result.


6.2.6 Remark

Complies with the test requirements.




7 Test Setup Photos and EUT Photographs


7.1 Test Setup Photos




<Radiated Emissions(Below 1 GHz) - Front> - Mode 1 , Mode 2



<Radiated Emissions(Below 1 GHz) - Rear> - Mode 1 , Mode 2



<Radiated Emissions(Above 1 GHz) - Front> - Mode 1 , Mode 2



<Radiated Emissions(Above 1 GHz) - Rear> - Mode 1 , Mode 2

The End.