

RF Exposure Evaluation Report

Report Reference No......: **MTWG2206116-H**

FCC ID.....: **2ASBG-YH8203GX**

Compiled by

(position+printed name+signature)..: File administrators Alisa Luo

Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng

Approved by

(position+printed name+signature)..: Manager Yvette Zhou

Date of issue.....: **July 25,2022**

Representative Laboratory Name .: **Shenzhen Most Technology Service Co., Ltd.**

Address: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name.....: **FUJIAN YIHE ELECTRONICS CO., LTD**

Address: JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,
355000 CHINA

Test specification/ Standard: **47 CFR Part 1.1307**

47 CFR Part 1.1310

KDB447498D01 General RF Exposure Guidance v06

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Massage Chair

Trade Mark: Mynta

Manufacturer: **FUJIAN YIHE ELECTRONICS CO., LTD**

Model/Type reference.....: YH-8203GX

Listed Models: M1611E,M1611B,M1611,M1610

Modulation Type: GFSK, $\pi/4$ DQPSK, 8DPSK

Operation Frequency.....: 2402MHz to 2480MHz

Hardware Version.....: V1.1

Software Version: V1.0

Rating: 85-130V,50-60Hz,5A,150W

Result.....: **PASS**

TEST REPORT

Equipment under Test : Massage Chair

Model /Type : YH-8203GX

Listed Models : M1611E,M1611B, M1611,M1610

Remark : Same product, but different model.

Applicant : **FUJIAN YIHE ELECTRONICS CO., LTD**

Address : JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,
355000 CHINA

Manufacturer : **FUJIAN YIHE ELECTRONICS CO., LTD**

Address : JI'AN ROAD, QINXIYANG INDUSTRIAL PARK, FUAN, FUJIAN,
355000 CHINA

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2022-07-25	Initial Issue	Alisa Luo

2. SAR Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.1.3 EUT RF Exposure

Antenna Gain: -0.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.4 in linear scale. Output Power Into Antenna & RF Exposure Evaluation Distance:

BLE

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	5.845	5.845 ± 1	6.845
Middle(2440MHz)	7.007	7.007 ± 1	8.007
Highest(2480MHz)	6.426	6.426 ± 1	7.426

BLE

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest(2480 MHz)	8.007	6.32	0	0.0012	1.0	Pass

Note: 1) Refer to report **MTWG2206116-R2** for EUT test Max Conducted average Output Power value.Note: 2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (6.32 \cdot 1) / (4 \cdot 3.1416 \cdot 20^2) = 0.0012$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

EDR

GFSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	-0.398	-0.398 ± 1	0.602
Middle(2441MHz)	0.817	0.817 ± 1	1.817
Highest(2480MHz)	2.092	2.092 ± 1	3.092

$\pi/4$ DQPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	-0.431	-0.431 ± 1	0.569
Middle(2441MHz)	0.773	0.773 ± 1	1.773
Highest(2480MHz)	2.033	2.033 ± 1	3.033

8DPSK			
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power
			(dBm)
Lowest(2402 MHz)	-0.380	-0.380 ± 1	0.620
Middle(2441MHz)	0.706	0.706 ± 1	1.706
Highest(2480MHz)	2.046	2.046 ± 1	3.046

EDR

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Maximum Peak Conducted Output Power (MW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest(2441 MHz)	3.092	2.03	0	0.0004	1.0	Pass

Note: 1) Refer to report **MTWG2206116-R1** for EUT test Max Conducted average Output Power value.

Note: 2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (2.03 \cdot 0.89) / (4 \cdot 3.1416 \cdot 20^2) = 0.0004$

Note: 3) EUT's Bluetooth module is more than 20cm away from the human body.

.....THE END OF REPORT.....