# FCC Report

| | |
|---|---|
| **Applicant:** | Huizhou Tuoying Technology Limited Company |
| **Address of Applicant:** | Second Floor No.1 Factory, Lianhong Industrial Park, Sanhe Development Zone, Huiyang District, Huizhou City, China |
| **Manufacturer/Factory:** | Huizhou Tuoying Technology Limited Company |
| **Address of Manufacturer/Factory:** | Second Floor No.1 Factory, Lianhong Industrial Park, Sanhe Development Zone, Huiyang District, Huizhou City, China |
| **Equipment Under Test (EUT)** | |
| Product Name: | Fold four axis Toy UAV |
| Model No.: | TE-F360 |
| Trade Mark: | TOPE |
| **FCC ID:** | 2ASBP-TE-F360 |
| **Applicable standards:** | FCC CFR Title 47 Part 15 Subpart C Section 15.247 |
| **Date of sample receipt:** | December 26, 2018 |
| **Date of Test:** | December 27, 2018-January 12, 2019 |
| **Date of report issued:** | January 15, 2019 |
| **Test Result :** | PASS * |

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

**Robinson Lo**
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date | Description |
|---|---|---|
| *00* | *January 15, 2019* | *Original* |
| | | |
| | | |
| | | |
| | | |

| | | | |
|---|---|---|---|
| ***Prepared By:*** | ***Project Engineer*** | ***Date:*** | *January 15, 2019* |
| ***Check By:*** | ***Reviewer*** | ***Date:*** | *January 15, 2019* |

# 3 Contents

Page

1 COVER PAGE ..... 1
2 VERSION ..... 2
3 CONTENTS ..... 3
4 TEST SUMMARY ..... 4
5 GENERAL INFORMATION ..... 5
5.1 GENERAL DESCRIPTION OF EUT ..... 5
5.2 TEST MODE ..... 7
5.3 DESCRIPTION OF SUPPORT UNITS ..... 7
5.4 TEST FACILITY ..... 7
5.5 TEST LOCATION ..... 7
5.6 ADDITIONAL INSTRUCTIONS ..... 7
6 TEST INSTRUMENTS LIST ..... 8
7 TEST RESULTS AND MEASUREMENT DATA ..... 10
7.1 ANTENNA REQUIREMENT ..... 10
7.2 CONDUCTED EMISSIONS ..... 11
7.3 CONDUCTED OUTPUT POWER ..... 14
7.4 CHANNEL BANDWIDTH ..... 16
7.5 POWER SPECTRAL DENSITY ..... 18
7.6 BAND EDGES ..... 20
*7.6.1 Conducted Emission Method ..... 20*
*7.6.2 Radiated Emission Method ..... 21*
7.7 SPURIOUS EMISSION ..... 26
*7.7.1 Conducted Emission Method ..... 26*
*7.7.2 Radiated Emission Method ..... 28*
8 TEST SETUP PHOTO ..... 39
9 EUT CONSTRUCTIONAL DETAILS ..... 39

# 4 Test Summary

| Test Item | Section in CFR 47 | Result |
|---|---|---|
| Antenna requirement | 15.203/15.247 (c) | Pass |
| AC Power Line Conducted Emission | 15.207 | Pass |
| Conducted Output Power | 15.247 (b)(3) | Pass |
| Channel Bandwidth | 15.247 (a)(2) | Pass |
| Power Spectral Density | 15.247 (e) | Pass |
| Band Edge | 15.247(d) | Pass |
| Spurious Emission | 15.205/15.209 | Pass |

Pass: The EUT complies with the essential requirements in the standard.

*Remark: Test according to ANSI C63.10:2013.*

**Measurement Uncertainty**

| Test Item | Frequency Range | Measurement Uncertainty | Notes |
|---|---|---|---|
| Radiated Emission | 9kHz ~ 30MHz | ± 4.34dB | (1) |
| Radiated Emission | 30MHz ~ 1000MHz | ± 4.24dB | (1) |
| Radiated Emission | 1GHz ~ 26.5GHz | ± 4.68dB | (1) |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | ± 3.45dB | (1) |
| Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%. | | | |

# 5 General Information

## 5.1 General Description of EUT

| | |
|---|---|
| Product Name: | Fold four axis Toy UAV |
| Model No.: | TE-F360 |
| Test sample(s) ID: | GTS201812000159-1 |
| Sample(s) Status | Engineer sample |
| Operation Frequency: | 2405MHz-2475MHz |
| Channel Numbers: | 15 |
| Channel Separation: | 5MHz |
| Modulation Type: | GFSK |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | 2.0dBi(declare by manufacturer) |
| Power Supply: | DC 7.6V 4000mAh 34.8Wh |

| Operation Frequency each of channel | | | | | | | |
|---|---|---|---|---|---|---|---|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2405MHz | 5 | 2425MHz | 9 | 2445MHz | 13 | 2465MHz |
| 2 | 2410MHz | 6 | 2430MHz | 10 | 2450MHz | 14 | 2470MHz |
| 3 | 2415MHz | 7 | 2435MHz | 11 | 2455MHz | 15 | 2475MHz |
| 4 | 2420MHz | 8 | 2440MHz | 12 | 2460MHz | | |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---|---|
| The lowest channel | 2405MHz |
| The middle channel | 2440MHz |
| The Highest channel | 2475MHz |

## 5.2 Test mode

| | |
|---|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode. |
| *Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.* | |

## 5.3 Description of Support Units

None

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2.

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

● **CNAS (No. CNAS L5775)**

CNAS has accredited Global United Technology Services Co., Ltd., to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

## 5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

## 5.6 Additional Instructions

EUT Software Settings:

Special test software was pre-built-in by manufacturer. Power set default

# 6 Test Instruments list

| Radiated Emission: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | 3m Semi- Anechoic Chamber | ZhongYu Electron | 9.2(L)*6.2(W)* 6.4(H) | GTS250 | July. 03 2015 | July. 02 2020 |
| 2 | Control Room | ZhongYu Electron | 6.2(L)*2.5(W)* 2.4(H) | GTS251 | N/A | N/A |
| 3 | EMI Test Receiver | Rohde & Schwarz | ESU26 | GTS203 | June. 27 2018 | June. 26 2019 |
| 4 | BiConiLog Antenna | SCHWARZBECK MESS-ELEKTRONIK | VULB9163 | GTS214 | June. 27 2018 | June. 26 2019 |
| 5 | Double -ridged waveguide horn | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120 D | GTS208 | June. 27 2018 | June. 26 2019 |
| 6 | Horn Antenna | ETS-LINDGREN | 3160 | GTS217 | June. 27 2018 | June. 26 2019 |
| 7 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 8 | Coaxial Cable | GTS | N/A | GTS213 | June. 27 2018 | June. 26 2019 |
| 9 | Coaxial Cable | GTS | N/A | GTS211 | June. 27 2018 | June. 26 2019 |
| 10 | Coaxial cable | GTS | N/A | GTS210 | June. 27 2018 | June. 26 2019 |
| 11 | Coaxial Cable | GTS | N/A | GTS212 | June. 27 2018 | June. 26 2019 |
| 12 | Amplifier(100kHz-3GHz) | HP | 8347A | GTS204 | June. 27 2018 | June. 26 2019 |
| 13 | Amplifier(2GHz-20GHz) | HP | 84722A | GTS206 | June. 27 2018 | June. 26 2019 |
| 14 | Amplifier (18-26GHz) | Rohde & Schwarz | AFS33-18002 650-30-8P-44 | GTS218 | June. 27 2018 | June. 26 2019 |
| 15 | Band filter | Amindeon | 82346 | GTS219 | June. 27 2018 | June. 26 2019 |
| 16 | Power Meter | Anritsu | ML2495A | GTS540 | June. 27 2018 | June. 26 2019 |
| 17 | Power Sensor | Anritsu | MA2411B | GTS541 | June. 27 2018 | June. 26 2019 |
| 18 | Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | GTS575 | June. 27 2018 | June. 26 2019 |
| 19 | Splitter | Agilent | 11636B | GTS237 | June. 27 2018 | June. 26 2019 |
| 20 | Loop Antenna | ZHINAN | ZN30900A | GTS534 | June. 27 2018 | June. 26 2019 |

| General used equipment: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | Humidity/ Temperature Indicator | KTJ | TA328 | GTS243 | June. 27 2018 | June. 26 2019 |
| 2 | Barometer | ChangChun | DYM3 | GTS255 | June. 27 2018 | June. 26 2019 |

| Conducted Emission | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Inventory No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | Shielding Room | ZhongYu Electron | 7.3(L)x3.1(W)x2.9(H) | GTS252 | May.16 2014 | May.15 2019 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 27 2018 | June. 26 2019 |
| 3 | Coaxial Switch | ANRITSU CORP | MP59B | GTS225 | June. 27 2018 | June. 26 2019 |
| 4 | Artificial Mains Network | SCHWARZBECK MESS | NSLK8127 | GTS226 | June. 27 2018 | June. 26 2019 |
| 5 | Coaxial Cable | GTS | N/A | GTS227 | N/A | N/A |
| 6 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 7 | Thermo meter | KTJ | TA328 | GTS233 | June. 27 2018 | June. 26 2019 |
| 8 | Absorbing clamp | Elektronik-Feinmechanik | MDS21 | GTS229 | June. 27 2018 | June. 26 2019 |

| RF Conducted Test: | | | | | | |
|---|---|---|---|---|---|---|
| **Item** | **Test Equipment** | **Manufacturer** | **Model No.** | **Serial No.** | **Cal.Date (mm-dd-yy)** | **Cal.Due date (mm-dd-yy)** |
| 1 | MXA Signal Analyzer | Agilent | N9020A | GTS566 | June. 27 2018 | June. 26 2019 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 27 2018 | June. 26 2019 |
| 3 | Spectrum Analyzer | Agilent | E4440A | GTS533 | June. 27 2018 | June. 26 2019 |
| 4 | MXG vector Signal Generator | Agilent | N5182A | GTS567 | June. 27 2018 | June. 26 2019 |
| 5 | ESG Analog Signal Generator | Agilent | E4428C | GTS568 | June. 27 2018 | June. 26 2019 |
| 6 | USB RF Power Sensor | DARE | RPR3006W | GTS569 | June. 27 2018 | June. 26 2019 |
| 7 | RF Switch Box | Shongyi | RFSW3003328 | GTS571 | June. 27 2018 | June. 26 2019 |
| 8 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 27 2018 | June. 26 2019 |
| 9 | Programmable Constant Temp & Humi Test Chamber | WEWON | WHTH-150L-40-880 | GTS572 | June. 27 2018 | June. 26 2019 |

# 7 Test results and Measurement Data

## 7.1 Antenna requirement

| Standard requirement: | FCC Part15 C Section 15.203 /247(c) |
|---|---|

**15.203 requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**15.247(c) (1)(i) requirement:**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**E.U.T Antenna:**

*The antenna is Integral antenna, the best case gain of the antenna is 2.0dBi*



## 7.2 Conducted Emissions

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.207 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 150KHz to 30MHz |
| Class / Severity: | Class B |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto |
| Limit: | |

| Frequency range (MHz) | Limit (dBuV) | |
|---|---|---|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

Test setup:




*Remark:*
*E.U.T: Equipment Under Test*
*LISN: Line Impedence Stabilization Network*
*Test table height=0.8m*

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2009 on conducted measurement.

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test voltage: | AC 120V, 60Hz | | | | | |
| Test results: | Pass | | | | | |

**Measurement data**

Line:




| Freq MHz | Reading level dBuV | LISN/ISN factor dB/m | Cable loss dB | Level dBuV | Limit level dBuV | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|
| 0.15 | 44.13 | 0.40 | 0.07 | 44.60 | 65.82 | -21.22 | QP |
| 0.15 | 36.86 | 0.40 | 0.07 | 37.33 | 55.82 | -18.49 | Average |
| 0.20 | 39.37 | 0.40 | 0.11 | 39.88 | 63.54 | -23.66 | QP |
| 0.20 | 31.51 | 0.40 | 0.11 | 32.02 | 53.54 | -21.52 | Average |
| 0.26 | 34.03 | 0.40 | 0.10 | 34.53 | 61.56 | -27.03 | QP |
| 0.26 | 27.06 | 0.40 | 0.10 | 27.56 | 51.56 | -24.00 | Average |
| 0.63 | 30.21 | 0.28 | 0.12 | 30.61 | 56.00 | -25.39 | QP |
| 0.63 | 23.97 | 0.28 | 0.12 | 24.37 | 46.00 | -21.63 | Average |
| 2.17 | 20.36 | 0.20 | 0.18 | 20.74 | 56.00 | -35.26 | QP |
| 2.17 | 12.25 | 0.20 | 0.18 | 12.63 | 46.00 | -33.37 | Average |
| 12.72 | 31.67 | 0.20 | 0.21 | 32.08 | 60.00 | -27.92 | QP |
| 12.72 | 24.04 | 0.20 | 0.21 | 24.45 | 50.00 | -25.55 | Average |

Neutral:




| Freq MHz | Reading level dBuV | LISN/ISN factor dB/m | Cable loss dB | Level dBuV | Limit level dBuV | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|
| 0.15 | 44.06 | 0.40 | 0.07 | 44.53 | 65.87 | -21.34 | QP |
| 0.15 | 37.04 | 0.40 | 0.07 | 37.51 | 55.87 | -18.36 | Average |
| 0.20 | 39.63 | 0.40 | 0.11 | 40.14 | 63.49 | -23.35 | QP |
| 0.20 | 33.37 | 0.40 | 0.11 | 33.88 | 53.49 | -19.61 | Average |
| 0.64 | 34.36 | 0.28 | 0.12 | 34.76 | 56.00 | -21.24 | QP |
| 0.64 | 28.44 | 0.28 | 0.12 | 28.84 | 46.00 | -17.16 | Average |
| 1.28 | 27.55 | 0.20 | 0.16 | 27.91 | 56.00 | -28.09 | QP |
| 1.28 | 21.14 | 0.20 | 0.16 | 21.50 | 46.00 | -24.50 | Average |
| 2.93 | 25.99 | 0.20 | 0.19 | 26.38 | 56.00 | -29.62 | QP |
| 2.93 | 18.80 | 0.20 | 0.19 | 19.19 | 46.00 | -26.81 | Average |
| 12.65 | 30.11 | 0.20 | 0.21 | 30.52 | 60.00 | -29.48 | QP |
| 12.65 | 20.62 | 0.20 | 0.21 | 21.03 | 50.00 | -28.97 | Average |

*Notes:*

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. *Final Level =Receiver Read level + Correct factor*
4. *Correct factor = LISN Factor + Cable Loss*
5. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*

## 7.3 Conducted Output Power

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05 |
| Limit: | 30dBm |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

**Measurement Data**

| Test channel | Peak Output Power (dBm) | Limit(dBm) | Result |
|---|---|---|---|
| Lowest | 8.40 | 30.00 | Pass |
| Middle | 8.28 | | |
| Highest | 8.09 | | |

**Test plot as follows:**




Lowest channel




Middle channel




Highest channel

## 7.4 Channel Bandwidth

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05 |
| Limit: | >500KHz |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

**Measurement Data**

| Test channel | Channel Bandwidth (kHz) | Limit(KHz) | Result |
|---|---|---|---|
| Lowest | 557.079 | >500 | Pass |
| Middle | 559.591 | | |
| Highest | 552.879 | | |

**Test plot as follows:**




Lowest channel




Middle channel




Highest channel

## 7.5 Power Spectral Density

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (e) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05 |
| Limit: | 8dBm/3kHz |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

**Measurement Data**

| Test channel | Power Spectral Density (dBm/3KHz) | Limit(dBm/3kHz) | Result |
|---|---|---|---|
| Lowest | -4.16 | 8.00 | Pass |
| Middle | -4.22 | | |
| Highest | -4.44 | | |

**Test plot as follows:**




Lowest channel




Middle channel




Highest channel

## 7.6 Band edges

### 7.6.1 Conducted Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

**Test plot as follows:**




Lowest channel




Highest channel

### 7.6.2 Radiated Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2390MHz, 2483.5MHz to 2500MHz) data was showed. |
| Test site: | Measurement Distance: 3m |
| Receiver setup: | |

| Frequency | Detector | RBW | VBW | Value |
|---|---|---|---|---|
| Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | RMS | 1MHz | 3MHz | Average |

Limit:

| Frequency | Limit (dBuV/m @3m) | Value |
|---|---|---|
| Above 1GHz | 54.00 | Average |
| | 74.00 | Peak |

Test setup:




Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

| | | | | | | |
|---|---|---|---|---|---|---|
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test results: | Pass | | | | | |

Measurement data:

*Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

| Test channel: | Lowest |
|---|---|

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 2310.000 | 41.50 | 27.14 | 6.19 | 42.04 | 32.79 | 54.00 | -21.21 | Average |
| 2310.000 | 53.15 | 27.14 | 6.19 | 42.04 | 44.44 | 74.00 | -29.56 | Peak |
| 2390.000 | 44.50 | 27.37 | 6.31 | 42.11 | 36.07 | 54.00 | -17.93 | Average |
| 2390.000 | 63.96 | 27.37 | 6.31 | 42.11 | 55.53 | 74.00 | -18.47 | Peak |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 2310.000 | 33.79 | 27.14 | 6.19 | 42.04 | 25.08 | 54.00 | -28.92 | Average |
| 2310.000 | 45.11 | 27.14 | 6.19 | 42.04 | 36.40 | 74.00 | -37.60 | Peak |
| 2390.000 | 51.55 | 27.37 | 6.31 | 42.11 | 43.12 | 54.00 | -10.88 | Average |
| 2390.000 | 62.88 | 27.37 | 6.31 | 42.11 | 54.45 | 74.00 | -19.55 | Peak |

| Test channel: | Highest |
|---|---|

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 2483.500 | 51.50 | 27.66 | 6.45 | 42.01 | 43.60 | 54.00 | -10.40 | Average |
| 2483.500 | 61.78 | 27.66 | 6.45 | 42.01 | 53.88 | 74.00 | -20.12 | Peak |
| 2490.658 | 48.50 | 27.68 | 6.46 | 42.01 | 40.63 | 54.00 | -13.37 | Average |
| 2490.658 | 62.60 | 27.68 | 6.46 | 42.01 | 54.73 | 74.00 | -19.27 | Peak |
| 2500.000 | 33.50 | 27.70 | 6.47 | 42.00 | 25.67 | 54.00 | -28.33 | Average |
| 2500.000 | 44.53 | 27.70 | 6.47 | 42.00 | 36.70 | 74.00 | -37.30 | Peak |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 2483.500 | 42.50 | 27.66 | 6.45 | 42.01 | 34.60 | 54.00 | -19.40 | Average |
| 2483.500 | 53.29 | 27.66 | 6.45 | 42.01 | 45.39 | 74.00 | -28.61 | Peak |
| 2490.658 | 42.50 | 27.68 | 6.46 | 42.01 | 34.63 | 54.00 | -19.37 | Average |
| 2490.658 | 52.17 | 27.68 | 6.46 | 42.01 | 44.30 | 74.00 | -29.70 | Peak |
| 2500.000 | 33.50 | 27.70 | 6.47 | 42.00 | 25.67 | 54.00 | -28.33 | Average |
| 2500.000 | 44.60 | 27.70 | 6.47 | 42.00 | 36.77 | 74.00 | -37.23 | Peak |

Remark:

1. *Final Level =Receiver Read level + Correct factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *Correct factor= Antenna Factor + Cable Loss – Preamplifier Factor*

## 7.7 Spurious Emission

### 7.7.1 Conducted Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

**Test plot as follows:**

Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

### 7.7.2 Radiated Emission Method

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.209 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 9kHz to 25GHz |
| Test site: | Measurement Distance: 3m |
| Receiver setup: | |

| Frequency | Detector | RBW | VBW | Value |
|---|---|---|---|---|
| 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| 30MHz-1GHz | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
| Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | Peak | 1MHz | 10Hz | Average |

Limit:
(Spurious Emissions)

| Frequency | Limit (uV/m) | Value | Measurement Distance |
|---|---|---|---|
| 0.009MHz-0.490MHz | 2400/F(KHz) | QP | 300m |
| 0.490MHz-1.705MHz | 24000/F(KHz) | QP | 300m |
| 1.705MHz-30MHz | 30 | QP | 30m |
| 30MHz-88MHz | 100 | QP | 3m |
| 88MHz-216MHz | 150 | QP | |
| 216MHz-960MHz | 200 | QP | |
| 960MHz-1GHz | 500 | QP | |
| Above 1GHz | 500 | Average | |
| | 5000 | Peak | |

| | |
|---|---|
| Limit:<br>(band edge) | Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation. |

| | |
|---|---|
| Test setup: | Below 30MHz<br>  <br><br>Below 1GHz<br>  <br><br>Above 1GHz<br>  <br> |
| Test Procedure: | 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.<br>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.<br>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both |

| | | | | | | |
|---|---|---|---|---|---|---|
| | horizontal and vertical polarizations of the antenna are set to make the measurement.<br>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.<br>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.<br>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test environment: | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test results: | Pass | | | | | |

*Remark:*
*Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*

**Measurement Data**

- **9 kHz ~ 30 MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 34.517 | 46.73 | 11.29 | 0.60 | 35.32 | 23.30 | 40.00 | -16.70 | QP |
| 103.080 | 40.23 | 11.83 | 1.22 | 36.75 | 16.53 | 43.50 | -26.97 | QP |
| 204.238 | 44.46 | 10.58 | 1.86 | 37.33 | 19.57 | 43.50 | -23.93 | QP |
| 545.183 | 49.34 | 18.34 | 3.50 | 37.52 | 33.66 | 46.00 | -12.34 | QP |
| 576.644 | 46.68 | 19.00 | 3.63 | 37.53 | 31.78 | 46.00 | -14.22 | QP |
| 656.530 | 40.78 | 19.56 | 3.94 | 37.59 | 26.69 | 46.00 | -19.31 | QP |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 39.437 | 43.37 | 12.11 | 0.65 | 35.63 | 20.50 | 40.00 | -19.50 | QP |
| 48.332 | 45.73 | 12.29 | 0.75 | 36.10 | 22.67 | 40.00 | -17.33 | QP |
| 100.581 | 45.65 | 12.10 | 1.19 | 36.73 | 22.21 | 43.50 | -21.29 | QP |
| 204.238 | 43.49 | 10.58 | 1.86 | 37.33 | 18.60 | 43.50 | -24.90 | QP |
| 545.183 | 42.41 | 18.34 | 3.50 | 37.52 | 26.73 | 46.00 | -19.27 | QP |
| 576.644 | 40.61 | 19.00 | 3.63 | 37.53 | 25.71 | 46.00 | -20.29 | QP |

■ **Above 1GHz**

| Test channel: | Lowest |
|---|---|

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4810.000 | 27.44 | 31.36 | 4.61 | 37.58 | 25.83 | 54.00 | -28.17 | Average |
| 4810.000 | 36.20 | 31.36 | 4.61 | 37.58 | 34.59 | 74.00 | -39.41 | Peak |
| 7215.000 | 26.43 | 35.92 | 6.50 | 35.45 | 33.40 | 54.00 | -20.60 | Average |
| 7215.000 | 32.71 | 35.92 | 6.50 | 35.45 | 39.68 | 74.00 | -34.32 | Peak |
| 9620.000 | 25.47 | 37.76 | 7.98 | 34.97 | 36.24 | 54.00 | -17.76 | Average |
| 9620.000 | 31.95 | 37.76 | 7.98 | 34.97 | 42.72 | 74.00 | -31.28 | Peak |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4810.000 | 30.40 | 31.36 | 4.61 | 37.58 | 28.79 | 54.00 | -25.21 | Average |
| 4810.000 | 38.27 | 31.36 | 4.61 | 37.58 | 36.66 | 74.00 | -37.34 | Peak |
| 7215.000 | 25.28 | 35.92 | 6.50 | 35.45 | 32.25 | 54.00 | -21.75 | Average |
| 7215.000 | 32.34 | 35.92 | 6.50 | 35.45 | 39.31 | 74.00 | -34.69 | Peak |
| 9620.000 | 23.39 | 37.76 | 7.98 | 34.97 | 34.16 | 54.00 | -19.84 | Average |
| 9620.000 | 32.87 | 37.76 | 7.98 | 34.97 | 43.64 | 74.00 | -30.36 | Peak |

| Test channel: | Middle |
|---|---|

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4880.000 | 29.83 | 31.48 | 4.69 | 37.59 | 28.41 | 54.00 | -25.59 | Average |
| 4880.000 | 36.45 | 31.48 | 4.69 | 37.59 | 35.03 | 74.00 | -38.97 | Peak |
| 7320.000 | 27.31 | 36.17 | 6.63 | 35.47 | 34.64 | 54.00 | -19.36 | Average |
| 7320.000 | 33.10 | 36.17 | 6.63 | 35.47 | 40.43 | 74.00 | -33.57 | Peak |
| 9760.000 | 26.60 | 38.07 | 8.03 | 35.09 | 37.61 | 54.00 | -16.39 | Average |
| 9760.000 | 32.85 | 38.07 | 8.03 | 35.09 | 43.86 | 74.00 | -30.14 | Peak |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4880.000 | 29.93 | 31.48 | 4.69 | 37.59 | 28.51 | 54.00 | -25.49 | Average |
| 4880.000 | 37.63 | 31.48 | 4.69 | 37.59 | 36.21 | 74.00 | -37.79 | Peak |
| 7320.000 | 27.21 | 36.17 | 6.63 | 35.47 | 34.54 | 54.00 | -19.46 | Average |
| 7320.000 | 33.67 | 36.17 | 6.63 | 35.47 | 41.00 | 74.00 | -33.00 | Peak |
| 9760.000 | 25.28 | 38.07 | 8.03 | 35.09 | 36.29 | 54.00 | -17.71 | Average |
| 9760.000 | 32.54 | 38.07 | 8.03 | 35.09 | 43.55 | 74.00 | -30.45 | Peak |

| Test channel: | Highest |
|---|---|

**Horizontal:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4950.000 | 30.68 | 31.61 | 4.77 | 37.60 | 29.46 | 54.00 | -24.54 | Average |
| 4950.000 | 36.96 | 31.61 | 4.77 | 37.60 | 35.74 | 74.00 | -38.26 | Peak |
| 7425.000 | 27.68 | 36.42 | 6.75 | 35.49 | 35.36 | 54.00 | -18.64 | Average |
| 7425.000 | 33.03 | 36.42 | 6.75 | 35.49 | 40.71 | 74.00 | -33.29 | Peak |
| 9900.000 | 27.15 | 38.38 | 8.09 | 35.21 | 38.41 | 54.00 | -15.59 | Average |
| 9900.000 | 32.37 | 38.38 | 8.09 | 35.21 | 43.63 | 74.00 | -30.37 | Peak |

**Vertical:**




| Freq MHz | Reading level dBuV | Antenna factor dB/m | Cable loss dB | Preamp factor dB | level dBuV | Limit level dBuV/m | Over limit dB | Remark |
|---|---|---|---|---|---|---|---|---|
| 4950.000 | 30.22 | 31.61 | 4.77 | 37.60 | 29.00 | 54.00 | -25.00 | Average |
| 4950.000 | 37.59 | 31.61 | 4.77 | 37.60 | 36.37 | 74.00 | -37.63 | Peak |
| 7425.000 | 27.81 | 36.42 | 6.75 | 35.49 | 35.49 | 54.00 | -18.51 | Average |
| 7425.000 | 32.45 | 36.42 | 6.75 | 35.49 | 40.13 | 74.00 | -33.87 | Peak |
| 9900.000 | 26.79 | 38.38 | 8.09 | 35.21 | 38.05 | 54.00 | -15.95 | Average |
| 9900.000 | 33.15 | 38.38 | 8.09 | 35.21 | 44.41 | 74.00 | -29.59 | Peak |

# 8 Test Setup Photo

Reference to the **appendix I** for details.

# 9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------