


EMC TEST REPORT

Applicant Positec Technology (China) Co., Ltd.
FCC ID 2ASC3KR800
Product Lawn Mowing Robot
Brand KRESS
Model KR800
Report No. EFTA25060090-IE-04-E1V3
Issue Date September 26, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2024)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.



Prepared by: Liu Wei



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	5
1.1	Notes of the Test Report.....	5
1.2	Test Facility	5
1.3	Testing Location.....	5
2	General Description of Equipment Under Test	6
2.1	Applicant and Manufacturer Information	6
2.2	General Information	6
2.3	Applied Standards	8
2.4	Test Mode	9
3	Test Case Results	10
3.1	Radiated Emission	10
3.2	Conducted Emission	15
4	Uncertainty Measurement.....	18
5	Main Test Instruments	19
	ANNEX A: The EUT Appearance	20
	ANNEX B: Test Setup Photos	21

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	September 11, 2025
Rev.1	Updated information and description.	September 20, 2025
Rev.2	Updated description.	September 22, 2025
Rev.3	Updated description.	September 26, 2025
Note: This revised report (Report No.: EFTA25060090-IE-04-E1V3) supersedes and replaces the previously issued report (Report No.: EFTA25060090-IE-04-E1V2). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: June 14, 2025 ~ July 18, 2025 Date of Sample Received: June 6, 2025			
Note: 1. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

2 General Description of Equipment Under Test

2.1 Applicant and Manufacturer Information

Applicant	Positec Technology (China) Co., Ltd.
Applicant address	18, Dongwang Road, Suzhou Industrial Park, Jiangsu 215123, P.R. China
Manufacturer	Positec Technology (China) Co., Ltd.
Manufacturer address	18, Dongwang Road, Suzhou Industrial Park, Jiangsu 215123, P.R. China

2.2 General Information

EUT Description			
Device Type	Movable Device		
Model	KR800		
Lab internal SN	250606-39-001		
HW Version	HV1.51		
SW Version	3.3.2+4		
Power Supply	Battery / Charger		
Power Rating	DC 45V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	Internal Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 14	788 ~ 798	758 ~ 768
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	LTE Band 71	663 ~ 698	617 ~ 652
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4GHz	2400 ~ 2483.5	2400 ~ 2483.5

EUT Accessory	
Charger	Manufacturer: Positec Technology (China) Co., Ltd. Model: KAC841 Input: 220-240V~ 50/60Hz 1800W Output: 60.0V $\overline{\overline{\sim}}$ 30A
Battery (Built-in)	Manufacturer: Positec Technology (China) Co., Ltd. Model: KA3110 DC 45V, 268Ah
Battery (External)	Manufacturer: Positec Technology (China) Co., Ltd. Model: KAC815 60VDC 1500Wh Max 54VDC 25Ah
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.	

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2024)

ANSI C63.4-2014

2.4 Test Mode

Test Mode	
Mode 1	AC power Supply + Charger + Battery (External) + EUT (with Built-in Battery) + Charging
Mode 2	Built-in Battery powered + EUT +Working
Mode 3	Battery (External) + EUT (with Built-in Battery) + Charging

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2, 3	Mode 2
Conducted Emission	Mode 1	Mode 1
After technical evaluation or/and preliminary test, the test data of the worst-case condition was recorded in this report.		

3 Test Case Results

3.1 Radiated Emission

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on the ground plane which has a 15cm non-conductive covering to insulate the EUT from the ground plane. The distance between EUT and receive antenna should be 10 meters below 1GHz; 3 meters for above 1GHz. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.


Test Setup

Below 1GHz



Note: Area side: 21m x 12m

Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits

Class B

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	30.0	Quasi-peak
88-216	33.5	Quasi-peak
216 – 960	36.0	Quasi-peak
960-1000	44.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Frequency range of radiated measurements


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier.

The following graphs display the maximum values of horizontal and vertical by software.

Built-in Battery Powered (DC 45V)




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Polarization	Azimuth (deg)	Correct Factor (dB)
30.536	28.95	30.00	1.05	1.89	V	275.6	-12.55
33.275	26.67	30.00	3.33	1.11	V	185.4	-11.61
36.017	22.59	30.00	7.41	1.04	V	48.1	-10.75
68.502	24.24	30.00	5.76	2.17	V	107.5	-12.06
157.446	25.80	33.50	7.70	1.04	V	99.1	-12.73
226.019	25.92	36.00	10.08	1.14	V	8.3	-9.32

Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak



Radiated Emission from 1GHz to 18GHz

Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. Time [s]
1,123.250	30.07	74.00	43.93	18.39	54.00	35.61	-14.19	V	59.2	2.00	1.000
1,743.750	33.57	74.00	40.43	23.42	54.00	30.58	-12.62	V	85	1.00	1.000
2,799.875	33.45	74.00	40.55	20.48	54.00	33.52	-7.46	V	18.8	1.00	1.000
4,100.375	36.47	74.00	37.53	24.77	54.00	29.23	-4.40	H	93.7	2.00	1.000
6,348.625	45.66	74.00	28.34	33.42	54.00	20.58	3.56	V	221.8	2.00	1.000
11,331.750	48.64	74.00	25.36	36.41	54.00	17.59	7.91	H	167.4	2.00	1.000

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit – MaxPeak / Average

3.2 Conducted Emission


Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on the ground plane which has a 15cm non-conductive covering to insulate the EUT from the ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits


Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50
*: Decreases with the logarithm of the frequency.				

Note: The EUT should meet CLASS B limit.

Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.

AC 120V/60Hz




Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	49.86	---	66.00	16.14	1000.0	9.000	L1	ON	20.9
0.21	---	37.88	53.09	15.21	1000.0	9.000	L1	ON	21.0
0.80	---	45.48	46.00	0.52	1000.0	9.000	L1	ON	20.3
0.80	53.89	---	56.00	2.11	1000.0	9.000	L1	ON	20.3
0.89	---	40.00	46.00	6.00	1000.0	9.000	L1	ON	20.2
0.89	47.59	---	56.00	8.41	1000.0	9.000	L1	ON	20.2
4.77	22.40	---	56.00	33.60	1000.0	9.000	L1	ON	19.4
4.97	---	23.63	46.00	22.37	1000.0	9.000	L1	ON	19.4
8.06	---	20.87	50.00	29.13	1000.0	9.000	L1	ON	19.4
8.17	30.79	---	60.00	29.21	1000.0	9.000	L1	ON	19.4
13.73	---	28.35	50.00	21.65	1000.0	9.000	L1	ON	19.5
18.04	28.26	---	60.00	31.74	1000.0	9.000	L1	ON	19.6

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 kHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	48.30	---	66.00	17.70	1000.0	9.000	N	ON	20.9
0.21	---	37.83	53.09	15.26	1000.0	9.000	N	ON	21.0
0.80	---	45.26	46.00	0.74	1000.0	9.000	N	ON	20.3
0.81	53.29	---	56.00	2.71	1000.0	9.000	N	ON	20.3
0.89	48.17	---	56.00	7.83	1000.0	9.000	N	ON	20.3
0.89	---	40.21	46.00	5.79	1000.0	9.000	N	ON	20.3
4.97	---	22.95	46.00	23.05	1000.0	9.000	N	ON	19.4
4.97	25.99	---	56.00	30.01	1000.0	9.000	N	ON	19.4
8.06	33.19	---	60.00	26.81	1000.0	9.000	N	ON	19.4
8.06	---	20.97	50.00	29.03	1000.0	9.000	N	ON	19.4
13.72	---	28.50	50.00	21.50	1000.0	9.000	N	ON	19.5
17.84	24.91	---	60.00	35.09	1000.0	9.000	N	ON	19.6

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 kHz to 30 MHz

4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	3.39 dB	1.96
Radiated Emission 200MHz – 1GHz	3.82 dB	1.96
Radiated Emission 1GHz – 18GHz	6.51 dB	1.96
Conducted Emission	2.57 dB	2

5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	101667	2025-05-06	2026-05-05
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	01614	2023-09-13	2026-09-12
Signal Analyzer	R&S	FSV3044	101132	2025-05-06	2026-05-05
Horn Antenna	R&S	HF907	102724	2024-7-23	2027-7-22
Software	R&S	ELEKTRA	5.02.1	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2024-12-02	2026-12-01
EMI Test Receiver	R&S	ESR	101667	2025-05-06	2026-05-05
Software	R&S	EMC32	10.35.10	/	/

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

***** END OF REPORT *****