



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

# TEST REPORT

## 47 CFR Part 15, Subpart C 15.247

Report Reference No.: CTL2507222072-WF02

Compiled by:  
( position+printed name+signature)

Happy Guo  
(File administrators)

Tested by:  
( position+printed name+signature)

Jack Wang  
(Test Engineer)

Approved by:  
( position+printed name+signature)

Ivan Xie  
(Manager)



Product Name: Car Diagnostic Tool

Model/Type reference: DS500 BT

List Model(s): DS510 BT, DS520 BT, DS530 BT, DS540 BT, DS550 BT, DS560 BT, DS570 BT, DS580 BT, DS590 BT

Trade Mark: ANCEL

FCC ID: 2ASC7DS500BT

Applicant's name: OBDSpace Technology Co., Ltd.

Address of applicant: Room D03, Building A, No.973, MinZhi Avenue LongHua district, Shenzhen City, China

Test Firm: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

Test specification:

Standard: 47 CFR Part 15, Subpart C 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.

TRF Originator: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF: Dated 2011-01

Date of receipt of test item: July 24, 2025

Date of Test Date: July 27, 2025-October 14, 2025

Date of Issue: October 16, 2025

Result: Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

|                          |                           |                                   |
|--------------------------|---------------------------|-----------------------------------|
| <b>Test Report No. :</b> | <b>CTL2507222072-WF02</b> | October 16, 2025<br>Date of issue |
|--------------------------|---------------------------|-----------------------------------|

Equipment under Test : Car Diagnostic Tool

Sample No : CTL250722207013

Model /Type : DS500 BT

Listed Models : DS510 BT, DS520 BT, DS530 BT, DS540 BT, DS550 BT, DS560 BT, DS570 BT, DS580 BT, DS590 BT

**Applicant** : **OBDSPACE TECHNOLOGY CO.,LTD**

Address : Room D03, Building A, No.973, MinZhi Avenue  
LongHua district, Shenzhen City, China

**Manufacturer** : **OBDSPACE TECHNOLOGY CO.,LTD**

Address : Room D03, Building A, No.973, MinZhi Avenue  
LongHua district, Shenzhen City, China

| Test result | Pass * |
|-------------|--------|
|-------------|--------|

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

**\*\* Modified History \*\***

[illegible]

**Table of Contents****Page**

|                                                         |           |
|---------------------------------------------------------|-----------|
| <b>1. SUMMARY .....</b>                                 | <b>5</b>  |
| 1.1. TEST STANDARDS .....                               | 5         |
| 1.2. TEST DESCRIPTION .....                             | 5         |
| 1.3. TEST FACILITY .....                                | 6         |
| 1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY .....     | 6         |
| <b>2. GENERAL INFORMATION .....</b>                     | <b>7</b>  |
| 2.1. ENVIRONMENTAL CONDITIONS .....                     | 7         |
| 2.2. GENERAL DESCRIPTION OF EUT .....                   | 7         |
| 2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY ..... | 8         |
| 2.4. EQUIPMENTS USED DURING THE TEST .....              | 9         |
| 2.5. RELATED SUBMITTAL(S) / GRANT (S) .....             | 9         |
| 2.6. MODIFICATIONS .....                                | 9         |
| <b>3. TEST CONDITIONS AND RESULTS .....</b>             | <b>10</b> |
| 3.1. CONDUCTED EMISSIONS TEST .....                     | 10        |
| 3.2. RADIATED EMISSIONS AND BAND EDGE .....             | 13        |
| 3.3. MAXIMUM CONDUCTED OUTPUT POWER .....               | 23        |
| 3.4. POWER SPECTRAL DENSITY .....                       | 24        |
| 3.5. 6DB BANDWIDTH .....                                | 25        |
| 3.6. OUT-OF-BAND EMISSIONS .....                        | 26        |
| 3.7. ANTENNA REQUIREMENT .....                          | 27        |
| <b>4. TEST SETUP PHOTOS OF THE EUT .....</b>            | <b>28</b> |
| <b>5. PHOTOS OF THE EUT .....</b>                       | <b>28</b> |

# 1. SUMMARY

## 1.1. TEST STANDARDS

The tests were performed according to following standards:

[47 CFR Part 15, Subpart C 15.247](#) Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2020](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 v05r02](#): KDB558074 D01 15.247 Meas Guidance v05r02

## 1.2. Test Description

|                                                |                                |      |
|------------------------------------------------|--------------------------------|------|
| 47 CFR Part 15, Subpart C 15.247               |                                |      |
| 47 CFR Part 15, Subpart C 15.207               | AC Power Conducted Emission    | PASS |
| 47 CFR Part 15, Subpart C 15.247(a)(2)         | 6dB Bandwidth                  | PASS |
| 47 CFR Part 15, Subpart C 15.247(d)            | Spurious RF Conducted Emission | PASS |
| 47 CFR Part 15, Subpart C 15.247(b)            | Maximum Conducted Output Power | PASS |
| 47 CFR Part 15, Subpart C 15.247(e)            | Power Spectral Density         | PASS |
| 47 CFR Part 15, Subpart C 15.109/15.205/15.209 | Radiated Emissions             | PASS |
| 47 CFR Part 15, Subpart C 15.247(d)            | Band Edge                      | PASS |
| 47 CFR Part 15, Subpart C 15.203/15.247 (b)    | Antenna Requirement            | PASS |

### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.10 and CISPR 32/EN 55032 requirements.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

##### A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

##### IC Registration No.: 9618B

##### CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B.

##### FCC-Registration No.: 399832

##### Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

| Test                                            | Measurement Uncertainty                                 | Notes |
|-------------------------------------------------|---------------------------------------------------------|-------|
| Transmitter power Radiated                      | $\pm 2.20$ dB                                           | (1)   |
| Radiated Emission 9kHz~30MHz                    | $\pm 3.66$ dB                                           | (1)   |
| Radiated Emission 30~1000MHz                    | $\pm 4.08$ dB                                           | (1)   |
| Radiated Emission Above 1GHz                    | $\pm 4.32$ dB                                           | (1)   |
| DTS Bandwidth                                   | $\pm 1.9\%$                                             | (1)   |
| Maximum Conducted Output Power                  | $\pm 1.18$ dB                                           | (1)   |
| Maximum Power Spectral Density Level            | $\pm 0.98$ dB                                           | (1)   |
| Band-edge                                       | $\pm 1.21$ dB                                           | (1)   |
| Unwanted Emissions In Non-restricted Freq Bands | 9kHz-7GHz: $\pm 1.09$ dB<br>7GHz-26.5GHz: $\pm 3.27$ dB | (1)   |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                     |         |
|---------------------|---------|
| Normal Temperature: | 25°C    |
| Relative Humidity:  | 55 %    |
| Air Pressure:       | 101 kPa |

### 2.2. General Description of EUT

|                             |                                                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------|
| Product Name:               | Car Diagnostic Tool                                                                       |
| Model/Type reference:       | DS500 BT                                                                                  |
| Power supply:               | Powered by a 3.8V DC battery<br>Type-C Input: DC 5V/2.5A                                  |
| Test Voltage:               | Powered by a 3.8V DC battery<br>Type-C Input: DC 5V/2.5A                                  |
| Adapter information         | Model:FJ-SW1260502500UN<br>Input: 100-240V~ 50/60Hz 0.4A Max<br>Output:5.0V---2.5A, 12.5W |
| <b>Bluetooth Low Energy</b> |                                                                                           |
| Supported type:             | Bluetooth Low Energy                                                                      |
| Modulation:                 | GFSK                                                                                      |
| Operation frequency:        | 2402MHz to 2480MHz                                                                        |
| Channel number:             | 40                                                                                        |
| Channel separation:         | 2MHz                                                                                      |
| Antenna type:               | FPC Antenna                                                                               |
| Antenna gain:               | 1.29dBi                                                                                   |

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

## 2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

There are 40 channels provided to the EUT and Channel 00/19/39 were selected for Bluetooth Low Energy test.

### Operation Frequency List :

| Channel   | Frequency (MHz) |
|-----------|-----------------|
| <b>00</b> | <b>2402</b>     |
| 02        | 2404            |
| 03        | 2406            |
| ⋮         | ⋮               |
| <b>19</b> | <b>2440</b>     |
| ⋮         | ⋮               |
| 37        | 2476            |
| 38        | 2478            |
| <b>39</b> | <b>2480</b>     |

Note: The line display in grey were the channel selected for testing

| Software Version: adb.exe |             |
|---------------------------|-------------|
| Test Mode                 | Power level |
| BLE 1M                    | 0           |
| BLE 2M                    | 0           |

## 2.4. Equipments Used during the Test

| Conducted Emission |                 |           |              |                  |                 |
|--------------------|-----------------|-----------|--------------|------------------|-----------------|
| Test Equipment     | Manufacturer    | Model No. | Serial No.   | Last calibration | Calibration Due |
| EMI Test Receiver  | ROHDE & SCHWARZ | ESCI      | 1166.5950.03 | 2025/04/29       | 2026/04/28      |
| LISN               | ROHDE & SCHWARZ | ESH2-Z5   | 860014/010   | 2025/04/29       | 2026/04/28      |
| Limitator          | ROHDE & SCHWARZ | ESH3-Z2   | 100408       | 2025/04/29       | 2026/04/28      |
| Software:          |                 |           |              |                  |                 |
| Name of Software:  |                 |           | Version:     |                  |                 |
| ES-K1              |                 |           | V1.71        |                  |                 |

| Radiated Emission               |                      |           |              |            |            |
|---------------------------------|----------------------|-----------|--------------|------------|------------|
| Test Equipment                  | Manufacturer         | Model No. | Serial No.   | Last Cal.  | Cal.Due    |
| Active Loop Antenna             | Da Ze                | ZN30900A  | /            | 2024/04/30 | 2027/04/29 |
| Double cone logarithmic antenna | Schwarzbeck          | VULB 9168 | 824          | 2025/07/26 | 2026/07/25 |
| Horn Antenna                    | Sunol Sciences Corp. | DRH-118   | A062013      | 2024/11/25 | 2025/11/24 |
| Horn Antenna                    | Ocean Microwave      | OBH100400 | 26999002     | 2025/02/21 | 2028/02/20 |
| Amplifier                       | MRT-AP01M06          | MRT       | S-001        | 2025/04/29 | 2026/04/28 |
| Amplifier                       | Brief&Smart          | LNA-4018  | 2104197      | 2025/04/30 | 2026/04/29 |
| EMI Test Receiver               | ROHDE & SCHWARZ      | ESCI      | 1166.5950.03 | 2025/04/29 | 2026/04/28 |
| Spectrum Analyzer               | RS                   | FSP       | 1164.4391.38 | 2025/04/29 | 2026/04/28 |
| Software:                       |                      |           |              |            |            |
| Name of Software:               |                      |           | Version:     |            |            |
| EZ EMC(Below 1GHz)              |                      |           | V1.1.4.2     |            |            |
| EZ EMC(Above 1GHz)              |                      |           | V1.1.4.2     |            |            |

| RF Conducted               |              |           |            |            |            |
|----------------------------|--------------|-----------|------------|------------|------------|
| Test Equipment             | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal.Due    |
| Spectrum Analyzer          | Keysight     | N9020A    | MY53420874 | 2025/04/29 | 2026/04/28 |
| Temperature/Humidity Meter | Ji Yu        | MC501     | /          | 2025/05/06 | 2026/05/05 |
| Software:                  |              |           |            |            |            |
| Name of Software:          |              |           | Version:   |            |            |
| TST-PASS                   |              |           | V2.0.1     |            |            |

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emissions Test


##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION



##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2020.
2. Support equipment, if needed, was placed as per ANSI C63.10:2020.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2020.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

**TEST RESULTS**


Remark: Both BLE 1M and BLE2M have been tested, and only the low-channel data of the worst BLE 1M is reflected.

Line:

L

**SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL250915804\_fin"**

9/15/2025 8:31PM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.298500         | 26.20         | 9.9          | 60            | 34.1         | QP       | L1   | GND |
| 0.474000         | 17.70         | 9.9          | 56            | 38.7         | QP       | L1   | GND |
| 0.501000         | 19.20         | 10.0         | 56            | 36.8         | QP       | L1   | GND |
| 1.437000         | 14.20         | 10.1         | 56            | 41.8         | QP       | L1   | GND |
| 1.446000         | 12.50         | 10.1         | 56            | 43.5         | QP       | L1   | GND |
| 1.491000         | 15.50         | 10.1         | 56            | 40.5         | QP       | L1   | GND |

**MEASUREMENT RESULT: "CTL250915804\_fin2"**

9/15/2025 8:31PM


| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.298500         | 15.50         | 9.9          | 50            | 34.8         | AV       | L1   | GND |
| 0.447000         | 7.90          | 9.9          | 47            | 39.0         | AV       | L1   | GND |
| 1.441500         | 4.40          | 10.1         | 46            | 41.6         | AV       | L1   | GND |
| 1.477500         | 4.50          | 10.1         | 46            | 41.5         | AV       | L1   | GND |
| 1.500000         | 4.20          | 10.1         | 46            | 41.8         | AV       | L1   | GND |
| 1.707000         | 4.00          | 10.1         | 46            | 42.0         | AV       | L1   | GND |

Line:

N

**SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL250915801\_fin"**

9/15/2025 8:23PM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.298500         | 26.30         | 9.9          | 60            | 34.0         | QP       | N    | GND |
| 0.433500         | 18.80         | 9.9          | 57            | 38.4         | QP       | N    | GND |
| 0.447000         | 18.10         | 9.9          | 57            | 38.8         | QP       | N    | GND |
| 0.510000         | 16.80         | 10.0         | 56            | 39.2         | QP       | N    | GND |
| 0.523500         | 19.00         | 10.0         | 56            | 37.0         | QP       | N    | GND |
| 0.537000         | 17.10         | 10.0         | 56            | 38.9         | QP       | N    | GND |

**MEASUREMENT RESULT: "CTL250915801\_fin2"**

9/15/2025 8:23PM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.298500         | 15.50         | 9.9          | 50            | 34.8         | AV       | N    | GND |
| 0.433500         | 8.40          | 9.9          | 47            | 38.8         | AV       | N    | GND |
| 1.441500         | 2.90          | 10.1         | 46            | 43.1         | AV       | N    | GND |
| 1.482000         | 2.00          | 10.1         | 46            | 44.0         | AV       | N    | GND |
| 1.518000         | 2.70          | 10.1         | 46            | 43.3         | AV       | N    | GND |
| 1.815000         | 5.70          | 10.1         | 46            | 40.3         | AV       | N    | GND |

### 3.2. Radiated Emissions and Band Edge

#### Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


| Frequency (MHz) | Distance (Meters) | Radiated (dB $\mu$ V/m)                    | Radiated ( $\mu$ V/m) |
|-----------------|-------------------|--------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{kHz}))+40\log(300/3)$ | $2400/F(\text{kHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{kHz}))+40\log(30/3)$ | $24000/F(\text{kHz})$ |
| 1.705-30        | 3                 | $20\log(30)+40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                       | 100                   |
| 88-216          | 3                 | 43.5                                       | 150                   |
| 216-960         | 3                 | 46.0                                       | 200                   |
| Above 960       | 3                 | 54.0                                       | 500                   |

#### TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



## (C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**


1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.


**TEST RESULTS**

## Remark:


1. For below 1GHz testing recorded worst at Bluetooth Low Energy 1M low channel.
2. For above 1GHz testing recorded worst at Bluetooth Low Energy 1M low channel.
3. Radiated emission test from 9 kHz to 10th harmonic of fundamental was verified, Found the emission level are attenuated 20dB below the limits from 9 kHz to 30MHz, so it does not recorded in report.

For 30MHz-1GHz





For 1GHz to 25GHz



## Vertical



Shenzhen CTL Testing Technology Co., Ltd  
Tel: +86-755-89486194

## Radiated Emission Measurement


File :RF\_9

Data :#685

Date: 2025/09/16

Time: 10:26:04

80.0 dBuV/m



Site LAB Chamber 2

Polarization: **Vertical**

Temperature: 25(C)

Limit: FCC Part15 RE-Class C\_Above 1GHz\_PK

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N:

Mode: BLE1M 2402MHz


Note: CTL2507222072-WF


| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|--------|
| 1   | 4215.125        | 47.72          | -9.53         | 38.19          | 74.00          | 35.81       | peak     | 150         | 0              | P   |        |
| 2   | 8800.875        | 45.84          | -0.89         | 44.95          | 74.00          | 29.05       | peak     | 150         | 0              | P   |        |
| 3   | 10847.250       | 46.46          | 0.52          | 46.98          | 74.00          | 27.02       | peak     | 150         | 0              | P   |        |
| 4   | 13650.125       | 47.61          | 3.93          | 51.54          | 74.00          | 22.46       | peak     | 150         | 0              | P   |        |
| 5   | 15507.375       | 48.35          | 3.86          | 52.21          | 74.00          | 21.79       | peak     | 150         | 0              | P   |        |
| 6   | 16756.875       | 45.58          | 6.53          | 52.11          | 74.00          | 21.89       | peak     | 150         | 0              | P   |        |


## REMARKS:


- 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.
2. PK detector measurement value is lower than the average limit. Therefore, there is no need to test AV detector measurements.

Results of Band Edges Test (Radiated)









### 3.3. Maximum Conducted Output Power

#### Limit

The Maximum Peak Output Power Measurement is 30dBm.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.

- a) Set the  $RBW \geq DTS$  bandwidth.
- b) Set  $VBW \geq [3 \times RBW]$ .
- c) Set  $span \geq [3 \times RBW]$ .
- d) Sweep time = auto couple.
- e) Detector=peak.
- f) Trace mode=max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### Test Configuration



#### Test Results

Raw data reference to Section 3 of document No. CTL2507222072-WF02\_Bluetooth Low Energy\_Appendix.

### 3.4. Power Spectral Density

#### Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the  $100\text{kHz} \geq \text{RBW} \geq 3\text{ kHz}$ .
3. Set the  $\text{VBW} \geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

#### Test Configuration



#### Test Results

Raw data reference to Section 4 of document No. CTL2507222072-WF02\_Bluetooth Low Energy\_Appendix.

### 3.5. 6dB Bandwidth

#### Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

#### Test Procedure

The steps for the first option are as follows:

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down Amplitude” value, then it shall be as close as possible to this value.

#### Test Configuration



#### Test Results

Raw data reference to Section 2 of document No. CTL2507222072-WF02\_Bluetooth Low Energy\_Appendix.

### 3.6. Out-of-band Emissions

#### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

#### Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

#### Test Configuration



#### Test Results

Raw data reference to Section 5 of document No. CTL2507222072-WF02\_Bluetooth Low Energy\_Appendix.

### 3.7. Antenna Requirement

#### Standard Applicable

**For intentional device, according to FCC 47 CFR Section 15.203:**


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):**

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Result:

The maximum gain of antenna was 1.29dBi.



#### 4. Test Setup Photos of the EUT

Reference to the test report No.CTL2507222072-WF01.

#### 5. Photos of the EUT

Reference to the test report No.CTL2507222072-WF01.

\*\*\*\*\* End of Report \*\*\*\*\*