

TEST REPORT

Applicant : D2G Group LLC
Address : 81 Commerce Drive, Fall River, Massachusetts 02720, United States
Manufacturer : GUANGZHOU YOUGUANG OPTOELECTRONICS CO., LTD.
Address : No.75, Pacific Ind. Zone, Xingtang Town, Zengcheng, Guangzhou, 511340 China
Product Name : 43-inch Non-Touch Digital Signage Cash Wrap 14os
Model Number : DE043NLW14, DE043NLW
Trademark : N/A
FCC ID : 2ASCB-DE043NLW14
Test Date : Jul. 28, 2026
Date of Report : Jul. 28, 2026 to Sep. 03, 2026

Test Result : This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Prepared by(Test Engineer):
Gary Lu



Reviewer(Supervisor):
Cindy Qin



Approved(Manager):
Abel Yu



TABLE OF CONTENT

1. General Information	5
1.1. Description of Device (EUT)	5
1.2. Channel List	5
1.3. Test configuration	5
1.4. Summary of test result	6
1.5. Special Accessories and Auxiliary Equipment	6
1.6. Test mode	6
1.7. Block Diagram	7
1.8. Test Conditions	7
1.9. Measurement Uncertainty (95% confidence levels, k=2)	7
1.10. Test Facility	8
1.11. Test Equipment	8
2. Conducted emission at the mains terminals test	10
2.1. Limit	10
2.2. Test Setup	10
2.3. Test Procedure	10
2.4. Test Result	11
3. Radiated Spurious Emissions	13
3.1. Limit	13
3.2. Test Setup	14
3.3. Test Procedure	15
3.4. Test Result	16
4. Duty cycle	24
4.1. Limit	24
4.2. Test Setup	24
4.3. Test Procedure	24
4.4. Test Result	24
5. Conducted Spurious Emissions	25
5.1. Limit	25
5.2. Test Setup	25
5.3. Test Procedure	25
5.4. Test Result	26
6. Band Edge Measurement	32
6.1. Limit	32
6.2. Test setup	32
6.3. Test Procedure	32
6.4. Test Result	33
7. -6 dB Bandwidth and 99% Bandwidth Measurement	39
7.1. Limit	39
7.2. Test Setup	39
7.3. Test Procedure	39
7.4. Test Result	40
8. Maximum Output Power	53
8.1. Limit	53
8.2. Test Setup	53
8.3. Test Procedure	53
8.4. Test Result	54
9. Power Spectral density	55
9.1. Limit	55
9.2. Test Setup	55
9.3. Test Procedure	55

9.4. Test Result	56
10. Antenna Requirement.....	63
11. TEST SETUP & EUT PHOTOGRAPH	64

[illegible]

1. General Information

1.1. Description of Device (EUT)

EUT Name	:	43-inch Non-Touch Digital Signage Cash Wrap 14os
Model No.	:	DE043NLW14, DE043NLW
Model Difference	:	All the model are the same circuit and RF module, only the names and appearance colors are different. Test sample model: DE043NLW14
Power supply	:	AC 120V/60Hz
Operation frequency	:	2412-2462MHz for 802.11b/g/n20/ax20; 2422-2452MHz for 802.11n40/ax40
Modulation	:	802.11b:(DQPSK, DBPSK, CCK) DSSS 802.11g/n:(64-QAM, 16-QAM, QPSK, BPSK) OFDM 802.11ax:(1024-QAM, 256-QAM, 64-QAM, 16-QAM, QPSK, BPSK) OFDMA
Antenna Type	:	Rubber rod antenna, Maximum Gain is 2.43dBi
Intend use environment	:	Residential, commercial and light industrial environment

1.2. Channel List

Frequency and Channel list for 802.11 b/g/n(HT20/HT40)/ax (HE20/HE40):

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462		

Test Frequency and Channel for 802.11 b/g/n(HT20/HT40)/ax (HE20/HE40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	6	2437	11	2462
3	2422	6	2437	9	2452

1.3. Test configuration

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	set_txtone	Wifi_Test_Tor
Power level setup	Default	13 dBm

1.4.Summary of test result

RF PART		
Test Items	Test Requirement	Result
Antenna requirement	FCC part 15.203/15.247 (b)	PASS
Duty cycle		PASS
AC Power Line Conducted Emission	FCC part 15.207	PASS
Conducted Peak Output Power	FCC part 15.247 (b)(3)	PASS
Channel Bandwidth& 99% OCB	FCC part 15.247 (a)(2)	PASS
Power Spectral Density	FCC part 15.247 (e)	PASS
Band Edge	FCC part 15.247(d)	PASS
Spurious Emission	FCC part 15.205/15.209	PASS
Remark: N/A is an abbreviation for Not Applicable. Measurement Uncertainty is not taken into account for conformity statement		

1.5.Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Hardware Version	Software Version
Adapter	/	/	/	/
Laptop	DELL	Vostro 5490	/	/
cable	/	/	/	/

1.6.Test mode


The special RF test software was used to control EUT work in Continuous WIFI TX mode, and select test channel, wireless mode.

Test mode	Low channel	Middle channel	High channel
802.11b	2412MHz	2437MHz	2462MHz
802.11g	2412MHz	2437MHz	2462MHz
802.11n20	2412MHz	2437MHz	2462MHz
802.11n40	2422MHz	2437MHz	2452MHz
802.11ax20	2412MHz	2437MHz	2462MHz
802.11ax40	2422MHz	2437MHz	2452MHz


Note: All modes have been tested., Only the worst Data Record in the report

1.7.Block Diagram


Radiated Emission



Conducted Spurious



RF Conducted Test



1.8.Test Conditions

Category	Normal Conditions	Extreme Conditions
Temperature range	15-35℃	N/A
Humidity range	20-75%	N/A
Pressure range	86-106kPa	N/A
Power supply	AC 120V	N/A

Note: N/A is an abbreviation for Not Applicable.

1.9.Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for radio frequency	$\pm 7 \times 10^{-8}$	
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$	
Radiated Emission(9KHz~30MHz)	$\pm 4.51\text{dB}$	
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$	
Radiated Emission(1GHz~6GHz)	$\pm 3.92\text{dB}$	
Radiated Emission(6GHz~18GHz)	$\pm 4.33\text{dB}$	
Radiated Emission(18GHz~40GHz)	$\pm 3.38\text{dB}$	
Uncertainty for conducted RF Power	$\pm 0.20\text{dB}$	
Conducted spurious emissions	$\pm 0.24\text{dB}$	
Uncertainty for temperature	0.6℃	
Uncertainty for humidity	1%	
Bandwidth	$\pm 1.5 \times 10^{-6}$	
Time	$\pm 2\%$	
Duty Cycle	$\pm 2\%$	

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

1.10.Test Facility

Site Description		
Name of Firm	:	Shenzhen NTT Testing Technology Co.,Ltd.
Site Location	:	1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, China
FCC Designation Number	:	CN3446
FCC Test Firm Registration Number	:	129414

1.11.Test Equipment

Conducted Test Site

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	HSRCE944	/	HTEC	2025/4/30	2028/4/29
EMI Test Receiver	ESPI	/	RS	2025/9/8	2026/9/7
LISN	NNLK 8129	00603	Schwarzbeck	2025/9/8	2026/9/7
LISN	NNHV 8123-400	00694	Schwarzbeck	2025/9/8	2026/9/7
LISN	NNHV 8123-400	00680	Schwarzbeck	2025/9/8	2026/9/7
Cable	RG223-1500MM	NA	RG	2025/9/8	2026/9/7

Radiated Test Site(Below 1G and Above 1G)&RF Test Site

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2025/7/24	2028/7/23
EMI Test Receiver	ESCI	101018	RS	2025/9/8	2026/9/7
Amplifi (30MHz-1GHz)	BBV 9718D	00042	SCHWARZBECK	2025/9/8	2026/9/7
Bilog Antenna (30MHz-1GHz)	VULB9168	1858	SCHWARZBECK	2025/9/9	2026/9/8
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHWARZBECK	2025/9/9	2026/9/8
Pream plifier (1GHz-18GHz)	BBV 9718D	0024	SCHWARZBECK	2025/9/8	2026/9/7
Spectrum Analyze (10Hz-40GHz)	FSV 40	100952	Rohde & Schwarz	2025/9/8	2026/9/7

Pream plifier (18GHz-40GHz)	BBV 9721	0056	SCHWARZBECK	2025/9/8	2026/9/7
Double Ridge Guide Horn Antenna (18GHz-40GHz)	SAS-574	588	A.H.System	2025/9/8	2026/9/7
Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHWARZBECK	2025/9/8	2026/9/7
Amplifier (9KHz-30MHz)	CVP 9222 C	00109	SCHWARZBECK	2025/9/8	2026/9/7
MXG Signal Analyzer	N9020A	MY50510202	Agilent	2025/9/8	2026/9/7
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2025/9/8	2026/9/7
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2025/9/8	2026/9/7
Power Sensor	TR1029-2	512364	Techoy	2025/9/8	2026/9/7
RF Swith	TR1029-1	512364	Techoy	2025/9/8	2026/9/7
Cable	DA800- 4000MM	NA	DA	2025/9/8	2026/9/7
Cable	DA800- 11000MM	NA	DA	2025/9/8	2026/9/7

Test software

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ-EMC	Ver.EMC-CON 3A1.1+
2	EMC radiation test system	FALA	EZ-EMC	Ver.FA-03A2 RE+
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

2. Conducted emission at the mains terminals test


2.1.Limit

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.2.Test Setup




Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 10 cm from EUT and at least 10 from other units and other metal planes

2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.

2.4.Test Result

Conducted Emission At The Mains Terminals Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Line
Test Voltage :	DC 5V from Adapter Input AC 120V/60Hz	Test Mode:	802.11b(CH00)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1860	41.36	10.79	52.15	64.21	-12.06	QP
2		0.1860	26.74	10.79	37.53	54.21	-16.68	AVG
3		0.4540	34.62	10.51	45.13	56.80	-11.67	QP
4		0.4540	22.44	10.51	32.95	46.80	-13.85	AVG
5		2.4100	24.44	10.48	34.92	56.00	-21.08	QP
6		2.4100	12.35	10.48	22.83	46.00	-23.17	AVG
7 *		5.8659	41.52	10.53	52.05	60.00	-7.95	QP
8		5.8659	30.50	10.53	41.03	50.00	-8.97	AVG
9		7.2900	40.53	10.55	51.08	60.00	-8.92	QP
10		7.2900	31.18	10.55	41.73	50.00	-8.27	AVG
11		26.9700	30.91	11.37	42.28	60.00	-17.72	QP
12		26.9700	24.92	11.37	36.29	50.00	-13.71	AVG

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(802.11b-CH00) in the report

Conducted Emission At The Mains Terminals Test Data			
Temperature:	25.1°C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Neutral
Test Voltage :	DC 5V from Adapter Input AC 120V/60Hz	Test Mode:	802.11b(CH00)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2420	40.77	10.72	51.49	62.03	-10.54	QP
2		0.2420	27.83	10.72	38.55	52.03	-13.48	AVG
3		0.4900	33.84	10.48	44.32	56.17	-11.85	QP
4		0.4900	25.71	10.48	36.19	46.17	-9.98	AVG
5		1.1780	25.91	10.46	36.37	56.00	-19.63	QP
6		1.1780	14.17	10.46	24.63	46.00	-21.37	AVG
7		5.6819	40.92	10.52	51.44	60.00	-8.56	QP
8		5.6819	31.54	10.52	42.06	50.00	-7.94	AVG
9		7.2900	40.57	10.55	51.12	60.00	-8.88	QP
10	*	7.2900	31.91	10.55	42.46	50.00	-7.54	AVG
11		26.9700	30.51	11.37	41.88	60.00	-18.12	QP
12		26.9700	24.48	11.37	35.85	50.00	-14.15	AVG

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(802.11b-CH00) in the report

3. Radiated Spurious Emissions

3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
 Test Result: PASS
 Measurement Distance: 3m

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	360KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average


Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log(30) + 40$
30 ~ 88	100	3	100	$20\log(100)$
88 ~ 216	150	3	150	$20\log(150)$
216 ~ 960	200	3	200	$20\log(200)$
Above 960	500	3	500	$20\log(500)$


3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



3.3.Test Procedure

1. The EUT is placed on a turntable, which is 0.1m above ground plane for below 1GHz and 0.1m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.


3.4.Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 1GHz

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Horizontal
Test Voltage :	DC 5V from Adapter Input AC 120V/60Hz	Test Mode :	802.11b(2462.00MHz)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	!	150.5377	43.82	-4.35	39.47	43.50	-4.03	QP
2	!	298.2681	44.60	-2.60	42.00	46.00	-4.00	QP
3		381.2485	38.15	-1.20	36.95	46.00	-9.05	QP
4		483.0615	34.91	0.63	35.54	46.00	-10.46	QP
5		762.0384	31.70	7.73	39.43	46.00	-6.57	QP
6	*	892.2907	33.30	9.44	42.74	46.00	-3.26	QP

Note:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(802.11b-2462MHz) in the report

Radiation Emission Test Data			
Temperature:	25.1°C	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Vertical
Test Voltage :	DC 5V from Adapter Input AC 120V/60Hz	Test Mode :	802.11b(2462.00MHz)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	44.5086	42.38	-6.13	36.25	40.00	-3.75	QP
2		147.9214	41.78	-4.60	37.18	43.50	-6.32	QP
3		184.1665	39.95	-4.68	35.27	43.50	-8.23	QP
4	!	298.2681	43.26	-2.60	40.66	46.00	-5.34	QP
5		596.1770	34.86	3.87	38.73	46.00	-7.27	QP
6	!	916.0683	32.40	9.44	41.84	46.00	-4.16	QP

Note:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(802.11b-2462MHz) in the report

Test Frequency 1GHz-25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	52.09	34.12	5.03	32.39	55.39	74	-18.61	Pk
V	4824.00	39.43	34.12	5.03	32.39	42.73	54	-11.27	AV
V	7236.00	50.08	32.54	6.29	35.86	59.69	74	-14.31	Pk
V	7236.00	34.66	32.54	6.29	35.86	44.27	54	-9.73	AV
V	9648.00	48.47	32.98	7.55	38.4	61.44	74	-12.56	Pk
V	9648.00	34.04	32.98	7.55	38.4	47.01	54	-6.99	AV
V	12060.00	45.03	32.09	8.93	39	60.87	74	-13.13	Pk
V	12060.00	27.70	32.09	8.93	39	43.54	54	-10.46	AV
H	4824.00	49.22	34.12	5.03	32.39	52.52	74	-21.48	Pk
H	4824.00	40.94	34.12	5.03	32.39	44.24	54	-9.76	AV
H	7236.00	47.22	32.54	6.29	35.86	56.83	74	-17.17	Pk
H	7236.00	32.69	32.54	6.29	35.86	42.30	54	-11.70	AV
H	9648.00	48.12	32.98	7.55	38.4	61.09	74	-12.91	Pk
H	9648.00	30.83	32.98	7.55	38.4	43.80	54	-10.20	AV
H	12060.00	39.34	32.09	8.93	39	55.18	74	-18.82	Pk
H	12060.00	25.51	32.09	8.93	39	41.35	54	-12.65	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2437MHz									
V	4874.00	49.52	34.07	5.09	32.59	53.13	74	-20.87	Pk
V	4874.00	38.63	34.07	5.09	32.59	42.24	54	-11.76	AV
V	7311.00	44.75	32.63	6.34	35.96	54.42	74	-19.58	Pk
V	7311.00	36.62	32.63	6.34	35.96	46.29	54	-7.71	AV
V	9748.00	43.15	32.92	7.59	38.4	56.22	74	-17.78	Pk
V	9748.00	32.01	32.92	7.59	38.4	45.08	54	-8.92	AV
V	12815.00	41.00	31.96	8.88	39.04	56.96	74	-17.04	Pk
V	12815.00	30.35	31.96	8.88	39.04	46.31	54	-7.69	AV
H	4874.00	49.01	34.07	5.09	32.59	52.62	74	-21.38	Pk
H	4874.00	38.57	34.07	5.09	32.59	42.18	54	-11.82	AV
H	7311.00	46.36	32.63	6.34	35.96	56.03	74	-17.97	Pk
H	7311.00	35.30	32.63	6.34	35.96	44.97	54	-9.03	AV
H	9748.00	42.19	32.92	7.59	38.4	55.26	74	-18.74	Pk
H	9748.00	30.73	32.92	7.59	38.4	43.80	54	-10.20	AV
H	12815.00	39.54	31.96	8.88	39.04	55.50	74	-18.50	Pk
H	12815.00	29.04	31.96	8.88	39.04	45.00	54	-9.00	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2462MHz									
V	4924.00	49.00	34.02	5.15	32.8	52.93	74	-21.07	Pk
V	4924.00	35.06	34.02	5.15	32.8	38.99	54	-15.01	AV
V	7386.00	45.09	32.71	6.4	36.05	54.83	74	-19.17	Pk
V	7386.00	36.38	32.71	6.4	36.05	46.12	54	-7.88	AV
V	9848.00	41.55	32.86	7.62	38.4	54.71	74	-19.29	Pk
V	9848.00	30.13	32.86	7.62	38.4	43.29	54	-10.71	AV
V	12310.00	39.15	31.82	8.84	39.08	55.25	74	-18.75	Pk
V	12310.00	26.97	31.82	8.84	39.08	43.07	54	-10.93	AV
H	4924.00	47.69	34.02	5.15	32.8	51.62	74	-22.38	Pk
H	4924.00	38.64	34.02	5.15	32.8	42.57	54	-11.43	AV
H	7386.00	44.67	32.71	6.4	36.05	54.41	74	-19.59	Pk
H	7386.00	31.64	32.71	6.4	36.05	41.38	54	-12.62	AV
H	9848.00	41.17	32.86	7.62	38.4	54.33	74	-19.67	Pk
H	9848.00	28.06	32.86	7.62	38.4	41.22	54	-12.78	AV
H	12310.00	40.77	31.82	8.84	39.08	56.87	74	-17.13	Pk
H	12310.00	29.56	31.82	8.84	39.08	45.66	54	-8.34	AV

Note: 1. The testing has been conformed to 10*2480MHz=24800MHz.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

All the modes have tested and recorded the worst mode(802.11b) in the report.

The 1-25GHz range has been tested, and the report only records the worst performance of the 1-18G range.

Radiated Band Emission Measurement:

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
802.11b	Low Channel: 2412MHz									
	H	2390	57.48	35.17	3.48	27.49	53.28	74	-20.72	PK
	H	2390	51.11	35.17	3.48	27.49	46.91	54	-7.09	AV
	H	2400	61.33	35.16	3.49	27.52	57.18	74	-16.82	PK
	H	2400	49.62	35.16	3.49	27.52	45.47	54	-8.53	AV
	V	2390	60.14	35.17	3.48	27.49	55.94	74	-18.06	PK
	V	2390	51.89	35.17	3.48	27.49	47.69	54	-6.31	AV
	V	2400	60.82	35.16	3.49	27.52	56.67	74	-17.33	PK
	V	2400	51.48	35.16	3.49	27.52	47.33	54	-6.67	AV
	High Channel: 2462MHz									
	H	2483.5	57.90	35.11	3.56	27.75	54.10	74	-19.90	PK
	H	2483.5	50.60	35.11	3.56	27.75	46.80	54	-7.20	AV
	H	2500	60.79	35.1	3.57	27.8	57.06	74	-16.94	PK
	H	2500	51.58	35.1	3.57	27.8	47.85	54	-6.15	AV
	V	2483.5	59.25	35.11	3.56	27.75	55.45	74	-18.55	PK
	V	2483.5	50.72	35.11	3.56	27.75	46.92	54	-7.08	AV
	V	2500	60.45	35.1	3.57	27.8	56.72	74	-17.28	PK
	V	2500	51.94	35.1	3.57	27.8	48.21	54	-5.79	AV
802.11g	Low Channel: 2412MHz									
	H	2390	57.64	35.17	3.48	27.49	53.44	74	-20.56	PK
	H	2390	50.55	35.17	3.48	27.49	46.35	54	-7.65	AV
	H	2400	60.33	35.16	3.49	27.52	56.18	74	-17.82	PK
	H	2400	51.18	35.16	3.49	27.52	47.03	54	-6.97	AV
	V	2390	58.39	35.17	3.48	27.49	54.19	74	-19.81	PK
	V	2390	51.58	35.17	3.48	27.49	47.38	54	-6.62	AV
	V	2400	59.90	35.16	3.49	27.52	55.75	74	-18.25	PK
	V	2400	49.92	35.16	3.49	27.52	45.77	54	-8.23	AV
	High Channel: 2462MHz									
	H	2483.5	59.45	35.11	3.56	27.75	55.65	74	-18.35	PK
	H	2483.5	51.08	35.11	3.56	27.75	47.28	54	-6.72	AV
	H	2500	60.34	35.1	3.57	27.8	56.61	74	-17.39	PK
	H	2500	49.76	35.1	3.57	27.8	46.03	54	-7.97	AV
	V	2483.5	59.67	35.11	3.56	27.75	55.87	74	-18.13	PK
	V	2483.5	52.06	35.11	3.56	27.75	48.26	54	-5.74	AV
	V	2500	57.72	35.1	3.57	27.8	53.99	74	-20.01	PK
	V	2500	51.32	35.1	3.57	27.8	47.59	54	-6.41	AV
802.11 n20	Low Channel: 2412MHz									
	H	2390	59.17	35.17	3.48	27.49	54.97	74	-19.03	PK
	H	2390	49.37	35.17	3.48	27.49	45.17	54	-8.83	AV
	H	2400	61.30	35.16	3.49	27.52	57.15	74	-16.85	PK
	H	2400	49.00	35.16	3.49	27.52	44.85	54	-9.15	AV
	V	2390	58.91	35.17	3.48	27.49	54.71	74	-19.29	PK
	V	2390	51.49	35.17	3.48	27.49	47.29	54	-6.71	AV
	V	2400	60.03	35.16	3.49	27.52	55.88	74	-18.12	PK
	V	2400	49.46	35.16	3.49	27.52	45.31	54	-8.69	AV
	High Channel: 2462MHz									
	H	2483.5	58.92	35.11	3.56	27.75	55.12	74	-18.88	PK
	H	2483.5	50.76	35.11	3.56	27.75	46.96	54	-7.04	AV
	H	2500	60.91	35.1	3.57	27.8	57.18	74	-16.82	PK

	H	2500	51.80	35.1	3.57	27.8	48.07	54	-5.93	AV
	V	2483.5	60.19	35.11	3.56	27.75	56.39	74	-17.61	PK
	V	2483.5	51.81	35.11	3.56	27.75	48.01	54	-5.99	AV
	V	2500	59.60	35.1	3.57	27.8	55.87	74	-18.13	PK
	V	2500	50.83	35.1	3.57	27.8	47.10	54	-6.90	AV
802.11 n40	Low Channel 2422MHz									
	H	2390.00	58.71	35.17	3.48	27.49	54.51	74	-19.49	PK
	H	2390.00	50.20	35.17	3.48	27.49	46.00	54	-8.00	AV
	H	2400.00	61.70	35.16	3.49	27.52	57.55	74	-16.45	PK
	H	2400.00	50.56	35.16	3.49	27.52	46.41	54	-7.59	AV
	V	2390.00	58.14	35.17	3.48	27.49	53.94	74	-20.06	PK
	V	2390.00	50.08	35.17	3.48	27.49	45.88	54	-8.12	AV
	V	2400.00	59.51	35.16	3.49	27.52	55.36	74	-18.64	PK
	V	2400.00	51.42	35.16	3.49	27.52	47.27	54	-6.73	AV
	High Channel 2452MHz									
	H	2483.50	58.31	35.11	3.56	27.75	54.51	74	-19.49	PK
	H	2483.50	50.66	35.11	3.56	27.75	46.86	54	-7.14	AV
	H	2500.00	60.93	35.1	3.57	27.8	57.20	74	-16.80	PK
	H	2500.00	51.64	35.1	3.57	27.8	47.91	54	-6.09	AV
	V	2483.50	58.04	35.11	3.56	27.75	54.24	74	-19.76	PK
	V	2483.50	51.07	35.11	3.56	27.75	47.27	54	-6.73	AV
	V	2500.00	60.33	35.1	3.57	27.8	56.60	74	-17.40	PK
	V	2500.00	51.73	35.1	3.57	27.8	48.00	54	-6.00	AV
802.11 ax20	Low Channel 2412MHz									
	H	2390.00	57.09	35.17	3.48	27.49	52.89	74	-21.11	PK
	H	2390.00	49.86	35.17	3.48	27.49	45.66	54	-8.34	AV
	H	2400.00	61.46	35.16	3.49	27.52	57.31	74	-16.69	PK
	H	2400.00	48.99	35.16	3.49	27.52	44.84	54	-9.16	AV
	V	2390.00	59.70	35.17	3.48	27.49	55.50	74	-18.50	PK
	V	2390.00	52.31	35.17	3.48	27.49	48.11	54	-5.89	AV
	V	2400.00	59.42	35.16	3.49	27.52	55.27	74	-18.73	PK
	V	2400.00	48.76	35.16	3.49	27.52	44.61	54	-9.39	AV
	High Channel 2462MHz									
	H	2483.50	59.03	35.11	3.56	27.75	55.23	74	-18.77	PK
	H	2483.50	49.51	35.11	3.56	27.75	45.71	54	-8.29	AV
	H	2500.00	59.57	35.1	3.57	27.8	55.84	74	-18.16	PK
	H	2500.00	50.75	35.1	3.57	27.8	47.02	54	-6.98	AV
	V	2483.50	60.26	35.11	3.56	27.75	56.46	74	-17.54	PK
	V	2483.50	50.37	35.11	3.56	27.75	46.57	54	-7.43	AV
	V	2500.00	59.32	35.1	3.57	27.8	55.59	74	-18.41	PK
	V	2500.00	51.48	35.1	3.57	27.8	47.75	54	-6.25	AV
802.11 ax40	Low Channel 2422MHz									
	H	2390.00	57.52	35.17	3.48	27.49	53.32	74	-20.68	PK
	H	2390.00	49.02	35.17	3.48	27.49	44.82	54	-9.18	AV
	H	2400.00	61.23	35.16	3.49	27.52	57.08	74	-16.92	PK
	H	2400.00	51.42	35.16	3.49	27.52	47.27	54	-6.73	AV
	V	2390.00	58.59	35.17	3.48	27.49	54.39	74	-19.61	PK
	V	2390.00	50.43	35.17	3.48	27.49	46.23	54	-7.77	AV
	V	2400.00	59.24	35.16	3.49	27.52	55.09	74	-18.91	PK
	V	2400.00	50.80	35.16	3.49	27.52	46.65	54	-7.35	AV
	High Channel 2452MHz									
	H	2483.50	58.24	35.11	3.56	27.75	54.44	74	-19.56	PK
	H	2483.50	49.45	35.11	3.56	27.75	45.65	54	-8.35	AV

	H	2500.00	59.62	35.1	3.57	27.8	55.89	74	-18.11	PK
	H	2500.00	49.07	35.1	3.57	27.8	45.34	54	-8.66	AV
	V	2483.50	58.51	35.11	3.56	27.75	54.71	74	-19.29	PK
	V	2483.50	51.53	35.11	3.56	27.75	47.73	54	-6.27	AV
	V	2500.00	59.73	35.1	3.57	27.8	56.00	74	-18.00	PK
	V	2500.00	51.40	35.1	3.57	27.8	47.67	54	-6.33	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss - Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.


3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. Duty cycle

4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
 Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
 Test Result: PASS

4.2.Test Setup



4.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set the center frequency of the instrument to the center frequency of the transmission.
 - b) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - c) Set $VBW \geq RBW$. Detector = peak or average.
 - d) Sweep time = auto couple.
 - e) Trace mode = max hold.
 - f) Allow trace to fully stabilize.

4.4.Test Result

Duty Cycle

Mode	Channel.	Duty Cycle (%)	Correction Factor (dB)
802.11b	LCH	100	0
	MCH	100	0
	HCH	100	0
802.11g	LCH	100	0
	MCH	100	0
	HCH	100	0
802.11n(HT20)	LCH	100	0
	MCH	100	0
	HCH	100	0
802.11n(HT40)	LCH	100	0
	MCH	100	0
	HCH	100	0
802.11ax(HE20)	LCH	100	0
	MCH	100	0
	HCH	100	0
802.11ax(HE40)	LCH	100	0
	MCH	100	0
	HCH	100	0

5. Conducted Spurious Emissions

5.1.Limit

Test: FCC CFR47 Part 15 Section 15.247
Requirement:
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.2.Test Setup




5.3.Test Procedure

- Set instrument center frequency to DTS channel center frequency.
 - Set the span to ≥ 1.5 times the DTS bandwidth.
 - Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = No faster than coupled (auto) time.
 - Trace mode = max-hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum PSD level.
- Note that the channel found to contain the maximum PSD level can be used to establish the reference level. Establish an emission level by using the following procedure:
- Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.
- NOTE—the number of points can also be increased for large spans to retain frequency resolution
- Set the RBW = 100 kHz.
 - Set the VBW $\geq [3 \times \text{RBW}]$.
 - Detector = peak.
 - Sweep time = No faster than coupled (auto) time.
 - Trace mode = max-hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level.


5.4.Test Result

RF Conducted Spurious Emissions Graphs


802.11b/LCH



802.11b/MCH




802.11b/HCH




RF Conducted Spurious Emissions Graphs


802.11g/LCH



802.11g/MCH




802.11g/HCH




RF Conducted Spurious Emissions Graphs


802.11n(HT20)/LCH



802.11n(HT20)/MCH




802.11n(HT20)/HCH




RF Conducted Spurious Emissions Graphs


802.11n(HT40)/LCH



802.11n(HT40)/MCH




802.11n(HT40)/HCH




RF Conducted Spurious Emissions Graphs


802.11ax(HE20)/LCH



802.11ax(HE20)/MCH




802.11ax(HE20)/HCH




RF Conducted Spurious Emissions Graphs


802.11ax(HE40)/LCH



802.11ax(HE40)/MCH



802.11ax(HE40)/HCH



6. Band Edge Measurement

6.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting

6.2.Test setup



6.3.Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
3. Establish a reference level by using the following procedure
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to ≈ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW $\approx [3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = No faster than coupled (auto) time.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
4. Establish an emission level by using the following procedure:

a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution


- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

6.4.Test Result




BAND EDGE Graphs

802.11g/LCH




802.11g/HCH




BAND EDGE Graphs

802.11n(HT20)/LCH




802.11n(HT20)/HCH




BAND EDGE Graphs

802.11n(HT40)/LCH




802.11n(HT40)/HCH




BAND EDGE Graphs

802.11ax(HE20)/LCH




802.11ax(HE20)/HCH




BAND EDGE Graphs

802.11ax(HE40)/LCH



802.11ax(HE40)/HCH



7. -6 dB Bandwidth and 99% Bandwidth Measurement


7.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.2.Test Setup



7.3.Test Procedure

DTS Bandwidth

- a) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- b) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Trace mode = max-hold.
- f) Sweep = No faster than coupled (auto) time.
- g) Allow the trace to stabilize.

99% Bandwidth

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.

7.4.Test Result


Test Mode	Frequency	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
802.11b	LCH	10.174	14.9635	PASS
	MCH	10.182	14.9775	PASS
	HCH	10.187	14.9735	PASS
802.11g	LCH	16.556	16.5209	PASS
	MCH	16.501	16.5168	PASS
	HCH	16.472	16.5108	PASS
802.11n(HT20)	LCH	17.709	17.6160	PASS
	MCH	17.751	17.6006	PASS
	HCH	17.684	17.6504	PASS
802.11n(HT40)	LCH	36.408	36.1931	PASS
	MCH	36.251	36.1426	PASS
	HCH	36.277	36.2124	PASS
802.11ax(HE20)	LCH	17.689	17.6783	PASS
	MCH	17.764	17.6837	PASS
	HCH	17.61	17.6824	PASS
802.11ax(HE40)	LCH	36.416	36.2126	PASS
	MCH	36.243	36.1812	PASS
	HCH	36.305	36.1361	PASS

-6dB


Test Graph:




802.11g/LCH




802.11g/MCH




802.11g/HCH




802.11n(HT20)/LCH






802.11n(HT20)/MCH




802.11n(HT20)/HCH




802.11n(HT40)/LCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.422000000 GHz Ref Offset 7 dB Ref 27.00 dBm Mkr3 2.440216 GHz -7.6600 dBm Center 2.422 GHz #Res BW 430 kHz #VBW 1.5 MHz Span 60 MHz Sweep 1 ms Occupied Bandwidth 36.197 MHz Total Power 15.4 dBm Transmit Freq Error 12.101 kHz OBW Power 99.00 % x dB Bandwidth 36.41 MHz x dB -6.00 dB
802.11n(HT40)/MCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 7.01 dB Ref 27.01 dBm Mkr3 2.455132 GHz -6.8453 dBm Center 2.437 GHz #Res BW 430 kHz #VBW 1.5 MHz Span 60 MHz Sweep 1 ms Occupied Bandwidth 36.134 MHz Total Power 15.1 dBm Transmit Freq Error 6.226 kHz OBW Power 99.00 % x dB Bandwidth 36.25 MHz x dB -6.00 dB
802.11n(HT40)/HCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.452000000 GHz Ref Offset 7.03 dB Ref 27.03 dBm Mkr3 2.470128 GHz -7.2681 dBm Center 2.452 GHz #Res BW 430 kHz #VBW 1.5 MHz Span 60 MHz Sweep 1 ms Occupied Bandwidth 36.200 MHz Total Power 14.7 dBm Transmit Freq Error -10.217 kHz OBW Power 99.00 % x dB Bandwidth 36.28 MHz x dB -6.00 dB


802.11ax(HE20)/LCH




802.11ax(HE20)/MCH




802.11ax(HE20)/HCH




802.11ax(HE40)/LCH



802.11ax(HE40)/MCH



802.11ax(HE40)/HCH




99%


Test Graph:




802.11g/LCH




802.11g/MCH




802.11g/HCH




802.11n(HT20)/LCH









802.11n(HT20)/MCH




802.11n(HT20)/HCH




802.11n(HT40)/LCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.422000000 GHz Ref Offset 7 dB Ref 27.00 dBm Center 2.422 GHz #Res BW 430 kHz Occupied Bandwidth 36.193 MHz Total Power 15.3 dBm Transmit Freq Error 14.729 kHz OBW Power 99.00 % x dB Bandwidth 38.74 MHz x dB -20.00 dB
802.11n(HT40)/MCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 7.01 dB Ref 27.01 dBm Center 2.437 GHz #Res BW 430 kHz Occupied Bandwidth 36.143 MHz Total Power 15.1 dBm Transmit Freq Error 16.872 kHz OBW Power 99.00 % x dB Bandwidth 38.59 MHz x dB -20.00 dB
802.11n(HT40)/HCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.452000000 GHz Ref Offset 7.03 dB Ref 27.03 dBm Center 2.452 GHz #Res BW 430 kHz Occupied Bandwidth 36.212 MHz Total Power 14.6 dBm Transmit Freq Error -235 Hz OBW Power 99.00 % x dB Bandwidth 38.82 MHz x dB -20.00 dB

802.11ax(HE20)/LCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Ref Offset 6.99 dB Ref 26.99 dBm Center 2.412 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz Sweep 1 ms Occupied Bandwidth 17.678 MHz Total Power 14.7 dBm Transmit Freq Error 29.766 kHz OBW Power 99.00 % x dB Bandwidth 18.93 MHz x dB -20.00 dB
802.11ax(HE20)/MCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Ref Offset 7.01 dB Ref 27.01 dBm Center 2.437 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz Sweep 1 ms Occupied Bandwidth 17.684 MHz Total Power 14.7 dBm Transmit Freq Error 14.117 kHz OBW Power 99.00 % x dB Bandwidth 18.99 MHz x dB -20.00 dB
802.11ax(HE20)/HCH	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Ref Offset 7.04 dB Ref 27.04 dBm Center 2.462 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz Sweep 1 ms Occupied Bandwidth 17.682 MHz Total Power 14.2 dBm Transmit Freq Error 8.806 kHz OBW Power 99.00 % x dB Bandwidth 19.10 MHz x dB -20.00 dB


802.11ax(HE40)/LCH



802.11ax(HE40)/MCH



802.11ax(HE40)/HCH



8. Maximum Output Power


8.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;ANSI C63.10-2020+Cor.1-2023

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2.Test Setup



8.3.Test Procedure

ANSI C63.10-2020 section 11.9.2.2.5

Method AVGSA-2A uses rms detection with slow sweep with spectrum bin averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction. The procedure for this method is as follows:

- Measure the duty cycle D of the transmitter output signal as described in 11.6.
- Set span to >1.5 times the OBW.
- Set RBW = 1% to 5% of the OBW, but do not exceed 1 MHz.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Manually set sweep time $\geq [10 \times (\text{number of points in sweep}) \times (\text{total ON/OFF period of the transmitted signal})]$.
- Set detector = Power averaging (rms).
- Perform a single sweep.
- Compute power by integrating the spectrum across the OBW of the signal using the instrument's band-power measurement function with band limits set equal to the OBW band-edges. If the instrument does not have a band-power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW.
- Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

8.4.Test Result

Mode	Channel.	Maximum Peak Output Power [dBm]	Limit [dBm]	Verdict
802.11b	LCH	14.956	30	PASS
	MCH	15.288	30	PASS
	HCH	14.183	30	PASS
802.11g	LCH	16.56	30	PASS
	MCH	15.697	30	PASS
	HCH	14.983	30	PASS
802.11n(HT20)	LCH	16.114	30	PASS
	MCH	15.695	30	PASS
	HCH	15.06	30	PASS
802.11n(HT40)	LCH	16.32	30	PASS
	MCH	15.974	30	PASS
	HCH	15.579	30	PASS
802.11ax(HE20)	LCH	15.96	30	PASS
	MCH	15.895	30	PASS
	HCH	15.439	30	PASS
802.11ax(HE40)	LCH	16.214	30	PASS
	MCH	14.943	30	PASS
	HCH	14.998	30	PASS

9. Power Spectral density


9.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019; ANSI C63.10-2020+Cor.1-2023

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

9.2.Test Setup



9.3.Test Procedure


KDB 558074 D01 15.247 Meas Guidance v05r02;

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set instrument center frequency to DTS channel center frequency
3. Set span to > 1.5 times the OBW.
4. Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
5. Set VBW $\geq [3 \times \text{RBW}]$
6. Detector = power averaging (rms) or sample detector (when rms not available).
7. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
8. Sweep time = auto couple.
9. Employ trace averaging (rms) mode over a minimum of 100 traces.
10. Use the peak marker function to determine the maximum amplitude level.
11. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat(note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).
12. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


9.4.Test Result

Mode	Channel.	Power Spectral Density [dBm /3kHz]	Limit(8 dBm (in any 3kHz))	Verdict
802.11b	LCH	-4.314	8	PASS
	MCH	-4.805	8	PASS
	HCH	-5.487	8	PASS
802.11g	LCH	-4.18	8	PASS
	MCH	-4.61	8	PASS
	HCH	-5.298	8	PASS
802.11n(HT20)	LCH	-4.203	8	PASS
	MCH	-4.635	8	PASS
	HCH	-5.305	8	PASS
802.11n(HT40)	LCH	-4.317	8	PASS
	MCH	-4.647	8	PASS
	HCH	-5.035	8	PASS
802.11ax(HE20)	LCH	-4.136	8	PASS
	MCH	-4.599	8	PASS
	HCH	-5.315	8	PASS
802.11ax(HE40)	LCH	-4.349	8	PASS
	MCH	-4.584	8	PASS
	HCH	-5.02	8	PASS


Test Graph




802.11g/LCH









802.11g/MCH









802.11g/HCH



802.11n(HT20)/LCH	
802.11n(HT20)/MCH	
802.11n(HT20)/HCH	

802.11n(HT40)/LCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.42200000 GHz Ref Offset 7 dB Ref 20.00 dBm Mkr1 2.422 00 GHz -4.317 dBm Center 2.42200 GHz #Res BW 3.0 kHz #VBW 10 kHz Span 60.00 MHz Sweep 6.326 s (1001 pts)
802.11n(HT40)/MCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz Ref Offset 7.01 dB Ref 20.00 dBm Mkr1 2.437 00 GHz -4.647 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 10 kHz Span 60.00 MHz Sweep 6.326 s (1001 pts)
802.11n(HT40)/HCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.45200000 GHz Ref Offset 7.03 dB Ref 20.00 dBm Mkr1 2.452 00 GHz -5.035 dBm Center 2.45200 GHz #Res BW 3.0 kHz #VBW 10 kHz Span 60.00 MHz Sweep 6.326 s (1001 pts)

802.11ax(HE20)/LCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz Ref Offset 6.99 dB Ref 20.00 dBm Mkr1 2.412 00 GHz -4.136 dBm Center 2.41200 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 3.163 s (1001 pts)
802.11ax(HE20)/MCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz Ref Offset 7.01 dB Ref 20.00 dBm Mkr1 2.437 00 GHz -4.599 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 3.163 s (1001 pts)
802.11ax(HE20)/HCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.46200000 GHz Ref Offset 7.04 dB Ref 20.00 dBm Mkr1 2.462 00 GHz -5.315 dBm Center 2.46200 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 3.163 s (1001 pts)

802.11ax(HE40)/LCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.422000000 GHz Ref Offset 7 dB Ref 20.00 dBm Mkr1 2.422 00 GHz -4.349 dBm Span 60.00 MHz Sweep 6.326 s (1001 pts)
802.11ax(HE40)/MCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.437000000 GHz Ref Offset 7.01 dB Ref 20.00 dBm Mkr1 2.437 00 GHz -4.584 dBm Span 60.00 MHz Sweep 6.326 s (1001 pts)
802.11ax(HE40)/HCH	 Agilent Spectrum Analyzer - Swept SA Center Freq 2.452000000 GHz Ref Offset 7.03 dB Ref 20.00 dBm Mkr1 2.452 00 GHz -5.020 dBm Span 60.00 MHz Sweep 6.326 s (1001 pts)

10. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

This product has an Rubber rod antenna, and the maximum antenna gain is 2.43dBi, fulfill the requirement of this section.

11. TEST SETUP & EUT PHOTOGRAPH

Reference to EUT photo attachment for details.

----- End of Report -----