

MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2ASCB-DK4311KSK
EUT	43inch Indoor Landscape IR Touch Digital Kiosk - White
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GH ☒ WLAN: 2.412GHz ~ 2.462GHz ☒ RLAN: 5.180GHz ~ 5.240GHz ☒ RLAN: 5.260GHz ~ 5.320GHz ☒ RLAN: 5.500GHz ~ 5.700GHz ☒ RLAN: 5.745GHz ~ 5.825GHz ☐ Others:
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	BLE: 3.94 dBm (0.0025W) WiFi 2.4G: 13.94 dBm (0.0248W) WiFi 5.2G: 14.09 dBm (0.0256W) WiFi 5.3G: 14.70 dBm (0.0295W) WiFi 5.6G: 13.34 dBm (0.0216W) WiFi 5.8G: 14.85 dBm (0.0305W)
Antenna gain (Max)	BLE: 4.92dBi WiFi 2.4G: 4.92dBi WiFi 5.2G: 5.06dBi WiFi 5.3G: 5.17dBi WiFi 5.6G: 5.21dBi WiFi 5.8G: 5.28dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline
 400-003-0500
 www.anbotek.com.cn



Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
BLE	3.94	3.94 ±1	4.94	4.92	0.0019	1
WiFi 2.4G	13.94	13.94 ±1	14.94	4.92	0.0193	1
WiFi 5.2G	14.09	14.09 ±1	15.09	5.06	0.0206	1
WiFi 5.3G	14.70	14.70 ±1	15.70	5.17	0.0243	1
WiFi 5.6G	13.34	13.34 ±1	14.34	5.21	0.0179	1
WiFi 5.8G	14.85	14.85 ±1	15.85	5.28	0.0258	1

The ratios cannot simultaneous transmission.

Result: No Standalone SAR test is required.

