

RF Exposure Considerations
FCC ID: 2ASCK-GW14
Product: Lamp w/wireless charger and pen holder
Model: ENZ1001-BLK

1. Measuring Standard

KDB 680106 D01 RF Exposure Wireless Charging Apps v03

2. Requirements

According to the item 5.b of KDB 680106 D01v03:

Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC or a PAG for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.


- (1) Power transfer frequency is less than 1 MHz.
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

3. Test Setup



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 15cm measured from the center of the probe(s) to the edge of the device.

4. Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at 15 cm surrounding the device and 20 cm above the top surface of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 v03.

Remark;

The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

5. Test Equipment List

Equipment	Manufacturer	Model No.	Calibration Due
Magnetic field meter	NARDA	ELT-400	Mar. 07, 2022
Mobile Phone	SAMSUNG	SM-G9350	/

6. Test Result

E-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (V/m)

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (V/m)	Limits Test (V/m)
113.14 ~ 146.15	Full load	1.30	1.12	1.41	1.32	1.45	307	614
113.14 ~ 146.15	Half load	1.25	1.33	1.76	1.24	1.28	307	614
113.14 ~ 146.15	No load	1.17	1.26	1.30	1.49	1.14	307	614

H-Filed Strength 15 cm surrounding the device and 20 cm above the top surface of the EUT (A/m)

Frequency Range (KHz)	Operation condition	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limits Test (A/m)	Limits Test ((A/m)
113.14 ~ 146.15	Full load	0.194	0.178	0.199	0.192	0.189	0.815	1.63
113.14 ~ 146.15	Half load	0.182	0.185	0.188	0.194	0.176	0.815	1.63
113.14 ~ 146.15	No load	0.197	0.191	0.187	0.198	0.181	0.815	1.63

NOTE: $uT=1.25*(A/m)$, $1mT=1000000uT$

According to KDB 680106 D01 v03 section 5, b, satisfy the following conditions.

Requirement of KDB 680106 D01	Yes/No	Description
Power transfer frequency is less than 1MHz	Yes	The device operate in the frequency range 113.14kHz - 146.15kHz
Output power from each primary coil is less than or equal to 15 watts	Yes	The maximum output power of the primary coil is 10W.
The transfer system includes only single primary and secondary coils.This includes charging system that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes single coil that is able to detect receiver device.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only(portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

7. Test Set-up Photo



