FCC RADIO TEST REPORT

FCC ID	:	**2ASD2-7483**
Equipment	:	**Digital Media Receiver**
Model name	:	**36EBT3**
Applicant	:	**Process Run LLC** **2815 Forbs Avenue, Suite 107** **Hoffman Estates, IL 60192** **United States**
Standard	:	**FCC Part 15 Subpart E §15.407**

The product was received on Feb. 12, 2019 and testing was started from Jun. 05, 2019 and completed on Jul. 01, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsai

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 5
1.3 Modification of EUT 5
1.4 Testing Location 6
1.5 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 7
2.3 Connection Diagram of Test System 8
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 9
3 Test Result **10**
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 10
3.2 Maximum Conducted Output Power Measurement 13
3.3 Power Spectral Density Measurement 14
3.4 Unwanted Emissions Measurement 16
3.5 AC Conducted Emission Measurement 22
3.6 Automatically Discontinue Transmission 24
3.7 Antenna Requirements 26
4 List of Measuring Equipment **27**
5 Uncertainty of Evaluation **28**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Appendix E. Duty Cycle Plots

History of this test report

Report No.	Version	Description	Issued Date
FR921234-01E	01	Initial issue of report	Jul. 15, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass
3.1	2.1049	99% Occupied Bandwidth	Reporting only
3.2	15.407 (a)	Maximum Conducted Output Power	Pass
3.3	15.407 (a)	Power Spectral Density	Pass
3.4	15.407(b)	Unwanted Emissions	Pass
3.5	15.207	AC Conducted Emission	Pass
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang
Report Producer: Elise Chang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	36EBT3
FCC ID	2ASD2-7483
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	802.11a : 18.20 dBm / 0.0661 W 802.11n HT20 : 18.00 dBm / 0.0631 W 802.11n HT40 : 17.70 dBm / 0.0589 W 802.11ac VHT20 : 17.90 dBm / 0.0617 W 802.11ac VHT40 : 17.60 dBm / 0.0575 W 802.11ac VHT80 : 17.30 dBm / 0.0537 W
99% Occupied Bandwidth	802.11a : 17.18 MHz 802.11n HT20 : 18.03 MHz 802.11n HT40 : 37.06 MHz 802.11ac VHT80 : 77.08 MHz
Antenna Gain / Gain	Printed Inverted-F Antenna with gain 3.0 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	**Sporton Site No.**		
	TH05-HY	CO05-HY	DFS02-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH16-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in two setup, without accessories and with accessories. The worst cases (with earphone) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	**6 Mbps**
802.11n HT20	**MCS0**
802.11n HT40	**MCS0**
802.11ac VHT20 (Covered by HT20)	**MCS0**
802.11ac VHT40 (Covered by HT40)	**MCS0**
802.11ac VHT80	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Play News + LED On + Speaker + Charging from Adapter

Ch. #		Band IV：5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	iPod Earphone	Apple	A1387	Verification	Unshielded, 1.0 m	N/A
4.	Speaker	JAMBOX	Min JAMBOX	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “Compliance Tool 1.0.0.50” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth



Maximum 99% Occupied Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

 # Method SA-3 #

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time ≤ (number of points in sweep) × T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
- Detector = power averaging (rms).
- Trace mode = max hold.
- Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/MHz)



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.3

(ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.[4]

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

EUT is verified this characteristic during the function check of normal sample associated with an access point:

A. Information start: make EUT supply information to the access point.

B. Information stop: stop supplying information to the access point.

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

C. Information start: make EUT supply information to the access point again.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5745MHz

Note : The control / signalling information during the period B is precluded.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	13I00030SNO32	9kHz~6GHz	Dec. 03, 2018	Jun. 11, 2019 ~ Jun. 18, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Jun. 11, 2019 ~ Jun. 18, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	Jun. 11, 2019 ~ Jun. 18, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 24, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jun. 24, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jun. 24, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jun. 24, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 24, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jun. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jun. 24, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 11, 2019	Jun. 05, 2019 ~ Jul. 01,.2019	Jan. 10, 2020	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL6111D&00802N1D01N-06	47020&06	30MHz to 1GHz	Oct. 13, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Oct. 12, 2019	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Sep. 07, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Sep. 06, 2019	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz ~ 40GHz	Nov. 20, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Nov. 19, 2019	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1000MHz	Oct. 02. 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Oct. 01. 2019	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800055007	1GHz~18GHz	Apr. 01, 2019	Jun. 05, 2019 ~ Jul. 01,.2019	Mar. 31, 2020	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 12, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Dec.11, 2019	Radiation (03CH16-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz,VSWR : 2.5:1 max	Jul. 16, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Jul. 15, 2019	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY57290111	3Hz~26.5GHz	Nov. 29, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Nov. 28, 2019	Radiation (03CH16-HY)
Spectrum Analyzer	Agilent	N9010A	MY54200486	10Hz~44GHz	Oct. 19, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Oct. 18, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	MY1082/26EA	30M-18G	Oct. 15, 2018	Jun. 05, 2019 ~ Jul. 01,.2019	Oct. 14, 2019	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15539/4	30M-18G	Feb. 26, 2019	Jun. 05, 2019 ~ Jul. 01,.2019	Feb. 25, 2020	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/4	30M~18GHz	Apr. 15, 2019	Jun. 05, 2019 ~ Jul. 01,.2019	Apr. 14, 2020	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Jun. 05, 2019 ~ Jul. 01,.2019	N/A	Radiation (03CH16-HY)
Spectrum Analyzer	Keysight	N9010A	MY56070412	10Hz~7GHz	Aug. 16, 2018	Jun. 08,2019	Aug. 15, 2019	DFS (DFS02-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.20

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.80

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.90

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Kai Liao	Temperature:	21~25	°C
Test Date:	2019/6/11 ~ 6/18	Relative Humidity:	51~54	%
TX Tool	ComplianceTool	TX Tool Version	1.0.0.50	

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	-	16.88	-	30.72	-	16.33	0.5	Pass
11a	6Mbps	1	157	5785	-	16.93	-	32.17	-	16.33	0.5	Pass
11a	6Mbps	1	165	5825	-	17.18	-	34.57	-	16.28	0.5	Pass
HT20	MCS0	1	149	5745	-	17.93	-	35.02	-	17.53	0.5	Pass
HT20	MCS0	1	157	5785	-	17.93	-	33.02	-	17.53	0.5	Pass
HT20	MCS0	1	165	5825	-	18.03	-	35.91	-	17.63	0.5	Pass
HT40	MCS0	1	151	5755	-	37.06	-	63.93	-	36.32	0.5	Pass
HT40	MCS0	1	159	5795	-	37.06	-	62.13	-	36.32	0.5	Pass
VHT80	MCS0	1	155	5775	-	77.08	-	146.41	-	76.40	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	-	17.50		-	30.00	-	3.00	Pass
11a	6Mbps	1	157	5785	-	17.60		-	30.00	-	3.00	Pass
11a	6Mbps	1	165	5825	-	18.20		-	30.00	-	3.00	Pass
HT20	MCS0	1	149	5745	-	17.50		-	30.00	-	3.00	Pass
HT20	MCS0	1	157	5785	-	17.30		-	30.00	-	3.00	Pass
HT20	MCS0	1	165	5825	-	18.00		-	30.00	-	3.00	Pass
HT40	MCS0	1	151	5755	-	17.70		-	30.00	-	3.00	Pass
HT40	MCS0	1	159	5795	-	17.40		-	30.00	-	3.00	Pass
VHT20	MCS0	1	149	5745	-	17.40		-	30.00	-	3.00	Pass
VHT20	MCS0	1	157	5785	-	17.20		-	30.00	-	3.00	Pass
VHT20	MCS0	1	165	5825	-	17.90		-	30.00	-	3.00	Pass
VHT40	MCS0	1	151	5755	-	17.60		-	30.00	-	3.00	Pass
VHT40	MCS0	1	159	5795	-	17.30		-	30.00	-	3.00	Pass
VHT80	MCS0	1	155	5775	-	17.30		-	30.00	-	3.00	Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	-	0.00	-	2.22	-	5.56		-	30.00	-	3.00	Pass
11a	6Mbps	1	157	5785	-	0.00	-	2.22	-	5.46		-	30.00	-	3.00	Pass
11a	6Mbps	1	165	5825	-	0.00	-	2.22	-	6.29		-	30.00	-	3.00	Pass
HT20	MCS0	1	149	5745	-	0.00	-	2.22	-	5.27		-	30.00	-	3.00	Pass
HT20	MCS0	1	157	5785	-	0.00	-	2.22	-	5.03		-	30.00	-	3.00	Pass
HT20	MCS0	1	165	5825	-	0.00	-	2.22	-	5.82		-	30.00	-	3.00	Pass
HT40	MCS0	1	151	5755	-	0.00	-	2.22	-	2.19		-	30.00	-	3.00	Pass
HT40	MCS0	1	159	5795	-	0.00	-	2.22	-	1.98		-	30.00	-	3.00	Pass
VHT80	MCS0	1	155	5775	-	0.00	-	2.22	-	-1.43		-	30.00	-	3.00	Pass

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	**Temperature :**	24~26℃
		Relative Humidity :	50~53%

EUT Information

Report NO :	921234-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.165750	---	28.67	55.17	26.50	L1	OFF	19.4
0.165750	39.58	---	65.17	25.59	L1	OFF	19.4
0.224250	---	25.30	52.66	27.36	L1	OFF	19.4
0.224250	35.40	---	62.66	27.26	L1	OFF	19.4
0.361500	---	22.97	48.69	25.72	L1	OFF	19.4
0.361500	26.25	---	58.69	32.44	L1	OFF	19.4
0.631500	---	27.77	46.00	18.23	L1	OFF	19.4
0.631500	35.39	---	56.00	20.61	L1	OFF	19.4
1.531500	---	31.70	46.00	14.30	L1	OFF	19.5
1.531500	33.40	---	56.00	22.60	L1	OFF	19.5
5.169750	---	34.77	50.00	15.23	L1	OFF	19.6
5.169750	35.52	---	60.00	24.48	L1	OFF	19.6
14.525250	---	25.00	50.00	25.00	L1	OFF	20.0
14.525250	26.62	---	60.00	33.38	L1	OFF	20.0

EUT Information

Report NO :	921234-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	29.98	55.52	25.54	N	OFF	19.5
0.159000	40.77	---	65.52	24.75	N	OFF	19.5
0.188250	---	26.85	54.11	27.26	N	OFF	19.5
0.188250	38.58	---	64.11	25.53	N	OFF	19.5
0.224250	---	25.02	52.66	27.64	N	OFF	19.5
0.224250	35.17	---	62.66	27.49	N	OFF	19.5
0.357000	---	22.85	48.80	25.95	N	OFF	19.5
0.357000	26.20	---	58.80	32.60	N	OFF	19.5
0.633750	---	25.88	46.00	20.12	N	OFF	19.5
0.633750	31.74	---	56.00	24.26	N	OFF	19.5
4.785000	---	26.64	46.00	19.36	N	OFF	19.7
4.785000	28.86	---	56.00	27.14	N	OFF	19.7
13.670250	---	25.25	50.00	24.75	N	OFF	20.0
13.670250	27.03	---	60.00	32.97	N	OFF	20.0

Appendix C. Radiated Spurious Emission

Test Engineer :	Jacky Hung, Austin Li, and CR Liro	**Temperature :**	20~25°C
		Relative Humidity :	50~60%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5617	57.15	-11.05	68.2	40.78	32.46	13.71	29.8	255	286	P	H
		5698.8	58.5	-45.82	104.32	41.77	32.64	13.93	29.84	255	286	P	H
		5716.6	67.94	-41.91	109.85	51.13	32.68	13.97	29.84	255	286	P	H
		5724	78.95	-40.97	119.92	62.12	32.69	13.99	29.85	255	286	P	H
	*	5745	114.44	-	-	97.51	32.74	14.05	29.86	255	286	P	H
	*	5745	106.3	-	-	89.37	32.74	14.05	29.86	255	286	A	H
		5605	57.31	-10.89	68.2	41	32.43	13.67	29.79	253	65	P	V
		5698.4	57.14	-46.88	104.02	40.41	32.64	13.93	29.84	253	65	P	V
		5719.4	65.1	-45.53	110.63	48.29	32.68	13.98	29.85	253	65	P	V
		5724.8	75.42	-46.32	121.74	58.58	32.69	14	29.85	253	65	P	V
	*	5745	109.73	-	-	92.8	32.74	14.05	29.86	253	65	P	V
	*	5745	101.7	-	-	84.77	32.74	14.05	29.86	253	65	A	V

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5640.6	57.41	-10.79	68.2	40.94	32.51	13.77	29.81	266	288	P	H
		5699.6	58.51	-46.4	104.91	41.78	32.64	13.93	29.84	266	288	P	H
		5715	59.35	-50.05	109.4	42.55	32.67	13.97	29.84	266	288	P	H
		5723.8	58.88	-60.58	119.46	42.05	32.69	13.99	29.85	266	288	P	H
	*	5785	114.38	-	-	97.27	32.83	14.16	29.88	266	288	P	H
	*	5785	106.76	-	-	89.65	32.83	14.16	29.88	266	288	A	H
		5853	58.07	-57.29	115.36	40.98	32.98	14.02	29.91	266	288	P	H
		5870.4	57.13	-49.36	106.49	40.08	33.01	13.96	29.92	266	288	P	H
		5893	56.54	-35.3	91.84	39.52	33.06	13.89	29.93	266	288	P	H
		5941.8	55.36	-12.84	68.2	38.42	33.17	13.72	29.95	266	288	P	H
		5648.8	56.48	-11.72	68.2	39.97	32.53	13.79	29.81	388	24	P	V
		5675.6	56.9	-30.28	87.18	40.27	32.59	13.86	29.82	388	24	P	V
		5716.2	57.73	-52.01	109.74	40.92	32.68	13.97	29.84	388	24	P	V
		5720.2	55.89	-55.37	111.26	39.08	32.68	13.98	29.85	388	24	P	V
	*	5785	109.97	-	-	92.86	32.83	14.16	29.88	388	24	P	V
	*	5785	102.47	-	-	85.36	32.83	14.16	29.88	388	24	A	V
		5851.2	54.68	-64.78	119.46	37.59	32.97	14.03	29.91	388	24	P	V
		5858.4	56.16	-53.69	109.85	39.08	32.99	14	29.91	388	24	P	V
		5917.6	56.09	-17.57	73.66	39.1	33.12	13.81	29.94	388	24	P	V
		5929	55.8	-12.4	68.2	38.84	33.14	13.77	29.95	388	24	P	V

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	113.93	-	-	96.79	32.92	14.12	29.9	265	287	P	H
	*	5825	106.12	-	-	88.98	32.92	14.12	29.9	265	287	A	H
		5850.4	68.33	-52.96	121.29	51.24	32.97	14.03	29.91	265	287	P	H
		5855.2	62.2	-48.54	110.74	45.11	32.98	14.02	29.91	265	287	P	H
		5877	57.97	-45.74	103.71	40.92	33.03	13.94	29.92	265	287	P	H
		5946.6	56.76	-11.44	68.2	39.82	33.18	13.71	29.95	265	287	P	H
	*	5825	109.23	-	-	92.09	32.92	14.12	29.9	376	21	P	V
	*	5825	101.32	-	-	84.18	32.92	14.12	29.9	376	21	A	V
		5850	63.26	-58.94	122.2	46.17	32.97	14.03	29.91	376	21	P	V
		5855	58.22	-52.58	110.8	41.13	32.98	14.02	29.91	376	21	P	V
		5920	56.6	-15.29	71.89	39.62	33.12	13.8	29.94	376	21	P	V
		5949	56.46	-11.74	68.2	39.53	33.19	13.7	29.96	376	21	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	60.83	-13.17	74	64.94	39.71	18.37	62.19	228	244	P	H
		11490	48.93	-5.07	54	53.04	39.71	18.37	62.19	228	244	A	H
		17235	52.65	-15.55	68.2	45.34	43.12	23.27	59.08	100	0	P	H
		11490	59.2	-14.8	74	63.31	39.71	18.37	62.19	219	133	P	V
		11490	48.95	-5.05	54	53.06	39.71	18.37	62.19	219	133	A	V
		17235	51.5	-16.7	68.2	44.19	43.12	23.27	59.08	100	0	P	V
802.11a CH 157 5785MHz		11570	60.01	-13.99	74	64.23	39.6	18.44	62.26	299	230	P	H
		11570	48.62	-5.38	54	52.84	39.6	18.44	62.26	299	230	A	H
		17355	50.93	-17.27	68.2	42.57	43.75	23.43	58.82	100	0	P	H
		11570	59.51	-14.49	74	63.73	39.6	18.44	62.26	201	158	P	V
		11570	48.49	-5.51	54	52.71	39.6	18.44	62.26	201	158	A	V
		17355	51.44	-16.76	68.2	43.08	43.75	23.43	58.82	100	0	P	V
802.11a CH 165 5825MHz		11650	60.5	-13.5	74	64.83	39.49	18.5	62.32	271	222	P	H
		11650	49.4	-4.6	54	53.73	39.49	18.5	62.32	271	222	A	H
		17475	51.7	-16.5	68.2	42.3	44.37	23.59	58.56	100	0	P	H
		11650	60.34	-13.66	74	64.67	39.49	18.5	62.32	190	153	P	V
		11650	49.59	-4.41	54	53.92	39.49	18.5	62.32	190	153	A	V
		17475	51.86	-16.34	68.2	42.46	44.37	23.59	58.56	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5643.2	59.23	-8.97	68.2	42.74	32.52	13.78	29.81	267	284	P	H
		5696.8	60.01	-42.83	102.84	43.29	32.63	13.92	29.83	267	284	P	H
		5715.4	70.58	-38.93	109.51	53.78	32.67	13.97	29.84	267	284	P	H
		5724.8	79.64	-42.1	121.74	62.8	32.69	14	29.85	267	284	P	H
	*	5745	113.52	-	-	96.59	32.74	14.05	29.86	267	284	P	H
	*	5745	105.99	-	-	89.06	32.74	14.05	29.86	267	284	A	H
		5637.2	57.65	-10.55	68.2	41.2	32.5	13.76	29.81	255	59	P	V
		5677	57.88	-30.34	88.22	41.24	32.59	13.87	29.82	255	59	P	V
		5720	65.04	-45.76	110.8	48.23	32.68	13.98	29.85	255	59	P	V
		5725	76.63	-45.57	122.2	59.79	32.69	14	29.85	255	59	P	V
	*	5745	109.57	-	-	92.64	32.74	14.05	29.86	255	59	P	V
	*	5745	101.47	-	-	84.54	32.74	14.05	29.86	255	59	A	V

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5648.6	58.11	-10.09	68.2	41.6	32.53	13.79	29.81	259	289	P	H
		5679.8	59.06	-31.23	90.29	42.41	32.6	13.88	29.83	259	289	P	H
		5700.4	60.01	-45.3	105.31	43.28	32.64	13.93	29.84	259	289	P	H
		5722.4	58.6	-57.67	116.27	41.77	32.69	13.99	29.85	259	289	P	H
	*	5785	114.22	-	-	97.11	32.83	14.16	29.88	259	289	P	H
	*	5785	106.6	-	-	89.49	32.83	14.16	29.88	259	289	A	H
		5853.4	57.25	-57.2	114.45	40.16	32.98	14.02	29.91	259	289	P	H
		5855.8	58.03	-52.55	110.58	40.95	32.98	14.01	29.91	259	289	P	H
		5875.2	57.38	-47.67	105.05	40.32	33.03	13.95	29.92	259	289	P	H
		5928.2	57.46	-10.74	68.2	40.5	33.14	13.77	29.95	259	289	P	H
		5638.6	56.17	-12.03	68.2	39.72	32.5	13.76	29.81	387	20	P	V
		5682.2	56.82	-35.25	92.07	40.17	32.6	13.88	29.83	387	20	P	V
		5712.4	57.39	-51.28	108.67	40.6	32.67	13.96	29.84	387	20	P	V
		5722.8	56.07	-61.11	117.18	39.24	32.69	13.99	29.85	387	20	P	V
	*	5785	109.68	-	-	92.57	32.83	14.16	29.88	387	20	P	V
	*	5785	102.06	-	-	84.95	32.83	14.16	29.88	387	20	A	V
		5852.4	55.85	-60.88	116.73	38.76	32.98	14.02	29.91	387	20	P	V
		5863.8	55.65	-52.68	108.33	38.57	33	13.99	29.91	387	20	P	V
		5916.6	56.91	-17.48	74.39	39.92	33.12	13.81	29.94	387	20	P	V
		5944	55.3	-12.9	68.2	38.35	33.18	13.72	29.95	387	20	P	V

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	113.3	-	-	96.16	32.92	14.12	29.9	263	291	P	H
	*	5825	105.42	-	-	88.28	32.92	14.12	29.9	263	291	A	H
		5851.6	66.89	-51.66	118.55	49.8	32.97	14.03	29.91	263	291	P	H
		5857.2	61.83	-48.35	110.18	44.74	32.99	14.01	29.91	263	291	P	H
		5908.4	57.77	-22.68	80.45	40.77	33.1	13.84	29.94	263	291	P	H
		5949.8	56.31	-11.89	68.2	39.38	33.19	13.7	29.96	263	291	P	H
	*	5825	109.27	-	-	92.13	32.92	14.12	29.9	400	24	P	V
	*	5825	101.49	-	-	84.35	32.92	14.12	29.9	400	24	A	V
		5850	63.68	-58.52	122.2	46.59	32.97	14.03	29.91	400	24	P	V
		5856	60.79	-49.73	110.52	43.71	32.98	14.01	29.91	400	24	P	V
		5888	56.25	-39.3	95.55	39.22	33.05	13.91	29.93	400	24	P	V
		5929.2	55.91	-12.29	68.2	38.95	33.14	13.77	29.95	400	24	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	60.12	-13.88	74	64.23	39.71	18.37	62.19	276	225	P	H
		11490	48.69	-5.31	54	52.8	39.71	18.37	62.19	276	225	A	H
		17235	50.93	-17.27	68.2	43.62	43.12	23.27	59.08	100	0	P	H
		11490	61.53	-12.47	74	65.64	39.71	18.37	62.19	230	153	P	V
		11490	50.04	-3.96	54	54.15	39.71	18.37	62.19	230	153	A	V
		17235	49.26	-18.94	68.2	41.95	43.12	23.27	59.08	100	0	P	V
802.11n HT20 CH 157 5785MHz		11570	60.05	-13.95	74	64.27	39.6	18.44	62.26	272	223	P	H
		11570	48.89	-5.11	54	53.11	39.6	18.44	62.26	272	223	A	H
		17355	50.66	-17.54	68.2	42.3	43.75	23.43	58.82	100	0	P	H
		11570	60.75	-13.25	74	64.97	39.6	18.44	62.26	228	150	P	V
		11570	49.54	-4.46	54	53.76	39.6	18.44	62.26	228	150	A	V
		17355	50.64	-17.56	68.2	42.28	43.75	23.43	58.82	100	0	P	V
802.11n HT20 CH 165 5825MHz		11650	60.15	-13.85	74	64.48	39.49	18.5	62.32	267	221	P	H
		11650	49.07	-4.93	54	53.4	39.49	18.5	62.32	267	221	A	H
		17475	51.16	-17.04	68.2	41.76	44.37	23.59	58.56	100	0	P	H
		11650	61.37	-12.63	74	65.7	39.49	18.5	62.32	230	150	P	V
		11650	49.74	-4.26	54	54.07	39.49	18.5	62.32	230	150	A	V
		17475	52.1	-16.1	68.2	42.7	44.37	23.59	58.56	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5646.6	58.47	-9.73	68.2	41.97	32.52	13.79	29.81	267	284	P	H
		5699.8	66.91	-38.14	105.05	50.18	32.64	13.93	29.84	267	284	P	H
		5717.8	83.97	-26.21	110.18	67.15	32.68	13.98	29.84	267	284	P	H
		5723.4	83.72	-34.83	118.55	66.89	32.69	13.99	29.85	267	284	P	H
	*	5755	111.89	-	-	94.91	32.76	14.08	29.86	267	284	P	H
	*	5755	103.15	-	-	86.17	32.76	14.08	29.86	267	284	A	H
		5853.6	57.04	-56.95	113.99	39.95	32.98	14.02	29.91	267	284	P	H
		5863.6	56.75	-51.64	108.39	39.67	33	13.99	29.91	267	284	P	H
		5908.4	56.31	-24.14	80.45	39.31	33.1	13.84	29.94	267	284	P	H
		5945.4	55.85	-12.35	68.2	38.91	33.18	13.71	29.95	267	284	P	H
		5646.6	57.03	-11.17	68.2	40.53	32.52	13.79	29.81	389	21	P	V
		5698.8	63.49	-40.83	104.32	46.76	32.64	13.93	29.84	389	21	P	V
		5720	78.07	-32.73	110.8	61.26	32.68	13.98	29.85	389	21	P	V
		5724	81.63	-38.29	119.92	64.8	32.69	13.99	29.85	389	21	P	V
	*	5755	108.09	-	-	91.11	32.76	14.08	29.86	389	21	P	V
	*	5755	99.44	-	-	82.46	32.76	14.08	29.86	389	21	A	V
		5851.8	55.67	-62.43	118.1	38.58	32.97	14.03	29.91	389	21	P	V
		5862.2	57.07	-51.71	108.78	39.99	33	13.99	29.91	389	21	P	V
		5888	55.87	-39.68	95.55	38.84	33.05	13.91	29.93	389	21	P	V
		5946.6	55.44	-12.76	68.2	38.5	33.18	13.71	29.95	389	21	P	V

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5610.4	57	-11.2	68.2	40.66	32.44	13.69	29.79	265	286	P	H
		5696.6	59.27	-43.42	102.69	42.55	32.63	13.92	29.83	265	286	P	H
		5717.4	60.33	-49.74	110.07	43.51	32.68	13.98	29.84	265	286	P	H
		5724.4	64.91	-55.92	120.83	48.07	32.69	14	29.85	265	286	P	H
	*	5795	111.46	-	-	94.3	32.85	14.19	29.88	265	286	P	H
	*	5795	103.56	-	-	86.4	32.85	14.19	29.88	265	286	A	H
		5851.6	63.78	-54.77	118.55	46.69	32.97	14.03	29.91	265	286	P	H
		5855	61.97	-48.83	110.8	44.88	32.98	14.02	29.91	265	286	P	H
		5879.2	57.93	-44.15	102.08	40.89	33.03	13.93	29.92	265	286	P	H
		5950	55.75	-12.45	68.2	38.82	33.19	13.7	29.96	265	286	P	H
		5639.2	55.97	-12.23	68.2	39.5	32.51	13.77	29.81	400	24	P	V
		5696.8	57.3	-45.54	102.84	40.58	32.63	13.92	29.83	400	24	P	V
		5720	58.15	-52.65	110.8	41.34	32.68	13.98	29.85	400	24	P	V
		5721.8	58.95	-55.95	114.9	42.12	32.69	13.99	29.85	400	24	P	V
	*	5795	107.06	-	-	89.9	32.85	14.19	29.88	400	24	P	V
	*	5795	98.81	-	-	81.65	32.85	14.19	29.88	400	24	A	V
		5851.8	60.24	-57.86	118.1	43.15	32.97	14.03	29.91	400	24	P	V
		5855	59.51	-51.29	110.8	42.42	32.98	14.02	29.91	400	24	P	V
		5906.8	56.86	-24.77	81.63	39.87	33.09	13.84	29.94	400	24	P	V
		5935.4	55.69	-12.51	68.2	38.73	33.16	13.75	29.95	400	24	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	58.14	-15.86	74	62.27	39.69	18.39	62.21	269	228	P	H
		11510	47.32	-6.68	54	51.45	39.69	18.39	62.21	269	228	A	H
		17265	50.23	-17.97	68.2	42.67	43.28	23.3	59.02	100	0	P	H
		11510	59.49	-14.51	74	63.62	39.69	18.39	62.21	206	131	P	V
		11510	48.13	-5.87	54	52.26	39.69	18.39	62.21	206	131	A	V
		17265	49.77	-18.43	68.2	42.21	43.28	23.3	59.02	100	0	P	V
802.11n HT40 CH 159 5795MHz		11590	58.85	-15.15	74	63.09	39.57	18.46	62.27	262	229	P	H
		11590	47.92	-6.08	54	52.16	39.57	18.46	62.27	262	229	A	H
		17385	51.5	-16.7	68.2	42.88	43.9	23.47	58.75	100	0	P	H
		11590	58.83	-15.17	74	63.07	39.57	18.46	62.27	210	128	P	V
		11590	48.07	-5.93	54	52.31	39.57	18.46	62.27	210	128	A	V
		17385	51.22	-16.98	68.2	42.6	43.9	23.47	58.75	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5649.8	61.06	-7.14	68.2	44.55	32.53	13.79	29.81	263	281	P	H
		5698.6	79.64	-24.53	104.17	62.91	32.64	13.93	29.84	263	281	P	H
		5720	83.64	-27.16	110.8	66.83	32.68	13.98	29.85	263	281	P	H
		5721.8	84.15	-30.75	114.9	67.32	32.69	13.99	29.85	263	281	P	H
	*	5775	107.51	-	-	90.44	32.81	14.13	29.87	263	281	P	H
	*	5775	99.3	-	-	82.23	32.81	14.13	29.87	263	281	A	H
		5854	75.18	-37.9	113.08	58.09	32.98	14.02	29.91	263	281	P	H
		5855	73.76	-37.04	110.8	56.67	32.98	14.02	29.91	263	281	P	H
		5876.4	67.29	-36.87	104.16	50.24	33.03	13.94	29.92	263	281	P	H
		5944	56.5	-11.7	68.2	39.55	33.18	13.72	29.95	263	281	P	H
		5642	57.89	-10.31	68.2	41.42	32.51	13.77	29.81	385	25	P	V
		5696	74.66	-27.59	102.25	57.94	32.63	13.92	29.83	385	25	P	V
		5719.4	78.75	-31.88	110.63	61.94	32.68	13.98	29.85	385	25	P	V
		5723.4	78.39	-40.16	118.55	61.56	32.69	13.99	29.85	385	25	P	V
	*	5775	103.23	-	-	86.16	32.81	14.13	29.87	385	25	P	V
	*	5775	94.96	-	-	77.89	32.81	14.13	29.87	385	25	A	V
		5853.4	68.74	-45.71	114.45	51.65	32.98	14.02	29.91	385	25	P	V
		5856	68.66	-41.86	110.52	51.58	32.98	14.01	29.91	385	25	P	V
		5876.6	61.57	-42.44	104.01	44.52	33.03	13.94	29.92	385	25	P	V
		5927.8	56.05	-12.15	68.2	39.09	33.14	13.77	29.95	385	25	P	V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	47.63	-26.37	74	51.82	39.63	18.42	62.24	100	0	P	H
		17325	50.22	-17.98	68.2	42.12	43.59	23.39	58.88	100	0	P	H
		11550	57.93	-16.07	74	62.12	39.63	18.42	62.24	210	125	P	V
		11550	47.19	-6.81	54	51.38	39.63	18.42	62.24	210	125	A	V
		17325	51.31	-16.89	68.2	43.21	43.59	23.39	58.88	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT20 (LF @ 3m)

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
5GHz 802.11n HT20 LF		91.11	21.64	-21.86	43.5	38.16	14.86	1	32.38	-	-	P	H
		162.89	23.04	-20.46	43.5	37.6	16.24	1.56	32.36	-	-	P	H
		522.76	28.08	-17.92	46	33.24	24.01	3.43	32.6	-	-	P	H
		740.04	30.64	-15.36	46	30.58	28.08	4.44	32.46	-	-	P	H
		834.13	31.04	-14.96	46	29.93	28.72	4.56	32.17	-	-	P	H
		952.47	33.68	-12.32	46	29.54	30.81	4.66	31.33	100	0	P	H
		82.38	28.14	-11.86	40	45.95	13.65	0.93	32.39	100	0	P	V
		164.83	22.73	-20.77	43.5	37.53	15.99	1.57	32.36	-	-	P	V
		373.38	30.54	-15.46	46	39.03	20.98	3.01	32.48	-	-	P	V
		756.53	30.29	-15.71	46	30.02	28.2	4.5	32.43	-	-	P	V
		858.38	31.47	-14.53	46	29.72	29.12	4.66	32.03	-	-	P	V
		967.02	33.51	-20.49	54	28.81	30.95	4.95	31.2	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Jacky Hung, Austin Li, and CR Liro	**Temperature :**	20~25°C
		Relative Humidity :	50~60%

Note symbol

-L	**Low channel location**
-R	**High channel location**

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
2	Vertical	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
2	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
2	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
2	Vertical	Fundamental
Peak		

Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
2	Vertical	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
2	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
2	Horizontal	Fundamental
Peak		

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
2	Vertical	Fundamental
Peak		

Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
2	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
2	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
2	Horizontal	Fundamental
Peak		
Peak		Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
2	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01
Peak	 Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 921234-01	Left blank

Band 4 - 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL Detector : Peak Project : 921234-01

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL Detector : Peak Project : 921234-01

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL Detector : Peak Project : 921234-01

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL Detector : Peak Project : 921234-01

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
2	Horizontal	Vertical
Peak Avg.		

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
2	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 HORIZONTAL Detector : Peak Project : 921234-01	 Site : 03CH16-HY Condition : PEAK(UNII) 3m 9120D_1522 VERTICAL Detector : Peak Project : 921234-01

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
2	Horizontal	Vertical
Peak Avg.		

Emission below 1GHz

5GHz WIFI 802.11n HT20 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT20 LF	
2	Horizontal	Vertical
QP / Peak		

Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
2	802.11a	100.00	-	-	10Hz	0.00
2	5GHz 802.11n HT20	100.00	-	-	10Hz	0.00
2	5GHz 802.11n HT40	100.00	-	-	10Hz	0.00
2	5GHz 802.11ac VHT20	100.00	-	-	10Hz	0.00
2	5GHz 802.11ac VHT40	100.00	-	-	10Hz	0.00
2	5GHz 802.11ac VHT80	100.00	-	-	10Hz	0.00

<Ant. 2>

802.11a



Date: 12.JUN.2019 01:00:20

802.11n HT20



Date: 12.JUN.2019 01:00:48

802.11n HT40



Date: 12.JUN.2019 01:02:12

802.11ac VHT20



Date: 12.JUN.2019 01:01:14

802.11ac VHT40



Date: 12.JUN.2019 01:01:42

802.11ac VHT80



Date: 12.JUN.2019 01:04:09

———THE END———