S T S L A B

RADIO TEST REPORT

Report No.:STS2003011W02

Issued for

Beijing Jinshan Security Software Co., Ltd.

East Zone, 2/f, No. 33 Xiaoying West Road, Haidian District, Beijing, China

Product Name:	cheetahTALK Plus
Brand Name:	Cheetah mobile
Model Name:	B03A
Series Model:	B03G, B03J
FCC ID:	2ASGM-B03A
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District,Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com

TEST RESULT CERTIFICATION

Applicant's Name ..... : Beijing Jinshan Security Software Co., Ltd.

Address ..... : East Zone, 2/f, No. 33 Xiaoying West Road, Haidian District, Beijing, China

Manufacture's Name ..... : Hefei Bei YU Electronic Technology Co., Ltd.

Address ..... : Standard workshop 8, Jinshan Road, Chaohu Economic Development Zone, Hefei City, Anhui Province

Product Description

Product Name ..... : cheetahTALK Plus

Brand Name ..... : Cheetah mobile

Model Name ..... : B03A

Series Model ..... : B03G, B03J

Test Standards ..... : FCC Part15.247

Test Procedure..... : ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item..... : 05 Mar. 2020

Date (s) of performance of tests..... : 05 Mar. 2020 ~ 16 Mar. 2020

Date of Issue ..... : 16 Mar. 2020

Test Result ..... : **Pass**

Testing Engineer : Chris Chen

(Chris Chen)

Technical Manager : Sean She

(Sean she)

Authorized Signatory : Vita Li

(Vita Li)

TESTING CONSULTING SOLUTION CERTIFICATION STS APPROVAL

Table of Contents

Page

1. SUMMARY OF TEST RESULTS **6#**
1.1 TEST FACTORY 7#
1.2 MEASUREMENT UNCERTAINTY 7#
2. GENERAL INFORMATION **8#**
2.1 GENERAL DESCRIPTION OF THE EUT 8#
2.2 DESCRIPTION OF THE TEST MODES 10#
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 11#
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS 12#
2.5 EQUIPMENTS LISTS 13#
3. EMC EMISSION TEST **14#**
3.1 CONDUCTED EMISSION MEASUREMENT 14#
3.2 RADIATED EMISSION MEASUREMENT 18#
4.CONDUCTED SPURIOUS & BAND EDGE EMISSION **30#**
4.1 LIMIT 30#
4.2 TEST PROCEDURE 30#
4.3 DEVIATION FROM STANDARD 30#
4.4 TEST SETUP 30#
4.5 EUT OPERATION CONDITIONS 30#
4.6 TEST RESULTS 31#
5. POWER SPECTRAL DENSITY TEST **43#**
5.1 LIMIT 43#
5.2 TEST PROCEDURE 43#
5.3 DEVIATION FROM STANDARD 43#
5.4 TEST SETUP 43#
5.5 EUT OPERATION CONDITIONS 43#
5.6 TEST RESULTS 44#
6. BANDWIDTH TEST **50#**
6.1 LIMIT 50#
6.2 TEST PROCEDURE 50#
6.3 DEVIATION FROM STANDARD 50#
6.4 TEST SETUP 50#
6.5 EUT OPERATION CONDITIONS 50#
6.6 TEST RESULTS 51#

Table of Contents

Page

7. PEAK OUTPUT POWER TEST **57#**
7.1 LIMIT 57#
7.2 TEST PROCEDURE 57#
7.3 DEVIATION FROM STANDARD 57#
7.4 TEST SETUP 57#
7.5 EUT OPERATION CONDITIONS 57#
7.6 TEST RESULTS 58#
8. ANTENNA REQUIREMENT **59#**
8.1 STANDARD REQUIREMENT 59#
8.2 EUT ANTENNA 59#
APPENDIX-PHOTOS OF TEST SETUP **60#**

Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	16 Mar. 2020	STS2003011W02	ALL	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.247 (c)	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) “N/A” denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD
Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	±0.68dB
2	Unwanted Emissions, conducted	±2.988dB
3	All emissions, radiated 30-1GHz	±6.7dB
4	All emissions, radiated 1G-6GHz	±5.5dB
5	All emissions, radiated>6G	±5.8dB
6	Conducted Emission (9KHz-150KHz)	±4.43dB
7	Conducted Emission (150KHz-30MHz)	±5dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

<table>
<tr><td>Product Name</td><td>cheetahTALK Plus</td></tr>
<tr><td>Trade Name</td><td>Cheetah mobile</td></tr>
<tr><td>Model Name</td><td>B03A</td></tr>
<tr><td>Series Model</td><td>B03G, B03J</td></tr>
<tr><td>Model Difference</td><td>Only different in model name</td></tr>
<tr><td>Product Description</td><td>The EUT is a cheetahTALK Plus
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n 20: 2412~2462 MHz</td></tr>
<tr><td>Modulation Type:</td><td>802.11b(DSSS):CCK,DQPSK,DBPSK
802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM
802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM</td></tr>
<tr><td>Bit Rate of Transmitter:</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n(20MHz):
65/58.5/52/39/26/19.5/13/6.5Mbps</td></tr>
<tr><td>Number of Channel:</td><td>802.11b/g/n20: 11CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please refer to see Note 3.</td></tr>
<tr><td>AntennaGain (dBi):</td><td>-5 dBi</td></tr>
<tr><td>Duty Cycle:</td><td>>98%</td></tr>
</table></td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Power Rating</td><td>Input: 5V,500mA</td></tr>
<tr><td>Battery</td><td>Rated Voltage: 3.8V
Charge Limit: 4.35V
Capacity: 1000mAh</td></tr>
<tr><td>Hardware version number</td><td>BY-V3.2</td></tr>
<tr><td>Software version number</td><td>V1.00.13</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the Note 1.</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

2.

Operation Frequency of channel	
802.11b/g/n(20MHz)	
Channel	Frequency
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, themiddle frequency, and the highest frequency of channel were selected to perform the test, and the selectedchannel see below:
Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)	
Channel	Freq.(MHz)
01	2412
06	2437
11	2462

3.

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	Cheetah mobile	B03A	FPC	N/A	-5 dBi	WLAN Antenna

2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0

Note:
(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V /60Hz is shown in the report.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode10: Keeping WIFI TX

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set



conduction Test Set



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-3	Adapter	LITEON	PA-1650-86	N/A	N/A
C-2	DC Cable	N/A	100cm	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Notebook	ThinkPad	N/A	N/A	N/A
C-1	USB Cable	N/A	110cm	N/A	N/A

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 EQUIPMENTS LISTS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2019.07.29	2020.07.28
Signal Analyzer	Agilent	N9020A	MY51110105	2020.03.05	2021.03.04
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.01
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2019.10.09	2020.10.08
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2019.10.12	2020.10.11
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2019.07.29	2020.07.28
LISN	R&S	ENV216	101242	2019.10.09	2020.10.08
LISN	EMCO	3810/2NM	23625	2019.10.09	2020.10.08
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2019.10.09	2020.10.08
Signal Analyzer	Agilent	N9020A	MY49100060	2019.10.09	2020.10.08
Temperature & Humidity	HH660	Mieo	N/A	2019.10.12	2020.10.11
Test SW	FARAD	LZ-RF /LzRf-3A3			

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	**Setting**
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.5 TEST RESULT

Temperature:	23.8(C)	Relative Humidity:	53%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 10		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	
1	0.2467	18.66	19.99	38.65	61.87	-23.22	QP
2	0.2467	5.96	19.99	25.95	51.87	-25.92	AVG
3	0.3870	17.95	20.06	38.01	58.13	-20.12	QP
4	0.3870	12.17	20.06	32.23	48.13	-15.90	AVG
5	1.0500	18.21	19.80	38.01	56.00	-17.99	QP
6	1.0500	6.18	19.80	25.98	46.00	-20.02	AVG
7	3.5980	13.07	19.82	32.89	56.00	-23.11	QP
8	3.5980	3.06	19.82	22.88	46.00	-23.12	AVG
9	7.0540	14.93	19.89	34.82	60.00	-25.18	QP
10	7.0540	2.73	19.89	22.62	50.00	-27.38	AVG
11	14.4380	11.79	20.23	32.02	60.00	-27.98	QP
12	14.4380	0.07	20.23	20.30	50.00	-29.70	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor)–Limit



Temperature:	23.8(C)	Relative Humidity:	53%RH
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 10		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	
1	0.1740	21.18	19.79	40.97	64.77	-23.80	QP
2	0.1740	5.26	19.79	25.05	54.77	-29.72	AVG
3	0.4540	19.92	20.03	39.95	56.80	-16.85	QP
4	0.4540	13.55	20.03	33.58	46.80	-13.22	AVG
5	0.9180	19.48	19.81	39.29	56.00	-16.71	QP
6	0.9180	7.79	19.81	27.60	46.00	-18.40	AVG
7	2.8740	13.96	19.81	33.77	56.00	-22.23	QP
8	2.8740	2.13	19.81	21.94	46.00	-24.06	AVG
9	7.8140	16.37	19.97	36.34	60.00	-23.66	QP
10	7.8140	1.52	19.97	21.49	50.00	-28.51	AVG
11	18.7580	11.99	20.40	32.39	60.00	-27.61	QP
12	18.7580	-1.03	20.40	19.37	50.00	-30.63	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result =Reading + Factor)–Limit



3.2 RADIATED EMISSION MEASUREMENT

3.2.1RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2425 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
b. The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were testedand performed test to three orthogonal axis. The worst case emissions were reported.

3.2.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting theAmplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

Factor=AF+CL-AG

3.2.6 TEST RESULT

9KHz-30MHz

Temperature:	22.9(C)	Relative Humidtity:	52%RH
Test Voltage:	DC 3.8V	Polarization:	--
Test Mode:	TX Mode		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F	Test Result
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

(30MHz - 1000MHz)

Temperature:	22.9(C)	Relative Humidtity:	52%RH
Test Voltage:	DC 3.8V	Phase:	Horizontal
Test Mode:	Mode 1/2/3/4/5/6/7/8/9(Mode 4 worst mode)		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	83.3500	53.88	-22.52	31.36	40.00	-8.64	QP
2	215.2700	54.73	-20.17	34.56	43.50	-8.94	QP
3	399.5700	40.60	-11.16	29.44	46.00	-16.56	QP
4	600.3600	36.36	-5.84	30.52	46.00	-15.48	QP
5	700.2700	38.41	-4.16	34.25	46.00	-11.75	QP
6	976.7200	29.77	2.45	32.22	54.00	-21.78	QP

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit



Temperature:	22.9(C)	Relative Humidtity:	52%RH
Test Voltage:	DC 3.8V	Phase:	Vertical
Test Mode:	Mode 1/2/3/4/5/6/7/8/9(Mode 4 worst mode)		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	71.7100	55.42	-24.56	30.86	40.00	-9.14	QP
2	215.2700	49.02	-20.17	28.85	43.50	-14.65	QP
3	348.1600	44.07	-13.13	30.94	46.00	-15.06	QP
4	534.4000	33.64	-7.20	26.44	46.00	-19.56	QP
5	644.9800	31.73	-4.87	26.86	46.00	-19.14	QP
6	899.1200	34.28	-0.47	33.81	46.00	-12.19	QP

Remark:.

1. Margin = Result (Result =Reading + Factor)–Limit



(1000MHz-25GHz) Restricted band and Spurious emission Requirements

802.11g

Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Orrected Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	（dB）	（dB）	（dB/m）	（dB）	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (802.11g/2412 MHz)										
3264.87	61.25	44.70	6.70	28.20	-9.80	51.45	74.00	-22.55	PK	Vertical
3264.87	51.82	44.70	6.70	28.20	-9.80	42.02	54.00	-11.98	AV	Vertical
3264.80	62.07	44.70	6.70	28.20	-9.80	52.27	74.00	-21.73	PK	Horizontal
3264.80	50.75	44.70	6.70	28.20	-9.80	40.95	54.00	-13.05	AV	Horizontal
4824.44	59.03	44.20	9.04	31.60	-3.56	55.47	74.00	-18.53	PK	Vertical
4824.44	49.71	44.20	9.04	31.60	-3.56	46.15	54.00	-7.85	AV	Vertical
4824.37	59.31	44.20	9.04	31.60	-3.56	55.75	74.00	-18.25	PK	Horizontal
4824.37	49.80	44.20	9.04	31.60	-3.56	46.24	54.00	-7.76	AV	Horizontal
5359.66	48.68	44.20	9.86	32.00	-2.34	46.34	74.00	-27.66	PK	Vertical
5359.66	39.91	44.20	9.86	32.00	-2.34	37.57	54.00	-16.43	AV	Vertical
5359.85	47.18	44.20	9.86	32.00	-2.34	44.84	74.00	-29.16	PK	Horizontal
5359.85	38.73	44.20	9.86	32.00	-2.34	36.39	54.00	-17.61	AV	Horizontal
7235.70	54.21	43.50	11.40	35.50	3.40	57.61	74.00	-16.39	PK	Vertical
7235.70	43.70	43.50	11.40	35.50	3.40	47.10	54.00	-6.90	AV	Vertical
7235.76	54.93	43.50	11.40	35.50	3.40	58.33	74.00	-15.67	PK	Horizontal
7235.90	44.85	43.50	11.40	35.50	3.40	48.25	54.00	-5.75	AV	Horizontal
Middle Channel (802.11g/2437 MHz)										
3264.72	62.29	44.70	6.70	28.20	-9.80	52.49	74.00	-21.51	PK	Vertical
3264.72	50.33	44.70	6.70	28.20	-9.80	40.53	54.00	-13.47	AV	Vertical
3264.82	61.04	44.70	6.70	28.20	-9.80	51.24	74.00	-22.76	PK	Horizontal
3264.82	50.97	44.70	6.70	28.20	-9.80	41.17	54.00	-12.83	AV	Horizontal
4874.40	58.55	44.20	9.04	31.60	-3.56	54.99	74.00	-19.01	PK	Vertical
4874.40	49.16	44.20	9.04	31.60	-3.56	45.60	54.00	-8.40	AV	Vertical
4874.34	58.50	44.20	9.04	31.60	-3.56	54.94	74.00	-19.06	PK	Horizontal
4874.34	49.31	44.20	9.04	31.60	-3.56	45.75	54.00	-8.25	AV	Horizontal
5359.62	49.06	44.20	9.86	32.00	-2.34	46.72	74.00	-27.28	PK	Vertical
5359.62	38.95	44.20	9.86	32.00	-2.34	36.61	54.00	-17.39	AV	Vertical
5359.87	47.31	44.20	9.86	32.00	-2.34	44.97	74.00	-29.03	PK	Horizontal
5359.87	39.15	44.20	9.86	32.00	-2.34	36.81	54.00	-17.19	AV	Horizontal
7310.94	53.61	43.50	11.40	35.50	3.40	57.01	74.00	-16.99	PK	Vertical
7310.94	43.71	43.50	11.40	35.50	3.40	47.11	54.00	-6.89	AV	Vertical
7310.85	53.83	43.50	11.40	35.50	3.40	57.23	74.00	-16.77	PK	Horizontal
7310.85	44.80	43.50	11.40	35.50	3.40	48.20	54.00	-5.80	AV	Horizontal

High Channel (802.11g/2462 MHz)										
3264.87	61.23	44.70	6.70	28.20	-9.80	51.43	74.00	-22.57	PK	Vertical
3264.87	50.62	44.70	6.70	28.20	-9.80	40.82	54.00	-13.18	AV	Vertical
3264.67	62.08	44.70	6.70	28.20	-9.80	52.28	74.00	-21.72	PK	Horizontal
3264.67	50.29	44.70	6.70	28.20	-9.80	40.49	54.00	-13.51	AV	Horizontal
4924.44	58.30	44.20	9.04	31.60	-3.56	54.74	74.00	-19.26	PK	Vertical
4924.44	50.14	44.20	9.04	31.60	-3.56	46.58	54.00	-7.42	AV	Vertical
4924.41	58.27	44.20	9.04	31.60	-3.56	54.71	74.00	-19.29	PK	Horizontal
4924.41	50.56	44.20	9.04	31.60	-3.56	47.00	54.00	-7.00	AV	Horizontal
5359.63	49.25	44.20	9.86	32.00	-2.34	46.91	74.00	-27.09	PK	Vertical
5359.63	40.26	44.20	9.86	32.00	-2.34	37.92	54.00	-16.08	AV	Vertical
5359.67	47.81	44.20	9.86	32.00	-2.34	45.47	74.00	-28.53	PK	Horizontal
5359.67	39.51	44.20	9.86	32.00	-2.34	37.17	54.00	-16.83	AV	Horizontal
7385.76	53.94	43.50	11.40	35.50	3.40	57.34	74.00	-16.66	PK	Vertical
7385.76	44.17	43.50	11.40	35.50	3.40	47.57	54.00	-6.43	AV	Vertical
7385.68	53.49	43.50	11.40	35.50	3.40	56.89	74.00	-17.11	PK	Horizontal
7385.68	44.91	43.50	11.40	35.50	3.40	48.31	54.00	-5.69	AV	Horizontal

Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11b, 802.11g, 802.11n (HT-20), the worst case is 802.11g.
   Emission Level = Reading + Factor
   Margin = Limit - Emission Level
3. The frequency emission of peak pointsthat did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

3.2.6 TEST RESULTS(Band edge Requirements)

802.11b-Low

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2326.100	42.04	3.61	45.65	74.00	-28.35	peak
2	2390.000	41.20	4.34	45.54	74.00	-28.46	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2329.665	41.82	3.63	45.45	74.00	-28.55	peak
2	2390.000	40.40	4.34	44.74	74.00	-29.26	peak

802.11b-High

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	42.01	4.60	46.61	74.00	-27.39	peak
2	2499.500	42.09	4.65	46.74	74.00	-27.26	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	40.99	4.60	45.59	74.00	-28.41	peak
2	2495.850	41.75	4.64	46.39	74.00	-27.61	peak

Note: 802.11b, 802.11g, 802.11n (HT-20) mode all have been tested, the worst case is 802.11b, only show the worst case.

4.CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

.

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2432 MHz Upper Band Edge: 2442 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP

The EUT which is powered by the Battery, is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX b Mode /CH01, CH06, CH11

CH 01



CH 06



CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:31:20 PM Mar 13, 2020
Ref Offset 0.5 dB
10 dB/div
Ref 14.74 dBm
Mkr1 2.462 7 GHz
4.735 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (40001 pts)
1 N 1 f 2.462 7 GHz 4.735 dBm
2 N 1 f 2.502 0 GHz -53.580 dBm
3 N 1 f 7.385 5 GHz -36.169 dBm
4 N 1 f 24.486 2 GHz -48.599 dBm

Band edge(it's also the reference level for conducted spurious emission)

CH 01



CH 06

CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.471000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:30:51 PM Mar 13, 2020
Ref Offset 0.5 dB
10 dB/div
Ref 16.09 dBm
Mkr1 2.461 546 GHz
6.086 dBm
Start 2.44200 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 5.60 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.461 546 GHz 6.086 dBm
2 N 1 f 2.483 528 GHz -54.756 dBm
3 N 1 f 2.484 514 GHz -50.039 dBm
4 N 1 f 2.491 996 GHz -49.025 dBm

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX g Mode /CH01, CH06, CH11

CH 01



CH06



CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:59:21 PM Mar 13, 2020
Ref Offset 0.5 dB
10 dB/div
Ref 9.20 dBm
Log
Mkr1 2.464 6 GHz
-0.804 dBm
-18.47 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (40001 pts)
1 N 1 f 2.464 6 GHz -0.804 dBm
2 N 1 f 3.693 1 GHz -52.060 dBm
3 N 1 f 7.387 4 GHz -43.805 dBm
4 N 1 f 24.417 0 GHz -48.109 dBm

Band edge(it's also the reference level for conducted spurious emission)

CH 01



CH06



CH11


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.471000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:58:51 PM Mar 13, 2020
Mkr1 2.455 804 GHz
1.533 dBm
Ref Offset 0.5 dB
10 dB/div
Ref 11.53 dBm
Log
1.53
-8.47
-18.5
-28.5
-38.5
-48.5
-58.5
-68.5
-78.5
-18.47 dBm
Start 2.44200 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 5.60 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.455 804 GHz 1.533 dBm
2 N 1 f 2.483 528 GHz -45.354 dBm
3 N 1 f 2.484 166 GHz -45.619 dBm
4 N 1 f 2.493 562 GHz -49.775 dBm
MSG
STATUS

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX n Mode(20M) /CH01, CH06, CH11

CH 01



CH 06



CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:55:37 PM Mar 13, 2020
Ref Offset 0.5 dB
10 dB/div
Ref 6.83 dBm
Log
Mkr1 2.455 8 GHz
-3.166 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.39 s (40001 pts)
1 N 1 f 2.455 8 GHz -3.166 dBm
2 N 1 f 3.693 1 GHz -51.424 dBm
3 N 1 f 7.371 8 GHz -46.072 dBm
4 N 1 f 24.453 8 GHz -46.856 dBm

Band edge(it's also the reference level for conducted spurious emission)

CH 01



CH 06



CH 11


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.471000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
01:55:07 PM Mar 13, 2020
Ref Offset 0.5 dB
10 dB/div
Ref 10.99 dBm
Log
Mkr1 2.468 332 GHz
0.993 dBm
-19.01 dBm
Start 2.44200 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.50000 GHz
Sweep 5.60 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.468 332 GHz 0.993 dBm
2 N 1 f 2.483 528 GHz -44.157 dBm
3 N 1 f 2.484 340 GHz -44.735 dBm
4 N 1 f 2.491 706 GHz -49.899 dBm
MSG
STATUS

5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤8 dBm (RBW ≥3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the 100 kHz ≥ RBW ≥3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX b Mode /CH01, CH06, CH11

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3KHz)	Result
2412 MHz	-8.286	≤8	PASS
2437 MHz	-7.414	≤8	PASS
2462 MHz	-8.329	≤8	PASS

TX CH01



TX CH06

TX CH11

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX g Mode /CH01, CH06, CH11

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3KHz)	Result
2412 MHz	-13.871	≤8	PASS
2437 MHz	-13.826	≤8	PASS
2462 MHz	-12.254	≤8	PASS

TX CH01

TX CH06

TX CH11

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX n Mode(20M) /CH01, CH06, CH11

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3KHz)	Result
2412 MHz	-14.526	≤8	PASS
2437 MHz	-12.825	≤8	PASS
2462 MHz	-13.177	≤8	PASS

TX CH01

TX CH06

TX CH11

6. BANDWIDTH TEST

6.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	≥500KHz (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW≥3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be≥6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX b Mode /CH01, CH06, CH11

Remark: PEAK DETECTOR IS USED

Frequency	6dB Bandwidth	Channel Separation	Result
	(MHz)	(KHz)	
2412 MHz	8.066	≥500KHz	PASS
2437 MHz	9.036	≥500KHz	PASS
2462 MHz	8.061	≥500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX g Mode /CH01, CH06, CH11

Frequency	6dB Bandwidth	Channel Separation	Result
	(MHz)	(KHz)	
2412 MHz	16.28	≥500KHz	PASS
2437 MHz	16.27	≥500KHz	PASS
2462 MHz	16.04	≥500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V	Test Mode:	TX n Mode(20M) /CH01, CH06, CH11

Frequency	6dB Bandwidth	Channel Separation	Result
	(MHz)	(KHz)	
2412 MHz	17.56	≥500KHz	PASS
2437 MHz	17.56	≥500KHz	PASS
2462 MHz	17.55	≥500KHz	PASS

TX CH 01



TX CH 06



TX CH 11



7. PEAK OUTPUT POWER TEST

7.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW ≥ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

a) Set the RBW ≥ DTS bandwidth.
b) Set VBW ≥ [3 × RBW].
c) Set span ≥ [3 × RBW].
d) Sweep time = auto couple.
e) Detector = peak.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the

DTS bandwidth:

a) Set the RBW = 1 MHz.
b) Set the VBW ≥ [3 × RBW].
c) Set the span ≥ [1.5 × DTS bandwidth].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Temperature:	25℃	Relative Humidity:	60%
Test Voltage:	DC 3.8V		

Mode	Test Channe	Frequency	Peak Conducted Output Power	Average Conducted Output Power	LIMIT
		(MHz)	(dBm)	(dBm)	dBm
TX 802.11b	CH01	2412	11.14	8.58	30
	CH06	2437	11.06	8.59	30
	CH11	2462	11.27	8.77	30
TX 802.11g	CH01	2412	18.28	8.16	30
	CH06	2437	19.38	8.23	30
	CH11	2462	18.83	8.42	30
TX 802.11n20	CH01	2412	18.03	8.10	30
	CH06	2437	18.29	8.11	30
	CH11	2462	17.77	8.16	30

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible partyshall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.

APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※