TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID: 2ASHW-V530

Product: Mobile Phone

Model No.: V530

Additional Model No.: N/A

Trade Mark: N/A

Report No.: TCT190212E004

Issued Date: Apr. 23, 2019

Issued for:

Techuniverse Limited

Flat B, 5/F, 53-55 Tong Mi Road, Tai Kok Tsui, Kowloon, Hong Kong

Issued By:

Shenzhen Tongce Testing Lab.

1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: *This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab. This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.*

TABLE OF CONTENTS

1. Test Certification 3
2. Test Result Summary 4
3. EUT Description 5
4. General Information 7
4.1. Test environment and mode 7
4.2. Test Mode 9
4.3. Description of Support Units 10
4.4. Configuration of Tested System 11
4.5. Measurement Results Explanation Example 11
5. Facilities and Accreditations 12
5.1. Facilities 12
5.2. Location 12
5.3. Measurement Uncertainty 12
6. Test Results and Measurement Data 13
6.1. Conducted Output Power Measurement 13
6.2. Peak to Average Ratio 15
6.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement 23
6.4. Band Edge and Conducted Spurious Emission Measurement 32
6.5. Effective Radiated Power and Effective Isotropic Radiated Power Measurement 45
6.6. Field Strength of Spurious Radiation Measurement 52
6.7. Frequency Stability Measurement 60
Appendix A: Photographs of Test Setup
Appendix B: Photographs of EUT

1. Test Certification

Product:	Mobile Phone
Model No.:	V530
Additional Model No.:	N/A
Trade Mark:	**N/A**
Applicant:	Techuniverse Limited
Address:	Flat B, 5/F, 53-55 Tong Mi Road, Tai Kok Tsui, Kowloon, Hong Kong
Manufacturer:	Primatronix Nanho Technology ltd.
Address:	Room 3A, 3/F, Block 2, Front Industrial zone, no. 215 Busha Road, Nanwan, Longgang, Guangdong, China
Date of Test:	Feb. 13, 2019 – Apr. 22, 2019
Applicable Standards:	FCC CFR Title 47 Part 2 FCC CFR Title 47 Part22 FCC CFR Title 47 Part24

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Jerry Xie ***Date:*** ***Apr. 22, 2019***

Jerry Xie

Reviewed By: Beryl Zhao ***Date:*** ***Apr. 23, 2019***

Beryl Zhao

Approved By: Tomsin ***Date:*** ***Apr. 23, 2019***

Tomsin

2. Test Result Summary

Requirement	CFR 47 Section	Result
Conducted Output Power	§22.913; §2.1046 §24.232	PASS
Peak-to-Average Ratio	§2.1046; §24.232(d)	PASS
Effective Radiated Power	§2.1046; §22.913(a) §24.232	PASS
Equivalent Isotropic Radiated Power	§2.1046; §22.913(a) §24.232	PASS
Occupied Bandwidth	§2.1049	PASS
Band Edge	§2.1051 §22.917(a) §24.238(a)	PASS
Conducted Spurious Emission	§2.1051; §22.917 §24.238	PASS
Field Strength of Spurious Radiation	§2.1053; §22.917(a) §24.238	PASS
Frequency Stability for Temperature & Voltage	§2.1055;§22.355 §24.235	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. EUT Description

Product:	Mobile Phone
Model No.:	V530
Additional Model No.:	N/A
Trade Mark:	**N/A**
Hardware Version:	W7607-MB-V2.0
Software Version:	W7607A_03J_NH_V530_QVGA_Y5R_V16_BT_FM_SC_V530_20181126_2042
3G Version:	WCDMA: R99 HSDPA: Release 5 HSUPA: Release 6
Tx Frequency:	GSM/GPRS850: 824.2MHz ~ 848.8MHz GSM/GPRS1900: 1850.2MHz ~ 1909.8MHz WCDMA Band V: 826.4MHz ~ 846.6MHz WCDMA Band II: 1852.4MHz ~ 1907.6MHz
Rx Frequency:	GSM/GPRS850: 869.2MHz ~ 893.8MHz GSM/GPRS1900: 1930.2MHz ~ 1989.8MHz WCDMA Band V: 871.4MHz ~ 891.6MHz WCDMA Band II: 1932.4MHz ~ 1987.6MHz
Maximum Output Power to Antenna:	GSM850: 30.80dBm GSM1900: 30.10dBm GPRS850: 30.74dBm GPRS1900: 29.62dBm WCDMA Band V: 23.98dBm WCDMA Band II: 21.80dBm
99% Occupied Bandwidth:	GSM850: 244KGXW GSM1900: 247KGXW GPRS850 Class 8:244KGXW GPRS1900 Class 8: 245KGXW WCDMA Band V RMC 12.2Kbps: 4M18F9W WCDMA Band II RMC 12.2Kbps: 4M17F9W
Type of Modulation:	GSM/GPRS: GMSK WCDMA/HSDPA/HSUPA: QPSK
Antenna Type:	Internal Antenna
Antenna Gain:	GSM/GPRS850: -0.6dBi GSM/GPRS1900: -0.5dBi WCDMA Band V: 1dBi WCDMA Band II: 1dBi
Power Supply:	Rechargeable Li-ion Battery DC 3.7V
AC adapter:	Adapter Information:

	MODEL: HP-050200A1-VDE INPUT: AC 100-240V, 50/60Hz, 0.3A OUTPUT: DC 5V, 1000mA

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

4. General Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Operation mode:	Keep the EUT in communication with CMU200 and select channel with modulation
Remark: This product has a built-in rechargeable battery, so in an independent test, the EUT battery was fully-charged. SIM1 supports GSM, WCDMA function, SIM2 only supports GSM function.	
The sample was placed (0.8m below 1GHz, 0.8m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case (Y axis)are shown in Test Results of the following pages.	

Description Operation Frequency

GSM 850		PCS1900	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
….	….	….	….
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
…	…	…	…
250	848.60	809	1909.60
251	848.80	810	1909.80

WCDMA Band V		WCDMA Band II	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
4132	826.40	9262	1852.40
4133	826.60	9263	1852.60
….	….	….	….
4182	836.40	9399	1879.80
4183	836.60	9400	1880.00
4184	836.80	9401	1880.20
…	…	…	…
4233	846.60	9538	1907.60

4.2. Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power. Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.
Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 20000 MHz for PCS1900, WCDMA Band II and WCDMA Band V.

All modes and data rates and positions were investigated.
Test modes are chosen to be reported as the worst case configuration below:

Test Mode		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	GSM Link GPRS class 12 Link	GSM Link GPRS class 12 Link
PCS 1900	GSM Link GPRS class 12 Link	GSM Link GPRS class 12 Link
WCDMA Band V	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDM Band II	RMC 12.2Kbps Link	RMC 12.2Kbps Link

Note: *The maximum power levels are chosen to test as the worst case configuration as follows: GPRS multi-slot class 12 mode for GMSK modulation.RMC 12.2Kbps mode for WCDMA band V and WCDMA band II, only these modes were used for all tests. In addition to above worst-case test, below investigating on all data rates and all modes are compliance with each FCC test case which has specific test limits. For spurious emissions at antenna port, the EUT was investigated the band edges on low and high channels, and the unwanted spurious emissions on middle channel for all modes, the results are PASS, then only the worst-results were reported in the test report. The Radiated Spurious emissions for GPRS modes were investigated on the middle channel and the PASS results were not worst than those data tested from the highest power channels.*

4.3. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4. Configuration of Tested System



4.5. Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level. The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 3 dB and a 5dB attenuator.

Example: *Offset (dB) = RF cable loss (dB) + attenuator factor (dB).*

= 8(dB)

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  Shenzhen Tongce Testing Lab
  The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
  The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab
Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China
TEL: +86-755-27673339

5.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	±2.56dB
2	RF power, conducted	±0.12dB
3	Spurious emissions, conducted	±0.11dB
4	All emissions, radiated(<1G)	±3.92dB
5	All emissions, radiated(>1G)	±4.28dB
6	Temperature	±0.1°C
7	Humidity	±1.0%

6. Test Results and Measurement Data

6.1. Conducted Output Power Measurement

6.1.1. Test Specification

Test Requirement:	FCC part 22.913(a) and FCC part 24.232(b)
Test Method:	FCC KDB 971168 D01 v03r01
Operation mode:	Refer to item 4.1
Limits:	ERP: GSM 850: 7W WCDMA Band V: 7W EIRP: PCS 1900: 2W WCDMA Band II: 2W
Test Setup:	
Test Procedure:	1. The transmitter output port was connected to the system simulator. 2. Set EUT at maximum power through system simulator. 3. Select lowest, middle, and highest channels for each band and different modulation. 4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.
Test Result:	PASS

6.1.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
System simulator	R&S	CMU200	111382	Sep. 20, 2019
RF cable (9kHz-40GHz)	TCT	RE-05	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-02	N/A	Sep. 20, 2019

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.1.3. Test data

Conducted Power Measurement Results:

Average Conducted Power (*Unit: dBm)						
Band	**GSM850**			**PCS 1900**		
Channel	128	190	251	512	661	810
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM	30.80	30.70	30.40	30.10	29.80	29.60
GPRS class8	30.74	30.66	30.42	29.55	29.25	29.62
GPRS class10	29.58	29.64	29.61	28.62	28.73	28.67
GPRS class11	28.68	28.74	28.61	27.74	27.80	27.64
GPRS class12	27.57	27.67	27.63	26.63	26.76	26.67

Average Conducted Power (*Unit: dBm)						
Band	**WCDMA Band V**			**WCDMA Band II**		
Channel	4132	4183	4233	9262	9400	9538
Frequency(MHz)	826.4	836.6	846.6	1852.4	1880.0	1907.6
WCDMA RMC 12.2K	23.95	23.20	23.98	21.72	21.04	21.54
HSDPA Subtest-1	23.89	23.35	23.90	21.80	21.05	21.55
HSDPA Subtest-2	23.19	23.31	23.26	20.94	21.07	21.03
HSDPA Subtest-3	23.13	23.26	23.20	20.91	21.03	20.97
HSDPA Subtest-4	23.07	23.24	23.19	20.84	21.02	20.95
HSUPA Subtest-1	22.83	22.96	22.86	20.36	20.61	20.35
HSUPA Subtest-2	22.73	22.86	22.78	20.50	20.63	20.55
HSUPA Subtest-3	22.68	22.49	22.46	20.46	20.26	20.23
HSUPA Subtest-4	22.29	22.43	22.34	20.02	20.20	20.11
HSUPA Subtest-5	22.20	22.27	22.25	19.95	20.04	20.02

6.2. Peak to Average Ratio

6.2.1. Test Specification

Test Requirement:	FCC part 24.232(d) ; FCC part 22.913;
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 4.1
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test Setup:	
Test Procedure:	1. The testing follows FCC KDB 971168 D01v03r01 Section 5.7.1. 2. The EUT was connected to spectrum analyzer and system simulator via a power divider. 3. Set EUT to transmit at maximum output power. 4. For GSM/EGPRS operating modes, signal gating is implemented on the spectrum analyzer by triggering from the system simulator. 5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.
Test Result:	PASS

6.2.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Spectrum Analyzer	R&S	FSU	200054	Sep. 20, 2019
RF cable (9kHz-40GHz)	TCT	RE-05	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-02	N/A	Sep. 20, 2019

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.2.3. Test Data

Cellular Band						
Mode	GSM850			GSM850 (GPRS class 8)		
Channel	128	190	251	128	190	251
Frequency (MHz)	824.2	836.6	848.8	824.2	836.6	848.8
Peak-to-Average Ratio (dB)	7.69	7.69	7.69	7.69	7.69	7.66

PCS Band						
Mode	GSM 1900			GSM 1900 (GPRS class 8)		
Channel	512	661	810	512	661	810
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	7.72	7.72	7.69	7.72	7.72	7.72

Cellular Band						
Mode	WCDMA Band V (RMC 12.2Kbps)			WCDMA Band II (RMC 12.2Kbps)		
Channel	4132	4183	4233	9262	9400	9538
Frequency (MHz)	826.4	836.6	846.6	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	3.01	2.79	2.85	3.04	3.04	2.98

Test plots as follows:

GSM 850

Peak-to-Average Ratio on Channel 128



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.67 dBm
Peak	29.35 dBm
Crest	7.68 dB
10 %	7.60 dB
1 %	7.63 dB
.1 %	7.69 dB
.01 %	7.72 dB

Date: 30.MAR.2019 10:23:36

Peak-to-Average Ratio on Channel 190



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.77 dBm
Peak	29.45 dBm
Crest	7.68 dB
10 %	7.60 dB
1 %	7.63 dB
.1 %	7.69 dB
.01 %	7.69 dB

Date: 30.MAR.2019 10:25:31

Peak-to-Average Ratio on Channel 251



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.78 dBm
Peak	29.46 dBm
Crest	7.68 dB
10 %	7.56 dB
1 %	7.66 dB
.1 %	7.69 dB
.01 %	7.69 dB

Date: 30.MAR.2019 10:26:00

Peak-to-Average Ratio on Channel 512



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.20 dBm
Peak	25.92 dBm
Crest	7.72 dB
10 %	7.60 dB
1 %	7.66 dB
.1 %	7.72 dB
.01 %	7.76 dB

Date: 30.MAR.2019 10:28:58

Peak-to-Average Ratio on Channel 661



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.10 dBm
Peak	25.81 dBm
Crest	7.71 dB
10 %	7.60 dB
1 %	7.66 dB
.1 %	7.72 dB
.01 %	7.76 dB

Date: 30.MAR.2019 10:30:05

Peak-to-Average Ratio on Channel 810



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.15 dBm
Peak	25.89 dBm
Crest	7.74 dB
10 %	7.60 dB
1 %	7.69 dB
.1 %	7.69 dB
.01 %	7.76 dB

Date: 30.MAR.2019 10:31:01

Peak-to-Average Ratio on Channel 128



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.46 dBm
Peak	29.14 dBm
Crest	7.68 dB
10 %	7.60 dB
1 %	7.63 dB
.1 %	7.69 dB
.01 %	7.69 dB

Date: 30.MAR.2019 10:39:34

Peak-to-Average Ratio on Channel 190



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.56 dBm
Peak	29.24 dBm
Crest	7.67 dB
10 %	7.56 dB
1 %	7.66 dB
.1 %	7.69 dB
.01 %	7.69 dB

Date: 30.MAR.2019 10:39:57

Peak-to-Average Ratio on Channel 251



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	21.60 dBm
Peak	29.32 dBm
Crest	7.71 dB
10 %	7.60 dB
1 %	7.66 dB
.1 %	7.66 dB
.01 %	7.66 dB

Date: 30.MAR.2019 10:40:31

Peak-to-Average Ratio on Channel 512



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.24 dBm
Peak	25.99 dBm
Crest	7.75 dB
10 %	7.60 dB
1 %	7.69 dB
.1 %	7.72 dB
.01 %	7.72 dB

Date: 30.MAR.2019 10:35:16

Peak-to-Average Ratio on Channel 661



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.10 dBm
Peak	25.88 dBm
Crest	7.79 dB
10 %	7.60 dB
1 %	7.66 dB
.1 %	7.72 dB
.01 %	7.76 dB

Date: 30.MAR.2019 10:34:50

Peak-to-Average Ratio on Channel 810



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.12 dBm
Peak	25.89 dBm
Crest	7.78 dB
10 %	7.60 dB
1 %	7.66 dB
.1 %	7.72 dB
.01 %	7.72 dB

Date: 30.MAR.2019 10:33:46

WCDMA Band V 12.2K

Peak-to-Average Ratio on Channel 4132



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	12.14 dBm
Peak	15.49 dBm
Crest	3.35 dB
10 %	1.73 dB
1 %	2.60 dB
.1 %	3.01 dB
.01 %	3.21 dB

Date: 30.MAR.2019 10:57:26

Peak-to-Average Ratio on Channel 4183



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	11.95 dBm
Peak	15.09 dBm
Crest	3.14 dB
10 %	1.67 dB
1 %	2.44 dB
.1 %	2.79 dB
.01 %	2.98 dB

Date: 30.MAR.2019 10:59:23

Peak-to-Average Ratio on Channel 4233



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	12.37 dBm
Peak	15.45 dBm
Crest	3.09 dB
10 %	1.70 dB
1 %	2.47 dB
.1 %	2.85 dB
.01 %	3.04 dB

Date: 30.MAR.2019 11:00:05

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

WCDMA Band II 12.2Kbps

Peak-to-Average Ratio on Channel 9262



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	19.23 dBm
Peak	22.68 dBm
Crest	3.45 dB
10 %	1.73 dB
1 %	2.60 dB
.1 %	3.04 dB
.01 %	3.27 dB

Date: 30.MAR.2019 10:46:04

Peak-to-Average Ratio on Channel 9400



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	19.14 dBm
Peak	22.57 dBm
Crest	3.43 dB
10 %	1.73 dB
1 %	2.56 dB
.1 %	3.04 dB
.01 %	3.27 dB

Date: 30.MAR.2019 10:46:54

Peak-to-Average Ratio on Channel 9538



Complementary Cumulative Distribution Function
NOF samples: 100000, Usable BW: 11.2MHz

	Trace 1
Mean	18.93 dBm
Peak	22.22 dBm
Crest	3.29 dB
10 %	1.73 dB
1 %	2.56 dB
.1 %	2.98 dB
.01 %	3.17 dB

Date: 30.MAR.2019 10:47:36

6.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement

6.3.1. Test Specification

Test Requirement:	FCC part 2.1049
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 4.1
Limit:	N/A
Test Setup:	
Test Procedure:	1. The testing follows FCC KDB 971168 D01v03r01 Section 4.2. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold. 5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Spectrum Analyzer	R&S	FSU	200054	Sep. 20, 2019
RF cable (9kHz-40GHz)	TCT	RE-05	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-02	N/A	Sep. 20, 2019

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.3.3. Test data

Cellular Band						
Mode	**GSM850**			**GSM 850 (GPRS)**		
Channel	**128**	**190**	**251**	**128**	**190**	**251**
Frequency (MHz)	**824.2**	**836.6**	**848.8**	**824.2**	**836.6**	**848.8**
99% OBW (kHz)	243.59	243.59	243.59	243.59	243.59	243.59
26dB BW (kHz)	323.72	318.91	315.71	317.31	323.72	323.72

Cellular Band						
Mode	**GSM1900**			**GSM 1900 (GPRS)**		
Channel	**512**	**661**	**810**	**512**	**661**	**810**
Frequency (MHz)	**1850.2**	**1880.0**	**1909.8**	**1850.2**	**1880.0**	**1909.8**
99% OBW (kHz)	245.19	246.79	245.19	245.19	245.19	243.59
26dB BW (kHz)	322.12	322.12	320.51	323.72	323.72	325.32

Cellular Band			
Mode	**WCDMA Band V (RMC 12.2Kbps)**		
Channel	**4132**	**4183**	**4233**
Frequency (MHz)	**826.4**	**836.6**	**846.6**
99% OBW (MHz)	4.17	4.18	4.17
26dB BW (MHz)	4.70	4.71	4.70

Cellular Band			
Mode	**WCDMA Band II (RMC 12.2Kbps)**		
Channel	**9262**	**9400**	**9538**
Frequency (MHz)	**1852.4**	**1880**	**1907.6**
99% OBW (MHz)	4.17	4.17	4.15
26dB BW (MHz)	4.70	4.68	4.68

Test plots as follows:

Band:	GSM 850	Test Mode:	GSM Link (GMSK)

26dB&99% Occupied Bandwidth Plot on Channel 128



Date: 22.APR.2019 20:33:57

26dB&99% Occupied Bandwidth Plot on Channel 190



Date: 22.APR.2019 20:35:29

26dB&99% Occupied Bandwidth Plot on Channel 251



Date: 22.APR.2019 20:37:20

Band:	GSM 1900	Test Mode:	GSM Link (GMSK)

26dB&99% Occupied Bandwidth Plot on Channel 512



Date: 30.MAR.2019 11:43:29

26dB&99% Occupied Bandwidth Plot on Channel 661



Date: 30.MAR.2019 11:44:56

26dB&99% Occupied Bandwidth Plot on Channel 810



Date: 30.MAR.2019 11:46:36

Band:	GPRS 850	Test Mode:	GPRS Class 8 Link (GMSK)

26dB&99% Occupied Bandwidth Plot on Channel 128



Date: 22.APR.2019 20:40:19

26dB&99% Occupied Bandwidth Plot on Channel 190



Date: 22.APR.2019 20:41:24

26dB&99% Occupied Bandwidth Plot on Channel 251



Date: 22.APR.2019 20:42:35

Band:	GPRS 1900	Test Mode:	GPRS Class 8 Link (GMSK)

26dB&99% Occupied Bandwidth Plot on Channel 512



26dB&99% Occupied Bandwidth Plot on Channel 661



26dB&99% Occupied Bandwidth Plot on Channel 810



Band:	WCDMA Band V	Test Mode:	RMC 12.2Kbps Link (QPSK)

26dB&99% Occupied Bandwidth Plot on Channel 4132



Date: 30.MAR.2019 11:08:59

26dB&99% Occupied Bandwidth Plot on Channel 4183



Date: 30.MAR.2019 11:13:33

26dB&99% Occupied Bandwidth Plot on Channel 4233



Date: 30.MAR.2019 11:11:22

Band:	WCDMA Band II	Test Mode:	RMC 12.2Kbps Link (QPSK)

26dB&99% Occupied Bandwidth Plot on Channel 9262



Date: 30.MAR.2019 11:18:21

26dB&99% Occupied Bandwidth Plot on Channel 9400



Date: 30.MAR.2019 11:19:50

26dB&99% Occupied Bandwidth Plot on Channel 9538



Date: 30.MAR.2019 11:21:37

6.4. Band Edge and Conducted Spurious Emission Measurement

6.4.1. Test Specification

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 4.1
Limit:	-13dBm
Test Setup:	
Test Procedure:	1. The testing follows FCC KDB 971168 D01v03r01 Section 6.0. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The band edges of low and high channels for the highest RF powers were measured. 5. The conducted spurious emission for the whole frequency range was taken. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts) = P(W) - [43 + 10log(P)] (dB) = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.
Test Result:	PASS

6.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Spectrum Analyzer	R&S	FSU	200054	Sep. 20, 2019
RF cable (9kHz-40GHz)	TCT	RE-05	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-02	N/A	Sep. 20, 2019

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.4.3. Test data

Test plots as follows:

Band:	GSM 850	Test Mode:	GSM Link (GMSK)

Lower Band Edge Plot on Channel 128



Date: 30.MAR.2019 14:40:51

Higher Band Edge Plot on Channel 251



Date: 30.MAR.2019 14:44:56

Band:	GSM 1900	Test Mode:	GSM Link (GMSK)

Lower Band Edge Plot on Channel 512



Date: 30.MAR.2019 14:55:58

Higher Band Edge Plot on Channel 810



Date: 30.MAR.2019 14:54:51

Band:	GPRS 850	Test Mode:	GPRS Class 8 Link (GMSK)

Lower Band Edge Plot on Channel 128



Date: 30.MAR.2019 14:48:54

Higher Band Edge Plot on Channel 251



Date: 30.MAR.2019 14:48:10

Band:	GPRS 1900	Test Mode:	GPRS Class 8 Link (GMSK)

Lower Band Edge Plot on Channel 512



Date: 30.MAR.2019 14:51:29

Higher Band Edge Plot on Channel 810



Date: 30.MAR.2019 14:53:14

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Band:	WCDMA Band V	Test Mode:	RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 4132



Date: 30.MAR.2019 15:02:06

Higher Band Edge Plot on Channel 4233



Date: 30.MAR.2019 15:02:59

Band:	WCDMA Band II	Test Mode:	RMC 12.2Kbps Link (QPSK)

Lower Band Edge Plot on Channel 9262



Date: 30.MAR.2019 14:59:07

Higher Band Edge Plot on Channel 9538



Date: 30.MAR.2019 15:00:20

Band:	GSM 850	Test Mode:	GSM Link (GMSK)

Conducted Spurious Emission on Channel 128



Date: 30.MAR.2019 15:30:15



Date: 30.MAR.2019 15:26:37

Conducted Spurious Emission on Channel 190



Date: 30.MAR.2019 15:29:51



Date: 30.MAR.2019 15:27:40

Conducted Spurious Emission on Channel 251



Date: 30.MAR.2019 15:29:15



Date: 30.MAR.2019 15:28:38

Band:	GSM 1900	Test Mode:	GSM Link (GMSK)

Conducted Spurious Emission on Channel 512



Date: 30.MAR.2019 15:32:38



Date: 30.MAR.2019 15:36:40

Conducted Spurious Emission on Channel 661



Date: 30.MAR.2019 15:33:09



Date: 30.MAR.2019 15:36:05

Conducted Spurious Emission on Channel 810



Date: 30.MAR.2019 15:33:49



Date: 30.MAR.2019 15:35:13

Band:	GPRS 850	Test Mode:	GPRS Class 8 Link (GMSK)

Conducted Spurious Emission on Channel 128



Date: 30.MAR.2019 15:21:20



Date: 30.MAR.2019 15:25:12

Conducted Spurious Emission on Channel 190



Date: 30.MAR.2019 15:21:59



Date: 30.MAR.2019 15:24:12

Conducted Spurious Emission on Channel 251



Date: 30.MAR.2019 15:22:32



Date: 30.MAR.2019 15:23:27

Band:	GPRS 1900	Test Mode:	GPRS Class 8 Link (GMSK)

Conducted Spurious Emission on Channel 512



Date: 30.MAR.2019 15:41:30



Date: 30.MAR.2019 15:38:23

Conducted Spurious Emission on Channel 661



Date: 30.MAR.2019 15:40:48



Date: 30.MAR.2019 15:39:02

Conducted Spurious Emission on Channel 810



Date: 30.MAR.2019 15:40:23



Date: 30.MAR.2019 15:39:45

Band:	WCDMA Band V	Test Mode:	RMC 12.2Kbps Link (QPSK)

Conducted Spurious Emission on Channel 4132



Date: 30.MAR.2019 15:06:56



Date: 30.MAR.2019 15:08:56

Conducted Spurious Emission on Channel 4183



Date: 30.MAR.2019 15:06:18



Date: 30.MAR.2019 15:10:00

Conducted Spurious Emission on Channel 4233



Date: 30.MAR.2019 15:05:09



Date: 30.MAR.2019 15:11:02

Band:	WCDMA Band II	Test Mode:	RMC 12.2Kbps Link (QPSK)

Conducted Spurious Emission on Channel 9262



Date: 30.MAR.2019 15:16:29



Date: 30.MAR.2019 15:15:23

Conducted Spurious Emission on Channel 9400



Date: 30.MAR.2019 15:17:10



Date: 30.MAR.2019 15:14:36

Conducted Spurious Emission on Channel 9538



Date: 30.MAR.2019 15:17:54



Date: 30.MAR.2019 15:13:55

6.5. Effective Radiated Power and Effective Isotropic Radiated Power Measurement

6.5.1. Test Specification

Test Requirement: FCC part 22.913(a) and FCC part 24.232(c)

Test Method: FCC KDB 971168 D01v03r01

Receiver Setup:

	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

Limit:

GSM850: 7W ERP
PCS1900: 2W EIRP
WCDMA Band V: 7W ERP
WCDMA Band II: 2W EIRP

Test Setup:

From 30MHz to 1GHz



Above 1GHz



Test Procedure:	1. The testing follows FCC KDB 971168 D01v03r01 Section 5.8. and ANSI / TIA-603-D-2010 Section 2.2.17. 2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01v03. 3. Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. 4. Replace the transmitter under test with a substitution antenna. The center of the antenna should be at the same location as the center of the antenna under test. 5. Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading. LOSS = Generator Output Power (dBm) – Analyzer reading (dBm) 6. Determine the effective radiated output power at each angular position from the readings in steps 3) and 5) using the following equation: ERP (dBm) = LVL (dBm) + LOSS (dB) 7. The maximum ERP is the maximum value determined in the preceding step. 8. Calculating ERP: ERP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBd) Antenna Gain (dBd) = Antenna Gain (dBi) - 2.15 EIRP = ERP – 2.15
Test results:	PASS

6.5.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Spectrum Analyzer	ROHDE&SCHWARZ	R&S	FSQ40	Sep. 20, 2019
Signal Generator	HP	83623B	3614A00396	Sep. 16, 2019
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 02, 2019
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Oct. 20, 2019
Broadband Antenna	Schwarzbeck	VULB9163	412	Sep. 02, 2019
Horn Antenna	Schwarzbeck	BBHA 9120D	1201	Oct. 20, 2019
Horn Antenna	A-INFO	LB-180400-KF	J211020657	Sep. 16, 2019
Dipole Antenna	TCT	TCT-RF	N/A	Sep. 20, 2019
Coax cable (9kHz-1GHz)	TCT	RE-low-01	N/A	Sep. 16, 2019
Coax cable (9kHz-40GHz)	TCT	RE-high-02	N/A	Sep. 16, 2019
Coax cable (9kHz-1GHz)	TCT	RE-low-03	N/A	Sep. 16, 2019
Coax cable (9kHz-40GHz)	TCT	RE-High-04	N/A	Sep. 16, 2019
Antenna Mast	Keleto	RE-AM	N/A	N/A
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.5.3. Test Data

Test Result of ERP

GSM850 (GSM) Radiated Power ERP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
824.2	H	7.58	21.66	29.24	0.84
836.6	H	7.91	21.54	29.45	0.88
848.8	H	8.03	21.46	29.49	0.89
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
824.2	H	7.24	21.66	28.90	0.78
836.6	H	7.63	21.54	29.17	0.83
848.8	H	7.96	21.46	29.42	0.87

GPRS 850 (1-solt) Radiated Power ERP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
824.2	H	6.95	21.66	28.61	0.73
836.6	H	7.04	21.54	28.58	0.72
848.8	H	7.56	21.46	29.02	0.80
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
824.2	H	6.87	21.66	28.53	0.71
836.6	H	6.93	21.54	28.47	0.70
848.8	H	7.14	21.46	28.60	0.72

***Note**: All GPRS slot have been tested, but only the worst GPRS 1-slot show in this test item.*

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
826.4	H	1.85	21.62	23.47	0.22
836.6	H	1.90	21.54	23.44	0.22
846.6	H	2.01	21.44	23.45	0.22
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
826.4	H	1.24	21.62	22.86	0.19
836.6	H	1.57	21.54	23.11	0.20
846.6	H	1.63	21.44	23.07	0.20

** ERP = LVL (dBm) + Correction Factor (dB) – 2.15*
Correction Factor= S.G. Power - Cable loss + Antenna Gain- SPA. Reading

Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1850.2	H	7.25	21.66	28.91	0.78
1880.0	H	7.61	21.54	29.15	0.82
1909.8	H	7.89	21.46	29.35	0.86
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1850.2	H	6.81	21.66	28.47	0.70
1880.0	H	6.99	21.54	28.53	0.71
1909.8	H	7.13	21.46	28.59	0.72

GPRS1900 (1-solt) Radiated Power EIRP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1850.2	H	7.02	21.66	28.68	0.74
1880.0	H	7.34	21.54	28.88	0.77
1909.8	H	7.58	21.46	29.04	0.80
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1850.2	H	6.79	21.66	28.45	0.70
1880.0	H	6.94	21.54	28.48	0.70
1909.8	H	7.08	21.46	28.54	0.71

***Note**: All GPRS slot have been tested, but only the worst GPRS 1-slot show in this test item*

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Horizontal Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1852.4	H	-0.59	21.62	21.03	0.13
1880.0	H	-0.84	21.54	20.70	0.12
1907.6	H	-0.16	21.48	21.32	0.14
Vertical Polarization (Antenna Pol.)					
Frequency (MHz)	**(EUT Pol.)**	**LVL (dBm)**	**Correction Factor (dB)**	**ERP (dBm)**	**ERP (W)**
1852.4	H	-0.86	21.62	20.76	0.12
1880.0	H	-0.49	21.54	21.05	0.13
1907.6	H	-0.33	21.48	21.15	0.13

** EIRP = LVL (dBm) + Correction Factor (dB)*
Correction Factor= S.G. Power - Cable loss + Substitution Antenna Gain- SPA. Reading

6.6. Field Strength of Spurious Radiation Measurement

6.6.1. Test Specification

Test Requirement:	FCC part 22.917(a) and FCC part 24.238(a)
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 4.1
Limit:	-13dBm
Test setup:	For 30MHz~1GHz  Above 1GHz 
Test Procedure:	1. The testing follows FCC KDB 971168 D01v03r01 Section 6 and ANSI / TIA-603-D-2010 Section 2.2.12. 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower. 4. The table was rotated 360 degrees to determine the position of the highest spurious emission. 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations. 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of

	maximum spurious emission. 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission. 9. Taking the record of output power at antenna port. 10. Repeat step 7 to step 8 for another polarization. 11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain 12. ERP (dBm) = EIRP - 2.15 13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts) = P(W) - [43 + 10log(P)] (dB) = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.
Test results:	PASS
Remark:	All modulations have been tested, but only the worst modulation show in this test item.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

6.6.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Spectrum Analyzer	ROHDE&SCHWARZ	R&S	FSQ40	Sep. 20, 2019
Signal Generator	HP	83623B	3614A00396	Sep. 16, 2019
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 02, 2019
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Oct. 20, 2019
Broadband Antenna	Schwarzbeck	VULB9163	412	Sep. 02, 2019
Horn Antenna	Schwarzbeck	BBHA 9120D	1201	Oct. 20, 2019
Horn Antenna	A-INFO	LB-180400-KF	J211020657	Sep. 16, 2019
Dipole Antenna	TCT	TCT-RF	N/A	Sep. 20, 2019
Coax cable (9kHz-1GHz)	TCT	RE-low-01	N/A	Sep. 16, 2019
Coax cable (9kHz-40GHz)	TCT	RE-high-02	N/A	Sep. 16, 2019
Coax cable (9kHz-1GHz)	TCT	RE-low-03	N/A	Sep. 16, 2019
Coax cable (9kHz-40GHz)	TCT	RE-High-04	N/A	Sep. 16, 2019
Antenna Mast	Keleto	RE-AM	N/A	N/A
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.6.3. Test Data

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: *1. Emission Level=Reading+ Cable loss+Antenna factor-Amp factor*

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Band	GSM 850		Test channel:	Lowest
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-33.56	-13.00	PASS
2472.60	V	-38.28		
3296.80	V	-52.30		
1648.40	Horizontal	-31.89		
2472.60	H	-37.64		
3296.80	H	-50.93		
Band	GSM 850		Test channel:	Middle
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-32.14	-13.00	PASS
2509.80	V	-43.85		
3346.40	V	-51.03		
1673.20	Horizontal	-30.58		
2509.80	H	-38.47		
3346.40	H	-51.69		
Band	GSM 850		Test channel:	Highest
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-34.23	-13.00	PASS
2546.40	V	-43.77		
3395.20	V	-51.84		
1697.60	Horizontal	-30.10		
2546.40	H	-39.75		
3395.20	H	-53.43		

Band	PCS 1900		Test channel:	Lowest
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-38.69	-13.00	PASS
5550.60	V	-46.24		
7400.80	V	-53.71		
3700.40	Horizontal	-35.53		
5550.60	H	-41.17		
7400.80	H	-51.09		
Test mode:	PCS 1900		Test channel:	Middle
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-38.18	-13.00	PASS
5640.00	V	-48.46		
7520.00	V	-46.75		
3760.00	Horizontal	-35.52		
5640.00	H	-47.01		
7520.00	H	-52.83		
Test mode:	PCS 1900		Test channel:	Highest
Test mode:			Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-36.23	-13.00	PASS
5729.40	V	-45.89		
7639.20	V	-52.37		
3819.60	Horizontal	-34.92		
5729.40	H	-41.55		
7639.20	H	-52.40		

Band	WCDMA Band V		Test channel:	Lowest
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1652.80	Vertical	-43.05	-13.00	PASS
2479.20	V	-52.89		
3305.60	V	-51.42		
1652.80	Horizontal	-41.97		
2479.20	H	-51.68		
3305.60	H	-53.71		
Test mode:	WCDMA Band V		Test channel:	Middle
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-42.53	-13.00	PASS
2509.80	V	-51.17		
3346.40	V	-51.23		
1673.20	Horizontal	-40.49		
2509.80	H	-54.67		
3346.40	H	-52.99		
Test mode:	WCDMA Band V		Test channel:	Highest
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1693.20	Vertical	-45.05	-13.00	PASS
2539.80	V	-52.22		
3386.40	V	-57.59		
1693.20	Horizontal	-42.84		
2539.80	H	-52.43		
3386.40	H	-55.61		

Band	WCDMA Band II		Test channel:	Lowest
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3704.80	Vertical	-41.29	-13.00	PASS
5557.20	V	-53.50		
7409.60	V	-57.18		
3704.80	Horizontal	-43.69		
5557.20	H	-51.94		
7409.60	H	-56.03		
Test mode:	WCDMA Band II		Test channel:	Middle
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-43.87	-13.00	PASS
5640.00	V	-52.29		
7520.00	V	-55.44		
3760.00	Horizontal	-44.72		
5640.00	H	-50.59		
7520.00	H	-58.13		
Test mode:	WCDMA Band II		Test channel:	Highest
Test mode:	RMC 12.2Kbps Link (QPSK)		Temperature :	25°C
			Relative Humidity:	56%
Note:	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.			
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3815.20	Vertical	-45.51	-13.00	PASS
5722.80	V	-55.40		
7630.40	V	-58.36		
3815.20	Horizontal	-42.18		
5722.80	H	-51.23		
7630.40	H	-59.09		

6.7. Frequency Stability Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part 2.1055 ; FCC Part 22.355 ; FCC Part 24.235
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 4.1
Limit:	FCC Part 22.355 : ±2.5 ppm FCC Part 24.235 : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
Test Setup:	
Test Procedure:	**Test Procedures for Temperature Variation** 1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0. 2. The EUT was set up in the thermal chamber and connected with the system simulator. 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute. 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute. **Test Procedures for Voltage Variation** 1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0. 2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator. 3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT. 4. The variation in frequency was measured for the worst case.
Test Result:	PASS
Remark:	All three channels of all modulations have been tested, but only the worst channel and the worst modulation

	show in this test item.

6.7.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
System simulator	R&S	CMU200	111382	Sep. 20, 2019
Programable tempratuce and humidity chamber	JQ	JQ-2000	N/A	Sep. 16, 2019
DC power supply	Kingrang	KR3005K	N/A	Sep. 16, 2019
RF cable (9kHz-40GHz)	TCT	RE-04	N/A	Sep. 20, 2019
Antenna Connector	TCT	RFC-03	N/A	Sep. 20, 2019

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.7.3. Test Data

Test Result of Temperature Variation

Band :	GSM 850	Channel:	190
Limit (ppm) :	2.5	Frequency:	836.6MHz
Temperature (°C)	Deviation (ppm)		Result
50	0.012		PASS
40	0.014		
30	0.013		
20	0.009		
10	0.013		
0	0.019		
-10	0.008		
-20	0.012		
-30	0.009		

Band :	GSM 1900	Channel:	661
Limit (ppm) :	*Note*	Frequency:	1880MHz
Temperature (°C)	Deviation (ppm)		Result
50	0.020		PASS
40	0.019		
30	0.016		
20	0.017		
10	0.020		
0	0.022		
-10	0.018		
-20	0.016		
-30	0.021		

Note: *The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.*

Band :	GPRS 850	Channel:	190
Limit (ppm) :	2.5	Frequency:	836.6MHz

Temperature (°C)	Deviation (ppm)	Result
50	0.015	PASS
40	0.013	
30	0.011	
20	0.007	
10	0.012	
0	0.014	
-10	0.009	
-20	0.008	
-30	0.011	

Band :	GPRS 1900	Channel:	661
Limit (ppm) :	*Note*	Frequency:	1880MHz

Temperature (°C)	Deviation (ppm)	Result
50	0.024	PASS
40	0.022	
30	0.019	
20	0.020	
10	0.021	
0	0.022	
-10	0.019	
-20	0.017	
-30	0.021	

Note: *The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.*

Band :	WCDMA Band V	Channel:	4183
Limit (ppm) :	2.5ppm	Frequency:	836.6MHz

Temperature (°C)	RMC 12.2Kbps Deviation (ppm)	Result
50	0.017	PASS
40	0.014	
30	0.007	
20	0.009	
10	0.012	
0	0.011	
-10	0.018	
-20	0.012	
-30	0.010	

Band :	WCDMA Band II	Channel:	9400
Limit (ppm) :	*Note*	Frequency:	1880MHz

Temperature (°C)	RMC 12.2Kbps Deviation (ppm)	Result
50	0.014	PASS
40	0.019	
30	0.015	
20	0.016	
10	0.017	
0	0.021	
-10	0.015	
-20	0.018	
-30	0.019	

Note: *The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.*

Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH190	GSM	4.2	+0.011	2.5	PASS
		3.7	+0.009		
		BEP	+0.012		
GSM 850 CH190	GPRS Class 8	4.2	+0.020	2.5	
		3.7	+0.021		
		BEP	+0.017		
GSM 1900 CH661	GSM	4.2	+0.020	(Note 3.)	
		3.7	+0.023		
		BEP	+0.018		
GSM 1900 CH661	GPRS Class 8	4.2	+0.007	(Note 3.)	
		3.7	+0.013		
		BEP	+0.021		
WCDMA Band V CH4182	RMC 12.2Kbps	4.2	-0.020	2.5	
		3.7	-0.018		
		BEP	-0.019		
WCDMA Band II CH9400	RMC 12.2Kbps	4.2	-0.013	(Note 3.)	
		3.7	-0.016		
		BEP	-0.018		

Note:

1. *Normal Voltage = 3.7V.*
2. *Battery End Point (BEP) = 3.40 V.*
3. *The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.*

Appendix A: Photographs of Test Setup

Refer to test report TCT190212E003

Appendix B: Photographs of EUT

Refer to test report TCT190212E003

********END OF REPORT********