

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2



CFR Title 47 FCC Parts

1.1307, 1.1310, 2.1091

RF Exposure Exhibit

Prepared for RSAE Labs, Inc.

Product Name: TSU-1

Hardware Version: 03-2003-01

Prepared by Yunus Faziloglu Sr. Wireless Engineer	Approved by Ahmed Ait Ahmed EMC Manager
	
Issue Date: Jan 15, 2025	Issue Number: 2



This test result relates only to the described test object.

This document shall not be reproduced, except in full, without the written approval of Bureau Veritas Test Lab.

Customer must not use this test report as the product certification of each accreditation body or each national organization.

The test is traceable to national standard or related international standard

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2

Contents

- 1 Device Under Test3
- 2 Test Laboratory Information4
- 3 RF Exposure Limit5
- 4 RF Exposure – MPE Evaluation6
- 5 Conclusion6

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2

1 Device Under Test

1.1 Product Information

Project Number:	EY0475-1	
Applicant Information:	RSAE Labs, Inc.	
	1002 Arthur Drive Suite 200, Lynn Haven, FL 32444	
Product Marketing Name:	TSU-1	
Hardware Version	03-2003-01	
Additional Versions	Product Marketing Name	Hardware Version Identification Number
	RSU-4	03-2002-01
	RSU-4	03-2002-02
	RSU-4	03-2002-03
	RSU-4	03-2002-04
	RSU-4	03-2002-05
	TSU-1	03-2003-01
	TSU-1	03-2003-02
	TSU-1	03-2003-03
	TSU-1	03-2003-04
	TSU-1	03-2003-05
	TSU-1	03-2003-06
	Version variants are for marketing purposes only. All versions are electrically identical to the tested version indicated in bold above.	
Separation Distance:	20cm	
Exposure Category of DUT:	Mobile	
Multiple Simultaneous RF Sources:	No	
Type of Evaluation:	MPE Calculation	
Evaluation Method:	447498 D01 General RF Exposure Guidance v06	
Deviations from Standard:	None	

1.2 Technical Information

Radio Description	2.4GHz 802.15.4
FCC ID:	2ASIM-TSU1
Exposure Category of Transmitter:	Mobile
Maximum Conducted Output Power (mW):	2.33mW (Average)
Maximum Tune-up Tolerance (dB):	N/A
Maximum Antenna Gain (dBi):	0.23dBi Peak

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2

2 Test Laboratory Information

Location of Test Lab:	One Distribution Center Circle #1 Littleton, MA 01460 (978) 486-8880
Key Contact:	Yunus Faziloglu Yunus.faziloglu@bureauveritas.com
Laboratory Accreditations:	BUREAU VERITAS CONSUMER PRODUCTS SERVICES, INC is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
ISO/IEC 17025:2017:	1627-01
FCC Test Site Number:	US1028

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2

3 RF Exposure Limit:

According to CFR Title 47 FCC section 1.1310, the criteria listed in the following table shall be used to evaluate Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

TABLE 1 TO § 1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Bureau Veritas Consumer Product Services, Inc.	Test Report Number:
One Distribution Center Circle #1, Littleton, MA 01460	EY0475-1-3 Issue 2

4 RF Exposure – MPE Evaluation

<u>Prediction of MPE limit at a given distance</u>				
Equation from page 18 of OET Bulletin 65, Edition 97-01				
$S = \frac{PG}{4\pi R^2}$				
where:	S = power density			
	P = power input to the antenna			
	G = power gain of the antenna in the direction of interest relative to an isotropic radiator			
	R = distance to the center of radiation of the antenna			
Maximum peak output power at the antenna terminal:	3.67	(dBm)		
Maximum peak output power at the antenna terminal:	2.33	(mW)		
Antenna gain(typical):	0.23	(dBi)		
Maximum antenna gain:	1.05	(numeric)		
Prediction distance:	20	(cm)		
Prediction frequency:	2405	(MHz)		
MPE limit for uncontrolled exposure at prediction frequency:	1	(mW/cm^2)		
Power density at prediction frequency:	0.000488	(mW/cm^2)		

5 Conclusion

EUT complies with FCC section 1.1310 MPE limits for general population as a mobile device.

Document Revisions

Issue No.	Summary of Changes	Date Issued	Prepared by	Approved by
1	Original Release	Nov 12, 2024	YF	AA
2	Updated applicant address	Jan 15, 2025	YF	AA

End of Report