

FCC ID: 2ASKH-DSI01

Test Requirement

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b), Limits for Maximum Permissible Exposure (MPE),

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW, **G** = gain of antenna in linear scale;

Pi = 3.1416, **R** = distance between observation point and center of the radiator in cm



Assessment Result

☒ **Passed**

☐ **Not Applicable**

BLE:

Frequency	Reading result(dBμV/m)	PK Output Power (dBm)	Maximum Tune-up Power(dBm)	Max Tune Up Power(mW)	Power Density (mW/cm2)	Limit (mW/cm2)	Result
GFSK 1M 2440MHz	90.56	-4.64	-4.5	0.355	0.000094	1.0000	Pass

Antenna Gain:1.23dBi

Note: PK Output Power (dBm)= Reading result(dBμV/m)-95.2

Reading result see the test report UNIA26070814ER-61.

Note: The exposure evaluation safety distance is 20cm.

-----The End-----