
FCC Test Report

Report No.: AGC00319251002FR01

FCC ID : 2ASNSMB4

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : CB Radio

BRAND NAME : RETEVIS

MODEL NAME : MB4

APPLICANT : Shenzhen Retevis Technology Co., Ltd.

DATE OF ISSUE : Dec. 16, 2025

STANDARD(S) : FCC Part 95 Subpart D

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 16, 2025	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	7
2.3 Related Submittal(S) / Grant (S)	8
2.4 Test Methodology	8
2.5 Calculation of Emission Indicators	8
2.6 Statement-Compliance To §95.977	8
2.7 Special Accessories	8
2.8 Equipment Modifications	8
3. Test Environment	9
3.1 Address of The Test Laboratory	9
3.2 Test Facility	9
3.3 Environmental Conditions	10
3.4 Measurement Uncertainty	10
3.5 List of Equipment Used	11
4. System Test Configuration.....	12
4.1 EUT Configuration	12
4.2 EUT Exercise.....	12
4.3 Configuration of Tested System	12
4.4 Equipment Used in Tested System.....	12
4.5 Summary of Test Results	13
5. Description of Test Modes	14
6. Frequency Stability	15
6.1 Provisions Applicable	15
6.2 Measurement Procedure.....	15
6.3 Measurement Setup	15
6.4 Measurement Result	16
7. 26dB Emission Bandwidth and 99% Occupied Bandwidth	18
7.1 Provisions Applicable	18
7.2 Measurement Procedure.....	18
7.3 Measurement Setup	18
7.4 Measurement Result	19
8. Radiated Spurious Emission and Emission Mask.....	23
8.1 Provisions Applicable	23
8.2 Measurement Procedure.....	23
8.3 Measurement Setup	24
8.4 Measurement Result	25
8.5 Emission Mask Measurement Part	50
9. Maximum Transmitter Power	53

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


9.1 Provisions Applicable	53
9.2 Measurement Procedure.....	53
9.3 Measurement Setup	53
9.4 Measurement Result	54
10. Spurious Emission on Antenna Port	58
10.1 Provisions Applicable	58
10.2 Measurement Procedure.....	58
10.3 Measurement Setup	58
10.4 Measurement Result	59
11. Modulation Characteristics	67
11.1 Provisions Applicable.....	67
11.2 Measurement Procedure.....	67
11.3 Measurement Setup	68
11.4 Measurement Result	69
Appendix I: Photographs of Test Setup.....	73
Appendix II: Photographs of Test EUT	73

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

1. General Information

Applicant	Shenzhen Retevis Technology Co., Ltd.
Address	7/F, 13-C, Zhonghaixin Science & Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China
Manufacturer	Shenzhen Retevis Technology Co., Ltd.
Address	7/F, 13-C, Zhonghaixin Science & Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China
Factory	N/A
Address	N/A
Product Designation	CB Radio
Brand Name	RETEVIS
Test Model	MB4
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Oct. 29, 2025
Date of Test	Oct. 29, 2025~Dec. 16, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-CBRS-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By		
	Bibo Zhang (Project Engineer)	Dec. 16, 2025
Reviewed By		
	Jack Gui (Reviewer)	Dec. 16, 2025
Approved By		
	Angela Li (Authorized Officer)	Dec. 16, 2025

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2. Product Information

2.1 Product Technical Description

Equipment Type	Citizens' Band (CB) Radio	
Communication Type	Voice / Tone only	
Operation Frequency Range	26.965MHz-27.405MHz	
Hardware Version	PA802ZA	
Software Version	V1.0	
Modulation Type	AM/FM	
Channel Separation	10kHz	
Emission Designator	8K00A3E/8K00F3E	
Number of Channels:	40 Channels	
Rated Output Power	4W(It was fixed by the manufacturer, any individual can't arbitrarily change it)	
Maximum Transmitter Power	AM: 35.692dBm-DC 12V	FM: 35.667dBm-DC 12V
	AM: 35.718dBm-DC 24V	FM: 35.695dBm-DC 24V
Antenna Designation	Detachable	
Antenna Gain	0dBi (Typical), 3dBi (Max)	
Frequency Tolerance	1.094ppm	
Power Supply	DC 12V/24V	

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.2 Test Frequency List

According to ANSI C63.26 section 5.1.2.1:

Measurements of transmitters shall be performed and, if required, reported for each frequency band in which the EUT can be operated with the device transmitting at the number of frequencies in each band specified in Table 2.

Frequency range Over which EUT operates	Number of Frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

Operation Frequency Each of Channel			
CBRS		CBRS	
Channel	Frequency	Channel	Frequency
1	26.965 MHz	21	27.215 MHz
2	26.975 MHz	22	27.225 MHz
3	26.985 MHz	23	27.255 MHz
4	27.005 MHz	24	27.235 MHz
5	27.015 MHz	25	27.245 MHz
6	27.025 MHz	26	27.265 MHz
7	27.035 MHz	27	27.275 MHz
8	27.055 MHz	28	27.285 MHz
9	27.065 MHz	29	27.295 MHz
10	27.075 MHz	30	27.305 MHz
11	27.085 MHz	31	27.315 MHz
12	27.105 MHz	32	27.325 MHz
13	27.115 MHz	33	27.335 MHz
14	27.125 MHz	34	27.345 MHz
15	27.135 MHz	35	27.355 MHz
16	27.155 MHz	36	27.365 MHz
17	27.165 MHz	37	27.375 MHz
18	27.175 MHz	38	27.385 MHz
19	27.185 MHz	39	27.395 MHz
20	27.205 MHz	40	27.405 MHz

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2ASNSMB4**, filing to comply with Part 2, Part 95 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 95	Personal Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
4	ANSI EIA/TIA 382-A-1989	Minimum standards – Citizens band radio service amplitude modulated (AM) transceivers operating in the 27MHz band.

2.5 Calculation of Emission Indicators

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For AM Mode (Channel Spacing: 10kHz)

Emission Designator 8K00A3E

Bn = 2M, M may vary between 4000 and 10000 depending on the quality desired.

Speech and music, M = 4000, Bandwidth: 8000 Hz= 8 kHz

A3E portion of the designator represents an AM voice transmission.

Therefore, the entire designator for 10 kHz channel spacing AM mode is 8K00A3E.

For FM Mode (Channel Spacing: 10kHz)

Emission Designator 8K00F3E

Bn = 2M, M may vary between 4000 and 10000 depending on the quality desired.

Speech and music, M = 4000, Bandwidth: 8000 Hz= 8 kHz

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 10 kHz channel spacing FM mode is 8K00F3E.

2.6 Statement-Compliance To §95.977

§95.977 CBRS tone transmissions.

In addition to the tones permitted under §95.377, CBRS transmitter types may be designed to transmit brief tones to indicate the beginning or end of a transmission.

This device is capable of transmitting a brief (less than one second) audio tone, “Roger Beep”, when the PTT button is released on the microphone indicating end of transmission. This function is user selectable and complies with the requirements of §95.377. See User’s Manual .

2.7 Special Accessories

Not available for this EUT intended for grant.

2.8 Equipment Modifications

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions
Temperature range (°C)	15 - 35	-30 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC12V	LV: DC 10.8V/HV:DC 15.6V
	DC24V	LV: DC 21.6V/HV:DC 31.2V

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.5 List of Equipment Used

● RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-ER-E086	Spectrum Analyzer	KEYSIGHT	N9020A	MY53300860	2025-05-08	2026-05-07
☒	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2025-05-08	2026-05-07
☒	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2024-07-24	2026-07-23
☒	AGC-EM-A007	30dB Attenuator	Weinachel	58-30-33	ML030	2025-05-31	2027-05-30
☒	AGC-EM-E040	Directional coupler	Werlatone	C5571-10	99463	2024-02-01	2026-01-31
☒	--	RF Connection Cable	N/A	1#	N/A	Each time	N/A
☒	--	RF Connection Cable	N/A	2#	N/A	Each time	N/A

● Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-E116	Test Receiver	R&S	ESCI	100034	2025-05-08	2026-05-07
☒	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
☒	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2025-01-15	2027-01-14
☒	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2025-05-16	2027-05-15
☒	AGC-EM-A136	Band Pass Filter	SHWHPH	50S	N/A	N/A	N/A

● Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
☒	AGC-EM-S011	RSE Test System	Tonscend	TS ⁺ Ver2.1(JS36-RSE)	4.0.0.0

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4. System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☒ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Load Antenna	HG-E10	Amphenol	Terminator DC -3G 50W	--
2	Bluetooth Speaker	SONY	SRS-XB01	DC5V/0.5A,AUX in, micro B	
3	DC 12V Battery	FengFan	N/A	N/A	

☒ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Hand microphone	N/A	N/A	N/A	0.8m Unshielded

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§ 95.967& 2.1046(a)	Maximum Transmitter Power	Pass
2	§95.975& 2.1047(a) (b)	Modulation Limit	Pass
3	§95.975& 2.1047(a)	Audio Frequency Response	Pass
4	§95.973& 2.1049	Emission Bandwidth	Pass
5	§95.979& 2.1049	Emission Mask	Pass
6	§95.965& 2.1055(a) (1)	Frequency Stability	Pass
7	§95.979& 2.1051	Spurious Emission on Antenna Port	Pass
8	§95.979& 2.1053	Radiated Spurious Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5. Description of Test Modes

The EUT (**CB Radio**) has been tested under normal operating condition. (CBRS TX) are chosen for testing at each channel separation.

No.	Test Mode Description	Channel Separation
1	CBRS AM TX Channel 1	10.0 kHz
2	CBRS AM TX Channel 20	10.0 kHz
3	CBRS AM TX Channel 40	10.0 kHz
4	CBRS FM TX Channel 1	10.0 kHz
5	CBRS FM TX Channel 20	10.0 kHz
6	CBRS FM TX Channel 40	10.0 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

6. Frequency Stability

6.1 Provisions Applicable

Standard Applicable [Part 95.963] The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

- The carrier frequency of each CBRS transmitter type must be designed such that the transmit carrier frequency (or in the case of SSB transmissions, the reference frequency) remains within 50 ppm

6.2 Measurement Procedure


6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50°C. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C. Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT should be powered by the normal operating voltage.
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6.4 Measurement Result

10 kHz Channel Separation, AM modulation, Assigned Frequency For CBRS						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		26.965MHz	27.205MHz	27.405MHz		
12.0	-30	0.974	0.653	0.713	50	Pass
	-20	0.507	0.727	0.903		
	-10	0.863	0.991	0.509		
	0	0.772	0.538	0.949		
	10	0.509	0.695	0.919		
	20	1.058	0.610	0.989		
	30	0.811	0.530	0.690		
	40	0.823	0.788	1.064		
	50	1.007	0.761	0.787		
15.6	20	1.059	0.630	0.544		
10.8	20	0.732	1.063	0.519		

10 kHz Channel Separation, FM modulation, Assigned Frequency For CBRS						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		26.965MHz	27.205MHz	27.405MHz		
12.0	-30	0.880	0.951	0.557	50	Pass
	-20	0.597	0.843	0.652		
	-10	1.051	0.515	1.086		
	0	0.885	0.960	0.893		
	10	0.736	0.976	0.532		
	20	1.050	1.094	0.875		
	30	0.925	1.002	0.853		
	40	0.786	0.791	0.850		
	50	0.645	0.890	0.938		
15.6	20	0.795	0.579	0.829		
10.8	20	0.717	0.822	1.036		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

10 kHz Channel Separation, AM modulation, Assigned Frequency For CBRS						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		26.965MHz	27.205MHz	27.405MHz		
24.0	-30	0.961	0.802	1.079	50	Pass
	-20	0.675	1.083	0.956		
	-10	0.722	0.837	0.535		
	0	0.963	0.523	1.075		
	10	1.092	0.517	0.598		
	20	0.984	0.691	0.964		
	30	0.653	0.914	0.563		
	40	0.830	0.873	0.532		
	50	1.002	0.693	0.758		
31.2	20	0.628	0.875	0.775		
21.6	20	0.634	0.993	0.636		

10 kHz Channel Separation, FM modulation, Assigned Frequency For CBRS						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		26.965MHz	27.205MHz	27.405MHz		
24.0	-30	0.644	0.963	0.526	50	Pass
	-20	0.514	1.028	0.985		
	-10	0.801	0.547	0.758		
	0	0.732	0.635	0.684		
	10	0.811	0.549	0.898		
	20	0.767	0.596	1.016		
	30	0.848	0.580	0.622		
	40	1.040	0.923	0.704		
	50	1.055	0.757	0.524		
31.2	20	0.757	1.003	1.026		
21.6	20	0.954	0.547	0.831		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7. 26dB Emission Bandwidth and 99% Occupied Bandwidth

7.1 Provisions Applicable


According to standard FCC Part 95.973, FCC Part 2.1049 reference is as follows: Each CBRS transmitter type must be designed such that the occupied bandwidth does not exceed the authorized bandwidth for the emission type under test.

- a) AM or FM modulation: the authorized bandwidth for emission type A3E and F3E is 8 kHz.
- b) SSB modulation: the authorized bandwidth for emission types J3E, R3E, and H3E is 4 kHz.

7.2 Measurement Procedure

1. Connect the equipment as illustrated
2. The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB
3. greater than that necessary to produce 50% of rated system deviation.
4. Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).
5. Spectrum set as follow:
6. Centre frequency = the nominal EUT channel center frequency,
7. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products
8. including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient)
9. RBW = 1% to 5% of the anticipated OBW, VBW $\geq 3 \times \text{RBW}$, Sweep = auto, Detector function = peak,
10. Trace = max hold
11. Set 99% Occupied Bandwidth and 26dB Bandwidth
12. Measure and record the results in the test report.

7.3 Measurement Setup




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7.4 Measurement Result

- For 12V System:

Emission Bandwidth Measurement Result-CBRS				
Operating Frequency (MHz)	10 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
26.965	5.180	5.284	8.0	Pass
27.205	5.181	5.283	8.0	Pass
27.405	5.181	5.281	8.0	Pass


Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Emission Bandwidth Measurement Result-CBRS				
Operating Frequency (MHz)	10 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
26.965 MHz	5.196	10.11	8.0	Pass
27.205 MHz	5.196	10.11	8.0	Pass
27.405 MHz	5.196	10.11	8.0	Pass

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

- For 24V System:

Emission Bandwidth Measurement Result-CBRs				
Operating Frequency (MHz)	10 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
26.965	5.178	5.283	8.0	Pass
27.205	5.182	5.283	8.0	Pass
27.405	5.181	5.280	8.0	Pass


Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Emission Bandwidth Measurement Result-CBRS				
Operating Frequency (MHz)	10 kHz Channel Separation			
	Occupied Bandwidth (kHz)	Emission Bandwidth (kHz)	Limits (kHz)	Result
26.965 MHz	5.196	10.11	8.0	Pass
27.205 MHz	5.197	10.11	8.0	Pass
27.405 MHz	5.197	10.12	8.0	Pass

Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. Radiated Spurious Emission and Emission Mask

8.1 Provisions Applicable

According to the standard FCC Part 95.979(a), the requirements of FCC Part 2.1053 are as follows:

Each GMRS transmitter type must be designed to comply with the applicable unwanted emissions limits in this section.

- Emission masks. Emission masks applicable to transmitting equipment in the GMRS are defined by the requirements in the following table. The numbers in the attenuation requirements column refer to rule paragraph numbers under paragraph (b) of this section.

Emission Types	Attenuation Requirements
A3E, F3E	(1), (3), (5), (6)
H3E, J3E, R3E	(2), (4), (5), (6)

- 1) 25 dB (decibels) in the frequency band 4 kHz to 8 kHz removed from the channel center frequency;
- 2) 25 dB in the frequency band 2 kHz to 6 kHz removed from the channel center frequency;
- 3) 35 dB in the frequency band 8 kHz to 20 kHz removed from the channel center frequency;
- 4) 35 dB in the frequency band 6 kHz to 10 kHz removed from the channel center frequency;
- 5) $53 + 10 \log(P)$ dB in any frequency band removed from the channel center frequency by more than 250% of the authorized bandwidth.
- 6) 60 dB in any frequency band centered on a harmonic (i.e., an integer multiple of two or more times) of the carrier frequency.

8.2 Measurement Procedure

- 1) EUT was placed on a 0.8 or 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- 2) A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3) The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- 4) The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.


- 5) A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test
- 6) The measurement results are obtained as described below: $Power(EIRP) = P_{Mea} - P_{Ag} - P_{cl} - G_a$ The measurement results are amend as described below: $Power(EIRP) = P_{Mea} - P_{cl} - G_a$
- 7) This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 8) ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dBi$.
- 9) Test the EUT in the lowest channel, the middle channel the Highest channel

8.3 Measurement Setup

Radiated Emissions Below 30MHz Test Setup



Radiated Emissions 30MHz-1000MHz Test Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8.4 Measurement Result

- The Unwanted spurious emissions limits are as follows:

Attenuation Requirement Results	Reference limit
At least $53+10*\log(P) = 53+10\log(4W) = 59.02$ (dB)	Limit=P(dBm)- Preliminary calculation=-23dBm

- The Harmonic emissions spurious limits are as follows:

The maximum power of the measured fundamental frequency drops by at least 60dB

- For 12V System:

Test Mode	Measuring Center frequency (MHz)	Maximum Power (dBm)	Reference limit (dBm)
AM	26.965	35.663	-24.34
	27.205	35.668	-24.33
	27.405	35.692	-24.31
FM	26.965	35.649	-24.35
	27.205	35.644	-24.36
	27.405	35.667	-24.33

- For 24V System:

Test Mode	Measuring Center frequency (MHz)	Maximum Power (dBm)	Reference limit (dBm)
AM	26.965	35.708	-24.29
	27.205	35.685	-24.32
	27.405	35.718	-24.28
FM	26.965	35.695	-24.31
	27.205	35.682	-24.32
	27.405	35.695	-24.31

There will be accuracy errors when the radiation spurious software reads the harmonic frequency points, which are in correspondence with the harmonic frequency points given by the reference limit. Please ignore them.

- The Radiated Spurious Measurement Parameters are as Follows:

Note 1: Factor=Antenna Factor + Cable loss. (Below 1GHz)

Note 2: Factor=Antenna Factor+ Cable loss -Pre-amplifier. (Above 1 GHz)

Note 3: Margin=Limit- Level

Note 4: Unwanted spurious signals in the 9kHz-30MHz band are below the limit by 20dB and are not recorded.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/


● For 12V System:

Test Mode		Mode 1			Supply Voltage		DC 12V	
Test graph and data for Unwanted Spurious Emissions								
								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	53.275	-79.44	-52.25	-23.00	29.25	27.19	Peak	Horizontal
2	107.875	-83.69	-63.77	-23.00	40.77	19.92	Peak	Horizontal
3	134.2	-90.63	-64.78	-23.00	41.78	25.85	Peak	Horizontal
4	242.425	-80.91	-54.28	-23.00	31.28	26.63	Peak	Horizontal
5	269.725	-82.86	-55.46	-23.00	32.46	27.40	Peak	Horizontal
6	296.05	-88.03	-60.80	-23.00	37.80	27.23	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	53.275	-79.44	-52.25	-24.34	27.91	27.19	Peak	Horizontal
2	107.875	-83.69	-63.77	-24.34	39.43	19.92	Peak	Horizontal
3	134.2	-90.63	-64.78	-24.34	40.44	25.85	Peak	Horizontal
	242.425	-80.91	-54.28	-24.34	29.94	26.63	Peak	Horizontal
	269.725	-82.86	-55.46	-24.34	31.12	27.40	Peak	Horizontal
	296.05	-88.03	-60.80	-24.34	36.46	27.23	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 1	Supply Voltage	DC 12V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions




No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	53.275	-70.16	-42.97	-23.00	19.97	27.19	Peak	Vertical
2	80.575	-93.15	-69.26	-23.00	46.26	23.89	Peak	Vertical
3	142.000	-92.76	-65.99	-23.00	42.99	26.77	Peak	Vertical
4	242.425	-79.06	-52.43	-23.00	29.43	26.63	Peak	Vertical
5	269.725	-80.68	-53.28	-23.00	30.28	27.40	Peak	Vertical
6	566.125	-91.36	-58.49	-23.00	35.49	32.87	Peak	Vertical

Test data for Harmonic emissions spurious

1	53.275	-70.16	-42.97	-24.34	18.63	27.19	Peak	Vertical
2	80.575	-93.15	-69.26	-24.34	44.92	23.89	Peak	Vertical
3	142.000	-92.76	-65.99	-24.34	41.65	26.77	Peak	Vertical
	242.425	-79.06	-52.43	-24.34	28.09	26.63	Peak	Vertical
	269.725	-80.68	-53.28	-24.34	28.94	27.40	Peak	Vertical
	566.125	-91.36	-58.49	-24.34	34.15	32.87	Peak	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 2	Supply Voltage	DC 12V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions




No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-70.04	-42.99	-23.00	19.99	27.05	Peak	Vertical
2	189.775	-88.02	-66.05	-23.00	43.05	21.97	Peak	Vertical
3	217.075	-76.07	-52.42	-23.00	29.42	23.65	Peak	Vertical
4	244.375	-63.69	-36.84	-23.00	13.84	26.85	Peak	Vertical
5	271.675	-80.92	-53.55	-23.00	30.55	27.37	Peak	Vertical
6	571.000	-90.48	-57.49	-23.00	34.49	32.99	Peak	Vertical

Test data for Harmonic emissions spurious

1	54.25	-70.04	-42.99	-24.33	41.72	27.05	Peak	Vertical
2	189.775	-88.02	-66.05	-24.33	28.09	21.97	Peak	Vertical
3	217.075	-76.07	-52.42	-24.33	12.51	23.65	Peak	Vertical
4	244.375	-63.69	-36.84	-24.33	29.22	26.85	Peak	Vertical
5	271.675	-80.92	-53.55	-24.33	33.16	27.37	Peak	Vertical
6	571.000	-90.48	-57.49	-24.33	41.72	32.99	Peak	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 3	Supply Voltage	DC 12V					
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX  — Limit ■ Final Test — Horizontal								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-76.67	-49.62	-23.00	26.62	27.05	Peak	Horizontal
2	108.85	-74.95	-55.02	-23.00	32.02	19.93	Peak	Horizontal
3	137.125	-81.68	-55.23	-23.00	32.23	26.45	Peak	Horizontal
4	246.325	-61.27	-34.20	-23.00	11.20	27.07	Peak	Horizontal
5	256.075	-64.57	-37.19	-23.00	14.19	27.38	Peak	Horizontal
6	263.875	-72.99	-45.56	-23.00	22.56	27.43	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	54.25	-76.67	-49.62	-24.31	25.31	27.05	Peak	Horizontal
2	108.85	-74.95	-55.02	-24.31	30.71	19.93	Peak	Horizontal
3	137.125	-81.68	-55.23	-24.31	30.92	26.45	Peak	Horizontal
4	246.325	-61.27	-34.20	-24.31	9.89	27.07	Peak	Horizontal
5	256.075	-64.57	-37.19	-24.31	12.88	27.38	Peak	Horizontal
6	263.875	-72.99	-45.56	-24.31	21.25	27.43	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 3	Supply Voltage	DC 12V					
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-67.39	-40.34	-23.00	17.34	27.05	Peak	Vertical
2	219.025	-71.75	-47.88	-23.00	24.88	23.87	Peak	Vertical
3	236.575	-74.86	-48.90	-23.00	25.90	25.96	Peak	Vertical
4	246.325	-58.66	-31.59	-23.00	8.59	27.07	Peak	Vertical
5	256.075	-66.58	-39.20	-23.00	16.20	27.38	Peak	Vertical
6	263.875	-73.57	-46.14	-23.00	23.14	27.43	Peak	Vertical
Test data for Harmonic emissions spurious								
1	54.25	-67.39	-40.34	-24.31	16.03	27.05	Peak	Vertical
2	219.025	-71.75	-47.88	-24.31	23.57	23.87	Peak	Vertical
3	236.575	-74.86	-48.90	-24.31	24.59	25.96	Peak	Vertical
4	246.325	-58.66	-31.59	-24.31	7.28	27.07	Peak	Vertical
5	256.075	-66.58	-39.20	-24.31	14.89	27.38	Peak	Vertical
6	263.875	-73.57	-46.14	-24.31	21.83	27.43	Peak	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 4				Supply Voltage		DC 12V																																																																
Test graph and data for Unwanted Spurious Emissions																																																																							
FCC Part 95D OPER TX  <table><thead><tr><th>No.</th><th>Frequency [MHz]</th><th>Reading [dBm]</th><th>Level [dBm]</th><th>Limit [dBm]</th><th>Margin [dB]</th><th>Factor [dB]</th><th>Detector</th><th>Polarity</th></tr></thead><tbody><tr><td>1</td><td>53.275</td><td>-71.37</td><td>-44.18</td><td>-23.00</td><td>21.18</td><td>27.19</td><td>Peak</td><td>Horizontal</td></tr><tr><td>2</td><td>107.875</td><td>-71.41</td><td>-51.49</td><td>-23.00</td><td>28.49</td><td>19.92</td><td>Peak</td><td>Horizontal</td></tr><tr><td>3</td><td>134.2</td><td>-79.78</td><td>-53.93</td><td>-23.00</td><td>30.93</td><td>25.85</td><td>Peak</td><td>Horizontal</td></tr><tr><td>4</td><td>161.5</td><td>-84.32</td><td>-60.55</td><td>-23.00</td><td>37.55</td><td>23.77</td><td>Peak</td><td>Horizontal</td></tr><tr><td>5</td><td>269.725</td><td>-85.46</td><td>-58.06</td><td>-23.00</td><td>35.06</td><td>27.40</td><td>Peak</td><td>Horizontal</td></tr><tr><td>6</td><td>323.35</td><td>-85.26</td><td>-58.00</td><td>-23.00</td><td>35.00</td><td>27.26</td><td>Peak</td><td>Horizontal</td></tr></tbody></table>									No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity	1	53.275	-71.37	-44.18	-23.00	21.18	27.19	Peak	Horizontal	2	107.875	-71.41	-51.49	-23.00	28.49	19.92	Peak	Horizontal	3	134.2	-79.78	-53.93	-23.00	30.93	25.85	Peak	Horizontal	4	161.5	-84.32	-60.55	-23.00	37.55	23.77	Peak	Horizontal	5	269.725	-85.46	-58.06	-23.00	35.06	27.40	Peak	Horizontal	6	323.35	-85.26	-58.00	-23.00	35.00	27.26	Peak	Horizontal
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity																																																															
1	53.275	-71.37	-44.18	-23.00	21.18	27.19	Peak	Horizontal																																																															
2	107.875	-71.41	-51.49	-23.00	28.49	19.92	Peak	Horizontal																																																															
3	134.2	-79.78	-53.93	-23.00	30.93	25.85	Peak	Horizontal																																																															
4	161.5	-84.32	-60.55	-23.00	37.55	23.77	Peak	Horizontal																																																															
5	269.725	-85.46	-58.06	-23.00	35.06	27.40	Peak	Horizontal																																																															
6	323.35	-85.26	-58.00	-23.00	35.00	27.26	Peak	Horizontal																																																															
Test data for Harmonic emissions spurious																																																																							
1	53.275	-71.37	-44.18	-24.35	19.83	27.19	Peak	Horizontal																																																															
2	107.875	-71.41	-51.49	-24.35	27.14	19.92	Peak	Horizontal																																																															
3	134.2	-79.78	-53.93	-24.35	29.58	25.85	Peak	Horizontal																																																															
4	161.5	-84.32	-60.55	-24.35	36.20	23.77	Peak	Horizontal																																																															
5	269.725	-85.46	-58.06	-24.35	33.71	27.40	Peak	Horizontal																																																															
6	323.35	-85.26	-58.00	-24.35	33.65	27.26	Peak	Horizontal																																																															

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 4			Supply Voltage		DC 12V	
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX <								

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 5	Supply Voltage	DC 12V					
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX Level [dBm] Frequency [Hz] — Limit ■ Final Test — Horizontal								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-77.29	-50.24	-23.00	27.24	27.05	Peak	Horizontal
2	108.85	-74.21	-54.28	-23.00	31.28	19.93	Peak	Horizontal
3	136.15	-87.77	-61.44	-23.00	38.44	26.33	Peak	Horizontal
4	244.375	-80.07	-53.22	-23.00	30.22	26.85	Peak	Horizontal
5	271.675	-82.90	-55.53	-23.00	32.53	27.37	Peak	Horizontal
6	298.975	-86.74	-59.46	-23.00	36.46	27.28	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	54.25	-77.29	-50.24	-24.36	25.88	27.05	Peak	Horizontal
2	108.85	-74.21	-54.28	-24.36	29.92	19.93	Peak	Horizontal
3	136.15	-87.77	-61.44	-24.36	37.08	26.33	Peak	Horizontal
4	244.375	-80.07	-53.22	-24.36	28.86	26.85	Peak	Horizontal
5	271.675	-82.90	-55.53	-24.36	31.17	27.37	Peak	Horizontal
6	298.975	-86.74	-59.46	-24.36	35.10	27.28	Peak	Horizontal


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 5			Supply Voltage		DC 12V	
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX Level [dBm] Frequency [Hz] — Limit * Final Test — Vertical								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-68.25	-41.20	-23.00	18.20	27.05	Peak	Vertical
2	108.85	-82.90	-62.97	-23.00	39.97	19.93	Peak	Vertical
3	217.075	-87.16	-63.51	-23.00	40.51	23.65	Peak	Vertical
4	244.375	-77.33	-50.48	-23.00	27.48	26.85	Peak	Vertical
5	271.675	-81.27	-53.90	-23.00	30.90	27.37	Peak	Vertical
6	598.3	-90.99	-57.12	-23.00	34.12	33.87	Peak	Vertical
Test data for Harmonic emissions spurious								
1	54.25	-68.25	-41.20	-24.36	16.84	27.05	Peak	Vertical
2	108.85	-82.90	-62.97	-24.36	38.61	19.93	Peak	Vertical
3	217.075	-87.16	-63.51	-24.36	39.15	23.65	Peak	Vertical
4	244.375	-77.33	-50.48	-24.36	26.12	26.85	Peak	Vertical
5	271.675	-81.27	-53.90	-24.36	29.54	27.37	Peak	Vertical
6	598.3	-90.99	-57.12	-24.36	32.76	33.87	Peak	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 6	Supply Voltage	DC 12V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions




No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-74.03	-46.98	-23.00	23.98	27.05	Peak	Horizontal
2	108.85	-80.12	-60.19	-23.00	37.19	19.93	Peak	Horizontal
3	137.125	-83.46	-57.01	-23.00	34.01	26.45	Peak	Horizontal
4	219.025	-78.60	-54.73	-23.00	31.73	23.87	Peak	Horizontal
5	246.325	-61.01	-33.94	-23.00	10.94	27.07	Peak	Horizontal
6	273.625	-81.63	-54.31	-23.00	31.31	27.32	Peak	Horizontal

Test data for Harmonic emissions spurious


1	54.25	-74.03	-46.98	-24.33	22.65	27.05	Peak	Horizontal
2	108.85	-80.12	-60.19	-24.33	35.86	19.93	Peak	Horizontal
3	137.125	-83.46	-57.01	-24.33	32.68	26.45	Peak	Horizontal
4	219.025	-78.60	-54.73	-24.33	30.40	23.87	Peak	Horizontal
5	246.325	-61.01	-33.94	-24.33	9.61	27.07	Peak	Horizontal
6	273.625	-81.63	-54.31	-24.33	29.98	27.32	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 6				Supply Voltage		DC 12V																																																																
Test graph and data for Unwanted Spurious Emissions																																																																							
FCC Part 95D OPER TX  <table><thead><tr><th>No.</th><th>Frequency [MHz]</th><th>Reading [dBm]</th><th>Level [dBm]</th><th>Limit [dBm]</th><th>Margin [dB]</th><th>Factor [dB]</th><th>Detector</th><th>Polarity</th></tr></thead><tbody><tr><td>1</td><td>54.25</td><td>-65.01</td><td>-37.96</td><td>-23.00</td><td>14.96</td><td>27.05</td><td>Peak</td><td>Vertical</td></tr><tr><td>2</td><td>219.025</td><td>-71.54</td><td>-47.67</td><td>-23.00</td><td>24.67</td><td>23.87</td><td>Peak</td><td>Vertical</td></tr><tr><td>3</td><td>246.325</td><td>-59.13</td><td>-32.06</td><td>-23.00</td><td>9.06</td><td>27.07</td><td>Peak</td><td>Vertical</td></tr><tr><td>4</td><td>273.625</td><td>-79.24</td><td>-51.92</td><td>-23.00</td><td>28.92</td><td>27.32</td><td>Peak</td><td>Vertical</td></tr><tr><td>5</td><td>411.1</td><td>-87.40</td><td>-58.40</td><td>-23.00</td><td>35.40</td><td>29.00</td><td>Peak</td><td>Vertical</td></tr><tr><td>6</td><td>767.95</td><td>-90.21</td><td>-54.52</td><td>-23.00</td><td>31.52</td><td>35.69</td><td>Peak</td><td>Vertical</td></tr></tbody></table>									No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity	1	54.25	-65.01	-37.96	-23.00	14.96	27.05	Peak	Vertical	2	219.025	-71.54	-47.67	-23.00	24.67	23.87	Peak	Vertical	3	246.325	-59.13	-32.06	-23.00	9.06	27.07	Peak	Vertical	4	273.625	-79.24	-51.92	-23.00	28.92	27.32	Peak	Vertical	5	411.1	-87.40	-58.40	-23.00	35.40	29.00	Peak	Vertical	6	767.95	-90.21	-54.52	-23.00	31.52	35.69	Peak	Vertical
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity																																																															
1	54.25	-65.01	-37.96	-23.00	14.96	27.05	Peak	Vertical																																																															
2	219.025	-71.54	-47.67	-23.00	24.67	23.87	Peak	Vertical																																																															
3	246.325	-59.13	-32.06	-23.00	9.06	27.07	Peak	Vertical																																																															
4	273.625	-79.24	-51.92	-23.00	28.92	27.32	Peak	Vertical																																																															
5	411.1	-87.40	-58.40	-23.00	35.40	29.00	Peak	Vertical																																																															
6	767.95	-90.21	-54.52	-23.00	31.52	35.69	Peak	Vertical																																																															
Test data for Harmonic emissions spurious																																																																							
1	54.25	-65.01	-37.96	-24.33	13.63	27.05	Peak	Vertical																																																															
2	219.025	-71.54	-47.67	-24.33	23.34	23.87	Peak	Vertical																																																															
3	246.325	-59.13	-32.06	-24.33	7.73	27.07	Peak	Vertical																																																															
4	273.625	-79.24	-51.92	-24.33	27.59	27.32	Peak	Vertical																																																															
5	411.1	-87.40	-58.40	-24.33	34.07	29.00	Peak	Vertical																																																															
6	767.95	-90.21	-54.52	-24.33	30.19	35.69	Peak	Vertical																																																															

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


● For 24V System:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 1			Supply Voltage		DC 24V	
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX								


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 2			Supply Voltage		DC 24V	
Test graph and data for Unwanted Spurious Emissions								
								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-72.90	-45.85	-23.00	22.85	27.05	Peak	Horizontal
2	108.85	-66.58	-46.65	-23.00	23.65	19.93	Peak	Horizontal
3	136.15	-79.53	-53.20	-23.00	30.20	26.33	Peak	Horizontal
4	244.375	-75.83	-48.98	-23.00	25.98	26.85	Peak	Horizontal
5	271.675	-80.81	-53.44	-23.00	30.44	27.37	Peak	Horizontal
6	326.275	-84.67	-57.45	-23.00	34.45	27.22	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	54.25	-72.90	-45.85	-24.32	21.53	27.05	Peak	Horizontal
2	108.85	-66.58	-46.65	-24.32	22.33	19.93	Peak	Horizontal
3	136.15	-79.53	-53.20	-24.32	28.88	26.33	Peak	Horizontal
4	244.375	-75.83	-48.98	-24.32	24.66	26.85	Peak	Horizontal
5	271.675	-80.81	-53.44	-24.32	29.12	27.37	Peak	Horizontal
6	326.275	-84.67	-57.45	-24.32	33.13	27.22	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 2	Supply Voltage	DC 24V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions




No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-63.26	-36.21	-23.00	13.21	27.05	Peak	Vertical
2	108.85	-75.38	-55.45	-23.00	32.45	19.93	Peak	Vertical
3	217.075	-80.22	-56.57	-23.00	33.57	23.65	Peak	Vertical
4	244.375	-73.58	-46.73	-23.00	23.73	26.85	Peak	Vertical
5	271.675	-79.84	-52.47	-23.00	29.47	27.37	Peak	Vertical
6	435.475	-85.69	-55.94	-23.00	32.94	29.75	Peak	Vertical

Test data for Harmonic emissions spurious

1	54.25	-63.26	-36.21	-24.32	11.89	27.05	Peak	Vertical
2	108.85	-75.38	-55.45	-24.32	31.13	19.93	Peak	Vertical
3	217.075	-80.22	-56.57	-24.32	32.25	23.65	Peak	Vertical
4	244.375	-73.58	-46.73	-24.32	22.41	26.85	Peak	Vertical
5	271.675	-79.84	-52.47	-24.32	28.15	27.37	Peak	Vertical
6	435.475	-85.69	-55.94	-24.32	31.62	29.75	Peak	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 3			Supply Voltage		DC 24V																																																																
Test graph and data for Unwanted Spurious Emissions																																																																							
FCC Part 95D OPER TX  <table><thead><tr><th>No.</th><th>Frequency [MHz]</th><th>Reading [dBm]</th><th>Level [dBm]</th><th>Limit [dBm]</th><th>Margin [dB]</th><th>Factor [dB]</th><th>Detector</th><th>Polarity</th></tr></thead><tbody><tr><td>1</td><td>54.25</td><td>-75.98</td><td>-48.93</td><td>-23.00</td><td>25.93</td><td>27.05</td><td>Peak</td><td>Horizontal</td></tr><tr><td>2</td><td>108.85</td><td>-76.07</td><td>-56.14</td><td>-23.00</td><td>33.14</td><td>19.93</td><td>Peak</td><td>Horizontal</td></tr><tr><td>3</td><td>137.125</td><td>-80.93</td><td>-54.48</td><td>-23.00</td><td>31.48</td><td>26.45</td><td>Peak</td><td>Horizontal</td></tr><tr><td>4</td><td>219.025</td><td>-81.34</td><td>-57.47</td><td>-23.00</td><td>34.47</td><td>23.87</td><td>Peak</td><td>Horizontal</td></tr><tr><td>5</td><td>246.325</td><td>-62.73</td><td>-35.66</td><td>-23.00</td><td>12.66</td><td>27.07</td><td>Peak</td><td>Horizontal</td></tr><tr><td>6</td><td>273.625</td><td>-79.52</td><td>-52.20</td><td>-23.00</td><td>29.20</td><td>27.32</td><td>Peak</td><td>Horizontal</td></tr></tbody></table>									No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity	1	54.25	-75.98	-48.93	-23.00	25.93	27.05	Peak	Horizontal	2	108.85	-76.07	-56.14	-23.00	33.14	19.93	Peak	Horizontal	3	137.125	-80.93	-54.48	-23.00	31.48	26.45	Peak	Horizontal	4	219.025	-81.34	-57.47	-23.00	34.47	23.87	Peak	Horizontal	5	246.325	-62.73	-35.66	-23.00	12.66	27.07	Peak	Horizontal	6	273.625	-79.52	-52.20	-23.00	29.20	27.32	Peak	Horizontal
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity																																																															
1	54.25	-75.98	-48.93	-23.00	25.93	27.05	Peak	Horizontal																																																															
2	108.85	-76.07	-56.14	-23.00	33.14	19.93	Peak	Horizontal																																																															
3	137.125	-80.93	-54.48	-23.00	31.48	26.45	Peak	Horizontal																																																															
4	219.025	-81.34	-57.47	-23.00	34.47	23.87	Peak	Horizontal																																																															
5	246.325	-62.73	-35.66	-23.00	12.66	27.07	Peak	Horizontal																																																															
6	273.625	-79.52	-52.20	-23.00	29.20	27.32	Peak	Horizontal																																																															
Test data for Harmonic emissions spurious																																																																							
1	54.25	-75.98	-48.93	-24.28	31.86	27.05	Peak	Horizontal																																																															
2	108.85	-76.07	-56.14	-24.28	30.20	19.93	Peak	Horizontal																																																															
3	137.125	-80.93	-54.48	-24.28	33.19	26.45	Peak	Horizontal																																																															
4	219.025	-81.34	-57.47	-24.28	11.38	23.87	Peak	Horizontal																																																															
5	246.325	-62.73	-35.66	-24.28	27.92	27.07	Peak	Horizontal																																																															
6	273.625	-79.52	-52.20	-24.28	31.86	27.32	Peak	Horizontal																																																															


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 3				Supply Voltage	DC 24V		
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX Level [dBm] 25M100M1G Frequency [Hz] LimitFinal TestVertical								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-66.72	-39.67	-23.00	16.67	27.05	Peak	Vertical
2	219.025	-73.79	-49.92	-23.00	26.92	23.87	Peak	Vertical
3	246.325	-60.49	-33.42	-23.00	10.42	27.07	Peak	Vertical
4	273.625	-79.02	-51.70	-23.00	28.70	27.32	Peak	Vertical
5	411.1	-86.18	-57.18	-23.00	34.18	29.00	Peak	Vertical
6	438.4	-85.43	-55.59	-23.00	32.59	29.84	Peak	Vertical
Test data for Harmonic emissions spurious								
1	54.25	-66.72	-39.67	-24.28	15.39	27.05	Peak	Vertical
2	219.025	-73.79	-49.92	-24.28	25.64	23.87	Peak	Vertical
3	246.325	-60.49	-33.42	-24.28	9.14	27.07	Peak	Vertical
4	273.625	-79.02	-51.70	-24.28	27.42	27.32	Peak	Vertical
5	411.1	-86.18	-57.18	-24.28	32.90	29.00	Peak	Vertical
6	438.4	-85.43	-55.59	-24.28	31.31	29.84	Peak	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 4	Supply Voltage	DC 24V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions




No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	53.275	-78.76	-51.57	-23.00	28.57	27.19	Peak	Horizontal
2	107.875	-81.37	-61.45	-23.00	38.45	19.92	Peak	Horizontal
3	242.425	-80.35	-53.72	-23.00	30.72	26.63	Peak	Horizontal
4	269.725	-82.07	-54.67	-23.00	31.67	27.40	Peak	Horizontal
5	296.05	-92.15	-64.92	-23.00	41.92	27.23	Peak	Horizontal
6	566.125	-92.91	-60.04	-23.00	37.04	32.87	Peak	Horizontal


Test data for Harmonic emissions spurious

1	53.275	-78.76	-51.57	-24.31	27.26	27.19	Peak	Horizontal
2	107.875	-81.37	-61.45	-24.31	37.14	19.92	Peak	Horizontal
3	242.425	-80.35	-53.72	-24.31	29.41	26.63	Peak	Horizontal
4	269.725	-82.07	-54.67	-24.31	30.36	27.40	Peak	Horizontal
5	296.05	-92.15	-64.92	-24.31	40.61	27.23	Peak	Horizontal
6	566.125	-92.91	-60.04	-24.31	35.73	32.87	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 4				Supply Voltage		DC 24V	
Test graph and data for Unwanted Spurious Emissions									
FCC Part 95D OPER TX  — Limit ■ Final Test — Vertical									
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity	
1	53.275	-69.85	-42.66	-23.00	19.66	27.19	Peak	Vertical	
2	142	-92.62	-65.85	-23.00	42.85	26.77	Peak	Vertical	
3	242.425	-78.53	-51.90	-23.00	28.90	26.63	Peak	Vertical	
4	269.725	-82.13	-54.73	-23.00	31.73	27.40	Peak	Vertical	
5	539.8	-93.08	-61.23	-23.00	38.23	31.85	Peak	Vertical	
6	566.125	-91.36	-58.49	-23.00	35.49	32.87	Peak	Vertical	
Test data for Harmonic emissions spurious									
1	53.275	-69.85	-42.66	-24.31	18.35	27.19	Peak	Vertical	
2	142	-92.62	-65.85	-24.31	41.54	26.77	Peak	Vertical	
3	242.425	-78.53	-51.90	-24.31	27.59	26.63	Peak	Vertical	
4	269.725	-82.13	-54.73	-24.31	30.42	27.40	Peak	Vertical	
5	539.8	-93.08	-61.23	-24.31	36.92	31.85	Peak	Vertical	
6	566.125	-91.36	-58.49	-24.31	34.18	32.87	Peak	Vertical	


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 5	Supply Voltage	DC 24V					
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX  — Limit ■ Final Test — Horizontal								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-76.99	-49.94	-23.00	26.94	27.05	Peak	Horizontal
2	108.85	-78.64	-58.71	-23.00	35.71	19.93	Peak	Horizontal
3	136.15	-81.39	-55.06	-23.00	32.06	26.33	Peak	Horizontal
4	217.075	-81.08	-57.43	-23.00	34.43	23.65	Peak	Horizontal
5	244.375	-65.14	-38.29	-23.00	15.29	26.85	Peak	Horizontal
6	271.675	-81.65	-54.28	-23.00	31.28	27.37	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	54.25	-76.99	-49.94	-24.32	25.62	27.05	Peak	Horizontal
2	108.85	-78.64	-58.71	-24.32	34.39	19.93	Peak	Horizontal
3	136.15	-81.39	-55.06	-24.32	30.74	26.33	Peak	Horizontal
4	217.075	-81.08	-57.43	-24.32	33.11	23.65	Peak	Horizontal
5	244.375	-65.14	-38.29	-24.32	13.97	26.85	Peak	Horizontal
6	271.675	-81.65	-54.28	-24.32	29.96	27.37	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 5	Supply Voltage	DC 24V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions



No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-67.48	-40.43	-23.00	17.43	27.05	Peak	Vertical
2	217.075	-75.54	-51.89	-23.00	28.89	23.65	Peak	Vertical
3	244.375	-62.68	-35.83	-23.00	12.83	26.85	Peak	Vertical
4	271.675	-82.65	-55.28	-23.00	32.28	27.37	Peak	Vertical
5	543.7	-90.43	-58.41	-23.00	35.41	32.02	Peak	Vertical
6	571.000	-91.42	-58.43	-23.00	35.43	32.99	Peak	Vertical

Test data for Harmonic emissions spurious

1	54.25	-67.48	-40.43	-24.32	16.11	27.05	Peak	Vertical
2	217.075	-75.54	-51.89	-24.32	27.57	23.65	Peak	Vertical
3	244.375	-62.68	-35.83	-24.32	11.51	26.85	Peak	Vertical
4	271.675	-82.65	-55.28	-24.32	30.96	27.37	Peak	Vertical
5	543.7	-90.43	-58.41	-24.32	34.09	32.02	Peak	Vertical
6	571.000	-91.42	-58.43	-24.32	34.11	32.99	Peak	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode		Mode 6			Supply Voltage		DC 24V	
Test graph and data for Unwanted Spurious Emissions								
FCC Part 95D OPER TX Level [dBm] Frequency [Hz] — Limit ■ Final Test — Horizontal								
No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	108.85	-68.76	-48.83	-23.00	25.83	19.93	Peak	Horizontal
2	219.025	-75.78	-51.91	-23.00	28.91	23.87	Peak	Horizontal
3	236.575	-76.59	-50.63	-23.00	27.63	25.96	Peak	Horizontal
4	246.325	-60.13	-33.06	-23.00	10.06	27.07	Peak	Horizontal
5	256.075	-63.75	-36.37	-23.00	13.37	27.38	Peak	Horizontal
6	263.875	-71.56	-44.13	-23.00	21.13	27.43	Peak	Horizontal
Test data for Harmonic emissions spurious								
1	108.85	-68.76	-48.83	-24.31	24.52	19.93	Peak	Horizontal
2	219.025	-75.78	-51.91	-24.31	27.60	23.87	Peak	Horizontal
3	236.575	-76.59	-50.63	-24.31	26.32	25.96	Peak	Horizontal
4	246.325	-60.13	-33.06	-24.31	8.75	27.07	Peak	Horizontal
5	256.075	-63.75	-36.37	-24.31	12.06	27.38	Peak	Horizontal
6	263.875	-71.56	-44.13	-24.31	19.82	27.43	Peak	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode	Mode 6	Supply Voltage	DC 24V
-----------	--------	----------------	--------

Test graph and data for Unwanted Spurious Emissions



No.	Frequency [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Detector	Polarity
1	54.25	-67.84	-40.79	-23.00	17.79	27.05	Peak	Vertical
2	219.025	-70.16	-46.29	-23.00	23.29	23.87	Peak	Vertical
3	236.575	-74.59	-48.63	-23.00	25.63	25.96	Peak	Vertical
4	246.325	-57.85	-30.78	-23.00	7.78	27.07	Peak	Vertical
5	256.075	-65.37	-37.99	-23.00	14.99	27.38	Peak	Vertical
6	263.875	-73.10	-45.67	-23.00	22.67	27.43	Peak	Vertical

Test data for Harmonic emissions spurious

1	54.25	-67.84	-40.79	-24.31	16.48	27.05	Peak	Vertical
2	219.025	-70.16	-46.29	-24.31	21.98	23.87	Peak	Vertical
3	236.575	-74.59	-48.63	-24.31	24.32	25.96	Peak	Vertical
4	246.325	-57.85	-30.78	-24.31	6.47	27.07	Peak	Vertical
5	256.075	-65.37	-37.99	-24.31	13.68	27.38	Peak	Vertical
6	263.875	-73.10	-45.67	-24.31	21.36	27.43	Peak	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


8.5 Emission Mask Measurement Part

The detailed procedure employed for Emission Mask measurements are specified as following:

-Connect the equipment as illustrated.

-Spectrum set as follow:


1. Centre frequency = fundamental frequency, Span=150kHz for 12.5kHz and 25kHz channel spacing, RBW=300Hz, VBW=1000Hz for 12.5kHz, RBW=300Hz, VBW=1000Hz for 25kHz, Sweep = auto, Detector function = peak, Trace = max hold
2. Key the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit.
4. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
5. Measure and record the results in the test report.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test plot as follows:

- For 12V System:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

- For 24V System:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9. Maximum Transmitter Power

9.1 Provisions Applicable

According to FCC§2.1046(a) and §95.967 the following requirements are required:


The maximum transmit power limits for each CBRS transmitter type are as follows:

- (a) When transmitting amplitude modulated (AM) voice signals or frequency modulated (FM) voice signals, the mean carrier power must not exceed 4 Watts
- (b) When transmitting single sideband (SSB) voice signals, the peak envelope power must not exceed 12 Watts.

9.2 Measurement Procedure

- Conducted RF Output Power:
 1. The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.
 2. The DUT was connected to a Spectrum Analyzer (SA) via a 30dB attenuator connected to the DUT's antenna port. The
 3. SA was configured as above using the Automatic 6dB Cursor Bandwidth measurement. The output power of the DUT was set to the manufacturer's highest output power setting at the Low, Mid and High frequency channels as permitted by the device.
 4. The DUT was set to transmit at its maximum Duty Cycle.
 5. Spectrum set as follow:
 6. Centre frequency = fundamental frequency, Span=150kHz , RBW=30kHz, VBW=100kHz ;
 7. Sweep = auto, Detector function = peak, Trace = max hold
 8. The final recorded maximum power is reported
- Calculation Formula: $CP = R + A + L$
 - CP: The final Conducted Power
 - R: The reading value from spectrum analyzer
 - A: The attenuation value of the used attenuator
 - L: The loss of all connection cables

9.3 Measurement Setup




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.4 Measurement Result

- For 12V System:

Conducted Power Measurement Results			
Test Mode	Channel Separation	Test Channel	Measurement Result (dBm)
CBRS TX_AM	10 kHz	26.965 MHz	35.663
		27.205 MHz	35.668
		27.405 MHz	35.692

Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.