FCC REPORT

Applicant:	Dinsafer Innovation Co., Ltd.
Address of Applicant:	Room 402/403, Floor 4, Area B, Unit B, West Silicon Valley, No. 5010, Baoan Avenue, Hangcheng Street, Baoan District, Shenzhen, 518128, China
Manufacturer:	Dinsafer Innovation Co., Ltd.
Address of Manufacturer:	Room 402/403, Floor 4, Area B, Unit B, West Silicon Valley, No. 5010, Baoan Avenue, Hangcheng Street, Baoan District, Shenzhen, 518128, China

Equipment Under Test (EUT)

Product Name:	Wireless Vibration Sensor
Model No.:	DVBA4(DVB *4,*=A-Z)(DVB A*,*=1-9)
FCC ID:	2ASON-DVBA4
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.231
Date of sample receipt:	March 22, 2019
Date of Test:	March 22~ April 1, 2019
Date of report issued:	April 2, 2019
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
01	*April 2, 2019*	*Original*

Prepared By:  ***Date:*** *April 2, 2019*

Project Engineer

Check By: ***Date:*** *April 2, 2019*

Reviewer

3 Contents

Page

1 COVER PAGE 1
2 VERSION 2
3 CONTENTS 3
4 TEST SUMMARY 4
4.1 MEASUREMENT UNCERTAINTY 4
5 GENERAL INFORMATION 5
5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 6
5.3 DESCRIPTION OF SUPPORT UNITS 6
5.4 TEST FACILITY 6
5.5 TEST LOCATION 6
5.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER 6
6 TEST INSTRUMENTS LIST 7
7 TEST RESULTS AND MEASUREMENT DATA 8
7.1 ANTENNA REQUIREMENT 8
7.2 RADIATED EMISSION METHOD 9
7.2.1 Field Strength of The Fundamental Signal 11
7.2.2 Spurious Emissions 12
7.3 20DB OCCUPY BANDWIDTH 15
7.4 DWELL TIME 16
8 TEST SETUP PHOTO 17
9 EUT CONSTRUCTIONAL DETAILS 17

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203	Pass
Conduction Emission	15.207	N/A
Field strength of the Fundamental Signal	15.231 (b)	Pass
Spurious Emissions	15.231 (b)/15.209	Pass
20dB Bandwidth	15.231 (c)	Pass
Dwell Time	15.231 (a)(2)	Pass

Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.54dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 5.34dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 5.34dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	Wireless Vibration Sensor
Model No.:	DVBA4(DVB *4,*=A-Z)(DVB A*,*=1-9)
Test model:	DVBA4
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is model name for commercial purpose.	
Serial No.:	2019-DVBA4
Hardware Version:	C006-V1.1
Software Version:	C006-F4_V1.0.0.2019.02.18_RS
Test sample(s) ID:	GTS201903000167-1
Sample(s) Status:	Engineer sample
Operation Frequency:	433.92MHz
Modulation technology:	2FSK
Antenna Type:	Integral Antenna
Antenna gain:	0dBi(declare by applicant)
Power supply:	DC3V by CR2032 battery

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode. (New battery is used during all test)

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which only the worst case was shown in this test report and defined as follows:

	Axis	X	Y	Z
433.92MHz	Field Strength(dBuV/m)	81.93	77.69	74.39

5.3 Description of Support Units

None.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

● **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2.

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone,
Xixiang Road, Baoan District, Shenzhen, Guangdong, China
Tel: 0755-27798480
Fax: 0755-27798960

5.6 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 27 2018	June. 26 2019

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Barometer	ChangChun	DYM3	GTS257	June 27 2018	June 26 2019

7 Test results and Measurement Data

7.1 Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement:	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is integral antenna; the best case gain of the antenna is 0dBi, reference to the appendix II for details.	

7.2 Radiated Emission Method

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.231 (b)& Section 15.209</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10:2013</td></tr>
<tr><td>Test Frequency Range:</td><td>9kHz to 5000MHz</td></tr>
<tr><td>Test site:</td><td>Measurement Distance: 3m</td></tr>
<tr><td>Receiver setup:</td><td>
<table>
<tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Value</td></tr>
<tr><td>9KHz-150KHz</td><td>PK,AV,QP</td><td>200Hz</td><td>600Hz</td><td>PK,AV,QP</td></tr>
<tr><td>150KHz-30MHz</td><td>PK,AV,QP</td><td>9KHz</td><td>30KHz</td><td>PK,AV,QP</td></tr>
<tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>120KHz</td><td>300KHz</td><td>Quasi-peak</td></tr>
<tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak</td></tr>
<tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average</td></tr>
</table>
</td></tr>
<tr><td>Limit:
(Field strength of the fundamental signal)</td><td>
<table>
<tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr>
<tr><td rowspan="2">433.92MHz</td><td>100.83</td><td>Peak Value</td></tr>
<tr><td>80.83</td><td>Average Value</td></tr>
</table>
</td></tr>
<tr><td>Limit:
(Spurious Emissions)</td><td>
<table>
<tr><td>Fundamental Frequency (MHz)</td><td>Field Strength of fundamental (microvolts/meter)</td><td>Field Strength of Unwanted Emissions (microvolts/meter)</td></tr>
<tr><td>40.66-40.70</td><td>1,000</td><td>100</td></tr>
<tr><td>70-130</td><td>500</td><td>50</td></tr>
<tr><td>130-174</td><td>500 to 1,500**</td><td>50 to 1,50**</td></tr>
<tr><td>174-260</td><td>1,500</td><td>1,50</td></tr>
<tr><td>260-470</td><td>1,500 to 5,000**</td><td>1,50 to 5,00**</td></tr>
<tr><td>Above 470</td><td>5,000</td><td>5,00</td></tr>
</table>
<table>
<tr><td rowspan="2">Frequency (MHz)</td><td colspan="2">Class B(dBuV/m @3m)</td></tr>
<tr><td>Peak</td><td>Average</td></tr>
<tr><td>Above 1000</td><td>74</td><td>54</td></tr>
</table>
Or The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level whichever limit permits higher field strength.
</td></tr>
<tr><td>Test setup:</td><td>Below 30MHz
 

Below 1GHz</td></tr>
</table>

<table>
<tr><td></td><td>


Above 1GHz


</td></tr>
<tr><td>Test Procedure:</td><td>
1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
</td></tr>
<tr><td>Test Instruments:</td><td>Refer to section 6.0 for details</td></tr>
<tr><td>Test mode:</td><td>Refer to section 5.2 for details</td></tr>
<tr><td>Test environment:</td><td>Temp.: | 25 °C | Humid.: | 50% | Press.: | 1 010mbar</td></tr>
<tr><td>Test results:</td><td>Pass</td></tr>
</table>

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
433.92	100.40	16.03	3.02	37.52	81.93	100.83	-18.9	Horizontal
433.92	96.65	16.03	3.02	37.52	78.18	100.83	-22.65	Vertical

Average value:

Frequency (MHz)	Peak Value (dBuV/m)	Duty cycle factor	Average value (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.92	81.93	-5.3	76.63	80.83	-4.2	Horizontal
433.92	78.18	-5.3	72.88	80.83	-7.95	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *Average value=Peak value + Duty cycle factor*

Average value:	
Calculate Formula:	Average value=Peak value + Duty Cycle Factor
	Duty cycle factor=20 log(Duty cycle)
	Duty cycle=on time/100 milliseconds or period, whichever is less
Test data:	T on time =54.33(ms)
	T period 100(ms)
	Duty cycle=0.5433
	duty cycle factor=-5.3



7.2.2 Spurious Emissions

Measurement data:

9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Below 1GHz:

Mode:	**Transmitting mode**	**Polarization:**	**Horizontal**



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
40.276	38.77	12.20	0.66	35.68	15.95	40.00	-24.05	QP
48.502	37.50	12.29	0.76	36.11	14.44	40.00	-25.56	QP
56.001	37.38	11.68	0.83	36.27	13.62	40.00	-26.38	QP
97.115	34.08	11.79	1.17	36.70	10.34	43.50	-33.16	QP
350.477	34.25	14.53	2.62	37.47	13.93	46.00	-32.07	QP
562.662	35.35	18.73	3.57	37.53	20.12	46.00	-25.88	QP

Mode:	Transmitting mode	Polarization:	Vertical



Freq	Reading level	Antenna factor	Cable loss	Preamp factor	level	Limit level	Over limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV	dBuV/m	dB	
40.276	38.16	12.20	0.66	35.68	15.34	40.00	-24.66	QP
45.375	38.21	12.26	0.72	35.96	15.23	40.00	-24.77	QP
93.440	33.25	11.25	1.14	36.67	8.97	43.50	-34.53	QP
216.024	38.21	11.02	1.93	37.35	13.81	46.00	-32.19	QP
414.722	32.93	15.63	2.92	37.52	13.96	46.00	-32.04	QP
558.730	32.63	18.62	3.56	37.53	17.28	46.00	-28.72	QP

Above 1G:

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1145	48.05	24.65	4.42	35.86	41.26	74.00	-32.74	Vertical
1550	49.47	25.59	4.71	36.21	43.56	74.00	-30.44	Vertical
1790	44.54	26.02	4.85	36.37	39.04	74.00	-34.96	Vertical
1530	47.95	25.55	4.7	36.19	42.01	74.00	-31.99	Horizontal
2065	45.68	26.57	5.04	36.56	40.73	74.00	-33.27	Horizontal
2095	43.69	26.65	5.07	36.59	38.82	74.00	-35.18	Horizontal

Remarks:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.231 (c)
Test Method:	ANSI C63.10:2013
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test Frequency (MHz)	20dB bandwidth (MHz)	Limit (MHz)	Result
433.92	0.097	1.085	Pass

Note: Limit= Fundamental frequency×0.25%

433.92×0.25%=1.085MHz

Test plot as follows:



7.4 Dwell Time

Test Requirement:	FCC Part15 C Section 15.231 (a)(2)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, span=0Hz, detector: Peak
Limit:	Not more than 5 seconds
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Frequency (MHz)	Duration of each TX (second)	Limit (second)	Result
433.92	0.05433	<5.0	Pass

Test plot as follows:





8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------ End ------