



Radio Test Report

Report No.: STS2603387W02

Issued for

Imagineear Ltd

The Blomfield Rooms, Fulham Palace, Bishop's Avenue,
London SW6 6EA United Kingdom

Product Name: Nostro

Brand Name: NA

Model Name: Nostro

Series Model(s): NA

FCC ID: 2ASPC-NOSTRO

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT****Applicant's Name** Imagineear LtdAddress The Blomfield Rooms, Fulham Palace, Bishop's Avenue, London SW6
6EA United Kingdom**Manufacturer's Name** Chempros LimitedAddress Unit 2312, Eastern Tower, Coastal Era Building, Nanshan, Shenzhen,
CHINA, 518051**Product Description**

Product Name Nostro

Brand Name NA

Model Name Nostro

Series Model(s) NA

Test Standards FCC Part15.247

Test Procedure ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item 2026-03-17

Date (s) of performance of tests 2026-03-17 to 2026-05-29

Date of Issue 2026-05-29

Test Result **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	9
2.3 TEST SOFTWARE AND POWER LEVEL	9
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	10
2.7 EQUIPMENTS LIST	11
3. EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.2 TEST PROCEDURE	13
3.3 TEST SETUP	13
3.4 EUT OPERATING CONDITIONS	13
4. RADIATED EMISSION MEASUREMENT	16
4.1 RADIATED EMISSION LIMITS	16
4.2 TEST PROCEDURE	18
4.3 TEST SETUP	19
4.4 EUT OPERATING CONDITIONS	19
4.5 FIELD STRENGTH CALCULATION	20
4.6 TEST RESULTS	21
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	29
5.1 LIMIT	29
5.2 TEST PROCEDURE	29
5.3 TEST SETUP	29
5.4 EUT OPERATION CONDITIONS	29
5.5 TEST RESULTS	29
6. POWER SPECTRAL DENSITY TEST	30
6.1 LIMIT	30
6.2 TEST PROCEDURE	30
6.3 TEST SETUP	30
6.4 EUT OPERATION CONDITIONS	30



Table of Contents	Page
6.5 TEST RESULTS	30
7. BANDWIDTH TEST	31
7.1 LIMIT	31
7.2 TEST PROCEDURE	31
7.3 TEST SETUP	31
7.4 EUT OPERATION CONDITIONS	31
7.5 TEST RESULTS	31
8. PEAK OUTPUT POWER TEST	32
8.1 LIMIT	32
8.2 TEST PROCEDURE	32
8.3 TEST SETUP	32
8.4 EUT OPERATION CONDITIONS	32
8.5 TEST RESULTS	32
9. ANTENNA REQUIREMENT	33
9.1 STANDARD REQUIREMENT	33
9.2 EUT ANTENNA	33
APPENDIX 1-TEST DATA	34
DUTY CYCLE	34
MAXIMUM CONDUCTED OUTPUT POWER	37
-6DB BANDWIDTH	38
MAXIMUM POWER SPECTRAL DENSITY LEVEL	41
BAND EDGE	44
CONDUCTED RF SPURIOUS EMISSION	48
APPENDIX 2- EUT TEST PHOTO	53



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	2026-05-29	STS2603387W02	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

Note:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Nostro	
Brand Name	NA	
Model Name	Nostro	
Series Model(s)	NA	
Model Difference	NA	
Product Description	The EUT is a Nostro	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	BLE(Support 1M/2M)
	Number Of Channel:	40
	Antenna Type:	Internal antenna
	Antenna Gain (dBi)	-1.98dBi
Channel List	Please refer to the Note 3.	
Power Rating	Input: DC 5V,1A	
Adapter	N/A	
Battery	DC 3.7V,5700mAh	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

For All Mode	Description	Modulation Type
Mode 1	CH00	GFSK(1Mbps)
Mode 2	CH19	
Mode 3	CH39	
Mode 4	CH00	GFSK(2Mbps)
Mode 5	CH19	
Mode 6	CH39	
Mode 7	Transmit mode (Radiated emission& Conducted Emission)	

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 TEST SOFTWARE AND POWER LEVEL


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
BLE	BLE_1M PHY	GFSK	-1.98	Default	adb
	BLE_2M PHY				


Note: The software cannot modify the power level; it can only use the default value.

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Device Type	Brand	Model	Note
E-1	Adapter	N/A	N/A	N/A

Item	Equipment	Mfr/Brand	Length	Note
C-1	Unshielded	NO	50cm	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.7 EQUIPMENTS LIST

RF Radiation Test Equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Pre-Amplifier(0.1 M-3GHz)	EM	EM330	060665	2026.02.04	2027.02.03
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2026.02.04	2027.02.03
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENGFENG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Limiter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2026.02.04	2027.02.03
Pulse Power Sensor	Anritsu	MA2411B	917389	2025.09.23	2026.09.22
Power Meter	Anritsu	ML2480	1005127	2025.09.23	2026.09.22
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2026.02.04	2027.02.03
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Test SW	MW	MTS 8310 2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT

Temperature:	26 °C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 7		




Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1725	33.22	10.71	43.93	64.84	-20.91	QP
2	0.1725	18.36	10.71	29.07	54.84	-25.77	AVG
3	0.2985	29.06	10.71	39.77	60.28	-20.51	QP
4	0.2985	17.28	10.71	27.99	50.28	-22.29	AVG
5	0.4155	26.20	10.73	36.93	57.54	-20.61	QP
6	0.4155	18.52	10.73	29.25	47.54	-18.29	AVG
7	0.8295	29.13	10.77	39.90	56.00	-16.10	QP
8 *	0.8295	19.95	10.77	30.72	46.00	-15.28	AVG
9	3.2415	24.40	11.70	36.10	56.00	-19.90	QP
10	3.2415	8.43	11.70	20.13	46.00	-25.87	AVG
11	24.0360	19.05	16.98	36.03	60.00	-23.97	QP
12	24.0360	8.24	16.98	25.22	50.00	-24.78	AVG



Temperature:	26 °C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 7		



Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1725	32.94	10.71	43.65	64.84	-21.19	QP
2	0.1725	18.21	10.71	28.92	54.84	-25.92	AVG
3	0.2985	30.57	10.71	41.28	60.28	-19.00	QP
4	0.2985	18.16	10.71	28.87	50.28	-21.41	AVG
5	0.4155	28.80	10.73	39.53	57.54	-18.01	QP
6	0.4155	17.50	10.73	28.23	47.54	-19.31	AVG
7	0.8880	27.46	10.88	38.34	56.00	-17.66	QP
8 *	0.8880	18.00	10.88	28.88	46.00	-17.12	AVG
9	3.2055	23.80	11.63	35.43	56.00	-20.57	QP
10	3.2055	6.39	11.63	18.02	46.00	-27.98	AVG
11	9.3255	20.87	13.51	34.38	60.00	-25.62	QP
12	9.3255	4.60	13.51	18.11	50.00	-31.89	AVG



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS



FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



4.6 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	25 °C	Relative Humidity:	54%
Test Voltage:	DC 3.7V	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



(30MHz -1000MHz)

Temperature:	25 °C	Relative Humidity:	54%
Test Voltage:	DC 3.7V	Phase:	Horizontal
Test Mode:	Mode 7		




Remark:

1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.7016	26.83	-10.82	16.01	40.00	-23.99	QP
2	51.8430	26.19	-10.56	15.63	40.00	-24.37	QP
3	154.8204	25.46	-9.79	15.67	43.50	-27.83	QP
4	360.4476	27.97	-9.34	18.63	46.00	-27.37	QP
5	779.6068	26.12	0.25	26.37	46.00	-19.63	QP
6 *	925.7563	32.65	0.48	33.13	46.00	-12.87	QP



Temperature:	25 °C	Relative Humidity:	54%
Test Voltage:	DC 3.7V	Phase:	Vertical
Test Mode:	Mode 7		



Remark:

1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.9942	25.99	-10.89	15.10	40.00	-24.90	QP
2	50.7637	25.91	-10.52	15.39	40.00	-24.61	QP
3	148.9625	26.12	-10.43	15.69	43.50	-27.81	QP
4	236.6447	32.77	-12.54	20.23	46.00	-25.77	QP
5	508.2582	26.21	-5.51	20.70	46.00	-25.30	QP
6 *	801.7863	24.71	0.44	25.15	46.00	-20.85	QP



(1GHz-25GHz) Spurious emission Requirements

1M PHY

GFSK

Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Detector Type
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low channel										
3264.88	61.87	44.70	6.70	28.20	-9.80	52.07	74.00	-21.93	PK	Vertical
3264.88	50.36	44.70	6.70	28.20	-9.80	40.56	54.00	-13.44	AV	Vertical
3264.67	61.02	44.70	6.70	28.20	-9.80	51.22	74.00	-22.78	PK	Horizontal
3264.67	51.28	44.70	6.70	28.20	-9.80	41.48	54.00	-12.52	AV	Horizontal
4804.35	59.25	44.20	9.04	31.60	-3.56	55.69	74.00	-18.31	PK	Vertical
4804.35	50.39	44.20	9.04	31.60	-3.56	46.83	54.00	-7.17	AV	Vertical
4804.46	59.05	44.20	9.04	31.60	-3.56	55.49	74.00	-18.51	PK	Horizontal
4804.46	50.06	44.20	9.04	31.60	-3.56	46.50	54.00	-7.50	AV	Horizontal
5359.80	49.04	44.20	9.86	32.00	-2.34	46.69	74.00	-27.31	PK	Vertical
5359.80	40.05	44.20	9.86	32.00	-2.34	37.71	54.00	-16.29	AV	Vertical
5359.86	48.15	44.20	9.86	32.00	-2.34	45.80	74.00	-28.20	PK	Horizontal
5359.86	39.38	44.20	9.86	32.00	-2.34	37.03	54.00	-16.97	AV	Horizontal
7205.79	54.22	43.50	11.40	35.50	3.40	57.62	74.00	-16.38	PK	Vertical
7205.79	44.04	43.50	11.40	35.50	3.40	47.44	54.00	-6.56	AV	Vertical
7205.84	53.83	43.50	11.40	35.50	3.40	57.23	74.00	-16.77	PK	Horizontal
7205.84	43.50	43.50	11.40	35.50	3.40	46.90	54.00	-7.10	AV	Horizontal
Middle channel										
3263.11	61.35	44.70	6.70	28.20	-9.80	51.55	74.00	-22.45	PK	Vertical
3263.11	51.28	44.70	6.70	28.20	-9.80	41.48	54.00	-12.52	AV	Vertical
3263.02	61.84	44.70	6.70	28.20	-9.80	52.04	74.00	-21.96	PK	Horizontal
3263.02	50.65	44.70	6.70	28.20	-9.80	40.85	54.00	-13.15	AV	Horizontal
4879.92	59.03	44.20	9.04	31.60	-3.56	55.47	74.00	-18.53	PK	Vertical
4879.92	50.35	44.20	9.04	31.60	-3.56	46.79	54.00	-7.21	AV	Vertical
4880.09	58.31	44.20	9.04	31.60	-3.56	54.75	74.00	-19.25	PK	Horizontal
4880.09	49.43	44.20	9.04	31.60	-3.56	45.87	54.00	-8.13	AV	Horizontal
5357.06	48.50	44.20	9.86	32.00	-2.34	46.16	74.00	-27.84	PK	Vertical
5357.06	39.58	44.20	9.86	32.00	-2.34	37.24	54.00	-16.76	AV	Vertical
5357.39	47.91	44.20	9.86	32.00	-2.34	45.57	74.00	-28.43	PK	Horizontal
5357.01	38.88	44.20	9.86	32.00	-2.34	36.54	54.00	-17.46	AV	Horizontal
7320.85	54.20	43.50	11.40	35.50	3.40	57.60	74.00	-16.40	PK	Vertical
7320.85	44.43	43.50	11.40	35.50	3.40	47.83	54.00	-6.17	AV	Vertical
7320.29	54.63	43.50	11.40	35.50	3.40	58.03	74.00	-15.97	PK	Horizontal
7320.29	44.31	43.50	11.40	35.50	3.40	47.71	54.00	-6.29	AV	Horizontal
High channel										
3264.73	62.11	44.70	6.70	28.20	-9.80	52.31	74.00	-21.69	PK	Vertical
3264.73	50.93	44.70	6.70	28.20	-9.80	41.13	54.00	-12.87	AV	Vertical
3264.79	61.02	44.70	6.70	28.20	-9.80	51.22	74.00	-22.78	PK	Horizontal
3264.79	50.47	44.70	6.70	28.20	-9.80	40.67	54.00	-13.33	AV	Horizontal
4960.53	59.12	44.20	9.04	31.60	-3.56	55.56	74.00	-18.44	PK	Vertical
4960.53	50.16	44.20	9.04	31.60	-3.56	46.60	54.00	-7.40	AV	Vertical
4960.55	59.12	44.20	9.04	31.60	-3.56	55.56	74.00	-18.44	PK	Horizontal
4960.55	50.05	44.20	9.04	31.60	-3.56	46.49	54.00	-7.51	AV	Horizontal
5359.85	49.34	44.20	9.86	32.00	-2.34	47.00	74.00	-27.00	PK	Vertical
5359.85	39.91	44.20	9.86	32.00	-2.34	37.56	54.00	-16.44	AV	Vertical
5359.58	48.55	44.20	9.86	32.00	-2.34	46.21	74.00	-27.79	PK	Horizontal
5359.58	38.62	44.20	9.86	32.00	-2.34	36.28	54.00	-17.72	AV	Horizontal
7439.89	54.95	43.50	11.40	35.50	3.40	58.35	74.00	-15.65	PK	Vertical



7439.89	43.76	43.50	11.40	35.50	3.40	47.16	54.00	-6.84	AV	Vertical
7439.79	54.35	43.50	11.40	35.50	3.40	57.75	74.00	-16.25	PK	Horizontal
7439.79	44.19	43.50	11.40	35.50	3.40	47.59	54.00	-6.41	AV	Horizontal

Note:

1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor.

2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.

2M PHY
GFSK

Frequency	Meter Reading	Amplifier	Loss	Antenna Factor	Corrected Factor	Emission Level	Limits	Margin	Detector	Detector Type
(MHz)	(dBμV)	(dB)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low channel										
3264.68	61.04	44.70	6.70	28.20	-9.80	51.24	74.00	-22.76	PK	Vertical
3264.68	51.17	44.70	6.70	28.20	-9.80	41.37	54.00	-12.63	AV	Vertical
3264.64	61.38	44.70	6.70	28.20	-9.80	51.58	74.00	-22.42	PK	Horizontal
3264.64	51.07	44.70	6.70	28.20	-9.80	41.27	54.00	-12.73	AV	Horizontal
4804.42	59.48	44.20	9.04	31.60	-3.56	55.92	74.00	-18.08	PK	Vertical
4804.42	49.71	44.20	9.04	31.60	-3.56	46.15	54.00	-7.85	AV	Vertical
4804.58	58.80	44.20	9.04	31.60	-3.56	55.24	74.00	-18.76	PK	Horizontal
4804.58	49.86	44.20	9.04	31.60	-3.56	46.30	54.00	-7.70	AV	Horizontal
5359.60	48.55	44.20	9.86	32.00	-2.34	46.20	74.00	-27.80	PK	Vertical
5359.60	39.53	44.20	9.86	32.00	-2.34	37.19	54.00	-16.81	AV	Vertical
5359.58	48.32	44.20	9.86	32.00	-2.34	45.97	74.00	-28.03	PK	Horizontal
5359.58	38.54	44.20	9.86	32.00	-2.34	36.19	54.00	-17.81	AV	Horizontal
7205.91	53.87	43.50	11.40	35.50	3.40	57.27	74.00	-16.73	PK	Vertical
7205.91	44.19	43.50	11.40	35.50	3.40	47.59	54.00	-6.41	AV	Vertical
7205.79	54.14	43.50	11.40	35.50	3.40	57.54	74.00	-16.46	PK	Horizontal
7205.79	43.50	43.50	11.40	35.50	3.40	46.90	54.00	-7.10	AV	Horizontal
Middle channel										
3263.17	62.15	44.70	6.70	28.20	-9.80	52.35	74.00	-21.65	PK	Vertical
3263.17	51.82	44.70	6.70	28.20	-9.80	42.02	54.00	-11.98	AV	Vertical
3263.17	60.98	44.70	6.70	28.20	-9.80	51.18	74.00	-22.82	PK	Horizontal
3263.17	51.30	44.70	6.70	28.20	-9.80	41.50	54.00	-12.50	AV	Horizontal
4879.90	58.20	44.20	9.04	31.60	-3.56	54.64	74.00	-19.36	PK	Vertical
4879.90	49.79	44.20	9.04	31.60	-3.56	46.23	54.00	-7.77	AV	Vertical
4880.09	59.07	44.20	9.04	31.60	-3.56	55.51	74.00	-18.49	PK	Horizontal
4880.09	49.47	44.20	9.04	31.60	-3.56	45.91	54.00	-8.09	AV	Horizontal
5357.23	49.39	44.20	9.86	32.00	-2.34	47.04	74.00	-26.96	PK	Vertical
5357.23	39.52	44.20	9.86	32.00	-2.34	37.18	54.00	-16.82	AV	Vertical
5357.39	47.38	44.20	9.86	32.00	-2.34	45.03	74.00	-28.97	PK	Horizontal
5357.00	38.07	44.20	9.86	32.00	-2.34	35.73	54.00	-18.27	AV	Horizontal
7320.85	54.03	43.50	11.40	35.50	3.40	57.43	74.00	-16.57	PK	Vertical
7320.85	43.99	43.50	11.40	35.50	3.40	47.39	54.00	-6.61	AV	Vertical
7320.42	53.94	43.50	11.40	35.50	3.40	57.34	74.00	-16.66	PK	Horizontal
7320.42	44.64	43.50	11.40	35.50	3.40	48.04	54.00	-5.96	AV	Horizontal
High channel										
3264.87	60.83	44.70	6.70	28.20	-9.80	51.03	74.00	-22.97	PK	Vertical
3264.87	50.36	44.70	6.70	28.20	-9.80	40.56	54.00	-13.44	AV	Vertical
3264.76	60.84	44.70	6.70	28.20	-9.80	51.04	74.00	-22.96	PK	Horizontal
3264.76	49.86	44.70	6.70	28.20	-9.80	40.06	54.00	-13.94	AV	Horizontal
4960.50	59.46	44.20	9.04	31.60	-3.56	55.90	74.00	-18.10	PK	Vertical
4960.50	49.45	44.20	9.04	31.60	-3.56	45.89	54.00	-8.11	AV	Vertical
4960.42	58.75	44.20	9.04	31.60	-3.56	55.19	74.00	-18.81	PK	Horizontal
4960.42	49.93	44.20	9.04	31.60	-3.56	46.37	54.00	-7.63	AV	Horizontal
5359.85	48.00	44.20	9.86	32.00	-2.34	45.66	74.00	-28.34	PK	Vertical
5359.85	39.20	44.20	9.86	32.00	-2.34	36.85	54.00	-17.15	AV	Vertical
5359.65	47.59	44.20	9.86	32.00	-2.34	45.25	74.00	-28.75	PK	Horizontal
5359.65	38.14	44.20	9.86	32.00	-2.34	35.80	54.00	-18.20	AV	Horizontal
7439.75	53.71	43.50	11.40	35.50	3.40	57.11	74.00	-16.89	PK	Vertical
7439.75	44.93	43.50	11.40	35.50	3.40	48.33	54.00	-5.67	AV	Vertical
7439.95	54.29	43.50	11.40	35.50	3.40	57.69	74.00	-16.31	PK	Horizontal



7439.95	44.21	43.50	11.40	35.50	3.40	47.61	54.00	-6.39	AV	Horizontal
---------	-------	-------	-------	-------	------	-------	-------	-------	----	------------

Note:

1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor.

2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



Restricted band Requirements

Test mode	Polar (H/V)	Frequenc y (MHz)	Measure- ment (dBuV/m)	Limits (dBuV/m)		Over	Result
			PK	PK	AV	PK	
GFSK 1M	Low Channel 2402MHz						
	H	2390.00	47.09	74.00	54.00	-26.91	PASS
	H	2400.00	49.83	74.00	54.00	-24.17	PASS
	V	2390.00	46.64	74.00	54.00	-27.36	PASS
	V	2400.00	47.15	74.00	54.00	-26.85	PASS
	High Channel 2480MHz						
	H	2483.50	46.00	74.00	54.00	-28.00	PASS
	H	2500.00	43.18	74.00	54.00	-30.82	PASS
	V	2483.50	47.41	74.00	54.00	-26.59	PASS
	V	2500.00	43.65	74.00	54.00	-30.35	PASS
GFSK 2M	Low Channel 2402MHz						
	H	2390.00	47.10	74.00	54.00	-26.90	PASS
	H	2400.00	50.06	74.00	54.00	-23.94	PASS
	V	2390.00	46.29	74.00	54.00	-27.71	PASS
	V	2400.00	47.89	74.00	54.00	-26.11	PASS
	High Channel 2480MHz						
	H	2483.50	45.90	74.00	54.00	-28.10	PASS
	H	2500.00	44.23	74.00	54.00	-29.77	PASS
	V	2483.50	46.32	74.00	54.00	-27.68	PASS
	V	2500.00	41.69	74.00	54.00	-32.31	PASS
Remark:							
1. Measurement = Reading Level + Correct Factor, Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.							
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB							
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.							

5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

5.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

6. POWER SPECTRAL DENSITY TEST

6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.

7. BANDWIDTH TEST

7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. PEAK OUTPUT POWER TEST

8.1 LIMIT


FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA


The EUT antenna is Internal antenna. It comply with the standard requirement.





APPENDIX 1-TEST DATA

Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	61.9	2.08	2.56
NVNT	BLE 1M	2440	60.32	2.2	2.63
NVNT	BLE 1M	2480	61.29	2.13	2.63
NVNT	BLE 2M	2402	56.91	2.45	0.93
NVNT	BLE 2M	2440	56.91	2.45	0.93
NVNT	BLE 2M	2480	57.22	2.42	0.93










Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	4.79	30	Pass
NVNT	BLE 1M	2440	5.34	30	Pass
NVNT	BLE 1M	2480	6.09	30	Pass
NVNT	BLE 2M	2402	4.84	30	Pass
NVNT	BLE 2M	2440	5.38	30	Pass
NVNT	BLE 2M	2480	6.2	30	Pass

**-6dB Bandwidth**

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	0.6764	0.5	Pass
NVNT	BLE 1M	2440	0.6805	0.5	Pass
NVNT	BLE 1M	2480	0.6633	0.5	Pass
NVNT	BLE 2M	2402	1.329	0.5	Pass
NVNT	BLE 2M	2440	1.23	0.5	Pass
NVNT	BLE 2M	2480	1.248	0.5	Pass












Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	-11.07	8	Pass
NVNT	BLE 1M	2440	-10.62	8	Pass
NVNT	BLE 1M	2480	-9.81	8	Pass
NVNT	BLE 2M	2402	-15.89	8	Pass
NVNT	BLE 2M	2440	-15.39	8	Pass
NVNT	BLE 2M	2480	-14.43	8	Pass













Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-58.87	-20	Pass
NVNT	BLE 1M	2480	-60.28	-20	Pass
NVNT	BLE 2M	2402	-40.34	-20	Pass
NVNT	BLE 2M	2480	-60.69	-20	Pass















Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-45.02	-20	Pass
NVNT	BLE 1M	2440	-45.76	-20	Pass
NVNT	BLE 1M	2480	-46.7	-20	Pass
NVNT	BLE 2M	2402	-45.05	-20	Pass
NVNT	BLE 2M	2440	-44.39	-20	Pass
NVNT	BLE 2M	2480	-45.89	-20	Pass











APPENDIX 2- EUT TEST PHOTO

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****