FCC TEST REPORT

Client Name	:	Shenzhen Lanlian Digital Technology Co., Ltd.
Address	:	424, Qingfeng Building, 11 Longgang Rd., Pingnan Community, Longgang Subdistrict, Longgang District, Shenzhen
Product Name	:	Wireless Charging Clock Speaker
Date	:	Jun. 16, 2021

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information....5
1.1. Client Information....5
1.2. Description of Device (EUT)....5
1.3. Auxiliary Equipment Used During Test....6
1.4. Description of Test Modes....7
1.5. List of channels....8
1.6. Description Of Test Setup....9
1.7. Test Equipment List....10
1.8. Measurement Uncertainty....11
1.9. Description of Test Facility....11
2. Summary of Test Results....12
3. Conducted Emission Test....13
3.1. Test Standard and Limit....13
3.2. Test Setup....13
3.3. Test Procedure....13
3.4. Test Data....13
4. Radiation Spurious Emission and Band Edge....19
4.1. Test Standard and Limit....19
4.2. Test Setup....19
4.3. Test Procedure....20
4.4. Test Data....21
5. Maximum Peak Output Power Test....29
5.1. Test Standard and Limit....29
5.2. Test Setup....29
5.3. Test Procedure....29
5.4. Test Data....29
6. 6DB Occupy Bandwidth Test....32
6.1. Test Standard and Limit....32
6.2. Test Setup....32
6.3. Test Procedure....32
6.4. Test Data....32
7. Power Spectral Density Test....35
7.1. Test Standard and Limit....35
7.2. Test Setup....35
7.3. Test Procedure....35
7.4. Test Data....35
8. 100kHz Bandwidth of Frequency Band Edge Requirement....38
8.1. Test Standard and Limit....38
8.2. Test Setup....38

8.3. Test Procedure....38
8.4. Test Data....38
9. Antenna Requirement....42
9.1. Test Standard and Requirement....42
9.2. Antenna Connected Construction....42
APPENDIX I -- TEST SETUP PHOTOGRAPH....43
APPENDIX II -- EXTERNAL PHOTOGRAPH....45
APPENDIX III -- INTERNAL PHOTOGRAPH....49

TEST REPORT

Applicant	:	Shenzhen Lanlian Digital Technology Co., Ltd.
Manufacturer	:	Dongguan Chuanglian Technology Co., Ltd.
Product Name	:	Wireless Charging Clock Speaker
Model No.	:	WD-300, WD-300 5~15W, WD-300A, WD-300B, WD-300C, WD-300D
Trade Mark	:	N.A
Rating(s)	:	Input: DC 5V/3A, DC 9V/2A, DC 12V/1.5A Output: DC 5V/1A Output power: 5W/7.5W/10W/15W Max
Test Standard(s)	:	**FCC Part15 Subpart C, Section 15.247**
Test Method(s)	:	**ANSI C63.10: 2013, KDB 558074 D01 15.247 Meas Guidance v05r02**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt	Apr. 15, 2021
Date of Test	Apr. 16~May 25, 2021
Reviewer	(Ella Liang)
Approved & Authorized Signer	(Kingkong Jin)

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Lanlian Digital Technology Co., Ltd.
Address	:	424, Qingfeng Building, 11 Longgang Rd., Pingnan Community, Longgang Subdistrict, Longgang District, Shenzhen
Manufacturer	:	Dongguan Chuanglian Technology Co., Ltd.
Address	:	Level 3,Building 3,No.19 Jinpeng Road,Fenggang Town, Dongguan, Guangdong, China
Factory	:	Dongguan Chuanglian Technology Co., Ltd.
Address	:	Level 3,Building 3,No.19 Jinpeng Road,Fenggang Town,Dongguan

1.2. Description of Device (EUT)

Product Name	:	Wireless Charging Clock Speaker	
Model No.	:	WD-300, WD-300 5~15W, WD-300A, WD-300B, WD-300C, WD-300D (Note: All samples are the same except mode name, so we prepare "WD-300" for test only.)	
Trade Mark	:	N.A	
Test Power Supply	:	AC 120V,60Hz for adapter/ AC 240V,60Hz for adapter	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	BDR+EDR:2402~2480MHz BLE: 2402~2480MHz WPT: 110.1-205KHz
		Number of Channel:	BDR+EDR: 79 Channels BLE: 40 Channels
		Modulation Type:	BDR+EDR: GFSK, π/4-DQPSK BLE: GFSK WPT: FSK
		Antenna Type:	BDR+EDR+BLE: PCB Antenna WPT: Inductive loop coil Antenna
		Antenna Gain(Peak):	BDR+EDR: -0.58 dBi BLE: -0.58 dBi WPT: 0 dBi
		Operation Frequency:	BDR+EDR:2402~2480MHz BLE: 2402~2480MHz WPT: 110.1-205KHz
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2)This report is for BT 5.0 BLE module.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: HA712 S/N: FCHA7121937001132 Input: 100-240V~ 50/60Hz, 1.5A Output: DC 5V/3A, DC9V/3A, DC12V/3A, DC15V/3A, DC20V/3.25A
Wireless charging load	:	Manufacturer: Gopod Group Holding Limited. M/N: DTE324EM Power: 5W/7.5W/10W/15W Last Cal.: Oct. 30, 2020 Cal. Interval: 1 Year

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	
Mode 1	CH00	TX+ Charging Mode
Mode 2	CH19	
Mode 3	CH39	

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotek.com
Hotline 400-003-0500
www.anbotek.com

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 26, 2020	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 26, 2020	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 26, 2020	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 26, 2020	1 Year
5.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Oct. 26, 2020	1 Year
7.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 02, 2020	2 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 02, 2020	2 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 02, 2020	2 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Nov. 02, 2020	2 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 26, 2020	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	RF Test Control System	YIHENG	YH3000	2017430	Oct. 26, 2020	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN045	Oct. 26, 2020	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN046	Oct. 26, 2020	1 Year
16.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 26, 2020	1 Year
17.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 26, 2020	1 Year
18.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 26, 2020	1 Year
19.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 26, 2020	1 Year
20.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 26, 2020	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, and found the “Low CH” which is the worst case, only the worst case is recorded in the report.

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 24.4℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3899	16.76	19.93	36.69	58.06	-21.37	QP	
2	0.3899	10.24	19.93	30.17	48.06	-17.89	AVG	
3	0.4700	16.91	19.97	36.88	56.51	-19.63	QP	
4	0.4940	1.87	19.98	21.85	46.10	-24.25	AVG	
5	1.3580	15.01	20.13	35.14	56.00	-20.86	QP	
6	1.3580	5.04	20.13	25.17	46.00	-20.83	AVG	
7	2.7340	13.91	20.15	34.06	56.00	-21.94	QP	
8	2.7340	6.46	20.15	26.61	46.00	-19.39	AVG	
9	4.7020	10.75	20.20	30.95	56.00	-25.05	QP	
10	4.7020	4.60	20.20	24.80	46.00	-21.20	AVG	
11	13.9780	16.68	20.28	36.96	60.00	-23.04	QP	
12	15.3660	7.99	20.27	28.26	50.00	-21.74	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.4℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3899	9.46	19.93	29.39	48.06	-18.67	AVG	
2	0.3940	20.57	19.93	40.50	57.98	-17.48	QP	
3	1.1740	16.19	20.12	36.31	56.00	-19.69	QP	
4	2.3300	17.04	20.15	37.19	56.00	-18.81	QP	
5	2.3300	8.36	20.15	28.51	46.00	-17.49	AVG	
6	2.7340	16.52	20.15	36.67	56.00	-19.33	QP	
7	2.7340	8.86	20.15	29.01	46.00	-16.99	AVG	
8	3.1099	16.11	20.16	36.27	56.00	-19.73	QP	
9	3.1099	7.97	20.16	28.13	46.00	-17.87	AVG	
10	4.7020	14.76	20.20	34.96	56.00	-21.04	QP	
11	4.7020	6.91	20.20	27.11	46.00	-18.89	AVG	
12	14.2060	8.62	20.27	28.89	50.00	-21.11	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 24.4℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3940	19.64	19.93	39.57	57.98	-18.41	QP	
2	0.3940	4.74	19.93	24.67	47.98	-23.31	AVG	
3	0.4500	17.10	19.96	37.06	56.87	-19.81	QP	
4	0.5540	0.15	20.00	20.15	46.00	-25.85	AVG	
5	0.5700	14.03	20.00	34.03	56.00	-21.97	QP	
6	1.1780	1.17	20.12	21.29	46.00	-24.71	AVG	
7	1.3820	15.95	20.13	36.08	56.00	-19.92	QP	
8	1.6660	-0.04	20.13	20.09	46.00	-25.91	AVG	
9	3.0700	1.14	20.16	21.30	46.00	-24.70	AVG	
10	3.1180	14.98	20.16	35.14	56.00	-20.86	QP	
11	4.5660	13.33	20.19	33.52	56.00	-22.48	QP	
12	4.8940	1.37	20.20	21.57	46.00	-24.43	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.4℃ Hum.: 49%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1980	20.52	19.90	40.42	63.69	-23.27	QP	
2	0.3339	17.55	19.91	37.46	59.35	-21.89	QP	
3	0.4500	19.26	19.96	39.22	56.87	-17.65	QP	
4	0.4500	5.34	19.96	25.30	46.87	-21.57	AVG	
5	0.5580	14.24	20.00	34.24	56.00	-21.76	QP	
6	0.5580	1.95	20.00	21.95	46.00	-24.05	AVG	
7	1.0980	12.47	20.12	32.59	56.00	-23.41	QP	
8	1.1940	1.12	20.12	21.24	46.00	-24.76	AVG	
9	1.4740	12.57	20.13	32.70	56.00	-23.30	QP	
10	1.8900	-0.94	20.14	19.20	46.00	-26.80	AVG	
11	2.3780	-1.77	20.15	18.38	46.00	-27.62	AVG	
12	4.5700	-1.38	20.20	18.82	46.00	-27.18	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, pre-scan all the modes, and found the Low channel(TX Only) which is the worst case, only the worst case is recorded in the report.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: AC 120V/60Hz

Polarization: Vertical

Temp.(℃)/Hum.(%RH): 24.8℃/53%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.8878	38.74	-14.18	24.56	40.00	-15.44	QP	100	360	
2	47.8260	40.14	-14.52	25.62	40.00	-14.38	QP	100	0	
3	62.4314	39.13	-17.07	22.06	40.00	-17.94	QP	100	360	
4	157.0074	49.83	-19.56	30.27	43.50	-13.23	QP	100	0	
5	480.5276	40.34	-9.21	31.13	46.00	-14.87	QP	100	360	
6	552.8832	35.50	-7.96	27.54	46.00	-18.46	QP	100	0	

Test Results (30~1000MHz)

Test Mode: Mode 1

Power Source: AC 120V/60Hz

Polarization: Horizontal

Temp.(℃)/Hum.(%RH): 22.4℃/47%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	96.0986	37.65	-19.76	17.89	43.50	-25.61	QP	100	360	
2	160.9089	48.94	-21.75	27.19	43.50	-16.31	QP	100	0	
3	258.3264	43.34	-18.08	25.26	46.00	-20.74	QP	100	360	
4	287.9904	49.84	-15.39	34.45	46.00	-11.55	QP	100	0	
5	383.9318	43.47	-12.98	30.49	46.00	-15.51	QP	100	360	
6	672.8444	37.04	-6.44	30.60	46.00	-15.40	QP	100	0	

Test Results (1GHz-25GHz)

Test Mode: CH00					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	38.17	34.04	6.58	34.09	44.70	74.00	-29.30	V
7206.00	32.41	37.11	7.73	34.50	42.75	74.00	-31.25	V
9608.00	31.98	39.31	9.23	34.79	45.73	74.00	-28.27	V
12010.00	*					74.00		V
14412.00	*					74.00		V
4804.00	42.64	34.04	6.58	34.09	49.17	74.00	-24.83	H
7206.00	34.24	37.11	7.73	34.50	44.58	74.00	-29.42	H
9608.00	31.49	39.31	9.23	34.79	45.24	74.00	-28.76	H
12010.00	*					74.00		H
14412.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	26.82	34.04	6.58	34.09	33.35	54.00	-20.65	V
7206.00	20.99	37.11	7.73	34.50	31.33	54.00	-22.67	V
9608.00	20.02	39.31	9.23	34.79	33.77	54.00	-20.23	V
12010.00	*					54.00		V
14412.00	*					54.00		V
4804.00	31.15	34.04	6.58	34.09	37.68	54.00	-16.32	H
7206.00	23.23	37.11	7.73	34.50	33.57	54.00	-20.43	H
9608.00	19.82	39.31	9.23	34.79	33.57	54.00	-20.43	H
12010.00	*					54.00		H
14412.00	*					54.00		H

Test Results (1GHz-25GHz)

Test Mode: CH19					Test channel: Middle			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	36.90	34.38	6.69	34.09	43.88	74.00	-30.12	V
7320.00	31.56	37.22	7.78	34.53	42.03	74.00	-31.97	V
9760.00	31.23	39.46	9.35	34.80	45.24	74.00	-28.76	V
12200.00	*					74.00		V
14640.00	*					74.00		V
4880.00	41.10	34.38	6.69	34.09	48.08	74.00	-25.92	H
7320.00	33.28	37.22	7.78	34.53	43.75	74.00	-30.25	H
9760.00	30.61	39.46	9.35	34.80	44.62	74.00	-29.38	H
12200.00	*					74.00		H
14640.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	25.80	34.38	6.69	34.09	32.78	54.00	-21.22	V
7320.00	20.30	37.22	7.78	34.53	30.77	54.00	-23.23	V
9760.00	19.40	39.46	9.35	34.80	33.41	54.00	-20.59	V
12200.00	*					54.00		V
14640.00	*					54.00		V
4880.00	29.98	34.38	6.69	34.09	36.96	54.00	-17.04	H
7320.00	22.45	37.22	7.78	34.53	32.92	54.00	-21.08	H
9760.00	19.10	39.46	9.35	34.80	33.11	54.00	-20.89	H
12200.00	*					54.00		H
14640.00	*					54.00		H

Test Results (1GHz-25GHz)

Test Mode: CH39					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	36.50	34.72	6.79	34.09	43.92	74.00	-30.08	V
7440.00	31.30	37.34	7.82	34.57	41.89	74.00	-32.11	V
9920.00	31.00	39.62	9.46	34.81	45.27	74.00	-28.73	V
12400.00	*					74.00		V
14880.00	*					74.00		V
4960.00	40.63	34.72	6.79	34.09	48.05	74.00	-25.95	H
7440.00	32.98	37.34	7.82	34.57	43.57	74.00	-30.43	H
9920.00	30.34	39.62	9.46	34.81	44.61	74.00	-29.39	H
12400.00	*					74.00		H
14880.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	25.53	34.72	6.79	34.09	32.95	54.00	-21.05	V
7440.00	20.12	37.34	7.82	34.57	30.71	54.00	-23.29	V
9920.00	19.24	39.62	9.46	34.81	33.51	54.00	-20.49	V
12400.00	*					54.00		V
14880.00	*					54.00		V
4960.00	29.70	34.72	6.79	34.09	37.12	54.00	-16.88	H
7440.00	22.25	37.34	7.82	34.57	32.84	54.00	-21.16	H
9920.00	18.92	39.62	9.46	34.81	33.19	54.00	-20.81	H
12400.00	*					54.00		H
14880.00	*					54.00		H

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: CH00	Test channel: Lowest
	
Peak Value(Vertical)	Peak Value(Horizontal)
	
Average Value(Vertical)	Average Value(Horizontal)

Test Mode: CH39	Test channel: Highest
	
Peak Value(Vertical)	Peak Value(Horizontal)
	
Average Value(Vertical)	Average Value(Horizontal)

Remark:

1. Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	30dBm

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW ≥DTS bandwidth.
2. Set the VBW≥3*RBW.
3. Set the span≥ 3*RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Test Item	:	Max. peak output power	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V,60Hz for adapter	Temperature	:	24℃
Test Result	:	PASS	Humidity	:	55%RH

Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
2402	-1.188	30	PASS
2440	-1.997	30	PASS
2480	-0.213	30	PASS



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Swept SA
Marker 1 2.480135000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
06:38:08 PM May 28, 2021
Mkr1 2.480 135 GHz
-0.213 dBm
10 dB/div
Log
Ref 20.00 dBm
Center 2.480000 GHz
#Res BW 1.0 MHz
#VBW 3.0 MHz
Span 5.000 MHz
Sweep 1.000 ms (1001 pts)

CH: High

6. 6DB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 100kHz, VBW≥3*RBW =300kHz,
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and –6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Test Item	:	6dB Bandwidth	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V,60Hz for adapter	Temperature	:	24℃
Test Result	:	PASS	Humidity	:	55%RH

Channel	Frequency(MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	2402	695.0	>500	PASS
Middle	2440	691.9		PASS
High	2480	698.3		PASS

CH: Low



CH: Middle


Agilent Spectrum Analyzer - Occupied BW
Center Freq 2.480000000 GHz
Center Freq: 2.480000000 GHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 30 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
06:38:36 PM May 28, 2021
10 dB/div
Ref 20.00 dBm
Log
Center 2.48 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 3 MHz
Sweep 1 ms
Occupied Bandwidth
1.0391 MHz
Total Power 6.26 dBm
Transmit Freq Error -117 Hz
OBW Power 99.00 %
x dB Bandwidth 698.3 kHz
x dB -6.00 dB

CH: High

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Test Item	:	Power Spectral Density	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V,60Hz for adapter	Temperature	:	24℃
Test Result	:	PASS	Humidity	:	55%RH

Channel	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Results
Low	2402	-15.951	8.00	PASS
Middle	2440	-16.826	8.00	PASS
High	2480	-20.903	8.00	PASS



CH: Low

CH: Middle


Keysight Spectrum Analyzer - Swept SA
RL
RF
50 Ω AC
SENSE:PULSE
ALIGN OFF
03:14:34 PM Apr 28, 2021
Marker 1 2.479776563000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 78/100
TRACE 1 2 3 4 5 6
TYPE M
DET P N N N N N
Mkr1 2.479 776 6 GHz
-20.903 dBm
10 dB/div
Log
Ref 20.00 dBm
10.0
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
1
Center 2.4800000 GHz
#Res BW 3.0 kHz
#VBW 10 kHz
Span 1.049 MHz
Sweep 110.7 ms (1001 pts)
MSG
STATUS

CH: High

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Test Item	:	Band edge	Test Mode	:	CH Low ~ CH High
Test Voltage	:	AC 120V,60Hz for adapter	Temperature	:	24℃
Test Result	:	PASS	Humidity	:	55%RH



CH: Low



CH: High

Conducted Emission Method



CH: Low



CH: Middle


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 11/100
06:41:01 PM May 28, 2021
Mkr1 2.480 GHz
-0.790 dBm
10 dB/div
Ref 20.00 dBm
Log
-20.78 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)
1 N 1 f 2.480 GHz -0.790 dBm
2 N 1 f 7.446 GHz -52.267 dBm

CH: High

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is -0.58dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement

Photo of Radiation Emission Test



16:12

APPENDIX II -- EXTERNAL PHOTOGRAPH

In
Card
Out
Aux

APPENDIX III -- INTERNAL PHOTOGRAPH









---------- End of Report ----------