



TEST REPORT

Test item description: Digital Projector
FCC ID: 2ASRT-NPX760
Trademark(s): PHILIPS
Model/Type reference: NeoPix 760 Smart, NPX760
Applicant's name: Screeneo Innovation SA
Address: 8A route de Suisse, 1163 Etoy - Switzerland
Manufacturer: Screeneo Innovation SA
Address: 8A route de Suisse, 1163 Etoy - Switzerland
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Jul. 19, 2026
Sample tested Date: Jul. 19, 2026 to Aug. 21, 2026
Issue Date: Aug. 21, 2026
Report No.: CTB26071900312RF04
Test Standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Test Results: PASS
Remark: This is WIFI-5GHz band radio test report.
Compiled by: Reviewed by: Approved by:

Kai Chen

Kai Chen

Martin Feng

Martin FengBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty. "★" indicates the testing items were fulfilled by subcontracted lab. "※" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	4
2. TEST SUMMARY	5
3. MEASUREMENT UNCERTAINTY	6
4. PRODUCT INFORMATION AND TEST SETUP.....	7
4.1 Product Information	7
4.2 Test Setup Configuration.....	7
4.3 Support Equipment.....	7
4.4 Channel List.....	8
4.5 Test Mode.....	8
4.6 Test Environment	9
5. TEST FACILITY AND TEST INSTRUMENT USED	10
5.1 Test Facility.....	10
5.2 Test Instrument Used	10
6. AC POWER LINE CONDUCTED EMISSION	13
6.1 Block Diagram Of Test Setup.....	13
6.2 Limit	13
6.3 Test procedure	13
6.4 Test Result.....	15
7. RADIATED SPURIOUS EMISSIONS	17
7.1 Block Diagram Of Test Setup.....	17
7.2 Limit	17
7.3 Test procedure	18
7.4 Test Result.....	19
8. BAND EDGE	24
8.1 Block Diagram Of Test Setup.....	24
8.2 Limit	24
8.3 Test procedure	24
8.4 Test Result.....	25
9. CONDUCTED OUTPUT POWER.....	33
9.1 Block Diagram Of Test Setup.....	33
9.2 Limit	33

9.3	Test procedure	34
9.4	Test Result.....	35
10.	EMISSION BANDWIDTH& OCCUPIED BANDWIDTH	57
10.1	Block Diagram Of Test Setup.....	57
10.2	Limits	57
10.3	Test Procedure	57
10.4	Test Results.....	59
11.	POWER SPECTRAL DENSITY	71
11.1	Block Diagram Of Test Setup.....	71
11.2	Limit	71
11.3	Test procedure	71
11.4	Test Result.....	73
12.	FREQUENCY STABILITY	84
12.1	Block Diagram Of Test Setup.....	84
12.2	Limit	84
12.3	Test procedure	84
12.4	Test Result.....	84
13.	OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT.....	97
13.1	Requirement	97
13.2	Test Results.....	97
14.	ANTENNA REQUIREMENT	98
15.	EUT TEST SETUP PHOTOGRAPHS	99

(Note: N/A means not applicable)

1. **VERSION**

Report No.	Issue Date	Description	Approved
CTB26071900312RF04	Aug. 21, 2026	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	ANSI C63.10-2020	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Band edge	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Emission Bandwidth & Occupied Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033	PASS
Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033	PASS
Operation in the absence of information to the transmit	47 CFR Part 15 Subpart E Section 15.407 (b)	47 CFR Part 15 Subpart E	PASS
Antenna Requirement	47 CFR Part 15 Subpart E Section 15.203	/	PASS

Remark:

Test according to ANSI C63.10-2020.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	U=±54.3Hz
Adjacent channel power	U=±1.3dB
Conducted Adjacent channel power	U=±1.38dB
Conducted output power above 1G	U=±1.0dB
Conducted output power below 1G	U=±0.9dB
Power Spectral Density, Conduction	U=±1.0dB
Conduction spurious emissions	U=±2.8dB
Out of band emission	U=±54Hz
3m camber Radiated spurious emission(9kHz-30MHz)	U=±4.8dB
3m camber Radiated spurious emission(30MHz-1GHz)	U=±4.3dB
3m chamber Radiated spurious emission(1GHz-18GHz)	U=±4.5dB
3m chamber Radiated spurious emission(18GHz-40GHz)	U=±3.4dB
Humidity uncertainty	U=±5.3%
Temperature uncertainty	U=±0.59℃
Supply voltages	U=±3%
Time	U=±5%
Conducted emission(150k-30MHz)	3.2dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model/Type reference:	NeoPix 760 Smart, NPX760
Model Description:	All the model are the same circuit and RF module, only the model names are different. Test sample model: NeoPix 760 Smart
Wi-Fi Specification:	IEEE 802.11a/n/ac
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac(80M): 5150MHz ~5250MHz/ 1 channel IEEE 802.11a/n/ac(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac(80M): 5725MHz ~5850MHz/ 1 channel
Max. RF output power:	WiFi (5G): 17.479dBm
Type of Modulation:	WiFi (5G): OFDM
Antenna installation:	WiFi (5G): PCB antenna WiFi (5.2G): Ant1: 3.98dBi Ant2: 3.77dBi
Antenna Gain:	WiFi (5.8G): Ant1: 5.81dBi Ant2: 2.63dBi
Ratings:	100-240V~, 50/60GHz, 2 A

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Laptop	DELL	Vostro 5490	N/A	AE

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

For 802.11a/n/ac(20M) Operation in the 5180MHz ~5240 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac(20M) Operation in the 5745MHz ~5825 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA

For 802.11n/ac(40M) Operation in the 5190MHz ~5230 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac(40M) Operation in the 5755MHz ~5795 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

For 802.11ac(80M) Operation in the 5210 MHz band			
Channel	Frequency	Channel	Frequency
42	5210MHz	NA	NA
For 802.11ac(80M) Operation in the 5775 MHz band			
Channel	Frequency	Channel	Frequency
155	5775MHz	NA	NA

NOTE: Duty cycle>98%.

Test mode	Rate
802.11a	54M
802.11n	500M
802.11/ac	500M

4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac(20M)	5180MHz ~5240 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac(40M)		Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11ac(80M)	5745MHz ~5825MHz	N/A	Channel 42	N/A
		N/A	5210MHz	N/A
802.11a/n/ac(20M)		Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac(40M)		Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz
802.11ac(80M)		N/A	Channel 155	N/A
		N/A	5775MHz	N/A

EUT has two Internal Antenna with Max Antenna Gain 5.81dBi on every antenna, CDD device with one spatial streams, according to KDB662911 D01 v02r01,

Directional gain= GANT + Array Gain, where Array Gain is as follows.

1) For power spectral density(PSD) measurements,

Array Gain= $10\log(\text{NANT}/\text{NSS})\text{dB}=10\log(2/1)=3.01\text{dB}$,

So the directional gain for PSD is 8.82dBi

2) For power measurements,

The Array gain=0 dB for $\text{NANT}\leq 4$,

So the directional gain for Power measurements is 5.81dBi

NOTE: Duty cycle>98%.

4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(AC):	120V
Normal Temperature(°C):NT	23
Low Temperature(°C):LT	0
High Temperature(°C):HT	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: CN1276

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated Date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2026/5/14	2027/5/13
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2026/5/14	2027/5/13
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2026/5/14	2027/5/13
4	Communication test set	R&S	CMW500	108058	V3.5.80	2026/5/14	2027/5/13
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2026/5/14	2027/5/13
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2026/5/14	2027/5/13
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2026/5/14	2027/5/13
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2026/5/14	2027/5/13
9	2.4 GHz Filter	Shenxiang	MSF2400-24 83.5MS-1154	20181015001	/	2026/5/16	2027/5/15
10	5 GHz Filter	Shenxiang	MSF5150-58 50MS-1155	20181015001	/	2026/5/16	2027/5/15
11	Filter	Xingbo	XBLBQ-DZA1 20	190821-1-1	/	2026/5/16	2027/5/15
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2025/10/20	2026/10/19
14	Temperature humidity chamber	Huitai	HT-HW-1000 L	/	/	2026/7/8	2027/7/7
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/	/
16	966 chamber	C.R.T.	966	/	/	2024/6/23	2027/6/22
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7	2026/5/15	2027/5/14

					(104489/003)		
18	Amplifier	HP	8447E	2945A02747	/	2026/5/15	2027/5/14
19	Amplifier	Agilent	8449B	3008A01838	/	2026/5/14	2027/5/13
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2026/5/17	2027/5/16
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2026/5/15	2027/5/14
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2026/5/17	2027/5/16
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/	/
25	40G Horn antenna	Schwarzbeck	BBHA9170	/	/	2026/5/15	2027/5/14
26	Amplifier	AEROFLEX	DLNA8-18-40 G-4063	03266684	/	2026/5/26	2027/5/25
27	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2026/5/15	2027/5/14
28	Horn Antenna	Rohde&Schwarz	BBHA9170	/	/	2026/5/15	2027/5/14


Continuous disturbance							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2024/6/22	2027/6/21
2	LISN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2026/5/14	2027/5/13
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2026/5/15	2027/5/14
4	Coaxial cable	ZDECL	Z302S	18091904	/	2026/5/14	2027/5/13
5	ISN	Schwarzbeck	NTFM8158	183	/	2026/5/18	2027/5/17
6	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2026/5/16	2027/5/15
7	EZ-EMC	Frad	EMC-con3A1.1	/	/	/	/
8	Current Probe	FCC	F-52B	199453	/	2026/5/22	2027/5/21
9	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2026/5/14	2027/5/13
10	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2026/5/14	2027/5/13

Radiated emission(No.1 Chamber)							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated until	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2024/6/23	2027/6/22
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2026/5/15	2027/5/14
3	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2026/5/17	2027/5/16

4	Amplifier	Agilent	8449B	3008A01838	/	2026/5/14	2027/5/13
5	Amplifier	HP	8447E	2945A02747	/	2026/5/15	2027/5/14
6	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2026/5/17	2027/5/16
7	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI	100362	RF_ATTEN_7 (104489/003)	2026/5/15	2027/5/14
8	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2026/5/14	2027/5/13
9	Coaxial cable	ETS	RFC-SNS-100-NMS-80	/	/	2026/5/14	2027/5/13
10	Coaxial cable	ETS	RFC-SN-100-NMS-20	/	/	2026/5/14	2027/5/13
11	Coaxial cable	ETS	RFC-SNS-100-SMS-20	/	/	2026/5/14	2027/5/13
12	Coaxial cable	ETS	RFC-NNS-100-NMS-300	/	/	2026/5/14	2027/5/13
13	EMI test software	Frad	EZ-EMC	Ver/ FA-03A2 RE	/	/	/
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2026/5/14	2027/5/13
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2026/5/14	2027/5/13

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane.


This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4 Test Result

Modulation: 802.11a (the worst data)

L:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1539	42.21	10.87	53.08	65.79	-12.71	QP
2		0.1539	9.74	10.87	20.61	55.79	-35.18	AVG
3		0.1980	39.23	10.76	49.99	63.69	-13.70	QP
4		0.1980	30.00	10.76	40.76	53.69	-12.93	AVG
5		0.5979	35.43	10.47	45.90	56.00	-10.10	QP
6	*	0.5979	28.22	10.47	38.69	46.00	-7.31	AVG
7		2.1900	37.91	10.47	48.38	56.00	-7.62	QP
8		2.1900	24.35	10.47	34.82	46.00	-11.18	AVG
9		6.0658	38.84	10.53	49.37	60.00	-10.63	QP
10		6.0658	28.54	10.53	39.07	50.00	-10.93	AVG
11		24.7379	36.92	11.26	48.18	60.00	-11.82	QP
12		24.7379	27.49	11.26	38.75	50.00	-11.25	AVG

Remark:

Factor = Cable loss + LISN factor, Margin = Measurement – Limit

N:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1539	42.21	10.87	53.08	65.79	-12.71	QP
2		0.1539	11.35	10.87	22.22	55.79	-33.57	AVG
3		0.1980	38.23	10.76	48.99	63.69	-14.70	QP
4		0.1980	29.00	10.76	39.76	53.69	-13.93	AVG
5		0.5979	34.93	10.47	45.40	56.00	-10.60	QP
6	*	0.5979	27.52	10.47	37.99	46.00	-8.01	AVG
7		2.1900	34.91	10.47	45.38	56.00	-10.62	QP
8		2.1900	23.30	10.47	33.77	46.00	-12.23	AVG
9		5.1619	32.60	10.51	43.11	60.00	-16.89	QP
10		5.1619	22.67	10.51	33.18	50.00	-16.82	AVG
11		24.7379	33.42	11.26	44.68	60.00	-15.32	QP
12		24.7379	23.99	11.26	35.25	50.00	-14.75	AVG

Remark:

- Factor = Cable loss + LISN factor, Margin = Limit – Level
- All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
- All the test modes completed for test. Only the worst result of was reported.

7. RADIATED SPURIOUS EMISSIONS

7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F \text{ (kHz)} + 80$	Quasi-peak	3
0.490MHz-1.705MHz	$20\log 24000/F \text{ (kHz)} + 40$	Quasi-peak	3
1.705MHz-30MHz	$20\log 30 + 40$	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

If radiated measurements are performed, field strength is then converted to EIRP as follows:

(i) $EIRP = ((E \cdot d)^2) / 30$

where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

(ii) Working in dB units, the above equation is equivalent to:

$$EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$$

(iii) Or, if d is 3 meters:

$$EIRP[dBm] = E[dB\mu V/m] - 95.2$$

7.3 Test procedure

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

7.4 Test Result

30MHz-1GHz Test Results:

Modulation: 802.11a (the worst data)

Test Channel: 5780MHz

Antenna polarity: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		150.5377	38.02	-4.53	33.49	43.50	-10.01	QP
2		237.4755	44.01	-6.66	37.35	46.00	-8.65	QP
3		300.8942	36.44	-3.29	33.15	46.00	-12.85	QP
4		555.7989	34.23	1.69	35.92	46.00	-10.08	QP
5	*	742.2586	34.82	6.66	41.48	46.00	-4.52	QP
6		932.2712	31.32	8.58	39.90	46.00	-6.10	QP

Antenna polarity: V



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	43.3534	40.68	-5.81	34.87	40.00	-5.13	QP
2		139.1168	41.84	-5.31	36.53	43.50	-6.97	QP
3		237.4755	42.68	-6.66	36.02	46.00	-9.98	QP
4		555.7989	37.76	1.69	39.45	46.00	-6.55	QP
5		796.1829	30.46	7.94	38.40	46.00	-7.60	QP
6	!	932.2712	31.66	8.58	40.24	46.00	-5.76	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

Radiated Spurious Emission (Above 1GHz):
ANT1+ANT2 MIMO

Modulation: 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	40.50	16.39	56.89	74	-17.11	PK	1.02	163	H
10360	25.97	16.39	42.36	54	-11.64	AV	1.06	182	H
10360	41.27	16.39	57.66	74	-16.34	PK	1.38	224	V
10360	26.71	16.39	43.10	54	-10.90	AV	1.31	17	V
Channel:5240MHz									
10480	40.50	16.11	56.61	74	-17.39	PK	1.38	165	H
10480	27.64	16.11	43.75	54	-10.25	AV	1.76	153	H
10480	40.53	16.11	56.64	74	-17.36	PK	1.05	137	V
10480	26.14	16.11	42.25	54	-11.75	AV	1.34	24	V
Channel:5745MHz									
11490	39.20	17.46	56.66	74	-17.34	PK	1.27	289	H
11490	25.34	17.46	42.80	54	-11.20	AV	1.57	125	H
11490	40.91	17.46	58.37	74	-15.63	PK	1.05	260	V
11490	26.60	17.46	44.06	54	-9.94	AV	1.68	10	V
Channel:5825MHz									
11650	41.23	17.57	58.80	74	-15.20	PK	1.57	200	H
11650	26.47	17.57	44.04	54	-9.96	AV	1.62	131	H
11650	39.48	17.57	57.05	74	-16.95	PK	1.69	110	V
11650	27.36	17.57	44.93	54	-9.07	AV	1.40	40	V

Modulation: 802.11(n40) (the worst data)
ANT1+ANT2 MIMO

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	41.14	16.34	57.48	74	-16.52	PK	1.71	68	H
10380	26.18	16.34	42.52	54	-11.48	AV	1.36	283	H
10380	41.37	16.34	57.71	74	-16.29	PK	1.71	213	V
10380	25.58	16.34	41.92	54	-12.08	AV	1.85	332	V
Channel:5230MHz									
10460	39.00	16.15	55.15	74	-18.85	PK	1.69	36	H
10460	25.58	16.15	41.73	54	-12.27	AV	1.10	194	H
10460	39.70	16.15	55.85	74	-18.15	PK	1.16	310	V
10460	27.07	16.15	43.22	54	-10.78	AV	1.10	61	V
Channel:5755MHz									
11510	40.15	17.49	57.64	74	-16.36	PK	1.75	232	H
11510	27.86	17.49	45.35	54	-8.65	AV	1.17	122	H
11510	39.04	17.49	56.53	74	-17.47	PK	1.44	331	V
11510	27.75	17.49	45.24	54	-8.76	AV	1.21	165	V
Channel:5795MHz									
11590	41.11	17.52	58.63	74	-16.94	PK	1.23	166	H
11590	26.88	17.52	44.40	54	-15.37	AV	1.55	76	H
11590	40.37	17.52	57.89	74	-16.11	PK	1.14	339	V
11590	27.35	17.52	44.87	54	-9.13	AV	1.56	71	V

Modulation: 802.11(VH80) (the worst data)
ANT1+ANT2 MIMO


Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5210MHz									
10420	40.81	16.25	57.06	74	-16.94	PK	1.77	352	H
10420	26.94	16.25	43.19	54	-10.81	AV	1.59	179	H
10420	39.39	16.25	55.64	74	-18.36	PK	1.14	310	V
10420	25.91	16.25	42.16	54	-11.84	AV	1.88	87	V
Channel:5775MHz									
11550	41.75	17.50	59.25	74	-14.75	PK	1.03	189	H
11550	27.19	17.50	44.69	54	-9.31	AV	1.00	292	H
11550	41.37	17.50	58.87	74	-15.13	PK	1.30	244	V
11550	27.70	17.50	45.20	54	-8.80	AV	1.55	43	V

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits
2. The EUT was tested in the low, high channel and the worst case position data was reported.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. BAND EDGE

8.1 Block Diagram Of Test Setup



8.2 Limit


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.


8.3 Test procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


8.4 Test Result

Test Graph ANT 1








802.11n(HT40)-5190




802.11n(HT40)-5230




802.11ac(VH80)-5210




ANT2:








802.11n(HT40)-5190




802.11n(HT40)-5230



802.11ac(VH80)-5210



ANT1:








802.11n(HT40)-5755




802.11n(HT40)-5795



802.11ac(VHT80)-5775




ANT2:







802.11n(HT40)-5755



802.11n(HT40)-5795




802.11ac(VHT80)-5775



9. CONDUCTED OUTPUT POWER

9.1 Block Diagram Of Test Setup



9.2 Limit

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.

at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution

bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).

(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW $\geq$ 3 MHz.

(iv) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle $< 98\%$, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

9.4 Test Result

ANT 1+ANT 2

Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5180	13.996	11.728	/	23.98
	5200	14.634	12.878	/	23.98
	5240	15.986	12.432	/	23.98
802.11ac20	5180	11.438	11.253	14.357	23.98
	5200	12.323	11.072	14.753	23.98
	5240	14.017	11.023	15.783	23.98
802.11ac40	5190	12.473	11.747	15.135	23.98
	5230	14.13	12.406	16.363	23.98
802.11ac80	5210	12.633	10.657	14.767	23.98
802.11n(HT20)	5180	13.927	12.377	16.231	23.98
	5200	14.784	12.739	16.891	23.98
	5240	13.807	12.336	16.144	23.98
802.11n(HT40)	5190	11.422	12.613	15.068	23.98
	5230	13.13	12.418	15.799	23.98

ANT 1+ANT 2




Test mode1	Test Channel (MHz)	Output Power dBm ANT1	Output Power dBm ANT2	Output Power dBm Total	Limit dBm
802.11a	5745	12.181	11.714	/	30
	5785	11.665	13.664	/	30
	5825	12.206	14.524	/	30
802.11ac20	5745	11.952	11.918	14.945	30
	5785	11.516	14.948	16.573	30
	5825	12.274	15.92	17.479	30
802.11ac40	5755	11.962	13.136	15.599	30
	5795	10.857	14.908	16.349	30
802.11ac80	5775	11.461	13.428	15.565	30
802.11n(HT20)	5745	12.064	12.031	15.058	30
	5785	11.359	14.32	16.097	30
	5825	12.12	14.943	16.767	30
802.11n(HT40)	5755	11.808	13.334	15.648	30
	5795	10.969	14.918	16.388	30

Duty cycle: 5180-5240MHz ANT 1

Mode	Channel.	Duty Cycle(%)	Correction Factor (dB)
802.11a	LCH	100	0
802.11ac20	LCH	100	0
802.11ac40	LCH	100	0
802.11n(HT20)	LCH	100	0
802.11n(HT40)	LCH	100	0
802.11ac80	LCH	100	0

Duty Cycle:





802.11ac40	 Agilent Spectrum Analyzer - Swept SA Center Freq 5.190000000 GHz Ref Offset 8.61 dB Ref 20.00 dBm Mkr1 40.71 ms 4.49 dBm Center 5.190000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11n(HT20)	 Agilent Spectrum Analyzer - Swept SA Center Freq 5.180000000 GHz Ref Offset 8.44 dB Ref 20.00 dBm Mkr1 38.59 ms 9.30 dBm Center 5.180000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11n(HT40)	 Agilent Spectrum Analyzer - Swept SA Center Freq 5.190000000 GHz Ref Offset 8.61 dB Ref 20.00 dBm Mkr1 48.17 ms 4.57 dBm Center 5.190000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)




Duty cycle: 5180-5240MHz ANT 2

Mode	Channel.	Duty Cycle(%)	Correction Factor (dB)
802.11a	LCH	100	0
802.11ac20	LCH	100	0
802.11ac40	LCH	100	0
802.11n(HT20)	LCH	100	0
802.11n(HT40)	LCH	100	0
802.11ac80	LCH	100	0

Duty Cycle:

Graphs	
802.11a	
802.11ac20	
802.11ac40	




802.11n(HT20)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.180000000 GHz Ref Offset 8.44 dB Ref 20.00 dBm Mkr1 95.28 ms 9.32 dBm Center 5.180000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11n(HT40)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.190000000 GHz Ref Offset 8.61 dB Ref 20.00 dBm Mkr1 26.43 ms 4.99 dBm Center 5.190000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11ac80	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.210000000 GHz Ref Offset 8.62 dB Ref 20.00 dBm Mkr1 4.250 ms -3.24 dBm Center 5.210000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)


Duty cycle: 5745-5825MHz ANT 1

Mode	Channel.	Duty Cycle(%)	Correction Factor (dB)
802.11a	LCH	100	0
802.11ac20	LCH	100	0
802.11ac40	LCH	100	0
802.11n(HT20)	LCH	100	0
802.11n(HT40)	LCH	100	0
802.11ac80	LCH	100	0

Duty Cycle:



802.11ac40	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.755000000 GHz Ref Offset 8.99 dB Ref 20.00 dBm Mkr1 78.82 ms 5.07 dBm Center 5.755000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts) Span 0 Hz
802.11n(HT20)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.745000000 GHz Ref Offset 8.72 dB Ref 20.00 dBm Mkr1 96.42 ms 8.70 dBm Center 5.745000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts) Span 0 Hz
802.11n(HT40)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.755000000 GHz Ref Offset 8.99 dB Ref 20.00 dBm Mkr1 52.34 ms 4.80 dBm Center 5.755000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts) Span 0 Hz






Duty cycle: 5745-5825MHz ANT 2


Mode	Channel.	Duty Cycle(%)	Correction Factor (dB)
802.11a	LCH	100	0
802.11ac20	LCH	100	0
802.11ac40	LCH	100	0
802.11n(HT20)	LCH	100	0
802.11n(HT40)	LCH	100	0
802.11ac80	LCH	100	0

Duty Cycle:



802.11ac40	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.755000000 GHz Ref Offset 8.99 dB Ref 20.00 dBm Mkr1 58.20 ms 4.50 dBm Center 5.755000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11n(HT20)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.745000000 GHz Ref Offset 8.72 dB Ref 20.00 dBm Mkr1 19.44 ms 9.31 dBm Center 5.745000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)
802.11n(HT40)	 Agilent Spectrum Analyzer - Sweep SA Center Freq 5.755000000 GHz Ref Offset 8.99 dB Ref 20.00 dBm Mkr1 4.650 ms 4.59 dBm Center 5.755000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 100.0 ms (10001 pts)


802.11ac80




5180-5240MHz

ANT 1


802.11a-5180




802.11a-5200



802.11a-5240



802.11ac(VHT20)-5180



802.11ac(VHT20)-5200




802.11ac(VHT20)-5240



802.11ac(VHT40)-5190


802.11ac(VHT40)-5230




802.11ac(VHT80)-5210




802.11n(HT20)-5180




802.11n(HT20)-5200




802.11n(HT20)-5240



802.11n(HT40)-5190




802.11n(HT40)-5230



ANT2


802.11a-5180




802.11a-5200



802.11a-5240




802.11ac(VHT20)-5180



802.11ac(VHT20)-5200


802.11ac(VHT20)-5240



802.11ac(VHT40)-5190




802.11ac(VHT40)-5230




802.11ac(VHT80)-5210




802.11n(HT20)-5180



802.11n(HT20)-5200




802.11n(HT20)-5240



802.11n(HT40)-5190



802.11n(HT40)-5230




5745-5825MHz

ANT 1:

802.11a-5745




802.11a-5785




802.11a-5825




802.11ac(VHT20)-5745



802.11ac(VHT20)-5785




802.11ac(VHT20)-5825



802.11ac(VHT40)-5755


802.11ac(VHT40)-5795



802.11ac(VHT80)-5775




802.11n(HT20)-5745




802.11n(HT20)-5785



802.11n(HT20)-5825



5802.11n(HT40)-5755



802.11n(HT40)-5795