

FCC Radio Test Report

FCC ID : 2AST4MO68
Equipment : JMOTION
Brand Name : JACFIT
Model Name : JMO101
Applicant : JSports TECHNOLOGY CO., LTD
18F., No.502, Sec. 2, Ren'ai Rd., Linkou Dist.,
New Taipei City 244020, Taiwan (R.O.C.)
Manufacturer : Chen Wei Electronics inc.
No.12, Nanyuan Rd., Zhongli Dist.,
Taoyuan City 32063, Taiwan (R.O.C.)
Standard : 47 CFR FCC Part 15.247

The product was received on Apr. 10, 2026, and testing was started from Apr. 24, 2026 and completed on Apr. 29, 2026. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Applied Standards	7
1.3 Testing Location Information	7
1.4 Measurement Uncertainty	7
2 TEST CONFIGURATION OF EUT.....	8
2.1 Test Channel Mode	8
2.2 The Worst Case Measurement Configuration	9
2.3 Accessories	10
2.4 Support Equipment.....	10
2.5 Test Setup Diagram	11
3 TRANSMITTER TEST RESULT	12
3.1 AC Power-line Conducted Emissions	12
3.2 DTS Bandwidth.....	14
3.3 Maximum Conducted Output Power	15
3.4 Power Spectral Density	17
3.5 Emissions in Non-restricted Frequency Bands	18
3.6 Emissions in Restricted Frequency Bands.....	19
4 TEST EQUIPMENT AND CALIBRATION DATA.....	23
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS	
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH	
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY	
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS	
APPENDIX G. TEST PHOTOS	
PHOTOGRAPHS OF EUT V01	



History of this test report

TEL : 886-3-3273456
FAX : 886-3-3270973
Report Template No.: HE1-C10 Ver4.5
FCC ID: 2AST4MO68

Summary of Test Result

Report Clause	Ref.Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and explanations:

None

Reviewed by: Daniel Hsu

Report Producer: Wendy Chen

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX
2.4-2.4835GHz	BT-LE(2Mbps)	2.0	1TX

Note:

- ♦ Bluetooth LE uses a GFSK (1Mbps/2Mbps) modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support	Gain (dBi)
1	JACFIT	JM101	PCB	N/A	BT	0.85

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive.

1.1.3 EUT Information

Operational Condition	
EUT Power Type	From AC Adapter / Host system
EUT Function	☒ Point-to-multipoint ☐ Point-to-point
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device)
	Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems)
	Host System - Brand Name / Model No.: ...
☐	Other:

1.1.4 Mode Test Duty Cycle

Mode	DC	DCF (dB)	T (s)	VBW (Hz)_1/T
BT-LE(1Mbps)	0.856	0.68	2.139m	500
BT-LE(2Mbps)	0.587	2.31	1.082m	1k

Note. If DC < 0.98, the DCF was added while measuring Output power and PSD.

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ KDB 558074 D01 v05r02
- ♦ KDB 414788 D01 v01r01

1.3 Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory				
☒ Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)			
	TEL: 886-3-327-3456		FAX: 886-3-327-0973	
Test site Designation No. TW3785 with FCC.				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
AC Conduction	CO04-HY	Lego Lin	20.5~22.7°C / 57~59%	29/Apr/2026
☒ Wenhua 3rd. (TAF: 3785)	ADD: No. 58, Aly. 75, Ln. 564, Wenhua 3rd Rd., Guishan Dist. Taoyuan City 333, Taiwan (R.O.C.)			
	TEL: 886-3-327-0868			
Test site Designation No. TW0036 with FCC.				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH06-HY	Peng Huang	23.4~23.9°C / 52~55%	28/Apr/2026
Radiated	03CH25-HY	Lego Lin	22.2~23.4°C / 50~52%	24/Apr/2026~25/Apr/2026

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
AC Power-line Conducted Emissions	3.24 dB	Confidence levels of 95%
Conducted Output Power	1.12 dB	Confidence levels of 95%
Bandwidth	0.07 MHz	Confidence levels of 95%
Conducted Emission	1.12 dB	Confidence levels of 95%
Power Spectral Density	1.22 dB	Confidence levels of 95%
Radiated Emission (9 kHz ~ 30 MHz)	1.76 dB	Confidence levels of 95%
Radiated Emission (30 MHz ~ 1 GHz)	5.38 dB	Confidence levels of 95%
Radiated Emission (1 GHz ~ 18 GHz)	4.94 dB	Confidence levels of 95%
Radiated Emission (18 GHz ~ 40 GHz)	4.92 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Channel Mode

Test Software Version	Direct Test Mode v2.4.0
------------------------------	-------------------------

Mode	Power Setting
BT-LE(1Mbps)	-
2402MHz	0
2440MHz	0
2480MHz	0
BT-LE(2Mbps)	-
2402MHz	0
2440MHz	0
2480MHz	0

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	CTX
1	Adapter Mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	Adapter Mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT			V

2.3 Accessories

Accessories				
Battery	Brand Name	Chen Wei Electronics inc.	Model Name	601220
	Manufacturer	HELIX CO., LTD.	-	-
	Power Rating	3.7Vdc, 90mAh	Type	Li-ion, Yes
Charging Cable	Brand Name	JACFIT	Model Name	S949-02U
	Signal Line	0.8 meter, shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.


2.4 Support Equipment

Support Equipment – AC Conduction					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	Adapter	Apple	A1385	-	-
2	Fixture cable	Dupont	2.54mm pitch 200mm rainbow flat cable	-	Provided by Customer
3	AC Power Cable	Sync	TPCMRN0018	-	-

Support Equipment – Conducted					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	Notebook	DELL	E5410	-	-
2	Adapter for NB	DELL	HA65NM130	-	Provided by Customer

Support Equipment – Radiated					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	AC Power Cable	Sync	TPCMRN0018	-	-
2	Adapter	Apple	A1385	-	-
3	Fixture cable	Dupont	2.54mm pitch 200mm rainbow flat cable	-	Provided by Customer

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method
Refer as ANSI C63.10, clause 6.2 foray power-line conducted emissions.

3.1.4 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Raw(Read Level) + LISN(LISN Factor) + CL(Cable Loss) + AT(Attenuator).

3.1.5 Test Setup



3.1.6 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
☒	Refer as KDB 558074, clause 8.2 (11.8 of ANSI C63.10) DTS bandwidth measurement.
☒	Refer as RSS-Gen, clause 6.7 for occupied bandwidth testing.
☐	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
e.i.r.p. Power Limit:	
	2400-2483.5 MHz Band
	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	Smart antenna system (SAS)
	- Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	- Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	- Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as KDB 558074, clause 8.3.1.1 (11.9.1.1 of ANSI C63.10) RBW ≥ EBW method.
☐	Refer as KDB 558074, clause 8.3.1.2 integrated band power method.
☐	Refer as KDB 558074, clause 8.3.1.3 (11.9.1.2 of ANSI C63.10) peak power meter.
Maximum Average Conducted Output Power	
☐	Refer as KDB 558074, clause 8.3.2.2 (11.9.2.2 of ANSI C63.10) using a spectrum analyzer.
☒	Refer as KDB 558074, clause 8.3.2.3 (11.9.2.3 of ANSI C63.10) using a power meter.
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
☒ Refer as KDB 558074, clause 8.4 (11.10 of ANSI C63.10) Max. PSD.
- For conducted measurement. - If The EUT supports multiple transmit chains using options given below: - Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as KDB 558074, clause 8.5 (11.11 of ANSI C63.10) for non-restricted frequency bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Test Method	
▪	The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
	Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
▪	For the transmitter unwanted emissions shall be measured using following options below:
	Refer as KDB 558074, clause 8.6 (11.12 of ANSI C63.10) for restricted frequency bands.
▪	For the transmitter band-edge emissions shall be measured using following options below:
	Refer as KDB 558074 clause 8.7.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
▪	Refer as KDB 558074, clause 8.7.2 (6.10.6 of ANSI C63.10) for marker-delta method for band-edge measurements.
	Refer as KDB 558074, clause 8.7.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels.
▪	Use the following spectrum analyzer settings:
	Set RBW=100 kHz for $f < 1$ GHz; VBW=3 * RBW; Sweep = auto; Detector function = peak; Trace = max hold.
▪	Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement, refer as 1.1.4.
	KDB 414788 Open-Field Test Sites and Chamber Correlation Justification.
▪	Based on FCC 15.31(f)(2): measurements may be performed at a distance closer than that specified in regulations; however, an attempt should be made to avoid making measurements in the near field.
	Open-field site and chamber correlation testing had been performed and chamber measured test result is the worst case test result.


3.6.4 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Raw(Read Level) + AF(Antenna Factor) + CL(Cable Loss) - PA(Preamplifier Factor)

3.6.5 Test Setup





3.6.6 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

4 Test Equipment and Calibration Data

Instrument for AC Conduction

Instrument	Manufacturer /Brand	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESR3	102051	9kHz ~ 3.6GHz	21/May/2025	20/May/2026
Two-Line V-Network	ROHDE & SCHWARZ	ENV 216	101578	9kHz ~ 30MHz	24/Aug/2025	23/Aug/2026
RF Cable 5m	TITAN	TITAN	CO04-cable-01	9 kHz~200MHz	25/Feb/2026	24/Feb/2027
Pulse Limiter	SCHWARZBECK	VTSD 9561F-N	1056	9kHz ~ 30MHz	25/Jun/2025	24/Jun/2026
Software	Sporton	SENSE-EMI	V5.11.6	-	NCR	NCR

NCR: No Calibration Required

Instrument for Conducted Test

Instrument	Manufacturer /Brand	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Signal Analyzer	R&S	FSV 40	101029	10Hz~40GHz	30/Oct/2025	29/Oct/2026
SMB100A Signal Generator	R&S	SMB100A	181147	100kHz~40GHz	29/Oct/2025	28/Oct/2026
Power Meter	Anritsu	ML2495A	1124009	300MHz~40GHz	26/Mar/2026	25/Mar/2027
Pulse Sensor	Anritsu	MA2411B	1027452	300MHz~40GHz	26/Mar/2026	25/Mar/2027
SENSE-15247_FS	Sporton	V5.11.28	N/A	N/A	N/A	N/A

Instrument for Radiated Test

Instrument	Manufacturer /Brand	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH25-HY	30MHz~1GHz 3m	18/Jul/2025	17/Jul/2026
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH25-HY	1GHz~18GHz 3m	07/Aug/2025	06/Aug/2026
ESR7 EMI Test Receiver	ROHDE & SCHWARZ	ESR7	102956	9kHz~3.6GHz	26/Aug/2025	25/Aug/2026
Signal Analyzer	ROHDE & SCHWARZ	FSV3044	101410	10Hz~44GHz	19/Nov/2025	18/Nov/2026
Loop Antenna	TESEQ	HLA 6120	31244	9kHz~30MHz	16/Mar/2026	15/Mar/2027
Bilog Antenna & 6dB Attenuator	TESEQ & VGT	CBL 6111D & VFA 04002-06	63537/001	30MHz~1GHz	23/May/2025	22/May/2026
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	02876	1GHz~18GHz	02/Jul/2025	01/Jul/2026
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	01248	18GHz~40GHz	07/Oct/2025	06/Oct/2026
RF Cable	HUBER+SUHNER	SUOFLEX 104	CB007	9kHz~1GHz	22/Apr/2026	21/Apr/2027
RF Cable	HUBER+SUHNER	SUOFLEX 104	CB007	1GHz~40GHz	10/Feb/2026	09/Feb/2027
Preamplifier	SGH	PRAMP 903	20230515-1	25MHz~3GHz	21/May/2025	20/May/2026
Preamplifier	SGH	PRAMP 118-H	20230515-3	1GHz~18GHz	21/May/2025	20/May/2026
Preamplifier	EMCI	EM01G18G	060940	1GHz~18GHz	21/Oct/2025	20/Oct/2026
Microwave Preamplifier	EMC INSTRUMENTS	EM18G40G	060604	18GHz ~ 40GHz	26/Apr/2025	25/Apr/2026
SENSE-15407-NII	Sporton	V5.11.24	NA	NA	NA	NA



Conducted Emissions at Powerline

Appendix A


Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 1	Pass	AV	746.524k	28.85	46.00	-17.15	Neutral

Result


Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 1	Pass	QP	165.743k	42.42	65.18	-22.76	Line
Mode 1	Pass	AV	165.743k	26.31	55.18	-28.87	Line
Mode 1	Pass	QP	246.077k	39.12	61.89	-22.77	Line
Mode 1	Pass	AV	246.077k	23.11	51.89	-28.78	Line
Mode 1	Pass	QP	334.632k	36.12	59.33	-23.21	Line
Mode 1	Pass	AV	334.632k	20.69	49.33	-28.64	Line
Mode 1	Pass	QP	752.508k	36.18	56.00	-19.82	Line
Mode 1	Pass	AV	752.508k	26.23	46.00	-19.77	Line
Mode 1	Pass	QP	3.527M	26.59	56.00	-29.41	Line
Mode 1	Pass	AV	3.527M	21.15	46.00	-24.85	Line
Mode 1	Pass	QP	6.119M	26.60	60.00	-33.40	Line
Mode 1	Pass	AV	6.119M	21.56	50.00	-28.44	Line
Mode 1	Pass	QP	164.425k	41.94	65.24	-23.30	Neutral
Mode 1	Pass	AV	164.425k	26.64	55.24	-28.60	Neutral
Mode 1	Pass	QP	248.05k	39.22	61.81	-22.59	Neutral
Mode 1	Pass	AV	248.05k	25.87	51.81	-25.94	Neutral
Mode 1	Pass	QP	341.378k	33.08	59.17	-26.09	Neutral
Mode 1	Pass	AV	341.378k	19.82	49.17	-29.35	Neutral
Mode 1	Pass	QP	746.524k	37.03	56.00	-18.97	Neutral
Mode 1	Pass	AV	746.524k	28.85	46.00	-17.15	Neutral
Mode 1	Pass	QP	2.283M	27.06	56.00	-28.94	Neutral
Mode 1	Pass	AV	2.283M	20.98	46.00	-25.02	Neutral
Mode 1	Pass	QP	6.071M	28.79	60.00	-31.21	Neutral
Mode 1	Pass	AV	6.071M	22.76	50.00	-27.24	Neutral

Conducted Emissions at Powerline_Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Raw (dBuV)	LISN (dB)	CL (dB)										
QP	165.743k	42.42	65.18	-22.76	19.92	Line	22.50	9.64	0.16										
AV	165.743k	26.31	55.18	-28.87	19.92	Line	6.39	9.64	0.16										
QP	246.077k	39.12	61.89	-22.77	19.88	Line	19.24	9.64	0.12										
AV	246.077k	23.11	51.89	-28.78	19.88	Line	3.23	9.64	0.12										
QP	334.632k	36.12	59.33	-23.21	19.86	Line	16.26	9.63	0.11										
AV	334.632k	20.69	49.33	-28.64	19.86	Line	0.83	9.63	0.11										
QP	752.508k	36.18	56.00	-19.82	19.84	Line	16.34	9.64	0.08										
AV	752.508k	26.23	46.00	-19.77	19.84	Line	6.39	9.64	0.08										
QP	3.527M	26.59	56.00	-29.41	19.90	Line	6.69	9.66	0.11										
AV	3.527M	21.15	46.00	-24.85	19.90	Line	1.25	9.66	0.11										
QP	6.119M	26.60	60.00	-33.40	19.98	Line	6.62	9.67	0.18										
AV	6.119M	21.56	50.00	-28.44	19.98	Line	1.58	9.67	0.18										

Conducted Emissions at Powerline_Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Raw (dBuV)	LISN (dB)	CL (dB)										
QP	164.425k	41.94	65.24	-23.30	19.92	Neutral	22.02	9.64	0.16										
AV	164.425k	26.64	55.24	-28.60	19.92	Neutral	6.72	9.64	0.16										
QP	248.05k	39.22	61.81	-22.59	19.87	Neutral	19.35	9.63	0.12										
AV	248.05k	25.87	51.81	-25.94	19.87	Neutral	6.00	9.63	0.12										
QP	341.378k	33.08	59.17	-26.09	19.86	Neutral	13.22	9.63	0.11										
AV	341.378k	19.82	49.17	-29.35	19.86	Neutral	-0.04	9.63	0.11										
QP	746.524k	37.03	56.00	-18.97	19.84	Neutral	17.19	9.64	0.08										
AV	746.524k	28.85	46.00	-17.15	19.84	Neutral	9.01	9.64	0.08										
QP	2.283M	27.06	56.00	-28.94	19.84	Neutral	7.22	9.65	0.06										
AV	2.283M	20.98	46.00	-25.02	19.84	Neutral	1.14	9.65	0.06										
QP	6.071M	28.79	60.00	-31.21	19.99	Neutral	8.80	9.68	0.18										
AV	6.071M	22.76	50.00	-27.24	19.99	Neutral	2.77	9.68	0.18										



Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	738.75k	1.066M	1M07F1D	581.25k	1.058M
BT-LE(2Mbps)	967.5k	2.094M	2M09F1D	935k	2.066M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth



Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	581.25k	1.058M
2440MHz	Pass	500k	738.75k	1.066M
2480MHz	Pass	500k	706.25k	1.058M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	935k	2.086M
2440MHz	Pass	500k	967.5k	2.066M
2480MHz	Pass	500k	957.5k	2.094M



Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

2.4-2.4835GHz_BT-LE(1Mbps)
EBW-DTS
2440MHz

28/04/2026


2.4-2.4835GHz_BT-LE(2Mbps)
EBW-DTS
2440MHz

28/04/2026





Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	-1.12	0.00077
BT-LE(2Mbps)	-1.17	0.00076

**Result**

Mode	Result	DG (dBi)	Total Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	0.85	-1.12	30.00
2440MHz	Pass	0.85	-1.91	30.00
2480MHz	Pass	0.85	-2.25	30.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	0.85	-1.17	30.00
2440MHz	Pass	0.85	-1.92	30.00
2480MHz	Pass	0.85	-2.25	30.00

DG = Directional Gain; Port X = Port X output power;
Inf = There's no restriction for the limit.



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-17.22
BT-LE(2Mbps)	-19.87

RBW = 3kHz;

Result

Mode	Result	DG (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	0.85	-17.22	8.00
2440MHz	Pass	0.85	-18.42	8.00
2480MHz	Pass	0.85	-18.54	8.00
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	0.85	-19.87	8.00
2440MHz	Pass	0.85	-19.92	8.00
2480MHz	Pass	0.85	-22.02	8.00


DG = Directional Gain; RBW = 3kHz;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;
Inf = There's no restriction for the limit.

2.4-2.4835GHz_BT-LE(1Mbps)

PSD

2402MHz

28/04/2026




2.4-2.4835GHz_BT-LE(2Mbps)

PSD

2402MHz

28/04/2026



Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.402G	-2.16	-32.16	2.17673G	-55.50	2.39972G	-48.09	2.4G	-49.08	2.50062G	-53.97	17.62396G	-41.71	1
BT-LE(2Mbps)	Pass	2.402G	-1.31	-31.31	2.18848G	-54.94	2.4G	-36.56	2.4G	-33.42	2.5033G	-53.96	16.24605G	-40.29	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.402G	-2.16	-32.16	2.17673G	-55.50	2.39972G	-48.09	2.4G	-49.08	2.50062G	-53.97	17.62396G	-41.71	1
2440MHz	Pass	2.402G	-2.16	-32.16	2.3095G	-54.69	2.39948G	-53.70	2.4G	-56.99	2.50094G	-52.84	16.22918G	-41.39	1
2480MHz	Pass	2.402G	-2.16	-32.16	2.0651G	-55.02	2.39476G	-53.26	2.4G	-56.18	2.50182G	-53.15	17.66895G	-41.51	1
BT-LE(2Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.402G	-1.31	-31.31	2.18848G	-54.94	2.4G	-36.56	2.4G	-33.42	2.5033G	-53.96	16.24605G	-40.29	1
2440MHz	Pass	2.402G	-1.31	-31.31	1.77135G	-55.11	2.39152G	-53.93	2.4G	-54.73	2.50122G	-53.57	17.61552G	-42.35	1
2480MHz	Pass	2.402G	-1.31	-31.31	2.16968G	-54.92	2.39848G	-54.07	2.4G	-56.45	2.5027G	-53.84	17.62396G	-42.38	1


2.4-2.4835GHz_BT-LE(1Mbps)

CSEndB-DTS

2402MHz

28/04/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.402G	-2.16	-32.16	2.17673G	-55.50	2.39972G	-48.09	2.4G	-49.08	2.50062G	-53.97	17.62396G	-41.71	1


2.4-2.4835GHz_BT-LE(2Mbps)

CSEndB-DTS

2402MHz

28/04/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.402G	-1.31	-31.31	2.18848G	-54.94	2.4G	-36.56	2.4G	-33.42	2.5033G	-53.96	16.24605G	-40.29	1



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-
BT-LE(2Mbps)	Pass	PK	575.14M	39.09	46.00	-6.91	3	Horizontal	360	1.00

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
BT-LE(2Mbps)	-	-	-	-	-	-	-	-	-	-
2440MHz_Adapter	Pass	PK	167.74M	32.36	43.50	-11.14	3	Vertical	0	1.00
2440MHz_Adapter	Pass	PK	216M	32.10	43.50	-11.40	3	Vertical	0	1.00
2440MHz_Adapter	Pass	PK	359.8M	31.75	46.00	-14.25	3	Vertical	0	1.00
2440MHz_Adapter	Pass	PK	575.14M	38.80	46.00	-7.20	3	Vertical	0	1.00
2440MHz_Adapter	Pass	PK	745.86M	37.46	46.00	-8.54	3	Vertical	0	1.00
2440MHz_Adapter	Pass	QP	50.91M	10.91	40.00	-29.09	3	Vertical	0	1.00
2440MHz_Adapter	Pass	PK	49.4M	26.66	40.00	-13.34	3	Horizontal	360	1.00
2440MHz_Adapter	Pass	PK	167.74M	29.47	43.50	-14.03	3	Horizontal	360	1.00
2440MHz_Adapter	Pass	PK	216M	33.78	43.50	-9.72	3	Horizontal	360	1.00
2440MHz_Adapter	Pass	PK	359.8M	31.99	46.00	-14.01	3	Horizontal	360	1.00
2440MHz_Adapter	Pass	PK	575.14M	39.09	46.00	-6.91	3	Horizontal	360	1.00
2440MHz_Adapter	Pass	PK	648.86M	31.82	46.00	-14.18	3	Horizontal	360	1.00


2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_Adapter



2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_Adapter





Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	4.80409G	51.22	54.00	-2.78	3	Horizontal	91	1.23
BT-LE(2Mbps)	Pass	AV	2.4835G	48.23	54.00	-5.77	3	Horizontal	29	1.01


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.388G	46.66	54.00	-7.34	3	Vertical	283	2.79
2402MHz	Pass	AV	2.402G	89.62	Inf	-Inf	3	Vertical	283	2.79
2402MHz	Pass	PK	2.3776G	59.12	74.00	-14.88	3	Vertical	283	2.79
2402MHz	Pass	PK	2.4022G	90.81	Inf	-Inf	3	Vertical	283	2.79
2402MHz	Pass	AV	2.38G	46.62	54.00	-7.38	3	Horizontal	16	1.16
2402MHz	Pass	AV	2.402G	90.45	Inf	-Inf	3	Horizontal	16	1.16
2402MHz	Pass	PK	2.3876G	59.03	74.00	-14.97	3	Horizontal	16	1.16
2402MHz	Pass	PK	2.4022G	91.58	Inf	-Inf	3	Horizontal	16	1.16
2402MHz	Pass	AV	4.80408G	44.58	54.00	-9.42	3	Vertical	68	2.59
2402MHz	Pass	PK	4.80412G	53.65	74.00	-20.35	3	Vertical	68	2.59
2402MHz	Pass	AV	4.80409G	51.22	54.00	-2.78	3	Horizontal	91	1.23
2402MHz	Pass	PK	4.80407G	59.24	74.00	-14.76	3	Horizontal	91	1.23
2402MHz	Pass	AV	2.388G	46.68	54.00	-7.32	3	Vertical	276	1.50
2440MHz	Pass	AV	2.44G	83.68	Inf	-Inf	3	Vertical	276	1.50
2440MHz	Pass	AV	2.496G	47.69	54.00	-6.31	3	Vertical	276	1.50
2440MHz	Pass	PK	2.38G	58.68	74.00	-15.32	3	Vertical	276	1.50
2440MHz	Pass	PK	2.44G	84.92	Inf	-Inf	3	Vertical	276	1.50
2440MHz	Pass	PK	2.4936G	59.94	74.00	-14.06	3	Vertical	276	1.50
2440MHz	Pass	AV	2.3792G	46.82	54.00	-7.18	3	Horizontal	28	1.00
2440MHz	Pass	AV	2.44G	94.15	Inf	-Inf	3	Horizontal	28	1.00
2440MHz	Pass	AV	2.4992G	47.64	54.00	-6.36	3	Horizontal	28	1.00
2440MHz	Pass	PK	2.3564G	58.39	74.00	-15.61	3	Horizontal	28	1.00
2440MHz	Pass	PK	2.4396G	95.18	Inf	-Inf	3	Horizontal	28	1.00
2440MHz	Pass	PK	2.4964G	60.65	74.00	-13.35	3	Horizontal	28	1.00
2440MHz	Pass	AV	4.88014G	44.27	54.00	-9.73	3	Vertical	82	2.50
2440MHz	Pass	PK	4.88007G	52.56	74.00	-21.44	3	Vertical	82	2.50
2440MHz	Pass	AV	4.88009G	49.60	54.00	-4.40	3	Horizontal	122	2.87
2440MHz	Pass	PK	4.88003G	57.43	74.00	-16.57	3	Horizontal	122	2.87
2480MHz	Pass	AV	2.48G	88.41	Inf	-Inf	3	Vertical	157	1.18
2480MHz	Pass	AV	2.4914G	47.74	54.00	-6.26	3	Vertical	157	1.18
2480MHz	Pass	PK	2.4804G	89.57	Inf	-Inf	3	Vertical	157	1.18
2480MHz	Pass	PK	2.4934G	59.39	74.00	-14.61	3	Vertical	157	1.18
2480MHz	Pass	AV	2.48G	94.93	Inf	-Inf	3	Horizontal	29	1.00
2480MHz	Pass	AV	2.491G	47.78	54.00	-6.22	3	Horizontal	29	1.00
2480MHz	Pass	PK	2.4804G	96.05	Inf	-Inf	3	Horizontal	29	1.00
2480MHz	Pass	PK	2.4844G	61.28	74.00	-12.72	3	Horizontal	29	1.00
2480MHz	Pass	AV	4.96009G	43.58	54.00	-10.42	3	Vertical	70	2.48
2480MHz	Pass	PK	4.95996G	52.39	74.00	-21.61	3	Vertical	70	2.48
2480MHz	Pass	AV	4.96009G	47.53	54.00	-6.47	3	Horizontal	138	3.00
2480MHz	Pass	PK	4.96007G	55.03	74.00	-18.97	3	Horizontal	138	3.00
BT-LE(2Mbps)	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.3896G	47.00	54.00	-7.00	3	Vertical	309	2.51
2402MHz	Pass	AV	2.402G	84.91	Inf	-Inf	3	Vertical	309	2.51
2402MHz	Pass	PK	2.3824G	58.60	74.00	-15.40	3	Vertical	309	2.51
2402MHz	Pass	PK	2.4026G	87.55	Inf	-Inf	3	Vertical	309	2.51
2402MHz	Pass	AV	2.3816G	47.00	54.00	-7.00	3	Horizontal	30	1.08
2402MHz	Pass	AV	2.402G	91.27	Inf	-Inf	3	Horizontal	30	1.08
2402MHz	Pass	PK	2.3664G	59.47	74.00	-14.53	3	Horizontal	30	1.08
2402MHz	Pass	PK	2.4026G	93.85	Inf	-Inf	3	Horizontal	30	1.08
2402MHz	Pass	AV	4.80496G	42.37	54.00	-11.63	3	Vertical	83	2.44
2402MHz	Pass	PK	4.80416G	52.48	74.00	-21.52	3	Vertical	83	2.44
2402MHz	Pass	AV	4.80312G	47.05	54.00	-6.95	3	Horizontal	137	3.00
2402MHz	Pass	PK	4.80416G	57.25	74.00	-16.75	3	Horizontal	137	3.00
2440MHz	Pass	AV	2.3428G	46.99	54.00	-7.01	3	Vertical	275	1.50
2440MHz	Pass	AV	2.44G	82.01	Inf	-Inf	3	Vertical	275	1.50
2440MHz	Pass	AV	2.4912G	47.95	54.00	-6.05	3	Vertical	275	1.50
2440MHz	Pass	PK	2.3584G	59.00	74.00	-15.00	3	Vertical	275	1.50
2440MHz	Pass	PK	2.44G	84.81	Inf	-Inf	3	Vertical	275	1.50
2440MHz	Pass	PK	2.4972G	59.58	74.00	-14.42	3	Vertical	275	1.50
2440MHz	Pass	AV	2.3832G	47.07	54.00	-6.93	3	Horizontal	29	1.00

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
2440MHz	Pass	AV	2.44G	92.40	Inf	-Inf	3	Horizontal	29	1.00
2440MHz	Pass	AV	2.4976G	47.92	54.00	-6.08	3	Horizontal	29	1.00
2440MHz	Pass	PK	2.3828G	59.00	74.00	-15.00	3	Horizontal	29	1.00
2440MHz	Pass	PK	2.4396G	95.02	Inf	-Inf	3	Horizontal	29	1.00
2440MHz	Pass	PK	2.4984G	60.20	74.00	-13.80	3	Horizontal	29	1.00
2440MHz	Pass	AV	4.88104G	40.65	54.00	-13.35	3	Vertical	242	2.61
2440MHz	Pass	PK	4.88008G	51.18	74.00	-22.82	3	Vertical	242	2.61
2440MHz	Pass	AV	4.8792G	46.36	54.00	-7.64	3	Horizontal	137	1.09
2440MHz	Pass	PK	4.88008G	56.09	74.00	-17.91	3	Horizontal	137	1.09
2480MHz	Pass	AV	2.48G	86.59	Inf	-Inf	3	Vertical	157	1.16
2480MHz	Pass	AV	2.495G	48.01	54.00	-5.99	3	Vertical	157	1.16
2480MHz	Pass	PK	2.4806G	89.30	Inf	-Inf	3	Vertical	157	1.16
2480MHz	Pass	PK	2.4844G	59.88	74.00	-14.12	3	Vertical	157	1.16
2480MHz	Pass	AV	2.48G	93.19	Inf	-Inf	3	Horizontal	29	1.01
2480MHz	Pass	AV	2.4835G	48.23	54.00	-5.77	3	Horizontal	29	1.01
2480MHz	Pass	PK	2.4806G	95.87	Inf	-Inf	3	Horizontal	29	1.01
2480MHz	Pass	PK	2.4838G	61.58	74.00	-12.42	3	Horizontal	29	1.01
2480MHz	Pass	AV	4.96112G	41.98	54.00	-12.02	3	Vertical	70	2.48
2480MHz	Pass	PK	4.95992G	51.94	74.00	-22.06	3	Vertical	70	2.48
2480MHz	Pass	AV	4.95928G	46.73	54.00	-7.27	3	Horizontal	141	3.00
2480MHz	Pass	PK	4.96G	56.09	74.00	-17.91	3	Horizontal	141	3.00


2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX




2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX



2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX



2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX

