

Prüfbericht-Nr.: Test report no.:	CN268YGY 002	Auftrags-Nr.: Order no.:	27220249	Seite 1 von 27 Page 1 of 27
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-02-05	
Auftraggeber: Client:	SharkNinja Operating LLC 89 A Street Suite 100 Needham MA 02494 USA			
Prüfgegenstand: Test item:	Robotic Vacuum Cleaner			
Bezeichnung / Typ-Nr.: Identification / Type no.:	QRA1*****, URA1*****, RVA1*****, AVA1***** (*=0-9, A-Z or blank") (Trademark: Shark)			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15: Subpart C Section 15.247 RSS-247 Issue 4 July 2025 RSS-Gen Issue 5 February 2021			
Wareneingangsdatum: Date of sample receipt:	2026-02-25	Please refer to photo documents		
Prüfmuster-Nr.: Test sample no.:	A004216282-001 A004212973-001~002			
Prüfzeitraum: Testing period:	2026-03-09 - 2026-03-13			
Ort der Prüfung: Place of testing:	Refer to section 2.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	☒ <u>Breeze Jiang</u>		genehmigt von: authorized by:	☒ <u>Bell Hu</u>
Datum: Date:	2026-05-20 Signed by: Breeze Jiang	Ausstellungsdatum: Issue date:	2026-05-20 Signed by: Bell Hu	
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: 2ASV9RVA100 IC: 24909-RVA100 HVIN: HS331 This report for Bluetooth dual mode.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht-Nr.: CN268YGY 002
Test report no.:

Seite 2 von 27
Page 2 of 27

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 6dB BANDWIDTH

RESULT: Pass

5.1.5 99% BANDWIDTH

RESULT: Pass

5.1.6 20dB BANDWIDTH

RESULT: Pass

5.1.7 CARRIER FREQUENCY SEPARATION

RESULT: Pass

5.1.8 NUMBER OF HOPPING FREQUENCY

RESULT: Pass

5.1.9 TIME OF OCCUPANCY

RESULT: Pass

5.1.10 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.11 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.12 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2	TEST SITES.....	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
2.3	TRACEABILITY	7
2.4	CALIBRATION.....	7
2.5	MEASUREMENT UNCERTAINTY	7
2.6	LOCATION OF ORIGINAL DATA	7
2.7	STATUS OF FACILITY USED FOR TESTING	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	RATINGS AND SYSTEM DETAILS.....	9
3.3	INDEPENDENT OPERATION MODES.....	11
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.5	SUBMITTED DOCUMENTS.....	11
4	TEST SET-UP AND OPERATION MODES.....	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	12
4.5	TEST SETUP DIAGRAM	13
5	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	15
5.1.1	<i>Antenna Requirement.....</i>	<i>15</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>16</i>
5.1.3	<i>Conducted Power Spectral Density.....</i>	<i>17</i>
5.1.4	<i>6dB Bandwidth</i>	<i>18</i>
5.1.5	<i>99% Bandwidth.....</i>	<i>19</i>
5.1.6	<i>20dB Bandwidth</i>	<i>20</i>
5.1.7	<i>Carrier Frequency Separation</i>	<i>21</i>
5.1.8	<i>Number of Hopping Frequency</i>	<i>22</i>
5.1.9	<i>Time of Occupancy.....</i>	<i>23</i>
5.1.10	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>24</i>
5.1.11	<i>Radiated Spurious Emission</i>	<i>25</i>
5.1.12	<i>Conducted Emission on AC Mains.....</i>	<i>26</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	27
7	LIST OF TABLES.....	27

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of Bluetooth BR & EDR

Appendix B: Test Results of Bluetooth LE

Appendix C: Photographs of the Test Set-up

2 Test Sites

2.1 Test Facilities

Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Registration number: CNAS L19010

A2LA CAB identifier: CN0158

Note: The all tests in Shenzhen PSI Testing Co., Ltd. have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.18	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
4.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
5.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2025.12.18	1 Year
6.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
7.	Amplifier	SKET	LAPA_01G18 G-45dB	SK2022032901	/	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
9.	Amplifier	SKET	LNPA_0118G-45	SK2020010801	/	2025.12.18	1 Year
10.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	/	2025.12.18	1 Year
11.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2025.12.18	1 Year
12.	Vector Signal Generator	Agilent	N5182A	MY47420724	/	2025.12.18	1 Year
13.	Analog signal generator	Agilent	N5181A	MY50145363	/	2025.12.18	1 Year
14.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.18	1 Year
15.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
16.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
17.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638		2025.12.18	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EMC-I	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

For Power Line Conducted Emission Test Equipment:

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
2.	L.I.S.N.	Rohde&Schwarz	ENV 216	102282	/	2025.12.18	1 Year
3.	L.I.S.N.	RFT	NNB111	13835240	/	2025.12.18	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
CE	EZ-EMC	Farad	PSI-3A1

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Item	Uncertainty
Power Line Conducted Emissions Test	2.13dB
Radiation Emission test in 3m chamber(30MHz to 1GHz)	4.51dB
Radiation Emission test in 3m chamber(1GHz to 18GHz)	5.07dB
Radiation Emission test in 3m chamber(18GHz to 40GHz)	5.21dB
Radio Frequency	48.24KHz
Conducted RF Power	0.41dB
Occupied-Bandwidth	968Hz
Duty Cycle	1%
Conducted-Spurious Emission	1.26dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 8 von 27
Page 8 of 27

2.7 Status of Facility Used for Testing

The Shenzhen PSI Testing Co., Ltd. Test facility located at 1-2F, Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The product is Robotic Vacuum Cleaner, which supports Bluetooth and 2.4GHz Wi-Fi wireless technologies.

The series models: QRA1*****, URA1*****, RVA1*****, AVA1***** (*=0-9, A-Z or blank"), no constructional differences, select AVA111E2EU as the representative for testing in this report.

For details refer to the User Manual.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Robotic Vacuum Cleaner
Type Designation:	QRA1*****, URA1*****, RVA1*****, AVA1***** (*=0-9, A-Z or blank")
Trademark:	Shark
FCC ID:	2ASV9RVA100
IC:	24909-RVA100
HVIN:	HS331
Operating Voltage:	AC 120V, 60Hz input via AED Dock or Internal battery operated (14.4Vdc)
Testing Voltage:	AC 120V, 60Hz or fully charged battery
Operating Temperature Range:	+10 °C ~ +40 °C
Technical Specification of Bluetooth (dual mode)	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	BR & EDR mode:79 channels, Low Energy mode:40 channels
Channel Separation:	BR & EDR mode:1MHz, Low Energy mode:2MHz
Data Rate:	BR & EDR mode: 1Mbps, 2Mbps, 3Mbps Low Energy mode: 1Mbps
Antenna Type:	Integral Antenna
Antenna Gain:	1.22 dBi (Provided by the Client)

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 4: RF Channel and Frequency of Bluetooth BR & EDR

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	20	2422.00	40	2442.00	60	2462.00
1	2403.00	21	2423.00	41	2443.00	61	2463.00
2	2404.00	22	2424.00	42	2444.00	62	2464.00
3	2405.00	23	2425.00	43	2445.00	63	2465.00
4	2406.00	24	2426.00	44	2446.00	64	2466.00
5	2407.00	25	2427.00	45	2447.00	65	2467.00
6	2408.00	26	2428.00	46	2448.00	66	2468.00
7	2409.00	27	2429.00	47	2449.00	67	2469.00
8	2410.00	28	2430.00	48	2450.00	68	2470.00
9	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00		

Test frequencies are lowest channel: 2402 MHz, middle channel: 2441 MHz and highest channel: 2480 MHz for Bluetooth BR & EDR

Table 5: RF Channel and Frequency of Bluetooth LE

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz for Bluetooth LE

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode (BR & EDR mode)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Bluetooth transmitting mode (Bluetooth LE mode)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- C. On, Transmitting on Hopping channel
- D. On, Charging + BT Link
- E. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - User Manual |
| - Operation Description | - FCC/IC Label and Location Info |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024.

According to clause 3.1, all tests were performed on model AVA111E2US in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 6: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
CellPhone	Xiaonmi	Redmi Note10	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 6.8

According to the manufacturer declared, the EUT has Integral Antenna, permanent attachment and no consideration of replacement, refer to section 3.2 for details.

Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:Seite 16 von 27
Page 16 of 27

5.1.2 Maximum Peak Conducted Output Power

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(b)(1)&(3) RSS-247 Clause 6.2.3.2 & RSS-247 Clause 6.3.2
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: FCC: FHSS < 0.125 Watts, DSSS < 1.0 Watts IC: FHSS < 1.0 Watts, DSSS < 1.0 Watts
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 17 von 27
Page 17 of 27

5.1.3 Conducted Power Spectral Density

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(e) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 8 dBm / 3kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 18 von 27
Page 18 of 27

5.1.4 6dB Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(a)(2) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: > 500 kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 19 von 27
Page 19 of 27

5.1.5 99% Bandwidth

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(a)
RSS-Gen Clause 6.7
Basic standard : ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+
C63.10a:2024
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-03-09 to 2026-03-13
Input voltage : Fully charged battery
Operation mode : A, B
Test channel : Low / Middle / High
Ambient temperature : 24 °C
Relative humidity : 56 %
Atmospheric pressure : 101.3 kPa

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 20 von 27
Page 20 of 27

5.1.6 20dB Bandwidth

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(a)(1)
RSS-247 Clause 6.2.3.1
Basic standard : ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+
C63.10a:2024
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-03-09 to 2026-03-13
Input voltage : Fully charged battery
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24 °C
Relative humidity : 56 %
Atmospheric pressure : 101.3 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:Seite 21 von 27
Page 21 of 27

5.1.7 Carrier Frequency Separation

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1) RSS-247 Clause 6.2.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: $\geq 25\text{kHz}$ or $2/3$ of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: C
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 22 von 27
Page 22 of 27

5.1.8 Number of Hopping Frequency

RESULT:

Pass

Test Specification

Test standard	: FCC part 15.247(a)(1)(iii) RSS-247 Clause 6.2.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: ≥ 15 non-overlapping channels
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: C
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:

Seite 23 von 27
Page 23 of 27

5.1.9 Time of Occupancy

RESULT:

Pass

Test Specification

Test standard	: FCC part 15.247(a)(1)(iii) RSS-247 Clause 6.2.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 0.4s
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: C
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:Seite 24 von 27
Page 24 of 27

5.1.10 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(d) RSS-247 Clause 6.6
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09 to 2026-03-13
Input voltage	: Fully charged battery
Operation mode	: A, B, C
Test channel	: Low / Middle / High
Ambient temperature	: 24 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101.3 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:Seite 25 von 27
Page 25 of 27

5.1.11 Radiated Spurious Emission

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 2.4
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Section 8.9 & 8.10
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2026-03-10 to 2026-03-11
Input voltage	: Fully charged battery
Operation mode	: A, B
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101.3 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A, B.

Prüfbericht - Nr.: CN268YGY 002
Test Report No.:Seite 26 von 27
Page 26 of 27**5.1.12 Conducted Emission on AC Mains****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.207(a) RSS-Gen Section 8.8
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Frequency range	: 0.15 – 30MHz
Classification	: Class B
Limits	: FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-03-09
Input voltage	: AC 120V, 60Hz
Operation mode	: D
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix C.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of EUT.....	9
Table 4: RF Channel and Frequency of Bluetooth BR & EDR	10
Table 5: RF Channel and Frequency of Bluetooth LE	10
Table 6: List of Accessories and Auxiliary Equipment.....	12