

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: JM Zengge Co.,Ltd
Address of applicant: Unit 401 & 501, Building 3, 8 Dongsheng Road, Jianghai District, Jiangmen City 529000, China

Manufacturer: JM Zengge Co.,Ltd
Address of manufacturer: Unit 401 & 501, Building 3, 8 Dongsheng Road, Jianghai District, Jiangmen City 529000, China

General Description of EUT:

Product Name: LED Matrix Panel

Trade Name /

Model No.: ZJ-BPSB3-RGB2-9616-CS-A-S
ZJ-BPSB1-RGB2-6416-CS-A-S, ZJ-BPSB2-RGB2-3216-CS-A-S,
ZJ-BPSB4-RGB2-12816-CS-A-S, ZJ-BPSB1-RGB2-6416-CS-S,
ZJ-BPSB2-RGB2-3216-CS-S, ZJ-BPSB3-RGB2-9616-CS-S,
ZJ-BPSB4-RGB2-12816-CS-S, ZJ-BPSB10-RGB2-4824-AS-S,
ZJ-BPSB11-RGB2-6432-AS-S, ZJ-BPSB12-RGB2-9632-AS-S,
ZJ-BPSB13-RGB2-12832-AS-S, ZJ-BPSB14-RGB2-16032-AS-S,
ZJ-BPSB15-RGB2-19232-AS-S, ZJ-BPSB21-RGB2-11248-AS-S,
ZJ-BPSB21-RGB2-11248-AS-USB-S, ZJ-BPSB31-RGB2-14464-AS-S,
ZJ-BPSB31-RGB2-14464-AS-USB-S, ZJ-BPSA1S-2-6416-CS-OVH-S,
ZJ-BPSA1S-2-CS-OVH-EN-S, ZJ-BPSA2S-2-6416-CS-OVH-S,
ZJ-BPSA2S-A2X2-CS-OVH-EN-S, ZJ-BPSAT1S-2-CS-OVH-EN-S,
ZJ-BPSAT1S-2-6416-CS-OVH-S, ZJ-BPSAT1S-2-CS-S,
ZJ-BPSAT1S-2-CS-S-M02, ZJ-BPSAT2S-2-CS-OVH-S,
Adding Model(s): ZJ-BPSAT2S-2-CS-OVH-EN-S, ZJ-BPSAT2S-2-CS-S,
ZJ-BPSAT2S-2-CS-S-M02, ZJ-BPSAT3S-2-CS-S,
ZJ-BPSAT2S-2-AS-S, ZJ-BPSAT3S-2-AS-S, ZJ-BPSAT4S-2-AS-S,
ZJ-BPSC1-HC2-C1X2-CS-S, ZJ-BPSC2-HC2-C2X2-CS-S,
ZJ-BPSC3-HC2-C3X2-CS-S, ZJ-BPSC4-HC2-7212-CS-S,
ZJ-BPSC5-HC2-9012-CS-S, ZJ-BPSC6-HC2-12012-CS-S,
ZJ-BPSD1-HC2-9616-AS-S, ZJ-BPSD1-HC2-9616-AS-USB-S,
ZJ-BPSD2-HC2-14416-AS-S, ZJ-BPSD2-HC2-14416-AS-USB-S,
ZJ-BPSD3-HC2-19216-AS-S, ZJ-BPSD3-HC2-19216-AS-USB-S,
ZJ-BPSD4-HC2-12816-AS-S, ZJ-BPSD4-HC2-12816-AS-USB-S,
ZJ-WPSD1-HC2-9616-AS-S, ZJ-WPSD1-HC2-9616-AS-USB-S,
ZJ-WPSD2-HC2-14416-AS-S, ZJ-WPSD2-HC2-14416-AS-USB-S,
ZJ-WPSD3-HC2-19216-AS-S, ZJ-WPSD3-HC2-19216-AS-USB-S,
ZJ-WPSD4-HC2-12816-AS-S, ZJ-WPSD4-HC2-12816-AS-USB-S,

ZJ-BPSDT1-HC2-9616-AS-S, ZJ-BPSDT1-HC2-9616-AS-USB-S,
ZJ-BPSDT2-HC2-14416-AS-S, ZJ-BPSDT2-HC2-14416-AS-USB-S,
ZJ-BPSDT3-HC2-19216-AS-S, ZJ-BPSDT3-HC2-19216-AS-USB-S,
ZJ-BPSDT4-HC2-12816-AS-S, ZJ-BPSDT4-HC2-12816-AS-USB-S,
ZJ-BPSDT11-HC2-9632-AS-S, ZJ-BPSDT11-HC2-9632-AS-USB-S,
ZJ-BPSDT12-HC2-14432-AS-S, ZJ-BPSDT13-HC2-19232-AS-S,
ZJ-BPSDT14-HC2-12832-AS-S, ZJ-BPSDT14-HC2-12832-AS-USB-S,
ZJ-WPSDT1-HC2-9616-AS-S, ZJ-WPSDT1-HC2-9616-AS-USB-S,
ZJ-WPSDT2-HC2-14416-AS-S, ZJ-WPSDT2-HC2-14416-AS-USB-S,
ZJ-WPSDT3-HC2-19216-AS-S, ZJ-WPSDT3-HC2-19216-AS-USB-S,
ZJ-WPSDT4-HC2-12816-AS-S, ZJ-WPSDT4-HC2-12816-AS-USB-S,
ZJ-WPSDT11-HC2-9632-AS-S, ZJ-WPSDT11-HC2-9632-AS-USB-S,
ZJ-WPSDT12-HC2-14432-AS-S, ZJ-WPSDT13-HC2-19232-AS-S,
ZJ-WPSDT14-HC2-12832-AS-S, ZJ-WPSDT14-HC2-12832-AS-USB-S,
ZJ-BPSC1-HC2-C1X2-CS-B16, ZJ-BPSC2-HC2-C2X2-CS-B16,
ZJ-BPSC3-HC2-C3X2-CS-B16, ZJ-BPSC4-HC2-7212-CS-B16,
ZJ-BPSC5-HC2-9012-CS-B16, ZJ-BPSC6-HC2-12012-CS-B16,
ZJ-BGSEG1-7-9616-AS-W-S, ZJ-BGSEG2-7-14416-AS-W-S,
ZJ-BGSEG3-7-19216-AS-W-S, ZJ-BPSC1-HC2-C1X2-CS-A-S,
ZJ-BPSC2-HC2-C2X2-CS-A-S, ZJ-BPSC3-HC2-C3X2-CS-A-S,
ZJ-BPSC4-HC2-7212-CS-A-S, ZJ-BPSC5-HC2-9012-CS-A-S,
ZJ-BPSC6-HC2-12012-CS-A-S, ZJ-BPSC1-HC2-C1X2-CS-A-STD-S,
ZJ-BPSC2-HC2-C2X2-CS-A-STD-S, ZJ-BPSC3-HC2-C3X2-CS-A-STD-S,
ZJ-BPSC4-HC2-7212-CS-A-STD-S, ZJ-BPSC5-HC2-9012-CS-A-STD-S,
ZJ-BPSC6-HC2-12012-CS-A-STD-S, ZJ-OVCUA-SH2-1K-CS,
ZJ-OVCUA-SH2-1K-CS-EN

Rated Voltage: DC 5V
Power Adapter: /
FCC ID: 2ASVX-ZJBTCSC
Equipment Type: Portable device

Technical Characteristics of EUT:

Bluetooth

Bluetooth Version: V5.0 (LE mode)
Frequency Range: 2402-2480MHz
RF Output Power: -7.42dBm (Conducted)
Data Rate: 1Mbps
Modulation: GFSK
Quantity of Channels: 40
Channel Separation: 2MHz
Type of Antenna: PCB Antenna
Antenna Gain: -10.37dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Bluetooth	2402	-7.42	-10.37	100	-7.00	-19.52

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm) (mW)		Exposure Limit (mW)	Ratio	Result Pass/Fail
2402	B	0.5	-7.00	0.20	2.788	0.07	Pass

*Note: 1. Time-Averaged Power=Output Power * Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB*

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result Pass/Fail
--	--	--	--	--	--

Result: Pass