



No.:  
FCCSZ2024-0023-H

## TEST REPORT

FCC ID : 2ASWY24PIONEERX101


NAME OF SAMPLE : GPS Tracker

APPLICANT : SHENZHEN TOPFLYtech CO., LIMITED

CLASSIFICATION OF TEST : N/A

**CVC Testing Technology (Shenzhen) Co., Ltd.**



|                                                                                                                                                                  |            |                                                                                                                                                                                    |                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>                                                                                                                                                 |            | Name: SHENZHEN TOPFLYtech CO., LIMITED<br><br>Address: Rm 409, Scientific Research Building, Tsinghua Hi-tech Park Hi-tech Industrial Nanshan District, Shenzhen, Guangdong, China |                                                                                                                                                                       |
| <b>Manufacturer</b>                                                                                                                                              |            | Name: SHENZHEN TOPFLYtech CO., LIMITED<br><br>Address: Rm 409, Scientific Research Building, Tsinghua Hi-tech Park Hi-tech Industrial Nanshan District, Shenzhen, Guangdong, China |                                                                                                                                                                       |
| <b>Equipment Under Test</b>                                                                                                                                      |            | Name: GPS Tracker<br><br>Model/Type: PioneerX 101<br><br>Brand: TOPFLYtech<br><br>Serial NO.: N/A<br><br>Sample NO.: 4-1                                                           |                                                                                                                                                                       |
| Date of Receipt.                                                                                                                                                 | 2024-04-11 | Date of Testing                                                                                                                                                                    | 2024-04-12~2024-07-18                                                                                                                                                 |
| <b>Test Specification</b>                                                                                                                                        |            | <b>Test Result</b>                                                                                                                                                                 |                                                                                                                                                                       |
| FCC Part 2 (Section 2.1091)<br>KDB 447498 D04 v01<br>IEEE C95.1                                                                                                  |            | PASS                                                                                                                                                                               |                                                                                                                                                                       |
| <b>Evaluation of Test Result</b>                                                                                                                                 |            | The equipment under test was found to comply with the requirements of the standards applied.<br><br>Seal of CVC<br><b>Issue Date: 2024-07-18</b>                                   |                                                                                                                                                                       |
| Tested by:<br><br><br><b>Zhu Yulin</b><br>Name                      Signature |            | Reviewed by:<br><br><br><b>Mo Xianbiao</b><br>Name                      Signature               | Approved by:<br><br><br><b>Dong Sanbi</b><br>Name                      Signature |
| <b>Other Aspects: NONE.</b>                                                                                                                                      |            |                                                                                                                                                                                    |                                                                                                                                                                       |
| Abbreviations: OK,    Pass= passed    Fail = failed    N/A= not applicable    EUT= equipment, sample(s) under tested                                             |            |                                                                                                                                                                                    |                                                                                                                                                                       |

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



## TABLE OF CONTENTS

|                                                        |   |
|--------------------------------------------------------|---|
| RELEASE CONTROL RECORD .....                           | 4 |
| 1. GENERAL INFORMATION .....                           | 5 |
| 2. DESCRIPTION OF ACCESSORIES .....                    | 5 |
| 3. RF EXPOSURE LIMIT .....                             | 6 |
| 4. CLASSIFICATION .....                                | 8 |
| 5. ANTENNA GAIN .....                                  | 8 |
| 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER ..... | 9 |



## RELEASE CONTROL RECORD

| ISSUE NO.        | REASON FOR CHANGE | DATE ISSUED |
|------------------|-------------------|-------------|
| FCCSZ2024-0023-H | Original release  | 2024-07-18  |



## 1. GENERAL INFORMATION

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| PRODUCT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | GPS Tracker                                                                                       |
| BRAND                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | TOPFLYtech                                                                                        |
| MODEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | PioneerX 101                                                                                      |
| ADDITIONAL MODEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | N/A                                                                                               |
| POWER SUPPLY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1. DC 5V from USB host<br>2. DC 3.7V from Li-ion battery<br>3. DC 12V/24V from Electrical harness |
| MODULATIONTECHNOLOGY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | GFSK                                                                                              |
| MODULATION TYPE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | GFSK for BT-LE                                                                                    |
| OPERATING FREQUENCY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2402MHz ~ 2480MHz for BT-LE (1Mbps/2Mbps)                                                         |
| NUMBER OF CHANNEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | GFSK (1Mbps/2Mbps): 40                                                                            |
| PEAK OUTPUT POWER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 6.64dBm (Maximum)                                                                                 |
| ANTENNA TYPE AND GAIN<br>(Remark 4/5)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | See Section 5                                                                                     |
| I/O PORTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Refer to user's manual                                                                            |
| CABLE SUPPLIED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | N/A                                                                                               |
| <p>Remark:</p> <ol style="list-style-type: none"><li>For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.</li><li>For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.</li><li>Please refer to the EUT photo document for detailed product photo. (Report NO.: FCCSZ2024-0023-EUT)</li><li>Please refer to the antenna report.</li><li>Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, CVC is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.</li></ol> |                                                                                                   |

## 2. DESCRIPTION OF ACCESSORIES

N/A



## 3. RF EXPOSURE LIMIT

(Option B) According to FCC Part2.1091 and FCC Part1.1307b, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz;

and

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

(Option C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source Frequency (MHz) | Threshold ERP (W) |
|---------------------------|-------------------|
| 0.3 - 1.34                | $1920R^2$         |
| 1.34 - 30                 | $3450R^2 / f^2$   |
| 30 - 300                  | $3.38R^2$         |
| 300 - 1500                | $0.0128R^2 / f^2$ |
| 1500 - 100000             | $19.2R^2$         |



For multiple RF sources: Multiple RF sources are exempt if:

- The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

*Evaluatedk* = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

*Exposure Limitk* = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



## 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

| Mode     | Frequency (MHz) | Peak Gain (dBi) |
|----------|-----------------|-----------------|
| BT-LE    | 2402 ~ 2480     | 2.17            |
| GSM850*  | 824 ~ 849       | -1.88           |
| GSM1900* | 1850 ~ 1910     | 0.79            |
| LTE B2*  | 1850 ~ 1910     | 0.79            |
| LTE B4*  | 1710 ~ 1755     | 0.63            |
| LTE B5*  | 824 ~ 849       | -1.88           |
| LTE B7*  | 2500 ~ 2570     | 0.61            |
| LTE B12* | 699 ~ 716       | -2.34           |
| LTE B13* | 777 ~ 787       | -2.18           |
| LTE B17* | 704 ~ 716       | -2.84           |
| LTE B25* | 1850 ~ 1915     | 0.75            |
| LTE B26* | 814~ 849        | -1.88           |
| LTE B38* | 2570 ~ 2620     | -0.46           |
| LTE B40* | 2305 ~ 2315     | -0.20           |
|          | 2350 ~ 2360     | -0.17           |
| LTE B41* | 2496 ~ 2690     | 0.61            |
| LTE B66* | 1710 ~ 1780     | 0.63            |

Remark:

1. This is provided by the manufacturer. The laboratory is not responsible for technical data provided by the customer.
2. \*The EUT contains a certified module (FCC ID: 2AJYU-8BAE003), according to the MPE reports of FCC ID: 2AJYU-8BAE003, Date of Grant: 07/08/2024.



## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

| Mode     | Maximum<br>tune up<br>power<br>(dBm) | Maximum<br>Antenna<br>Gain<br>(dBi) | EIRP<br>(dBm) | ERP<br>(dBm) | ERP<br>(mW) | Part1.1307b<br>Threshold<br>(mW) | Ratio        | Verify |
|----------|--------------------------------------|-------------------------------------|---------------|--------------|-------------|----------------------------------|--------------|--------|
| BT-LE    | 7                                    | 2.17                                | 9.17          | 7.02         | 5.04        | 3060                             | <b>0.002</b> | PASS   |
| GSM850*  | 23.97                                | -1.88                               | 22.09         | 19.94        | 98.63       | 1680.96                          | 0.059        | PASS   |
| GSM1900* | 19.97                                | 0.79                                | 20.76         | 18.61        | 72.61       | 3060                             | 0.024        | PASS   |
| LTE B2*  | 24.00                                | 0.79                                | 24.79         | 22.64        | 183.65      | 3060                             | 0.060        | PASS   |
| LTE B4*  | 25.00                                | 0.63                                | 25.63         | 23.48        | 222.84      | 3060                             | 0.073        | PASS   |
| LTE B5*  | 24.00                                | -1.88                               | 22.12         | 19.97        | 99.31       | 1680.96                          | 0.059        | PASS   |
| LTE B7*  | 22.00                                | 0.61                                | 22.61         | 20.46        | 111.17      | 3060                             | 0.036        | PASS   |
| LTE B12* | 25.00                                | -2.34                               | 22.66         | 20.51        | 112.46      | 1425.96                          | <b>0.079</b> | PASS   |
| LTE B13* | 24.00                                | -2.18                               | 21.82         | 19.67        | 92.68       | 1585.08                          | 0.058        | PASS   |
| LTE B17* | 25.00                                | -2.84                               | 22.16         | 20.01        | 100.23      | 1436.16                          | 0.070        | PASS   |
| LTE B25* | 24.00                                | 0.75                                | 24.75         | 22.6         | 181.97      | 3060                             | 0.059        | PASS   |
| LTE B26* | 24.00                                | -1.88                               | 22.12         | 19.97        | 99.31       | 1660.56                          | 0.060        | PASS   |
| LTE B38* | 24.00                                | -0.46                               | 23.54         | 21.39        | 137.72      | 3060                             | 0.045        | PASS   |
| LTE B40* | 23.98                                | -0.17                               | 23.81         | 21.66        | 146.55      | 3060                             | 0.048        | PASS   |
| LTE B41* | 24.00                                | 0.61                                | 24.61         | 22.46        | 176.20      | 3060                             | 0.058        | PASS   |
| LTE B66* | 25.00                                | 0.63                                | 25.63         | 23.48        | 222.84      | 3060                             | 0.073        | PASS   |

Remark: \*The EUT contains a certified module (FCC ID: 2AJYU-8BAE003), according to the MPE reports of FCC ID: 2AJYU-8BAE003, Date of Grant: 07/08/2024.

## CALCULATION FOR SIMULTANEOUS TRANSMISSION:

BT and GSM/LTE can transmit simultaneously, the formula of calculated the MPE is

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Max:  $0.002 + 0.079 = 0.081 < 1$ , which is less than the "1" limit.

----- End of the Report -----



## Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

Address: No. 1301-14&16, Guanguang Road, Xinlan Community, Guanlan Subdistrict,  
Longhua District, Shenzhen, Guangdong, China

Post Code: 518110      Tel: 0755-23763060-8805

Fax: 0755-23763060      E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>