# RADIO TEST REPORT
# FCC ID: 2AT26-M029B

| | | |
|---|---|---|
| **Product Designation** | : | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology |
| **Trademark** | : | MAGNAVOX,CRAIG,borne,Bluestream,naxa |
| **Model Name** | : | MM435,M029B,MS500B,BS029MS,NS-441,MM434 |
| **Applicant** | : | Dongguan Yihua Electrical Appliance Technology CO., LTD |
| **Date of Issue** | : | July. 23, 2020 |
| **Standard(s)** | : | FCC Part 15.247 |
| **Report No** | : | S20072801206001 |

**Prepared for**

Dongguan Yihua Electrical Appliance Technology CO., LTD
No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet,
Wangniudun Town, Dongguan City,Guangdong Province, China

## Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China
Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599
Website:http://www.ntek.org.cn

## REPORT REVISE RECORD

| Report No | Revise Time | Issued Date | Valid Version | Notes |
|---|---|---|---|---|
| S20072801206001 | / | July 23, 2020 | Invalid | Initial release |

## TABLE OF CONTENTS

**1. GENERAL INFORMATION.....5**

1.1. PRODUCT DESCRIPTION.....5
1.2. TABLE OF CARRIER FREQUENCYS.....5
1.3. RECEIVER INPUT BANDWIDTH.....6
1.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE.....6
1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR.....6
1.6. RELATED SUBMITTAL(S) / GRANT (S).....6
1.7. TEST METHODOLOGY.....7

**2. MEASUREMENT UNCERTAINTY.....7**

**3. DESCRIPTION OF TEST MODES.....7**

**4. SYSTEM TEST CONFIGURATION.....8**

4.1. CONFIGURATION OF EUT SYSTEM.....8
4.2 EQUIPMENT USED IN TESTED SYSTEM.....8
4.3. SUMMARY OF TEST RESULTS.....8

**5. TEST FACILITY.....9**

**6. PEAK OUTPUT POWER.....10**

6.1. MEASUREMENT PROCEDURE.....10
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....10
6.3. LIMITS AND MEASUREMENT RESULT.....11

**7. 20DB BANDWIDTH.....17**

7.1. MEASUREMENT PROCEDURE.....17
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....17
7.3. LIMITS AND MEASUREMENT RESULTS.....17

**8. CONDUCTED SPURIOUS EMISSION.....24**

8.1. MEASUREMENT PROCEDURE.....24
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....24

8.3. MEASUREMENT EQUIPMENT USED..... 24
8.4. LIMITS AND MEASUREMENT RESULT..... 24

**9. RADIATED EMISSION..... 34**

9.1. MEASUREMENT PROCEDURE..... 34
9.2. TEST SETUP..... 36
9.3. LIMITS AND MEASUREMENT RESULT..... 37
9.4. TEST RESULT..... 37

**10. NUMBER OF HOPPING FREQUENCY..... 47**

10.1. MEASUREMENT PROCEDURE..... 47
10.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)..... 47
10.3. MEASUREMENT EQUIPMENT USED..... 47
10.4. LIMITS AND MEASUREMENT RESULT..... 47

**11. TIME OF OCCUPANCY (DWELL TIME)..... 48**

11.1. MEASUREMENT PROCEDURE..... 48
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)..... 48
11.3. MEASUREMENT EQUIPMENT USED..... 48
11.4. LIMITS AND MEASUREMENT RESULT..... 48

**12. FREQUENCY SEPARATION..... 52**

12.1. MEASUREMENT PROCEDURE..... 52
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)..... 52
12.3. MEASUREMENT EQUIPMENT USED..... 52
12.4. LIMITS AND MEASUREMENT RESULT..... 52

**13. FCC LINE CONDUCTED EMISSION TEST..... 55**

13.1. LIMITS OF LINE CONDUCTED EMISSION TEST..... 55
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST..... 55
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST..... 56
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST..... 56
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST..... 57

**APPENDIX A: PHOTOGRAPHS OF TEST SETUP..... 59**

# TEST RESULT CERTIFICATION

**Applicant's name**.....: Dongguan Yihua Electrical Appliance Technology CO., LTD

Address..... : No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City,Guangdong Province, China

**Manufacturer's Name**..... : Dongguan Yihua Electrical Appliance Technology CO., LTD

Address..... : No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City,Guangdong Province, China

**Product description**

Product name..... : CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology

Trademark .....: MAGNAVOX,CRAIG,borne,Bluestream,naxa

Model Name ..... : MM435

Series Model.....: M029B,MS500B,BS029MS,NS-441,MM434

Difference Description.....: The circuit principle and internal structure are the same, appearance color and the model name are different.

Rating(s).....: Input: AC 120V 60Hz 18W

**Standards**..... : FCC PART 15.247

We hereby certify that:

The above equipment was tested by Shenzhen NTEK Testing Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

**Date of Test**.....

Date (s) of performance of tests..... July. 11, 2020 to July. 23, 2020

Date of Issue..... July. 23, 2020

Test Result..... **Pass**

Testing Engineer : Leo.Zhu

(Leo.Zhu)

Technical Manager : Eder.Zhan

(Eder.Zhan)

Authorized Signatory : Wetow Huang

(Wetow Huang)

# 1. GENERAL INFORMATION

## 1.1. PRODUCT DESCRIPTION

The EUT is designed as “Bluetooth Headset”. It is designed by way of utilizing the GFSK, Pi/4 DQPSK and 8DPSK technology to achieve the system operation.

A major technical description of EUT is described as following

| | |
|---|---|
| **Operation Frequency** | 2.402 GHz to 2.480GHz |
| **RF Output Power** | 1.36dBm(Max) |
| **Bluetooth Version** | V 5.0 |
| **Modulation** | BR ☒ GFSK, EDR ☒ π /4-DQPSK, ☒ 8DPSK<br>BLE ☐ GFSK 1Mbps ☐ GFSK 2Mbps |
| **Number of channels** | 79 |
| **Hardware Version** | V1.0 |
| **Software Version** | V1.0 |
| **Antenna Designation** | PCB Antenna(Comply with requirements of the FCC part 15.203) |
| **Antenna Gain** | 1.0dBi |
| **Power Supply** | Input: DC 5V 1.0A by Micro USB; 3.7V by Battery |

## 1.2. TABLE OF CARRIER FREQUENCYS

| Frequency Band | Channel Number | Frequency |
|---|---|---|
| 2402~2480MHZ | 0 | 2402MHZ |
| | 1 | 2403MHZ |
| | : | : |
| | 38 | 2440 MHZ |
| | 39 | 2441 MHZ |
| | 40 | 2442 MHZ |
| | : | : |
| | 77 | 2479 MHZ |
| | 78 | 2480 MHZ |

**1.3. RECEIVER INPUT BANDWIDTH**

The input bandwidth of the receiver is 1.3MHZ,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

**1.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE**

Example of a 79 hopping sequence in data mode:
40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06
01, 51, 03, 55, 05, 04

**1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR**

The generation of the hopping sequence in connection mode depends essentially on two input values:
1. LAP/UAP of the master of the connection.
2. Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD_ADDRESS.The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For ehavior zation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us.The clock has a cycle of about one day(23h30).In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire. LAP(24 bits),4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permutations, additions, XOR-operations)are performed to generate te Sequence. This will be done at the beginning of every new transmission.Regarding short transmissions the Bluetooth system has the following ehavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter) than the minimum resolution of the clock(312.5us).The hopping sequence will always Differ from the first one.

**1.6. RELATED SUBMITTAL(S) / GRANT (S)**

This submittal(s) (test report) is intended for **FCC ID: 2AT26-M029B** filing to comply with the FCC PART 15.247 requirements.

### 1.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013).
Radiated testing was performed at an antenna to EUT distance 3 meters.

## 2. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB
- Uncertainty of total RF power, conducted, Uc = ±0.8dB
- Uncertainty of spurious emissions, conducted, Uc = ±2.7dB
- Uncertainty of Occupied Channel Bandwidth: Uc = ±2 %
- Uncertainty of Dwell Time: Uc = ±2 %
- Uncertainty of Frequency: Uc = ±2 %

## 3. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|---|---|
| 1 | Low channel GFSK |
| 2 | Middle channel GFSK |
| 3 | High channel GFSK |
| 4 | Low channel π/4-DQPSK |
| 5 | Middle channel π/4-DQPSK |
| 6 | High channel π/4-DQPSK |
| 7 | Low channel 8DPSK |
| 8 | Middle channel 8DPSK |
| 9 | High channel 8DPSK |
| 10 | Hopping mode GFSK |
| 11 | Hopping mode π/4-DQPSK |
| 12 | Hopping mode 8DPSK |

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
4. The test software is the Blue Test3 which can set the EUT into the individual test modes.

# 4. SYSTEM TEST CONFIGURATION

## 4.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure :




Conducted Emission Configure :




## 4.2 EQUIPMENT USED IN TESTED SYSTEM

| Item | Equipment | Model No. | ID or Specification | Remark |
|---|---|---|---|---|
| 1 | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | MM435,M029B,MS500B,BS029MS,NS-441,MM434 | 2AT26-M029B | EUT |
| 2 | Charger line | / | 0.7m | AE |
| | | | | |

## 4.3. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|---|---|---|
| 15.247 (b)(1) | Peak Output Power | Compliant |
| 15.247 (a)(1) | 20 dB Bandwidth | Compliant |
| 15.247 (d) | Conducted Spurious Emission | Compliant |
| 15.209 | Radiated Emission | Compliant |
| 15.247 (a)(1)(iii) | Number of Hopping Frequency | Compliant |
| 15.247 (a)(1)(iii) | Time of Occupancy | Compliant |
| 15.247 (a)(1) | Frequency Separation | Compliant |
| 15.207 | Conducted Emission | Compliant |

## 5. TEST FACILITY

| | | |
|---|---|---|
| Site Description | | |
| CNAS-Lab. | : | The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)<br>The Certificate Registration Number is L5516. |
| IC-Registration | : | The Certificate Registration Number is 9270A-1. |
| FCC- Accredited | : | Test Firm Registration Number: 463705.<br>Designation Number: CN1184 |
| A2LA-Lab. | : | The Certificate Registration Number is 4298.01<br>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.<br>This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system<br>(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009). |
| Name of Firm | : | Shenzhen NTEK Testing Technology Co., Ltd. |
| Site Location | : | 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China. |

### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|---|---|---|---|---|---|
| TEST RECEIVER | R&S | ESPI | 101206 | Jun. 10, 2020 | Jun. 09, 2021 |
| LISN | R&S | ESH2-Z5 | 101313 | Apr. 18, 2020 | Apr. 17, 2021 |

### TEST EQUIPMENT OF RADIATED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|---|---|---|---|---|---|
| TEST RECEIVER | R&S | ESCI | 10096 | Jun. 10, 2020 | Jun. 09, 2021 |
| EXA Signal Analyzer | Aglient | N9020A | MY49100060 | May. 11, 2020 | May. 10,, 2021 |
| 2.4GHz Fliter | EM Electronics | 2400-2500MHz | N/A | Feb. 27, 2020 | Feb. 26, 2021 |
| Attenuator | ZHINAN | E-002 | N/A | Aug. 26, 2019 | Aug. 25, 2020 |
| Horn antenna | SCHWARZBECK | BBHA 9170 | #768 | Sep. 21, 2017 | Sep. 20, 2020 |
| Active loop antenna (9K-30MHz) | ZHINAN | ZN30900C | 18051 | Jun. 14, 2020 | Jun. 13, 2022 |
| Double-Ridged Waveguide Horn | ETS LINDGREN | 3117 | 00034609 | May. 26, 2020 | May. 25, 2022 |
| Broadband Preamplifier | ETS LINDGREN | 3117PA | 00225134 | Oct. 25, 2019 | Oct. 24, 2020 |
| ANTENNA | SCHWARZBECK | VULB9168 | D69250 | Sep. 28, 2020 | Sep. 27, 2022 |
| Spectrum analyzer | R&S | FSU | HKE-048 | Dec. 20, 2019 | Dec. 19, 2020 |

# 6. PEAK OUTPUT POWER

## 6.1. MEASUREMENT PROCEDURE

For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
3. RBW > 20 dB bandwidth of the emission being measured.
4. VBW ≥RBW.
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

## 6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

**PEAK POWER TEST SETUP**



## 6.3. LIMITS AND MEASUREMENT RESULT

| PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION | | | |
|---|---|---|---|
| **Frequency (GHz)** | **Peak Power (dBm)** | **Applicable Limits (dBm)** | **Pass or Fail** |
| 2.402 | -1.81 | 30 | Pass |
| 2.441 | -2.82 | 30 | Pass |
| 2.480 | -4.08 | 30 | Pass |

CH0



## CH39




Date: 22.JUL.2020 13:34:04

## CH78




Date: 22.JUL.2020 13:34:29

| PEAK OUTPUT POWER MEASUREMENT RESULT FOR Π /4-DQPSK MODULATION | | | |
|---|---|---|---|
| **Frequency (GHz)** | **Peak Power (dBm)** | **Applicable Limits (dBm)** | **Pass or Fail** |
| 2.402 | 0.94 | 30 | Pass |
| 2.441 | -0.50 | 30 | Pass |
| 2.480 | -1.43 | 30 | Pass |

CH0



## CH39




Date: 22.JUL.2020 13:35:34

## CH78




Date: 23.JUL.2020 11:05:01

| PEAK OUTPUT POWER MEASUREMENT RESULT FOR 8-DPSK MODULATION | | | |
|---|---|---|---|
| **Frequency (GHz)** | **Peak Power (dBm)** | **Applicable Limits (dBm)** | **Pass or Fail** |
| 2.402 | 1.36 | 30 | Pass |
| 2.441 | 0.25 | 30 | Pass |
| 2.480 | -1.08 | 30 | Pass |

CH0




Date: 22.JUL.2020 13:36:14

## CH39




Date: 22.JUL.2020 13:36:28

## CH78




Date: 22.JUL.2020 13:38:12

# 7. 20DB BANDWIDTH

## 7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
   The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




## 7.3. LIMITS AND MEASUREMENT RESULTS

| MEASUREMENT RESULT FOR GFSK MOUDULATION | | | |
|---|---|---|---|
| Applicable Limits | Measurement Result | | |
| | Test Data (MHz) | | Criteria |
| N/A | Low Channel | 814.102 | PASS |
| | Middle Channel | 814.1025 | PASS |
| | High Channel | 814.102 | PASS |

## TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:12:42

## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




Date: 23.JUL.2020 11:13:25

# TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




Date: 23.JUL.2020 11:13:59

| MEASUREMENT RESULT FORΠ /4-DQPSK MODULATION | | | |
|---|---|---|---|
| Applicable Limits | Measurement Result | | |
| | Test Data (MHz) | | Criteria |
| N/A | Low Channel | 1.29807 | PASS |
| | Middle Channel | 1.2980 | PASS |
| | High Channel | 1.2980 | PASS |

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:15:49

## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




Date: 23.JUL.2020 11:15:28

## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




Date: 23.JUL.2020 11:15:02

| MEASUREMENT RESULT FOR 8-DPSK MODULATION | | | |
|---|---|---|---|
| Applicable Limits | Measurement Result | | |
| | Test Data (MHz) | | Criteria |
| N/A | Low Channel | 1.2916 | PASS |
| | Middle Channel | 1.2948 | PASS |
| | High Channel | 1.2980 | PASS |

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:16:14

## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




Date: 23.JUL.2020 11:16:38

## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




Date: 23.JUL.2020 11:17:05

# 8. CONDUCTED SPURIOUS EMISSION

## 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
   RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
4. Set SPA Trace 1 Max hold, then View.

## 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2

## 8.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

## 8.4. LIMITS AND MEASUREMENT RESULT

| LIMITS AND MEASUREMENT RESULT | | |
|---|---|---|
| **Applicable Limits** | **Measurement Result** | |
| | **Test Data** | **Criteria** |
| In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.<br>In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a)) | At least -20dBc than the limit Specified on the BOTTOM Channel | PASS |
| | At least -20dBc than the limit Specified on the TOP Channel | PASS |

## TEST RESULT FOR ENTIRE FREQUENCY RANGE

TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF 8DPQSK MODULATION IN LOW CHANNEL




Date: 22.JUL.2020 14:02:10




Date: 22.JUL.2020 14:03:30

TEST PLOT OF OUT OF BAND EMISSIONS
OF 8DPQSK MODULATION IN MIDDLE CHANNEL




Date: 22.JUL.2020 14:04:12




Date: 22.JUL.2020 14:04:50

TEST PLOT OF OUT OF BAND EMISSIONS
OF 8DPQSK MODULATION IN HIGH CHANNEL




Date: 22.JUL.2020 14:05:59




Date: 22.JUL.2020 14:06:41

Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit. The GFSK modulation is the worst case and only those data recorded in the report.

## TEST RESULT FOR BAND EDGE

GFSK MODULATION IN LOW CHANNEL

Hopping off




Date: 22.JUL.2020 14:20:54

Hopping on




Date: 22.JUL.2020 14:24:30

## GFSK MODULATION IN HIGH CHANNEL

### Hopping off




Date: 22.JUL.2020 14:26:39

### Hopping on




Date: 22.JUL.2020 14:28:50

## π /4-DQPSK MODULATION IN LOW CHANNEL

### Hopping off




Date: 22.JUL.2020 14:40:02

### Hopping on




Date: 22.JUL.2020 14:43:21

## π /4-DQPSK MODULATION IN HIGH CHANNEL

### Hopping off




Date: 22.JUL.2020 14:31:43

### Hopping on




Date: 22.JUL.2020 14:36:32

## 8-DPSK MODULATION IN LOW CHANNEL

### Hopping off




Date: 22.JUL.2020 14:49:28

### Hopping on




Date: 22.JUL.2020 14:53:54

## 8-DPSK MODULATION IN HIGH CHANNEL

### Hopping off




Date: 22.JUL.2020 15:04:37

### Hopping on




Date: 22.JUL.2020 15:08:11

# 9. RADIATED EMISSION

## 9.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |
| Start ~Stop Frequency | 1GHz~26.5GHz<br>1MHz/3MHz for Peak, 1MHz/3MHz for Average |

| Receiver Parameter | Setting |
|---|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |

## 9.2. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz




RADIATED EMISSION TEST SETUP ABOVE 1000MHz



## 9.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|---|---|---|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.

## 9.4. TEST RESULT

**RADIATED EMISSION BELOW 30MHZ**

Emission from 9kHz to 30MHz are more than 20dB below the limit.

## RADIATED EMISSION BELOW 1GHZ

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 4 | **Antenna** | Horizontal |




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | | Antenna Height | Table Degree | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector | cm | degree | Comment |
| 1 | * | 33.5770 | 50.61 | -22.11 | 28.50 | 40.00 | -11.50 | QP | | | |
| 2 | | 35.2821 | 45.03 | -23.21 | 21.82 | 40.00 | -18.18 | QP | | | |
| 3 | | 37.2202 | 46.14 | -24.09 | 22.05 | 40.00 | -17.95 | QP | | | |
| 4 | | 44.6064 | 42.43 | -26.63 | 15.80 | 40.00 | -24.20 | QP | | | |
| 5 | | 79.6954 | 44.23 | -30.03 | 14.20 | 40.00 | -25.80 | QP | | | |
| 6 | | 102.7192 | 40.84 | -25.64 | 15.20 | 43.50 | -28.30 | QP | | | |

**RESULT: PASS**

| EUT | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | Model Name | MM435 |
|---|---|---|---|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 4 | Antenna | Vertical |




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | | Antenna Height | Table Degree | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV | dB | dBuV/m | dB/m | dB | Detector | cm | degree | Comment |
| 1 | | 32.3492 | 45.17 | -21.80 | 23.37 | 40.00 | -16.63 | QP | | | |
| 2 | | 34.0813 | 43.89 | -22.89 | 21.00 | 40.00 | -19.00 | QP | | | |
| 3 | * | 36.0638 | 52.63 | -23.77 | 28.86 | 40.00 | -11.14 | QP | | | |
| 4 | | 37.9117 | 40.56 | -24.29 | 16.27 | 40.00 | -23.73 | QP | | | |
| 5 | | 80.8210 | 44.79 | -28.98 | 15.81 | 40.00 | -24.19 | QP | | | |
| 6 | | 102.7192 | 46.75 | -26.14 | 20.61 | 43.50 | -22.89 | QP | | | |

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 4 is the worst case and recorded in the report.

## RADIATED EMISSION ABOVE 1GHZ

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 7 | **Antenna** | Horizontal |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4804.000 | 47.75 | 0.28 | 48.03 | 74 | -25.97 | peak |
| 4804.000 | 41.02 | 0.14 | 41.17 | 54 | -12.83 | AVG |
| 7206.000 | 42.54 | 2.45 | 44.99 | 74 | -29.01 | peak |
| 7206.000 | 37.63 | 2.50 | 40.13 | 54 | -13.87 | AVG |
| | | | | | | |
| | | | | | | |

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 7 | **Antenna** | Vertical |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4804.000 | 46.24 | 0.18 | 46.41 | 74 | -27.59 | peak |
| 4804.000 | 39.74 | 0.26 | 40.00 | 54 | -14.00 | AVG |
| 7206.000 | 42.80 | 2.34 | 45.14 | 74 | -28.86 | peak |
| 7206.000 | 32.53 | 2.50 | 35.03 | 54 | -18.97 | AVG |
| | | | | | | |
| | | | | | | |

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 8 | **Antenna** | Horizontal |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4882.000 | 46.18 | 0.26 | 46.44 | 74 | -27.56 | peak |
| 4882.000 | 42.24 | 0.42 | 42.66 | 54 | -11.34 | AVG |
| 7323.000 | 41.21 | 2.44 | 43.65 | 74 | -30.35 | peak |
| 7323.000 | 37.52 | 2.57 | 40.08 | 54 | -13.92 | AVG |
| | | | | | | |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 8 | **Antenna** | Vertical |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4882.000 | 44.14 | 0.22 | 44.36 | 74 | -29.64 | peak |
| 4882.000 | 39.30 | 0.40 | 39.70 | 54 | -14.30 | AVG |
| 7323.000 | 42.80 | 2.60 | 45.39 | 74 | -28.61 | peak |
| 7323.000 | 36.08 | 2.66 | 38.74 | 54 | -15.26 | AVG |
| | | | | | | |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 9 | **Antenna** | Horizontal |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4960.000 | 47.74 | 0.43 | 48.18 | 74 | -25.82 | peak |
| 4960.000 | 39.06 | 0.50 | 39.56 | 54 | -14.44 | AVG |
| 7440.000 | 41.96 | 2.65 | 44.60 | 74 | -29.40 | peak |
| 7440.000 | 37.06 | 2.74 | 39.81 | 54 | -14.19 | AVG |
| | | | | | | |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 9 | **Antenna** | Vertical |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|---|---|---|---|---|---|
| 4960.000 | 46.45 | 0.22 | 46.67 | 74 | -27.33 | peak |
| 4960.000 | 39.37 | 0.40 | 39.77 | 54 | -14.23 | AVG |
| 7440.000 | 41.16 | 2.91 | 44.07 | 74 | -29.93 | peak |
| 7440.000 | 34.81 | 2.66 | 37.47 | 54 | -16.53 | AVG |
| | | | | | | |
| | | | | | | |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

**RESULT: PASS**

**Note:**

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

All test modes had been tested. The GFSK modulation is the worst case and recorded in the report.

## TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 7 | **Antenna** | Horizontal |

PK




Date: 22.JUL.2020 16:02:03

AV




Date: 22.JUL.2020 16:02:41

**RESULT: PASS**

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 7 | **Antenna** | Vertical |

PK




Date: 22.JUL.2020 16:04:26

AV




Date: 22.JUL.2020 16:03:37

**RESULT: PASS**

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 9 | **Antenna** | Horizontal |

PK




Date: 22.JUL.2020 16:07:43

AV




Date: 22.JUL.2020 16:15:09

**RESULT: PASS**

| | | | |
|---|---|---|---|
| **EUT** | CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology | **Model Name** | MM435 |
| **Temperature** | 25°C | **Relative Humidity** | 55.4% |
| **Pressure** | 960hPa | **Test Voltage** | Normal Voltage |
| **Test Mode** | Mode 9 | **Antenna** | Vertical |

PK




Date: 22.JUL.2020 16:16:33

AV




Date: 22.JUL.2020 16:15:50

**RESULT: PASS**

**Note**: The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(µV) to represent the Amplitude. Use the F dB(µV/m) to represent the Field Strength. So A=F. All test modes had been pre-tested. The GFSK modulation is the worst case and recorded in the report.

# 10. NUMBER OF HOPPING FREQUENCY

## 10.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. VBW ⩾ RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.
4. Allow the trace to stabilize.

## 10.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

## 10.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

## 10.4. LIMITS AND MEASUREMENT RESULT

| TOTAL NO. OF HOPPING CHANNEL | LIMIT (NO. OF CH) | MEASUREMENT (NO. OF CH) | RESULT |
|---|---|---|---|
| | >=15 | 79 | PASS |

TEST PLOT FOR NO. OF TOTAL CHANNELS




Note: The GFSK modulation is the worst case and recorded in the report.

# 11. TIME OF OCCUPANCY (DWELL TIME)

## 11.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
1. Span: Zero span, centered on a hopping channel.
2. RBW shall be≤channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
4. Detector function: Peak. Trace: Max hold.
5. Use the marker-delta function to determine the transmit time per hop.
6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:
(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)
7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

## 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

## 11.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

## 11.4. LIMITS AND MEASUREMENT RESULT

| Channel | Time of Pulse for DH5 (ms) | Number of hops in the period specified in the requirements | Sweep Time (ms) | Limit (ms) |
|---|---|---|---|---|
| Low | 2.341 | 31*3 | 250.038 | 400 |
| Middle | 2.890 | 32*3 | 308.675 | 400 |
| High | 2.879 | 30*3 | 307.500 | 400 |

Note: The 8-DPSK modulation is the worst case and recorded in the report.

# TEST PLOT OF LOW CHANNEL




Date: 22.JUL.2020 16:38:44




Date: 22.JUL.2020 16:49:01

# TEST PLOT OF MIDDLE CHANNEL




Date: 22.JUL.2020 16:41:23




Date: 22.JUL.2020 16:44:06

# TEST PLOT OF HIGH CHANNEL




Date: 22.JUL.2020 16:46:26




Date: 22.JUL.2020 16:48:02

# 12. FREQUENCY SEPARATION

## 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
1. Span: Wide enough to capture the peaks of two adjacent channels.
2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
3. Video (or average) bandwidth (VBW) ≥ RBW.
4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.
Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

## 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

## 12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

## 12.4. LIMITS AND MEASUREMENT RESULT

| CHANNEL | CHANNEL SEPARATION | LIMIT | RESULT |
|---|---|---|---|
| | KHz | KHz | |
| CH00 | 1000 | 2/3 20 dB BW | Pass |
| CH39 | 1005 | 2/3 20 dB BW | Pass |
| CH78 | 1001 | 2/3 20 dB BW | Pass |

TEST PLOT FOR FREQUENCY SEPARATION

CH00




CH39



CH78




Note: The 8-DPSK modulation is the worst case and recorded in the report.

# 13. FCC LINE CONDUCTED EMISSION TEST

## 13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency | Maximum RF Line Voltage | |
|---|---|---|
| | Q.P.( dBuV) | Average( dBuV) |
| 150kHz~500kHz | 66-56 | 56-46 |
| 500kHz~5MHz | 56 | 46 |
| 5MHz~30MHz | 60 | 50 |

Note:
1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### 13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### 13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

## 13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV/m | dB | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 0.1620 | 19.88 | 9.94 | 29.82 | 65.36 | -35.54 | QP | |
| 2 | | 0.1660 | 8.79 | 9.93 | 18.72 | 55.16 | -36.44 | AVG | |
| 3 | | 0.1860 | 8.33 | 9.91 | 18.24 | 54.21 | -35.97 | AVG | |
| 4 | | 0.1945 | 18.89 | 9.90 | 28.79 | 63.84 | -35.05 | QP | |
| 5 | | 0.3060 | 17.48 | 9.92 | 27.40 | 60.08 | -32.68 | QP | |
| 6 | | 0.3067 | 4.07 | 9.92 | 13.99 | 50.06 | -36.07 | AVG | |
| 7 | | 0.3620 | 4.70 | 9.92 | 14.62 | 48.68 | -34.06 | AVG | |
| 8 | * | 0.3660 | 18.28 | 9.92 | 28.20 | 58.59 | -30.39 | QP | |
| 9 | | 0.4380 | 16.28 | 9.92 | 26.20 | 57.10 | -30.90 | QP | |
| 10 | | 0.4420 | 4.31 | 9.92 | 14.23 | 47.02 | -32.79 | AVG | |
| 11 | | 0.6980 | 14.39 | 9.95 | 24.34 | 56.00 | -31.66 | QP | |
| 12 | | 0.7019 | 1.14 | 9.95 | 11.09 | 46.00 | -34.91 | AVG | |

**RESULT: PASS**

Line Conducted Emission Test Line 2-N




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | | |
|---|---|---|---|---|---|---|---|---|---|
| | | MHz | dBuV/m | dB | dBuV/m | dBuV/m | dB | Detector | Comment |
| 1 | | 0.1924 | 17.35 | 9.90 | 27.25 | 63.93 | -36.68 | QP | |
| 2 | | 0.1949 | 8.21 | 9.90 | 18.11 | 53.83 | -35.72 | AVG | |
| 3 | | 0.2404 | 17.22 | 9.90 | 27.12 | 62.08 | -34.96 | QP | |
| 4 | | 0.2429 | 4.30 | 9.90 | 14.20 | 52.00 | -37.80 | AVG | |
| 5 | | 0.2878 | 16.60 | 9.92 | 26.52 | 60.59 | -34.07 | QP | |
| 6 | | 0.2878 | 4.28 | 9.92 | 14.20 | 50.59 | -36.39 | AVG | |
| 7 | | 0.3303 | 14.49 | 9.92 | 24.41 | 59.44 | -35.03 | QP | |
| 8 | | 0.3345 | 4.83 | 9.92 | 14.75 | 49.34 | -34.59 | AVG | |
| 9 | | 0.3704 | 16.61 | 9.93 | 26.54 | 58.49 | -31.95 | QP | |
| 10 | | 0.3704 | 4.19 | 9.93 | 14.12 | 48.49 | -34.37 | AVG | |
| 11 | | 0.4965 | 13.81 | 9.94 | 23.75 | 56.06 | -32.31 | QP | |
| 12 | * | 0.4965 | 4.38 | 9.94 | 14.32 | 46.06 | -31.74 | AVG | |

**RESULT: PASS**

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION TEST SETUP

RADIATED EMISSION TEST SETUP BELOW 1GHZ



RADIATED EMISSION TEST SETUP ABOVE 1GHZ



**----END OF REPORT----**