

OEM GNSS Antenna HX-CSX260A



HX-CSX260A is an embedded full frequency GNSS antenna covering GPS, GLONASS, BDS, GALILEO, and QZSS. It is also compatible with 4G and WiFi /bluetooth, meeting the demand for multi-system compatibility in current survey devices. It can be widely used in various applications such as geodetic surveying, marine surveying, channel surveying, dredging surveying, seismic monitoring, bridge deformation monitoring, landslide monitoring, and port container operations.

HIGHLY INTEGRATED ANTENNA FOR EASY INTEGRATION

HX-CSX260A integrates GNSS antenna and 4G, WiFi/BT into one compact enclosure, greatly simplifying RTK integration. Deep optimization has been carried out for the isolation between antennas of various systems, systematically addressing the electromagnetic compatibility issues that have long troubled RTK receivers.

STABLE PHASE CENTER FOR ROBUST POSITIONING PERFORMANCE

It features multi-point feeding capability, guaranteeing a reliable phase center for millimeter positioning accuracy.

TRACKING IN COMPLEX ENVIRONMENTS

This antenna exhibits superior high gain performance with ultralow signal loss, ensuring reliable satellite signal tracking. It also delivers wide beam width that covers wide frequencies with high marginal gain. These features guarantee robust signal availability even in low elevation, making the antenna a perfect option for complex environments with blockage, such as forests and buildings.

RELIABLE STRUCTURE FOR STABLE PERFORMANCE

This antenna uses air dielectric and low-loss microwave board materials. The overall weight is reduced, the structure is more robust, and the electrical performance becomes more stable and reliable.

STRONG ANTI-INTERFERENCE PERFORMANCE

The advanced LNA (Low Noise Amplifier) excels in improved signal filtering and out-of-band rejection, perfectly restraining unwanted electromagnetic interferences. With strong multi-path reduction capacity for strong anti-interference performance, consistent and reliable GNSS signals can be achieved even under complicated environments such as power grids, communication base stations and broadcast stations.

Key Features

- Supports GPS, GLONASS, Beidou, Galileo, QZSS
- Supports 4G, WiFi /BT
- Anti-electromagnetic interference, tracking in complex environments
- Powerful system compatibility, easy for machine integration

OEM GNSS Antenna HX-CSX260A

Specifications


PERFORMANCE	
Signal Received	GPS L1/L2/L5 BDS B1I/B2I/B3I/B1C/B2a/B2b GLONASS L1/L2/L3 GALILEO E1/E5a/E5b/E6 QZSS L1、L2、L5、L6 IRNSS L5 L-Band 4G、WIFI/BT
Nominal Impedance	50 Ω
Polarization	RHCP
Axial Ratio	$\leq 3\text{dB}$
Azimuth Coverage	360°
Azimuth Coverage	≤ 2.0
Peak Gain	GNSS: 5dBi WIFI: 0.5dBi 4G: 0.5dBi
Phase Center Deviation	$\pm 2\text{mm}$
LOW NOISE AMPLIFIER	

LNA Gain	30 $\pm$ 2dB
Noise Figure	$\leq 2\text{dB}$
VSWR	≤ 2.0
Passband Ripple	$\pm 2\text{dB}$
Passband Ripple	+3.3 ~ +12VDC
Operation Current	$\leq 45\text{mA}$
Group Delay Ripple	$\leq 5\text{ns}$
MECHANICAL	
Dimensions	$\Phi 111.0 \times H19.8\text{mm}$
Connector	GNSS: MMCX 4G & BT/WIFI: IPEX
ENVIRONMENTAL	
Operating Temperature	-40°C ~ +85°C
Storage Temperature	-55°C ~ +85°C
Humidity	95% non-condensing


OEM GNSS Antenna HX-CSX260A

GNSS Antenna Performance


Frequency (MHz)	1176	1206	1227	1268	1559	1561	1575	1606
Gain (dBi)	3.0	4.0	4.5	4.4	4.0	4.2	4.6	4.1




1176MHz



1227MHz




1268MHz




1559MHz


OEM GNSS Antenna HX-CSX260A



1561MHz



1575MHz




1606MHz


OEM GNSS Antenna HX-CSX260A

BT Antenna Performance

Frequency (MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Gain (dBi)	2.4	3.0	3.2	3.3	3.5	3.5	3.4	3.3	2.9	3.0	2.8



WIFI/BT Antenna VSWR




2450MHz


OEM GNSS Antenna HX-CSX260A

WIFI Antenna Performance


Frequency (MHz)	820	890	960	1710	1910	2110	2410	2450	2480	2690
Gain (dBi)	-3.1	0.0	-1.5	1.0	-5.7	0.9	-5.3	-5.5	-5.5	-8.9



4G Antenna VSWR




820MHz




960MHz


OEM GNSS Antenna HX-CSX260A




1710MHz



1910MHz




2110MHz




2410MHz


OEM GNSS Antenna HX-CSX260A



2450MHz




2480MHz



2690MHz

Harxon
a **BDStar** company

a **BDStar** company



Label size: 15*30mm, the content of the label is shown as below.

