



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 1 of 78

TEST REPORT

Application No.: SHCR2509002438HS
FCC ID: 2AT72-HAIRBRUSH
Applicant: VIS (Shanghai) Technology Limited
Address of Applicant: No.58, Linsheng Road, Tinglin Town, Jinshan District, Shanghai, China
Manufacturer: FOREO AB
Address of Manufacturer: KARLAVÄGEN 41, 114 31 STOCKHOLM, SWEDEN
Factory: VIS (Shanghai) Technology Limited
Address of Factory: No.58, Linsheng Road, Tinglin Town, Jinshan District, Shanghai, China
Equipment Under Test (EUT):
EUT Name: LED light hairbrush
Model No.: FLIP™ 2 play advanced LED light hairbrush, FLIP™ 2 play red light hairbrush, FLIP™ play advanced LED light hairbrush, FLIP™ play red light hairbrush
Remark: Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: FOREO
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-09-17
Date of Test: 2025-09-18 to 2025-10-11
Date of Issue: 2025-10-14

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Member of the SGS Group (SGS SA)



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 2 of 78

Revision Record			
Version	Description	Date	Remark
00	Original	2025-10-14	/

Authorized for issue by:				
Tested By		Bill Wu		
		Bill Wu/Project Engineer		
Approved By		Parlam Zhan		
		Parlam Zhan / Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Note: All models share similar construction and circuit diagram except from model number, appearance color, number of LED and LED color, FLIP™ 2 play advanced LED light hairbrush covers all functions. Only the model FLIP™ 2 play advanced LED light hairbrush was tested.

Model	Number of LED	LED Color	Appearance Color
FLIP™ 2 play advanced LED light hairbrush	12	Tricolor LED (Red, Green, Blue)	Purple
FLIP™ 2 play red light hairbrush	12	Red LED	Pink
FLIP™ play advanced LED light hairbrush	8	Tricolor LED (Red, Green, Blue)	Purple
FLIP™ play red light hairbrush	8	Red LED	Pink

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Power level setting using in test.....	6
4.4 Measurement Uncertainty	6
4.5 Test Location	7
4.6 Test Facility.....	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	9
6.1 Antenna Requirement	9
6.1.1 Test Requirement:	9
6.1.2 Conclusion	9
7 Radio Spectrum Matter Test Results.....	10
7.1 Radiated Emissions which fall in the restricted bands	10
7.1.1 E.U.T. Operation	10
7.1.2 Test Mode Description	10
7.1.3 Test Setup Diagram	11
7.1.4 Measurement Procedure and Data.....	11
7.2 Radiated Spurious Emissions Below 1GHz.....	20
7.2.1 E.U.T. Operation	20
7.2.2 Test Mode Description	20
7.2.3 Test Setup Diagram	20
7.2.4 Measurement Procedure and Data.....	21
7.3 Radiated Spurious Emissions Above 1GHz	24
7.3.1 E.U.T. Operation	24
7.3.2 Test Mode Description	24
7.3.3 Test Setup Diagram	24
7.3.4 Measurement Procedure and Data.....	25
7.4 Conducted Peak Output Power	50
7.4.1 E.U.T. Operation	50
7.4.2 Test Mode Description	50
7.4.3 Test Setup Diagram	50
7.4.4 Measurement Procedure and Data.....	50
7.5 Minimum 6dB Bandwidth.....	51
7.5.1 E.U.T. Operation	51
7.5.2 Test Mode Description	51
7.5.3 Test Setup Diagram	51
7.5.4 Measurement Procedure and Data.....	51
7.6 Power Spectrum Density	52
7.6.1 E.U.T. Operation	52
7.6.2 Test Mode Description	52



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 5 of 78

7.6.3 Test Setup Diagram52

7.6.4 Measurement Procedure and Data.....52

7.7 Conducted Band Edges Measurement53

7.7.1 E.U.T. Operation53

7.7.2 Test Mode Description53

7.7.3 Test Setup Diagram53

7.7.4 Measurement Procedure and Data.....53

7.8 Conducted Spurious Emissions54

7.8.1 E.U.T. Operation54

7.8.2 Test Mode Description54

7.8.3 Test Setup Diagram54

7.8.4 Measurement Procedure and Data.....54

8 Test Setup Photo55

9 EUT Constructional Details (EUT Photos).....55

10 Appendix.....55

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V 300mAh Rechargeable battery
Test Voltage:	DC 3.7V
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi (Provided by manufacturer)

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	LENOVO	L460	-
Serial port adapter plate	-	Test Plate 3	-

4.3 Power level setting using in test

Channel	Power setting
2402	-1.4
2440	-1.4
2480	-1.4

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty cycle	0.4%
4	Occupied Bandwidth	3%
5	RF conducted power	0.6dB
6	RF power density	2.9dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-6GHz)
		5.4dB (6GHz-18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab
588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.
Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Conducted Test					
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2024/12/18	2025/12/17
Spectrum Analyzer	Keysight	N9020B	SHEM241-1	2024/12/18	2025/12/17
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2025/04/30	2026/04/29
Signal Generator	R&S	SMR20	SHEM006-1	2025/07/30	2026/07/29
Signal Generator	Agilent	N5182A	SHEM182-1	2025/07/30	2026/07/29
Communication Tester	R&S	CMW270	SHEM183-1	2025/04/30	2026/04/29
Communication Tester	R&S	CMW500	SHEM268-1	2025/04/30	2026/04/29
Power Sensor	Keysight	U2021XA * 4	SHEM293-1	2025/07/30	2026/07/29
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2024/11/05	2026/11/04
AC Power Stabilizer	APC	KDF-31020T-V0-F0	SHEM216-1	2024/12/18	2025/12/17
DC Power Supply	HP	6010A	SHEM222-1	2024/12/18	2025/12/17
Conducted test Cable	/	RF01~RF04	/	2024/12/18	2025/12/17
Switcher	Tonscend	JS0806	SHEM293-1	2025/07/30	2026/07/29
Test software	Tonscend	JS Tonscend BT/WIFI System	Version: 2.6	/	/
Switcher+Power Sensor	TST	TSPS2023R	SHEM263-1	2025/07/30	2026/07/29
Test software	TST	TST PASS	Version: 2.0	/	/
RF Radiated Test					
EMI test Receiver	R&S	ESU40	SHEM051-1	2024/12/18	2025/12/17
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2024/12/18	2025/12/17
Communication Tester	R&S	CMW500	SHEM268-1	2025/04/30	2026/04/29
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2024/12/18	2025/12/17
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2025/08/31	2027/08/30
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM202-1	2025/04/12	2027/04/11
Horn Antenna (1-18GHz)	Schwarzbeck	HF906	SHEM009-1	2024/08/05	2026/08/04
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2025/08/31	2027/08/30
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2025/08/31	2027/08/30
Pre-Amplifier	HP	8447D	SHEM236-1	2024/12/18	2025/12/17
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2024/12/18	2025/12/17
Band Filter	LORCH	9BRX-875/X150	SHEM156-1	/	/
Band Filter	LORCH	13BRX-1950/X500	SHEM083-2	/	/
Band Filter	LORCH	5BRX-2400/X200	SHEM155-1	/	/
Band Filter	LORCH	5BRX-5500/X1000	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2023/05/06	2026/05/05
RE test Cable	/	PT18-NMMN-10M	SHEM217-2	2024/12/18	2025/12/17
Test software	ESE	E3	Version: 6.111221a	/	/

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 0 dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2361.371	45.37	28.66	3.30	35.16	42.17	74.00	-31.83	Peak
2390.000	44.38	28.80	3.33	35.18	41.33	74.00	-32.67	Peak
2402.250	76.16	28.85	3.34	35.19	73.16	74.00	-0.84	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2366.380	44.46	28.68	3.31	35.16	41.29	74.00	-32.71	Peak
2390.000	43.04	28.80	3.33	35.18	39.99	74.00	-34.01	Peak
2402.250	76.48	28.85	3.34	35.19	73.48	74.00	-0.52	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2479.659	77.02	29.08	3.40	35.25	74.25	74.00	0.25	Peak
2483.500	42.63	29.09	3.41	35.26	39.87	74.00	-34.13	Peak
2494.806	44.08	29.10	3.41	35.26	41.33	74.00	-32.67	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2480.251	76.05	29.08	3.40	35.25	73.28	74.00	-0.72	Peak
2483.500	43.37	29.09	3.41	35.26	40.61	74.00	-33.39	Peak
2502.415	44.42	29.12	3.42	35.27	41.69	74.00	-32.31	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2365.377	44.43	28.68	3.31	35.16	41.26	74.00	-32.74	Peak
2390.000	43.44	28.80	3.33	35.18	40.39	74.00	-33.61	Peak
2402.454	76.25	28.85	3.34	35.19	73.25	74.00	-0.75	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
2369.993	45.17	28.71	3.32	35.17	42.03	74.00	-31.97	Peak
2390.000	43.19	28.80	3.33	35.18	40.14	74.00	-33.86	Peak
2402.454	76.22	28.85	3.34	35.19	73.22	74.00	-0.78	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2480.474	76.84	29.08	3.40	35.25	74.07	74.00	0.07	Peak
2483.500	42.68	29.09	3.41	35.26	39.92	74.00	-34.08	Peak
2503.087	44.32	29.12	3.42	35.27	41.59	74.00	-32.41	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High



Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
2479.511	77.95	29.08	3.40	35.25	75.18	74.00	1.18	Peak
2483.500	43.38	29.09	3.41	35.26	40.62	74.00	-33.38	Peak
2500.548	44.73	29.12	3.42	35.27	42.00	74.00	-32.00	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test Mode: 00; Polarity: Horizontal



Antenna Polarity :HORIZONTAL


EUT/Project :2438HS

Test mode :00

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	127.665	44.50	11.50	1.16	27.04	30.12	43.50	-13.38	QP
2	167.824	41.09	12.30	1.33	26.89	27.83	43.50	-15.67	QP
3	216.024	43.47	9.24	1.56	26.63	27.64	46.00	-18.36	QP
4	263.819	40.69	11.36	1.75	26.50	27.30	46.00	-18.70	QP
5	329.039	36.12	13.28	1.98	26.73	24.65	46.00	-21.35	QP
6	501.179	36.02	16.80	2.51	27.90	27.43	46.00	-18.57	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Test Mode: 00; Polarity: Vertical



Antenna Polarity :VERTICAL
EUT/Project :2438HS
Test mode :00

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	65.114	32.17	11.20	0.78	27.20	16.95	40.00	-23.05	QP
2	167.824	33.04	12.30	1.33	26.89	19.78	43.50	-23.72	QP
3	331.355	34.09	13.30	1.98	26.75	22.62	46.00	-23.38	QP
4	420.580	35.90	15.22	2.26	27.47	25.91	46.00	-20.09	QP
5	526.397	30.95	17.10	2.54	27.95	22.64	46.00	-23.36	QP
6	766.057	27.07	22.00	3.09	27.93	24.23	46.00	-21.77	QP

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor




7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5149.197	41.54	33.78	5.48	36.88	43.92	74.00	-30.08	Peak
8663.404	36.68	37.17	8.31	38.24	43.92	74.00	-30.08	Peak
17286.170	34.25	42.05	13.44	40.32	49.42	74.00	-24.58	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5567.137	33.75	34.52	5.76	36.99	37.04	54.00	-16.96	Average
10244.580	30.92	37.85	9.01	37.49	40.29	54.00	-13.71	Average
15577.900	30.93	43.29	12.37	40.81	45.78	54.00	-8.22	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4831.962	40.42	33.63	5.25	36.79	42.51	74.00	-31.49	Peak
9178.972	36.28	37.24	8.55	38.83	43.24	74.00	-30.76	Peak
15265.880	34.58	43.33	12.18	41.83	48.26	74.00	-25.74	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5567.137	33.75	34.52	5.76	36.99	37.04	54.00	-16.96	Average
10885.670	30.64	38.28	9.26	36.84	41.34	54.00	-12.66	Average
15265.880	32.40	43.33	12.18	41.83	46.08	54.00	-7.92	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5164.102	39.53	33.82	5.49	36.89	41.95	74.00	-32.05	Peak
8713.630	35.48	37.22	8.33	38.19	42.84	74.00	-31.16	Peak
17793.090	32.45	42.90	13.75	40.64	48.46	74.00	-25.54	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5567.137	33.75	34.52	5.76	36.99	37.04	54.00	-16.96	Average
10244.580	30.92	37.85	9.01	37.49	40.29	54.00	-13.71	Average
15577.900	30.93	43.29	12.37	40.81	45.78	54.00	-8.22	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4279.589	40.99	32.49	4.64	36.54	41.58	74.00	-32.42	Peak
7390.070	36.88	36.36	7.49	37.37	43.36	74.00	-30.64	Peak
17487.180	34.23	42.21	13.57	41.05	48.96	74.00	-25.04	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4988.058	34.67	33.67	5.37	36.84	36.87	54.00	-17.13	Average
9781.603	30.94	37.56	8.82	37.49	39.83	54.00	-14.17	Average
15443.410	31.25	43.68	12.29	41.82	45.40	54.00	-8.60	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
3790.361	40.09	32.90	4.34	36.21	41.12	74.00	-32.88	Peak
8814.957	36.35	37.28	8.38	39.10	42.91	74.00	-31.09	Peak
15398.830	34.24	43.68	12.26	41.83	48.35	74.00	-25.65	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5535.047	34.49	34.52	5.74	36.99	37.76	54.00	-16.24	Average
10854.250	31.08	38.26	9.25	37.83	40.76	54.00	-13.24	Average
15221.820	32.03	43.17	12.16	41.84	45.52	54.00	-8.48	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4062.629	39.75	32.55	4.51	36.37	40.44	74.00	-33.56	Peak
7221.150	37.47	36.26	7.34	37.51	43.56	74.00	-30.44	Peak
15443.410	34.20	43.68	12.29	41.82	48.35	74.00	-25.65	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5090.007	34.72	33.67	5.44	36.87	36.96	54.00	-17.04	Average
8248.005	31.65	37.02	8.11	38.63	38.15	54.00	-15.85	Average
15896.290	31.30	42.45	12.56	40.80	45.51	54.00	-8.49	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4230.396	40.64	32.51	4.61	36.50	41.26	74.00	-32.74	Peak
7673.034	35.71	36.14	7.73	37.14	42.44	74.00	-31.56	Peak
14916.940	34.71	42.65	11.97	40.99	48.34	74.00	-25.66	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6267.553	33.28	35.51	6.45	36.68	38.56	54.00	-15.44	Average
11044.130	31.52	38.28	9.32	38.04	41.08	54.00	-12.92	Average
15398.830	31.51	43.68	12.26	41.83	45.62	54.00	-8.38	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4230.396	40.69	32.51	4.61	36.50	41.31	74.00	-32.69	Peak
6894.806	38.05	36.01	7.05	37.84	43.27	74.00	-30.73	Peak
15310.070	34.60	43.48	12.21	41.83	48.46	74.00	-25.54	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:Low




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
5090.007	34.68	33.67	5.44	36.87	36.92	54.00	-17.08	Average
8738.852	30.92	37.26	8.35	38.17	38.36	54.00	-15.64	Average
15265.880	32.39	43.33	12.18	41.83	46.07	54.00	-7.93	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4959.307	40.50	33.65	5.34	36.83	42.66	74.00	-31.34	Peak
9781.603	34.35	37.56	8.82	37.49	43.24	74.00	-30.76	Peak
15577.900	34.00	43.29	12.37	40.81	48.85	74.00	-25.15	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6249.464	32.26	35.50	6.43	36.70	37.49	54.00	-16.51	Average
11837.450	31.33	38.18	9.82	38.07	41.26	54.00	-12.74	Average
15398.830	31.28	43.68	12.26	41.83	45.39	54.00	-8.61	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
5194.041	40.49	33.91	5.51	36.89	43.02	74.00	-30.98	Peak
12290.700	35.61	38.66	10.17	38.64	45.80	74.00	-28.20	Peak
15134.080	34.89	43.11	12.10	41.84	48.26	74.00	-25.74	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:middle




Antenna Polarity :VERTICAL

EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6267.553	32.31	35.51	6.45	36.68	37.59	54.00	-16.41	Average
11467.000	31.12	38.28	9.52	37.68	41.24	54.00	-12.76	Average
15354.390	31.52	43.59	12.24	41.83	45.52	54.00	-8.48	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
4874.043	41.10	33.66	5.28	36.81	43.23	74.00	-30.77	Peak
10885.670	34.84	38.28	9.26	36.84	45.54	74.00	-28.46	Peak
15354.390	34.81	43.59	12.24	41.83	48.81	74.00	-25.19	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Horizontal; Modulation:GFSK; Channel:High




Antenna Polarity :HORIZONTAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
6231.427	32.76	35.49	6.41	36.73	37.93	54.00	-16.07	Average
10760.540	31.47	38.14	9.21	37.78	41.04	54.00	-12.96	Average
15668.210	30.55	43.09	12.42	40.81	45.25	54.00	-8.75	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High




Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
4888.151	41.87	33.66	5.29	36.81	44.01	74.00	-29.99	Peak
7829.860	37.11	36.32	7.86	38.01	43.28	74.00	-30.72	Peak
15398.830	34.26	43.68	12.26	41.83	48.37	74.00	-25.63	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamplifier Factor

Test Mode: 01; Polarity: Vertical; Modulation:GFSK; Channel:High



Antenna Polarity :VERTICAL
EUT/Project :2438HS

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
6249.464	32.71	35.50	6.43	36.70	37.94	54.00	-16.06	Average
10885.670	29.94	38.28	9.26	36.84	40.64	54.00	-13.36	Average
15310.070	31.68	43.48	12.21	41.83	45.54	54.00	-8.46	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

7.4 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.5 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2020) Section 11.8.1
Limit:	≥500 kHz


7.5.1 E.U.T. Operation

Operating Environment:					
Temperature:	22 °C	Humidity:	50 % RH	Atmospheric Pressure:	1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.6 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.2

Limit:
 ≤8dBm in any 3 kHz band during any time interval of continuous transmission


7.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C


Humidity: 50 % RH

Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SHCR2509002438HS

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for SHCR2509002438HS

10 Appendix

1. Bandwidth

1.1 Test Result

1.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.031	/	Pass
		2440	1	1.029	/	Pass
		2480	1	1.020	/	Pass
2M	SISO	2402	1	2.050	/	Pass
		2440	1	2.044	/	Pass
		2480	1	2.046	/	Pass


1.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.685	≥ 0.5	Pass
		2440	1	0.682	≥ 0.5	Pass
		2480	1	0.673	≥ 0.5	Pass
2M	SISO	2402	1	1.335	≥ 0.5	Pass
		2440	1	1.363	≥ 0.5	Pass
		2480	1	1.308	≥ 0.5	Pass

1.2 Test Graph


1.2.1 OBW









1.2.2 6dB BW









SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 62 of 78

2. Maximum Conducted Output Power

2.1 Test Result

2.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-1.83	<=30	Pass
		2440	-1.71	<=30	Pass
		2480	-1.89	<=30	Pass
2M	SISO	2402	-1.81	<=30	Pass
		2440	-1.68	<=30	Pass
		2480	-1.88	<=30	Pass

Note1: Antenna Gain: Ant1: 0.00dBi;



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.


SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 63 of 78

2.2 Test Graph

2.2.1 Power






SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 64 of 78






SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 65 of 78





SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 66 of 78

3. Maximum Power Spectral Density

3.1 Test Result

3.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
1M	SISO	2402	-12.87	<=8	Pass
		2440	-10.78	<=8	Pass
		2480	-12.05	<=8	Pass
2M	SISO	2402	-15.23	<=8	Pass
		2440	-15.72	<=8	Pass
		2480	-14.92	<=8	Pass

Note1: Antenna Gain: Ant1: 0.00dBi;



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.


SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 67 of 78

3.2 Test Graph

3.2.1 PSD






SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 68 of 78






SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 69 of 78



4. Unwanted Emissions In Non-restricted Frequency Bands

4.1 Test Result

4.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	-2.00
		2440	1	-1.81
		2480	1	-2.08
2M	SISO	2402	1	-3.18
		2440	1	-2.98
		2480	1	-3.46

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

4.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	-1.81	-21.81	Pass
		2440	1	-1.81	-21.81	Pass
		2480	1	-1.81	-21.81	Pass
2M	SISO	2402	1	-2.98	-22.98	Pass
		2440	1	-2.98	-22.98	Pass
		2480	1	-2.98	-22.98	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.


SHEM-TRF-001 Rev. 02 Sep01, 2023


Report No.: SHCR250900243801

Page: 71 of 78

4.2 Test Graph

4.2.1 Ref








SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.


SHEM-TRF-001 Rev. 02 Sep01, 2023


Report No.: SHCR250900243801


Page: 73 of 78




4.2.2 CSE












SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR250900243801

Page: 78 of 78



-- End of the Report -