





Test data

For 30-1000MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	54.16	27.76	-8.22	19.54	40.00	20.46	100	267	PK	H
2	127.11	27.70	-9.69	18.01	43.50	25.49	100	311	PK	H
3	169.21	29.17	-8.25	20.92	43.50	22.58	100	339	PK	H
4	289.99	28.59	-7.24	21.35	46.00	24.65	100	0	PK	H
5	407.17	30.60	-4.20	26.40	46.00	19.60	100	100	PK	H
6	479.54	29.65	-2.24	27.41	46.00	18.59	100	320	PK	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	49.69	27.69	-8.06	19.63	40.00	20.37	100	166	PK	V
2	108.58	29.12	-11.39	17.73	43.50	25.77	100	236	PK	V
3	157.76	28.77	-7.79	20.98	43.50	22.52	100	66	PK	V
4	244.29	30.18	-9.04	21.14	46.00	24.86	100	184	PK	V
5	338.49	28.48	-5.90	22.58	46.00	23.42	100	84	PK	V
6	434.34	31.07	-3.20	27.87	46.00	18.13	100	75	PK	V




For above 1GHz

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	44.66	-4.61	40.05	74.00	33.95	150	137	PK	H
2	7206.00	43.26	-1.76	41.50	74.00	32.50	150	185	PK	H
3	9608.00	41.27	0.88	42.15	74.00	31.85	150	185	PK	H
4	4804.00	36.54	-4.61	31.93	54.00	22.07	150	137	AV	H
5	7206.00	34.56	-1.76	32.80	54.00	21.20	150	3	AV	H
6	9608.00	33.30	0.88	34.18	54.00	19.82	150	360	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.00	44.63	-4.61	40.02	74.00	33.98	150	241	PK	V
2	7206.00	44.29	-1.76	42.53	74.00	31.47	150	267	PK	V
3	9608.00	41.34	0.88	42.22	74.00	31.78	150	218	PK	V
4	4804.00	36.83	-4.61	32.22	54.00	21.78	150	267	AV	V
5	7206.00	34.52	-1.76	32.76	54.00	21.24	150	267	AV	V
6	9608.00	33.41	0.88	34.29	54.00	19.71	150	338	AV	V



DH5 2441MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	47.37	-4.72	42.65	74.00	31.35	150	251	PK	H
2	7323.00	43.52	-1.49	42.03	74.00	31.97	150	202	PK	H
3	9764.00	42.28	1.64	43.92	74.00	30.08	150	23	PK	H
4	4882.00	38.00	-4.72	33.28	54.00	20.72	150	150	AV	H
5	7323.00	35.10	-1.49	33.61	54.00	20.39	150	74	AV	H
6	9764.00	33.80	1.64	35.44	54.00	18.56	150	228	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.00	45.88	-4.72	41.16	74.00	32.84	150	329	PK	V
2	7323.00	43.25	-1.49	41.76	74.00	32.24	150	48	PK	V
3	9764.00	41.22	1.64	42.86	74.00	31.14	150	24	PK	V
4	4882.00	40.35	-4.72	35.63	54.00	18.37	150	24	AV	V
5	7323.00	35.11	-1.49	33.62	54.00	20.38	150	350	AV	V
6	9764.00	33.37	1.64	35.01	54.00	18.99	150	178	AV	V



DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	46.14	-4.86	41.28	74.00	32.72	150	149	PK	H
2	7440.00	44.04	-1.34	42.70	74.00	31.30	150	72	PK	H
3	9920.00	42.43	2.27	44.70	74.00	29.30	150	301	PK	H
4	4960.00	38.97	-4.86	34.11	54.00	19.89	150	126	AV	H
5	7440.00	34.99	-1.34	33.65	54.00	20.35	150	326	AV	H
6	9920.00	36.07	2.27	38.34	54.00	15.66	150	326	AV	H



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.00	45.35	-4.86	40.49	74.00	33.51	150	21	PK	V
2	7440.00	43.26	-1.34	41.92	74.00	32.08	150	247	PK	V
3	9920.00	42.31	2.27	44.58	74.00	29.42	150	21	PK	V
4	4960.00	39.12	-4.86	34.26	54.00	19.74	150	21	AV	V
5	7440.00	34.66	-1.34	33.32	54.00	20.68	150	93	AV	V
6	9920.00	33.99	2.27	36.26	54.00	17.74	150	4	AV	V



Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:
$$\text{Result Level} = \text{Reading Level} + \text{Correct Factor}(\text{including Ant.Factor, Cable Factor etc.})$$
2. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
3. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be report.
4. All channels had been pre-test, DH5 is the worst case, only the worst case was reported.



3.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2020 Section 7.8.8 /6.3 / 6.6		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel - Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.
-----------------	---




Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT Transmitting mode. Through Pre-scan, find the DH5 of data type is the worst case of all modulation type. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass




Test Date

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2384.00	56.29	-0.82	55.47	74.00	18.53	150	357	PK	H
2	2390.01	53.58	-0.80	52.78	74.00	21.22	150	357	PK	H
3	2381.14	45.68	-0.83	44.85	54.00	9.15	150	73	AV	H
4	2390.01	45.17	-0.80	44.37	54.00	9.63	150	344	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2380.56	55.61	-0.83	54.78	74.00	19.22	150	357	PK	V
2	2390.01	54.10	-0.80	53.30	74.00	20.70	150	259	PK	V
3	2382.53	45.03	-0.83	44.20	54.00	9.80	150	234	AV	V
4	2390.01	44.29	-0.80	43.49	54.00	10.51	150	302	AV	V



DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2483.50	49.61	-0.29	49.32	74.00	24.68	150	346	PK	H
2	2485.50	51.54	-0.27	51.27	74.00	22.73	150	142	PK	H
3	2483.50	39.82	-0.29	39.53	54.00	14.47	150	102	AV	H
4	2486.41	40.68	-0.26	40.42	54.00	13.58	150	90	AV	H




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2483.50	49.93	-0.29	49.64	74.00	24.36	150	321	PK	V
2	2488.50	51.49	-0.25	51.24	74.00	22.76	150	156	PK	V
3	2483.50	39.94	-0.29	39.65	54.00	14.35	150	94	AV	V
4	2487.37	40.80	-0.26	40.54	54.00	13.46	150	114	AV	V

Note:

1. All channels had been pre-test, DH5 is the worst case, only the worst case was reported
2. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including Ant.Factor ,Cable Factor etc.)



3.11 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2020 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.		
Test Setup:			
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Charge + Transmitting mode.		
Final Test Mode:	Through Pre-scan, find the the worst case.		




Instruments Used:	Refer to section 2.9 for details
Test Results:	PASS

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:




Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.546	9.85	39.85	56.00	16.15	34.32	46.00	11.68	PASS
2	1.122	9.72	36.58	56.00	19.42	29.17	46.00	16.83	PASS
3	1.95	9.73	33.70	56.00	22.30	24.76	46.00	21.24	PASS
4	3.246	9.74	35.28	56.00	20.72	25.61	46.00	20.39	PASS
5	4.9245	9.79	34.42	56.00	21.58	23.61	46.00	22.39	PASS
6	7.107	9.87	35.05	60.00	24.95	23.34	50.00	26.66	PASS



Neutral Line:



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1815	9.84	41.19	64.42	23.23	27.09	54.42	27.33	PASS
2	0.312	9.88	37.64	59.92	22.28	22.25	49.92	27.67	PASS
3	0.546	9.74	41.20	56.00	14.80	32.52	46.00	13.48	PASS
4	0.969	9.70	35.64	56.00	20.36	20.79	46.00	25.21	PASS
5	2.0535	9.78	33.73	56.00	22.27	17.79	46.00	28.21	PASS
6	3.3315	9.90	37.04	56.00	18.96	20.25	46.00	25.75	PASS

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including LISN Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including LISN Factor, Cable Factor etc.)



4 Appendix

4.1 Appendix A: 20dB Emission Bandwidth

4.1.1 Test Result


TestMode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.951	2401.616	2402.567	---	---
		2441	0.951	2440.610	2441.561	---	---
		2480	0.951	2479.619	2480.570	---	---
2DH5	Ant1	2402	1.317	2401.418	2402.735	---	---
		2441	1.278	2440.451	2441.729	---	---
		2480	1.272	2479.463	2480.735	---	---
3DH5	Ant1	2402	1.359	2401.397	2402.756	---	---
		2441	1.314	2440.430	2441.744	---	---
		2480	1.314	2479.427	2480.741	---	---




4.1.2

Test Graphs


DH5_Ant1_2402




DH5_Ant1_2441



DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480





4.2 Appendix B: Maximum conducted output power


4.2.1 Test Result

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	2.42	≤20.97	PASS
		2441	4.20	≤20.97	PASS
		2480	3.77	≤20.97	PASS
2DH5	Ant1	2402	3.29	≤20.97	PASS
		2441	4.53	≤20.97	PASS
		2480	4.47	≤20.97	PASS
3DH5	Ant1	2402	3.72	≤20.97	PASS
		2441	4.51	≤20.97	PASS
		2480	4.82	≤20.97	PASS




4.2.2 Test Graphs


DH5_Ant1_2402




DH5_Ant1_2441




DH5_Ant1_2480




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480





4.3 Appendix C: Carrier frequency separation

4.3.1 Test Result

TestMode	Antenna	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.904	≥0.634	PASS
2DH5	Ant1	Hop	1.146	≥0.878	PASS
3DH5	Ant1	Hop	0.982	≥0.906	PASS