







11N20SISO_Ant1_5180




11N20SISO_Ant1_5200




11N20SISO_Ant1_5240




11N20SISO_Ant1_5260




11N20SISO_Ant1_5280




11N20SISO_Ant1_5320




11N20SISO_Ant1_5745




11N20SISO_Ant1_5785




11N20SISO_Ant1_5825




11N40SISO_Ant1_5190




11N40SISO_Ant1_5230




11N40SISO_Ant1_5270




11N40SISO_Ant1_5310




11N40SISO_Ant1_5755




11N40SISO_Ant1_5795




11AC20SISO Ant1 5180




11AC20SISO Ant1 5200




11AC20SISO Ant1 5240




11AC20SISO Ant1 5260




11AC20SISO Ant1 5280




11AC20SISO Ant1 5320




11AC20SISO Ant1 5745




11AC20SISO Ant1 5785




11AC20SISO Ant1 5825






11AC40SISO_Ant1_5190




11AC40SISO_Ant1_5230




11AC40SISO_Ant1_5270







11AC80SISO Ant1 5210



11AC80SISO Ant1 5290



11AC80SISO Ant1 5775



10. Frequency Stability Measurement

10.1. Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

10.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


10.3. Test procedures

(1) To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.

(2) The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.

(3) The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

10.4. Test setup



10.5. Test result

Test Engineer:	Wayne Huang	Test Site:	RF Measurement System 1#
Ambient Condition:	26.2℃,47.1%RH	Test Date:	2025.10.31-2025.12.06
Test Power Supply:	DC 12V	Sample Number:	S25092809-001

Voltage								
Test Mode	Antenna	Frequency[MHz]	Voltage [Vdc]	Temperature (℃)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5200	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5240	NV	NT	-20000.00	-3.816794	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	-20000.00	-3.816794	20	PASS
		5260	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	20000.00	3.802281	20	PASS
		5280	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5320	NV	NT	-20000.00	-3.759398	20	PASS
			LV	NT	-20000.00	-3.759398	20	PASS
			HV	NT	-20000.00	-3.759398	20	PASS
		5745	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5785	NV	NT	20000.00	3.457217	20	PASS
			LV	NT	20000.00	3.457217	20	PASS
			HV	NT	20000.00	3.457217	20	PASS
		5825	NV	NT	0.00	0.000000	20	PASS
			LV	NT	20000.00	3.433476	20	PASS
			HV	NT	0.00	0.000000	20	PASS
11N40SISO	Ant1	5190	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5230	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	-40000.00	-7.648184	20	PASS
		5270	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5310	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5510	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5550	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5670	NV	NT	0.00	0.000000	20	PASS
			LV	NT	-40000.00	-7.054674	20	PASS
			HV	NT	-40000.00	-7.054674	20	PASS
		5755	NV	NT	-40000.00	-6.950478	20	PASS
			LV	NT	-40000.00	-6.950478	20	PASS
			HV	NT	-40000.00	-6.950478	20	PASS
		5795	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS

11AC20SISO	Ant1	5785	HV	NT	0.00	0.000000	20	PASS
			NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
11AC80SISO	Ant1	5210	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5290	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5530	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5610	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5775	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS

Temperature								
Test Mode	Antenna	Frequency[MHz]	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5200	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5240	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	-20000.00	-3.816794	20	PASS
			NV	0	-20000.00	-3.816794	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	-20000.00	-3.816794	20	PASS
			NV	40	-20000.00	-3.816794	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5260	NV	-30	20000.00	3.802281	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5280	NV	-30	-20000.00	-3.787879	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS

			NV	10	0.00	0.000000	20	PASS
			NV	20	-20000.00	-3.787879	20	PASS
			NV	30	-20000.00	-3.787879	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5320	NV	-30	-20000.00	-3.759398	20	PASS
			NV	-20	-20000.00	-3.759398	20	PASS
			NV	-10	-20000.00	-3.759398	20	PASS
			NV	0	-20000.00	-3.759398	20	PASS
			NV	10	-20000.00	-3.759398	20	PASS
			NV	20	-20000.00	-3.759398	20	PASS
			NV	30	-20000.00	-3.759398	20	PASS
			NV	40	-20000.00	-3.759398	20	PASS
			NV	50	-20000.00	-3.759398	20	PASS
		5500	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
		5580	NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	20000.00	3.584229	20	PASS
			NV	-20	20000.00	3.584229	20	PASS
			NV	-10	20000.00	3.584229	20	PASS
			NV	0	20000.00	3.584229	20	PASS
			NV	10	20000.00	3.584229	20	PASS
			NV	20	20000.00	3.584229	20	PASS
		5700	NV	30	20000.00	3.584229	20	PASS
			NV	40	20000.00	3.584229	20	PASS
			NV	50	20000.00	3.584229	20	PASS
			NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
		5745	NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	20000.00	3.481288	20	PASS
			NV	0	20000.00	3.481288	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	20000.00	3.481288	20	PASS
		5785	NV	30	20000.00	3.481288	20	PASS
			NV	40	20000.00	3.481288	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	0.00	0.000000	20	PASS
			NV	-20	20000.00	3.457217	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	20000.00	3.457217	20	PASS
			NV	10	0.00	0.000000	20	PASS
		5825	NV	20	0.00	0.000000	20	PASS
			NV	30	20000.00	3.457217	20	PASS
			NV	40	20000.00	3.457217	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	20000.00	3.433476	20	PASS
			NV	-20	20000.00	3.433476	20	PASS
			NV	-10	20000.00	3.433476	20	PASS
			NV	0	20000.00	3.433476	20	PASS
			NV	10	20000.00	3.433476	20	PASS

			NV	20	40000.00	6.866953	20	PASS
			NV	30	20000.00	3.433476	20	PASS
			NV	40	20000.00	3.433476	20	PASS
			NV	50	20000.00	3.433476	20	PASS
11N40SISO	Ant1	5190	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5230	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5270	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5310	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5510	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5550	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5670	NV	-30	-40000.00	-7.054674	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	-40000.00	-7.054674	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	-40000.00	-7.054674	20	PASS

		5755	NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	-40000.00	-6.950478	20	PASS
			NV	-20	-40000.00	-6.950478	20	PASS
			NV	-10	-40000.00	-6.950478	20	PASS
			NV	0	-40000.00	-6.950478	20	PASS
			NV	10	-40000.00	-6.950478	20	PASS
			NV	20	-40000.00	-6.950478	20	PASS
			NV	30	-40000.00	-6.950478	20	PASS
			NV	40	-40000.00	-6.950478	20	PASS
			NV	50	-40000.00	-6.950478	20	PASS
		5795	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
11AC20SIS O	Ant1	5785	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
11AC80SIS O	Ant1	5210	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			5290	NV	-30	0.00	0.000000	20
		NV		-20	0.00	0.000000	20	PASS
		NV		-10	0.00	0.000000	20	PASS
		NV		0	0.00	0.000000	20	PASS
		NV		10	0.00	0.000000	20	PASS
		NV		20	0.00	0.000000	20	PASS
		NV		30	0.00	0.000000	20	PASS
		NV		40	0.00	0.000000	20	PASS
		NV		50	0.00	0.000000	20	PASS
		5530	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
		5610	NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS

		5775	NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS
			NV	-30	0.00	0.000000	20	PASS
			NV	-20	0.00	0.000000	20	PASS
			NV	-10	0.00	0.000000	20	PASS
			NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
			NV	50	0.00	0.000000	20	PASS

11. Dynamic Frequency Selection

11.1. Applicability of DFS requirements

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	☐ Master	☒ Client Without Radar Detection	☐ Client with Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

11.2. Limit

(1) DFS Detection Thresholds

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz	-62 dBm
EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.
 Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.
 Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

(2) DFS Response Requirements

Table 4: DFS Response Requirement Values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.
 Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required facilitating a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.
 Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

11.3. Parameters of radar test waveforms

This section provides the parameters for required test waveforms, minimum percentage of successful detections, and the minimum number of trials that must be used for determining DFS conformance. Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.

Table 5 Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
		Test B			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A					


A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. Test aggregate is average of the percentage of successful detections of short pulse radar types 1-4

11.4. Calibration of radar waveform

Radar Waveform Calibration Procedure:

- (1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- (2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 0\text{dBi} + 1\text{dB} = -61\text{dBm}$ that had been taken into account the output power range and antenna gain.
- (3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz. The spectrum analyzer had offset -1.0dB to compensate RF cable loss 1.0dB.
- (4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 0\text{dBi} + 1\text{dB} = -61\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.

Conducted Calibration Setup:





Note: 1. Use the software "Web" to set the frequency channel.
2. EUT is not support TPC and not with Radar detection.


Radar Waveform Calibration Result:

TestMode	Frequency[MHz]	Radar Type	Result	Limit[dbm]	Verdict
11A	5260	Type0	-55.13	-55.09	PASS
		Type1	-55.28	-55.09	PASS
		Type2	-55.42	-55.09	PASS
		Type3	-55.36	-55.09	PASS
		Type4	-55.33	-55.09	PASS
		Type5	-55.47	-55.09	PASS
		Type6	-55.15	-55.09	PASS

11.5. Test Graphs







11.6. Channel closing transmission time, channel move time and non-occupancy period


Block diagram of test setup Test Procedure:

- (1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- (2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- (3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- (4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Test Software in order to properly load the network for the entire period of the test.
- (5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- (6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- (7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the
- (8) spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.

Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

11.7. Test setup

Setup for Client with injection at the Master




11.8. Test result

Test Engineer:	Wayne Huang	Test Site:	RF Measurement System 1#
Ambient Condition:	26.2℃,47.1%RH	Test Date:	2025.10.31-2025.12.06
Test Power Supply:	DC 12V	Sample Number:	S25092809-001

TestMode	Frequency[MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11A	5260	200+13	200+60	935.7	10000	PASS

11.9. Test Graphs



12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

12.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


13. Radiated Emission

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

13.2. Block diagram of test setup





13.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	² 240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m

18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m
-----------------	-----------------------------	-----

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-12-22

Tested By:

Li Xiongbín

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 5G Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC BELOW 1G\11

Memo:

Sample Number:S25092809



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	228.718	38.11	12.02	4.99	22.72	46.00	23.28	QP	Horizontal
2	267.616	42.32	12.40	5.15	27.47	46.00	18.53	QP	Horizontal
3	318.890	37.15	14.11	5.36	24.20	46.00	21.80	QP	Horizontal
4	368.443	36.94	15.48	5.57	25.52	46.00	20.48	QP	Horizontal
5	429.595	35.71	15.76	5.81	24.75	46.00	21.25	QP	Horizontal
6	593.944	42.85	19.10	6.38	35.50	46.00	10.50	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-12-22

Tested By:

Li Xiongbín

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 5G Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC BELOW 1G\12

Memo:

Sample Number:S25092809



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.280	34.82	11.01	3.83	17.36	40.00	22.64	QP	Vertical
2	69.297	41.56	10.26	4.16	23.68	40.00	16.32	QP	Vertical
3	549.856	33.72	17.68	6.22	24.90	46.00	21.10	QP	Vertical
4	593.944	37.95	19.10	6.38	30.60	46.00	15.40	QP	Vertical
5	742.303	31.31	20.24	6.76	25.46	46.00	20.54	QP	Vertical
6	890.748	30.5	21.57	7.09	27.20	46.00	18.80	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\63

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4002.200	47.24	30.91	4.46	-39.70	42.91	74.00	31.09	PK	Horizontal
2	4915.100	45.74	33.10	4.92	-39.79	43.97	74.00	30.03	PK	Horizontal
3	7349.500	44.02	37.00	6.06	-39.87	47.21	74.00	26.79	PK	Horizontal
4	9474.500	42.98	38.54	7.12	-39.12	49.52	74.00	24.48	PK	Horizontal
5	11030.000	42.60	39.46	7.22	-39.60	49.68	74.00	24.32	PK	Horizontal
6	12160.500	42.00	39.32	7.71	-39.47	49.56	74.00	24.44	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\64

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4009.000	47.85	30.95	4.46	-39.70	43.56	74.00	30.44	PK	Vertical
2	4933.800	47.56	33.10	4.93	-39.79	45.80	74.00	28.20	PK	Vertical
3	7585.800	44.55	36.20	6.14	-39.84	47.05	74.00	26.95	PK	Vertical
4	9131.100	42.50	38.62	7.05	-38.74	49.43	74.00	24.57	PK	Vertical
5	10917.800	41.90	39.62	7.20	-39.61	49.11	74.00	24.89	PK	Vertical
6	12485.200	42.51	39.61	7.69	-39.21	50.60	74.00	23.40	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-03 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N20 5200MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\65
Memo: Sample Numbler:S25092809

**Suspected Data List**


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3884.900	46.06	30.72	4.43	-39.65	41.56	74.00	32.44	PK	Horizontal
2	5035.800	46.00	33.07	4.98	-39.79	44.26	74.00	29.74	PK	Horizontal
3	7573.900	45.01	36.20	6.13	-39.84	47.50	74.00	26.50	PK	Horizontal
4	9357.200	42.66	38.79	7.10	-38.99	49.56	74.00	24.44	PK	Horizontal
5	10764.800	42.16	39.18	7.20	-39.62	48.92	74.00	25.08	PK	Horizontal
6	11441.400	43.15	39.39	7.43	-39.60	50.37	74.00	23.63	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-03 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N20 5200MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\66
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3803.300	47.69	30.86	4.40	-39.62	43.33	74.00	30.67	PK	Vertical
2	5037.500	46.40	33.08	4.98	-39.79	44.67	74.00	29.33	PK	Vertical
3	7398.800	44.57	36.71	6.08	-39.86	47.50	74.00	26.50	PK	Vertical
4	9357.200	43.57	38.79	7.10	-38.99	50.47	74.00	23.53	PK	Vertical
5	10792.000	43.36	39.04	7.20	-39.62	49.98	74.00	24.02	PK	Vertical
6	12500.500	42.65	39.70	7.68	-39.20	50.83	74.00	23.17	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5240MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\67

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3886.600	48.48	30.74	4.43	-39.65	44.00	74.00	30.00	PK	Horizontal
2	4930.400	46.35	33.10	4.93	-39.79	44.59	74.00	29.41	PK	Horizontal
3	7626.600	43.92	36.63	6.15	-39.84	46.86	74.00	27.14	PK	Horizontal
4	9197.400	42.29	38.43	7.07	-38.82	48.97	74.00	25.03	PK	Horizontal
5	10644.100	42.58	39.33	7.21	-39.64	49.48	74.00	24.52	PK	Horizontal
6	12352.600	42.18	39.24	7.70	-39.32	49.80	74.00	24.20	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5240MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\68

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3878.100	46.81	30.64	4.42	-39.65	42.22	74.00	31.78	PK	Vertical
2	4933.800	45.44	33.10	4.93	-39.79	43.68	74.00	30.32	PK	Vertical
3	7347.800	44.05	37.00	6.06	-39.87	47.24	74.00	26.76	PK	Vertical
4	9353.800	42.38	38.79	7.10	-38.99	49.28	74.00	24.72	PK	Vertical
5	10848.100	42.61	39.29	7.20	-39.62	49.48	74.00	24.52	PK	Vertical
6	12291.400	41.88	39.38	7.70	-39.37	49.59	74.00	24.41	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5260MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\69

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3895.100	47.32	30.84	4.43	-39.66	42.93	74.00	31.07	PK	Horizontal
2	4908.300	46.04	33.10	4.91	-39.79	44.26	74.00	29.74	PK	Horizontal
3	7648.700	43.59	36.98	6.15	-39.84	46.88	74.00	27.12	PK	Horizontal
4	9132.800	42.84	38.66	7.06	-38.75	49.81	74.00	24.19	PK	Horizontal
5	10938.200	42.46	39.64	7.20	-39.61	49.69	74.00	24.31	PK	Horizontal
6	12345.800	42.44	39.26	7.70	-39.32	50.08	74.00	23.92	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5260MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\70

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3978.400	47.38	30.64	4.45	-39.69	42.78	74.00	31.22	PK	Vertical
2	5027.300	45.99	33.05	4.97	-39.79	44.22	74.00	29.78	PK	Vertical
3	7342.700	44.50	37.00	6.06	-39.87	47.69	74.00	26.31	PK	Vertical
4	9365.700	42.36	38.77	7.10	-39.00	49.23	74.00	24.77	PK	Vertical
5	11388.700	42.47	39.66	7.40	-39.60	49.93	74.00	24.07	PK	Vertical
6	12503.900	41.89	39.68	7.68	-39.20	50.05	74.00	23.95	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5280MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\71

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3891.700	46.43	30.80	4.43	-39.66	42.00	74.00	32.00	PK	Horizontal
2	5090.200	46.12	32.62	5.01	-39.78	43.97	74.00	30.03	PK	Horizontal
3	7461.700	44.57	36.67	6.10	-39.85	47.49	74.00	26.51	PK	Horizontal
4	9163.400	42.34	38.84	7.06	-38.78	49.46	74.00	24.54	PK	Horizontal
5	11048.700	41.77	39.31	7.23	-39.60	48.71	74.00	25.29	PK	Horizontal
6	12461.400	42.24	39.47	7.69	-39.23	50.17	74.00	23.83	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5280MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\72

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3900.200	46.99	30.90	4.43	-39.66	42.66	74.00	31.34	PK	Vertical
2	4998.400	46.38	33.00	4.96	-39.80	44.54	74.00	29.46	PK	Vertical
3	7453.200	44.09	36.62	6.10	-39.85	46.96	74.00	27.04	PK	Vertical
4	9024.000	42.28	38.69	7.03	-38.63	49.37	74.00	24.63	PK	Vertical
5	11033.400	42.09	39.43	7.22	-39.60	49.14	74.00	24.86	PK	Vertical
6	12492.000	41.86	39.65	7.69	-39.21	49.99	74.00	24.01	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\73

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4308.200	46.69	31.89	4.61	-39.73	43.46	74.00	30.54	PK	Horizontal
2	4930.400	45.87	33.10	4.93	-39.79	44.11	74.00	29.89	PK	Horizontal
3	7679.300	43.83	36.82	6.16	-39.83	46.98	74.00	27.02	PK	Horizontal
4	9132.800	42.99	38.66	7.06	-38.75	49.96	74.00	24.04	PK	Horizontal
5	11018.100	41.78	39.56	7.21	-39.60	48.95	74.00	25.05	PK	Horizontal
6	12369.600	42.57	39.19	7.69	-39.30	50.15	74.00	23.85	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\74

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3881.500	47.36	30.68	4.42	-39.65	42.81	74.00	31.19	PK	Vertical
2	4928.700	46.18	33.10	4.92	-39.79	44.41	74.00	29.59	PK	Vertical
3	7477.000	43.61	36.76	6.10	-39.85	46.62	74.00	27.38	PK	Vertical
4	9369.100	42.47	38.76	7.10	-39.01	49.32	74.00	24.68	PK	Vertical
5	10950.100	41.73	39.65	7.20	-39.60	48.98	74.00	25.02	PK	Vertical
6	12510.700	42.52	39.64	7.68	-39.19	50.65	74.00	23.35	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-05 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\1
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3796.500	47.09	30.82	4.40	-39.62	42.69	74.00	31.31	PK	Horizontal
2	5003.500	45.83	33.01	4.96	-39.80	44.00	74.00	30.00	PK	Horizontal
3	7313.800	43.72	37.00	6.05	-39.87	46.90	74.00	27.10	PK	Horizontal
4	9161.700	41.63	38.86	7.06	-38.78	48.77	74.00	25.23	PK	Horizontal
5	10858.300	42.19	39.35	7.20	-39.61	49.13	74.00	24.87	PK	Horizontal
6	12033.000	42.15	39.17	7.72	-39.57	49.47	74.00	24.53	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-05

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5745MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\2

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3890.000	47.00	30.78	4.43	-39.66	42.55	74.00	31.45	PK	Vertical
2	4961.000	45.41	33.08	4.94	-39.80	43.63	74.00	30.37	PK	Vertical
3	7630.000	44.03	36.68	6.15	-39.84	47.02	74.00	26.98	PK	Vertical
4	9156.600	41.63	38.92	7.06	-38.77	48.84	74.00	25.16	PK	Vertical
5	10693.400	41.55	39.48	7.21	-39.63	48.61	74.00	25.39	PK	Vertical
6	11982.000	42.91	38.91	7.71	-39.60	49.93	74.00	24.07	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-05

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5785MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\3

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4182.400	47.14	31.18	4.55	-39.72	43.15	74.00	30.85	PK	Horizontal
2	4908.300	45.72	33.10	4.91	-39.79	43.94	74.00	30.06	PK	Horizontal
3	7497.400	44.24	36.88	6.11	-39.85	47.38	74.00	26.62	PK	Horizontal
4	9141.300	41.95	38.83	7.06	-38.76	49.08	74.00	24.92	PK	Horizontal
5	10890.600	41.88	39.54	7.20	-39.61	49.01	74.00	24.99	PK	Horizontal
6	12237.000	41.90	39.27	7.70	-39.41	49.46	74.00	24.54	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-05

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5785MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\4

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4095.700	47.36	31.11	4.51	-39.71	43.27	74.00	30.73	PK	Vertical
2	4962.700	45.28	33.07	4.94	-39.80	43.49	74.00	30.51	PK	Vertical
3	7521.200	44.45	36.60	6.12	-39.85	47.32	74.00	26.68	PK	Vertical
4	9163.400	42.78	38.84	7.06	-38.78	49.90	74.00	24.10	PK	Vertical
5	10965.400	41.65	39.67	7.20	-39.60	48.92	74.00	25.08	PK	Vertical
6	12549.800	41.25	39.40	7.68	-39.16	49.17	74.00	24.83	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-05

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5825MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\5

Memo:

Sample Numbler:S25092809




Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3774.400	48.29	30.34	4.39	-39.61	43.41	74.00	30.59	PK	Horizontal
2	4998.400	46.41	33.00	4.96	-39.80	44.57	74.00	29.43	PK	Horizontal
3	7376.700	44.04	36.84	6.07	-39.86	47.09	74.00	26.91	PK	Horizontal
4	11154.100	42.78	38.85	7.28	-39.60	49.31	74.00	24.69	PK	Horizontal
5	12072.100	41.89	39.36	7.71	-39.54	49.42	74.00	24.58	PK	Horizontal
6	15448.300	40.43	38.50	8.28	-38.99	48.22	74.00	25.78	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-05 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5.8G\6
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3871.300	47.55	30.56	4.42	-39.65	42.88	74.00	31.12	PK	Vertical
2	4911.700	46.26	33.10	4.92	-39.79	44.49	74.00	29.51	PK	Vertical
3	7715.000	43.64	36.61	6.17	-39.83	46.59	74.00	27.41	PK	Vertical
4	9129.400	42.68	38.59	7.05	-38.74	49.58	74.00	24.42	PK	Vertical
5	10661.100	42.20	39.38	7.21	-39.63	49.16	74.00	24.84	PK	Vertical
6	12104.400	42.15	39.49	7.71	-39.52	49.83	74.00	24.17	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Band Edge Compliance

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

14.2. Block diagram of test setup



14.3. Limits

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

Same with Emissions in Restricted Frequency Bands except change investigated frequency range from 5.15-5.25 GHz, 5250-5350 GHz, 5470-5725 GHz, 5.725-5.85 GHz.
Remark: All restriction band have been tested, and only the worst case is shown in report.


14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-29 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11A 5180MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\15
Memo: Sample Numbel:S25092809



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5145.400	53.49	32.86	5.03	-29.77	61.61	74.00	12.39	PK	Horizontal
2	5150.000	51.32	32.90	5.04	-29.77	59.49	68.20	8.71	PK	Horizontal

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5145.562	38.70	32.86	5.03	46.82	54.00	7.18	AV	Horizontal
2	5150.116	41.67	32.90	5.04	49.84	54.00	4.16	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-29

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11A 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\16

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5141.920	45.53	32.84	5.03	-29.77	53.63	74.00	20.37	PK	Vertical
2	5150.000	42.49	32.90	5.04	-29.77	50.66	68.20	17.54	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5141.920	39.27	32.84	5.03	47.37	54.00	6.63	AV	Vertical	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-29 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11A 5320MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\17
Memo: Sample Numbler:S25092809



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.52	32.50	5.14	-29.73	50.43	68.20	17.77	PK	Horizontal
2	5351.810	47.13	32.51	5.14	-29.73	55.05	74.00	18.95	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5351.687	39.69	32.51	5.14	47.61	54.00	6.39	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-29 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11A 5320MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\18
Memo: Sample Numbler:S25092809



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.82	32.50	5.14	-29.73	50.73	68.20	17.47	PK	Vertical
2	5356.270	45.23	32.55	5.14	-29.73	53.19	74.00	20.81	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5356.270	39.16	32.55	5.14	47.12	54.00	6.88	AV	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-29

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\23

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.580	52.97	32.89	5.03	-29.77	61.12	74.00	12.88	PK	Horizontal
2	5150.000	51.17	32.90	5.04	-29.77	59.34	68.20	8.86	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5148.752	41.35	32.89	5.03	49.50	54.00	4.50	AV	Horizontal	
2	5150.166	41.94	32.90	5.04	50.11	54.00	3.89	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-29

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\24

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5147.410	44.75	32.88	5.03	-29.77	52.89	74.00	21.11	PK	Vertical
2	5150.000	41.50	32.90	5.04	-29.77	49.67	68.20	18.53	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5147.410	40.58	32.88	5.03	48.72	54.00	5.28	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-29

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N20 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\25

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.84	32.50	5.14	-29.73	50.75	68.20	17.45	PK	Horizontal
2	5351.920	48.20	32.52	5.14	-29.73	56.13	74.00	17.87	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5351.707	40.06	32.52	5.14	47.99	54.00	6.01	AV	Horizontal	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-29 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N20 5320MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\26
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	41.70	32.50	5.14	-29.73	49.61	68.20	18.59	PK	Vertical
2	5355.540	45.44	32.54	5.14	-29.73	53.39	74.00	20.61	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5355.540	40.18	32.54	5.14	48.13	54.00	5.87	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N40 5190MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\31

Memo:

Sample Numbel:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5146.560	53.87	32.87	5.03	-29.77	62.00	74.00	12.00	PK	Horizontal
2	5150.000	51.90	32.90	5.04	-29.77	60.07	68.20	8.13	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5146.694	40.49	32.87	5.03	48.62	54.00	5.38	AV	Horizontal	
2	5149.963	41.60	32.90	5.04	49.77	54.00	4.23	AV	Horizontal	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-31 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N40 5190MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\32
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5147.484	44.72	32.88	5.03	-29.77	52.86	74.00	21.14	PK	Vertical
2	5150.000	42.54	32.90	5.04	-29.77	50.71	68.20	17.49	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5147.484	38.26	32.88	5.03	46.40	54.00	7.60	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-31 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11N40 5310MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\33
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.83	32.50	5.14	-29.73	50.74	68.20	17.46	PK	Horizontal
2	5355.105	45.34	32.54	5.14	-29.73	53.29	74.00	20.71	PK	Horizontal

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5355.105	39.52	32.54	5.14	47.47	54.00	6.53	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11N40 5310MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\34

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	43.07	32.50	5.14	-29.73	50.98	68.20	17.22	PK	Vertical
2	5353.890	44.71	32.53	5.14	-29.73	52.65	74.00	21.35	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5353.890	39.07	32.53	5.14	47.01	54.00	6.99	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\39

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5145.810	55.51	32.87	5.03	-29.77	63.64	74.00	10.36	PK	Horizontal
2	5149.270	54.56	32.89	5.03	-29.77	62.71	74.00	11.29	PK	Horizontal
3	5150.000	48.71	32.90	5.04	-29.77	56.88	68.20	11.32	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5145.810	41.15	32.87	5.03	49.28	54.00	4.72	AV	Horizontal	
2	5149.442	41.52	32.89	5.03	49.67	54.00	4.33	AV	Horizontal	
3	5150.108	42.15	32.90	5.04	50.32	54.00	3.68	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC20 5180MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\40

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5142.790	45.46	32.84	5.03	-29.77	53.56	74.00	20.44	PK	Vertical
2	5150.000	42.76	32.90	5.04	-29.77	50.93	68.20	17.27	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5142.790	40.97	32.84	5.03	49.07	54.00	4.93	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC20 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\41

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	43.78	32.50	5.14	-29.73	51.69	68.20	16.51	PK	Horizontal
2	5351.510	47.19	32.51	5.14	-29.73	55.11	74.00	18.89	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5350.000	40.76	32.50	5.14	48.67	54.00	5.33	AV	Horizontal	
2	5351.510	40.64	32.51	5.14	48.56	54.00	5.44	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC20 5320MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\42

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.26	32.50	5.14	-29.73	50.17	68.20	18.03	PK	Vertical
2	5354.440	44.97	32.54	5.14	-29.73	52.92	74.00	21.08	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5354.440	40.35	32.54	5.14	48.30	54.00	5.70	AV	Vertical	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-03 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11AC40 5190MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\47
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.348	52.97	32.89	5.03	-29.77	61.12	74.00	12.88	PK	Horizontal
2	5150.000	49.60	32.90	5.04	-29.77	57.77	68.20	10.43	PK	Horizontal

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.598	42.15	32.89	5.03	50.30	54.00	3.70	AV	Horizontal
2	5150.124	42.62	32.90	5.04	50.79	54.00	3.21	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC40 5190MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\48

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5138.076	45.13	32.80	5.03	-29.77	53.19	74.00	20.81	PK	Vertical
2	5150.000	42.17	32.90	5.04	-29.77	50.34	68.20	17.86	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5138.076	41.32	32.80	5.03	49.38	54.00	4.62	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-03

Tested By:

Lin Guoyuan

EUT:

Monitor System

Model Number:

AV-151E-TW

Test Mode:

TX 11AC40 5310MHz Mode

Power Supply:

DC 12V

Condition:

Temp:23.9°C;Humi:54.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\49

Memo:

Sample Numbler:S25092809



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	43.12	32.50	5.14	-29.73	51.03	68.20	17.17	PK	Horizontal
2	5355.300	46.49	32.54	5.14	-29.73	54.44	74.00	19.56	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5349.797	39.86	32.50	5.14	47.77	54.00	6.23	AV	Horizontal	
2	5349.927	39.96	32.50	5.14	47.87	54.00	6.13	AV	Horizontal	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-11-03 **Tested By:** Lin Guoyuan
EUT: Monitor System **Model Number:** AV-151E-TW
Test Mode: TX 11AC40 5310MHz Mode **Power Supply:** DC 12V
Condition: Temp:23.9°C;Humi:54.9% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25092809-1E\FCC ABOVE 1G 5G\50
Memo: Sample Numbler:S25092809

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	42.91	32.50	5.14	-29.73	50.82	68.20	17.38	PK	Vertical
2	5381.040	45.45	32.75	5.15	-29.72	53.63	74.00	20.37	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5381.040	39.67	32.75	5.15	47.85	54.00	6.15	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.