

DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

TEST REPORT

SCOPE OF WORK

FCC TESTING—ECH-REFL03-SPT, ECH-REFL03, ECH-REFL02-5G

REPORT NUMBER

210623023SZN-001

ISSUE DATE

07 February 2022

[REVISED DATE]

[-----]

PAGES

52

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTDApplication
For
Certification**FCC ID: 2ATAP-ECHELONFIT****REFLECT MIRROR, REFLECT TOUCH SPORT****Model: ECH-REFL03-SPT, ECH-REFL03, ECH-REFL02-5G**

2.4GHz Wi-Fi Transceiver

Report No.: 210623023SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-20]

Prepared and Checked by:**Approved by:****Ryan Chen**
Project Engineer

Peter Kang
Senior Technical Supervisor
Date: 07 February 2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change _____

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No ☒

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-20] Edition] provision.

Report prepared by:

Ryan Chen
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community,
GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.
Tel: (86 755) 8614 0682 Fax: (86 755) 8601 6751

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	6
3.0	<u>System Test Configuration</u>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	7
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<u>Measurement Results</u>	9
4.1	Maximum Conducted Output Power at Antenna Terminals	9
4.2	Minimum 6 dB RF Bandwidth	10
4.3	Maximum Power Density Reading	14
4.4	Out of Band Conducted Emissions	18
4.5	Out of Band Radiated Emissions	31
4.6	Transmitter Radiated Emissions in Restricted Bands	32
4.7	Field Strength Calculation	33
4.8	Radiated Spurious Emission	34
4.9	Conducted Emission at Mains Terminals	46
4.10	Radiated Emissions from Digital Section of Transceiver	49
4.11	Transmitter Duty Cycle Calculation and Measurements	50
5.0	<u>Equipment Photographs</u>	51
6.0	<u>Product Labelling</u>	51
7.0	<u>Technical Specifications</u>	51
8.0	<u>Instruction Manual</u>	51
9.0	<u>Confidentiality Request</u>	51
10.0	<u>Discussion of Pulse Desensitization</u>	51
11.0	<u>Test Equipment List</u>	52

TEST REPORT

Intertek Report: 210623023SZN-001

1.0 Summary of Test results

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Applicant Address: Room 201, Building 3rd, No. 43 of Gangjian RD. Changping town, Dongguan City, Guangdong Province, China

Manufacturer: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Manufacturer Address: Room 201, Building 3rd, No. 43 of Gangjian RD. Changping town, Dongguan City, Guangdong Province, China

Model: ECH-REFL03-SPT, ECH-REFL03, ECH-REFL02-5G

FCC ID: 2ATAP-ECHELONFIT

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

TEST REPORT

Intertek Report: 210623023SZN-001

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is an Echelon Reflect with BT5.0 (dual-mode) operating in 2402-2480MHz, 2.4G Wi-Fi function operating in 2412-2462MHz and 5G Wi-Fi function operating in 5150-5250&5725-5850MHz. The EUT is powered by A.C. 100-240V, 50/60Hz. User cannot access USB/SD card ports in normal use. For more detailed features description, please refer to the user's manual.

Type of Modulation: CCK, BPSK, QPSK, 16QAM, 64QAM, DQPSK, DBPSK

Antenna Type: Internal Antenna

Antenna Gain: 3dBi

The Model: ECH-REFL03, ECH-REFL02-5G are the same as the Model: ECH-REFL03-SPT in hardware aspect. Their difference in product name, model number and with/without support touch screen function for marketing purpose. Details as below:

Product name	Model Number	Description
REFLECT MIRROR	ECH-REFL03	Not support touch screen function
REFLECT TOUCH SPORT	ECH-REFL03-SPT	Support touch screen function
REFLECT MIRROR	ECH-REFL02-5G	Not support touch screen function

Both design (not support touch screen function and support touch screen function) were tested, but only the worst-case testing data were recorded in this report.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz Wi-Fi transmitter portion).

Remaining functions are subjected to the following documents:

For the 5G Wi-Fi function was tested and demonstrated in report 210623023SZN-002.

For the BT 5.0 EDR function was tested and demonstrated in report 210623023SZN-003.

For the BT 5.0 BLE function was tested and demonstrated in report 210623023SZN-004.

For other functions were reported in the SDOC report: 210526036SZN-001.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

TEST REPORT

Intertek Report: 210623023SZN-001

3.0 System Test Configuration**3.1 Justification**

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by A.C. 100-240V, 50/60Hz during the test. Both designing schemes have been considered, only the worst data was reported in this report.

On 802.11b/g/n-HT20 mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The EUT and transmitting antennas were centered on the turntable.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

Test Software: Ampak RFTTestTool, VER: 5.6

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

3.3 Special Accessories

N/A.

TEST REPORT

Intertek Report: 210623023SZN-001

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Portable computer (Provided by Intertek)	DELL	Latitude 3480

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

4.1.1 Test Result

IEEE 802.11b (Antenna Gain = 3dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	17.5	56.23
Middle Channel: 2437	17.7	58.88
High Channel: 2462	17.2	52.48

IEEE 802.11g (Antenna Gain = 3dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	19.7	93.33
Middle Channel: 2437	19.6	91.20
High Channel: 2462	19.3	85.11

IEEE 802.11n-HT20 (Antenna Gain = 3dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	19.3	85.11
Middle Channel: 2437	19.3	85.11
High Channel: 2462	19.8	95.50

Cable loss: 2.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 19.8dBm

EUT max. E.I.R.P = 19.8dBm + 3dBi = 22.8dBm = 190.55mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

4.2.1 Test Result

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	8.070
2437	7.620
2462	7.620


IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	15.150
2437	15.450
2462	13.920

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	15.210
2437	15.750
2462	15.210


The test plots are attached as below.

TEST REPORT


Intertek Report: 210623023SZN-001



11G_2412




11G_2437




11G_2462

TEST REPORT


Intertek Report: 210623023SZN-001



11N20 2412




11N20 2437




11N20 2462

TEST REPORT


Intertek Report: 210623023SZN-001



11B 2412



11B 2437



11B 2462

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/100 kHz.

4.3.1 Test Result

IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-4.81
2437	-4.20
2462	-4.66


IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-6.92
2437	-6.13
2462	-5.21

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 100KHz
2412	-6.46
2437	-5.52
2462	-4.08


The test plots are attached as below.

TEST REPORT


Intertek Report: 210623023SZN-001



11G_2412




11G_2437




11G_2462

TEST REPORT


Intertek Report: 210623023SZN-001



11N20 2412




11N20 2437




11N20 2462

TEST REPORT


Intertek Report: 210623023SZN-001



11B 2412



11B 2437



11B 2462

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.


TEST REPORT

Intertek Report: 210623023SZN-001


4.4.1 Test Result

802.11b


Channel 01 (2412MHz) Reference Level: 7.66dBm



11B 2412 0~Reference




11B 2412 1~2400



TEST REPORT


Intertek Report: 210623023SZN-001



TEST REPORT

Intertek Report: 210623023SZN-001


Channel 06 (2437MHz) Reference Level: 7.89dBm




Channel 11 (2462MHz) Reference Level: 8.66dBm

TEST REPORT


Intertek Report: 210623023SZN-001



11B_2462_0~Reference




11B_2462_1~2400



11B_2462_2483.5~25000



TEST REPORT

Intertek Report: 210623023SZN-001




802.11g

Channel 01 (2412MHz) Reference Level: 4.03dBm




TEST REPORT


Intertek Report: 210623023SZN-001




Channel 06 (2437MHz) Reference Level: 4.77dBm



11G_2437_0-Reference



11G_2437_1~2400




11G_2437_2483.5~25000


Channel 11 (2462MHz) Reference Level: 5.70dBm

TEST REPORT


Intertek Report: 210623023SZN-001



11G_2462_0-Reference




11G_2462_1-2400



11G_2462_2483.5-25000



TEST REPORT

Intertek Report: 210623023SZN-001




802.11n-HT20

Channel 01 (2412MHz) Reference Level: 4.97dBm




TEST REPORT

Intertek Report: 210623023SZN-001




11N20 2412 2483.5~25000



11N20 2412 Band Edge


Channel 06 (2437MHz) Reference Level: 5.53dBm




11N20 2437_0~Reference

TEST REPORT


Intertek Report: 210623023SZN-001



11N20_2437_1~2400




Channel 11 (2462MHz) Reference Level: 6.37dBm




11N20_2462_0~Reference

TEST REPORT


Intertek Report: 210623023SZN-001



11N20_2462_1~2400



11N20_2462_2483.5~25000



11N20_2462_Band Edge

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier),
FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental.

☐ See attached data sheet.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at 50.370000MHz
is passed by 5.7dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf. Simultaneous transmission was considered during the test.

TEST PERSONNEL:

Sign on file

Ryan Chen, Project Engineer
Typed/Printed Name

23 October 2021
Date

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD


Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode: Simultaneous transmission

ANT Polarity: Horizontal

FCC Part 15



Limit and Margin

Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
148.825000	35.5	1000.0	120.000	H	10.5	8.0	43.5
197.810000	30.3	1000.0	120.000	H	12.3	13.2	43.5
300.145000	33.5	1000.0	120.000	H	16.2	12.5	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Limit Line(dBμV/m) – Level (dBμV/m)

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD


Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode: Simultaneous transmission

ANT Polarity: Vertical

FCC Part 15



Limit and Margin

Frequency (MHz)	Quasi Peak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
50.370000	34.3	1000.0	120.000	V	7.9	5.7	40.0
54.250000	33.9	1000.0	120.000	V	7.9	6.1	40.0
298.205000	35.7	1000.0	120.000	V	16.2	10.3	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode:

Transmitting (802.11b-Channel 01)

Radiated Emissions

(802.11b-Channel 01)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	61.6	36.8	33.5	58.3	74.0	-15.7
Horizontal	*2390.000	67.2	36.4	29.1	59.9	74.0	-14.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	46.8	36.8	33.5	43.5	54.0	-10.5
Horizontal	*2390.000	51.4	36.4	29.1	44.1	54.0	-9.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode:

Transmitting (802.11b-Channel 06)

Radiated Emissions

(802.11b-Channel 06)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	59.2	36.7	33.4	55.9	74.0	-18.1
Horizontal	*7311.000	59.2	36.6	35.8	58.4	74.0	-15.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	45.5	36.7	33.4	42.2	54.0	-11.8
Horizontal	*7311.000	46.0	36.6	35.8	45.2	54.0	-8.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode:

Transmitting (802.11b-Channel 11)

Radiated Emissions

(802.11b-Channel 11)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	57.6	36.8	33.3	54.1	74.0	-19.9
Horizontal	*2484.50	63.4	36.5	29.3	56.2	74.0	-17.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	45.0	36.8	33.3	41.5	54.0	-12.5
Horizontal	*2484.500	53.3	36.5	29.3	46.1	54.0	-7.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

Worst Case Operating Mode:

Transmitting (802.11g-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	65.9	36.8	33.5	62.6	74.0	-11.4
Horizontal	*2390.000	66.4	36.4	29.1	59.1	74.0	-14.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	45.6	36.8	33.5	42.3	54.0	-11.7
Horizontal	*2390.000	48.7	36.4	29.1	41.4	54.0	-12.6

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

Worst Case Operating Mode:

Transmitting (802.11g-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	65.1	36.7	33.4	61.8	74.0	-12.2
Horizontal	*7311.000	59.9	36.6	35.8	59.1	74.0	-14.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	45.6	36.7	33.4	42.3	54.0	-11.7
Horizontal	*7311.000	42.7	36.6	35.8	41.9	54.0	-12.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

Worst Case Operating Mode:

Transmitting (802.11g-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	65.3	36.8	33.3	61.8	74.0	-12.2
Horizontal	*7386.000	69.8	36.5	29.3	62.6	74.0	-11.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	45.7	36.8	33.3	42.2	54.0	-11.8
Horizontal	*7386.000	50.3	36.5	29.3	43.1	54.0	-10.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	66.4	36.8	33.5	63.1	74.0	-10.9
Horizontal	*2390.000	64.1	36.4	29.1	56.8	74.0	-17.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	45.8	36.8	33.5	42.5	54.0	-11.5
Horizontal	*2390.000	46.4	36.4	29.1	39.1	54.0	-14.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	66.0	36.7	33.4	62.7	74.0	-11.3
Horizontal	*7311.000	56.7	36.6	35.8	55.9	74.0	-18.1

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	45.2	36.7	33.4	41.9	54.0	-12.1
Horizontal	*7311.000	37.7	36.6	35.8	36.9	54.0	-17.1

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFLO3-SPT

Worst Case Operating Mode:

Transmitting (802.11n20-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	64.0	36.8	33.3	60.5	74.0	-13.5
Horizontal	*7386.000	64.0	36.5	29.3	56.8	74.0	-17.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	44.4	36.8	33.3	40.9	54.0	-13.1
Horizontal	*7386.000	44.8	36.5	29.3	37.6	54.0	-16.4

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.9 Conducted Emission

Worst Case Conducted Emission (WIFI Link)
at 0.886000MHz
is passed by 5.7dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

TEST PERSONNEL:

Sign on file

Ryan Chen, Project Engineer
Typed/Printed Name

23 October 2021
Date


TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD
Date of Test: 23 October 2021 Model: ECH-REFL03-SPT
Worst Case Operating Mode: Simultaneous transmission
Phase: Live

Graphic / Data Table

**Conducted Emissions
Pursuant to FCC 15.207: Emissions Requirement**



Result Table QP

Frequency (MHz)	Quasi Peak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.181500	49.7	L1	9.6	14.7	64.4
0.242000	49.4	L1	9.6	12.6	62.0
0.306000	42.8	L1	9.6	17.3	60.1
0.438000	44.1	L1	9.6	13.0	57.1
0.606000	46.0	L1	9.6	10.0	56.0
0.710000	46.4	L1	9.6	9.6	56.0

Result Table AV

Frequency (MHz)	Average (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.181500	41.3	L1	9.6	13.1	54.4
0.242000	40.7	L1	9.6	11.4	52.0
0.306000	35.9	L1	9.6	14.2	50.1
0.438000	30.3	L1	9.6	16.8	47.1
0.606000	33.8	L1	9.6	12.2	46.0
0.710000	35.1	L1	9.6	10.9	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBuV) – Level (dBuV)

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021


Model: ECH-REFL03-SPT

Worst Case Operating Mode: Simultaneous transmission

Phase: Neutral

Graphic / Data Table

**Conducted Emissions
Pursuant to FCC 15.207: Emissions Requirement**



Result Table QP

Frequency (MHz)	QuasiPeak (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.177000	50.1	N	9.5	14.5	64.6
0.242000	45.7	N	9.5	16.3	62.0
0.306000	42.9	N	9.5	17.2	60.1
0.646000	45.4	N	9.5	10.6	56.0
0.722000	45.8	N	9.5	10.2	56.0
0.886000	50.3	N	9.5	5.7	56.0

Result Table AV

Frequency (MHz)	Average (dBμV)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.177000	39.5	N	9.5	15.1	54.6
0.242000	35.5	N	9.5	16.5	52.0
0.306000	36.2	N	9.5	13.9	50.1
0.646000	34.5	N	9.5	11.5	46.0
0.722000	33.9	N	9.5	12.1	46.0
0.886000	34.2	N	9.5	11.8	46.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Limit (dBuV) – Level (dBuV)

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

TEST REPORT

Intertek Report: 210623023SZN-001

Applicant: DONGGUAN TYSTART GLASS TECHNOLOGY CO., LTD

Date of Test: 23 October 2021

Model: ECH-REFL03-SPT

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

TEST REPORT

Intertek Report: 210623023SZN-001

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-13	Biconilog Antenna	ETS	3142E	00217919	2019-06-10	2022-06-10
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2021-05-18	2023-05-18
SZ061-08	Horn Antenna	ETS	3115	00092346	2021-09-07	2022-09-07
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	2019-08-13	2022-08-13
SZ056-03	Spectrum Analyzer	R&S	FSP30	101148	2021-05-10	2022-05-10
SZ185-01	EMI Receiver	R & S	ESCI	100547	2020-12-22	2021-12-22
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	2021-05-10	2022-05-10
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2018-12-15	2021-12-15
SZ062-02	RF Cable	RADIALL	RG 213U	--	2021-06-01	2021-12-01
SZ062-05	RF Cable	RADIALL	0.04-26.5GHz	--	2021-06-01	2021-12-01
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	2021-06-01	2021-12-01
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	2021-05-11	2022-05-11
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2021-10-15	2022-10-15
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2021-05-11	2022-05-11
SZ188-03	Shielding Room	ETS	RFD-100	4100	2018-12-15	2021-12-15
SZ062-16	RF Cable	HUBER+SUHNER	CBL2-BN-1m	110127-2231000	2021-10-15	2022-10-15
SZ016-12	Programmable Temperature & Humidity Chamber	Taili	MHK-120NK	AB0105	2021-01-12	2022-01-12
SZ006-30	DC Power Supply	Guwei	SPS-3610	GEQ920551	2021-01-05	2022-01-05

***** End of Report *****