

TEST REPORT

Application No.: KSCR2603000501AT
FCC ID: 2ATCK-TMSS6F2
Applicant: Baolong Huf Shanghai Electronics Co., Ltd.
Address of Applicant: No. Building 3, Lane 1099, Zhangjing Road, Dongjing Town, Songjiang District, Shanghai City, P.R. China
Manufacturer: Baolong Huf Shanghai Electronics Co., Ltd.
Address of Manufacturer: No. Building 3, Lane 1099, Zhangjing Road, Dongjing Town, Songjiang District, Shanghai City, P.R. China
Factory: Baolong Huf Shanghai Electronics Co., Ltd.
Address of Factory: No. Building 3, Lane 1099, Zhangjing Road, Dongjing Town, Songjiang District, Shanghai City, P.R. China
Equipment Under Test (EUT):
EUT Name: TPMS SENSOR
Model No.: TMSS6F2
Trade Mark: BH SENS
Standard(s) : 47 CFR Part 15, Subpart C 15.231
Date of Receipt: 2026-03-11
Date of Test: 2026-03-26 to 2026-03-27
Date of Issue: 2026-03-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2026-03-27	/

Authorized for issue by:			
Tested By		Btuce . Li	
		Bruce-WP_Li/Project Engineer	
Approved By		Terry Hou	
		Terry Hou /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.231	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
20dB Bandwidth	47 CFR Part 15, Subpart C 15.231	ANSI C63.10 (2020) Section 6.9.2	47 CFR Part 15, Subpart C 15.231(c)	Pass
Field Strength of the Fundamental Signal (15.231(e))		ANSI C63.10 (2020) Section 7.4	Field Strength of the Fundamental Signal (15.231(e))	Pass
Radiated Emissions below 1GHz		ANSI C63.10 (2020) Section 6.4&6.5	47 CFR Part 15C Section 15.231(e) and 15.209	Pass
Dwell Time (15.231(e))		ANSI C63.10 (2020) Section 7.4	47 CFR Part 15, Subpart C 15.231(e)	Pass
Radiated Emissions above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15C Section 15.231(e) and 15.209	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units.....	5
4.3 Power level setting using in test.....	5
4.4 Measurement Uncertainty	5
4.5 Test Location	7
4.6 Test Facility.....	7
4.7 Deviation from Standards	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	9
6.1 Antenna Requirement	9
7 Radio Spectrum Matter Test Results	10
7.1 20dB Bandwidth	10
7.2 Field Strength of the Fundamental Signal (15.231(e))	11
7.3 Radiated Emissions below 1GHz.....	13
7.4 Dwell Time (15.231(e)).....	15
7.5 Radiated Emissions above 1GHz	16
8 Test Setup Photo	19
9 EUT Constructional Details (EUT Photos).....	19
10 Appendix.....	20
10.1 Field Strength of the Fundamental Signal	20
10.2 Spurious Emissions.....	22
10.3 20dB Bandwidth	27
10.4 Dwell Time	29

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.0V by Battery Battery model:CR2032HT Output: DC 3.0V
Operation Frequency	433.92MHz 315MHz
Channel Numbers:	1
Modulation Type:	FSK
Antenna Type:	Monopole antenna
Antenna Gain:	-25dBi
Operation Type:	Periodic transmitter
Hardware Version	V3.0
Firmware Version	V1.0
Software Version	V1.0
Serial No	8B09D4B4

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
TPMS Smart Tool	GEELY	Smar Tool	/

4.3 Power level setting using in test

Frequency (MHz)	Power level setting
433.92	default
315	default

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz) 5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz) 4.5dB (30MHz-1GHz) 5.1dB (1GHz-18GHz) 5.4dB (Above 18GHz)



Report No.: KSCR260300050101

Page: 6 of 30

10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%
Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1172)**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

- **VCCI (Member No:1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESCI	KS301196	07/09/2025	07/08/2026
2	LISN	R&S	ENV216	KS301197	01/08/2026	01/07/2027
3	LISN	Schwarzbeck	NNLK 8129	KS301091	01/08/2026	01/07/2027
4	Pulse Limiter	R&S	ESH3-Z2	KUS1902E001	12/18/2025	12/17/2026
5	CE test Cable	Thermax	/	CZ301102	12/18/2025	12/17/2026
6	Software	Faratronic	E3	/	N.C.R	N.C.R
RF Conducted Test						
1	Spectrum Analyzer	Keysight	N9020A	KUS1911E004-2	07/09/2025	07/08/2026
2	Spectrum Analyzer	Keysight	N9020A	KUS2001M001-2	07/09/2025	07/08/2026
3	Spectrum Analyzer	Keysight	N9030B	KSEM021-1	12/17/2025	12/16/2026
4	Signal Generator	R&S	SMBV100B	KSEM032	12/17/2025	12/16/2026
5	Signal Generator	R&S	SMW200A	KSEM020-1	07/09/2025	07/08/2026
6	Signal Generator	Agilent	N5182A	KUS2001M001-1	07/08/2025	07/07/2026
7	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
8	Radio Communication Test Station	Anritsu	MT8000A	KSEM001-1	07/09/2025	07/08/2026
9	Radio Communication Analyzer	Anritsu	MT8821C	KSEM002-1	12/17/2025	12/16/2026
10	Universal Radio Communication Tester	R&S	CMW500	KUS1911E004-1	07/08/2025	07/07/2026
11	Switcher	TST	FY562	KUS2001M001-4	12/17/2025	12/16/2026
12	Conducted Test Cable	Thermax	RF01-RF04	CZ301111- CZ301120	12/17/2025	12/16/2026
13	Temp. / Humidity Chamber	TERCHY	MHK-120AK	KS301190	07/15/2025	07/14/2026
14	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-5	12/30/2025	12/29/2026
15	Software	BST	TST-PASS	/	NCR	NCR
RF Radiated Test						
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	07/09/2025	07/08/2026
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	12/17/2025	12/16/2026
3	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
4	Loop Antenna (9KHz-30MHz)	COM-POWER	AL-130R	KUS1806E001	07/11/2025	07/10/2026
5	Bilog Antenna (30MHz-1GHz)	TESEQ	CBL 6112D	KUS1806E005	07/12/2025	07/11/2026
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	01/11/2026	01/10/2028
7	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	01/11/2026	01/10/2028
8	Amplifier(30MHz~1GHz)	TST	LNA009100G30	KSEM061	12/18/2025	12/17/2026
9	Amplifier(400MHz~8GHz)	TST	LNA004080G30	KSEM062	12/18/2025	12/17/2026
10	Amplifier(1GHz~18GHz)	TST	LNA010180G45	KSEM039	07/09/2025	07/08/2026
11	Amplifier(18~40GHz)	TST	LNA180400G40	KSEM038	07/09/2025	07/08/2026
12	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	12/30/2025	12/29/2026
13	Software	ESE	E3_V 6.111221a	/	NCR	NCR
14	Measurement Software	Tonscend	JS32-RE V5.0.0.1	/	NCR	NCR
15	Measurement Software	Tonscend	JS32-RSE V5.0.0.0	/	NCR	NCR

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Monopole antenna and no consideration of replacement.

Antenna location: Refer to Internal photos

7 Radio Spectrum Matter Test Results

7.1 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.231(c)

Test Method: ANSI C63.10 (2020) Section 6.9.2

Limit:

Frequency range(MHz)	Limit
70-900	No wider than 0.25% of the center frequency
Above 900	No wider than 0.5% of the center frequency

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.1 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.2 Field Strength of the Fundamental Signal (15.231(e))

Test Requirement Field Strength of the Fundamental Signal (15.231(e))

Test Method: ANSI C63.10 (2020) Section 7.4

Limit:

Fundamental frequency(MHz)	Field strength of fundamental(microvolts/meter)	Field strength of spurious emissions(microvolts/meter)
40.66-40.70	1000	100
70-130	500	50
130-174	500 to 1500	50 to 150
174-260	1500	150
260-470	1500 to 5000	150 to 500
Above 470	5000	500

Remark: the emission limit is based on measurement instrumentation employing an average detector at a distance of 3 meters. The frequencies above 1000MHz are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.1 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_ Keep the EUT in continuously transmitting mode

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Please Refer to Appendix for Details

7.3 Radiated Emissions below 1GHz

Test Requirement 47 CFR Part 15C Section 15.231(e) and 15.209

Test Method: ANSI C63.10 (2020) Section 6.4&6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.1 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 2) Scan from 9kHz to 1GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Please Refer to Appendix for Details

7.4 Dwell Time (15.231(e))

Test Requirement 47 CFR Part 15, Subpart C 15.231(e)
Test Method: ANSI C63.10 (2020) Section 7.4

Limit:

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.1 °C Humidity: 53.2 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.5 Radiated Emissions above 1GHz

Test Requirement 47 CFR Part 15C Section 15.231(e) and 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Limit:

For Restricted bands

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

For Other bands

Fundamental Frequency MHz	Field Strength of Fundamental (dBμV/m @ 3 m)	Field Strength of Hasrmonics and Spurious Emissions (dBμV/m @ 3 m)
40.66 to 40.70	60	40
70 to 130	53.98	33.98
130 to 174	**53.98 to 63.52	33.98 to 43.52
174 to 260	63.52	43.52
260 to 470	**63.52 to 73.98	43.52 to 53.98
Above 470	73.98	53.98
Detector:	Peak for pre-scan	
	QP for 30MHz to1000 MHz:120 kHz resolution bandwidth	
	Peak for Above 1 GHz: 1 MHz resolution bandwidth	

** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

for the band 130-174 MHz, uV/m at 3 meters = $(22.73 \times f) - 2454.55$;

for the band 260-470 MHz, uV/m at 3 meters = $(16.67 \times f) - 2833.33$;

The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

The fundamental frequency of the EUT is 433.92 MHz&315 MHz

The limit for average or QP field strength dBuv/m for the fundamental emission= 72.87 dBμV/m (433.92MHz)& 67.66 dBμV/m(315MHz)

No fundamental is allowed in the restricted bands.

The limit for average field strength dBuV/m for the spurious emission=52.87 dBuV/m(433.92 MHz) & 47.66 dBuV/m(315 MHz). Spurious in the restricted bands must be less than 52.87 dBuV/m(433.92 MHz) & 47.66 dBuV/m(315 MHz) or 15.209, whichever limit permits a higher field strength.

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.1 °C


Humidity: 53.2 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2603000501AT

9 EUT Constructional Details (EUT Photos)


Refer to Appendix_Photographs of EUT Constructional Details for KSCR2603000501AT

10 Appendix

10.1 Field Strength of the Fundamental Signal

433MHz:

Test channel	Freq. (MHz)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
Channel 1	433.92	71.58	92.87	-21.29	Peak	Vertical
		65.46	92.87	-27.41	Peak	Horizontal
		57.51	72.87	-16.92	AVG	Vertical
		51.39	72.87	-23.04	AVG	Horizontal




Remark:

1. If the Peak value below the AV Limit, the AV test doesn't perform for this submission.
2. Average level = Peak level - Duty Cycle Factor
3. Duty Cycle Factor = $20 \cdot \log(\text{Duty Cycle}) = -14.07\text{dB}$

315MHz:

Test channel	Freq. (MHz)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
Channel 1	315	59.76	87.66	-27.90	Peak	Vertical
		70.65	87.66	-17.01	Peak	Horizontal
		45.69	67.66	-21.97	AVG	Vertical
		56.58	67.66	-11.08	AVG	Horizontal



Remark:


- If the Peak value below the AV Limit, the AV test doesn't perform for this submission.
- Average level = Peak level - Duty Cycle Factor
- Duty Cycle Factor = $20 \cdot \log(\text{Duty Cycle}) = -14.07 \text{ dB}$

10.2 Spurious Emissions

Below 1GHz:


433.92MHz:

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.64	2.63	24.61	27.24	40.00	-12.76	QP
2	35.50	3.29	21.41	24.70	40.00	-15.30	QP
3	106.76	3.73	18.64	22.37	43.50	-21.13	QP
4	128.56	3.02	20.29	23.31	43.50	-20.19	QP
5	434.07	47.06	24.52	71.58	Fundamental frequency		peak
6	633.91	3.63	29.15	32.78	46.00	-13.22	QP
7	909.67	3.99	31.51	35.50	46.00	-10.50	QP

Horizontal:




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.53	3.23	24.70	27.93	40.00	-12.07	QP
2	35.62	2.95	21.35	24.30	40.00	-15.70	QP
3	108.65	3.31	19.34	22.65	43.50	-20.85	QP
4	133.62	3.98	20.01	23.99	43.50	-19.51	QP
5	434.07	40.94	24.52	65.46	Fundamental frequency		Peak
6	633.91	3.55	29.15	32.70	46.00	-13.30	QP
7	869.13	19.13	30.79	49.92	72.87	-27.95	Peak


Below 1GHz:

315MHz:

Vertical:



Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.21	3.21	24.95	28.16	40.00	-11.84	QP
2	32.98	3.71	23.15	26.86	40.00	-13.14	QP
3	95.43	3.94	18.03	21.97	43.50	-21.53	QP
4	141.83	3.83	19.57	23.40	43.50	-20.10	QP
5	315.48	49.09	21.57	70.65	Fundamental frequency		Peak
6	537.59	3.85	27.37	31.22	46.00	-14.78	QP
7	912.86	3.88	31.44	35.32	46.00	-10.68	QP

Above 1GHz

433.92MHz:

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	polarization
1	1650.00	85.71	-54.45	31.26	54	-22.74	peak	Vertical
2	2411.25	91.95	-53.61	38.34	54	-15.66	peak	Vertical
3	5533.75	89.99	-47.10	42.89	54	-11.11	peak	Vertical
4	1736.25	92.44	-54.11	38.33	54	-15.67	peak	Horizontal
5	3106.25	88.76	-52.74	36.02	54	-17.98	peak	Horizontal
6	4295.00	89.09	-50.66	38.43	54	-15.57	peak	Horizontal

315MHz:

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	polarization
1	1458.75	86.65	-54.66	31.99	54.00	-22.01	peak	Vertical
2	3026.25	88.73	-53.14	35.59	54.00	-18.41	peak	Vertical
3	4685.00	88.98	-47.75	41.23	54.00	-12.77	peak	Vertical
4	1587.50	85.76	-54.87	30.89	54.00	-23.11	peak	Horizontal
5	2411.25	94.08	-53.61	40.47	54.00	-13.53	peak	Horizontal
6	5176.25	92.29	-47.90	44.39	54.00	-9.61	peak	Horizontal


10.3 20dB Bandwidth

433.92MHz:

Measurement Data:

Frequency (MHz)	20dB bandwidth (kHz)	Limit (kHz)	Results
433.92	139.29	1084.8	Pass

Test plot as follows:




315MHz:

Measurement Data:

Frequency (MHz)	20dB bandwidth (kHz)	Limit (kHz)	Results
315	138.95	787.5	Pass

Test plot as follows:



10.4 Dwell Time



433.92MHz:

Measurement Data:

Test item	Limit (s)	Results
Silent period	$\geq 10s$	Pass

Test item	Test Result (s)	Limit (s)	Results
Overtime	0.0297	$\leq 1s$	Pass

Test plot as follows:




315MHz:

Measurement Data:

Test item	Limit (s)	Results
Transmission Duration	$\geq 10s$	Pass

Test item	Test Result (s)	Limit (s)	Results
Ontime	0.0297	$\leq 1s$	Pass

Test plot as follows:



- End of the Report -