



Power Spectral Density U-NII - 3
Test Model 802.11ac(HT20) Frequency(MHz) 5745




Date: 23.MAY.2019 14:03:13

Power Spectral Density U-NII - 3
Test Model 802.11ac(HT20) Frequency(MHz) 5785



Date: 23.MAY.2019 14:03:52

Power Spectral Density U-NII - 3
Test Model 802.11ac(HT20) Frequency(MHz) 5825



Date: 23.MAY.2019 14:04:22

Power Spectral Density U-NII - 3
Test Model 802.11n-HT40 Frequency(MHz) 5755



Date: 23.MAY.2019 14:08:10

Power Spectral Density U-NII - 3
Test Model 802.11n-HT40 Frequency(MHz) 5795




Date: 23.MAY.2019 14:08:40

Power Spectral Density U-NII - 3
Test Model 802.11ac(HT40) Frequency(MHz) 5755




Date: 23.MAY.2019 14:11:46

Power Spectral Density U-NII - 3
Test Model 802.11ac(HT40) Frequency(MHz) 5795



Date: 23.MAY.2019 14:12:22

Power Spectral Density U-NII - 3
Test Model 802.11ac 80 Frequency(MHz) 5775



Date: 23.MAY.2019 14:15:22

For 2T2R– Total

5150-5250MHz

Operating mode	Test Channel	Power Spectral Density dBm/MHz			Limit (dBm/MHz)
		Antenna A	Antenna B	Total	
802.11a	5180	2.67	2.70	5.70	11
	5200	3.28	3.15	6.23	11
	5240	3.19	3.18	6.20	11
802.11n-HT20	5180	2.21	2.00	5.12	11
	5200	2.73	2.70	5.73	11
	5240	2.6	2.54	5.58	11
802.11ac(HT20)	5180	2.07	2.11	5.10	11
	5200	2.73	2.65	5.70	11
	5240	2.59	2.40	5.51	11
802.11n-HT40	5190	-0.08	-0.64	2.66	11
	5230	-0.01	-0.19	2.91	11
802.11ac(VHT40)	5190	0.03	-0.10	2.98	11
	5230	0.01	-0.13	2.95	11
802.11ac(VHT80)	5210	-3.03	-2.99	0.00	11

5250-5350MHz

Operating mode	Test Channel	Power Spectral Density dBm/MHz			Limit (dBm/MHz)
		Antenna A	Antenna B	Total	
802.11a	5260	3.19	3.1	6.16	11
	5300	3.61	3.66	6.65	11
	5320	4.33	4.26	7.31	11
802.11n-HT20	5260	2.6	2.6	5.61	11
	5300	3	3.13	6.08	11
	5320	3.83	3.85	6.85	11
802.11ac(HT20)	5260	2.69	2.72	5.72	11
	5300	3.22	3.19	6.22	11
	5320	3.88	3.66	6.78	11
802.11n-HT40	5270	0.56	0.26	3.42	11
	5310	1.22	0.81	4.03	11
802.11ac(VHT40)	5270	0.66	0.49	3.59	11
	5310	1.19	0.81	4.01	11
802.11ac(VHT80)	5290	-2.01	-2.13	0.94	11

5725-5850MHz

Operating mode	Test Channel	Power Spectral Density dBm/MHz			Limit (dBm/MHz)
		Antenna A	Antenna B	Total	
802.11a	5745	-1.68	-1.63	1.36	30
	5785	-2.71	-3.17	0.08	30
	5825	-2.95	-3.17	-0.05	30
802.11n-HT20	5745	-1.91	-1.97	1.07	30
	5785	-3.18	-3.24	-0.20	30
	5825	-3.34	-3.55	-0.43	30
802.11ac(HT20)	5745	-1.98	-1.91	1.07	30
	5785	-3.16	-3.14	-0.14	30
	5825	-3.23	-3.58	-0.39	30
802.11n-HT40	5755	-4.79	-4.84	-1.80	30
	5795	-5.75	-5.97	-2.85	30
802.11ac(VHT40)	5755	-4.67	-4.7	-1.67	30
	5795	-5.81	-5.91	-2.85	30
802.11ac(VHT80)	5775	-8.44	-8.56	-5.49	30

8.4 FREQUENCY STABILITY

8.4.1 Applicable Standard

According to FCC Part 15.407(g)
ANSI C63.10 Section 6.8

8.4.2 Conformance Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

8.4.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.4.4 Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 10 kHz.

Set Span= Entire absence of modulation emissions band

Set the video bandwidth (VBW) =30 kHz. width

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.

Beginning at each temperature level specified in user manual , the frequency shall be measured within one minute after application of primary power to the transmitter and at intervals of no more than one minute thereafter until ten minutes have elapsed or until sufficient measurements are obtained to indicate clearly that the frequency has stabilized within the applicable tolerance, whichever time period is greater. During each test, the ambient temperature shall not be allowed to rise more than 10° centigrade above the respective beginning ambient temperature level

Measure and record the results in the test report.

8.4.5 Test Results

802.11a

5180

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5180.0116	11.6	Pass
	-10	5179.9874	-12.6	Pass
	0	5180.0121	12.1	Pass
	10	5180.0032	3.2	Pass
	20	5180.0091	9.1	Pass
	30	5179.9826	-17.4	Pass
	40	5179.9868	-13.2	Pass
	55	5179.9943	-5.7	Pass
85% Vnom	25	5180.0141	14.1	Pass
115% Vnom	25	5180.0135	13.5	Pass

5200

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5199.9952	-4.8	Pass
	-10	5199.9996	-0.4	Pass
	0	5199.9992	-0.8	Pass
	10	5199.9986	-1.4	Pass
	20	5199.9820	-18	Pass
	30	5199.9846	-15.4	Pass
	40	5200.0073	7.3	Pass
	55	5200.0082	8.2	Pass
85% Vnom	25	5200.0062	6.2	Pass
115% Vnom	25	5199.992	-8.0	Pass

5240

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5240.0048	4.8	Pass
	-10	5239.9943	-5.7	Pass
	0	5239.9918	-8.2	Pass
	10	5239.9933	-6.7	Pass
	20	5239.9825	-17.5	Pass
	30	5240.0107	10.7	Pass
	40	5240.0165	16.5	Pass
	55	5240.0099	9.9	Pass
85% Vnom	25	5240.0287	28.7	Pass
115% Vnom	25	5240.0189	18.9	Pass

5190

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5190.0022	2.2	Pass
	-10	5189.9925	-7.5	Pass
	0	5189.9810	-19	Pass
	10	5189.9992	-0.8	Pass
	20	5190.0122	12.2	Pass
	30	5189.9823	-17.7	Pass
	40	5189.9954	-4.6	Pass
	55	5189.9825	-17.5	Pass
85% Vnom	25	5190.0119	11.9	Pass
115% Vnom	25	5189.9995	-0.5	Pass

5230

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5230.0141	14.1	Pass
	-10	5230.0018	1.8	Pass
	0	5229.9822	-17.8	Pass
	10	5230.0166	16.6	Pass
	20	5229.9977	-2.3	Pass
	30	5230.0105	10.5	Pass
	40	5230.0049	4.9	Pass
	55	5230.0134	13.4	Pass
85% Vnom	25	5230.0204	20.4	Pass
115% Vnom	25	5230.0205	20.5	Pass

5210

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5210.0132	13.2	Pass
	-10	5209.9888	-11.2	Pass
	0	5210.0201	20.1	Pass
	10	5210.0224	22.4	Pass
	20	5210.0116	11.6	Pass
	30	5210.0086	8.6	Pass
	40	5210.0195	19.5	Pass
	55	5210.0062	6.2	Pass
85% Vnom	25	5209.9893	-10.7	Pass
115% Vnom	25	5210.0215	21.5	Pass

802.11a

5260

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5259.9921	-7.9	Pass
	-10	5260.005	5.0	Pass
	0	5259.9873	-12.7	Pass
	10	5260.0061	6.1	Pass
	20	5260.0007	0.7	Pass
	30	5259.9842	-15.8	Pass
	40	5259.9911	-8.9	Pass
	55	5260.027	27	Pass
85% Vnom	25	5259.9806	-19.4	Pass
115% Vnom	25	5259.9832	-16.8	Pass

5280

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5280.0045	4.5	Pass
	-10	5280.0200	20	Pass
	0	5279.9842	-15.8	Pass
	10	5279.9882	-11.8	Pass
	20	5279.9816	-18.4	Pass
	30	5280.0008	0.8	Pass
	40	5280.0092	9.2	Pass
	55	5280.0201	20.1	Pass
85% Vnom	25	5280.0254	25.4	Pass
115% Vnom	25	5280.0188	18.8	Pass

5320

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5319.9894	-10.6	Pass
	-10	5319.9954	-4.6	Pass
	0	5320.0161	16.1	Pass
	10	5319.9807	-19.3	Pass
	20	5319.9958	-4.2	Pass
	30	5319.9887	-11.3	Pass
	40	5319.9929	-7.1	Pass
	55	5319.9935	-6.5	Pass
85% Vnom	25	5320.0091	9.1	Pass
115% Vnom	25	5320.0277	27.7	Pass

5270

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5270.0017	1.7	Pass
	-10	5270.0078	7.8	Pass
	0	5270.0142	14.2	Pass
	10	5270.027	27	Pass
	20	5270.0254	25.4	Pass
	30	5270.0161	16.1	Pass
	40	5270.0269	26.9	Pass
	55	5270.0003	0.3	Pass
85% Vnom	25	5270.0017	1.7	Pass
115% Vnom	25	5270.0262	26.2	Pass

5310

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5309.9971	-2.9	Pass
	-10	5309.9921	-7.9	Pass
	0	5310.0131	13.1	Pass
	10	5309.9991	-0.9	Pass
	20	5310.0169	16.9	Pass
	30	5309.9939	-6.1	Pass
	40	5309.9975	-2.5	Pass
	55	5309.9887	-11.3	Pass
85% Vnom	25	5310.0046	4.6	Pass
115% Vnom	25	5310.0054	5.4	Pass

5290

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5289.9846	-15.4	Pass
	-10	5289.9999	-0.1	Pass
	0	5290.0062	6.2	Pass
	10	5290.0232	23.2	Pass
	20	5289.9834	-16.6	Pass
	30	5289.9891	-10.9	Pass
	40	5290.0144	14.4	Pass
	55	5290.0127	12.7	Pass
85% Vnom	25	5289.9881	-11.9	Pass
115% Vnom	25	5290.0057	5.7	Pass

802.11a

5745

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5744.9979	-2.1	Pass
	-10	5745.0044	4.4	Pass
	0	5745.0008	0.8	Pass
	10	5745.0006	0.6	Pass
	20	5745.0293	29.3	Pass
	30	5744.9917	-8.3	Pass
	40	5744.9857	-14.3	Pass
	55	5744.9804	-19.6	Pass
85% Vnom	25	5745.0080	8.0	Pass
115% Vnom	25	5744.9920	-8.0	Pass

5785

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5785.0071	7.1	Pass
	-10	5784.9963	-3.7	Pass
	0	5784.9817	-18.3	Pass
	10	5785.0077	7.7	Pass
	20	5785.0165	16.5	Pass
	30	5785.015	15	Pass
	40	5785.0219	21.9	Pass
	55	5785.0169	16.9	Pass
85% Vnom	25	5784.9954	-4.6	Pass
115% Vnom	25	5785.0202	20.2	Pass

5825

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5824.9986	-1.4	Pass
	-10	5825.0239	23.9	Pass
	0	5824.9802	-19.8	Pass
	10	5824.9959	-4.1	Pass
	20	5824.9824	-17.6	Pass
	30	5825.0227	22.7	Pass
	40	5825.028	28	Pass
	55	5825.0175	17.5	Pass
85% Vnom	25	5825.0033	3.3	Pass
115% Vnom	25	5825.0204	20.4	Pass

5755

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5755.0042	4.2	Pass
	-10	5755.0094	9.4	Pass
	0	5755.0076	7.6	Pass
	10	5754.9992	-0.8	Pass
	20	5755.0145	14.5	Pass
	30	5755.0224	22.4	Pass
	40	5754.9893	-10.7	Pass
	55	5755.0084	8.4	Pass
85% Vnom	25	5754.9851	-14.9	Pass
115% Vnom	25	5755.0006	0.6	Pass

5795

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5794.9913	-8.7	Pass
	-10	5795.0159	15.9	Pass
	0	5795.0134	13.4	Pass
	10	5795.0204	20.4	Pass
	20	5795.0059	5.9	Pass
	30	5795.0026	2.6	Pass
	40	5795.0175	17.5	Pass
	55	5795.0066	6.6	Pass
85% Vnom	25	5795.0068	6.8	Pass
115% Vnom	25	5795.0085	8.5	Pass

5775

Voltage(V)	Temp(°C)	Test Frequency (MHz)	Max. Deviation (KHz)	Verdict
Vnom	-20	5775.0129	12.9	Pass
	-10	5774.9910	-9.0	Pass
	0	5775.0052	5.2	Pass
	10	5774.9986	-1.4	Pass
	20	5775.0163	16.3	Pass
	30	5774.9873	-12.7	Pass
	40	5775.0062	6.2	Pass
	55	5774.9922	-7.8	Pass
85% Vnom	25	5774.9992	-0.8	Pass
115% Vnom	25	5775.0222	22.2	Pass

8.5 UNDESIRABLE RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.407 (b)

According to 789033 D02 Section II(G)

8.5.2 Conformance Limit

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

8.5.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.5.4 Test Procedure

■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

Set RBW=120kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for < 30 MHz (150KHz to 30KHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Repeat above procedures until all frequency measured was complete.

■ Unwanted Maximum peak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW $\geq$ 3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

■ Unwanted Average Emissions Measurements above 1000 MHz

Method VB (Averaging using reduced video bandwidth): Alternative method.

RBW = 1 MHz.

Video bandwidth. • If the EUT is configured to transmit with duty cycle $\geq$ 98 percent, set $VBW \leq RBW/100$ (i.e., 10 kHz) but not less than 10 Hz.

• If the EUT duty cycle is $<$ 98 percent, set $VBW \geq 1/T$, where T is defined in section II.B.1.a).

Video bandwidth mode or display mode • The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).

• As an alternative, the analyzer may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some analyzers require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of $1/x$, where x is the duty cycle. For example, use at least 200 traces if the duty cycle is 25 percent. (If a specific emission is demonstrated to be continuous—i.e., 100 percent duty cycle—rather than turning on and off with the transmit cycle, at least 50 traces shall be averaged.)

■ Band edge measurements.

Unwanted band-edge emissions may be measured using either of the special band-edge measurement techniques (the marker-delta or integration methods) described below. Note that the marker-delta method is primarily a radiated measurement technique that requires the 99% occupied bandwidth edge to be within 2 MHz of the authorized band edge, whereas the integration method can be used in either a radiated or conducted measurement without any special requirement with regards to the displacement of the unwanted emission(s) relative to the authorized bandwidth.

Marker-Delta Method.

The marker-delta method, as described in ANSI C63.10, can be used to perform measurements of the radiated unwanted emissions level of emissions provided that the 99% occupied bandwidth of the fundamental is within 2 MHz of the authorized band-edge.

8.5.5 Test Results

The voltage 120V & 240V and the modes 802.11a/n/ac has been tested and the worst result recorded as below

- ☒ For Undesirable radiated Spurious Emission in U-NII – 1
 All the modes 802.11a/n/ac has been tested, the worst result antenna A 802.11a recorded as below:

☒ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

Test mode: 802.11a Frequency(MHz): 5180

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
6686.11	V	62.42	-32.81	-27	-5.81
10360.00	V	61.33	-33.90	-27	-6.90
15540.00	V	57.78	-37.45	-27	-10.45
6686.11	H	60.88	-34.35	-27	-7.35
10360.00	H	64.48	-30.75	-27	-3.75
15540.00	H	59.41	-35.82	-27	-8.82

Test mode: 802.11a Frequency(MHz): 5200

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5847.78	V	60.51	-34.72	-27	-7.72
10400.00	V	59.23	-36.00	-27	-9.00
15600.00	V	58.05	-37.18	-27	-10.18
5847.78	H	61.87	-33.36	-27	-6.36
10400.00	H	61.63	-33.60	-27	-6.60
15600.00	H	57.16	-38.07	-27	-11.07

Test mode: 802.11a Frequency(MHz): 5240

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
6603.46	V	61.95	-33.28	-27	-6.28
10480.00	V	59.83	-35.40	-27	-8.40
15720.00	V	61.3	-33.93	-27	-6.93
6603.46	H	64.26	-30.97	-27	-3.97
10480.00	H	57.11	-38.12	-27	-11.12
15720.00	H	58.66	-36.57	-27	-9.57

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77

d is the measurement distance in 3 meters

- ☒ Undesirable radiated Undesirable radiated Spurious Emission in Band Edge

Test mode: 802.11a Frequency(MHz): 5180


Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5149.75	H	58.47	-36.76	-27	Pass
5148.15	V	56.11	-39.12	-27	Pass

Test mode: 802.11a Frequency(MHz): 5240

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5350.55	V	55.59	-39.64	-27	Pass
5350.40	H	54.44	-40.79	-27	Pass


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

U-NII - 1			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ 5180	☐ 5200	☐ 5240
	Ant. Pol		H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII - 1			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ 5180	☐ 5200	☐ 5240
	Ant. Pol		V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII - 1			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☐ 5180	☐ 5200	☒ 5240
	Ant. Pol		H



U-NII - 1			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☐ 5180	☐ 5200	☒ 5240
	Ant. Pol		V



- ☒ For Undesirable radiated Spurious Emission in U-NII -2A
All the modes 802.11a/n/ac has been tested and the worst result 802.11a recorded as below:
: ☒ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

Test mode: 802.11a Frequency(MHz): 5260

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
7137.13	V	64.03	-31.20	-27	-4.20
10520.00	V	57.60	-37.63	-27	-10.63
15780.00	V	61.64	-33.59	-27	-6.59
7137.13	H	60.15	-35.08	-27	-8.08
10520.00	H	60.80	-34.43	-27	-7.43
15780.00	H	62.08	-33.15	-27	-6.15

Test mode: 802.11a Frequency(MHz): 5280

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
6411.12	V	62.16	-33.07	-27	-6.07
10560.00	V	62.24	-32.99	-27	-5.99
15840.00	V	57.81	-37.42	-27	-10.42
6411.12	H	63.25	-31.98	-27	-4.98
10560.00	H	57.68	-37.55	-27	-10.55
15840.00	H	59.16	-36.07	-27	-9.07

Test mode: 802.11a Frequency(MHz): 5320

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5440.56	V	60.14	-35.09	-27	-8.09
10640.00	V	60.66	-34.57	-27	-7.57
15960.00	V	58.65	-36.58	-27	-9.58
5440.56	H	60.02	-35.21	-27	-8.21
10640.00	H	62.44	-32.79	-27	-5.79
15960.00	H	58.53	-36.70	-27	-9.70

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77
d is the measurement distance in 3 meters

- ☒ Undesirable radiated Undesirable radiated Spurious Emission in Band Edge

Test mode: 802.11a Frequency(MHz): 5260


Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5149.95	H	55.38	-39.85	-27	Pass
5147.90	V	54.10	-41.13	-27	Pass

Test mode: 802.11a Frequency(MHz): 5320

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5350.55	V	55.54	-39.69	-27	Pass
5351.75	H	55.30	-39.93	-27	Pass


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

U-NII -2A			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11 ac (VHT20)
	☒ 5260	☐ 5300	☐ 5320
	Ant.Pol		H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII -2A			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5100-5150MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11 ac (VHT20)
	☒ 5260	☐ 5300	☐ 5320
	Ant.Pol		V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII -2A			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11 ac (VHT20)
	☐ 5260	☐ 5300	☒ 5320
	Ant.Pol		H



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII -2A			
Test Model	Undesirable radiated Spurious Emission in Restricted Band (5350-5400MHz)		
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11 ac (VHT20)
	☐ 5260	☐ 5300	☒ 5320
	Ant.Pol		V



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

☒ For Undesirable radiated Spurious Emission in U-NII -3

All the modes 802.11a/n/ac has been tested and the worst result 802.11a recorded as below:

- ☒ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

Test mode: 802.11a Frequency(MHz): 5745

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
6455.51	V	63.03	-32.20	-27	-5.20
10640.00	V	60.88	-34.35	-27	-7.35
15960.00	V	60.69	-34.54	-27	-7.54
6455.51	H	62.67	-32.56	-27	-5.56
10640.00	H	58.44	-36.79	-27	-9.79
15960.00	H	58.75	-36.48	-27	-9.48

Test mode: 802.11a Frequency(MHz): 5785

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
6388.42	V	63.45	-31.78	-27	-4.78
11570.00	V	63.25	-31.98	-27	-4.98
17355.00	V	59.2	-36.03	-27	-9.03
6388.42	H	61.3	-33.93	-27	-6.93
11570.00	H	58.52	-36.71	-27	-9.71
17355.00	H	61.74	-33.49	-27	-6.49

Test mode: 802.11a Frequency(MHz): 5825

Freq. (MHz)	Ant.Pol. H/V	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5443.30	V	62.89	-32.34	-27	-5.34
11650.00	V	63.49	-31.74	-27	-4.74
17475.00	V	57.32	-37.91	-27	-10.91
5443.30	H	60.49	-34.74	-27	-7.74
11650.00	H	64.24	-30.99	-27	-3.99
17475.00	H	58.25	-36.98	-27	-9.98

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77

d is the measurement distance in 3 meters

- ☒ Undesirable radiated Spurious Emission in band edge

Test mode: 802.11a Frequency: 5745

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5725.00	H	64.37	-30.86	27.00	PASS
5724.37	V	65.82	-29.41	25.58	PASS

Test mode: 802.11a Frequency: 5825

Freq. (MHz)	Ant.Pol. H/V	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5850.00	V	64.64	-30.59	27.00	PASS
5850.00	H	64.77	-30.46	27.00	PASS

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Correct Factor +Cable Loss.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77


d is the measurement distance in 3 meters

U-NII -3
Test Model Undesirable radiated Undesirable radiated Spurious Emission in Band Edge
☒802.11a ☐802.11n(HT20) ☐802.11n(HT40)
☒5745 Ant.Pol H




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C B4 (Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %

U-NII -3
Test Model Undesirable radiated Undesirable radiated Spurious Emission in Band Edge
☒802.11a ☐802.11n(HT20) ☐802.11n(HT40)
☒5745 Ant.Pol V




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C B4 (Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %


U-NII -3			
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ 5825		Ant.Pol H




U-NII -3			
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge
	☒ 802.11a	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ 5825		Ant.Pol V




- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)
All the modes 802.11a/n/ac has been tested, the worst result antenna A 802.11a recorded as below:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		38.7300	36.05	-12.52	23.53	40.00	-16.47	QP		
2		63.9500	36.29	-13.37	22.92	40.00	-17.08	QP		
3		153.1900	39.71	-15.16	24.55	43.50	-18.95	QP		
4		415.0900	31.99	-5.66	26.33	46.00	-19.67	QP		
5	*	725.4900	30.21	-0.64	29.57	46.00	-16.43	QP		
6		983.5100	29.61	3.61	33.22	54.00	-20.78	QP		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		70.7400	36.78	-15.56	21.22	40.00	-18.78	QP		
2		224.0000	35.33	-10.91	24.42	46.00	-21.58	QP		
3		423.8200	34.46	-5.51	28.95	46.00	-17.05	QP		
4		754.5900	28.81	-0.15	28.66	46.00	-17.34	QP		
5	*	905.9100	29.64	2.20	31.84	46.00	-14.16	QP		
6		1000.0000	29.27	3.93	33.20	54.00	-20.80	QP		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		71.7100	37.13	-15.86	21.27	40.00	-18.73	QP			
2		221.0900	34.35	-11.06	23.29	46.00	-22.71	QP			
3	*	416.0600	38.45	-5.65	32.80	46.00	-13.20	QP			
4		457.7700	35.50	-5.33	30.17	46.00	-15.83	QP			
5		787.5700	30.44	0.14	30.58	46.00	-15.42	QP			
6		991.2700	30.31	3.79	34.10	54.00	-19.90	QP			



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		38.7300	35.25	-12.52	22.73	40.00	-17.27	QP		
2		153.1900	38.54	-15.16	23.38	43.50	-20.12	QP		
3		418.0000	33.39	-5.61	27.78	46.00	-18.22	QP		
4		631.4000	29.25	-1.86	27.39	46.00	-18.61	QP		
5		777.8700	29.54	0.10	29.64	46.00	-16.36	QP		
6	*	951.5000	29.54	2.98	32.52	46.00	-13.48	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		70.7400	37.18	-15.56	21.62	40.00	-18.38	QP		
2		211.3900	34.99	-11.70	23.29	43.50	-20.21	QP		
3		421.8800	35.00	-5.55	29.45	46.00	-16.55	QP		
4		712.8800	30.20	-0.82	29.38	46.00	-16.62	QP		
5	*	845.7700	29.51	0.88	30.39	46.00	-15.61	QP		
6		989.3300	29.19	3.76	32.95	54.00	-21.05	QP		



Mode:WIFI5G TX 5240MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		42.6100	34.52	-11.54	22.98	40.00	-17.02	QP		
2		152.2200	37.96	-15.21	22.75	43.50	-20.75	QP		
3		420.9100	30.99	-5.57	25.42	46.00	-20.58	QP		
4		662.4400	29.67	-1.51	28.16	46.00	-17.84	QP		
5	*	849.6500	30.24	0.93	31.17	46.00	-14.83	QP		
6		985.4500	28.70	3.65	32.35	54.00	-21.65	QP		

8.6 POWER LINE CONDUCTED EMISSIONS

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: **N**

Temperature: 24.9

Limit: CE)FCC PART15 class B_QP


Power: AC 120V/60Hz

Humidity: 54 %

Mode: TX

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	34.55	9.67	44.22	66.00	-21.78	QP	
2		0.1500	17.22	9.67	26.89	56.00	-29.11	AVG	
3		0.2500	33.09	9.55	42.64	61.76	-19.12	QP	
4		0.2500	19.65	9.55	29.20	51.76	-22.56	AVG	
5		0.5780	34.01	9.57	43.58	56.00	-12.42	QP	
6	*	0.5780	28.48	9.57	38.05	46.00	-7.95	AVG	
7		1.0820	28.58	9.59	38.17	56.00	-17.83	QP	
8		1.0820	19.85	9.59	29.44	46.00	-16.56	AVG	
9		1.7980	28.02	9.60	37.62	56.00	-18.38	QP	
10		1.7980	18.89	9.60	28.49	46.00	-17.51	AVG	
11		13.6180	29.39	9.87	39.26	60.00	-20.74	QP	
12		13.6180	15.09	9.87	24.96	50.00	-25.04	AVG	



Site Conduction #1

Phase: **L1**

Temperature: 24.9

Limit: CE)FCC PART15 class B_QP

Power: AC 120V/60Hz

Humidity: 54 %

Mode:TX

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1580	34.80	9.62	44.42	65.57	-21.15	QP	
2		0.1580	16.87	9.62	26.49	55.57	-29.08	AVG	
3		0.3220	31.80	9.56	41.36	59.66	-18.30	QP	
4		0.3220	18.82	9.56	28.38	49.66	-21.28	AVG	
5		0.5820	37.41	9.57	46.98	56.00	-9.02	QP	
6	*	0.5820	28.62	9.57	38.19	46.00	-7.81	AVG	
7		1.1460	31.88	9.59	41.47	56.00	-14.53	QP	
8		1.1460	19.83	9.59	29.42	46.00	-16.58	AVG	
9		1.8020	32.49	9.60	42.09	56.00	-13.91	QP	
10		1.8020	19.39	9.60	28.99	46.00	-17.01	AVG	
11		13.0180	33.55	9.86	43.41	60.00	-16.59	QP	
12		13.0180	22.73	9.86	32.59	50.00	-17.41	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

- The EUT has 2 antennas: an Internal Antenna for WIFI 5G, Othe gain is 2.3 dBi;
Note: ☒ Antennas use a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant F(dB)	Cab L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5