

1. RF Exposure Requirements

1.1 General Information

Client Information

Applicant: Hangzhou BroadLink Technology Co., Ltd.
Address of applicant: Building C, 57 Jiang'er Road, Binjiang Hangzhou Zhejiang 310052
China

Manufacturer: Hangzhou BroadLink Technology Co., Ltd.
Address of manufacturer: Building C, 57 Jiang'er Road, Binjiang Hangzhou Zhejiang 310052
China

General Description of EUT:

Product Name: Smart Control Screen
Trade Name: /
Model No.: IC.GG.4
Adding Model(s): IC.S5, BL-H22F4, ZB.SS.PO4, WIFI.BGM.3S, SS.P03
Rated Voltage: AC110-240V 50-60Hz
Battery Capacity: /
Power Adapter: 5W
Adapter Model: /
FCC ID: 2ATEV-ICGG4
Equipment Type: Mobile device

Technical Characteristics of EUT:

Bluetooth (LE mode)

Bluetooth Version: V5.0 (LE mode)
Frequency Range: 2402-2480MHz
RF Output Power: 1Mbps: 13.19dBm (Conducted)
2Mbps: 13.21dBm (Conducted)
Data Rate: 1Mbps, 2Mbps
Modulation: GFSK
Quantity of Channels: 40
Channel Separation: 2MHz
Type of Antenna: FPC Antenna
Antenna Gain: 2.99dBi

Bluetooth(BR/EDR mode)

Bluetooth Version: V5.0 (BR/EDR mode)
Frequency Range: 2402-2480MHz
RF Output Power: 14.47dBm (Conducted)
Data Rate: 1Mbps, 2Mbps, 3Mbps
Modulation: GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels: 79

Channel Separation: 1MHz
Type of Antenna: FPC Antenna
Antenna Gain: 2.99dBi

Bluetooth(Wi-Fi 2.4G mode)

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
RF Output Power: 20.31dBm (Conducted)
Type of Modulation: CCK, OFDM, BPSK, QPSK, 16QAM, 64QAM
Quantity of Channels: 11 for 802.11b/g/n(HT20)
Channel Separation: 5MHz
Type of Antenna: FPC Antenna
Antenna Gain: 2.99dBi

Bluetooth(Wi-Fi 5G mode)

Support Standards: 802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20,
802.11ac-VHT40,802.11ac-VHT80
Frequency Range: 5180-5240MHz, 5260-5320MHz
5500-5700MHz, 5745-5825MHz
Max. RF Output Power: 18.88dBm (Conducted)
Type of Modulation: BPSK,QPSK, 16QAM, 64QAM, 256QAM
Type of Antenna: FPC Antenna
Antenna Gain: 2.58dBi

1.2 RF Exposure Exemption

According to §1.1307(b)(3) and KDB 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Option A: FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1mW, regardless of separation distance.

Option B: FCC Rule Part 1.1307 (b)(3)(i)(B): The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C: FCC Rule Part 1.1307 (b)(3)(i)(C): The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$
1.34-30	$3,450 R^2/f^2$
30-300	$3.83 R^2$
300-1,500	$0.0128 R^2 f$
1,500-100,000	$19.2 R^2$

For Multiple RF sources: FCC Rule Part 1.1307(b)(3)(ii):

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

1.3 Calculated Result

Radio Access Technology	Prediction Frequency (MHz)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	Tune-Up Time-Averaged Power (dBm)	ERP (dBm)
Bluetooth	2402	14.47	2.99	100	15.00	15.84
Wi-Fi 2.4G	2412	20.31	2.99	100	21.00	21.84
Wi-Fi 5G	5180	17.74	2.58	100	18.00	18.43
Wi-Fi 5G	5260	17.60	2.58	100	18.00	18.43
Wi-Fi 5G	5500	17.29	2.58	100	18.00	18.43
Wi-Fi 5G	5745	18.88	2.58	100	19.00	19.43

Frequency (MHz)	Option	Min. Distance (cm)	Max. Power (dBm) (mW)		Exposure Limit (mW)	Ratio	Result Pass/Fail
2402	C	20.00	15.84	38.37	768.00	0.05	Pass
2412	C	20.00	21.84	152.76	768.00	0.20	Pass
5180	C	20.00	18.43	69.66	768.00	0.09	Pass
5260	C	20.00	18.43	69.66	768.00	0.09	Pass
5500	C	20.00	18.43	69.66	768.00	0.09	Pass
5745	C	20.00	19.43	87.70	768.00	0.11	Pass

Note: 1. Time-Averaged Power=Output Power * Duty Cycle; ERP= Time-Averaged Power+ Antenna gain-2.15dB

2. Option A, B and C refers as clause 1.2.

3. For option B, Max (time-averaged power, effective radiated power (ERP)) converts to Max. Power. For option C, ERP converts to Max. Power;

4. For option B, P_{th} (mW) converts to Exposure Limit (mW); For option C, ERP (W) converts to Exposure Limit (mW).

5. Ratio= Tune-Up ERP (mW)/ Exposure Limit (mW)

Mode for Simultaneous Multi-band Transmission:

Radio Access Technology	Ratio 1	Ratio 2	Simultaneous Ratio	Limit	Result
					Pass/Fail
--	--	--	--	--	--

Note: Bluetooth and Wi-Fi can't transmit at the same time.

Result: Pass