



SAR TEST REPORT

Applicant Huawei Device Co.,Ltd.
FCC ID 2ATEYPPA-LX3
Product Smart Phone
Model PPA-LX3
Report No. R2101A0041-S1
Issue Date January 8, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **IEEE 1528- 2013, ANSI C95.1: 1992,IEEE C95.1: 1991**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Yu Wang

Approved by: Guangchang Fan

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Test facility	4
1.3	Testing Location.....	4
1.4	Laboratory Environment.....	5
2	Statement of Compliance	6
3	Description of Equipment under Test.....	7
4	Test Specification, Methods and Procedures	10
5	Operational Conditions during Test	11
5.3	Test Positions.....	11
5.3.1	Against Phantom Head	11
5.3.2	Body Worn Configuration.....	11
5.3.3	Phablet SAR test considerations	12
5.4	Measurement Variability	13
5.5	Test Configuration	14
5.5.1	GSM Test Configuration.....	14
5.5.2	UMTS Test Configuration.....	14
5.5.3	LTE Test Configuration.....	18
5.5.4	Wi-Fi Test Configuration.....	20
5.5.5	BT Test Configuration	21
5.5.6	Dynamic antenna tuning description.....	21
5.5.7	Power Reduction Configuration	21
6	SAR Measurements System Configuration	23
6.1	SAR Measurement Set-up	23
6.2	DASY5 E-field Probe System.....	24
6.3	SAR Measurement Procedure	25
7	Main Test Equipment.....	27
8	Tissue Dielectric Parameter Measurements & System Verification	28
8.1	Tissue Verification	28
8.2	System Performance Check.....	29
8.3	SAR System Validation	31
9	Normal and Maximum Output Power	32
9.1	GSM Mode	32
9.2	WCDMA Mode	35
9.3	LTE Mode.....	41
9.4	WLAN Mode.....	93
9.5	Bluetooth Mode	95
10	Measured and Reported (Scaled) SAR Results	96
10.1	EUT Antenna Locations	96
10.2	Measured SAR Results	97
10.3	Simultaneous Transmission Analysis	129



11	Measurement Uncertainty	135
	ANNEX A: Test Layout.....	136
	ANNEX B: System Check Results.....	138
	ANNEX C: Highest Graph Results.....	151
	ANNEX D: Probe Calibration Certificate.....	216
	ANNEX E: D835V2 Dipole Calibration Certificate.....	225
	ANNEX F: D1750V2 Dipole Calibration Certificate.....	233
	ANNEX G: D1900V2 Dipole Calibration Certificate	241
	ANNEX H: D2450V2 Dipole Calibration Certificate	249
	ANNEX I: D2600V2 Dipole Calibration Certificate	257
	ANNEX J:DAE4 Calibration Certificate.....	265



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Fan Guangchang
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: fanguangchang@ta-shanghai.com



1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Table 1: Highest Reported SAR

Mode	Highest Reported SAR (W/kg)		
	1g SAR Head	1g SAR Body-worn (Separation 15mm)	1g SAR Hotspot (Separation 10mm)
GSM 850	0.54	0.10	0.24
GSM 1900	0.44	0.21	0.47
WCDMA Band II	0.42	0.61	0.70
WCDMA Band IV	0.60	0.35	0.65
WCDMA Band V	0.67	0.39	0.42
LTE FDD 2	0.60	0.28	0.71
LTE FDD 4	0.64	0.39	0.86
LTE FDD 5	0.63	0.34	0.35
LTE FDD 7	0.71	0.37	0.62
LTE FDD 66	0.32	0.24	0.64
Wi-Fi (2.4G)	0.14	0.10	0.27
BT	0.07	NA	0.04
Date of Testing:	September 9, 2020~ September 19, 2020		
Date of Sample Receiving:	September 7, 2020		
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

Note: 1) The highest Reported SAR for head, body-worn, hotspot and simultaneous transmission exposure conditions are 0.71W/kg, 0.61W/kg, 0.86W/kg and 0.91W/kg.

2) Stand-alone SAR evaluation is not required for BT, more details information see section 10.2

3) For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and that positions the handset a minimum of 15mm from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits according to the FCC rule § 2.1093, the ANSI C95.1: 1992/IEEE C95.1: 1991, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013.

This report is only added FCC ID, there is no test in this report and the original report number is R2009H0244-S1V1.

3 Description of Equipment under Test

Client Information

Applicant	Huawei Device Co.,Ltd.
Applicant address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China
Manufacturer	Huawei Device Co.,Ltd.
Manufacturer address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China

General Technologies

Application Purpose:	Original Grant		
EUT Stage:	Identical Prototype		
Model:	PPA-LX3		
SN:	2KTNU20811100262(Battery1) 2KTNU20811100771(Battery2) 2KTNU20811100733(Battery3)		
Hardware Version:	HL1PPAM		
Software Version:	10.1.1.100(C900E25R1P2)		
Antenna Type:	Internal Antenna		
Device Class:	B		
Wi-Fi Hotspot:	Wi-Fi 2.4G		
Power Class:	GSM 850:4 GSM 1900:1 UMTS Band II/IV/V:3 LTE FDD 2/4/5/7/66:3		
Power Level:	GSM 850:level 5 GSM 1900:level 0 UMTS Band II/IV/V:all up bits LTE FDD 2/4/5/7/66:max power		
EUT Accessory			
Accessory	Model	Manufacture	No.
Battery	HB526488EEW	Huawei Device Co.,Ltd. (Manufacturer: Dongguan NVT Technology Co., Ltd)	1
		Huawei Device Co.,Ltd. (Manufacturer: Huizhou Desay Battery Co., Ltd.)	2
		Huawei Device Co.,Ltd. (Manufacturer: Sunwoda Electronic Co., Ltd.	3
Earphone	MEND1532B528A 11	FUYU ELECTRICAL TECHNOLOGY(HUAIAN)CO., LTD	1



	1293-3283-3.5MM -339	Boluo County Quancheng Electronic Co.,ltd	2
	EPAB542-2WH05- DH	FOXCONN INTERCONNECT TECHNOLOGY LIMITED	3
Note: The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			

Wireless Technology and Frequency Range

Wireless Technology		Modulation	Operating mode	Tx (MHz)
GSM	850	Voice(GMSK) GPRS(GMSK)	☐ Multi-slot Class:8-1UP ☐ Multi-slot Class:10-2UP	824 ~ 849
	1900	EGPRS(GMSK,8PSK)	☒ Multi-slot Class:12-4UP ☐ Multi-slot Class:33-4UP	1850 ~ 1910
	Does this device support DTM (Dual Transfer Mode)? ☐ Yes ☒ No			
UMTS	Band II	QPSK	HSDPA UE Category:14	1850 ~ 1910
	Band IV		HSUPA UE Category:6	1710 ~ 1755
	Band V		DC-HSDPA UE Category:24	824 ~ 849
LTE	FDD 2	QPSK, 16QAM	Rel.12, Category 4	1850 ~ 1910
	FDD 4			1710 ~ 1755
	FDD 5			824 ~ 849
	FDD 7			2500 ~ 2570
	FDD 66			1710 ~ 1780
	Does this device support Carrier Aggregation (CA) ☐ Yes ☒ No			
Does this device support SV-LTE (1xRTT-LTE)? ☐ Yes ☒ No				
BT	2.4G	Version 5.1LE		2402 ~2480
Wi-Fi	2.4G	DSSS,OFDM	802.11b/g/n HT20	2412 ~ 2462
		OFDM	802.11n HT40	2422 ~ 2452
	Does this device support MIMO ☐ Yes ☒ No			



4 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE 1528- 2013, ANSI C95.1: 1992, IEEE C95.1: 1991, the following FCC Published RF exposure KDB procedures:

IEC 62209-1

Reference Standards

KDB 248227 D01 802.11Wi-Fi SAR v02r02

KDB 447498 D01 General RF Exposure Guidance v06

KDB 648474 D04 Handset SAR v01r03

KDB 690783 D01 SAR Listings on Grants v01r03

KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04

KDB 865664 D02 RF Exposure Reporting v01r02

KDB 941225 D01 3G SAR Procedures v03r01

KDB 941225 D05 SAR for LTE Devices v02r05

KDB 941225 D05A LTE Rel.10 KDB Inquiry Sheet v01r02

KDB 941225 D06 Hotspot Mode v02r01

5 Operational Conditions during Test

5.3 Test Positions

5.3.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2013 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.3.2 Body Worn Configuration

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

5.3.3 Phablet SAR test considerations

For smart phones, with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, that can provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets and support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance.

a) The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.

b) The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for product specific 10-g SAR according to the body-equivalent tissue dielectric parameters in KDB Publication 865664 D01 to address interactive hand use exposure conditions. The 1-g SAR at 5 mm for UMPC mini-tablets is not required. When hotspot mode applies, product specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold. The normal tablet procedures in KDB Publication 616217 are required when the overall diagonal dimension of the device is > 20.0 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Product specific 10-g SAR is also not required for the front (top) surface of larger form factor full size tablets. The more conservative normal tablet SAR results can be used to support phablet mode product specific 10-g SAR.

c) The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless modes and exposure conditions.

5.4 Measurement Variability

Per FCC KDB Publication 865664 D01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

5.5 Test Configuration

5.5.1 GSM Test Configuration

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Output power of reductions:

Table 2: The allowed power reduction in the multi-slot configuration

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power,(dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. GSM voice and GPRS data use GMSK, which is a constant amplitude modulation with minimal peak to average power difference within the time-slot burst. For EDGE, GMSK is used for MCS 1 – MCS 4 and 8-PSK is used for MCS 5 – MCS 9; where 8-PSK has an inherently higher peak-to-average power ratio. The GMSK and 8-PSK EDGE configurations are considered separately for SAR compliance. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

5.5.2 UMTS Test Configuration

5.5.2.1 3G SAR Test Reduction Procedure

The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations modes according to output power, exposure conditions and device operating capabilities. Maximum output power is verified by applying the applicable versions of 3GPP TS 34.121.

5.5.2.2 Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest SAR configuration in 12.2 kbps RMC for head exposure.

5.5.2.3 Body-worn accessory SAR

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits

configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the EUT with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the EUT, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC

5.5.2.4 Release 5 HSDPA Test Configuration

The 3G SAR test reduction procedure is applied to HSDPA body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices” section of this document, for the highest SAR body-worn accessory exposure configuration in 12.2 kbps RMC. EUT with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

HSDPA should be configured according to the UE category of a test device. The number of HSDSCH/ HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors(β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Table 3: Subtests for UMTS Release 5 HSDPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (note 1, note 2)	CM(dB) (note 3)	MPR(dB)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (note 4)	15/15 (note 4)	64	12/15 (note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ Note2: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. Note3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1,TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

5.5.2.5 Release 6 HSUPA Test Configuration

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices” section of this document, for the highest body-worn accessory exposure SAR configuration in 12.2 kbps RMC.

When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn accessory measurements is tested for next to the ear head exposure.

Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in Table 2 and other applicable procedures described in the 'WCDMA EUT and 'Release 5 HSDPA Data Devices' sections of this document

Table 4: Sub-Test 5 Setup for Release 6 HSUPA

Sub-set	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (⁽²⁾) (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} 47/15 β_{ed2} 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Figure 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Table 5: HSUPA UE category

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E- DCH TTI (ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00



Table 7.3.0.6: Report for UE Category 1 to 6				Report for UE Category 7		
6 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	11484	5.76
	4	4	10		20000	2.00
7 (No DPDCH)	4	8	2	2 SF2 & 2 SF4	22996	?
	4	4	10		20000	?
NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE Categories 1 to 6 supports QPSK only. UE Category 7 supports QPSK and 16QAM. (TS25.306-7.3.0)						

5.5.2.6 HSPA and DC-HSDPA Test Configuration

SAR test exclusion may apply to 3GPP Rel. 6 HSPA and Rel. 8 DC-HSDPA. When SAR measurement is required for HSPA or DC-HSDPA, a KDB inquiry is required to confirm that the wireless mode configurations in the test setup have remained stable throughout the SAR measurements. Without prior KDB confirmation to determine the SAR results are acceptable, a PAG is required for equipment approval.

SAR test exclusion for HSPA and DC-HSDPA is determined according to the following:

- 1) The HSPA procedures are applied to configure 3GPP Rel. 6 HSPA devices in the required sub-test mode(s) to determine SAR test exclusion.
- 2) SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.
- 3) Regardless of whether a PBA is required, the following information must be verified and included in the SAR report for devices supporting HSPA or DC-HSDPA:
 - a) The output power measurement results and applicable release version(s) of 3GPP TS 34.121.
 - i) Power measurement difficulties due to test equipment setup or availability must be resolved between the grantee and its test lab.
 - b) The power measurement results are in agreement with the individual device implementation and specifications. When Enhanced MPR (E-MPR) applies, the normal MPR targets may be modified according to the Cubic Metric (CM) measured by the device, which must be taken into consideration.
 - c) The UE category, operating parameters, such as the β and Δ values used to configure the device for testing, power setback procedures described in 3GPP TS 34.121 for the power measurements, and HSPA channel conditions (active and stable) for the entire duration of the measurement according to the required E-TFCI and AG index values.
- 4) When SAR measurement is required, the test configurations, procedures and power measurement results must be clearly described to confirm that the required test parameters are used, including E-TFCI and AG index stability and output power conditions.

Table 6: HS-DSCH UE category
Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI NOTE 1	Total number of soft channel bits	Supported modulations without MIMO operation or dual cell operation	Supported modulations with MIMO operation and without dual cell operation	Supported modulations with dual cell operation
Category 1	5	3	7298	19200	QPSK, 16QAM	Not applicable (MIMO not supported)	Not applicable (dual cell operation not supported)
Category 2	5	3	7298	28800			
Category 3	5	2	7298	28800			
Category 4	5	2	7298	38400			
Category 5	5	1	7298	57600			
Category 6	5	1	7298	67200			
Category 7	10	1	14411	115200			
Category 8	10	1	14411	134400			
Category 9	15	1	20251	172800			
Category 10	15	1	27952	172800			
Category 11	5	2	3630	14400	QPSK		
Category 12	5	1	3630	28800	QPSK, 16QAM, 64QAM		
Category 13	15	1	35280	259200			
Category 14	15	1	42192	259200			
Category 15	15	1	23370	345600	QPSK, 16QAM		
Category 16	15	1	27952	345600			
Category 17 NOTE 2	15	1	35280	259200	QPSK, 16QAM, 64QAM	–	
			23370	345600	–	QPSK, 16QAM	
Category 18 NOTE 3	15	1	42192	259200	QPSK, 16QAM, 64QAM	–	
			27952	345600	–	QPSK, 16QAM	
Category 19	15	1	35280	518400	QPSK, 16QAM, 64QAM		
Category 20	15	1	42192	518400			
Category 21	15	1	23370	345600	-	-	QPSK, 16QAM
Category 22	15	1	27952	345600			
Category 23	15	1	35280	518400			
Category 24	15	1	42192	518400			

5.5.3 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer

target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

C)A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the *reported* SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

5.5.4 Wi-Fi Test Configuration

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the *initial test position(s)* by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The *initial test position(s)* is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the *reported SAR* for the *initial test position* is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the *initial test position* to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the *reported SAR* is ≤ 0.8 W/kg or all required test positions are tested.
 - ✧ For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - ✧ When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the *initial test position* and subsequent test positions, when the *reported SAR* is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the *reported SAR* is ≤ 1.2 W/kg or all required test channels are considered.
 - ✧ The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.


To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered the worst case position; thus used as the initial test position.

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

5.5.5 BT Test Configuration

For BT SAR testing, BT engineering testing software installed on the EUT can provide continuous transmitting RF signal with maximum output power. And the CBT control the EUT operating with hopping off and data rate set for DH5.

The SAR measurement takes full account of the BT duty cycle and is reflected in the report, and the duty factor of the device is as follow:



Note: Duty factor= Ton (ms)/ T(on+off) (ms)=2.884/3.752=76.9%

5.5.6 Dynamic antenna tuning description

The device supports the dynamic antenna switching function to optimize transmission efficiency for wide range frequency operations. It has two 2G/3G/4G TX antennas (Main Antenna and Secondary Antenna). It can transmit from either Main Antenna(Ant1) or Secondary Antenna(Ant 2). The Main Antenna(Ant1) support GSM850/1900, WCDMA B2/B4/B5 LTE B2/B4/B5/B7/B66 operating bands, and Secondary Antenna(Ant 2) support GSM850/1900, WCDMA B2/B4/B5 LTE B2/B4/B5/B7/B66 operating bands, only one antenna can be used for 2G/3G/4G transmission at a time.

5.5.7 Power Reduction Configuration

This device uses the receiver to indicate whether the user is making a call in head scenario or not. The selection between head and body power levels is based on the receiver detection mechanism. It can determine proximity to head or body and set the relevant power level for 2G&3G&4G and Wi-Fi antennas accordingly.



More details information followings:

Main antenna										
Power Reduction Scenario	GSM850	GSM1900	UMTS B2	UMTS B4	UMTS B5	LTE B2	LTE B4	LTE B5	LTE B7	LTE B66
1)Receiver on	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2)Receiver off	0.00	0.00	0.00	1.00	0.00	0.00	0.50	0.00	0.50	0.50
3)WiFi and LTE In-Device Coexistence	0.00	0.00	0.00	1.00	0.00	0.00	0.50	0.00	0.50	0.50
4)hotspot	0.00	0.00	2.00	3.00	0.00	2.00	0.00	0.00	2.50	0.00

Second antenna										
Power Reduction Scenario	GSM850	GSM1900	UMTS B2	UMTS B4	UMTS B5	LTE B2	LTE B4	LTE B5	LTE B7	LTE B66
1)Receiver on	1.00	0.00	1.80	1.50	3.80	1.00	1.50	3.25	6.50	1.00
2)Receiver off	0.00	0.00	0.50	1.00	0.00	0.00	0.50	0.00	4.50	0.00
3)WiFi and LTE In-Device Coexistence	1.50	0.00	1.80	2.50	1.50	1.50	2.00	1.50	6.00	1.50
4)hotspot	1.50	0.00	1.80	2.50	1.50	1.50	2.00	1.50	6.00	1.50

WiFi antenna				
Power Reduction Scenario	WiFi 2.4G 11b	WiFi 2.4G 11g	WiFi 2.4G 11n 20M	WiFi 2.4G 11n 40M
1)Receiver on	6.5	7.0	5.0	1.0
2)Receiver off	0.0	0.0	0.0	0.0

SAR test Plan

Table: Summary of Receiver detection mechanism

Antenna	Receiver on (head scenario)	Receiver off (Body/other scenario)
2G&3G&4G second ant	Power Level A1	Power Level B1
2G&3G&4G main ant	Power Level A2	Power Level B2
WiFi Ant	Power Level A3	Power Level B3

Based on the summary table of Receiver detection mechanism above,

For Head SAR test,

- 1) Standalone Head SAR of 2G&3G&4G second ant is evaluated at power level A1(Receiver on);
- 2) Standalone Head SAR of 2G&3G&4G Main ant is evaluated at power level A2(Receiver on);
- 3) Standalone Head SAR of WiFi ant is evaluated at power level A3(Receiver on);


For Body SAR test,

- 1) Standalone Body SAR of 2G&3G&4G second ant is evaluated at power level B1(Receiver off);
- 2) Standalone Body SAR of 2G&3G&4G Main ant is evaluated at power level B2(Receiver off);
- 3) Standalone Body SAR of WiFi ant is evaluated at power level B3 (Receiver off);

6 SAR Measurements System Configuration

6.1 SAR Measurement Set-up

The DASY system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.2 DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

EX3DV4 Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure Scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than ± 0.25 dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \Delta T / \Delta t$$

Where: Δt = Exposure time (30 seconds),
 C = Heat capacity of tissue (brain or muscle),
 ΔT = Temperature increase due to RF exposure.

Or

$$SAR = |E|^2 \sigma / \rho$$

Where: σ = Simulated tissue conductivity,
 ρ = Tissue density (kg/m^3).

6.3 SAR Measurement Procedure

Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤3GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{zoom}} \Delta y_{\text{zoom}}$			≤2GHz: ≤8mm 2 – 3GHz: ≤5mm*	3 – 4GHz: ≤5mm* 4 – 6GHz: ≤4mm*
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{\text{zoom}}(n)$		≤5mm	3 – 4GHz: ≤4mm 4 – 5GHz: ≤3mm 5 – 6GHz: ≤2mm
	Graded grid	$\Delta z_{\text{zoom}}(1)$: between 1 st two points closest to phantom surface	≤4mm	3 – 4GHz: ≤3mm 4 – 5GHz: ≤2.5mm 5 – 6GHz: ≤2mm
		$\Delta z_{\text{zoom}}(n>1)$: between subsequent points	≤1.5• $\Delta z_{\text{zoom}}(n-1)$	
Minimum zoom scan volume	X, y, z		≥30mm	3 – 4GHz: ≥28mm 4 – 5GHz: ≥25mm 5 – 6GHz: ≥22mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4W/kg, ≤8mm, ≤7mm and ≤5mm zoom scan resolution may be applied, respectively, for 2GHz to 3GHz, 3GHz to 4GHz and 4GHz to 6GHz.				

Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



7 Main Test Equipment

Name of Equipment	Manufacturer	Type/Model	Serial Number	Last Cal.	Cal. Due Date
Network analyzer	Agilent	E5071B	MY42404014	2020-05-17	2021-05-16
Dielectric Probe Kit	Agilent	85070E	US44020115	2020-05-17	2021-05-16
Power meter	Agilent	E4417A	GB41291714	2020-05-17	2021-05-16
Power sensor	Agilent	N8481H	MY50350004	2020-05-17	2021-05-16
Power sensor	Agilent	E9327A	US40441622	2020-05-17	2021-05-16
Signal Generator	Agilent	N5181A	MY50140143	2020-05-17	2021-05-16
Dual directional coupler	Agilent	778D-012	50519	/	/
Dual directional coupler	Agilent	777D	50146	/	/
Amplifier	INDEXSAR	IXA-020	0401	2020-05-17	2021-05-16
Wireless communication tester	Anritsu	MT8820C	6201342015	2020-05-17	2021-05-16
Wideband radio communication tester	R&S	CMW 500	113645	2020-05-17	2021-05-16
Base Station Simulator	R&S	CMW270	100673	2020-05-17	2021-05-16
E-field Probe	SPEAG	EX3DV4	3677	2020-07-06	2021-07-05
DAE	SPEAG	DAE4	1317	2019-10-23	2020-10-22
Validation Kit 835MHz	SPEAG	D835V2	4d020	2020-08-28	2023-08-27
Validation Kit 1750MHz	SPEAG	D1750V2	1033	2020-02-25	2023-02-24
Validation Kit 1900MHz	SPEAG	D1900V2	5d060	2020-08-27	2023-08-26
Validation Kit 2450MHz	SPEAG	D2450V2	786	2020-08-27	2023-08-26
Validation Kit 2600MHz	SPEAG	D2600V2	1025	2018-05-02	2021-05-01
Temperature Probe	Tianjin jinming	JM222	381	2020-05-25	2021-05-24
Hygrothermograph	Anymetr	NT-311	20150731	2020-05-17	2021-05-16
Twin SAM Phantom	Speag	SAM1	TP-1534	/	/
Software for Test	Speag	DASY52	/	/	/
Software for Tissue	Agilent	85070	/	/	/

8 Tissue Dielectric Parameter Measurements & System Verification

8.1 Tissue Verification

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 24 hours of use; or earlier if the dielectric parameters can become out of tolerance.

Target values

Frequency (MHz)	Water (%)	Salt (%)	Sugar (%)	Glycol (%)	Preventol (%)	Cellulose (%)	ϵ_r	$\sigma(\text{s/m})$
835	41.45	1.45	56	0	0.1	1.0	41.5	0.90
1750	55.24	0.31	0	44.45	0	0	40.1	1.37
1900	55.242	0.306	0	44.452	0	0	40.0	1.40
2450	62.7	0.5	0	36.8	0	0	39.2	1.80
2600	55.242	0.306	0	44.452	0	0	39.0	1.96

Measurements results


Frequency (MHz)	Test Date	Temp $^\circ\text{C}$	Measured Dielectric Parameters		Target Dielectric Parameters		Limit (Within $\pm 5\%$)	
			ϵ_r	$\sigma(\text{s/m})$	ϵ_r	$\sigma(\text{s/m})$	Dev $\epsilon_r(\%)$	Dev $\sigma(\%)$
835	9/13/2020	21.5	41.4	0.88	41.5	0.90	-0.24	-2.22
	9/15/2020	21.5	41.3	0.87	41.5	0.90	-0.48	-3.33
	9/18/2020	21.5	41.4	0.92	41.5	0.90	-0.24	2.22
1750	9/12/2020	21.5	40.2	1.34	40.1	1.37	0.25	-2.19
	9/14/2020	21.5	40.1	1.34	40.1	1.37	0.00	-2.19
	9/16/2020	21.5	40.2	1.36	40.1	1.37	0.25	-0.73
	9/19/2020	21.5	40.5	1.38	40.1	1.37	1.00	0.73
1900	9/9/2020	21.5	40.2	1.42	40.0	1.40	0.50	1.43
	9/10/2020	21.5	40.1	1.41	40.0	1.40	0.25	0.71
	9/11/2020	21.5	40.2	1.43	40.0	1.40	0.50	2.14
2450	9/12/2020	21.5	38.6	1.81	39.2	1.80	-1.53	0.56
2600	9/17/2020	21.5	38.2	2.01	39.0	1.96	-2.05	2.55
	9/18/2020	21.5	38.4	1.94	39.0	1.96	-1.54	-1.02

Note: The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.

8.2 System Performance Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured using the dielectric probe kit and the network analyzer. A system check measurement for every day was made following the determination of the dielectric parameters of the Tissue simulates, using the dipole validation kit. The dipole antenna was placed under the flat section of the twin SAM phantom.

System check is performed regularly on all frequency bands where tests are performed with the DASY system.



Picture 1 System Performance Check setup



Picture 2 Setup Photo

**Justification for Extended SAR Dipole Calibrations**

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB 865664 D01:

Dipole		Date of Measurement	Return Loss(dB)	Δ %	Impedance (Ω)	$\Delta\Omega$
Dipole D2600V2 SN: 1025	Head Liquid	5/2/2018	-22.0	/	48.1	/
		5/1/2019	-22.5	-2.2	48.7	-0.6

System Check results

Frequency (MHz)	Test Date	Temp °C	250mW Measured SAR _{1g} (W/kg)	1W Normalized SAR _{1g} (W/kg)	1W Target SAR _{1g} (W/kg)	Δ % (Limit $\pm 10\%$)	Plot No.
835	9/13/2020	21.5	2.44	9.76	9.65	1.14	1
	9/15/2020	21.5	2.46	9.84	9.65	1.97	2
	9/18/2020	21.5	2.43	9.72	9.65	0.73	3
1750	9/12/2020	21.5	8.95	35.80	35.90	-0.28	4
	9/14/2020	21.5	9.11	36.44	35.90	1.50	5
	9/16/2020	21.5	8.96	35.84	35.90	-0.17	6
	9/19/2020	21.5	8.92	35.68	35.90	-0.61	7
1900	9/9/2020	21.5	10.55	42.20	39.50	6.84	8
	9/10/2020	21.5	9.88	39.52	39.50	0.05	9
	9/11/2020	21.5	9.85	39.40	39.50	-0.25	10
2450	9/12/2020	21.5	13.70	54.80	52.30	4.78	11
2600	9/17/2020	21.5	13.90	55.60	54.10	2.77	12
	9/18/2020	21.5	13.88	55.52	54.10	2.62	13
Note: Target Values used derive from the calibration certificate Data Storage and Evaluation.							

8.3 SAR System Validation

Per FCC KDB 865664 D02v01, SAR system verification is required to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles are used with the required tissue-equivalent media for system validation, according to the procedures outlined in FCC KDB 865664 D01 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point must be validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

a tabulated summary of the system validation status, measurement frequencies, SAR probes, calibrated signal type(s) and tissue dielectric parameters has been included.

Frequency [MHz]	Date	Probe SN	Probe Type	Probe Cal Point		PERM (Er)	COND (Σ)	CW Validation			Mod. Validation		
								Sensitivity	Probe Linearity	Probe Isotropy	Mod. Type	Duty Factor	PAR
750	8/4/2020	3677	EX3DV4	750	Head	42.81	0.85	PASS	PASS	PASS	FDD	PASS	N/A
835	8/4/2020	3677	EX3DV4	835	Head	42.22	0.90	PASS	PASS	PASS	GMSK	PASS	N/A
1750	8/4/2020	3677	EX3DV4	1750	Head	39.91	1.32	PASS	PASS	PASS	NA	N/A	N/A
1900	8/4/2020	3677	EX3DV4	1900	Head	39.43	1.42	PASS	PASS	PASS	GMSK	PASS	N/A
2450	8/4/2020	3677	EX3DV4	2450	Head	38.19	1.83	PASS	PASS	PASS	OFDM	PASS	PASS
2600	8/4/2020	3677	EX3DV4	2600	Head	37.60	1.99	PASS	PASS	PASS	TDD	PASS	N/A
5250	8/4/2020	3677	EX3DV4	5250	Head	35.36	4.83	PASS	PASS	PASS	OFDM	N/A	PASS
5600	8/4/2020	3677	EX3DV4	5600	Head	34.43	5.29	PASS	PASS	PASS	OFDM	N/A	PASS
5750	8/4/2020	3677	EX3DV4	5750	Head	34.07	5.47	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664D01v01 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5dB), such as OFDM according to KDB 865664.



9 Normal and Maximum Output Power

KDB 447498 D01 at the maximum rated output power and within the tune-up tolerance range specified for the product, but not more than 2 dB lower than the maximum tune-up tolerance limit.

9.1 GSM Mode

Main- Antenna

GSM 850 Receiver on/Receiver off/hotspot/Receiver off- Simultaneous with Wi-Fi		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	128 /824.2	190 /836.6	251 /848.8		MAX	128 /824.2	190 /836.6	251 /848.8
GSM	CS	33.50	32.32	32.53	32.37	9.03	24.47	23.29	23.50	23.34
GPRS/ EGPRS (GMSK)	1 Tx Slot	33.40	32.22	32.42	32.37	9.03	24.37	23.19	23.39	23.34
	2 Tx Slots	30.40	29.55	29.65	29.60	6.02	24.38	23.53	23.63	23.58
	3 Tx Slots	28.60	27.73	27.80	27.77	4.26	24.34	23.47	23.54	23.51
	4 Tx Slots	27.40	26.63	26.67	26.62	3.01	24.39	23.62	23.66	23.61
EGPRS (8PSK)	1 Tx Slot	27.20	26.39	26.25	26.14	9.03	18.17	17.36	17.22	17.11
	2 Tx Slots	24.10	23.28	23.35	23.25	6.02	18.08	17.26	17.33	17.23
	3 Tx Slots	22.20	21.49	21.47	21.42	4.26	17.94	17.23	17.21	17.16
	4 Tx Slots	20.80	20.05	20.15	20.00	3.01	17.79	17.04	17.14	16.99
GSM 1900 Receiver on/Receiver off/hotspot/Receiver off- Simultaneous with Wi-Fi		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	512 /1850.2	661 /1880	810 /1909.8		MAX	512 /1850.2	661 /1880	810 /1909.8
GSM	CS	31.00	30.58	30.14	29.96	9.03	21.97	21.55	21.11	20.93
GPRS/ EGPRS (GMSK)	1 Tx Slot	31.00	30.57	30.23	30.31	9.03	21.97	21.54	21.20	21.28
	2 Tx Slots	27.80	27.45	27.04	27.21	6.02	21.78	21.43	21.02	21.19
	3 Tx Slots	26.10	25.41	25.20	25.32	4.26	21.84	21.15	20.94	21.06
	4 Tx Slots	24.90	24.10	24.02	24.00	3.01	21.89	21.09	21.01	20.99
EGPRS (8PSK)	1 Tx Slot	26.60	26.01	26.10	25.98	9.03	17.57	16.98	17.07	16.95
	2 Tx Slots	23.30	22.60	22.74	22.65	6.02	17.28	16.58	16.72	16.63
	3 Tx Slots	21.20	20.61	20.56	20.50	4.26	16.94	16.35	16.30	16.24
	4 Tx Slots	19.90	19.30	19.37	19.22	3.01	16.89	16.29	16.36	16.21

Notes: The worst-case configuration and mode for SAR testing is determined to be as follows:

1. Standalone: GSM 850 GMSK (GPRS) mode with 4 time slots for Max power, GSM 1900 GMSK (GPRS) mode with 1 time slots for Max power, based on the output power measurements above.

**Second – Antenna**

GSM 850 Receiver off		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	128 /824.2	190 /836.6	251 /848.8		MAX	128 /824.2	190 /836.6	251 /848.8
GSM	CS	33.40	31.88	32.16	32.21	9.03	24.37	22.85	23.13	23.18
GPRS/ EGPRS (GMSK)	1 Tx Slot	33.40	31.95	32.25	32.29	9.03	24.37	22.92	23.22	23.26
	2 Tx Slots	30.40	29.53	29.67	29.67	6.02	24.38	23.51	23.65	23.65
	3 Tx Slots	28.60	27.75	27.86	27.84	4.26	24.34	23.49	23.60	23.58
	4 Tx Slots	27.40	26.64	26.72	26.71	3.01	24.39	23.63	23.71	23.70
EGPRS (8PSK)	1 Tx Slot	27.20	26.31	26.43	26.37	9.03	18.17	17.28	17.40	17.34
	2 Tx Slots	24.20	23.42	23.53	23.46	6.02	18.18	17.40	17.51	17.44
	3 Tx Slots	22.30	22.00	22.13	22.09	4.26	18.04	17.74	17.87	17.83
	4 Tx Slots	20.90	20.28	20.39	20.34	3.01	17.89	17.27	17.38	17.33
GSM 1900 Receiver on/Receiver off/hotspot/Receiver off - Simultaneous with Wi-Fi		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	512 /1850.2	661 /1880	810 /1909.8		MAX	512 /1850.2	661 /1880	810 /1909.8
GSM	CS	30.40	29.95	29.78	29.94	9.03	21.37	20.92	20.75	20.91
GPRS/ EGPRS (GMSK)	1 Tx Slot	30.40	30.06	29.90	30.06	9.03	21.37	21.03	20.87	21.03
	2 Tx Slots	27.50	26.89	26.58	26.94	6.02	21.48	20.87	20.56	20.92
	3 Tx Slots	25.70	25.04	24.72	25.09	4.26	21.44	20.78	20.46	20.83
	4 Tx Slots	24.50	23.81	23.54	23.85	3.01	21.49	20.80	20.53	20.84
EGPRS (8PSK)	1 Tx Slot	26.00	25.55	25.50	25.39	9.03	16.97	16.52	16.47	16.36
	2 Tx Slots	22.70	22.20	22.26	22.18	6.02	16.68	16.18	16.24	16.16
	3 Tx Slots	20.60	19.95	20.09	20.00	4.26	16.34	15.69	15.83	15.74
	4 Tx Slots	19.30	18.45	18.56	18.50	3.01	16.29	15.44	15.55	15.49

Notes: The worst-case configuration and mode for SAR testing is determined to be as follows:

1. Standalone: GSM 850 GMSK (GPRS) mode with 4 time slots for Max power, GSM 1900 GMSK (GPRS) mode with 4 time slots for Max power, based on the output power measurements above.

GSM 850 Receiver on		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	128 /824.2	190 /836.6	251 /848.8		MAX	128 /824.2	190 /836.6	251 /848.8
GSM	CS	32.40	31.28	31.47	31.55	9.03	23.37	22.25	22.44	22.52
GPRS/ EGPRS (GMSK)	1 Tx Slot	32.40	31.20	31.40	31.49	9.03	23.37	22.17	22.37	22.46
	2 Tx Slots	29.40	28.58	28.71	28.71	6.02	23.38	22.56	22.69	22.69
	3 Tx Slots	27.60	27.46	26.94	26.93	4.26	23.34	23.20	22.68	22.67
	4 Tx Slots	26.40	25.65	25.75	25.74	3.01	23.39	22.64	22.74	22.73
EGPRS (8PSK)	1 Tx Slot	26.20	25.55	25.64	25.50	9.03	17.17	16.52	16.61	16.47
	2 Tx Slots	23.20	22.60	22.72	22.68	6.02	17.18	16.58	16.70	16.66
	3 Tx Slots	21.70	20.81	20.93	20.85	4.26	17.44	16.55	16.67	16.59
	4 Tx Slots	20.50	19.62	19.69	19.53	3.01	17.49	16.61	16.68	16.52
GSM 850 hotspot/Receiver off- Simultaneous with Wi-Fi		Burst-Averaged output power(dBm)				Division Factors	Frame-Averaged output power(dBm)			
		Tune-up	Channel/Frenqucy(MHz)				Tune-up	Channel/Frenqucy(MHz)		
		MAX	128 /824.2	190 /836.6	251 /848.8		MAX	128 /824.2	190 /836.6	251 /848.8
GSM	CS	31.90	30.87	31.06	31.10	9.03	22.87	21.84	22.03	22.07
GPRS/ EGPRS (GMSK)	1 Tx Slot	31.90	30.89	31.05	31.12	9.03	22.87	21.86	22.02	22.09
	2 Tx Slots	28.90	28.07	28.18	28.18	6.02	22.88	22.05	22.16	22.16
	3 Tx Slots	27.10	26.34	26.48	26.47	4.26	22.84	22.08	22.22	22.21
	4 Tx Slots	25.90	25.20	25.25	25.24	3.01	22.89	22.19	22.24	22.23
EGPRS (8PSK)	1 Tx Slot	25.70	24.94	25.06	25.00	9.03	16.67	15.91	16.03	15.97
	2 Tx Slots	22.70	22.18	22.25	22.20	6.02	16.68	16.16	16.23	16.18
	3 Tx Slots	20.70	19.95	20.09	20.04	4.26	16.44	15.69	15.83	15.78
	4 Tx Slots	19.50	19.01	19.10	18.95	3.01	16.49	16.00	16.09	15.94
Notes:The worst-case configuration and mode for SAR testing is determined to be as follows: 1. Standalone: GSM 850 GMSK (GPRS) mode with 4 time slots for Max power.										

9.2 WCDMA Mode

The following tests were completed according to the test requirements outlined in the 3GPP TS34.121 specification.

Main- Antenna

WCDMA		Band II(dBm) Receiver on/Receiver off/Receiver off- Simultaneous with Wi-Fi				Band IV(dBm) Receiver off/Receiver off- Simultaneous with Wi-Fi				Band V(dBm) Receiver on/Receiver off/hotspot/Receiver off- Simultaneous with Wi-Fi			
Tx Channel		9262	9400	9538	Tune-up	1312	1413	1513	Tune-up	4132	4183	4233	Tune-up
Frequency(MHz)		1852.4	1880	1907.6	Limit	1712.4	1732.6	1752.6	Limit	826.4	836.6	846.6	Limit
RMC	12.2kbps	24.25	24.09	23.81	25.00	23.11	23.40	23.41	24.00	24.31	24.16	24.12	25.00
AMR	12.2kbps	24.15	24.00	23.68	25.00	23.01	23.31	23.28	24.00	24.21	24.07	23.99	25.00
HSDPA	Sub 1	23.67	23.51	23.23	24.50	22.53	22.82	22.83	23.50	23.73	23.58	23.54	24.50
	Sub 2	22.86	22.70	22.42	23.70	21.62	21.91	21.92	22.60	23.22	23.07	23.03	24.00
	Sub 3	22.35	22.19	21.91	23.20	21.11	21.40	21.41	22.10	22.81	22.66	22.62	23.60
	Sub 4	22.34	22.18	21.90	23.20	21.10	21.39	21.40	22.10	22.80	22.65	22.61	23.60
HSUPA	Sub 1	22.53	22.37	22.09	23.40	21.19	21.48	21.49	22.20	23.39	23.24	23.20	24.20
	Sub 2	19.82	19.66	19.38	20.70	18.38	18.67	18.68	19.40	20.48	20.33	20.29	21.30
	Sub 3	20.40	20.25	19.97	21.30	20.16	20.46	20.47	21.20	22.26	22.12	22.08	23.10
	Sub 4	20.39	20.24	19.96	21.30	19.15	19.45	19.46	20.20	21.15	21.01	20.97	22.00
	Sub 5	22.78	22.63	22.35	23.70	21.64	21.94	21.95	22.70	22.84	22.70	22.66	23.70
DC-HSDPA	Sub 1	23.59	23.45	23.15	24.50	22.45	22.76	22.75	23.50	23.65	23.52	23.46	24.50
	Sub 2	22.78	22.64	22.34	23.70	21.54	21.85	21.84	22.60	23.14	23.01	22.95	24.00
	Sub 3	22.36	22.13	21.85	23.20	21.12	21.34	21.35	22.10	22.82	22.60	22.56	23.60
	Sub 4	22.35	22.12	21.84	23.20	21.11	21.33	21.34	22.10	22.81	22.59	22.55	23.60

Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".



WCDMA		Band II(dBm) Hotspot				Band IV(dBm) Receiver on			
Tx Channel		9262	9400	9538	Tune-up	1312	1413	1513	Tune-up
Frequency(MHz)		1852.4	1880	1907.6	Limit	1712.4	1732.6	1752.6	Limit
RMC	12.2kbps	22.23	22.10	21.96	23.00	24.09	24.39	24.20	25.00
AMR	12.2kbps	22.13	22.01	21.83	23.00	23.99	24.30	24.07	25.00
HSDPA	Sub 1	21.65	21.52	21.38	22.50	23.51	23.81	23.62	24.50
	Sub 2	20.84	20.71	20.57	21.70	22.60	22.90	22.71	23.60
	Sub 3	20.33	20.20	20.06	21.20	22.09	22.39	22.20	23.10
	Sub 4	20.32	20.19	20.05	21.20	22.08	22.38	22.19	23.10
HSUPA	Sub 1	20.51	20.38	20.24	21.40	22.17	22.47	22.28	23.20
	Sub 2	17.80	17.67	17.53	18.70	19.36	19.66	19.47	20.40
	Sub 3	18.38	18.26	18.12	19.30	21.14	21.45	21.26	22.20
	Sub 4	18.37	18.25	18.11	19.30	20.03	20.34	20.15	21.10
	Sub 5	20.76	20.64	20.50	21.70	22.62	22.93	22.74	23.70
DC-HSDPA	Sub 1	21.57	21.46	21.30	22.50	23.43	23.75	23.54	24.50
	Sub 2	20.76	20.65	20.49	21.70	22.52	22.84	22.63	23.60
	Sub 3	20.34	20.14	20.00	21.20	22.10	22.33	22.14	23.10
	Sub 4	20.33	20.13	19.99	21.20	22.09	22.32	22.13	23.10
Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".									



WCDMA		Band IV(dBm) Hotspot			
Tx Channel		1312	1413	1513	Tune-up Limit
Frequency(MHz)		1712.4	1732.6	1752.6	
RMC	12.2kbps	21.09	21.40	21.22	22.00
AMR	12.2kbps	20.99	21.31	21.09	22.00
HSDPA	Sub 1	20.51	20.82	20.64	21.50
	Sub 2	19.60	19.91	19.73	20.60
	Sub 3	19.09	19.40	19.22	20.10
	Sub 4	19.08	19.39	19.21	20.10
HSUPA	Sub 1	19.17	19.48	19.30	20.20
	Sub 2	16.36	16.67	16.49	17.40
	Sub 3	18.14	18.46	18.28	19.20
	Sub 4	16.93	17.25	17.07	18.00
	Sub 5	19.62	19.94	19.76	20.70
DC-HSDPA	Sub 1	20.43	20.76	20.56	21.50
	Sub 2	19.52	19.85	19.65	20.60
	Sub 3	19.10	19.34	19.16	20.10
	Sub 4	19.09	19.33	19.15	20.10
Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".					

**Second - Antenna**

WCDMA		Band II(dBm) Receiver off				Band IV(dBm) Receiver off				Band V(dBm) Receiver off			
Tx Channel		9262	9400	9538	Tune-up	1312	1413	1513	Tune-up	4132	4183	4233	Tune-up
Frequency(MHz)		1852.4	1880	1907.6	Limit	1712.4	1732.6	1752.6	Limit	826.4	836.6	846.6	Limit
RMC	12.2kbps	23.70	23.59	23.55	23.90	22.57	22.80	22.51	23.30	24.18	24.05	24.06	25.20
AMR	12.2kbps	23.60	23.50	23.42	23.90	22.47	22.71	22.38	23.30	24.08	23.96	23.93	25.20
HSDPA	Sub 1	23.12	23.01	22.97	23.40	22.09	22.32	22.03	22.90	23.70	23.57	23.58	24.80
	Sub 2	22.31	22.20	22.16	22.60	21.18	21.41	21.12	22.00	23.19	23.06	23.07	24.30
	Sub 3	21.80	21.69	21.65	22.10	20.67	20.90	20.61	21.50	22.78	22.65	22.66	23.90
	Sub 4	21.79	21.68	21.64	22.10	20.66	20.89	20.60	21.50	22.77	22.64	22.65	23.90
HSUPA	Sub 1	21.98	21.87	21.83	22.30	20.75	20.98	20.69	21.60	23.06	22.93	22.94	24.20
	Sub 2	19.27	19.16	19.12	19.60	17.94	18.17	17.88	18.80	21.15	21.02	21.03	22.30
	Sub 3	19.85	19.75	19.71	20.20	19.72	19.96	19.67	20.60	22.03	21.91	21.92	23.20
	Sub 4	19.84	19.74	19.70	20.20	18.51	18.75	18.46	19.40	20.02	19.90	19.91	21.20
	Sub 5	22.23	22.13	22.09	22.60	21.20	21.44	21.15	22.10	22.81	22.69	22.70	24.00
DC-HSDPA	Sub 1	23.04	22.95	22.89	23.40	22.01	22.26	21.95	22.90	23.62	23.51	23.50	24.80
	Sub 2	22.23	22.14	22.08	22.60	21.20	21.45	21.14	22.10	23.11	23.00	22.99	24.30
	Sub 3	21.81	21.63	21.59	22.10	20.68	20.84	20.55	21.50	22.79	22.59	22.60	23.90
	Sub 4	21.80	21.62	21.58	22.10	20.67	20.83	20.54	21.50	22.78	22.58	22.59	23.90

Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".



WCDMA		Band II(dBm) Receiver on/hotspot/Receiver off- Simultaneous with Wi-Fi				Band IV(dBm) Receiver on				Band V(dBm) Receiver on			
Tx Channel		9262	9400	9538	Tune-up	1312	1413	1513	Tune-up	4132	4183	4233	Tune-up
Frequency(MHz)		1852.4	1880	1907.6	Limit	1712.4	1732.6	1752.6	Limit	826.4	836.6	846.6	Limit
RMC	12.2kbps	22.21	22.10	22.05	22.40	22.06	22.30	22.03	22.80	20.35	20.33	20.31	21.40
AMR	12.2kbps	22.11	22.01	21.92	22.40	21.96	22.21	21.90	22.80	20.25	20.24	20.18	21.40
HSDPA	Sub 1	21.63	21.52	21.47	21.90	21.58	21.82	21.55	22.40	19.87	19.85	19.83	21.00
	Sub 2	20.82	20.71	20.66	21.10	20.67	20.91	20.64	21.50	19.36	19.34	19.32	20.50
	Sub 3	20.31	20.20	20.15	20.60	20.16	20.40	20.13	21.00	19.95	19.93	19.91	21.10
	Sub 4	20.30	20.19	20.14	20.60	20.15	20.39	20.12	21.00	18.94	18.92	18.90	20.10
HSUPA	Sub 1	20.49	20.38	20.33	20.80	20.24	20.48	20.21	21.10	19.23	19.21	19.19	20.40
	Sub 2	17.78	17.67	17.62	18.10	17.43	17.67	17.40	18.30	17.32	17.30	17.28	18.50
	Sub 3	18.36	18.26	18.21	18.70	19.21	19.46	19.19	20.10	18.20	18.19	18.17	19.40
	Sub 4	18.35	18.25	18.20	18.70	18.00	18.25	17.98	18.90	16.19	16.18	16.16	17.40
	Sub 5	20.74	20.64	20.59	21.10	20.69	20.94	20.67	21.60	18.98	18.97	18.95	20.20
DC-HSDPA	Sub 1	21.55	21.46	21.39	21.90	21.50	21.76	21.47	22.40	19.79	19.79	19.75	21.00
	Sub 2	20.74	20.65	20.58	21.10	20.59	20.85	20.56	21.50	19.28	19.28	19.24	20.50
	Sub 3	20.32	20.14	20.09	20.60	20.17	20.34	20.07	21.00	18.96	18.87	18.85	20.10
	Sub 4	20.31	20.13	20.08	20.60	20.16	20.33	20.06	21.00	18.95	18.86	18.84	20.10

Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".

WCDMA		Band IV(dBm) hotspot/Receiver off- Simultaneous with Wi-Fi				Band V(dBm) hotspot/Receiver off- Simultaneous with Wi-Fi			
Tx Channel		1312	1413	1513	Tune-up	4132	4183	4233	Tune-up
Frequency(MHz)		1712.4	1732.6	1752.6	Limit	826.4	836.6	846.6	Limit
RMC	12.2kbps	20.55	20.80	20.51	21.80	22.68	22.55	22.53	23.70
AMR	12.2kbps	20.45	20.71	20.38	21.80	22.58	22.46	22.40	23.70
HSDPA	Sub 1	20.07	20.32	20.03	21.40	22.20	22.07	22.05	23.30
	Sub 2	19.16	19.41	19.12	20.50	21.69	21.56	21.54	22.80
	Sub 3	18.65	18.90	18.61	20.00	21.28	21.15	21.13	22.40
	Sub 4	18.64	18.89	18.60	20.00	21.27	21.14	21.12	22.40
HSUPA	Sub 1	18.73	18.98	18.69	20.10	21.56	21.43	21.41	22.70
	Sub 2	15.92	16.17	15.88	17.30	19.65	19.52	19.50	20.80
	Sub 3	17.70	17.96	17.67	19.10	20.53	20.41	20.39	21.70
	Sub 4	16.49	16.75	16.46	17.90	18.52	18.40	18.38	19.70
	Sub 5	19.18	19.44	19.15	20.60	21.31	21.19	21.17	22.50
DC-HSDPA	Sub 1	19.99	20.26	19.95	21.40	22.12	22.01	21.97	23.30
	Sub 2	19.08	19.35	19.04	20.50	21.61	21.50	21.46	22.80
	Sub 3	18.66	18.84	18.55	20.00	21.29	21.09	21.07	22.40
	Sub 4	18.65	18.83	18.54	20.00	21.28	21.08	21.06	22.40
Note: 1.Per KDB 941225 D01, SAR for each exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".									

9.3 LTE Mode

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

Main- Antenna

LTE FDD Band 2 Receiver on/Receiver off/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				18607/1850.7	18900/1880	19193/1909.3	
1.4MHz	QPSK	1	0	23.58	23.40	23.24	24.50
		1	2	23.93	23.89	22.81	24.50
		1	5	23.18	23.30	23.06	24.50
		3	0	23.38	23.18	23.07	24.50
		3	2	23.24	23.21	23.10	24.50
		3	3	23.20	23.17	23.07	24.50
		6	0	22.38	22.26	22.11	23.50
	16QAM	1	0	22.44	22.82	22.87	23.50
		1	2	22.42	22.17	22.17	23.50
		1	5	22.68	22.56	22.61	23.50
		3	0	22.21	22.05	22.11	23.50
		3	2	22.19	22.06	22.11	23.50
		3	3	22.17	22.06	22.10	23.50
		6	0	21.21	21.12	21.17	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18615/1851.5	18900/1880	19185/1908.5	
3MHz	QPSK	1	0	23.60	23.44	23.27	24.50
		1	7	23.91	23.92	22.85	24.50
		1	14	23.21	23.35	23.10	24.50
		8	0	22.48	22.30	22.20	23.50
		8	4	22.36	22.31	22.22	23.50
		8	7	22.30	22.28	22.17	23.50
		15	0	22.38	22.30	22.14	23.50
	16QAM	1	0	22.47	22.84	22.90	23.50
		1	7	22.45	22.17	22.21	23.50



		1	14	22.70	22.60	22.64	23.50
		8	0	21.32	21.18	21.23	22.50
		8	4	21.30	21.19	21.23	22.50
		8	7	21.27	21.18	21.23	22.50
		15	0	21.24	21.16	21.20	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18625/1852.5	18900/1880	19175/1907.5	
5MHz	QPSK	1	0	23.57	23.42	23.23	24.50
		1	13	23.89	23.88	22.82	24.50
		1	24	23.18	23.30	23.06	24.50
		12	0	22.45	22.25	22.16	23.50
		12	6	22.34	22.27	22.17	23.50
		12	13	22.28	22.26	22.13	23.50
		25	0	22.38	22.29	22.12	23.50
	16QAM	1	0	22.44	22.80	22.87	23.50
		1	13	22.42	22.15	22.18	23.50
		1	24	22.67	22.58	22.60	23.50
		12	0	21.30	21.14	21.20	22.50
		12	6	21.27	21.14	21.19	22.50
		12	13	21.24	21.13	21.19	22.50
		25	0	21.22	21.12	21.15	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18650/1855	18900/1880	19150/1905	
10MHz	QPSK	1	0	23.59	23.43	23.26	24.50
		1	25	23.92	23.93	22.86	24.50
		1	49	23.20	23.34	23.09	24.50
		25	0	22.48	22.30	22.20	23.50
		25	13	22.37	22.32	22.21	23.50
		25	25	22.30	22.30	22.18	23.50
		50	0	22.42	22.31	22.16	23.50
	16QAM	1	0	22.46	22.83	22.89	23.50
		1	25	22.45	22.19	22.21	23.50
		1	49	22.70	22.60	22.63	23.50
		25	0	21.33	21.19	21.24	22.50
		25	13	21.29	21.18	21.22	22.50
		25	25	21.27	21.18	21.23	22.50
		50	0	21.25	21.17	21.19	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18675/1857.5	18900/1880	19125/1902.5	
15MHz	QPSK	1	0	23.58	23.39	23.24	24.50
		1	38	23.90	23.92	22.83	24.50
		1	74	23.17	23.29	23.05	24.50
		36	0	22.46	22.26	22.17	23.50



		36	18	22.34	22.27	22.17	23.50
		36	39	22.27	22.27	22.14	23.50
		75	0	22.40	22.27	22.11	23.50
	16QAM	1	0	22.41	22.81	22.87	23.50
		1	38	22.43	22.16	22.19	23.50
		1	74	22.67	22.56	22.60	23.50
		36	0	21.30	21.17	21.21	22.50
		36	18	21.26	21.13	21.18	22.50
		36	39	21.25	21.14	21.20	22.50
		75	0	21.22	21.12	21.15	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18700/1860	18900/1880	19100/1900	
20MHz	QPSK	1	0	23.55	23.35	23.21	24.50
		1	50	23.89	23.88	22.81	24.50
		1	99	23.15	23.28	23.02	24.50
		50	0	22.43	22.21	22.13	23.50
		50	25	22.32	22.23	22.14	23.50
		50	50	22.24	22.22	22.10	23.50
		100	0	22.37	22.22	22.07	23.50
	16QAM	1	0	22.91	22.77	22.82	23.50
		1	50	22.39	22.14	22.15	23.50
		1	99	22.65	22.53	22.58	23.50
		50	0	21.27	21.13	21.18	22.50
		50	25	21.23	21.11	21.15	22.50
		50	50	21.22	21.09	21.16	22.50
		100	0	21.20	21.08	21.12	22.50

LTE FDD Band 2 Hotspot				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				18607/1850.7	18900/1880	19193/1909.3	
1.4MHz	QPSK	1	0	21.59	21.23	21.14	22.50
		1	2	21.12	20.91	21.12	22.50
		1	5	21.14	21.19	21.13	22.50
		3	0	21.36	21.08	21.10	22.50
		3	2	21.35	21.00	21.15	22.50
		3	3	21.28	21.06	21.13	22.50
		6	0	21.17	21.07	21.09	22.50
	16QAM	1	0	21.87	21.73	21.54	22.50
		1	2	21.65	21.07	21.35	22.50
		1	5	21.54	21.67	21.39	22.50
		3	0	21.33	21.06	21.13	22.50
		3	2	21.22	20.99	21.11	22.50



		3	3	21.16	21.04	21.00	22.50
		6	0	21.15	21.02	21.27	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18615/1851.5	18900/1880	19185/1908.5	
3MHz	QPSK	1	0	21.61	21.27	21.17	22.50
		1	7	21.12	20.93	21.16	22.50
		1	14	21.17	21.24	21.17	22.50
		8	0	21.40	21.15	21.17	22.50
		8	4	21.38	21.08	21.21	22.50
		8	7	21.32	21.11	21.17	22.50
		15	0	21.19	21.11	21.12	22.50
	16QAM	1	0	21.90	21.75	21.57	22.50
		1	7	21.68	21.09	21.39	22.50
		1	14	21.56	21.71	21.42	22.50
		8	0	21.38	21.10	21.16	22.50
		8	4	21.27	21.06	21.17	22.50
		8	7	21.20	21.10	21.07	22.50
		15	0	21.18	21.06	21.30	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18625/1852.5	18900/1880	19175/1907.5	
5MHz	QPSK	1	0	21.58	21.25	21.13	22.50
		1	13	21.10	20.89	21.13	22.50
		1	24	21.14	21.19	21.13	22.50
		12	0	21.37	21.10	21.13	22.50
		12	6	21.36	21.04	21.16	22.50
		12	13	21.30	21.09	21.13	22.50
		25	0	21.17	21.10	21.10	22.50
	16QAM	1	0	21.87	21.71	21.54	22.50
		1	13	21.65	21.07	21.36	22.50
		1	24	21.53	21.69	21.38	22.50
		12	0	21.36	21.06	21.13	22.50
		12	6	21.24	21.01	21.13	22.50
		12	13	21.17	21.05	21.03	22.50
		25	0	21.16	21.02	21.25	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18650/1855	18900/1880	19150/1905	
10MHz	QPSK	1	0	21.59	21.24	21.15	22.50
		1	25	21.11	20.93	21.15	22.50
		1	49	21.15	21.21	21.15	22.50
		25	0	21.38	21.14	21.15	22.50
		25	13	21.38	21.07	21.19	22.50
		25	25	21.30	21.09	21.17	22.50
		50	0	21.17	21.11	21.11	22.50



	16QAM	1	0	21.86	21.69	21.54	22.50
		1	25	21.67	21.10	21.34	22.50
		1	49	21.54	21.67	21.40	22.50
		25	0	21.34	21.10	21.14	22.50
		25	13	21.23	21.00	21.14	22.50
		25	25	21.19	21.09	21.02	22.50
		50	0	21.15	21.04	21.25	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18675/1857.5	18900/1880	19125/1902.5	
15MHz	QPSK	1	0	21.59	21.22	21.14	22.50
		1	38	21.11	20.93	21.14	22.50
		1	74	21.13	21.18	21.12	22.50
		36	0	21.38	21.11	21.14	22.50
		36	18	21.36	21.04	21.16	22.50
		36	39	21.29	21.10	21.14	22.50
		75	0	21.20	21.08	21.09	22.50
	16QAM	1	0	21.84	21.72	21.54	22.50
		1	38	21.66	21.08	21.37	22.50
		1	74	21.53	21.67	21.38	22.50
		36	0	21.36	21.09	21.14	22.50
		36	18	21.23	21.00	21.12	22.50
		36	39	21.18	21.06	21.04	22.50
		75	0	21.16	21.02	21.25	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18700/1860	18900/1880	19100/1900	
20MHz	QPSK	1	0	21.56	21.18	21.11	22.50
		1	50	21.10	20.89	21.12	22.50
		1	99	21.11	21.17	21.09	22.50
		50	0	21.35	21.06	21.10	22.50
		50	25	21.34	21.00	21.13	22.50
		50	50	21.26	21.05	21.10	22.50
		100	0	21.17	21.03	21.05	22.50
	16QAM	1	0	21.82	21.68	21.49	22.50
		1	50	21.62	21.06	21.33	22.50
		1	99	21.51	21.64	21.36	22.50
		50	0	21.33	21.05	21.11	22.50
		50	25	21.20	20.98	21.09	22.50
		50	50	21.15	21.01	21.00	22.50
		100	0	21.14	20.98	21.22	22.50

LTE FDD Band 4 Receiver off/Receiver off-	Output Power(dBm)	Tune-up Limit
--	-------------------	---------------



Simultaneous with Wi-Fi				Channel/Frequency (MHz)			
Bandwidth	Modulation	RB size	RB offset	19957/1710.7	20175/1732.5	20393/1754.3	
1.4MHz	QPSK	1	0	23.27	23.45	23.44	24.00
		1	2	23.05	23.14	23.18	24.00
		1	5	23.24	23.28	23.24	24.00
		3	0	23.66	23.71	23.82	24.00
		3	2	23.60	23.76	23.70	24.00
		3	3	23.66	23.68	23.61	24.00
		6	0	22.64	22.74	22.83	23.50
	16QAM	1	0	22.62	22.86	22.95	23.50
		1	2	22.60	22.51	22.54	23.50
		1	5	22.82	22.69	22.76	23.50
		3	0	22.88	22.68	22.78	23.50
		3	2	22.83	22.65	22.74	23.50
		3	3	22.83	22.71	22.74	23.50
		6	0	21.95	21.81	21.90	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19965/1711.5	20175/1732.5	20385/1753.5	
3MHz	QPSK	1	0	23.29	23.49	23.47	24.00
		1	7	23.03	23.17	23.22	24.00
		1	14	23.27	23.33	23.28	24.00
		8	0	22.76	22.83	22.95	23.50
		8	4	22.72	22.86	22.82	23.50
		8	7	22.76	22.79	22.71	23.50
		15	0	22.64	22.78	22.86	23.50
	16QAM	1	0	22.65	22.88	22.98	23.50
		1	7	22.63	22.51	22.58	23.50
		1	14	22.84	22.73	22.79	23.50
		8	0	21.99	21.81	21.90	22.50
		8	4	21.94	21.78	21.86	22.50
		8	7	21.93	21.83	21.87	22.50
		15	0	21.98	21.85	21.93	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19975/1712.5	20175/1732.5	20375/1752.5	
5MHz	QPSK	1	0	23.26	23.47	23.43	24.00
		1	13	23.01	23.13	23.19	24.00
		1	24	23.24	23.28	23.24	24.00
		12	0	22.73	22.78	22.91	23.50
		12	6	22.70	22.82	22.77	23.50
		12	13	22.74	22.77	22.67	23.50
		25	0	22.64	22.77	22.84	23.50
	16QAM	1	0	22.62	22.84	22.95	23.50



		1	13	22.60	22.49	22.55	23.50
		1	24	22.81	22.71	22.75	23.50
		12	0	21.97	21.77	21.87	22.50
		12	6	21.91	21.73	21.82	22.50
		12	13	21.90	21.78	21.83	22.50
		25	0	21.96	21.81	21.88	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20000/1715	20175/1732.5	20350/1750	
10MHz	QPSK	1	0	23.28	23.48	23.46	24.00
		1	25	23.04	23.18	23.23	24.00
		1	49	23.26	23.32	23.27	24.00
		25	0	22.76	22.83	22.95	23.50
		25	13	22.73	22.87	22.81	23.50
		25	25	22.76	22.81	22.72	23.50
		50	0	22.68	22.79	22.88	23.50
	16QAM	1	0	22.64	22.87	22.97	23.50
		1	25	22.63	22.53	22.58	23.50
		1	49	22.84	22.73	22.78	23.50
		25	0	22.00	21.82	21.91	22.50
		25	13	21.93	21.77	21.85	22.50
		25	25	21.93	21.83	21.87	22.50
		50	0	21.99	21.86	21.92	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20025/1717.5	20175/1732.5	20325/1747.5	
15MHz	QPSK	1	0	23.27	23.44	23.44	24.00
		1	38	23.02	23.17	23.20	24.00
		1	74	23.23	23.27	23.23	24.00
		36	0	22.74	22.79	22.92	23.50
		36	18	22.70	22.82	22.77	23.50
		36	39	22.73	22.78	22.68	23.50
		75	0	22.66	22.75	22.83	23.50
	16QAM	1	0	22.59	22.85	22.95	23.50
		1	38	22.61	22.50	22.56	23.50
		1	74	22.81	22.69	22.75	23.50
		36	0	21.97	21.80	21.88	22.50
		36	18	21.90	21.72	21.81	22.50
		36	39	21.91	21.79	21.84	22.50
		75	0	21.96	21.81	21.88	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20050/1720	20175/1732.5	20300/1745	
20MHz	QPSK	1	0	23.24	23.40	23.41	24.00
		1	50	23.01	23.13	23.18	24.00
		1	99	23.21	23.26	23.20	24.00



		50	0	22.71	22.74	22.88	23.50
		50	25	22.68	22.78	22.74	23.50
		50	50	22.70	22.73	22.64	23.50
		100	0	22.63	22.70	22.79	23.50
	16QAM	1	0	22.98	22.81	22.90	23.50
		1	50	22.57	22.48	22.52	23.50
		1	99	22.79	22.66	22.73	23.50
		50	0	21.94	21.76	21.85	22.50
		50	25	21.87	21.70	21.78	22.50
		50	50	21.88	21.74	21.80	22.50
		100	0	21.94	21.77	21.85	22.50

LTE FDD Band 4 Receiver on/hotspot				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				19957/1710.7	20175/1732.5	20393/1754.3	
1.4MHz	QPSK	1	0	23.78	23.91	23.94	24.50
		1	2	23.69	23.58	23.67	24.50
		1	5	23.71	23.72	23.79	24.50
		3	0	23.69	23.83	23.87	24.50
		3	2	23.62	23.77	23.66	24.50
		3	3	23.67	23.77	23.69	24.50
		6	0	22.76	22.85	22.90	23.50
	16QAM	1	0	22.68	23.13	23.20	23.50
		1	2	22.66	22.80	22.74	23.50
		1	5	22.70	23.19	22.87	23.50
		3	0	22.63	22.67	22.76	23.50
		3	2	22.58	22.64	22.63	23.50
		3	3	22.66	22.69	22.58	23.50
		6	0	21.64	21.78	21.78	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19965/1711.5	20175/1732.5	20385/1753.5	
3MHz	QPSK	1	0	23.80	23.95	23.97	24.50
		1	7	23.67	23.61	23.71	24.50
		1	14	23.74	23.77	23.83	24.50
		8	0	22.79	22.95	23.00	23.50
		8	4	22.74	22.87	22.78	23.50
		8	7	22.77	22.88	22.79	23.50
		15	0	22.76	22.89	22.93	23.50
	16QAM	1	0	22.71	23.15	23.23	23.50
		1	7	22.69	22.80	22.78	23.50
		1	14	22.72	23.23	22.90	23.50
		8	0	21.74	21.80	21.88	22.50



		8	4	21.69	21.77	21.75	22.50
		8	7	21.76	21.81	21.71	22.50
		15	0	21.67	21.82	21.81	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19975/1712.5	20175/1732.5	20375/1752.5	
5MHz	QPSK	1	0	23.77	23.93	23.93	24.50
		1	13	23.65	23.57	23.68	24.50
		1	24	23.71	23.72	23.79	24.50
		12	0	22.76	22.90	22.96	23.50
		12	6	22.72	22.83	22.73	23.50
		12	13	22.75	22.86	22.75	23.50
		25	0	22.76	22.88	22.91	23.50
	16QAM	1	0	22.68	23.11	23.20	23.50
		1	13	22.66	22.78	22.75	23.50
		1	24	22.69	23.21	22.86	23.50
		12	0	21.72	21.76	21.85	22.50
		12	6	21.66	21.72	21.71	22.50
		12	13	21.73	21.76	21.67	22.50
		25	0	21.65	21.78	21.76	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20000/1715	20175/1732.5	20350/1750	
10MHz	QPSK	1	0	23.79	23.94	23.96	24.50
		1	25	23.68	23.62	23.72	24.50
		1	49	23.73	23.76	23.82	24.50
		25	0	22.79	22.95	23.00	23.50
		25	13	22.75	22.88	22.77	23.50
		25	25	22.77	22.90	22.80	23.50
		50	0	22.80	22.90	22.95	23.50
	16QAM	1	0	22.70	23.14	23.22	23.50
		1	25	22.69	22.82	22.78	23.50
		1	49	22.72	23.23	22.89	23.50
		25	0	21.75	21.81	21.89	22.50
		25	13	21.68	21.76	21.74	22.50
		25	25	21.76	21.81	21.71	22.50
		50	0	21.68	21.83	21.80	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20025/1717.5	20175/1732.5	20325/1747.5	
15MHz	QPSK	1	0	23.78	23.90	23.94	24.50
		1	38	23.66	23.61	23.69	24.50
		1	74	23.70	23.71	23.78	24.50
		36	0	22.77	22.91	22.97	23.50
		36	18	22.72	22.83	22.73	23.50
		36	39	22.74	22.87	22.76	23.50



	16QAM	75	0	22.78	22.86	22.90	23.50
		1	0	22.65	23.12	23.20	23.50
		1	38	22.67	22.79	22.76	23.50
		1	74	22.69	23.19	22.86	23.50
		36	0	21.72	21.79	21.86	22.50
		36	18	21.65	21.71	21.70	22.50
		36	39	21.74	21.77	21.68	22.50
		75	0	21.65	21.78	21.76	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20050/1720	20175/1732.5	20300/1745	
20MHz	QPSK	1	0	23.75	23.86	23.91	24.50
		1	50	23.65	23.57	23.67	24.50
		1	99	23.68	23.70	23.75	24.50
		50	0	22.74	22.86	22.93	23.50
		50	25	22.70	22.79	22.70	23.50
		50	50	22.71	22.82	22.72	23.50
		100	0	22.75	22.81	22.86	23.50
	16QAM	1	0	22.86	23.08	23.15	23.50
		1	50	22.63	22.77	22.72	23.50
		1	99	22.67	23.16	22.84	23.50
		50	0	21.69	21.75	21.83	22.50
		50	25	21.62	21.69	21.67	22.50
		50	50	21.71	21.72	21.64	22.50
		100	0	21.63	21.74	21.73	22.50

LTE FDD Band 5 Receiver on/Receiver off/hotspot/Receiver off-Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20407/824.7	20525/836.5	20643/848.3	
1.4MHz	QPSK	1	0	22.68	22.73	22.70	24.00
		1	2	23.31	23.68	23.52	24.00
		1	5	22.70	22.58	22.56	24.00
		3	0	22.71	22.69	22.53	24.00
		3	2	22.72	22.70	22.70	24.00
		3	3	22.68	22.68	22.62	24.00
		6	0	22.70	22.70	22.70	23.00
	16QAM	1	0	22.37	22.80	22.84	23.00
		1	2	22.35	22.72	22.74	23.00
		1	5	22.43	22.71	22.71	23.00
		3	0	21.31	21.58	21.61	23.00
		3	2	21.24	21.54	21.57	23.00



		3	3	21.34	21.59	21.62	23.00
		6	0	21.17	21.58	21.58	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20415/825.5	20525/836.5	20635/847.5	
3MHz	QPSK	1	0	22.70	22.74	22.73	24.00
		1	7	23.34	23.73	23.56	24.00
		1	14	22.72	22.62	22.59	24.00
		8	0	22.74	22.74	22.57	23.00
		8	4	22.75	22.75	22.74	23.00
		8	7	22.70	22.72	22.67	23.00
		15	0	22.74	22.72	22.74	23.00
	16QAM	1	0	22.39	22.83	22.86	23.00
		1	7	22.38	22.76	22.77	23.00
		1	14	22.46	22.73	22.74	23.00
		8	0	21.34	21.63	21.65	22.00
		8	4	21.26	21.58	21.60	22.00
		8	7	21.37	21.64	21.66	22.00
		15	0	21.20	21.63	21.62	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20425/826.5	20525/836.5	20625/846.5	
5MHz	QPSK	1	0	22.69	22.70	22.71	24.00
		1	13	23.32	23.72	23.53	24.00
		1	24	22.69	22.57	22.55	24.00
		12	0	22.72	22.70	22.54	23.00
		12	6	22.72	22.70	22.70	23.00
		12	13	22.67	22.69	22.63	23.00
		25	0	22.72	22.68	22.69	23.00
	16QAM	1	0	22.34	22.81	22.84	23.00
		1	13	22.36	22.73	22.75	23.00
		1	24	22.43	22.69	22.71	23.00
		12	0	21.31	21.61	21.62	22.00
		12	6	21.23	21.53	21.56	22.00
		12	13	21.35	21.60	21.63	22.00
		25	0	21.17	21.58	21.58	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20450/829	20525/836.5	20600/844	
10MHz	QPSK	1	0	22.66	22.66	22.68	24.00
		1	25	23.31	23.68	23.51	24.00
		1	49	22.67	22.56	22.52	24.00
		25	0	22.69	22.65	22.50	23.00
		25	13	22.70	22.66	22.67	23.00
		25	25	22.64	22.64	22.59	23.00
		50	0	22.69	22.63	22.65	23.00



	16QAM	1	0	22.48	22.77	22.79	23.00
		1	25	22.32	22.71	22.71	23.00
		1	49	22.41	22.66	22.69	23.00
		25	0	21.28	21.57	21.59	22.00
		25	13	21.20	21.51	21.53	22.00
		25	25	21.32	21.55	21.59	22.00
		50	0	21.15	21.54	21.55	22.00

LTE FDD Band 7 Receiver off/Receiver off -Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	22.61	22.81	22.87	23.50
		1	13	22.56	22.80	22.73	23.50
		1	24	22.74	23.07	22.73	23.50
		12	0	22.09	22.36	22.37	23.00
		12	6	22.05	22.45	22.89	23.00
		12	13	22.05	22.51	22.62	23.00
		25	0	22.11	22.51	22.75	23.00
	16QAM	1	0	22.60	22.54	22.65	23.00
		1	13	22.58	22.44	22.50	23.00
		1	24	22.70	22.62	22.66	23.00
		12	0	21.52	21.23	21.33	22.00
		12	6	21.72	21.47	21.56	22.00
		12	13	21.70	21.54	21.59	22.00
		25	0	21.61	21.39	21.46	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	22.63	22.82	22.90	23.50
		1	25	22.59	22.85	22.77	23.50
		1	49	22.76	23.11	22.76	23.50
		25	0	22.12	22.41	22.41	23.00
		25	13	22.08	22.50	22.93	23.00
		25	25	22.07	22.55	22.67	23.00
		50	0	22.15	22.53	22.79	23.00
	16QAM	1	0	22.62	22.57	22.67	23.00
		1	25	22.61	22.48	22.53	23.00
		1	49	22.73	22.64	22.69	23.00
		25	0	21.55	21.28	21.37	22.00
		25	13	21.74	21.51	21.59	22.00
		25	25	21.73	21.59	21.63	22.00
		50	0	21.64	21.44	21.50	22.00



Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	22.62	22.78	22.88	23.50
		1	38	22.57	22.84	22.74	23.50
		1	74	22.73	23.06	22.72	23.50
		36	0	22.10	22.37	22.38	23.00
		36	18	22.05	22.45	22.89	23.00
		36	39	22.04	22.52	22.63	23.00
		75	0	22.13	22.49	22.74	23.00
	16QAM	1	0	22.57	22.55	22.65	23.00
		1	38	22.59	22.45	22.51	23.00
		1	74	22.70	22.60	22.66	23.00
		36	0	21.52	21.26	21.34	22.00
		36	18	21.71	21.46	21.55	22.00
		36	39	21.71	21.55	21.60	22.00
		75	0	21.61	21.39	21.46	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20850/2510	21100/2535	21350/2560	
20MHz	QPSK	1	0	22.59	22.74	22.85	23.50
		1	50	22.56	22.80	22.72	23.50
		1	99	22.71	23.05	22.69	23.50
		50	0	22.07	22.32	22.34	23.00
		50	25	22.03	22.41	22.86	23.00
		50	50	22.01	22.47	22.59	23.00
		100	0	22.10	22.44	22.70	23.00
	16QAM	1	0	22.78	22.51	22.60	23.00
		1	50	22.55	22.43	22.47	23.00
		1	99	22.68	22.57	22.64	23.00
		50	0	21.49	21.22	21.31	22.00
		50	25	21.68	21.44	21.52	22.00
		50	50	21.68	21.50	21.56	22.00
		100	0	21.59	21.35	21.43	22.00

LTE FDD Band 7 Receiver on				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	22.75	22.76	22.96	24.00
		1	13	22.33	22.72	22.66	24.00
		1	24	22.71	23.24	22.81	24.00
		12	0	22.14	22.47	22.31	23.00
		12	6	22.07	22.60	22.28	23.00
		12	13	22.23	22.65	22.22	23.00



		25	0	22.23	22.57	22.28	23.00
	16QAM	1	0	22.06	22.66	22.83	23.00
		1	13	22.04	22.33	22.49	23.00
		1	24	22.73	22.90	22.84	23.00
		12	0	21.16	21.32	21.38	22.00
		12	6	21.12	21.52	21.25	22.00
		12	13	21.18	21.65	21.16	22.00
		25	0	21.16	21.47	21.26	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	22.77	22.77	22.99	24.00
		1	25	22.36	22.77	22.70	24.00
		1	49	22.73	23.28	22.84	24.00
		25	0	22.17	22.52	22.35	23.00
		25	13	22.10	22.65	22.32	23.00
		25	25	22.25	22.69	22.27	23.00
		50	0	22.27	22.59	22.32	23.00
	16QAM	1	0	22.08	22.69	22.85	23.00
		1	25	22.07	22.37	22.52	23.00
		1	49	22.76	22.92	22.87	23.00
		25	0	21.19	21.37	21.42	22.00
		25	13	21.14	21.56	21.28	22.00
		25	25	21.21	21.70	21.20	22.00
		50	0	21.19	21.52	21.30	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	22.76	22.73	22.97	24.00
		1	38	22.34	22.76	22.67	24.00
		1	74	22.70	23.23	22.80	24.00
		36	0	22.15	22.48	22.32	23.00
		36	18	22.07	22.60	22.28	23.00
		36	39	22.22	22.66	22.23	23.00
		75	0	22.25	22.55	22.27	23.00
	16QAM	1	0	22.03	22.67	22.83	23.00
		1	38	22.05	22.34	22.50	23.00
		1	74	22.73	22.88	22.84	23.00
		36	0	21.16	21.35	21.39	22.00
		36	18	21.11	21.51	21.24	22.00
		36	39	21.19	21.66	21.17	22.00
		75	0	21.16	21.47	21.26	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20850/2510	21100/2535	21350/2560	
20MHz	QPSK	1	0	22.73	22.69	22.94	24.00



		1	50	22.33	22.72	22.65	24.00
		1	99	22.68	23.22	22.77	24.00
		50	0	22.12	22.43	22.28	23.00
		50	25	22.05	22.56	22.25	23.00
		50	50	22.19	22.61	22.19	23.00
		100	0	22.22	22.50	22.23	23.00
	16QAM	1	0	22.50	22.63	22.78	23.00
		1	50	22.01	22.32	22.46	23.00
		1	99	22.71	22.85	22.82	23.00
		50	0	21.13	21.31	21.36	22.00
		50	25	21.08	21.49	21.21	22.00
		50	50	21.16	21.61	21.13	22.00
		100	0	21.14	21.43	21.23	22.00

LTE FDD Band 7 Hotspot				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	20.34	20.48	20.52	21.50
		1	13	20.08	20.33	20.26	21.50
		1	24	20.36	20.70	20.39	21.50
		12	0	20.26	20.47	20.39	21.50
		12	6	20.19	20.54	20.21	21.50
		12	13	20.19	20.64	20.24	21.50
		25	0	20.20	20.61	20.32	21.50
	16QAM	1	0	20.28	20.59	20.73	21.50
		1	13	20.26	20.79	20.18	21.50
		1	24	20.56	21.08	20.66	21.50
		12	0	20.10	20.44	20.34	21.50
		12	6	20.05	20.42	20.18	21.50
		12	13	20.15	20.61	20.23	21.50
		25	0	20.16	20.46	20.22	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	20.36	20.49	20.55	21.50
		1	25	20.11	20.38	20.30	21.50
		1	49	20.38	20.74	20.42	21.50
		25	0	20.29	20.52	20.43	21.50
		25	13	20.22	20.59	20.25	21.50
		25	25	20.21	20.68	20.29	21.50
		50	0	20.24	20.63	20.36	21.50
	16QAM	1	0	20.30	20.62	20.75	21.50
		1	25	20.29	20.83	20.21	21.50



		1	49	20.59	21.10	20.69	21.50
		25	0	20.13	20.49	20.38	21.50
		25	13	20.07	20.46	20.21	21.50
		25	25	20.18	20.66	20.27	21.50
		50	0	20.19	20.51	20.26	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	20.35	20.45	20.53	21.50
		1	38	20.09	20.37	20.27	21.50
		1	74	20.35	20.69	20.38	21.50
		36	0	20.27	20.48	20.40	21.50
		36	18	20.19	20.54	20.21	21.50
		36	39	20.18	20.65	20.25	21.50
		75	0	20.22	20.59	20.31	21.50
	16QAM	1	0	20.25	20.60	20.73	21.50
		1	38	20.27	20.80	20.19	21.50
		1	74	20.56	21.06	20.66	21.50
		36	0	20.10	20.47	20.35	21.50
		36	18	20.04	20.41	20.17	21.50
		36	39	20.16	20.62	20.24	21.50
		75	0	20.16	20.46	20.22	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20850/2510	21100/2535	21350/2560	
20MHz	QPSK	1	0	20.32	20.41	20.50	21.50
		1	50	20.08	20.33	20.25	21.50
		1	99	20.33	20.68	20.35	21.50
		50	0	20.24	20.43	20.36	21.50
		50	25	20.17	20.50	20.18	21.50
		50	50	20.15	20.60	20.21	21.50
		100	0	20.19	20.54	20.27	21.50
	16QAM	1	0	20.65	20.56	20.68	21.50
		1	50	20.23	20.78	20.15	21.50
		1	99	20.54	21.03	20.64	21.50
		50	0	20.07	20.43	20.32	21.50
		50	25	20.01	20.39	20.14	21.50
		50	50	20.13	20.57	20.20	21.50
		100	0	20.14	20.42	20.19	21.50

LTE FDD Band 66				Output Power(dBm)	Tune-up Limit
Receiver off/Receiver off -Simultaneous with Wi-Fi					
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)	



				131979/1710.7	132322/1745	132665/1779.3	
1.4MHz	QPSK	1	0	23.18	23.55	23.43	24.00
		1	2	22.95	23.27	23.39	24.00
		1	5	23.28	23.31	23.55	24.00
		3	0	23.67	23.97	23.86	24.00
		3	2	23.65	23.91	23.90	24.00
		3	3	23.73	23.86	23.97	24.00
		6	0	22.73	22.94	22.95	23.50
	16QAM	1	0	22.96	22.98	23.11	23.50
		1	2	22.94	22.80	22.75	23.50
		1	5	22.91	22.80	23.07	23.50
		3	0	22.93	22.95	22.90	23.50
		3	2	22.86	22.90	22.88	23.50
		3	3	22.57	22.87	22.96	23.50
		6	0	22.07	22.05	22.02	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131987/1711.5	132322/1745	132657/1778.5	
3MHz	QPSK	1	0	23.20	23.59	23.46	24.00
		1	7	22.93	23.30	23.43	24.00
		1	14	23.31	23.36	23.59	24.00
		8	0	22.77	23.09	22.99	23.50
		8	4	22.77	23.01	23.02	23.50
		8	7	22.83	22.97	23.07	23.50
		15	0	22.73	22.98	22.98	23.50
	16QAM	1	0	22.99	23.00	23.14	23.50
		1	7	22.97	22.80	22.79	23.50
		1	14	22.93	22.84	23.10	23.50
		8	0	22.04	22.08	22.02	22.50
		8	4	21.97	22.03	22.00	22.50
		8	7	21.67	21.99	22.09	22.50
		15	0	22.10	22.09	22.05	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131997/1712.5	132322/1745	132647/1777.5	
5MHz	QPSK	1	0	0.00	23.17	23.57	24.00
		1	13	13.00	22.91	23.26	24.00
		1	24	24.00	23.28	23.31	24.00
		12	0	0.00	22.74	23.04	23.50
		12	6	6.00	22.75	22.97	23.50
		12	13	13.00	22.81	22.95	23.50
		25	0	0.00	22.73	22.97	23.50
	16QAM	1	0	0.00	22.96	22.96	23.50
		1	13	13.00	22.94	22.78	23.50
		1	24	24.00	22.90	22.82	23.50



		12	0	0.00	22.02	22.04	22.50
		12	6	6.00	21.94	21.98	22.50
		12	13	13.00	21.64	21.94	22.50
		25	0	0.00	22.08	22.05	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132022/1715	132322/1745	132622/1775	
10MHz	QPSK	1	0	23.19	23.58	23.45	24.00
		1	25	22.94	23.31	23.44	24.00
		1	49	23.30	23.35	23.58	24.00
		25	0	22.77	23.09	22.99	23.50
		25	13	22.78	23.02	23.01	23.50
		25	25	22.83	22.99	23.08	23.50
		50	0	22.77	22.99	23.00	23.50
	16QAM	1	0	22.98	22.99	23.13	23.50
		1	25	22.97	22.82	22.79	23.50
		1	49	22.93	22.84	23.09	23.50
		25	0	22.05	22.09	22.03	22.50
		25	13	21.96	22.02	21.99	22.50
		25	25	21.67	21.99	22.09	22.50
		50	0	22.11	22.10	22.04	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132047/1717.5	132322/1745	132597/1772.5	
15MHz	QPSK	1	0	23.18	23.54	23.43	24.00
		1	38	22.92	23.30	23.41	24.00
		1	74	23.27	23.30	23.54	24.00
		36	0	22.75	23.05	22.96	23.50
		36	18	22.75	22.97	22.97	23.50
		36	39	22.80	22.96	23.04	23.50
		75	0	22.75	22.95	22.95	23.50
	16QAM	1	0	22.93	22.97	23.11	23.50
		1	38	22.95	22.79	22.77	23.50
		1	74	22.90	22.80	23.06	23.50
		36	0	22.02	22.07	22.00	22.50
		36	18	21.93	21.97	21.95	22.50
		36	39	21.65	21.95	22.06	22.50
		75	0	22.08	22.05	22.00	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132072/1720	132322/1745	132572/1770	
20MHz	QPSK	1	0	23.15	23.50	23.40	24.00
		1	50	22.91	23.26	23.39	24.00
		1	99	23.25	23.29	23.51	24.00
		50	0	22.72	23.00	22.92	23.50
		50	25	22.73	22.93	22.94	23.50



		50	50	22.77	22.91	23.00	23.50
		100	0	22.72	22.90	22.91	23.50
	16QAM	1	0	23.05	22.93	23.06	23.50
		1	50	22.91	22.77	22.73	23.50
		1	99	22.88	22.77	23.04	23.50
		50	0	21.99	22.03	21.97	22.50
		50	25	21.90	21.95	21.92	22.50
		50	50	21.62	21.90	22.02	22.50
		100	0	22.06	22.01	21.97	22.50

LTE FDD Band 66 Receiver on/hotspot				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				131979/1710.7	132322/1745	132665/1779.3	
1.4MHz	QPSK	1	0	23.74	24.02	23.92	24.50
		1	2	23.61	23.88	23.84	24.50
		1	5	23.92	23.91	24.10	24.50
		3	0	23.68	23.96	23.90	24.50
		3	2	23.63	23.91	23.91	24.50
		3	3	23.78	23.86	23.94	24.50
		6	0	22.88	22.94	22.96	23.50
	16QAM	1	0	22.98	23.07	23.17	23.50
		1	2	22.96	22.84	22.79	23.50
		1	5	22.97	22.87	23.15	23.50
		3	0	22.98	23.04	22.97	23.50
		3	2	22.90	22.98	22.96	23.50
		3	3	22.63	22.93	23.03	23.50
		6	0	22.08	22.13	22.09	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				1319871711.5	132322/1745	132657/1778.5	
3MHz	QPSK	1	0	23.76	24.06	23.95	24.50
		1	7	23.59	23.91	23.88	24.50
		1	14	23.95	23.96	24.14	24.50
		8	0	22.78	23.08	23.03	23.50
		8	4	22.75	23.01	23.03	23.50
		8	7	22.88	22.97	23.04	23.50
		15	0	22.88	22.98	22.99	23.50
	16QAM	1	0	23.01	23.09	23.20	23.50
		1	7	22.99	22.84	22.83	23.50
		1	14	22.99	22.91	23.18	23.50
		8	0	22.09	22.17	22.09	22.50
		8	4	22.01	22.11	22.08	22.50
		8	7	21.73	22.05	22.16	22.50



		15	0	22.11	22.17	22.12	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131997/1712.5	132322/1745	132647/1777.5	
5MHz	QPSK	1	0	23.73	24.04	23.91	24.50
		1	13	23.57	23.87	23.85	24.50
		1	24	23.92	23.91	24.10	24.50
		12	0	22.75	23.03	22.99	23.50
		12	6	22.73	22.97	22.98	23.50
		12	13	22.86	22.95	23.00	23.50
		25	0	22.88	22.97	22.97	23.50
	16QAM	1	0	22.98	23.05	23.17	23.50
		1	13	22.96	22.82	22.80	23.50
		1	24	22.96	22.89	23.14	23.50
		12	0	22.07	22.13	22.06	22.50
		12	6	21.98	22.06	22.04	22.50
		12	13	21.70	22.00	22.12	22.50
		25	0	22.09	22.13	22.07	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132022/1715	132322/1745	132622/1775	
10MHz	QPSK	1	0	23.75	24.05	23.94	24.50
		1	25	23.60	23.92	23.89	24.50
		1	49	23.94	23.95	24.13	24.50
		25	0	22.78	23.08	23.03	23.50
		25	13	22.76	23.02	23.02	23.50
		25	25	22.88	22.99	23.05	23.50
		50	0	22.92	22.99	23.01	23.50
	16QAM	1	0	23.00	23.08	23.19	23.50
		1	25	22.99	22.86	22.83	23.50
		1	49	22.99	22.91	23.17	23.50
		25	0	22.10	22.18	22.10	22.50
		25	13	22.00	22.10	22.07	22.50
		25	25	21.73	22.05	22.16	22.50
		50	0	22.12	22.18	22.11	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132047/1717.5	132322/1745	132597/1772.5	
15MHz	QPSK	1	0	23.74	24.01	23.92	24.50
		1	38	23.58	23.91	23.86	24.50
		1	74	23.91	23.90	24.09	24.50
		36	0	22.76	23.04	23.00	23.50
		36	18	22.73	22.97	22.98	23.50
		36	39	22.85	22.96	23.01	23.50
		75	0	22.90	22.95	22.96	23.50
	16QAM	1	0	22.95	23.06	23.17	23.50



		1	38	22.97	22.83	22.81	23.50
		1	74	22.96	22.87	23.14	23.50
		36	0	22.07	22.16	22.07	22.50
		36	18	21.97	22.05	22.03	22.50
		36	39	21.71	22.01	22.13	22.50
		75	0	22.09	22.13	22.07	22.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132072/1720	132322/1745	132572/1770	
20MHz	QPSK	1	0	23.71	23.97	23.89	24.50
		1	50	23.57	23.87	23.84	24.50
		1	99	23.89	23.89	24.06	24.50
		50	0	22.73	22.99	22.96	23.50
		50	25	22.71	22.93	22.95	23.50
		50	50	22.82	22.91	22.97	23.50
		100	0	22.87	22.90	22.92	23.50
	16QAM	1	0	23.10	23.02	23.12	23.50
		1	50	22.93	22.81	22.77	23.50
		1	99	22.94	22.84	23.12	23.50
		50	0	22.04	22.12	22.04	22.50
		50	25	21.94	22.03	22.00	22.50
		50	50	21.68	21.96	22.09	22.50
		100	0	22.07	22.09	22.04	22.50



Second - Antenna

LTE FDD Band 2 Receiver off				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				18607/1850.7	18900/1880	19193/1909.3	
1.4MHz	QPSK	1	0	23.39	23.30	23.08	23.60
		1	2	23.13	22.96	22.89	23.60
		1	5	23.19	23.04	22.82	23.60
		3	0	23.30	23.07	22.91	23.60
		3	2	23.19	23.04	22.85	23.60
		3	3	23.15	23.03	22.76	23.60
		6	0	22.22	22.12	21.99	22.60
	16QAM	1	0	22.08	22.36	22.40	22.60
		1	2	22.06	22.14	22.16	22.60
		1	5	22.26	22.40	22.45	22.60
		3	0	21.83	21.93	21.99	22.60
		3	2	21.75	21.86	21.92	22.60
		3	3	21.80	21.93	21.96	22.60
		6	0	20.86	20.98	21.04	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18615/1851.5	18900/1880	19185/1908.5	
3MHz	QPSK	1	0	23.41	23.34	23.11	23.60
		1	7	23.11	22.99	22.93	23.60
		1	14	23.22	23.09	22.86	23.60
		8	0	22.40	22.19	22.04	22.60
		8	4	22.31	22.14	21.97	22.60
		8	7	22.25	22.14	21.86	22.60
		15	0	22.22	22.16	22.02	22.60
	16QAM	1	0	22.11	22.38	22.43	22.60
		1	7	22.09	22.14	22.20	22.60
		1	14	22.28	22.44	22.48	22.60
		8	0	20.94	21.06	21.11	21.60
		8	4	20.86	20.99	21.04	21.60
		8	7	20.90	21.05	21.09	21.60
		15	0	20.89	21.02	21.07	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18625/1852.5	18900/1880	19175/1907.5	
5MHz	QPSK	1	0	23.38	23.32	23.07	23.60
		1	13	23.09	22.95	22.90	23.60
		1	24	23.19	23.04	22.82	23.60
		12	0	22.37	22.14	22.00	22.60
		12	6	22.29	22.10	21.92	22.60
		12	13	22.23	22.12	21.82	22.60



		25	0	22.22	22.15	22.00	22.60
	16QAM	1	0	22.08	22.34	22.40	22.60
		1	13	22.06	22.12	22.17	22.60
		1	24	22.25	22.42	22.44	22.60
		12	0	20.92	21.02	21.08	21.60
		12	6	20.83	20.94	21.00	21.60
		12	13	20.87	21.00	21.05	21.60
		25	0	20.87	20.98	21.02	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18650/1855	18900/1880	19150/1905	
10MHz	QPSK	1	0	23.40	23.33	23.10	23.60
		1	25	23.12	23.00	22.94	23.60
		1	49	23.21	23.08	22.85	23.60
		25	0	22.40	22.19	22.04	22.60
		25	13	22.32	22.15	21.96	22.60
		25	25	22.25	22.16	21.87	22.60
		50	0	22.26	22.17	22.04	22.60
	16QAM	1	0	22.10	22.37	22.42	22.60
		1	25	22.09	22.16	22.20	22.60
		1	49	22.28	22.44	22.47	22.60
		25	0	20.95	21.07	21.12	21.60
		25	13	20.85	20.98	21.03	21.60
		25	25	20.90	21.05	21.09	21.60
		50	0	20.90	21.03	21.06	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18675/1857.5	18900/1880	19125/1902.5	
15MHz	QPSK	1	0	23.39	23.29	23.08	23.60
		1	38	23.10	22.99	22.91	23.60
		1	74	23.18	23.03	22.81	23.60
		36	0	22.38	22.15	22.01	22.60
		36	18	22.29	22.10	21.92	22.60
		36	39	22.22	22.13	21.83	22.60
		75	0	22.24	22.13	21.99	22.60
	16QAM	1	0	22.05	22.35	22.40	22.60
		1	38	22.07	22.13	22.18	22.60
		1	74	22.25	22.40	22.44	22.60
		36	0	20.92	21.05	21.09	21.60
		36	18	20.82	20.93	20.99	21.60
		36	39	20.88	21.01	21.06	21.60
		75	0	20.87	20.98	21.02	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18700/1860	18900/1880	19100/1900	
20MHz	QPSK	1	0	23.36	23.25	23.05	23.60



		1	50	23.09	22.95	22.89	23.60
		1	99	23.16	23.02	22.78	23.60
		50	0	22.35	22.10	21.97	22.60
		50	25	22.27	22.06	21.89	22.60
		50	50	22.19	22.08	21.79	22.60
		100	0	22.21	22.08	21.95	22.60
	16QAM	1	0	22.22	22.31	22.35	22.60
		1	50	22.03	22.11	22.14	22.60
		1	99	22.23	22.37	22.42	22.60
		50	0	20.89	21.01	21.06	21.60
		50	25	20.79	20.91	20.96	21.60
		50	50	20.85	20.96	21.02	21.60
		100	0	20.85	20.94	20.99	21.60

LTE FDD Band 2 Receiver on				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				18607/1850.7	18900/1880	19193/1909.3	
1.4MHz	QPSK	1	0	22.32	22.21	22.13	22.60
		1	2	22.22	22.22	21.74	22.60
		1	5	22.13	22.07	21.92	22.60
		3	0	22.37	22.23	22.03	22.60
		3	2	22.31	22.18	21.92	22.60
		3	3	22.28	22.14	21.86	22.60
		6	0	22.25	22.02	21.99	22.60
	16QAM	1	0	21.51	22.24	22.31	22.60
		1	2	21.49	21.52	21.53	22.60
		1	5	22.08	22.13	22.22	22.60
		3	0	22.01	22.11	22.05	22.60
		3	2	21.85	21.95	21.90	22.60
		3	3	22.02	22.20	22.07	22.60
		6	0	21.11	21.21	21.20	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18615/1851.5	18900/1880	19185/1908.5	
3MHz	QPSK	1	0	22.34	22.25	22.16	22.60
		1	7	22.20	22.25	21.78	22.60
		1	14	22.16	22.12	21.96	22.60
		8	0	22.37	22.25	22.06	22.60
		8	4	22.33	22.18	21.94	22.60
		8	7	22.28	22.15	21.86	22.60
		15	0	22.25	22.06	22.02	22.60
	16QAM	1	0	21.54	22.26	22.34	22.60



		1	7	21.52	21.52	21.57	22.60
		1	14	22.10	22.17	22.25	22.60
		8	0	21.12	21.24	21.17	21.60
		8	4	20.96	21.08	21.02	21.60
		8	7	21.12	21.32	21.20	21.60
		15	0	21.14	21.25	21.23	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18625/1852.5	18900/1880	19175/1907.5	
5MHz	QPSK	1	0	22.31	22.23	22.12	22.60
		1	13	22.18	22.21	21.75	22.60
		1	24	22.13	22.07	21.92	22.60
		12	0	22.34	22.20	22.02	22.60
		12	6	22.31	22.14	21.89	22.60
		12	13	22.26	22.13	21.82	22.60
		25	0	22.25	22.05	22.00	22.60
	16QAM	1	0	21.51	22.22	22.31	22.60
		1	13	21.49	21.50	21.54	22.60
		1	24	22.07	22.15	22.21	22.60
		12	0	21.10	21.20	21.14	21.60
		12	6	20.93	21.03	20.98	21.60
		12	13	21.09	21.27	21.16	21.60
		25	0	21.12	21.21	21.18	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18650/1855	18900/1880	19150/1905	
10MHz	QPSK	1	0	22.33	22.24	22.15	22.60
		1	25	22.21	22.26	21.79	22.60
		1	49	22.15	22.11	21.95	22.60
		25	0	22.37	22.25	22.06	22.60
		25	13	22.34	22.19	21.93	22.60
		25	25	22.28	22.17	21.87	22.60
		50	0	22.29	22.07	22.04	22.60
	16QAM	1	0	21.53	22.25	22.33	22.60
		1	25	21.52	21.54	21.57	22.60
		1	49	22.10	22.17	22.24	22.60
		25	0	21.13	21.25	21.18	21.60
		25	13	20.95	21.07	21.01	21.60
		25	25	21.12	21.32	21.20	21.60
		50	0	21.15	21.26	21.22	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18675/1857.5	18900/1880	19125/1902.5	
15MHz	QPSK	1	0	22.32	22.20	22.13	22.60
		1	38	22.19	22.25	21.76	22.60
		1	74	22.12	22.06	21.91	22.60



		36	0	22.35	22.21	22.03	22.60
		36	18	22.31	22.14	21.89	22.60
		36	39	22.25	22.14	21.83	22.60
		75	0	22.27	22.03	21.99	22.60
	16QAM	1	0	21.48	22.23	22.31	22.60
		1	38	21.50	21.51	21.55	22.60
		1	74	22.07	22.13	22.21	22.60
		36	0	21.10	21.23	21.15	21.60
		36	18	20.92	21.02	20.97	21.60
		36	39	21.10	21.28	21.17	21.60
		75	0	21.12	21.21	21.18	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18700/1860	18900/1880	19100/1900	
20MHz	QPSK	1	0	22.29	22.16	22.10	22.60
		1	50	22.18	22.21	21.74	22.60
		1	99	22.10	22.05	21.88	22.60
		50	0	22.32	22.16	21.99	22.60
		50	25	22.29	22.10	21.86	22.60
		50	50	22.22	22.09	21.79	22.60
		100	0	22.24	21.98	21.95	22.60
	16QAM	1	0	22.15	22.19	22.26	22.60
		1	50	21.46	21.49	21.51	22.60
		1	99	22.05	22.10	22.19	22.60
		50	0	21.07	21.19	21.12	21.60
		50	25	20.89	21.00	20.94	21.60
		50	50	21.07	21.23	21.13	21.60
		100	0	21.10	21.17	21.15	21.60

LTE FDD Band 2 hotspot/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				18607/1850.7	18900/1880	19193/1909.3	
1.4MHz	QPSK	1	0	20.97	20.80	20.71	22.10
		1	2	20.81	20.90	20.32	22.10
		1	5	20.75	20.66	20.44	22.10
		3	0	21.84	21.59	21.50	22.10
		3	2	21.73	21.52	21.43	22.10
		3	3	21.67	21.60	21.43	22.10
		6	0	20.80	20.68	20.56	22.10
	16QAM	1	0	21.13	21.23	21.16	22.10
		1	2	21.11	21.13	21.12	22.10
		1	5	20.61	20.69	20.67	22.10



		3	0	21.85	21.92	21.89	22.10
		3	2	21.78	21.85	21.82	22.10
		3	3	21.69	21.81	21.74	22.10
		6	0	20.81	20.92	20.86	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18615/1851.5	18900/1880	19185/1908.5	
3MHz	QPSK	1	0	20.99	20.84	20.74	22.10
		1	7	20.79	20.93	20.36	22.10
		1	14	20.78	20.71	20.48	22.10
		8	0	20.94	20.71	20.63	22.10
		8	4	20.85	20.62	20.55	22.10
		8	7	20.77	20.71	20.53	22.10
		15	0	20.80	20.72	20.59	22.10
	16QAM	1	0	21.16	21.25	21.19	22.10
		1	7	21.14	21.13	21.16	22.10
		1	14	20.63	20.73	20.70	22.10
		8	0	20.96	21.05	21.01	21.60
		8	4	20.89	20.98	20.94	21.60
		8	7	20.79	20.93	20.87	21.60
		15	0	20.84	20.96	20.89	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18625/1852.5	18900/1880	19175/1907.5	
5MHz	QPSK	1	0	20.96	20.82	20.70	22.10
		1	13	20.77	20.89	20.33	22.10
		1	24	20.75	20.66	20.44	22.10
		12	0	20.91	20.66	20.59	22.10
		12	6	20.83	20.58	20.50	22.10
		12	13	20.75	20.69	20.49	22.10
		25	0	20.80	20.71	20.57	22.10
	16QAM	1	0	21.13	21.21	21.16	22.10
		1	13	21.11	21.11	21.13	22.10
		1	24	20.60	20.71	20.66	22.10
		12	0	20.94	21.01	20.98	21.60
		12	6	20.86	20.93	20.90	21.60
		12	13	20.76	20.88	20.83	21.60
		25	0	20.82	20.92	20.84	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18650/1855	18900/1880	19150/1905	
10MHz	QPSK	1	0	20.98	20.83	20.73	22.10
		1	25	20.80	20.94	20.37	22.10
		1	49	20.77	20.70	20.47	22.10
		25	0	20.94	20.71	20.63	22.10
		25	13	20.86	20.63	20.54	22.10



		25	25	20.77	20.73	20.54	22.10
		50	0	20.84	20.73	20.61	22.10
	16QAM	1	0	21.15	21.24	21.18	22.10
		1	25	21.14	21.15	21.16	22.10
		1	49	20.63	20.73	20.69	22.10
		25	0	20.97	21.06	21.02	21.60
		25	13	20.88	20.97	20.93	21.60
		25	25	20.79	20.93	20.87	21.60
		50	0	20.85	20.97	20.88	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18675/1857.5	18900/1880	19125/1902.5	
15MHz	QPSK	1	0	20.97	20.79	20.71	22.10
		1	38	20.78	20.93	20.34	22.10
		1	74	20.74	20.65	20.43	22.10
		36	0	20.92	20.67	20.60	22.10
		36	18	20.83	20.58	20.50	22.10
		36	39	20.74	20.70	20.50	22.10
		75	0	20.82	20.69	20.56	22.10
	16QAM	1	0	21.10	21.22	21.16	22.10
		1	38	21.12	21.12	21.14	22.10
		1	74	20.60	20.69	20.66	22.10
		36	0	20.94	21.04	20.99	21.60
		36	18	20.85	20.92	20.89	21.60
		36	39	20.77	20.89	20.84	21.60
		75	0	20.82	20.92	20.84	21.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				18700/1860	18900/1880	19100/1900	
20MHz	QPSK	1	0	20.94	20.75	20.68	22.10
		1	50	20.77	20.89	20.32	22.10
		1	99	20.72	20.64	20.40	22.10
		50	0	20.89	20.62	20.56	22.10
		50	25	20.81	20.54	20.47	22.10
		50	50	20.71	20.65	20.46	22.10
		100	0	20.79	20.64	20.52	22.10
	16QAM	1	0	21.06	21.18	21.11	22.10
		1	50	21.08	21.10	21.10	22.10
		1	99	20.58	20.66	20.64	22.10
		50	0	20.91	21.00	20.96	21.60
		50	25	20.82	20.90	20.86	21.60
		50	50	20.74	20.84	20.80	21.60
		100	0	20.80	20.88	20.81	21.60



LTE FDD Band 4 Receiver off				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				19957/1710.7	20175/1732.5	20393/1754.3	
1.4MHz	QPSK	1	0	22.17	22.36	22.29	23.00
		1	2	22.03	22.01	21.85	23.00
		1	5	22.05	22.04	21.87	23.00
		3	0	22.00	22.21	22.01	23.00
		3	2	22.05	22.01	21.88	23.00
		3	3	22.03	21.86	21.75	23.00
		6	0	21.57	21.60	21.55	22.50
	16QAM	1	0	21.25	21.86	21.63	22.50
		1	2	21.73	21.71	21.45	22.50
		1	5	22.05	21.99	21.87	22.50
		3	0	21.69	21.59	21.47	22.50
		3	2	21.54	21.49	21.37	22.50
		3	3	21.46	21.43	21.21	22.50
		6	0	20.49	20.48	20.45	21.20
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19965/1711.5	20175/1732.5	20385/1753.5	
3MHz	QPSK	1	0	22.17	22.35	22.29	23.00
		1	7	22.00	22.04	21.87	23.00
		1	14	22.04	22.03	21.86	23.00
		8	0	21.58	21.79	21.61	22.50
		8	4	21.65	21.57	21.45	22.50
		8	7	21.60	21.46	21.32	22.50
		15	0	21.59	21.61	21.55	22.50
	16QAM	1	0	21.72	22.35	22.13	22.50
		1	7	21.74	21.70	21.47	22.50
		1	14	22.04	21.99	21.86	22.50
		8	0	20.78	20.71	20.57	21.50
		8	4	20.61	20.56	20.44	21.50
		8	7	20.54	20.51	20.31	21.50
		15	0	20.50	20.48	20.43	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19975/1712.5	20175/1732.5	20375/1752.5	
5MHz	QPSK	1	0	22.18	22.39	22.31	23.00
		1	13	22.02	22.05	21.90	23.00
		1	24	22.07	22.08	21.90	23.00
		12	0	21.60	21.83	21.64	22.50
		12	6	21.68	21.62	21.49	22.50
		12	13	21.63	21.49	21.36	22.50
		25	0	21.61	21.65	21.60	22.50



	16QAM	1	0	21.77	22.37	22.15	22.50
		1	13	21.76	21.73	21.49	22.50
		1	24	22.07	22.03	21.89	22.50
		12	0	20.81	20.73	20.60	21.50
		12	6	20.64	20.61	20.48	21.50
		12	13	20.56	20.55	20.34	21.50
		25	0	20.53	20.53	20.47	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20000/1715	20175/1732.5	20350/1750	
10MHz	QPSK	1	0	22.16	22.38	22.28	23.00
		1	25	21.99	22.00	21.86	23.00
		1	49	22.05	22.04	21.87	23.00
		25	0	21.57	21.78	21.60	22.50
		25	13	21.65	21.57	21.45	22.50
		25	25	21.61	21.45	21.31	22.50
		50	0	21.57	21.63	21.56	22.50
	16QAM	1	0	21.75	22.34	22.13	22.50
		1	25	21.73	21.69	21.46	22.50
		1	49	22.04	22.01	21.86	22.50
		25	0	20.78	20.68	20.56	21.50
		25	13	20.62	20.57	20.45	21.50
		25	25	20.53	20.50	20.30	21.50
		50	0	20.50	20.48	20.43	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20025/1717.5	20175/1732.5	20325/1747.5	
15MHz	QPSK	1	0	22.19	22.40	22.32	23.00
		1	38	22.01	22.04	21.89	23.00
		1	74	22.08	22.09	21.91	23.00
		36	0	21.60	21.83	21.64	22.50
		36	18	21.67	21.61	21.50	22.50
		36	39	21.63	21.47	21.35	22.50
		75	0	21.57	21.64	21.58	22.50
	16QAM	1	0	21.78	22.38	22.16	22.50
		1	38	21.76	21.71	21.49	22.50
		1	74	22.07	22.03	21.90	22.50
		36	0	20.80	20.72	20.59	21.50
		36	18	20.65	20.62	20.49	21.50
		36	39	20.56	20.55	20.34	21.50
		75	0	20.52	20.52	20.48	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20050/1720	20175/1732.5	20300/1745	
20MHz	QPSK	1	0	22.14	22.31	22.26	23.00
		1	50	21.99	22.00	21.85	23.00



		1	99	22.02	22.02	21.83	23.00
		50	0	21.55	21.74	21.57	22.50
		50	25	21.63	21.53	21.42	22.50
		50	50	21.57	21.41	21.28	22.50
		100	0	21.56	21.56	21.51	22.50
	16QAM	1	0	22.35	22.31	22.08	22.50
		1	50	21.70	21.68	21.43	22.50
		1	99	22.02	21.96	21.84	22.50
		50	0	20.75	20.67	20.54	21.50
		50	25	20.58	20.54	20.41	21.50
		50	50	20.51	20.46	20.27	21.50
		100	0	20.48	20.44	20.40	21.50

LTE FDD Band 4 Receiver on				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				19957/1710.7	20175/1732.5	20393/1754.3	
1.4MHz	QPSK	1	0	21.08	21.23	21.20	22.00
		1	2	20.99	20.94	20.68	22.00
		1	5	21.09	20.94	20.96	22.00
		3	0	20.97	21.08	21.09	22.00
		3	2	20.98	21.04	20.88	22.00
		3	3	20.99	21.02	20.86	22.00
		6	0	21.03	21.08	21.01	22.00
	16QAM	1	0	21.00	21.51	21.27	22.00
		1	2	20.98	21.29	21.22	22.00
		1	5	21.11	21.28	21.13	22.00
		3	0	21.45	21.47	21.47	22.00
		3	2	21.50	21.47	21.32	22.00
		3	3	21.42	21.45	21.22	22.00
		6	0	20.51	20.57	20.42	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19965/1711.5	20175/1732.5	20385/1753.5	
3MHz	QPSK	1	0	21.10	21.27	21.23	22.00
		1	7	20.97	20.97	20.72	22.00
		1	14	21.12	20.99	21.00	22.00
		8	0	21.07	21.20	21.22	22.00
		8	4	21.10	21.14	21.00	22.00
		8	7	21.09	21.13	20.96	22.00
		15	0	21.03	21.12	21.04	22.00
	16QAM	1	0	21.03	21.53	21.30	22.00
		1	7	21.01	21.29	21.26	22.00
		1	14	21.13	21.32	21.16	22.00



		8	0	20.56	20.60	20.59	21.50
		8	4	20.61	20.60	20.44	21.50
		8	7	20.52	20.57	20.35	21.50
		15	0	20.54	20.61	20.45	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19975/1712.5	20175/1732.5	20375/1752.5	
5MHz	QPSK	1	0	21.07	21.25	21.19	22.00
		1	13	20.95	20.93	20.69	22.00
		1	24	21.09	20.94	20.96	22.00
		12	0	21.04	21.15	21.18	22.00
		12	6	21.08	21.10	20.95	22.00
		12	13	21.07	21.11	20.92	22.00
		25	0	21.03	21.11	21.02	22.00
	16QAM	1	0	21.00	21.49	21.27	22.00
		1	13	20.98	21.27	21.23	22.00
		1	24	21.10	21.30	21.12	22.00
		12	0	20.54	20.56	20.56	21.50
		12	6	20.58	20.55	20.40	21.50
		12	13	20.49	20.52	20.31	21.50
		25	0	20.52	20.57	20.40	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20000/1715	20175/1732.5	20350/1750	
10MHz	QPSK	1	0	21.09	21.26	21.22	22.00
		1	25	20.98	20.98	20.73	22.00
		1	49	21.11	20.98	20.99	22.00
		25	0	21.07	21.20	21.22	22.00
		25	13	21.11	21.15	20.99	22.00
		25	25	21.09	21.15	20.97	22.00
		50	0	21.07	21.13	21.06	22.00
	16QAM	1	0	21.02	21.52	21.29	22.00
		1	25	21.01	21.31	21.26	22.00
		1	49	21.13	21.32	21.15	22.00
		25	0	20.57	20.61	20.60	21.50
		25	13	20.60	20.59	20.43	21.50
		25	25	20.52	20.57	20.35	21.50
		50	0	20.55	20.62	20.44	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20025/1717.5	20175/1732.5	20325/1747.5	
15MHz	QPSK	1	0	21.08	21.22	21.20	22.00
		1	38	20.96	20.97	20.70	22.00
		1	74	21.08	20.93	20.95	22.00
		36	0	21.05	21.16	21.19	22.00
		36	18	21.08	21.10	20.95	22.00



		36	39	21.06	21.12	20.93	22.00
		75	0	21.05	21.09	21.01	22.00
	16QAM	1	0	20.97	21.50	21.27	22.00
		1	38	20.99	21.28	21.24	22.00
		1	74	21.10	21.28	21.12	22.00
		36	0	20.54	20.59	20.57	21.50
		36	18	20.57	20.54	20.39	21.50
		36	39	20.50	20.53	20.32	21.50
		75	0	20.52	20.57	20.40	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20050/1720	20175/1732.5	20300/1745	
20MHz	QPSK	1	0	21.05	21.18	21.17	22.00
		1	50	20.95	20.93	20.68	22.00
		1	99	21.06	20.92	20.92	22.00
		50	0	21.02	21.11	21.15	22.00
		50	25	21.06	21.06	20.92	22.00
		50	50	21.03	21.07	20.89	22.00
		100	0	21.02	21.04	20.97	22.00
	16QAM	1	0	21.37	21.46	21.22	22.00
		1	50	20.95	21.26	21.20	22.00
		1	99	21.08	21.25	21.10	22.00
		50	0	20.51	20.55	20.54	21.50
		50	25	20.54	20.52	20.36	21.50
		50	50	20.47	20.48	20.28	21.50
		100	0	20.50	20.53	20.37	21.50

LTE FDD Band 4 hotspot/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				19957/1710.7	20175/1732.5	20393/1754.3	
1.4MHz	QPSK	1	0	20.27	20.42	20.57	21.50
		1	2	19.93	20.26	20.19	21.50
		1	5	20.28	20.23	20.18	21.50
		3	0	20.31	20.38	20.38	21.50
		3	2	20.32	20.35	20.29	21.50
		3	3	20.35	20.29	20.24	21.50
		6	0	20.35	20.31	20.20	21.50
	16QAM	1	0	20.28	20.34	20.85	21.50
		1	2	20.35	20.21	20.35	21.50
		1	5	20.42	20.34	20.29	21.50
		3	0	20.17	20.27	20.25	21.50
		3	2	20.32	20.25	20.24	21.50



		3	3	20.19	20.25	20.14	21.50
		6	0	20.23	20.27	20.23	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19965/1711.5	20175/1732.5	20385/1753.5	
3MHz	QPSK	1	0	20.29	20.46	20.60	21.50
		1	7	19.93	20.28	20.23	21.50
		1	14	20.31	20.28	20.22	21.50
		8	0	20.35	20.45	20.45	21.50
		8	4	20.35	20.43	20.35	21.50
		8	7	20.39	20.34	20.28	21.50
		15	0	20.37	20.35	20.23	21.50
	16QAM	1	0	20.31	20.36	20.88	21.50
		1	7	20.38	20.23	20.39	21.50
		1	14	20.44	20.38	20.32	21.50
		8	0	20.22	20.31	20.28	21.50
		8	4	20.37	20.32	20.30	21.50
		8	7	20.23	20.31	20.21	21.50
		15	0	20.26	20.31	20.26	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				19975/1712.5	20175/1732.5	20375/1752.5	
5MHz	QPSK	1	0	20.26	20.44	20.56	21.50
		1	13	19.91	20.24	20.20	21.50
		1	24	20.28	20.23	20.18	21.50
		12	0	20.32	20.40	20.41	21.50
		12	6	20.33	20.39	20.30	21.50
		12	13	20.37	20.32	20.24	21.50
		25	0	20.35	20.34	20.21	21.50
	16QAM	1	0	20.28	20.32	20.85	21.50
		1	13	20.35	20.21	20.36	21.50
		1	24	20.41	20.36	20.28	21.50
		12	0	20.20	20.27	20.25	21.50
		12	6	20.34	20.27	20.26	21.50
		12	13	20.20	20.26	20.17	21.50
		25	0	20.24	20.27	20.21	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20000/1715	20175/1732.5	20350/1750	
10MHz	QPSK	1	0	20.27	20.43	20.58	21.50
		1	25	19.92	20.28	20.22	21.50
		1	49	20.29	20.25	20.20	21.50
		25	0	20.33	20.44	20.43	21.50



		25	13	20.35	20.42	20.33	21.50
		25	25	20.37	20.32	20.28	21.50
		50	0	20.35	20.35	20.22	21.50
	16QAM	1	0	20.27	20.30	20.85	21.50
		1	25	20.37	20.24	20.34	21.50
		1	49	20.42	20.34	20.30	21.50
		25	0	20.18	20.31	20.26	21.50
		25	13	20.33	20.26	20.27	21.50
		25	25	20.22	20.30	20.16	21.50
		50	0	20.23	20.29	20.21	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20025/1717.5	20175/1732.5	20325/1747.5	
15MHz	QPSK	1	0	20.27	20.41	20.57	21.50
		1	38	19.92	20.28	20.21	21.50
		1	74	20.27	20.22	20.17	21.50
		36	0	20.33	20.41	20.42	21.50
		36	18	20.33	20.39	20.30	21.50
		36	39	20.36	20.33	20.25	21.50
		75	0	20.38	20.32	20.20	21.50
	16QAM	1	0	20.25	20.33	20.85	21.50
		1	38	20.36	20.22	20.37	21.50
		1	74	20.41	20.34	20.28	21.50
		36	0	20.20	20.30	20.26	21.50
		36	18	20.33	20.26	20.25	21.50
		36	39	20.21	20.27	20.18	21.50
		75	0	20.24	20.27	20.21	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20050/1720	20175/1732.5	20300/1745	
20MHz	QPSK	1	0	20.24	20.37	20.54	21.50
		1	50	19.91	20.24	20.19	21.50
		1	99	20.25	20.21	20.14	21.50
		50	0	20.30	20.36	20.38	21.50
		50	25	20.31	20.35	20.27	21.50
		50	50	20.33	20.28	20.21	21.50
		100	0	20.35	20.27	20.16	21.50
	16QAM	1	0	20.23	20.29	20.80	21.50
		1	50	20.32	20.20	20.33	21.50
		1	99	20.39	20.31	20.26	21.50
		50	0	20.17	20.26	20.23	21.50
		50	25	20.30	20.24	20.22	21.50
		50	50	20.18	20.22	20.14	21.50



		100	0	20.22	20.23	20.18	21.50
--	--	-----	---	-------	-------	-------	-------

LTE FDD Band 5 Receiver off				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20407/824.7	20525/836.5	20643/848.3	
1.4MHz	QPSK	1	0	22.73	22.63	22.60	23.40
		1	2	22.89	22.44	22.53	23.40
		1	5	22.67	22.59	22.42	23.40
		3	0	22.86	22.86	22.82	23.40
		3	2	22.80	22.81	22.80	23.40
		3	3	22.92	22.83	22.77	23.40
		6	0	21.88	21.90	21.82	22.40
	16QAM	1	0	22.15	22.10	22.15	22.40
		1	2	22.13	22.10	21.58	22.40
		1	5	21.99	22.06	21.93	22.40
		3	0	21.83	21.76	21.74	22.40
		3	2	21.86	21.78	21.70	22.40
		3	3	21.91	21.75	21.61	22.40
		6	0	20.78	20.81	20.85	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20415/825.5	20525/836.5	20635/847.5	
3MHz	QPSK	1	0	22.74	22.66	22.62	23.40
		1	7	22.88	22.48	22.58	23.40
		1	14	22.69	22.63	22.45	23.40
		8	0	21.96	21.98	21.95	22.40
		8	4	21.93	21.92	21.91	22.40
		8	7	22.02	21.96	21.88	22.40
		15	0	21.92	21.95	21.87	22.40
	16QAM	1	0	22.17	22.11	22.17	22.40
		1	7	22.16	22.12	21.62	22.40
		1	14	22.01	22.10	21.95	22.40
		8	0	20.95	20.90	20.87	21.40
		8	4	20.96	20.90	20.81	21.40
		8	7	21.01	20.87	20.74	21.40
		15	0	20.82	20.86	20.87	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20425/826.5	20525/836.5	20625/846.5	
5MHz	QPSK	1	0	22.73	22.62	22.60	23.40
		1	13	22.86	22.47	22.55	23.40
		1	24	22.66	22.58	22.41	23.40
		12	0	21.94	21.94	21.92	22.40



		12	6	21.90	21.87	21.87	22.40
		12	13	21.99	21.93	21.84	22.40
		25	0	21.90	21.91	21.82	22.40
	16QAM	1	0	22.12	22.09	22.15	22.40
		1	13	22.14	22.09	21.60	22.40
		1	24	21.98	22.06	21.92	22.40
		12	0	20.92	20.88	20.84	21.40
		12	6	20.93	20.85	20.77	21.40
		12	13	20.99	20.83	20.71	21.40
		25	0	20.79	20.81	20.83	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20450/829	20525/836.5	20600/844	
10MHz	QPSK	1	0	22.70	22.58	22.57	23.40
		1	25	22.85	22.43	22.53	23.40
		1	49	22.64	22.57	22.38	23.40
		25	0	21.91	21.89	21.88	22.40
		25	13	21.88	21.83	21.84	22.40
		25	25	21.96	21.88	21.80	22.40
		50	0	21.87	21.86	21.78	22.40
	16QAM	1	0	22.12	22.05	22.10	22.40
		1	25	22.10	22.07	21.56	22.40
		1	49	21.96	22.03	21.90	22.40
		25	0	20.89	20.84	20.81	21.40
		25	13	20.90	20.83	20.74	21.40
		25	25	20.96	20.78	20.67	21.40
		50	0	20.77	20.77	20.80	21.40

LTE FDD Band 5 Receiver on/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20407/824.7	20525/836.5	20643/848.3	
1.4MHz	QPSK	1	0	19.88	19.92	19.82	20.20
		1	2	19.69	19.61	19.80	20.20
		1	5	19.89	19.78	19.70	20.20
		3	0	19.89	19.87	19.81	20.20
		3	2	19.90	19.74	19.78	20.20
		3	3	19.88	19.83	19.76	20.20
		6	0	19.87	19.85	19.82	20.20
	16QAM	1	0	20.13	19.97	20.08	20.20
		1	2	19.98	19.58	20.12	20.20
		1	5	20.05	19.75	19.92	20.20
		3	0	19.82	19.84	19.84	20.20



		3	2	19.86	19.71	19.76	20.20
		3	3	19.84	19.78	19.71	20.20
		6	0	19.78	19.83	19.82	20.20
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20415/825.5	20525/836.5	20635/847.5	
3MHz	QPSK	1	0	19.90	19.96	19.85	20.20
		1	7	19.69	19.63	19.84	20.20
		1	14	19.92	19.83	19.74	20.20
		8	0	19.93	19.94	19.88	20.20
		8	4	19.93	19.82	19.84	20.20
		8	7	19.92	19.88	19.80	20.20
		15	0	19.89	19.89	19.85	20.20
	16QAM	1	0	20.16	19.99	20.11	20.20
		1	7	20.01	19.60	20.16	20.20
		1	14	20.07	19.79	19.95	20.20
		8	0	19.87	19.88	19.87	20.20
		8	4	19.91	19.78	19.82	20.20
		8	7	19.88	19.84	19.78	20.20
		15	0	19.81	19.87	19.85	20.20
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20425/826.5	20525/836.5	20625/846.5	
5MHz	QPSK	1	0	19.88	19.93	19.83	20.20
		1	13	19.68	19.63	19.83	20.20
		1	24	19.90	19.80	19.72	20.20
		12	0	19.91	19.93	19.86	20.20
		12	6	19.93	19.81	19.82	20.20
		12	13	19.90	19.86	19.80	20.20
		25	0	19.87	19.89	19.84	20.20
	16QAM	1	0	20.12	19.93	20.08	20.20
		1	13	20.00	19.61	20.11	20.20
		1	24	20.05	19.75	19.93	20.20
		12	0	19.83	19.88	19.85	20.20
		12	6	19.87	19.72	19.79	20.20
		12	13	19.87	19.83	19.73	20.20
		25	0	19.78	19.85	19.80	20.20
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20450/829	20525/836.5	20600/844	
10MHz	QPSK	1	0	19.85	19.87	19.79	20.20
		1	25	19.67	19.59	19.80	20.20
		1	49	19.86	19.76	19.66	20.20
		25	0	19.88	19.85	19.81	20.20
		25	13	19.89	19.74	19.76	20.20
		25	25	19.86	19.82	19.73	20.20



	16QAM	50	0	19.87	19.81	19.78	20.20
		1	0	20.08	19.92	20.03	20.20
		1	25	19.95	19.57	20.10	20.20
		1	49	20.02	19.72	19.89	20.20
		25	0	19.82	19.83	19.82	20.20
		25	13	19.84	19.70	19.74	20.20
		25	25	19.83	19.75	19.71	20.20
		50	0	19.77	19.79	19.77	20.20

LTE FDD Band 5 Hotspot				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20407/824.7	20525/836.5	20643/848.3	
1.4MHz	QPSK	1	0	21.41	21.45	21.37	21.90
		1	2	21.40	21.22	21.06	21.90
		1	5	21.48	21.32	21.27	21.90
		3	0	21.43	21.45	21.35	21.90
		3	2	21.40	21.33	21.24	21.90
		3	3	21.46	21.37	21.32	21.90
		6	0	21.44	21.41	21.38	21.90
	16QAM	1	0	21.67	21.68	21.44	21.90
		1	2	21.65	21.42	21.85	21.90
		1	5	21.57	21.74	21.42	21.90
		3	0	21.27	21.25	21.19	21.90
		3	2	21.36	21.17	21.20	21.90
		3	3	21.40	21.24	21.08	21.90
		6	0	20.85	20.90	20.73	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20415/825.5	20525/836.5	20635/847.5	
3MHz	QPSK	1	0	21.43	21.46	21.40	21.90
		1	7	21.43	21.27	21.10	21.90
		1	14	21.50	21.36	21.30	21.90
		8	0	21.46	21.50	21.39	21.90
		8	4	21.43	21.38	21.28	21.90
		8	7	21.48	21.41	21.37	21.90
		15	0	21.48	21.43	21.42	21.90
	16QAM	1	0	21.69	21.71	21.46	21.90
		1	7	21.68	21.46	21.88	21.90
		1	14	21.60	21.76	21.45	21.90
		8	0	20.90	20.90	20.83	21.40
		8	4	20.98	20.81	20.83	21.40
		8	7	21.03	20.89	20.72	21.40
		15	0	20.88	20.95	20.77	21.40



Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20425/826.5	20525/836.5	20625/846.5	
5MHz	QPSK	1	0	21.42	21.42	21.38	21.90
		1	13	21.41	21.26	21.07	21.90
		1	24	21.47	21.31	21.26	21.90
		12	0	21.44	21.46	21.36	21.90
		12	6	21.40	21.33	21.24	21.90
		12	13	21.45	21.38	21.33	21.90
		25	0	21.46	21.39	21.37	21.90
	16QAM	1	0	21.64	21.69	21.44	21.90
		1	13	21.66	21.43	21.86	21.90
		1	24	21.57	21.72	21.42	21.90
		12	0	20.87	20.88	20.80	21.40
		12	6	20.95	20.76	20.79	21.40
		12	13	21.01	20.85	20.69	21.40
		25	0	20.85	20.90	20.73	21.40
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20450/829	20525/836.5	20600/844	
10MHz	QPSK	1	0	21.39	21.38	21.35	21.90
		1	25	21.40	21.22	21.05	21.90
		1	49	21.45	21.30	21.23	21.90
		25	0	21.41	21.41	21.32	21.90
		25	13	21.38	21.29	21.21	21.90
		25	25	21.42	21.33	21.29	21.90
		50	0	21.43	21.34	21.33	21.90
	16QAM	1	0	21.87	21.65	21.39	21.90
		1	25	21.62	21.41	21.82	21.90
		1	49	21.55	21.69	21.40	21.90
		25	0	20.84	20.84	20.77	21.40
		25	13	20.92	20.74	20.76	21.40
		25	25	20.98	20.80	20.65	21.40
		50	0	20.83	20.86	20.70	21.40

LTE FDD Band 7 Receiver off				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	19.04	19.21	19.39	19.60
		1	13	18.85	19.35	18.76	19.60
		1	24	19.20	19.43	19.04	19.60
		12	0	19.00	19.32	19.14	19.60



		12	6	18.91	19.41	19.01	19.60
		12	13	19.06	19.50	18.92	19.60
		25	0	19.10	19.40	19.06	19.60
	16QAM	1	0	19.07	19.37	19.44	19.60
		1	13	19.05	19.39	19.25	19.60
		1	24	19.13	19.46	19.22	19.60
		12	0	18.97	19.25	19.11	19.60
		12	6	18.87	19.39	18.89	19.60
		12	13	18.98	19.41	18.85	19.60
		25	0	19.03	19.30	18.91	19.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	19.06	19.22	19.42	19.60
		1	25	18.88	19.40	18.80	19.60
		1	49	19.22	19.47	19.07	19.60
		25	0	19.03	19.37	19.18	19.60
		25	13	18.94	19.46	19.05	19.60
		25	25	19.08	19.44	18.97	19.60
		50	0	19.14	19.42	19.10	19.60
	16QAM	1	0	19.09	19.40	19.46	19.60
		1	25	19.08	19.43	19.28	19.60
		1	49	19.16	19.48	19.25	19.60
		25	0	19.00	19.30	19.15	19.60
		25	13	18.89	19.43	18.92	19.60
		25	25	19.01	19.46	18.89	19.60
		50	0	19.06	19.35	18.95	19.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	19.05	19.18	19.40	19.60
		1	38	18.86	19.39	18.77	19.60
		1	74	19.19	19.42	19.03	19.60
		36	0	19.01	19.33	19.15	19.60
		36	18	18.91	19.41	19.01	19.60
		36	39	19.05	19.51	18.93	19.60
		75	0	19.12	19.38	19.05	19.60
	16QAM	1	0	19.04	19.38	19.44	19.60
		1	38	19.06	19.40	19.26	19.60
		1	74	19.13	19.44	19.22	19.60
		36	0	18.97	19.28	19.12	19.60
		36	18	18.86	19.38	18.88	19.60
		36	39	18.99	19.42	18.86	19.60
		75	0	19.03	19.30	18.91	19.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up



				20850/2510	21100/2535	21350/2560	Limit
20MHz	QPSK	1	0	19.02	19.14	19.37	19.60
		1	50	18.85	19.35	18.75	19.60
		1	99	19.17	19.41	19.00	19.60
		50	0	18.98	19.28	19.11	19.60
		50	25	18.89	19.37	18.98	19.60
		50	50	19.02	19.46	18.89	19.60
		100	0	19.09	19.33	19.01	19.60
	16QAM	1	0	19.32	19.34	19.39	19.60
		1	50	19.02	19.38	19.22	19.60
		1	99	19.11	19.41	19.20	19.60
		50	0	18.94	19.24	19.09	19.60
		50	25	18.83	19.36	18.85	19.60
		50	50	18.96	19.37	18.82	19.60
		100	0	19.01	19.26	18.88	19.60

LTE FDD Band 7 hotspot/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	17.51	17.79	17.78	18.10
		1	13	17.37	17.62	17.51	18.10
		1	24	17.76	17.99	17.49	18.10
		12	0	17.51	17.79	17.61	18.10
		12	6	17.41	17.86	17.46	18.10
		12	13	17.55	17.94	17.50	18.10
		25	0	17.59	17.93	17.51	18.10
	16QAM	1	0	17.59	17.99	17.87	18.10
		1	13	17.57	17.90	17.76	18.10
		1	24	17.89	18.00	17.97	18.10
		12	0	17.49	17.78	17.60	18.10
		12	6	17.41	17.85	17.46	18.10
		12	13	17.43	17.93	17.47	18.10
		25	0	17.52	17.78	17.51	18.10
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	17.53	17.80	17.81	18.10
		1	25	17.40	17.67	17.55	18.10
		1	49	17.78	18.03	17.52	18.10
		25	0	17.54	17.84	17.65	18.10
		25	13	17.44	17.91	17.50	18.10
		25	25	17.57	17.98	17.55	18.10
		50	0	17.63	17.95	17.55	18.10



	16QAM	1	0	17.61	18.02	17.89	18.10
		1	25	17.60	17.94	17.79	18.10
		1	49	17.92	18.02	18.00	18.10
		25	0	17.52	17.83	17.64	18.10
		25	13	17.43	17.89	17.49	18.10
		25	25	17.46	17.98	17.51	18.10
		50	0	17.55	17.83	17.55	18.10
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	17.52	17.76	17.79	18.10
		1	38	17.38	17.66	17.52	18.10
		1	74	17.75	17.98	17.48	18.10
		36	0	17.52	17.80	17.62	18.10
		36	18	17.41	17.86	17.46	18.10
		36	39	17.54	17.95	17.51	18.10
		75	0	17.61	17.91	17.50	18.10
	16QAM	1	0	17.56	18.00	17.87	18.10
		1	38	17.58	17.91	17.77	18.10
		1	74	17.89	17.98	17.97	18.10
		36	0	17.49	17.81	17.61	18.10
		36	18	17.40	17.84	17.45	18.10
		36	39	17.44	17.94	17.48	18.10
		75	0	17.52	17.78	17.51	18.10
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20850/2510	21100/2535	21350/2560	
20MHz	QPSK	1	0	17.49	17.72	17.76	18.10
		1	50	17.37	17.62	17.50	18.10
		1	99	17.73	17.97	17.45	18.10
		50	0	17.49	17.75	17.58	18.10
		50	25	17.39	17.82	17.43	18.10
		50	50	17.51	17.90	17.47	18.10
		100	0	17.58	17.86	17.46	18.10
	16QAM	1	0	17.98	17.96	17.82	18.10
		1	50	17.54	17.89	17.73	18.10
		1	99	17.87	17.95	17.95	18.10
		50	0	17.46	17.77	17.58	18.10
		50	25	17.37	17.82	17.42	18.10
		50	50	17.41	17.89	17.44	18.10
		100	0	17.50	17.74	17.48	18.10

LTE FDD Band 7				Output Power(dBm)	Tune-up Limit
Receiver on					
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)	



				20775/2502.5	21100/2535	21425/2567.5	
5MHz	QPSK	1	0	17.17	17.23	17.27	17.60
		1	13	16.90	17.26	16.67	17.60
		1	24	17.20	17.42	17.06	17.60
		12	0	17.05	17.29	17.12	17.60
		12	6	17.00	17.37	17.01	17.60
		12	13	17.09	17.47	17.10	17.60
		25	0	16.98	17.46	17.07	17.60
	16QAM	1	0	16.97	17.17	17.29	17.60
		1	13	16.95	17.30	16.86	17.60
		1	24	17.25	17.45	17.01	17.60
		12	0	17.01	17.24	17.09	17.60
		12	6	16.94	17.35	17.00	17.60
		12	13	17.02	17.43	16.85	17.60
		25	0	16.93	17.37	16.97	17.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20800/2505	21100/2535	21400/2565	
10MHz	QPSK	1	0	17.19	17.24	17.30	17.60
		1	25	16.93	17.31	16.71	17.60
		1	49	17.22	17.46	17.09	17.60
		25	0	17.08	17.34	17.16	17.60
		25	13	17.03	17.42	17.05	17.60
		25	25	17.11	17.51	17.15	17.60
		50	0	17.02	17.48	17.11	17.60
	16QAM	1	0	16.99	17.20	17.31	17.60
		1	25	16.98	17.34	16.89	17.60
		1	49	17.28	17.47	17.04	17.60
		25	0	17.04	17.29	17.13	17.60
		25	13	16.96	17.39	17.03	17.60
		25	25	17.05	17.48	16.89	17.60
		50	0	16.96	17.42	17.01	17.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20825/2507.5	21100/2535	21375/2562.5	
15MHz	QPSK	1	0	17.18	17.20	17.28	17.60
		1	38	16.91	17.30	16.68	17.60
		1	74	17.19	17.41	17.05	17.60
		36	0	17.06	17.30	17.13	17.60
		36	18	17.00	17.37	17.01	17.60
		36	39	17.08	17.48	17.11	17.60
		75	0	17.00	17.44	17.06	17.60
	16QAM	1	0	16.94	17.18	17.29	17.60
		1	38	16.96	17.31	16.87	17.60
		1	74	17.25	17.43	17.01	17.60



		36	0	17.01	17.27	17.10	17.60
		36	18	16.93	17.34	16.99	17.60
		36	39	17.03	17.44	16.86	17.60
		75	0	16.93	17.37	16.97	17.60
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				20850/2510	21100/2535	21350/2560	
20MHz	QPSK	1	0	17.15	17.16	17.25	17.60
		1	50	16.90	17.26	16.66	17.60
		1	99	17.17	17.40	17.02	17.60
		50	0	17.03	17.25	17.09	17.60
		50	25	16.98	17.33	16.98	17.60
		50	50	17.05	17.43	17.07	17.60
		100	0	16.97	17.39	17.02	17.60
	16QAM	1	0	17.18	17.14	17.24	17.60
		1	50	16.92	17.29	16.83	17.60
		1	99	17.23	17.40	16.99	17.60
		50	0	16.98	17.23	17.07	17.60
		50	25	16.90	17.32	16.96	17.60
		50	50	17.00	17.39	16.82	17.60
		100	0	16.91	17.33	16.94	17.60

LTE FDD Band 66 Receiver off				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				131979/1710.7	132322/1745	132665/1779.3	
1.4MHz	QPSK	1	0	23.02	22.90	23.03	23.50
		1	2	22.93	22.70	22.69	23.50
		1	5	22.87	22.77	23.02	23.50
		3	0	22.88	22.90	22.83	23.50
		3	2	22.78	22.85	22.82	23.50
		3	3	22.52	22.75	22.91	23.50
		6	0	22.01	21.95	21.93	22.50
	16QAM	1	0	21.99	22.18	22.22	22.50
		1	2	21.97	21.88	21.82	22.50
		1	5	22.02	21.90	22.22	22.50
		3	0	22.03	22.13	22.04	22.50
		3	2	21.94	22.06	22.02	22.50
		3	3	21.70	22.02	22.10	22.50
		6	0	21.12	21.25	21.18	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131987/1711.5	132322/1745	132657/1778.5	
3MHz	QPSK	1	0	23.04	22.94	23.06	23.50



		1	7	22.91	22.73	22.73	23.50
		1	14	22.90	22.82	23.06	23.50
		8	0	21.98	22.02	21.96	22.50
		8	4	21.90	21.95	21.94	22.50
		8	7	21.62	21.86	22.01	22.50
		15	0	22.01	21.99	21.96	22.50
		1	0	22.02	22.20	22.25	22.50
	16QAM	1	7	22.00	21.88	21.86	22.50
		1	14	22.04	21.94	22.25	22.50
		8	0	21.14	21.26	21.16	21.50
		8	4	21.05	21.19	21.14	21.50
		8	7	20.80	21.14	21.23	21.50
		15	0	21.15	21.29	21.21	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131997/1712.5	132322/1745	132647/1777.5	
5MHz	QPSK	1	0	23.03	22.93	23.05	23.50
		1	13	22.92	22.74	22.74	23.50
		1	24	22.89	22.81	23.05	23.50
		12	0	21.98	22.02	21.96	22.50
		12	6	21.91	21.96	21.93	22.50
		12	13	21.62	21.88	22.02	22.50
		25	0	22.05	22.00	21.98	22.50
	16QAM	1	0	22.01	22.19	22.24	22.50
		1	13	22.00	21.90	21.86	22.50
		1	24	22.04	21.94	22.24	22.50
		12	0	21.15	21.27	21.17	21.50
		12	6	21.04	21.18	21.13	21.50
		12	13	20.80	21.14	21.23	21.50
		25	0	21.16	21.30	21.20	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132022/1715	132322/1745	132622/1775	
10MHz	QPSK	1	0	23.01	22.92	23.02	23.50
		1	25	22.89	22.69	22.70	23.50
		1	49	22.87	22.77	23.02	23.50
		25	0	21.95	21.97	21.92	22.50
		25	13	21.88	21.91	21.89	22.50
		25	25	21.60	21.84	21.97	22.50
		50	0	22.01	21.98	21.94	22.50
	16QAM	1	0	21.99	22.16	22.22	22.50
		1	25	21.97	21.86	21.83	22.50
		1	49	22.01	21.92	22.21	22.50
		25	0	21.12	21.22	21.13	21.50
		25	13	21.02	21.14	21.10	21.50



		25	25	20.77	21.09	21.19	21.50
		50	0	21.13	21.25	21.16	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132047/1717.5	132322/1745	132597/1772.5	
15MHz	QPSK	1	0	23.02	22.89	23.03	23.50
		1	38	22.90	22.73	22.71	23.50
		1	74	22.86	22.76	23.01	23.50
		36	0	21.96	21.98	21.93	22.50
		36	18	21.88	21.91	21.89	22.50
		36	39	21.59	21.85	21.98	22.50
		75	0	22.03	21.96	21.93	22.50
	16QAM	1	0	21.96	22.17	22.22	22.50
		1	38	21.98	21.87	21.84	22.50
		1	74	22.01	21.90	22.21	22.50
		36	0	21.12	21.25	21.14	21.50
		36	18	21.01	21.13	21.09	21.50
		36	39	20.78	21.10	21.20	21.50
		75	0	21.13	21.25	21.16	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132072/1720	132322/1745	132572/1770	
20MHz	QPSK	1	0	22.99	22.85	23.00	23.50
		1	50	22.89	22.69	22.69	23.50
		1	99	22.84	22.75	22.98	23.50
		50	0	21.93	21.93	21.89	22.50
		50	25	21.86	21.87	21.86	22.50
		50	50	21.56	21.80	21.94	22.50
		100	0	22.00	21.91	21.89	22.50
	16QAM	1	0	22.15	22.13	22.17	22.50
		1	50	21.94	21.85	21.80	22.50
		1	99	21.99	21.87	22.19	22.50
		50	0	21.09	21.21	21.11	21.50
		50	25	20.98	21.11	21.06	21.50
		50	50	20.75	21.05	21.16	21.50
		100	0	21.11	21.21	21.13	21.50

LTE FDD Band 66 hotspot/Receiver off- Simultaneous with Wi-Fi				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				131979/1710.7	132322/1745	132665/1779.3	
1.4MHz	QPSK	1	0	21.15	21.24	21.27	22.00
		1	2	21.11	21.07	21.05	22.00
		1	5	21.34	21.27	21.22	22.00



		3	0	21.43	21.47	21.53	22.00
		3	2	21.31	21.27	21.45	22.00
		3	3	21.48	21.53	21.72	22.00
		6	0	21.10	20.89	21.00	22.00
	16QAM	1	0	21.18	21.36	21.47	22.00
		1	2	21.16	21.09	21.13	22.00
		1	5	21.32	21.21	21.34	22.00
		3	0	21.45	21.34	21.48	22.00
		3	2	21.51	21.43	21.56	22.00
		3	3	21.49	21.42	21.53	22.00
		6	0	20.50	20.45	20.58	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131987/1711.5	132322/1745	132657/1778.5	
3MHz	QPSK	1	0	21.15	21.23	21.27	22.00
		1	7	21.08	21.10	21.07	22.00
		1	14	21.33	21.26	21.21	22.00
		8	0	21.01	21.05	21.13	22.00
		8	4	20.91	20.83	21.02	22.00
		8	7	21.05	21.13	21.29	22.00
		15	0	21.12	20.90	21.00	22.00
	16QAM	1	0	21.15	21.35	21.47	22.00
		1	7	21.17	21.08	21.15	22.00
		1	14	21.31	21.21	21.33	22.00
		8	0	20.54	20.46	20.58	21.50
		8	4	20.58	20.50	20.63	21.50
		8	7	20.57	20.50	20.63	21.50
		15	0	20.51	20.45	20.56	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131997/1712.5	132322/1745	132647/1777.5	
5MHz	QPSK	1	0	21.16	21.27	21.29	22.00
		1	13	21.10	21.11	21.10	22.00
		1	24	21.36	21.31	21.25	22.00
		12	0	21.03	21.09	21.16	22.00
		12	6	20.94	20.88	21.06	22.00
		12	13	21.08	21.16	21.33	22.00
		25	0	21.14	20.94	21.05	22.00
	16QAM	1	0	21.20	21.37	21.49	22.00
		1	13	21.19	21.11	21.17	22.00
		1	24	21.34	21.25	21.36	22.00
		12	0	20.57	20.48	20.61	21.50
		12	6	20.61	20.55	20.67	21.50
		12	13	20.59	20.54	20.66	21.50
		25	0	20.54	20.50	20.60	21.50



Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132022/1715	132322/1745	132622/1775	
10MHz	QPSK	1	0	21.14	21.26	21.26	22.00
		1	25	21.07	21.06	21.06	22.00
		1	49	21.34	21.27	21.22	22.00
		25	0	21.00	21.04	21.12	22.00
		25	13	20.91	20.83	21.02	22.00
		25	25	21.06	21.12	21.28	22.00
		50	0	21.10	20.92	21.01	22.00
	16QAM	1	0	21.18	21.34	21.47	22.00
		1	25	21.16	21.07	21.14	22.00
		1	49	21.31	21.23	21.33	22.00
		25	0	20.54	20.43	20.57	21.50
		25	13	20.59	20.51	20.64	21.50
		25	25	20.56	20.49	20.62	21.50
		50	0	20.51	20.45	20.56	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132047/1717.5	132322/1745	132597/1772.5	
15MHz	QPSK	1	0	21.17	21.28	21.30	22.00
		1	38	21.09	21.10	21.09	22.00
		1	74	21.37	21.32	21.26	22.00
		36	0	21.03	21.09	21.16	22.00
		36	18	20.93	20.87	21.07	22.00
		36	39	21.08	21.14	21.32	22.00
		75	0	21.10	20.93	21.03	22.00
	16QAM	1	0	21.21	21.38	21.50	22.00
		1	38	21.19	21.09	21.17	22.00
		1	74	21.34	21.25	21.37	22.00
		36	0	20.56	20.47	20.60	21.50
		36	18	20.62	20.56	20.68	21.50
		36	39	20.59	20.54	20.66	21.50
		75	0	20.53	20.49	20.61	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132072/1720	132322/1745	132572/1770	
20MHz	QPSK	1	0	21.12	21.19	21.24	22.00
		1	50	21.07	21.06	21.05	22.00
		1	99	21.31	21.25	21.18	22.00
		50	0	20.98	21.00	21.09	22.00
		50	25	20.89	20.79	20.99	22.00
		50	50	21.02	21.08	21.25	22.00
		100	0	21.09	20.85	20.96	22.00
	16QAM	1	0	21.42	21.31	21.42	22.00
		1	50	21.13	21.06	21.11	22.00



		1	99	21.29	21.18	21.31	22.00
		50	0	20.51	20.42	20.55	21.50
		50	25	20.55	20.48	20.60	21.50
		50	50	20.54	20.45	20.59	21.50
		100	0	20.49	20.41	20.53	21.50

LTE FDD Band 66 Receiver on				Output Power(dBm)			Tune-up Limit
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			
				131979/1710.7	132322/1745	132665/1779.3	
1.4MHz	QPSK	1	0	21.26	21.43	21.29	22.50
		1	2	21.04	21.07	21.20	22.50
		1	5	21.22	21.23	21.54	22.50
		3	0	22.13	22.22	22.54	22.50
		3	2	22.12	22.19	22.28	22.50
		3	3	22.19	22.15	22.28	22.50
		6	0	21.25	21.27	21.41	22.50
	16QAM	1	0	22.08	22.32	22.35	22.50
		1	2	22.06	21.96	21.91	22.50
		1	5	22.13	22.02	22.30	22.50
		3	0	22.11	22.19	22.15	22.50
		3	2	22.05	22.17	22.14	22.50
		3	3	21.77	22.15	22.20	22.50
		6	0	21.18	21.37	21.29	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				1319871711.5	132322/1745	132657/1778.5	
3MHz	QPSK	1	0	21.26	21.42	21.29	22.50
		1	7	21.01	21.10	21.22	22.50
		1	14	21.21	21.22	21.53	22.50
		8	0	21.21	21.30	21.64	22.50
		8	4	21.22	21.25	21.35	22.50
		8	7	21.26	21.25	21.35	22.50
		15	0	21.27	21.28	21.41	22.50
	16QAM	1	0	22.05	22.31	22.35	22.50
		1	7	22.07	21.95	21.93	22.50
		1	14	22.12	22.02	22.29	22.50
		8	0	21.20	21.31	21.25	21.50
		8	4	21.12	21.24	21.21	21.50
		8	7	20.85	21.23	21.30	21.50
		15	0	21.19	21.37	21.27	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				131997/1712.5	132322/1745	132647/1777.5	
5MHz	QPSK	1	0	21.27	21.46	21.31	22.50



		1	13	21.03	21.11	21.25	22.50
		1	24	21.24	21.27	21.57	22.50
		12	0	21.23	21.34	21.67	22.50
		12	6	21.25	21.30	21.39	22.50
		12	13	21.29	21.28	21.39	22.50
		25	0	21.29	21.32	21.46	22.50
	16QAM	1	0	22.10	22.33	22.37	22.50
		1	13	22.09	21.98	21.95	22.50
		1	24	22.15	22.06	22.32	22.50
		12	0	21.23	21.33	21.28	21.50
		12	6	21.15	21.29	21.25	21.50
		12	13	20.87	21.27	21.33	21.50
		25	0	21.22	21.42	21.31	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132022/1715	132322/1745	132622/1775	
10MHz	QPSK	1	0	21.28	21.47	21.32	22.50
		1	25	21.02	21.10	21.24	22.50
		1	49	21.25	21.28	21.58	22.50
		25	0	21.23	21.34	21.67	22.50
		25	13	21.24	21.29	21.40	22.50
		25	25	21.29	21.26	21.38	22.50
	16QAM	50	0	21.25	21.31	21.44	22.50
		1	0	22.11	22.34	22.38	22.50
		1	25	22.09	21.96	21.95	22.50
		1	49	22.15	22.06	22.33	22.50
		25	0	21.22	21.32	21.27	21.50
		25	13	21.16	21.30	21.26	21.50
		25	25	20.87	21.27	21.33	21.50
		50	0	21.21	21.41	21.32	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132047/1717.5	132322/1745	132597/1772.5	
15MHz	QPSK	1	0	21.25	21.45	21.28	22.50
		1	38	21.00	21.06	21.21	22.50
		1	74	21.22	21.23	21.54	22.50
		36	0	21.20	21.29	21.63	22.50
		36	18	21.22	21.25	21.35	22.50
		36	39	21.27	21.24	21.34	22.50
		75	0	21.25	21.30	21.42	22.50
	16QAM	1	0	22.08	22.30	22.35	22.50
		1	38	22.06	21.94	21.92	22.50
		1	74	22.12	22.04	22.29	22.50
		36	0	21.20	21.28	21.24	21.50
		36	18	21.13	21.25	21.22	21.50



		36	39	20.84	21.22	21.29	21.50
		75	0	21.19	21.37	21.27	21.50
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)			Tune-up Limit
				132072/1720	132322/1745	132572/1770	
20MHz	QPSK	1	0	21.23	21.38	21.26	22.50
		1	50	21.00	21.06	21.20	22.50
		1	99	21.19	21.21	21.50	22.50
		50	0	21.18	21.25	21.60	22.50
		50	25	21.20	21.21	21.32	22.50
		50	50	21.23	21.20	21.31	22.50
		100	0	21.24	21.23	21.37	22.50
	16QAM	1	0	22.28	22.27	22.30	22.50
		1	50	22.03	21.93	21.89	22.50
		1	99	22.10	21.99	22.27	22.50
		50	0	21.17	21.27	21.22	21.50
		50	25	21.09	21.22	21.18	21.50
		50	50	20.82	21.18	21.26	21.50
		100	0	21.17	21.33	21.24	21.50

9.4 WLAN Mode

Wi-Fi 2.4G receiver off Mode	Channel /Frequency(MHz)	Maximum Output Power (dBm)	
		Tune-up	Meas.
802.11b (1M)	1/2412	18.50	17.37
	6/2437	18.50	17.58
	11/2462	18.50	17.28
802.11g (6M)	1/2412	11.00	10.40
	2/2417	14.00	13.48
	4/2427	17.00	16.62
	5/2432	19.00	18.35
	6/2437	19.00	18.15
	7/2442	19.00	18.03
	10/2457	15.00	13.95
	11/2462	12.00	11.09
802.11n-HT20 (MCS0)	1/2412	11.00	10.34
	2/2417	14.00	13.53
	5/2432	17.00	16.45
	6/2437	17.00	16.24
	7/2442	17.00	16.07
	10/2457	15.00	13.90
	11/2462	12.00	11.11
802.11n-HT40 (MCS0)	3/2422	8.00	7.12
	4/2427	10.00	9.26
	6/2437	13.00	12.17
	8/2447	12.00	11.05
	9/2452	10.00	9.01
Note: Initial test configuration is 802.11b mode.			

Wi-Fi 2.4G receiver on	Channel /Frequency(MHz)	Maximum Output Power (dBm)	
		Tune-up	Meas.
Mode			
802.11b (1M)	1/2412	12.00	10.91
	6/2437	12.00	11.23
	11/2462	12.00	11.00
802.11g (6M)	1/2412	11.00	10.26
	6/2437	12.00	11.32
	7/2442	12.00	11.11
	11/2462	12.00	11.08
802.11n-HT20 (MCS0)	1/2412	11.00	10.30
	6/2437	12.00	11.39
	7/2442	12.00	11.10
	11/2462	12.00	11.24
802.11n-HT40 (MCS0)	3/2422	8.00	7.12
	5/2432	10.00	9.26
	6/2437	12.00	11.13
	7/2442	12.00	11.15
	8/2447	12.00	11.05
	9/2452	10.00	9.01
Note: Initial test configuration is 802.11b mode.			

9.5 Bluetooth Mode

BT	Output Power(dBm)			Tune-up Limit (dBm)
	Channel/Frequency(MHz)			
	Ch 0/2402 MHz	Ch 39/2441 MHz	Ch 78/2480 MHz	
GFSK	11.24	11.39	11.56	12.50
π/4DQPSK	10.34	10.54	10.44	11.00
8DPSK	10.39	10.36	10.27	11.00
BLE	Ch 0/2402 MHz	Ch 19/2440 MHz	Ch 39/2480 MHz	Tune-up Limit (dBm)
GFSK(1M)	8.72	7.83	8.01	10.00
GFSK(2M)	6.87	6.03	6.31	10.00

10 Measured and Reported (Scaled) SAR Results

10.1 EUT Antenna Locations

The Detailed Antenna Locations refer to *Antenna Locations*.

Overall (Length x Width): 165.7 mm x 76.8 mm						
Overall Diagonal: 173.3 mm/Display Diagonal: 166mm						
Distance of the Antenna to the EUT surface/edge						
Antenna	Back Side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
Main-Antenna	<25mm	<25mm	<25mm	<25mm	>25mm	<25mm
Second-Antenna	<25mm	<25mm	<25mm	>25mm	<25mm	>25mm
BT/Wi-Fi Antenna	<25mm	<25mm	>25mm	<25mm	<25mm	>25mm
Hotspot mode, Positions for SAR tests						
Mode	Back Side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
Main-Antenna	Yes	Yes	Yes	Yes	N/A	Yes
Second-Antenna	Yes	Yes	Yes	N/A	Yes	N/A
BT/Wi-Fi Antenna	Yes	Yes	N/A	Yes	Yes	N/A
Note: 1. Per KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge. 2. For smart phones with an overall diagonal dimension is 166mm. Per KDB 648474 D04, for smart phones with a display diagonal dimension $> 15.0\text{ cm}$ or an overall diagonal dimension $> 16.0\text{ cm}$, product specific 10-g SAR must be tested as a phablet to determine SAR compliance. For Phablet, Since hotspot mode 1-g reported SAR $< 1.2\text{ W/kg}$, product specific 10-g SAR is no required. 3. Per FCC KDB 447498 D01, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is: a) $\leq 0.8\text{ W/kg}$ or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is $\leq 100\text{MHz}$ b) $\leq 0.6\text{ W/kg}$ or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz. c) $\leq 0.4\text{ W/kg}$ or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is $\geq 200\text{ MHz}$. 4. When the original highest measured SAR is $\geq 0.80\text{ W/kg}$, the measurement was repeated once. 5. Per FCC KDB Publication 648474 D04, SAR was evaluated without a headset connected to the device. Since the reported SAR was $\leq 1.2\text{ W/kg}$, no additional SAR evaluations using a headset cable were required.						



10.2 Measured SAR Results

Table 7: GSM 850 (Main-antenna)

Test Position	Cover Type	Time slot	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.012	0.098	1.25	0.015	/
Left Tilt	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.012	0.053	1.25	0.016	/
Right Cheek	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.013	0.066	1.25	0.016	14
Right Tilt	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.009	0.028	1.25	0.011	/
Right Cheek	Battery2	GSM	1:8.3	190/836.6	33.50	32.53	0.010	0.052	1.25	0.013	/
Right Cheek	Battery3	GSM	1:8.3	190/836.6	33.50	32.53	0.010	0.020	1.25	0.012	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.044	0.060	1.25	0.055	15
Front Side	standard	GSM	1:8.3	190/836.6	33.50	32.53	0.032	0.022	1.25	0.040	/
Back Side	Battery2	GSM	1:8.3	190/836.6	33.50	32.53	0.038	0.033	1.25	0.048	/
Back Side	Battery3	GSM	1:8.3	190/836.6	33.50	32.53	0.041	-0.020	1.25	0.051	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	4Txslots	1:2.07	190/836.6	27.40	26.67	0.111	-0.030	1.18	0.131	16
Front Side	standard	4Txslots	1:2.07	190/836.6	27.40	26.67	0.098	0.054	1.18	0.116	/
Left Edge	standard	4Txslots	1:2.07	190/836.6	27.40	26.67	0.049	0.037	1.18	0.058	/
Right Edge	standard	4Txslots	1:2.07	190/836.6	27.40	26.67	0.000	-0.100	1.18	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	4Txslots	1:2.07	190/836.6	27.40	26.67	0.108	-0.042	1.18	0.128	/
Back Side	Battery2	4Txslots	1:2.07	190/836.6	27.40	26.67	0.105	-0.037	1.18	0.124	/
Back Side	Battery3	4Txslots	1:2.07	190/836.6	27.40	26.67	0.099	0.052	1.18	0.117	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2.When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.											



Table 8: GSM 1900(Main-antenna)

Test Position	Cover Type	Time slot	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	GSM	1:8.3	661/1880	31.00	30.14	0.078	-0.058	1.22	0.095	17
Left Tilt	standard	GSM	1:8.3	661/1880	31.00	30.14	0.038	-0.130	1.22	0.046	/
Right Cheek	standard	GSM	1:8.3	661/1880	31.00	30.14	0.071	0.068	1.22	0.087	/
Right Tilt	standard	GSM	1:8.3	661/1880	31.00	30.14	0.034	-0.032	1.22	0.042	/
Left Cheek	Battery2	GSM	1:8.3	661/1880	31.00	30.14	0.072	-0.031	1.22	0.088	/
Left Cheek	Battery3	GSM	1:8.3	661/1880	31.00	30.14	0.068	-0.010	1.22	0.083	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	GSM	1:8.3	661/1880	31.00	30.14	0.173	-0.080	1.22	0.211	18
Front Side	standard	GSM	1:8.3	661/1880	31.00	30.14	0.096	0.067	1.22	0.117	/
Back Side	Battery2	GSM	1:8.3	661/1880	31.00	30.14	0.168	0.025	1.22	0.205	/
Back Side	Battery3	GSM	1:8.3	661/1880	31.00	30.14	0.161	0.068	1.22	0.196	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	1Txslots	1:8.3	661/1880	31.00	30.23	0.249	0.081	1.19	0.297	/
Front Side	standard	1Txslots	1:8.3	661/1880	31.00	30.23	0.165	0.110	1.19	0.197	/
Left Edge	standard	1Txslots	1:8.3	661/1880	31.00	30.23	0.068	-0.051	1.19	0.081	/
Right Edge	standard	1Txslots	1:8.3	661/1880	31.00	30.23	0.000	-0.100	1.19	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1Txslots	1:8.3	661/1880	31.00	30.23	0.396	-0.129	1.19	0.473	19
Bottom Edge	Battery2	1Txslots	1:8.3	661/1880	31.00	30.23	0.372	-0.015	1.19	0.444	/
Bottom Edge	Battery3	1Txslots	1:8.3	661/1880	31.00	30.23	0.354	0.020	1.19	0.423	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2.When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.											



Table 9: UMTS Band II (Main-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.183	-0.029	1.35	0.246	20
Left Tilt	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.087	-0.040	1.35	0.116	/
Right Cheek	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.132	0.100	1.35	0.178	/
Right Tilt	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.089	0.010	1.35	0.119	/
Left Cheek	SIM2	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.176	0.010	1.35	0.237	/
Left Cheek	Battery2	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.174	0.022	1.35	0.234	/
Left Cheek	Battery3	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.165	-0.065	1.35	0.222	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.451	-0.030	1.35	0.607	21
Front Side	standard	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.312	0.025	1.35	0.420	/
Back Side	SIM2	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.442	0.028	1.35	0.595	/
Back Side	Battery2	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.448	0.091	1.35	0.603	/
Back Side	Battery3	RMC 12.2K	1:1	9400/1880	25.00	23.71	0.439	0.041	1.35	0.591	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.525	0.086	1.23	0.646	/
Front Side	standard	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.364	0.110	1.23	0.448	/
Left Edge	standard	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.135	-0.078	1.23	0.166	/
Right Edge	standard	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.043	-0.034	1.23	0.053	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.566	0.040	1.23	0.696	22
Bottom Edge	Battery2	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.548	-0.022	1.23	0.674	/
Bottom Edge	Battery3	RMC 12.2K	1:1	9400/1880	23.00	22.10	0.550	0.081	1.23	0.677	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

3. Accessories that do not contain RF transmitters and have been proven to increase the peak SAR by less than 5 %, such as hands-free kits, do not need SAR tests separate from the SAR tests attached to a main EUT configuration.



Test Position	Channel Type	Duty Cycle	Channel Frequency(MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	RMC 12.2K	1:1	9400/1880	25.00	23.00	0.646	1.58	1.024	no
Front Side	RMC 12.2K	1:1	9400/1880	25.00	23.00	0.448	1.58	0.710	no
Left Edge	RMC 12.2K	1:1	9400/1880	25.00	23.00	0.166	1.58	0.263	no
Right Edge	RMC 12.2K	1:1	9400/1880	25.00	23.00	0.053	1.58	0.084	no
Bottom Edge	RMC 12.2K	1:1	9400/1880	25.00	23.00	0.696	1.58	1.104	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 10: UMTS Band IV (Main-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.200	-0.027	1.15	0.230	23
Left Tilt	standard	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.081	-0.040	1.15	0.094	/
Right Cheek	standard	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.121	0.100	1.15	0.139	/
Right Tilt	standard	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.092	0.050	1.15	0.105	/
Left Cheek	Battery2	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.183	0.011	1.15	0.211	/
Left Cheek	Battery3	RMC 12.2K	1:1	1413/1732.6	25.00	24.39	0.192	0.013	1.15	0.221	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	1413/1732.6	24.00	23.40	0.305	-0.040	1.15	0.350	24
Front Side	standard	RMC 12.2K	1:1	1413/1732.6	24.00	23.40	0.179	0.120	1.15	0.206	/
Back Side	Battery2	RMC 12.2K	1:1	1413/1732.6	24.00	23.40	0.287	0.000	1.15	0.330	/
Back Side	Battery3	RMC 12.2K	1:1	1413/1732.6	24.00	23.40	0.296	0.095	1.15	0.340	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.353	0.041	1.15	0.405	/
Front Side	standard	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.205	0.072	1.15	0.235	/
Left Edge	standard	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.044	-0.033	1.15	0.051	/
Right Edge	standard	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.084	-0.026	1.15	0.096	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.463	-0.090	1.15	0.532	25
Bottom Edge	Battery2	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.447	-0.014	1.15	0.513	/
Bottom Edge	Battery3	RMC 12.2K	1:1	1413/1732.6	22.00	21.40	0.452	0.053	1.15	0.519	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.											

Test Position	Channel Type	Duty Cycle	Channel Frequency(MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	RMC 12.2K	1:1	1413/1732.6	24.00	22.00	0.405	1.58	0.642	no
Front Side	RMC 12.2K	1:1	1413/1732.6	24.00	22.00	0.235	1.58	0.373	no
Left Edge	RMC 12.2K	1:1	1413/1732.6	24.00	22.00	0.051	1.58	0.080	no
Right Edge	RMC 12.2K	1:1	1413/1732.6	24.00	22.00	0.096	1.58	0.153	no
Bottom Edge	RMC 12.2K	1:1	1413/1732.6	24.00	22.00	0.532	1.58	0.843	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.									



Table 11: UMTS Band V (Main-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.020	0.099	1.21	0.024	26
Left Tilt	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.006	0.041	1.21	0.007	/
Right Cheek	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.012	0.048	1.21	0.015	/
Right Tilt	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.005	0.029	1.21	0.006	/
Left Cheek	Battery2	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.016	0.033	1.21	0.019	/
Left Cheek	Battery3	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.013	0.010	1.21	0.016	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.073	0.170	1.21	0.088	27
Front Side	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.061	-0.046	1.21	0.074	/
Back Side	Battery2	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.068	-0.021	1.21	0.083	/
Back Side	Battery3	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.070	0.038	1.21	0.085	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.126	0.090	1.21	0.153	28
Front Side	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.111	0.077	1.21	0.135	/
Left Edge	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.059	-0.021	1.21	0.072	/
Right Edge	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.000	-0.100	1.21	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.095	-0.022	1.21	0.115	/
Back Side	Battery2	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.112	0.010	1.21	0.136	/
Back Side	Battery3	RMC 12.2K	1:1	4183/836.6	25.00	24.16	0.119	0.012	1.21	0.144	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.											



Table 12: LTE Band 2 (20MHz, Main-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	50	18700/1860	24.20	23.89	0.174	-0.012	1.07	0.187	29
Left Tilt	standard	1:1	1	50	18700/1860	24.20	23.89	0.069	0.000	1.07	0.074	/
Right Cheek	standard	1:1	1	50	18700/1860	24.20	23.89	0.099	0.080	1.07	0.106	/
Right Tilt	standard	1:1	1	50	18700/1860	24.20	23.89	0.068	-0.049	1.07	0.073	/
Left Cheek	standard	1:1	50%	0	18700/1860	23.20	22.43	0.072	-0.110	1.19	0.086	/
Left Tilt	standard	1:1	50%	0	18700/1860	23.20	22.43	0.072	-0.110	1.19	0.086	/
Right Cheek	standard	1:1	50%	0	18700/1860	23.20	22.43	0.075	0.092	1.19	0.090	/
Right Tilt	standard	1:1	50%	0	18700/1860	23.20	22.43	0.052	0.150	1.19	0.062	/
Left Cheek	Battery2	1:1	1	50	18700/1860	24.20	23.89	0.119	-0.022	1.07	0.128	/
Left Cheek	Battery3	1:1	1	50	18700/1860	24.20	23.89	0.135	0.010	1.07	0.145	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	50	18700/1860	24.20	23.89	0.260	-0.020	1.07	0.279	30
Front Side	standard	1:1	1	50	18700/1860	24.20	23.89	0.153	0.029	1.07	0.164	/
Back Side	standard	1:1	50%	0	18700/1860	23.20	22.43	0.188	-0.027	1.19	0.224	/
Front Side	standard	1:1	50%	0	18700/1860	23.20	22.43	0.120	0.013	1.19	0.143	/
Back Side	Battery2	1:1	1	50	18700/1860	24.20	23.89	0.241	-0.023	1.07	0.259	/
Back Side	Battery3	1:1	1	50	18700/1860	24.20	23.89	0.251	0.025	1.07	0.270	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	0	18700/1860	22.50	21.56	0.517	-0.120	1.24	0.642	/
Front Side	standard	1:1	1	0	18700/1860	22.50	21.56	0.282	-0.098	1.24	0.350	/
Left Edge	standard	1:1	1	0	18700/1860	22.50	21.56	0.124	0.010	1.24	0.154	/
Right Edge	standard	1:1	1	0	18700/1860	22.50	21.56	0.000	0.021	1.24	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	1	0	18700/1860	22.50	21.56	0.568	-0.080	1.24	0.705	31
Back Side	standard	1:1	50%	0	18700/1860	22.50	21.35	0.331	-0.021	1.30	0.431	/
Front Side	standard	1:1	50%	0	18700/1860	22.50	21.35	0.223	0.060	1.30	0.291	/
Left Edge	standard	1:1	50%	0	18700/1860	22.50	21.35	0.099	0.190	1.30	0.129	/
Right Edge	standard	1:1	50%	0	18700/1860	22.50	21.35	0.000	0.028	1.30	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	50%	0	18700/1860	22.50	21.35	0.367	0.022	1.30	0.478	/
Bottom Edge	Battery2	1:1	1	0	18700/1860	22.50	21.56	0.550	-0.030	1.24	0.683	/
Bottom Edge	Battery3	1:1	1	0	18700/1860	22.50	21.56	0.519	-0.011	1.24	0.644	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 50% limit(1g).												



Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	0	18700/1860	24.20	22.50	0.642	1.48	0.949	no
Front Side	QPSK	1:1	1	0	18700/1860	24.20	22.50	0.350	1.48	0.518	no
Left Edge	QPSK	1:1	1	0	18700/1860	24.20	22.50	0.154	1.48	0.228	no
Right Edge	QPSK	1:1	1	0	18700/1860	24.20	22.50	0.000	1.48	0.000	no
Bottom Edge	QPSK	1:1	1	0	18700/1860	24.20	22.50	0.705	1.48	1.043	no
Back Side	QPSK	1:1	50%	0	18700/1860	23.20	22.50	0.431	1.17	0.507	no
Front Side	QPSK	1:1	50%	0	18700/1860	23.20	22.50	0.291	1.17	0.341	no
Left Edge	QPSK	1:1	50%	0	18700/1860	23.20	22.50	0.129	1.17	0.152	no
Right Edge	QPSK	1:1	50%	0	18700/1860	23.20	22.50	0.000	1.17	0.000	no
Bottom Edge	QPSK	1:1	50%	0	18700/1860	23.20	22.50	0.478	1.17	0.562	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 13: LTE Band 4 (20MHz, Main-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-u p (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	0	20300/1745	24.50	23.91	0.182	0.047	1.15	0.208	32
Left Tilt	standard	1:1	1	0	20300/1745	24.50	23.91	0.063	0.021	1.15	0.072	/
Right Cheek	standard	1:1	1	0	20300/1745	24.50	23.91	0.107	0.150	1.15	0.123	/
Right Tilt	standard	1:1	1	0	20300/1745	24.50	23.91	0.062	0.090	1.15	0.071	/
Left Cheek	standard	1:1	50%	0	20300/1745	23.50	22.93	0.164	0.086	1.14	0.187	/
Left Tilt	standard	1:1	50%	0	20300/1745	23.50	22.93	0.057	0.150	1.14	0.065	/
Right Cheek	standard	1:1	50%	0	20300/1745	23.50	22.93	0.095	0.046	1.14	0.108	/
Right Tilt	standard	1:1	50%	0	20300/1745	23.50	22.93	0.053	0.170	1.14	0.060	/
Left Cheek	Battery2	1:1	50%	0	20300/1745	23.50	22.93	0.163	0.032	1.14	0.186	/
Left Cheek	Battery3	1:1	50%	0	20300/1745	23.50	22.93	0.152	0.012	1.14	0.173	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	0	20300/1745	24.00	23.41	0.295	0.033	1.15	0.338	33
Front Side	standard	1:1	1	0	20300/1745	24.00	23.41	0.178	0.019	1.15	0.204	/
Back Side	standard	1:1	50%	0	20300/1745	23.50	22.88	0.256	0.025	1.15	0.295	/
Front Side	standard	1:1	50%	0	20300/1745	23.50	22.88	0.154	0.090	1.15	0.178	/
Back Side	Battery2	1:1	1	0	20300/1745	24.00	23.41	0.257	0.021	1.15	0.294	/
Back Side	Battery3	1:1	1	0	20300/1745	24.00	23.41	0.261	-0.030	1.15	0.299	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	0	20300/1745	24.50	23.91	0.525	0.024	1.15	0.601	/
Front Side	standard	1:1	1	0	20300/1745	24.50	23.91	0.304	0.037	1.15	0.348	/
Left Edge	standard	1:1	1	0	20300/1745	24.50	23.91	0.089	0.060	1.15	0.102	/
Right Edge	standard	1:1	1	0	20300/1745	24.50	23.91	0.000	0.055	1.15	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	1	0	20050/1720	24.50	23.75	0.693	0.029	1.19	0.824	/
	standard	1:1	1	0	20175/1732.5	24.50	23.86	0.736	0.032	1.16	0.853	/
	standard	1:1	1	0	20300/1745	24.50	23.91	0.751	-0.010	1.15	0.860	34
Back Side	standard	1:1	50%	0	20300/1745	23.50	22.93	0.463	0.028	1.14	0.528	/
Front Side	standard	1:1	50%	0	20300/1745	23.50	22.93	0.276	0.012	1.14	0.315	/
Left Edge	standard	1:1	50%	0	20300/1745	23.50	22.93	0.000	0.060	1.14	0.000	/
Right Edge	standard	1:1	50%	0	20300/1745	23.50	22.93	0.097	0.034	1.14	0.111	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	50%	0	20300/1745	23.50	22.93	0.553	0.058	1.14	0.631	/
Bottom Edge	standard	1:1	100%	0	20300/1745	23.50	22.86	0.681	0.022	1.16	0.789	/
Bottom Edge	SIM2	1:1	1	0	20300/1745	24.50	23.91	0.729	0.022	1.15	0.835	/
Bottom Edge	Battery2	1:1	1	0	20300/1745	24.50	23.91	0.690	0.019	1.15	0.790	/



Bottom Edge	Battery3	1:1	1	0	20300/1745	24.50	23.91	0.688	0.029	1.15	0.788	/
Bottom Edge	Repeated	1:1	1	0	20300/1745	24.50	23.91	0.730	0.021	1.15	0.836	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are $\geq$ 50% limit(1g).

3. Accessories that do not contain RF transmitters and have been proven to increase the peak SAR by less than 5 %, such as hands-free kits, do not need SAR tests separate from the SAR tests attached to a main EUT configuration.

Measurement Variability

Test Position	Channel/ Frequency(MHz)	MAX Measured SAR _{1g} (W/kg)	1 st Repeated SAR _{1g} (W/kg)	Ratio
Bottom Edge	20300/1745	0.751	0.730	1.03

Note: 1) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).

2) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .



Table 14: LTE Band 5 (10MHz, Main-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-u p (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	25	20525/836.5	24.00	23.68	0.020	0.030	1.08	0.021	/
Left Tilt	standard	1:1	1	25	20525/836.5	24.00	23.68	0.008	0.106	1.08	0.009	/
Right Cheek	standard	1:1	1	25	20525/836.5	24.00	23.68	0.033	0.023	1.08	0.035	35
Right Tilt	standard	1:1	1	25	20525/836.5	24.00	23.68	0.020	0.114	1.08	0.022	/
Left Cheek	standard	1:1	50%	13	20450/829	23.00	22.70	0.012	0.100	1.07	0.013	/
Left Tilt	standard	1:1	50%	13	20450/829	23.00	22.70	0.007	0.170	1.07	0.008	/
Right Cheek	standard	1:1	50%	13	20450/829	23.00	22.70	0.020	0.046	1.07	0.021	/
Right Tilt	standard	1:1	50%	13	20450/829	23.00	22.70	0.013	0.093	1.07	0.014	/
Right Cheek	Battery2	1:1	1	25	20525/836.5	24.00	23.68	0.027	-0.027	1.08	0.029	/
Right Cheek	Battery3	1:1	1	25	20525/836.5	24.00	23.68	0.030	-0.029	1.08	0.032	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	25	20525/836.5	24.00	23.68	0.122	0.023	1.08	0.131	36
Front Side	standard	1:1	1	25	20525/836.5	24.00	23.68	0.094	0.088	1.08	0.101	/
Back Side	standard	1:1	50%	13	20450/829	23.00	22.70	0.087	0.025	1.07	0.093	/
Front Side	standard	1:1	50%	13	20450/829	23.00	22.70	0.063	0.031	1.07	0.068	/
Back Side	Battery2	1:1	1	25	20525/836.5	24.00	23.68	0.099	-0.034	1.08	0.107	/
Back Side	Battery3	1:1	1	25	20525/836.5	24.00	23.68	0.101	-0.022	1.08	0.109	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	25	20525/836.5	24.00	23.68	0.208	0.024	1.08	0.224	37
Front Side	standard	1:1	1	25	20525/836.5	24.00	23.68	0.138	0.180	1.08	0.149	/
Left Edge	standard	1:1	1	25	20525/836.5	24.00	23.68	0.059	0.032	1.08	0.064	/
Right Edge	standard	1:1	1	25	20525/836.5	24.00	23.68	0.000	0.060	1.08	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	1	25	20525/836.5	24.00	23.68	0.169	-0.099	1.08	0.182	/
Back Side	standard	1:1	50%	13	20450/829	23.00	22.70	0.143	0.024	1.07	0.153	/
Front Side	standard	1:1	50%	13	20450/829	23.00	22.70	0.095	0.035	1.07	0.102	/
Left Edge	standard	1:1	50%	13	20450/829	23.00	22.70	0.043	0.010	1.07	0.046	/
Right Edge	standard	1:1	50%	13	20450/829	23.00	22.70	0.000	0.090	1.07	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	50%	13	20450/829	23.00	22.70	0.117	0.022	1.07	0.125	/
Back Side	Battery2	1:1	1	25	20525/836.5	24.00	23.68	0.159	0.012	1.08	0.171	/
Back Side	Battery3	1:1	1	25	20525/836.5	24.00	23.68	0.168	0.078	1.08	0.181	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥ 50% limit(1g).												



Table 15: LTE Band 7 (20MHz, Main-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-u p (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	99	21100/2535	24.00	23.22	0.069	-0.100	1.20	0.083	/
Left Tilt	standard	1:1	1	99	21100/2535	24.00	23.22	0.094	-0.081	1.20	0.112	/
Right Cheek	standard	1:1	1	99	21100/2535	24.00	23.22	0.123	0.023	1.20	0.147	38
Right Tilt	standard	1:1	1	99	21100/2535	24.00	23.22	0.054	0.083	1.20	0.064	/
Left Cheek	standard	1:1	50%	50	21100/2535	23.00	22.61	0.055	-0.036	1.09	0.060	/
Left Tilt	standard	1:1	50%	50	21100/2535	23.00	22.61	0.073	-0.050	1.09	0.080	/
Right Cheek	standard	1:1	50%	50	21100/2535	23.00	22.61	0.099	0.060	1.09	0.108	/
Right Tilt	standard	1:1	50%	50	21100/2535	23.00	22.61	0.045	0.169	1.09	0.049	/
Right Cheek	Battery2	1:1	1	99	21100/2535	24.00	23.22	0.098	-0.037	1.20	0.117	/
Right Cheek	Battery3	1:1	1	99	21100/2535	24.00	23.22	0.102	-0.023	1.20	0.122	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	99	21100/2535	23.50	23.05	0.334	0.090	1.11	0.370	39
Front Side	standard	1:1	1	99	21100/2535	23.50	23.05	0.174	0.038	1.11	0.193	/
Back Side	standard	1:1	50%	25	21350/2560	23.00	22.86	0.248	-0.025	1.03	0.256	/
Front Side	standard	1:1	50%	25	21350/2560	23.00	22.86	0.167	0.120	1.03	0.172	/
Back Side	Battery2	1:1	1	99	21100/2535	23.50	23.05	0.275	0.021	1.11	0.305	/
Back Side	Battery3	1:1	1	99	21100/2535	23.50	23.05	0.253	0.031	1.11	0.281	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	99	21100/2535	21.50	20.68	0.336	-0.036	1.21	0.406	/
Front Side	standard	1:1	1	99	21100/2535	21.50	20.68	0.159	0.019	1.21	0.192	/
Left Edge	standard	1:1	1	99	21100/2535	21.50	20.68	0.034	0.042	1.21	0.041	/
Right Edge	standard	1:1	1	99	21100/2535	21.50	20.68	0.000	0.070	1.21	0.000	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	1	99	21100/2535	21.50	20.68	0.488	-0.022	1.21	0.589	/
Back Side	standard	1:1	50%	50	21100/2535	21.50	20.60	0.319	0.038	1.23	0.392	/
Front Side	standard	1:1	50%	50	21100/2535	21.50	20.60	0.159	0.024	1.23	0.196	/
Left Edge	standard	1:1	50%	50	21100/2535	21.50	20.60	0.023	-0.062	1.23	0.028	/
Right Edge	standard	1:1	50%	50	21100/2535	21.50	20.60	0.036	-0.029	1.23	0.044	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	50%	50	21100/2535	21.50	20.60	0.504	0.044	1.23	0.620	40
Bottom Edge	Battery2	1:1	50%	50	21100/2535	21.50	20.60	0.479	0.011	1.23	0.589	/
Bottom Edge	Battery3	1:1	50%	50	21100/2535	21.50	20.60	0.452	-0.014	1.23	0.556	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥ 50% limit(1g).												



Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	99	21100/2535	23.50	21.50	0.406	1.58	0.643	no
Front Side	QPSK	1:1	1	99	21100/2535	23.50	21.50	0.192	1.58	0.304	no
Left Edge	QPSK	1:1	1	99	21100/2535	23.50	21.50	0.041	1.58	0.065	no
Right Edge	QPSK	1:1	1	99	21100/2535	23.50	21.50	0.000	1.58	0.000	no
Bottom Edge	QPSK	1:1	1	99	21100/2535	23.50	21.50	0.589	1.58	0.934	no
Back Side	QPSK	1:1	50%	50	21100/2535	23.00	21.50	0.392	1.41	0.554	no
Front Side	QPSK	1:1	50%	50	21100/2535	23.00	21.50	0.196	1.41	0.276	no
Left Edge	QPSK	1:1	50%	50	21100/2535	23.00	21.50	0.028	1.41	0.040	no
Right Edge	QPSK	1:1	50%	50	21100/2535	23.00	21.50	0.044	1.41	0.063	no
Bottom Edge	QPSK	1:1	50%	50	21100/2535	23.00	21.50	0.620	1.41	0.876	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.											



Table 16: LTE Band 66 (20MHz, Main-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-u p (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	99	132572/1770	24.20	24.06	0.030	0.148	1.03	0.030	/
Left Tilt	standard	1:1	1	99	132572/1770	24.20	24.06	0.021	0.087	1.03	0.021	/
Right Cheek	standard	1:1	1	99	132572/1770	24.20	24.06	0.046	0.057	1.03	0.047	41
Right Tilt	standard	1:1	1	99	132572/1770	24.20	24.06	0.020	0.101	1.03	0.020	/
Left Cheek	standard	1:1	50%	0	132322/1745	23.50	22.99	0.011	-0.073	1.12	0.013	/
Left Tilt	standard	1:1	50%	0	132322/1745	23.50	22.99	0.006	0.115	1.12	0.006	/
Right Cheek	standard	1:1	50%	0	132322/1745	23.50	22.99	0.019	0.028	1.12	0.021	/
Right Tilt	standard	1:1	50%	0	132322/1745	23.50	22.99	0.009	0.197	1.12	0.010	/
Right Cheek	Battery2	1:1	1	99	132572/1770	24.20	24.06	0.032	-0.028	1.03	0.033	/
Right Cheek	Battery3	1:1	1	99	132572/1770	24.20	24.06	0.025	0.059	1.03	0.026	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	99	132572/1770	24.00	23.51	0.212	0.134	1.12	0.237	42
Front Side	standard	1:1	1	99	132572/1770	24.00	23.51	0.085	0.021	1.12	0.095	/
Back Side	standard	1:1	50%	0	132322/1745	23.50	23.00	0.183	-0.150	1.12	0.205	/
Front Side	standard	1:1	50%	0	132322/1745	23.50	23.00	0.061	0.030	1.12	0.068	/
Back Side	Battery2	1:1	1	99	132572/1770	24.00	23.51	0.175	-0.038	1.12	0.196	/
Back Side	Battery3	1:1	1	99	132572/1770	24.00	23.51	0.163	-0.080	1.12	0.182	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	99	132572/1770	24.50	24.06	0.491	0.140	1.11	0.543	/
Front Side	standard	1:1	1	99	132572/1770	24.50	24.06	0.183	0.131	1.11	0.203	/
Left Edge	standard	1:1	1	99	132572/1770	24.50	24.06	0.041	0.020	1.11	0.045	/
Right Edge	standard	1:1	1	99	132572/1770	24.50	24.06	0.045	-0.036	1.11	0.050	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	1	99	132572/1770	24.50	24.06	0.576	-0.120	1.11	0.637	43
Back Side	standard	1:1	50%	0	132322/1745	23.50	22.99	0.411	0.022	1.12	0.462	/
Front Side	standard	1:1	50%	0	132322/1745	23.50	22.99	0.129	0.130	1.12	0.145	/
Left Edge	standard	1:1	50%	0	132322/1745	23.50	22.99	0.023	0.014	1.12	0.026	/
Right Edge	standard	1:1	50%	0	132322/1745	23.50	22.99	0.033	0.060	1.12	0.037	/
Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Bottom Edge	standard	1:1	50%	0	132322/1745	23.50	22.99	0.516	-0.080	1.12	0.580	/
Bottom Edge	Battery2	1:1	1	99	132572/1770	24.50	24.06	0.509	-0.130	1.11	0.563	/
Bottom Edge	Battery3	1:1	1	99	132572/1770	24.50	24.06	0.485	0.010	1.11	0.537	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥ 50% limit(1g).												



Table 17: GSM 850 (Second-antenna)

Test Position	Cover Type	Time slot	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.302	-0.050	1.24	0.374	/
Left Tilt	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.245	0.020	1.24	0.304	/
Right Cheek	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.437	-0.020	1.24	0.541	44
Right Tilt	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.401	0.070	1.24	0.497	/
Right Cheek	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.426	0.053	1.24	0.528	/
Right Cheek	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.418	-0.022	1.24	0.518	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.081	0.029	1.24	0.101	45
Front Side	standard	GSM	1:8.3	190/836.6	32.40	31.47	0.072	0.030	1.24	0.089	/
Back Side	Battery2	GSM	1:8.3	190/836.6	32.40	31.47	0.078	0.023	1.24	0.097	/
Back Side	Battery3	GSM	1:8.3	190/836.6	32.40	31.47	0.080	-0.072	1.24	0.099	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	4Txslots	1:2.07	190/836.6	25.90	25.25	0.205	0.140	1.16	0.238	46
Front Side	standard	4Txslots	1:2.07	190/836.6	25.90	25.25	0.159	0.081	1.16	0.185	/
Left Edge	standard	4Txslots	1:2.07	190/836.6	25.90	25.25	0.061	-0.020	1.16	0.071	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	4Txslots	1:2.07	190/836.6	25.90	25.25	0.116	0.026	1.16	0.135	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	Battery2	4Txslots	1:2.07	190/836.6	25.90	25.25	0.195	-0.056	1.16	0.226	/
Back Side	Battery3	4Txslots	1:2.07	190/836.6	25.90	25.25	0.193	0.023	1.16	0.224	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2.When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.											

Test Position	Time slot	Duty Cycle	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	4Txslots	1:2.07	190/836.6	27.40	25.90	0.238	1.41	0.336	no
Front Side	4Txslots	1:2.07	190/836.6	27.40	25.90	0.185	1.41	0.261	no
Left Edge	4Txslots	1:2.07	190/836.6	27.40	25.90	0.071	1.41	0.100	no
Top Edge	4Txslots	1:2.07	190/836.6	27.40	25.90	0.135	1.41	0.190	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.									



Table 18: GSM 1900 (Second-antenna)

Test Position	Cover Type	Time slot	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	GSM	1:8.3	661/1880	30.40	29.78	0.166	0.082	1.15	0.191	/
Left Tilt	standard	GSM	1:8.3	661/1880	30.40	29.78	0.243	-0.020	1.15	0.280	/
Right Cheek	standard	GSM	1:8.3	661/1880	30.40	29.78	0.237	-0.120	1.15	0.273	/
Right Tilt	standard	GSM	1:8.3	661/1880	30.40	29.78	0.377	0.010	1.15	0.435	47
Right Tilt	standard	GSM	1:8.3	661/1880	30.40	29.78	0.346	-0.097	1.15	0.399	/
Right Tilt	standard	GSM	1:8.3	661/1880	30.40	29.78	0.367	0.023	1.15	0.423	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	GSM	1:8.3	661/1880	30.40	29.78	0.067	0.090	1.15	0.077	48
Front Side	standard	GSM	1:8.3	661/1880	30.40	29.78	0.041	0.073	1.15	0.047	/
Back Side	Battery2	GSM	1:8.3	661/1880	30.40	29.78	0.062	0.078	1.15	0.072	/
Back Side	Battery3	GSM	1:8.3	661/1880	30.40	29.78	0.058	0.014	1.15	0.067	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	4Txslots	1:2.07	661/1880	24.50	23.54	0.109	0.037	1.25	0.136	/
Front Side	standard	4Txslots	1:2.07	661/1880	24.50	23.54	0.076	-0.026	1.25	0.095	/
Left Edge	standard	4Txslots	1:2.07	661/1880	24.50	23.54	0.065	-0.045	1.25	0.081	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	4Txslots	1:2.07	661/1880	24.50	23.54	0.235	-0.070	1.25	0.293	49
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	Battery2	4Txslots	1:2.07	661/1880	24.50	23.54	0.216	0.036	1.25	0.269	/
Top Edge	Battery3	4Txslots	1:2.07	661/1880	24.50	23.54	0.229	0.019	1.25	0.286	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2.When multiple slots are used, SAR should be tested to account for the maximum source-based time-averaged output power.											



Table 19: UMTS Band II (Second-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.254	0.090	1.07	0.272	/
Left Tilt	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.317	0.020	1.07	0.340	/
Right Cheek	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.310	0.100	1.07	0.332	/
Right Tilt	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.394	-0.157	1.07	0.422	50
Right Tilt	Battery2	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.384	-0.010	1.07	0.411	/
Right Tilt	Battery3	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.374	0.100	1.07	0.401	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	9400/1880	23.90	23.59	0.146	0.130	1.07	0.157	51
Front Side	standard	RMC 12.2K	1:1	9400/1880	23.90	23.59	0.075	0.031	1.07	0.081	/
Back Side	Battery2	RMC 12.2K	1:1	9400/1880	23.90	23.59	0.134	0.000	1.07	0.144	/
Back Side	Battery3	RMC 12.2K	1:1	9400/1880	23.90	23.59	0.139	0.000	1.07	0.149	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.151	0.085	1.07	0.162	/
Front Side	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.092	-0.043	1.07	0.099	/
Left Edge	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.096	0.055	1.07	0.103	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.321	0.100	1.07	0.344	52
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	Battery2	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.310	-0.097	1.07	0.332	/
Top Edge	Battery3	RMC 12.2K	1:1	9400/1880	22.40	22.10	0.315	-0.062	1.07	0.338	/

Note: 1. The value with blue color is the maximum SAR Value of each test band.

2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

Test Position	Channel Type	Duty Cycle	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	RMC 12.2K	1:1	9400/1880	23.90	22.40	0.162	1.41	0.229	no
Front Side	RMC 12.2K	1:1	9400/1880	23.90	22.40	0.099	1.41	0.139	no
Left Edge	RMC 12.2K	1:1	9400/1880	23.90	22.40	0.103	1.41	0.145	no
Top Edge	RMC 12.2K	1:1	9400/1880	23.90	22.40	0.344	1.41	0.486	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 20: UMTS Band IV (Second-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.464	-0.090	1.12	0.521	/
Left Tilt	standard	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.536	-0.010	1.12	0.601	53
Right Cheek	standard	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.514	-0.010	1.12	0.577	/
Right Tilt	standard	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.333	0.060	1.12	0.374	/
Left Tilt	Battery2	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.532	-0.091	1.12	0.597	/
Left Tilt	Battery3	RMC 12.2K	1:1	1413/1732.6	22.80	22.30	0.529	0.012	1.12	0.594	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	1413/1732.6	23.30	22.80	0.288	-0.030	1.12	0.323	54
Front Side	standard	RMC 12.2K	1:1	1413/1732.6	23.30	22.80	0.124	0.021	1.12	0.139	/
Back Side	Battery2	RMC 12.2K	1:1	1413/1732.6	23.30	22.80	0.277	0.033	1.12	0.311	/
Back Side	Battery3	RMC 12.2K	1:1	1413/1732.6	23.30	22.80	0.268	0.078	1.12	0.301	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.312	0.140	1.26	0.393	/
Front Side	standard	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.142	-0.100	1.26	0.179	/
Left Edge	standard	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.519	0.020	1.26	0.653	55
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.041	-0.076	1.26	0.052	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Left Edge	SIM2	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.510	0.015	1.26	0.642	/
Left Edge	Battery2	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.502	0.026	1.26	0.632	/
Left Edge	Battery3	RMC 12.2K	1:1	1413/1732.6	21.80	20.80	0.496	0.062	1.26	0.624	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.											
3. Accessories that do not contain RF transmitters and have been proven to increase the peak SAR by less than 5 %, such as hands-free kits, do not need SAR tests separate from the SAR tests attached to a main EUT configuration.											



Test Position	Channel Type	Duty Cycle	Channel Frequency(MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	RMC 12.2K	1:1	1413/1732.6	23.30	21.80	0.393	1.41	0.555	no
Front Side	RMC 12.2K	1:1	1413/1732.6	23.30	21.80	0.179	1.41	0.253	no
Left Edge	RMC 12.2K	1:1	1413/1732.6	23.30	21.80	0.653	1.41	0.923	no
Top Edge	RMC 12.2K	1:1	1413/1732.6	23.30	21.80	0.052	1.41	0.073	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 21: UMTS Band V (Second-antenna)

Test Position	Cover Type	Channel Type	Duty Cycle	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR											
Left Cheek	standard	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.360	0.010	1.28	0.461	/
Left Tilt	standard	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.255	0.020	1.28	0.326	/
Right Cheek	standard	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.527	-0.010	1.28	0.674	56
Right Tilt	standard	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.438	-0.030	1.28	0.560	/
Right Cheek	Battery2	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.506	-0.030	1.28	0.647	/
Right Cheek	Battery3	RMC 12.2K	1:1	4183/836.6	21.40	20.33	0.513	0.000	1.28	0.656	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	RMC 12.2K	1:1	4183/836.6	25.20	24.05	0.296	0.100	1.30	0.386	57
Front Side	standard	RMC 12.2K	1:1	4183/836.6	25.20	24.05	0.221	0.082	1.30	0.288	/
Back Side	Battery2	RMC 12.2K	1:1	4183/836.6	25.20	24.05	0.254	0.011	1.30	0.331	/
Back Side	Battery3	RMC 12.2K	1:1	4183/836.6	25.20	24.05	0.273	0.028	1.30	0.356	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.319	0.090	1.30	0.416	58
Front Side	standard	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.274	-0.061	1.30	0.357	/
Left Edge	standard	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.123	-0.025	1.30	0.160	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.236	0.100	1.30	0.308	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	Battery2	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.289	-0.010	1.30	0.377	/
Back Side	Battery3	RMC 12.2K	1:1	4183/836.6	23.70	22.55	0.305	-0.120	1.30	0.397	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.											
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.											

Test Position	Channel Type	Duty Cycle	Channel Frequency(MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	RMC 12.2K	1:1	4183/836.6	25.20	23.70	0.416	1.41	0.587	no
Front Side	RMC 12.2K	1:1	4183/836.6	25.20	23.70	0.357	1.41	0.504	no
Left Edge	RMC 12.2K	1:1	4183/836.6	25.20	23.70	0.160	1.41	0.226	no
Top Edge	RMC 12.2K	1:1	4183/836.6	25.20	23.70	0.308	1.41	0.434	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.									



Table 22: LTE Band 2 (20MHz, Second-antenna)

Test Position	Cover Type	Duty Cycle	RB allocation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	0	18700/1860	22.60	22.29	0.327	-0.032	1.07	0.351	/
Left Tilt	standard	1:1	1	0	18700/1860	22.60	22.29	0.397	-0.080	1.07	0.426	/
Right Cheek	standard	1:1	1	0	18700/1860	22.60	22.29	0.429	-0.025	1.07	0.461	/
Right Tilt	standard	1:1	1	0	18700/1860	22.60	22.29	0.557	0.120	1.07	0.598	59
Left Cheek	standard	1:1	50%	0	18700/1860	22.60	22.32	0.307	-0.020	1.07	0.327	/
Left Tilt	standard	1:1	50%	0	18700/1860	22.60	22.32	0.392	-0.060	1.07	0.418	/
Right Cheek	standard	1:1	50%	0	18700/1860	22.60	22.32	0.441	0.020	1.07	0.470	/
Right Tilt	standard	1:1	50%	0	18700/1860	22.60	22.32	0.557	0.080	1.07	0.594	/
Right Tilt	Battery2	1:1	1	0	18700/1860	22.60	22.29	0.539	-0.015	1.07	0.579	/
Right Tilt	Battery3	1:1	1	0	18700/1860	22.60	22.29	0.521	0.019	1.07	0.560	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	0	18700/1860	23.60	23.36	0.145	0.024	1.06	0.153	60
Front Side	standard	1:1	1	0	18700/1860	23.60	23.36	0.093	0.035	1.06	0.098	/
Back Side	standard	1:1	50%	0	18700/1860	22.60	22.35	0.077	0.090	1.06	0.082	/
Front Side	standard	1:1	50%	0	18700/1860	22.60	22.35	0.052	-0.010	1.06	0.055	/
Back Side	Battery2	1:1	1	0	18700/1860	23.60	23.36	0.129	-0.053	1.06	0.136	/
Back Side	Battery3	1:1	1	0	18700/1860	23.60	23.36	0.130	0.019	1.06	0.137	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	0	18700/1860	22.10	20.94	0.122	0.019	1.31	0.159	/
Front Side	standard	1:1	1	0	18700/1860	22.10	20.94	0.080	0.022	1.31	0.104	/
Left Edge	standard	1:1	1	0	18700/1860	22.10	20.94	0.122	0.038	1.31	0.159	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	1	0	18700/1860	22.10	20.94	0.347	0.170	1.31	0.453	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	standard	1:1	50%	0	18700/1860	22.10	20.89	0.118	0.058	1.32	0.156	/
Front Side	standard	1:1	50%	0	18700/1860	22.10	20.89	0.085	0.029	1.32	0.112	/
Left Edge	standard	1:1	50%	0	18700/1860	22.10	20.89	0.093	0.010	1.32	0.123	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	50%	0	18700/1860	22.10	20.89	0.358	0.130	1.32	0.473	61
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	Battery2	1:1	50%	0	18700/1860	22.10	20.89	0.341	0.079	1.32	0.451	/
Top Edge	Battery3	1:1	50%	0	18700/1860	22.10	20.89	0.308	0.029	1.32	0.407	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥ 50% limit(1g).												



Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	0	18700/1860	23.60	22.10	0.159	1.41	0.225	no
Front Side	QPSK	1:1	1	0	18700/1860	23.60	22.10	0.104	1.41	0.148	no
Left Edge	QPSK	1:1	1	0	18700/1860	23.60	22.10	0.159	1.41	0.225	no
Top Edge	QPSK	1:1	1	0	18700/1860	23.60	22.10	0.453	1.41	0.640	no
Back Side	QPSK	1:1	50%	0	18700/1860	22.60	22.10	0.156	1.12	0.175	no
Front Side	QPSK	1:1	50%	0	18700/1860	22.60	22.10	0.112	1.12	0.126	no
Left Edge	QPSK	1:1	50%	0	18700/1860	22.60	22.10	0.123	1.12	0.138	no
Top Edge	QPSK	1:1	50%	0	18700/1860	22.60	22.10	0.473	1.12	0.531	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.											



Table 23: LTE Band 4 (20MHz, Second-antenna)

Test Position	Cover Type	Duty Cycle	RB allocation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	0	20175/1732.5	22.00	21.18	0.429	0.140	1.21	0.518	/
Left Tilt	standard	1:1	1	0	20175/1732.5	22.00	21.18	0.379	0.026	1.21	0.458	/
Right Cheek	standard	1:1	1	0	20175/1732.5	22.00	21.18	0.529	-0.010	1.21	0.639	62
Right Tilt	standard	1:1	1	0	20175/1732.5	22.00	21.18	0.237	0.010	1.21	0.286	/
Left Cheek	standard	1:1	50%	0	20300/1745	22.00	21.15	0.352	-0.020	1.22	0.428	/
Left Tilt	standard	1:1	50%	0	20300/1745	22.00	21.15	0.328	-0.010	1.22	0.399	/
Right Cheek	standard	1:1	50%	0	20300/1745	22.00	21.15	0.425	0.080	1.22	0.517	/
Right Tilt	standard	1:1	50%	0	20300/1745	22.00	21.15	0.247	0.070	1.22	0.300	/
Right Cheek	Battery2	1:1	1	0	20175/1732.5	22.00	21.18	0.438	-0.040	1.21	0.529	/
Right Cheek	Battery3	1:1	1	0	20175/1732.5	22.00	21.18	0.420	-0.012	1.21	0.507	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	0	20175/1732.5	23.00	22.31	0.332	0.010	1.17	0.389	63
Front Side	standard	1:1	1	0	20175/1732.5	23.00	22.31	0.235	0.069	1.17	0.275	/
Back Side	standard	1:1	50%	0	20175/1732.5	22.50	21.74	0.259	0.052	1.19	0.309	/
Front Side	standard	1:1	50%	0	20175/1732.5	22.50	21.74	0.190	0.028	1.19	0.226	/
Back Side	SIM2	1:1	1	0	20175/1732.5	23.00	22.31	0.312	-0.010	1.17	0.366	/
Back Side	Battery2	1:1	1	0	20175/1732.5	23.00	22.31	0.297	0.029	1.17	0.348	/
Back Side	Battery3	1:1	1	0	20175/1732.5	23.00	22.31	0.273	0.022	1.17	0.320	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	0	20300/1745	21.50	20.54	0.262	0.041	1.25	0.327	/
Front Side	standard	1:1	1	0	20300/1745	21.50	20.54	0.110	0.027	1.25	0.137	/
Left Edge	standard	1:1	1	0	20300/1745	21.50	20.54	0.395	-0.020	1.25	0.493	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	1	0	20300/1745	21.50	20.54	0.047	0.032	1.25	0.059	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	standard	1:1	50%	0	20300/1745	21.50	20.38	0.287	0.012	1.29	0.371	/
Front Side	standard	1:1	50%	0	20300/1745	21.50	20.38	0.126	0.090	1.29	0.163	/
Left Edge	standard	1:1	50%	0	20300/1745	21.50	20.38	0.446	-0.120	1.29	0.577	64
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	50%	0	20300/1745	21.50	20.38	0.042	0.050	1.29	0.054	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Left Edge	Battery2	1:1	50%	0	20300/1745	21.50	20.38	0.409	-0.041	1.29	0.529	/
Left Edge	Battery3	1:1	50%	0	20300/1745	21.50	20.38	0.382	-0.033	1.29	0.494	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥												



50% limit(1g).

3. Accessories that do not contain RF transmitters and have been proven to increase the peak SAR by less than 5 %, such as hands-free kits, do not need SAR tests separate from the SAR tests attached to a main EUT configuration.

Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	0	20300/1745	23.00	21.50	0.327	1.41	0.462	no
Front Side	QPSK	1:1	1	0	20300/1745	23.00	21.50	0.137	1.41	0.194	no
Left Edge	QPSK	1:1	1	0	20300/1745	23.00	21.50	0.493	1.41	0.696	no
Top Edge	QPSK	1:1	1	0	20300/1745	23.00	21.50	0.059	1.41	0.083	no
Back Side	QPSK	1:1	50%	0	20300/1745	23.00	21.50	0.371	1.41	0.525	no
Front Side	QPSK	1:1	50%	0	20300/1745	23.00	21.50	0.163	1.41	0.230	no
Left Edge	QPSK	1:1	50%	0	20300/1745	23.00	21.50	0.577	1.41	0.815	no
Top Edge	QPSK	1:1	50%	.0	20300/1745	22.50	21.50	0.054	1.26	0.068	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 24: LTE Band 5 (10MHz, Second-antenna)

Test Position	Cover Type	Duty Cycle	RB allocation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	0	20525/836.5	20.20	19.87	0.439	-0.040	1.08	0.474	/
Left Tilt	standard	1:1	1	0	20525/836.5	20.20	19.87	0.378	-0.020	1.08	0.408	/
Right Cheek	standard	1:1	1	0	20525/836.5	20.20	19.87	0.578	-0.030	1.08	0.624	/
Right Tilt	standard	1:1	1	0	20525/836.5	20.20	19.87	0.470	-0.020	1.08	0.507	/
Left Cheek	standard	1:1	50%	13	20450/829	20.20	19.89	0.448	-0.040	1.07	0.481	/
Left Tilt	standard	1:1	50%	13	20450/829	20.20	19.89	0.383	-0.010	1.07	0.411	/
Right Cheek	standard	1:1	50%	13	20450/829	20.20	19.89	0.590	-0.030	1.07	0.634	65
Right Tilt	standard	1:1	50%	13	20450/829	20.20	19.89	0.481	-0.060	1.07	0.517	/
Right Cheek	Battery2	1:1	50%	13	20450/829	20.20	19.89	0.559	-0.021	1.07	0.600	/
Right Cheek	Battery3	1:1	50%	13	20450/829	20.20	19.89	0.518	0.029	1.07	0.556	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	25	20450/829	23.40	22.85	0.296	0.100	1.14	0.336	66
Front Side	standard	1:1	1	25	20450/829	23.40	22.85	0.164	0.018	1.14	0.186	/
Back Side	standard	1:1	50%	25	20450/829	22.40	21.96	0.188	0.022	1.11	0.208	/
Front Side	standard	1:1	50%	25	20450/829	22.40	21.96	0.148	0.050	1.11	0.164	/
Back Side	Battery2	1:1	1	25	20450/829	23.40	22.85	0.226	0.028	1.14	0.257	/
Back Side	Battery3	1:1	1	25	20450/829	23.40	22.85	0.217	0.010	1.14	0.246	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	49	20450/829	21.90	21.45	0.319	0.090	1.11	0.354	67
Front Side	standard	1:1	1	49	20450/829	21.90	21.45	0.111	0.038	1.11	0.123	/
Left Edge	standard	1:1	1	49	20450/829	21.90	21.45	0.100	0.015	1.11	0.111	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	1	49	20450/829	21.90	21.45	0.178	0.027	1.11	0.197	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	standard	1:1	50%	25	20450/829	21.90	21.42	0.304	0.061	1.12	0.340	/
Front Side	standard	1:1	50%	25	20450/829	21.90	21.42	0.221	0.034	1.12	0.247	/
Left Edge	standard	1:1	50%	25	20450/829	21.90	21.42	0.096	0.025	1.12	0.107	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	50%	25	20450/829	21.90	21.42	0.217	0.011	1.12	0.242	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	Battery2	1:1	1	49	20450/829	21.90	21.45	0.307	-0.021	1.11	0.341	/
Back Side	Battery3	1:1	1	49	20450/829	21.90	21.45	0.276	0.016	1.11	0.306	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥ 50% limit(1g).												



Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	49	20450/829	23.40	21.90	0.354	1.41	0.500	no
Front Side	QPSK	1:1	1	49	20450/829	23.40	21.90	0.123	1.41	0.174	no
Left Edge	QPSK	1:1	1	49	20450/829	23.40	21.90	0.111	1.41	0.157	no
Top Edge	QPSK	1:1	1	49	20450/829	23.40	21.90	0.197	1.41	0.279	no
Back Side	QPSK	1:1	50%	25	20450/829	22.40	21.90	0.340	1.12	0.381	no
Front Side	QPSK	1:1	50%	25	20450/829	22.40	21.90	0.247	1.12	0.277	no
Left Edge	QPSK	1:1	50%	25	20450/829	22.40	21.90	0.107	1.12	0.120	no
Top Edge	QPSK	1:1	50%	25	20450/829	22.40	21.90	0.242	1.12	0.272	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 25: LTE Band 7 (20MHz, Second-antenna)

Test Position	Cover Type	Duty Cycle	RB alloc ation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	99	21100/2535	17.60	17.40	0.169	-0.034	1.05	0.177	/
Left Tilt	standard	1:1	1	99	21100/2535	17.60	17.40	0.207	-0.170	1.05	0.217	/
Right Cheek	standard	1:1	1	99	21100/2535	17.60	17.40	0.679	0.057	1.05	0.711	68
Right Tilt	standard	1:1	1	99	21100/2535	17.60	17.40	0.676	-0.050	1.05	0.708	/
Left Cheek	standard	1:1	50%	50	21100/2535	17.60	17.43	0.209	-0.029	1.04	0.217	/
Left Tilt	standard	1:1	50%	50	21100/2535	17.60	17.43	0.195	-0.160	1.04	0.203	/
Right Cheek	standard	1:1	50%	50	21100/2535	17.60	17.43	0.566	-0.040	1.04	0.589	/
Right Tilt	standard	1:1	50%	50	21100/2535	17.60	17.43	0.571	0.110	1.04	0.594	/
Right Cheek	SIM2	1:1	1	99	21100/2535	17.60	17.40	0.660	-0.032	1.05	0.691	/
Right Cheek	Battery2	1:1	1	99	21100/2535	17.60	17.40	0.579	-0.039	1.05	0.606	/
Right Cheek	Battery3	1:1	1	99	21100/2535	17.60	17.40	0.509	-0.037	1.05	0.533	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	99	21100/2535	19.60	19.41	0.343	-0.020	1.04	0.358	69
Front Side	standard	1:1	1	99	21100/2535	19.60	19.41	0.169	-0.043	1.04	0.177	/
Back Side	standard	1:1	50%	50	21100/2535	19.60	19.46	0.291	0.019	1.03	0.301	/
Front Side	standard	1:1	50%	50	21100/2535	19.60	19.46	0.138	0.025	1.03	0.143	/
Back Side	Battery2	1:1	1	99	21100/2535	19.60	19.41	0.305	-0.024	1.04	0.319	/
Back Side	Battery3	1:1	1	99	21100/2535	19.60	19.41	0.283	-0.057	1.04	0.296	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	99	21100/2535	18.10	17.97	0.212	0.038	1.03	0.218	/
Front Side	standard	1:1	1	99	21100/2535	18.10	17.97	0.135	0.050	1.03	0.139	/
Left Edge	standard	1:1	1	99	21100/2535	18.10	17.97	0.110	0.062	1.03	0.113	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	1	99	21100/2535	18.10	17.97	0.233	0.013	1.03	0.240	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	standard	1:1	50%	50	21100/2535	18.10	17.90	0.217	0.027	1.05	0.227	/
Front Side	standard	1:1	50%	50	21100/2535	18.10	17.90	0.138	0.011	1.05	0.145	/
Left Edge	standard	1:1	50%	50	21100/2535	18.10	17.90	0.136	-0.025	1.05	0.142	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	50%	50	21100/2535	18.10	17.90	0.286	0.040	1.05	0.299	70
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	Battery2	1:1	50%	50	21100/2535	18.10	17.90	0.230	0.025	1.05	0.241	/
Top Edge	Battery3	1:1	50%	50	21100/2535	18.10	17.90	0.247	0.075	1.05	0.259	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are ≥												



50% limit(1g).

3. Accessories that do not contain RF transmitters and have been proven to increase the peak SAR by less than 5 %, such as hands-free kits, do not need SAR tests separate from the SAR tests attached to a main EUT configuration.

Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	99	21100/2535	19.60	18.10	0.218	1.41	0.309	no
Front Side	QPSK	1:1	1	99	21100/2535	19.60	18.10	0.139	1.41	0.196	no
Left Edge	QPSK	1:1	1	99	21100/2535	19.60	18.10	0.113	1.41	0.160	no
Top Edge	QPSK	1:1	1	99	21100/2535	19.60	18.10	0.240	1.41	0.339	no
Back Side	QPSK	1:1	50%	50	21100/2535	19.60	18.10	0.227	1.41	0.321	no
Front Side	QPSK	1:1	50%	50	21100/2535	19.60	18.10	0.145	1.41	0.204	no
Left Edge	QPSK	1:1	50%	50	21100/2535	19.60	18.10	0.142	1.41	0.201	no
Top Edge	QPSK	1:1	50%	50	21100/2535	19.60	18.10	0.299	1.41	0.423	no

Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.



Table 26: LTE Band 66 (20MHz, Second-antenna)

Test Position	Cover Type	Duty Cycle	RB allocation	RB offset	Channel/ Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
								Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR1g	
Head SAR (QPSK)												
Left Cheek	standard	1:1	1	99	132572/1770	22.50	21.50	0.134	0.090	1.26	0.169	/
Left Tilt	standard	1:1	1	99	132572/1770	22.50	21.50	0.143	0.040	1.26	0.180	/
Right Cheek	standard	1:1	1	99	132572/1770	22.50	21.50	0.154	0.044	1.26	0.194	/
Right Tilt	standard	1:1	1	99	132572/1770	22.50	21.50	0.224	0.082	1.26	0.282	/
Left Cheek	standard	1:1	50%	0	132572/1770	22.50	21.60	0.170	0.150	1.23	0.209	/
Left Tilt	standard	1:1	50%	0	132572/1770	22.50	21.60	0.110	0.140	1.23	0.135	/
Right Cheek	standard	1:1	50%	0	132572/1770	22.50	21.60	0.258	0.103	1.23	0.317	71
Right Tilt	standard	1:1	50%	0	132572/1770	22.50	21.60	0.186	0.037	1.23	0.229	/
Right Cheek	Battery2	1:1	50%	0	132572/1770	22.50	21.60	0.220	-0.030	1.23	0.271	/
Right Cheek	Battery3	1:1	50%	0	132572/1770	22.50	21.60	0.234	0.080	1.23	0.288	/
Body-worn SAR (QPSK, Distance 15mm)												
Back Side	standard	1:1	1	0	132572/1770	23.50	23.00	0.106	0.180	1.12	0.119	72
Front Side	standard	1:1	1	0	132572/1770	23.50	23.00	0.060	0.120	1.12	0.067	/
Back Side	standard	1:1	50%	50	132572/1770	22.50	21.94	0.081	0.020	1.14	0.092	/
Front Side	standard	1:1	50%	50	132572/1770	22.50	21.94	0.044	0.140	1.14	0.050	/
Back Side	Battery2	1:1	1	0	132572/1770	23.50	23.00	0.092	-0.027	1.12	0.103	/
Back Side	Battery3	1:1	1	0	132572/1770	23.50	23.00	0.089	0.012	1.12	0.100	/
Hotspot SAR(QPSK, Distance 10mm)												
Back Side	standard	1:1	1	99	132072/1720	22.00	21.31	0.107	-0.033	1.17	0.125	73
Front Side	standard	1:1	1	99	132072/1720	22.00	21.31	0.044	0.026	1.17	0.052	/
Left Edge	standard	1:1	1	99	132072/1720	22.00	21.31	0.083	0.110	1.17	0.097	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	1	99	132072/1720	22.00	21.31	0.000	0.020	1.17	0.000	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	standard	1:1	50%	50	132572/1770	22.00	21.25	0.096	0.030	1.19	0.114	/
Front Side	standard	1:1	50%	50	132572/1770	22.00	21.25	0.045	0.121	1.19	0.053	/
Left Edge	standard	1:1	50%	50	132572/1770	22.00	21.25	0.074	0.031	1.19	0.088	/
Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	standard	1:1	50%	50	132572/1770	22.00	21.25	0.000	0.010	1.19	0.000	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	Battery2	1:1	1	99	132072/1720	22.00	21.31	0.098	-0.021	1.17	0.115	/
Back Side	Battery3	1:1	1	99	132072/1720	22.00	21.31	0.082	-0.012	1.17	0.096	/
Note: 1.The value with blue color is the maximum SAR Value of each test band.												
2.For QPSK with 100% RB allocation, SAR is required when and the highest reported SAR for 1 RB and 50% RB allocation in are≥ 50% limit(1g).												



Test Position	Mode	Duty Cycle	RB allocation	offset	Channel Frequency (MHz)	Tune-up (dBm)	Measured power (dBm)	Measured SAR1g	Scaling Factor	Report SAR1g	Need to test
Back Side	QPSK	1:1	1	99	132072/1720	23.50	22.00	0.125	1.41	0.177	no
Front Side	QPSK	1:1	1	99	132072/1720	23.50	22.00	0.052	1.41	0.073	no
Left Edge	QPSK	1:1	1	99	132072/1720	23.50	22.00	0.097	1.41	0.137	no
Top Edge	QPSK	1:1	1	99	132072/1720	23.50	22.00	0.000	1.41	0.000	no
Back Side	QPSK	1:1	50%	50	132572/1770	22.50	22.00	0.114	1.12	0.128	no
Front Side	QPSK	1:1	50%	50	132572/1770	22.50	22.00	0.053	1.12	0.060	no
Left Edge	QPSK	1:1	50%	50	132572/1770	22.50	22.00	0.088	1.12	0.099	no
Top Edge	QPSK	1:1	50%	50	132572/1770	22.50	22.00	0.000	1.12	0.000	no
Note: According to 648474 D04 Handset SAR v01r03, For Phablet, Since hotspot mode 1-g reported SAR < 1.2 W/kg, Product Specific 10-g SAR is not required.											



Table 27: Wi-Fi (2.4G)

Test Position	Cover Type	Mode 802.11b	Duty Cycle	Channel/ Frequency (MHz)	Tune-up dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR 1g	
Head SAR											
Left Cheek	standard	DSSS	100.0%	6/2437	12.00	11.23	0.107	-0.054	1.19	0.128	/
Left Tilt	standard	DSSS	100.0%	6/2437	12.00	11.23	0.114	0.050	1.19	0.136	74
Right Cheek	standard	DSSS	100.0%	6/2437	12.00	11.23	0.044	-0.069	1.19	0.052	/
Right Tilt	standard	DSSS	100.0%	6/2437	12.00	11.23	0.056	-0.130	1.19	0.067	/
Left Tilt	Battery2	DSSS	100.0%	6/2437	12.00	11.23	0.080	0.010	1.19	0.096	/
Left Tilt	Battery3	DSSS	100.0%	6/2437	12.00	11.23	0.089	-0.037	1.19	0.106	/
Body-worn SAR (Distance 15mm)											
Back Side	standard	DSSS	100.0%	6/2437	18.50	17.58	0.077	-0.048	1.24	0.095	75
Front Side	standard	DSSS	100.0%	6/2437	18.50	17.58	0.049	-0.091	1.24	0.061	/
Back Side	Battery2	DSSS	100.0%	6/2437	18.50	17.58	0.059	-0.010	1.24	0.073	/
Back Side	Battery3	DSSS	100.0%	6/2437	18.50	17.58	0.055	0.072	1.24	0.068	/
Hotspot SAR(Distance 10mm)											
Back Side	standard	DSSS	100.0%	6/2437	18.50	17.58	0.210	-0.045	1.24	0.260	/
Front Side	standard	DSSS	100.0%	6/2437	18.50	17.58	0.102	-0.120	1.24	0.126	/
Left Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Right Edge	standard	DSSS	100.0%	6/2437	18.50	17.58	0.073	-0.022	1.24	0.090	/
Top Edge	standard	DSSS	100.0%	6/2437	18.50	17.58	0.221	-0.132	1.24	0.273	76
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Top Edge	Battery2	DSSS	100.0%	6/2437	18.50	17.58	0.173	-0.021	1.24	0.214	/
Top Edge	Battery3	DSSS	100.0%	6/2437	18.50	17.58	0.165	0.027	1.24	0.204	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.											

MAX Adjusted SAR							
Mode	Test Position	Channel/ Frequency (MHz)	MAX Reported SAR _{1g} (W/kg)	802.11b Tune-up limit (dBm)	Tune-up limit (dBm)	Scaling Factor	Adjusted SAR _{1g} (W/kg)
802.11g	Top Edge	6/2437	0.273	18.50	19.00	1.12	0.306
802.11n HT20	Top Edge	6/2437	0.273	18.50	17.00	0.71	0.193
802.11n HT40	Top Edge	6/2437	0.273	18.50	13.00	0.28	0.077
Note: SAR is not required for OFDM when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.							



Table 28: BT

Test Position	Cover Type	Mode	Duty Cycle	Channel/ Frequency (MHz)	Tune-up dBm)	Measured power (dBm)	Limit of SAR 1.6 W/kg (mW/g)				Plot No.
							Measured SAR1g	Power Drift (dB)	Scaling Factor	Report SAR 1g	
Head SAR											
Left Cheek	standard	DH5	76.9%	78/2480	12.50	11.56	0.038	0.010	1.62	0.061	/
Left Tilt	standard	DH5	76.9%	78/2480	12.50	11.56	0.046	-0.021	1.62	0.074	77
Right Cheek	standard	DH5	76.9%	78/2480	12.50	11.56	0.028	0.022	1.62	0.045	/
Right Tilt	standard	DH5	76.9%	78/2480	12.50	11.56	0.019	0.140	1.62	0.031	/
Left Tilt	Battery2	DH5	76.9%	78/2480	12.50	11.56	0.035	-0.010	1.62	0.057	/
Left Tilt	Battery3	DH5	76.9%	78/2480	12.50	11.56	0.032	-0.020	1.62	0.052	/
Body SAR (Distance 10mm)											
Back Side	standard	DH5	76.9%	78/2480	12.50	11.56	0.023	-0.172	1.62	0.037	78
Front Side	standard	DH5	76.9%	78/2480	12.50	11.56	0.014	-0.026	1.62	0.022	/
Left Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Right Edge	standard	DH5	76.9%	78/2480	12.50	11.56	0.021	0.020	1.62	0.034	/
Top Edge	standard	DH5	76.9%	78/2480	12.50	11.56	0.009	0.100	1.62	0.015	/
Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Back Side	Battery2	DH5	76.9%	78/2480	12.50	11.56	0.020	-0.030	1.62	0.032	/
Back Side	Battery3	DH5	76.9%	78/2480	12.50	11.56	0.016	0.010	1.62	0.026	/
Note: 1. The value with blue color is the maximum SAR Value of each test band.											

10.3 Simultaneous Transmission Analysis

Simultaneous TX Combination	Head	Body-worn	Hotspot
GSM Voice(Main-Antenna) + BT	Yes	Yes	Yes
GSM DATA(Main-Antenna) + BT	N/A	Yes	Yes
GSM Voice(Second-Antenna) + BT	Yes	Yes	Yes
GSM DATA (Second-Antenna)+ BT	N/A	Yes	Yes
GSM Voice(Main-Antenna) + WiFi2.4G	Yes	Yes	Yes
GSM DATA(Main-Antenna) + WiFi2.4G	N/A	Yes	Yes
GSM Voice(Second-Antenna) + WiFi2.4G	Yes	Yes	Yes
GSM DATA(Second-Antenna) + WiFi2.4G	N/A	Yes	Yes
UMTS (Main-Antenna) + BT	Yes	Yes	Yes
UMTS (Second-Antenna) + BT	Yes	Yes	Yes
UMTS (Main-Antenna) + WiFi2.4G	Yes	Yes	Yes
UMTS (Second-Antenna) + WiFi2.4G	Yes	Yes	Yes
LTE (Main-Antenna) + WiFi2.4G	Yes	Yes	Yes
LTE (Main-Antenna) + BT	Yes	Yes	Yes
LTE (Second-Antenna) + WiFi2.4G	Yes	Yes	Yes
LTE (Second-Antenna) + BT	Yes	Yes	Yes
WiFi2.4G+ BT	N/A	N/A	N/A
Note: The Main Antenna and Second Antenna can't transmit simultaneously.			

General Note:

- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6\text{W/kg}$, simultaneously transmission SAR measurement is not necessary.
 - $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

**The maximum SAR_{1g} Value for Main-Antenna**

SAR _{1g} (W/kg)		GSM	GSM	WCDMA	WCDMA	WCDMA	LTE	LTE	LTE	LTE	LTE	MAX.
Test Position		850	1900	Band II	Band IV	Band V	FDD 2	FDD 4	FDD 5	FDD 7	FDD 66	SAR _{1g}
Left Cheek		0.015	0.095	0.246	0.230	0.024	0.187	0.208	0.021	0.083	0.030	0.246
Left Tilt		0.016	0.046	0.116	0.094	0.007	0.086	0.072	0.009	0.112	0.021	0.116
Right Cheek		0.016	0.087	0.178	0.139	0.015	0.106	0.123	0.035	0.147	0.047	0.178
Right Tilt		0.011	0.042	0.119	0.105	0.006	0.073	0.071	0.022	0.064	0.020	0.119
Body worn	Back Side	0.055	0.211	0.607	0.350	0.088	0.279	0.338	0.131	0.370	0.237	0.607
	Front Side	0.040	0.117	0.420	0.206	0.074	0.164	0.204	0.101	0.193	0.095	0.420
Hotspot	Back Side	0.131	0.297	0.646	0.405	0.153	0.642	0.601	0.224	0.406	0.543	0.646
	Front Side	0.116	0.197	0.448	0.235	0.135	0.350	0.348	0.149	0.196	0.203	0.448
	Left Edge	0.058	0.081	0.166	0.051	0.072	0.154	0.102	0.064	0.041	0.045	0.166
	Right Edge	0.000	0.000	0.053	0.096	0.000	0.000	0.111	0.000	0.044	0.050	0.111
	Top Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Bottom Edge	0.128	0.473	0.696	0.532	0.115	0.705	0.860	0.182	0.620	0.637	0.860

The maximum SAR_{1g} Value for Second-Antenna

SAR _{1g} (W/kg)		GSM	GSM	WCDMA	WCDMA	WCDMA	LTE	LTE	LTE	LTE	LTE	MAX.
Test Position		850	1900	Band II	Band IV	Band V	FDD 2	FDD 4	FDD 5	FDD 7	FDD 66	SAR _{1g}
Left Cheek		0.374	0.191	0.272	0.521	0.461	0.351	0.518	0.481	0.217	0.209	0.521
Left Tilt		0.304	0.280	0.340	0.601	0.326	0.426	0.458	0.411	0.217	0.180	0.601
Right Cheek		0.541	0.273	0.332	0.577	0.674	0.470	0.639	0.634	0.711	0.317	0.711
Right Tilt		0.497	0.435	0.422	0.374	0.560	0.598	0.300	0.517	0.708	0.282	0.708
Body worn	Back Side	0.101	0.077	0.157	0.323	0.386	0.153	0.389	0.336	0.358	0.119	0.389
	Front Side	0.089	0.047	0.081	0.139	0.288	0.098	0.275	0.186	0.177	0.067	0.288
Hotspot	Back Side	0.238	0.136	0.162	0.393	0.416	0.159	0.371	0.354	0.227	0.125	0.416
	Front Side	0.185	0.095	0.099	0.179	0.357	0.112	0.163	0.247	0.145	0.053	0.357
	Left Edge	0.071	0.081	0.103	0.653	0.160	0.159	0.577	0.111	0.142	0.097	0.653
	Right Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Top Edge	0.135	0.293	0.344	0.052	0.308	0.473	0.059	0.242	0.299	0.000	0.473
	Bottom Edge	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

About BT and Main- Antenna

SAR _{1g} (W/kg)		Main-antenna	BT	MAX. Σ SAR _{1g}
Test Position				
Head	Left, Cheek	0.246	0.061	0.307
	Left, Tilt	0.116	0.074	0.190
	Right, Cheek	0.178	0.045	0.223
	Right, Tilt	0.119	0.031	0.150
Body worn	Back Side	0.607	0.037	0.644
	Front Side	0.420	0.022	0.442
Hotspot	Back Side	0.646	0.037	0.683
	Front Side	0.448	0.022	0.470
	Left Edge	0.166	N/A	0.166
	Right Edge	0.111	0.034	0.145
	Top Edge	N/A	0.015	0.015
	Bottom Edge	0.860	N/A	0.860
Note: 1.The value with blue color is the maximum Σ SAR _{1g} Value. 2.MAX. Σ SAR _{1g} =Unlicensed SAR _{MAX} +Licensed SAR _{MAX}				

MAX. Σ SAR_{1g} =0.860W/kg<1.6W/kg, so the Simultaneous transimission SAR with volum scan are not required for BT and Main-Antenna.

About Wi-Fi and Main-Antenna

SAR _{1g} (W/kg)		Main-antenna	Wi-Fi 2.4G	MAX. Σ SAR _{1g}
Test Position				
Head	Left, Cheek	0.246	0.128	0.374
	Left, Tilt	0.116	0.136	0.252
	Right, Cheek	0.178	0.052	0.230
	Right, Tilt	0.119	0.067	0.186
Body worn	Back Side	0.607	0.095	0.702
	Front Side	0.420	0.061	0.481
Hotspot	Back Side	0.646	0.260	0.906
	Front Side	0.448	0.126	0.574
	Left Edge	0.166	N/A	0.166
	Right Edge	0.111	0.090	0.201
	Top Edge	N/A	0.273	0.273
	Bottom Edge	0.860	N/A	0.860
Note: 1.The value with blue color is the maximum Σ SAR _{1g} Value. 2.MAX. Σ SAR _{1g} =Unlicensed SAR _{MAX} +Licensed SAR _{MAX}				

MAX. Σ SAR_{1g} = 0.906W/kg<1.6W/kg, so the Simultaneous transimition SAR with volum scan are not required for Wi-Fi and Main-Antenna.

About BT and Second- Antenna

SAR _{1g} (W/kg)		Second-antenna	BT	MAX. Σ SAR _{1g}
Test Position				
Head	Left, Cheek	0.521	0.061	0.582
	Left, Tilt	0.601	0.074	0.675
	Right, Cheek	0.711	0.045	0.756
	Right, Tilt	0.708	0.031	0.739
Body worn	Back Side	0.389	0.037	0.426
	Front Side	0.288	0.022	0.310
Hotspot	Back Side	0.416	0.037	0.453
	Front Side	0.357	0.022	0.379
	Left Edge	0.653	N/A	0.653
	Right Edge	N/A	0.034	0.034
	Top Edge	0.473	0.015	0.488
	Bottom Edge	N/A	N/A	0.000
Note: 1.The value with blue color is the maximum Σ SAR _{1g} Value. 2.MAX. Σ SAR _{1g} =Unlicensed SAR _{MAX} +Licensed SAR _{MAX}				

MAX. Σ SAR_{1g} = 0.756W/kg<1.6W/kg, so the Simultaneous transimition SAR with volum scan are not required for BT and Second-Antenna.

About Wi-Fi and Second- Antenna

SAR _{1g} (W/kg)		Second-antenna	Wi-Fi 2.4G	MAX. ΣSAR _{1g}
Test Position				
Head	Left, Cheek	0.521	0.128	0.649
	Left, Tilt	0.601	0.136	0.737
	Right, Cheek	0.711	0.052	0.763
	Right, Tilt	0.708	0.067	0.775
Body worn	Back Side	0.389	0.095	0.484
	Front Side	0.288	0.061	0.349
Hotspot	Back Side	0.416	0.260	0.676
	Front Side	0.357	0.126	0.483
	Left Edge	0.653	N/A	0.653
	Right Edge	N/A	0.090	0.090
	Top Edge	0.473	0.273	0.746
	Bottom Edge	N/A	N/A	0.000

Note: 1.The value with blue color is the maximum ΣSAR_{1g} Value.

2.MAX. ΣSAR_{1g} =Unlicensed SAR_{MAX} +Licensed SAR_{MAX}

MAX. Σ SAR_{1g} = 0.775W/kg<1.6W/kg, so the Simultaneous transimition SAR with volum scan are not required for Wi-Fi and Second-Antenna.

Conclusion:

According to the KDB 690783 D01 section 1) d) i), when the sum of 1-g SAR applies for simultaneous transmission SAR test exclusion, the highest sum of 1-g SAR according to the highest reported stand-alone SAR values is used, and the highest Reported SAR for simultaneous transmission exposure conditions is 0.906 W/kg



11 Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528- 2013 is not required in SAR reports submitted for equipment approval.

ANNEX A: Test Layout




Tissue Simulating Liquids

For the measurement of the field distribution inside the flat phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For Head and Body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Picture 3 and Picture 4.



Picture 3: liquid depth in the head Phantom



Picture 4: Liquid depth in the flat Phantom

ANNEX B: System Check Results

Plot 1 System Performance Check at 835 MHz TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2

Date: 9/13/2020

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.88 \text{ S/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=15mm, Pin=250mW/Area Scan (4x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.64 mW/g


d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.4 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.44 mW/g; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.64 mW/g



Plot 2 System Performance Check at 835 MHz TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2

Date: 9/15/2020

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.87 \text{ S/m}$; $\epsilon_r = 41.3$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C

Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=15mm, Pin=250mW/Area Scan (4x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.59 mW/g


d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.3 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.46 mW/g; SAR(10 g) = 1.65 mW/g

Maximum value of SAR (measured) = 2.70 mW/g



Plot 3 System Performance Check at 835 MHz TSL

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2

Date: 9/18/2020

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ S/m}$; $\epsilon_r = 41.4$; $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature: 22.3°C

Liquid Temperature: 21.5°C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=15mm, Pin=250mW/Area Scan (4x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 2.64 mW/g


d=15mm, Pin=250mW/Zoom Scan(5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.4 V/m ; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.43 mW/g ; SAR(10 g) = 1.61 mW/g

Maximum value of SAR (measured) = 2.66 mW/g



Plot 4 System Performance Check at 1750 MHz TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2

Date: 9/12/2020

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.34$ S/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.78 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 80 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 15.5 W/kg

SAR(1 g) = 8.95 mW/g; SAR(10 g) = 4.5 mW/g

Maximum value of SAR (measured) = 9.46 mW/g



Plot 5 System Performance Check at 1750 MHz TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2

Date: 9/14/2020

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.34$ S/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.77 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 80 V/m; Power Drift = 0.055 dB

Peak SAR (extrapolated) = 15.51 W/kg

SAR(1 g) = 9.11 mW/g; SAR(10 g) = 4.77 mW/g

Maximum value of SAR (measured) = 9.87 mW/g



Plot 6 System Performance Check at 1750 MHz TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2

Date: 9/16/2020

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.36$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.11 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 80 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 15.47 W/kg

SAR(1 g) = 8.96 mW/g; SAR(10 g) = 4.75 mW/g

Maximum value of SAR (measured) = 9.46 mW/g



Plot 7 System Performance Check at 1750 MHz TSL

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2

Date: 9/19/2020

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.11 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 80 V/m; Power Drift = 0.065 dB

Peak SAR (extrapolated) = 14.8 W/kg

SAR(1 g) = 8.92 mW/g; SAR(10 g) = 4.76 mW/g

Maximum value of SAR (measured) = 10.68 mW/g



Plot 8 System Performance Check at 1900 MHz

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2

Date: 9/9/2020

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 12.9 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.8 V/m; Power Drift = 0.030 dB

Peak SAR (extrapolated) = 20.1 W/kg

SAR(1 g) = 10.55 mW/g; SAR(10 g) = 5.39 mW/g

Maximum value of SAR (measured) = 11.52 mW/g



Plot 9 System Performance Check at 1900 MHz TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2

Date: 9/10/2020

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.41$ S/m; $\epsilon_r = 40.1$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 11.3 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 85.5 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.88 mW/g; SAR(10 g) = 4.9 mW/g

Maximum value of SAR (measured) = 10.7 mW/g



Plot 10 System Performance Check at 1900 MHz TSL

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2

Date: 9/11/2020

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 11.23 mW/g


d=10mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 85.0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.85 mW/g; SAR(10 g) = 4.93 mW/g

Maximum value of SAR (measured) = 11.12 mW/g



Plot 11 System Performance Check at 2450 MHz TSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2

Date: 9/12/2020

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.81$ S/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C

Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.54, 7.54, 7.54); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 18.2 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.8 V/m; Power Drift = 0.075 dB

Peak SAR (extrapolated) = 30 W/kg

SAR(1 g) = 13.7 mW/g; SAR(10 g) = 6.22 mW/g

Maximum value of SAR (measured) = 15.9 mW/g



Plot 12 System Performance Check at 2600 MHz TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2

Date: 9/17/2020

Communication System: CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.01$ S/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.26, 7.26, 7.26); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid:dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.439 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.998 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 31.858 W/kg

SAR(1 g) = 13.9 mW/g; SAR(10 g) = 6.07 mW/g

Maximum value of SAR (measured) = 15.617 mW/g



Plot 13 System Performance Check at 2600 MHz TSL

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2

Date:9/18/2020

Communication System: CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.94$ S/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.26, 7.26, 7.26); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

d=10mm, Pin=250mW/Area Scan (4x7x1): Measurement grid:dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.59 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.998 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 31.858 W/kg

SAR(1 g) = 13.88 mW/g; SAR(10 g) = 6.09 mW/g

Maximum value of SAR (measured) = 15.66 mW/g



ANNEX C: Highest Graph Results

Plot 14 GSM 850 Right Cheek Middle (Main-Antenna)

Date: 9/13/2020

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Right Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0132 W/kg


Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.424 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 0.0170 W/kg

SAR(1 g) = 0.013 W/kg; SAR(10 g) = 0.010 W/kg

Maximum value of SAR (measured) = 0.014 W/kg



Plot 15 GSM 850 Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/13/2020

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0473 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.659 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.0590 W/kg

SAR(1 g) = 0.044 W/kg; SAR(10 g) = 0.030 W/kg

Maximum value of SAR (measured) = 0.047 W/kg



Plot 16 GSM 850 GPRS (4Txslots) Back Side Middle (Main-Antenna, Distance 10mm)

Date: 9/13/2020

Communication System: UID 0, GPRS (4Txslots); Frequency: 836.6 MHz; Duty Cycle: 1:2.07

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.121 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.778 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.167 W/kg

SAR(1 g) = 0.111 W/kg; SAR(10 g) = 0.074 W/kg

Maximum value of SAR (measured) = 0.119 W/kg



Plot 17 GSM 1900 Left Cheek Middle (Main-Antenna)

Date: 9/9/2020

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.393$ S/m; $\epsilon_r = 38.344$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0818 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.770 V/m; Power Drift = -0.058 dB

Peak SAR (extrapolated) = 0.115 W/kg

SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.083 W/kg



Plot 18 GSM 1900 Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/9/2020

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.42$ S/m; $\epsilon_r = 38.948$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.188 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.554 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.282 W/kg

SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 0.188 W/kg



Plot 19 GSM 1900 GPRS (1Txslots) Bottom Edge Middle (Main-Antenna, Distance 10mm)

Date: 9/9/2020

Communication System: UID 0, GPRS 1TX (0); Frequency: 1880 MHz; Duty Cycle: 1:2.07491

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.393$ S/m; $\epsilon_r = 38.344$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge Middle/Area Scan (4x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.324 W/kg


Bottom Edge Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.04 V/m; Power Drift = -0.129 dB

Peak SAR (extrapolated) = 0.876 W/kg

SAR(1 g) = 0.396 W/kg; SAR(10 g) = 0.176 W/kg

Maximum value of SAR (measured) = 0.403 W/kg



Plot 20 UMTS Band II Left Cheek Middle (Main-Antenna)

Date: 9/10/2020

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.393$ S/m; $\epsilon_r = 38.344$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.196 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.780 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR(1 g) = 0.183 W/kg; SAR(10 g) = 0.120 W/kg

Maximum value of SAR (measured) = 0.194 W/kg



Plot 21 UMTS Band II Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/10/2020

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.42$ S/m; $\epsilon_r = 38.948$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.459 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.01 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.742 W/kg

SAR(1 g) = 0.451 W/kg; SAR(10 g) = 0.269 W/kg

Maximum value of SAR (measured) = 0.489 W/kg



Plot 22 UMTS Band II Bottom Edge Middle (Main-Antenna, Distance 10mm)

Date: 9/10/2020

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.42$ S/m; $\epsilon_r = 38.948$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge Middle/Area Scan (4x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.549 W/kg


Bottom Edge Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.50 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.566 W/kg; SAR(10 g) = 0.313 W/kg

Maximum value of SAR (measured) = 0.626 W/kg



Plot 23 UMTS Band IV Left Cheek Middle (Main-Antenna)

Date: 9/12/2020

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.293$ S/m; $\epsilon_r = 38.782$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.211 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.934 V/m; Power Drift = -0.027 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.133 W/kg

Maximum value of SAR (measured) = 0.210 W/kg



Plot 24 UMTS Band IV Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/12/2020

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.312$ S/m; $\epsilon_r = 39.365$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.333 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.47 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.478 W/kg

SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.188 W/kg

Maximum value of SAR (measured) = 0.328 W/kg



Plot 25 UMTS Band IV Bottom Edge Middle (Main-Antenna, Distance 10mm)

Date: 9/12/2020

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1733$ MHz; $\sigma = 1.312$ S/m; $\epsilon_r = 39.365$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge Middle/Area Scan (4x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.420 W/kg


Bottom Edge Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.76 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.790 W/kg

SAR(1 g) = 0.463 W/kg; SAR(10 g) = 0.262 W/kg

Maximum value of SAR (measured) = 0.511 W/kg



Plot 26 UMTS Band V Left Cheek Middle (Main-Antenna)

Date: 9/15/2020

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0192 W/kg


Left Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0 V/m; Power Drift = 0.099 dB

Peak SAR (extrapolated) = 0.0250 W/kg

SAR(1 g) = 0.020 W/kg; SAR(10 g) = 0.014 W/kg

Maximum value of SAR (measured) = 0.021 W/kg



Plot 27 UMTS Band V Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/15/2020

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0776 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.659 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.0990 W/kg

SAR(1 g) = 0.073 W/kg; SAR(10 g) = 0.050 W/kg

Maximum value of SAR (measured) = 0.078 W/kg



Plot 28 UMTS Band V Back Side Middle (Main-Antenna, Distance 10mm)

Date: 9/15/2020

Communication System: UID 0, WCDMA (0); Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 837$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.201$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.137 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.636 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.191 W/kg

SAR(1 g) = 0.126 W/kg; SAR(10 g) = 0.081 W/kg

Maximum value of SAR (measured) = 0.136 W/kg



Plot 29 LTE Band 2 1RB Left Cheek Low (Main-Antenna)

Date: 9/11/2020

Communication System: UID 0, LTE (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1860$ MHz; $\sigma = 1.407$ S/m; $\epsilon_r = 39.071$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek Low/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.177 W/kg


Left Cheek Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.613 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 0.271 W/kg

SAR(1 g) = 0.174 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.182 W/kg



Plot 30 LTE Band 2 1RB Back Side Low (Main-Antenna, Distance 15mm)

Date: 9/11/2020

Communication System: UID 0, LTE (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1860$ MHz; $\sigma = 1.407$ S/m; $\epsilon_r = 39.071$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Low/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.280 W/kg


Back Side Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.169 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 0.430 W/kg

SAR(1 g) = 0.260 W/kg; SAR(10 g) = 0.156 W/kg

Maximum value of SAR (measured) = 0.278 W/kg



Plot 31 LTE Band 2 1RB Bottom Edge Low (Main-Antenna, Distance 10mm)

Date: 9/11/2020

Communication System: UID 0, LTE (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1860$ MHz; $\sigma = 1.407$ S/m; $\epsilon_r = 39.071$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.90, 7.90, 7.90); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge Low/Area Scan (4x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.487 W/kg


Bottom Edge Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.04 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.995 W/kg

SAR(1 g) = 0.568 W/kg; SAR(10 g) = 0.310 W/kg

Maximum value of SAR (measured) = 0.634 W/kg



Plot 32 LTE Band 4 1RB Left Cheek High (Main-Antenna)

Date: 9/12/2020

Communication System: UID 0, LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.323$ S/m; $\epsilon_r = 39.378$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Left Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Left Cheek High/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.175 W/kg


Left Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.384 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.243 W/kg

SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.144 W/kg

Maximum value of SAR (measured) = 0.174 W/kg



Plot 33 LTE Band 4 1RB Back Side High (Main-Antenna, Distance 15mm)

Date: 9/12/2020

Communication System: UID 0, LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.323$ S/m; $\epsilon_r = 39.378$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side High/Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.371 W/kg


Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.626 V/m; Power Drift = 0.033 dB

Peak SAR (extrapolated) = 0.562 W/kg

SAR(1 g) = 0.295 W/kg; SAR(10 g) = 0.177 W/kg

Maximum value of SAR (measured) = 0.352 W/kg



Plot 34 LTE Band 4 1RB Bottom Edge High (Main-Antenna, Distance 10mm)

Date: 9/14/2020

Communication System: UID 0, LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1745$ MHz; $\sigma = 1.323$ S/m; $\epsilon_r = 39.378$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge High/Area Scan (4x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.621 W/kg


Bottom Edge High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.12 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.751 W/kg; SAR(10 g) = 0.423 W/kg

Maximum value of SAR (measured) = 0.764 W/kg



Plot 35 LTE Band 5 1RB Right Cheek Middle (Main-Antenna)

Date: 9/18/2020

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Right Cheek Middle/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0341 W/kg


Right Cheek Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.468 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.0400 W/kg

SAR(1 g) = 0.033 W/kg; SAR(10 g) = 0.026 W/kg

Maximum value of SAR (measured) = 0.034 W/kg



Plot 36 LTE Band 5 1RB Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/18/2020

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.120 W/kg


Back Side Middle/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.100 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.122 W/kg; SAR(10 g) = 0.081 W/kg

Maximum value of SAR (measured) = 0.132 W/kg



Plot 37 LTE Band 5 1RB Back Side Middle (Main-Antenna, Distance 10mm)

Date: 9/18/2020

Communication System: UID 0, LTE (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 42.199$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(9.38, 9.38, 9.38); Calibrated: 7/6/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle /Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.204 W/kg


Back Side Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.67 V/m; Power Drift = 0.024 dB

Peak SAR (extrapolated) = 0.261 W/kg

SAR(1 g) = 0.208 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.215 W/kg



Plot 38 LTE Band 7 1RB Right Cheek Middle (Main-Antenna)

Date: 9/17/2020

Communication System: UID 0, LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.905$ S/m; $\epsilon_r = 38.267$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.26, 7.26, 7.26); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Right Cheek Middle/Area Scan (10x18x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.106 W/kg


Right Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.846 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 0.240 W/kg

SAR(1 g) = 0.123 W/kg; SAR(10 g) = 0.061 W/kg

Maximum value of SAR (measured) = 0.130 W/kg



Plot 39 LTE Band 7 1RB Back Side Middle (Main-Antenna, Distance 15mm)

Date: 9/17/2020

Communication System: UID 0, LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.905$ S/m; $\epsilon_r = 38.267$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.26, 7.26, 7.26); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side Middle/Area Scan (9x18x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.341 W/kg


Back Side Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.6690 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.547 W/kg

SAR(1 g) = 0.334 W/kg; SAR(10 g) = 0.175 W/kg

Maximum value of SAR (measured) = 0.356 W/kg



Plot 40 LTE Band 7 50%RB Bottom Edge Middle (Main-Antenna, Distance 10mm)

Date: 9/17/2020

Communication System: UID 0, LTE (0); Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 1.905$ S/m; $\epsilon_r = 38.267$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(7.26, 7.26, 7.26); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge Middle/Area Scan (5x12x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.529 W/kg


Bottom Edge Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.27 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.504 W/kg; SAR(10 g) = 0.233 W/kg

Maximum value of SAR (measured) = 0.574 W/kg



Plot 41 LTE Band 66 1RB Right Cheek High (Main-Antenna)

Date: 9/14/2020

Communication System: UID 0, LTE (0); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1770$ MHz; $\sigma = 1.341$ S/m; $\epsilon_r = 39.287$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Right Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Right Cheek High/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.0501 W/kg


Right Cheek High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.258 V/m; Power Drift = 0.057 dB

Peak SAR (extrapolated) = 0.0700 W/kg

SAR(1 g) = 0.046 W/kg; SAR(10 g) = 0.027 W/kg

Maximum value of SAR (measured) = 0.049 W/kg



Plot 42 LTE Band 66 1RB Back Side High (Main-Antenna, Distance 15mm)

Date: 9/14/2020

Communication System: UID 0, LTE (0); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1770$ MHz; $\sigma = 1.341$ S/m; $\epsilon_r = 39.287$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Back Side High/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.236 W/kg


Back Side High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.342 V/m; Power Drift = 0.134 dB

Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.212 W/kg; SAR(10 g) = 0.122 W/kg

Maximum value of SAR (measured) = 0.237 W/kg



Plot 43 LTE Band 66 1RB Bottom Edge High (Main-Antenna, Distance 10mm)

Date: 9/14/2020

Communication System: UID 0, LTE (0); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1770$ MHz; $\sigma = 1.341$ S/m; $\epsilon_r = 39.287$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.3 °C Liquid Temperature: 21.5 °C

Phantom section: Flat Section

DASY5 Configuration:

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Probe: EX3DV4 - SN3677; ConvF(8.25, 8.25, 8.25); Calibrated: 7/06/2020;

Electronics: DAE4 SN1317; Calibrated: 10/23/2019

Phantom: SAM1; Type: SAM; Serial: TP-1534

Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Bottom Edge High/Area Scan (4x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.551 W/kg

Bottom Edge High/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.52 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.982 W/kg

SAR(1 g) = 0.576 W/kg; SAR(10 g) = 0.315 W/kg

Maximum value of SAR (measured) = 0.644 W/kg

