TEST REPORT

Product Name	:	True Wireless Earbuds
Brand Mark	:	AUKEY
Model No.	:	EP-T32, EP-T32L
FCC ID	:	2ATIH-EPT32L
Report Number	:	BLA-EMC-202101-A6601
Date of Sample Receipt	:	2021/1/26
Date of Test	:	2021/1/26 to 2021/2/20
Date of Issue	:	2021/3/16
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Aukey Technology Co.,Ltd
Room 102,Building P09,South China City Electronics Trading Center, Longgang District,Shenzhen,Guangdong,518111,China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Jason

Review by: Sweet. Liang

Approved by: Tomen Li

Date: 2021/3/16

BlueAsia of Technical Services(Shenzhen) Co., Ltd. BLA

BlueAsia

REPORT REVISE RECORD

Version No.	Date	Description
00	2021/3/3	Original
01	2021/3/16	Replace the applicant, product name and model

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY 6
2 GENERAL INFORMATION 7
3 GENERAL DESCRIPTION OF E.U.T. 7
4 TEST ENVIRONMENT 8
5 TEST MODE 8
6 MEASUREMENT UNCERTAINTY 8
7 DESCRIPTION OF SUPPORT UNIT 9
8 LABORATORY LOCATION 9
9 TEST INSTRUMENTS LIST 10
10 ANTENNA REQUIREMENT 14
10.1 CONCLUSION 14
11 CONDUCTED SPURIOUS EMISSIONS 15
11.1 LIMITS 15
11.2 BLOCK DIAGRAM OF TEST SETUP 15
11.3 TEST DATA 16
12 RADIATED SPURIOUS EMISSIONS 17
12.1 LIMITS 17
12.2 BLOCK DIAGRAM OF TEST SETUP 18
12.3 PROCEDURE 18
12.4 TEST DATA 20
13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 28
13.1 LIMITS 28
13.2 BLOCK DIAGRAM OF TEST SETUP 29
13.3 PROCEDURE 29
13.4 TEST DATA 31
14 CONDUCTED BAND EDGES MEASUREMENT 35
14.1 LIMITS 35
14.2 BLOCK DIAGRAM OF TEST SETUP 35
14.3 TEST DATA 36

BlueAsia

15 DWELL TIME 37

15.1 LIMITS 37
15.2 BLOCK DIAGRAM OF TEST SETUP 37
15.3 TEST DATA 38

16 HOPPING CHANNEL NUMBER 39

16.1 LIMITS 39
16.2 BLOCK DIAGRAM OF TEST SETUP 39
16.3 TEST DATA 39

17 CARRIER FREQUENCIES SEPARATION 40

17.1 LIMITS 40
17.2 BLOCK DIAGRAM OF TEST SETUP 40
17.3 TEST DATA 40

18 20DB BANDWIDTH 41

18.1 BLOCK DIAGRAM OF TEST SETUP 41
18.2 TEST DATA 41

19 CONDUCTED PEAK OUTPUT POWER 42

19.1 LIMITS 42
19.2 BLOCK DIAGRAM OF TEST SETUP 42
19.3 TEST DATA 43

20 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 44

20.1 LIMITS 44
20.2 BLOCK DIAGRAM OF TEST SETUP 44
20.3 PROCEDURE 44
20.4 TEST DATA 46

21 APPENDIX 48

21.1 APPENDIX A: 20DB EMISSION BANDWIDTH 48
Test Result 48
Test Graphs 49
21.2 APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER 52
Test Result 52
Test Graphs 53
21.3 APPENDIX D: CARRIER FREQUENCY SEPARATION 57
Test Result 57

BlueAsia

Test Graphs *58*

21.4 APPENDIX E: TIME OF OCCUPANCY 59

Test Result *59*

Test Graphs *60*

21.5 APPENDIX F: NUMBER OF HOPPING CHANNELS 62

Test Result *62*

Test Graphs *63*

21.6 APPENDIX G: BAND EDGE MEASUREMENTS 64

Test Result *64*

Test Graphs *65*

21.7 APPENDIX H: CONDUCTED SPURIOUS EMISSION 69

Test Result *69*

Test Graphs *70*

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 79

APPENDIX B: PHOTOGRAPHS OF EUT 81

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass

Remark:

About FCC ID: 2ATIH-EPT32L (Product Name: True Wireless Earbuds, Model No.: EP-T32, EP-T32L). All models are electrically identical with certified FCC ID: 2AMQ6-T17L (Product Name: Haylou Wireless Earbuds, Model No.: Haylou-T17, Haylou-T17L). All data of FCC report for FCC ID: 2ATIH-EPT32L come from FCC report for certified FCC ID: 2AMQ6-T17L.

BlueAsia

2 GENERAL INFORMATION

Applicant	Aukey Technology Co.,Ltd
Address	Room 102,Building P09,South China City Electronics Trading Center, Longgang District,Shenzhen,Guangdong,518111,China
Manufacturer	Aukey Technology Co.,Ltd
Address	Room 102,Building P09,South China City Electronics Trading Center, Longgang District,Shenzhen,Guangdong,518111,China
Factory	Aukey Technology Co.,Ltd
Address	Room 102,Building P09,South China City Electronics Trading Center, Longgang District,Shenzhen,Guangdong,518111,China
Product Name	True Wireless Earbuds
Test Model No.	EP-T32

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	V1.0

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	FPC Antenna
Antenna Gain:	0.91dBi(Provided by customer)

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: *Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only worst mode GFSK would be recorded in this report.*	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands

BlueAsia

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Dwell Time					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11

BlueAsia

Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Hopping Channel Number					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Carrier Frequencies Separation					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of 20dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

BlueAsia

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

BlueAsia

10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

10.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.91dBi.

11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

12 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX mode (SE) below 1G; TX mode (SE) Above 1G
Test Mode (Final Test)	TX mode (SE) below 1G; TX mode (SE) Above 1G
Tester	Eason
Temperature	25℃
Humidity	52%

12.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

BlueAsia

12.2 BLOCK DIAGRAM OF TEST SETUP







12.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor ¨C Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

12.4 TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]



Site
Limit: FCC Part15 Class B
EUT: Haylou Wireless Earbuds
M/N: Haylou-T17
Mode: BT mode
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		56.3948	5.38	23.08	28.46	40.00	-11.54	QP			
2		151.0666	-0.43	23.99	23.56	43.50	-19.94	QP			
3		255.6231	0.14	22.68	22.82	46.00	-23.18	QP			
4		423.5403	0.15	27.70	27.85	46.00	-18.15	QP			
5		716.6820	1.63	33.04	34.67	46.00	-11.33	QP			
6	*	881.4067	1.85	34.65	36.50	46.00	-9.50	QP			

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]



Site	Polarization: *Vertical*	Temperature:
Limit: FCC Part15 Class B	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: BT mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		47.6586	2.79	23.65	26.44	40.00	-13.56	QP			
2		56.3948	3.23	23.08	26.31	40.00	-13.69	QP			
3		126.3286	5.11	22.41	27.52	43.50	-15.98	QP			
4		261.9753	1.50	22.87	24.37	46.00	-21.63	QP			
5		477.1694	0.20	28.28	28.48	46.00	-17.52	QP			
6	*	716.6820	1.70	33.04	34.74	46.00	-11.26	QP			

Test Result: Pass

[Polarity: Vertical];[TestMode: TX mode (SE) Above 1G];[lowest channel]

Radiated Emission Measurement

File :RE Data :#17 Date: 2021/2/1 星期 Time: 下午 3:04:32

Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	50.39	-7.27	43.12	74.00	-30.88	peak			
2		7206.000	50.80	-4.42	46.38	74.00	-27.62	peak			
3	*	9608.000	47.83	-0.29	47.54	74.00	-26.46	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Horizontal]; [TestMode: TX mode (SE) Above 1G] [lowest channel]

Radiated Emission Measurement

File :RE Data :#18 Date: 2021/2/1 星期 Time: 下午 3:07:07

Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	51.07	-7.27	43.80	74.00	-30.20	peak			
2		7206.000	50.53	-4.42	46.11	74.00	-27.89	peak			
3	*	9608.000	48.28	-0.29	47.99	74.00	-26.01	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Horizontal]; [TestMode: TX mode (SE) Above 1G] [Middle channel]

Radiated Emission Measurement

File :RE Data :#15 Date: 2021/2/1 星期 Time: 下午 2:54:19

Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	51.43	-7.51	43.92	74.00	-30.08	peak			
2		7323.000	50.54	-3.35	47.19	74.00	-26.81	peak			
3	*	9764.000	47.71	0.56	48.27	74.00	-25.73	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Vertical] [TestMode: TX mode (SE) Above 1G] [Middle channel]

Radiated Emission Measurement

File :RE Data :#16 Date: 2021/2/1 星期 Time: 下午 3:01:23

Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-M		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	51.75	-7.51	44.24	74.00	-29.76	peak			
2		7323.000	49.75	-3.35	46.40	74.00	-27.60	peak			
3	*	9764.000	48.09	0.56	48.65	74.00	-25.35	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Horizontal]; [TestMode: TX mode (SE) Above 1G] [Highest channel]

Radiated Emission Measurement

File :RE Data :#13 Date: 2021/2/1 星期 Time: 下午 2:31:57

Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	50.86	-6.99	43.87	74.00	-30.13	peak			
2		7440.000	49.83	-2.43	47.40	74.00	-26.60	peak			
3	*	9920.000	48.51	1.63	50.14	74.00	-23.86	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Vertical]; [TestMode: TX mode (SE) Above 1G];[Highest channel]

Radiated Emission Measurement

File :RE Data :#14 Date: 2021/2/1 星期 Time: 下午 2:41:32



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4960.000	50.82	-6.99	43.83	74.00	-30.17	peak			
2		7440.000	49.75	-2.43	47.32	74.00	-26.68	peak			
3	*	9920.000	47.57	1.63	49.20	74.00	-24.80	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

13.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

BlueAsia

13.2 BLOCK DIAGRAM OF TEST SETUP







13.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

13.4 TEST DATA

[Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	55.25	-15.49	39.76	74.00	-34.24	peak			
2		2390.000	54.79	-15.18	39.61	74.00	-34.39	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Vertical]



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2310.000	55.19	-15.49	39.70	74.00	-34.30	peak			
2	*	2384.260	59.82	-15.20	44.62	74.00	-29.38	peak			
3		2390.000	54.95	-15.18	39.77	74.00	-34.23	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	55.36	-14.79	40.57	74.00	-33.43	peak			
2	*	2492.454	61.30	-14.75	46.55	74.00	-27.45	peak			
3		2500.000	54.72	-14.72	40.00	74.00	-34.00	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[Polarity: Vertical]



Site	Polarization: ***Vertical***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Haylou Wireless Earbuds	Distance: 3m	
M/N: Haylou-T17		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	53.96	-14.79	39.17	74.00	-34.83	peak			
2	*	2496.304	57.85	-14.75	43.10	74.00	-30.90	peak			
3		2500.000	53.74	-14.72	39.02	74.00	-34.98	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

14 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

14.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

15 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

15.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

16 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

16.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: For Details

17 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

17.1 LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: For Details

18 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

18.1 BLOCK DIAGRAM OF TEST SETUP



18.2 TEST DATA

Pass: Please Refer To Appendix: For Details

19 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

19.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

19.2 BLOCK DIAGRAM OF TEST SETUP



19.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

20 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	25℃
Humidity	52%

20.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

20.2 BLOCK DIAGRAM OF TEST SETUP



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

20.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50?H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

20.4 TEST DATA

[TestMode: TX mode]; [Line: Line]



Site
Limit: FCC Class B Conduction(QP)
EUT: Haylou Wireless Earbuds
M/N: Haylou-T17
Mode: BT mode
Note:

Phase: *L1*
Power: AC 120V 60Hz

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5420	36.11	9.73	45.84	56.00	-10.16	QP	
2	*	0.5420	28.48	9.73	38.21	46.00	-7.79	AVG	
3		0.8820	23.47	9.75	33.22	56.00	-22.78	QP	
4		0.8820	16.33	9.75	26.08	46.00	-19.92	AVG	
5		1.0820	24.30	9.85	34.15	56.00	-21.85	QP	
6		1.0820	15.73	9.85	25.58	46.00	-20.42	AVG	
7		1.5140	23.63	9.84	33.47	56.00	-22.53	QP	
8		1.5140	15.67	9.84	25.51	46.00	-20.49	AVG	
9		2.7139	21.34	9.84	31.18	56.00	-24.82	QP	
10		2.7139	12.46	9.84	22.30	46.00	-23.70	AVG	
11		3.9820	20.03	9.83	29.86	56.00	-26.14	QP	
12		3.9820	10.71	9.83	20.54	46.00	-25.46	AVG	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX mode]; [Line: Neutral]

Conducted Emission Measurement

File :CE Data :#2 Date: 2021/1/27 Time: 15:31:56



Site		Phase:	*N*	Temperature:	
Limit:	FCC Class B Conduction(QP)	Power:	AC 120V 60Hz	Humidity:	%
EUT:	Haylou Wireless Earbuds				
M/N:	Haylou-T17				
Mode:	BT mode				
Note:					

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2260	23.92	9.86	33.78	62.60	-28.82	QP	
2		0.2260	16.60	9.86	26.46	52.60	-26.14	AVG	
3		0.5340	27.59	9.73	37.32	56.00	-18.68	QP	
4	*	0.5340	19.60	9.73	29.33	46.00	-16.67	AVG	
5		0.8540	22.11	9.75	31.86	56.00	-24.14	QP	
6		0.8540	15.45	9.75	25.20	46.00	-20.80	AVG	
7		1.4780	19.68	9.83	29.51	56.00	-26.49	QP	
8		1.4780	13.32	9.83	23.15	46.00	-22.85	AVG	
9		2.7260	18.34	9.88	28.22	56.00	-27.78	QP	
10		2.7260	11.30	9.88	21.18	46.00	-24.82	AVG	
11		4.6700	16.70	9.89	26.59	56.00	-29.41	QP	
12		4.6700	8.64	9.89	18.53	46.00	-27.47	AVG	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass