

Smart Stack Coaster Pro/EVO

Paging system

Mode : AT-DAP-105P



- UHF Paging transmitter
- Frequency :433.92MHz
- Send out both Numeric and Alpha messages via USB cable with attached PC software
- Send out Numeric message via on board buttons directly.
- Backlit LCD display and numeric keypad
- Power DC12V, 2A
- Size : 14 x 12 x 4 cm (5.5 x 4.7 x 1.6 inch)

Operation :

1. Plug 12V2A Adapter to AT105
2. Press membrane number 1-9 buttons for coaster's number
3. Press SEND button to call the coaster

FCC Statement:

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1) this device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC Radiation Exposure Statement

This device complies with FCC RF radiation exposure limits set forth for an uncontrolled environment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This device must operate with a minimum distance of 20 cm between the radiator and user body.